




PCTEST ENGINEERING LABORATORY, INC.

6660-B Dobbin Road, Columbia, MD 21045 USA
Tel. 410.290.6652 / Fax 410.290.6554
<http://www.pctestlab.com>



CERTIFICATE OF COMPLIANCE FCC Part 22/24/27 Certification

Applicant Name:
LG Electronics USA
1000 Sylvan Avenue
Englewood Cliffs, NJ 07632
United States

Date of Testing:
December 22 - 23, 2009
Test Site/Location:
PCTEST Lab., Columbia, MD, USA
Test Report Serial No.:
0912182292.BEJ

FCC ID:	BEJMN240
APPLICANT:	LG ELECTRONICS USA

Application Type: Certification
FCC Classification: PCS Licensed Transmitter Held to Ear (PCE)
FCC Rule Part(s): §2; §22(H), §24(E), §27(C)(L)
EUT Type: Cellular/AWS/PCS CDMA/EvDO Phone with Bluetooth
Model(s): MN240, LW240
Tx Frequency Range: 824.70 - 848.31MHz (Cell. CDMA) / 1711.25 - 1753.75MHz (AWS CDMA)
1851.25 - 1908.75MHz (PCS CDMA)
Max. RF Output Power: 0.29 W ERP Cell. CDMA (24.62 dBm)
0.412 W EIRP AWS CDMA (26.15 dBm)
0.465 W EIRP PCS CDMA (26.67 dBm)
Emission Designator(s): 1M28F9W (Cellular) / 1M28F9W (AWS) / 1M28F9W (PCS)
Test Device Serial No.: *identical prototype* [S/N: N/A]

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in §2.947. Test results reported herein relate only to the item(s) tested.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

Grant Conditions: Power output listed is ERP for Part 22 and EIRP for Part 24 and Part 27.

PCTEST certifies that no party to this application has been denied the FCC benefits pursuant to Section 5301 of the Anti-Drug Abuse Act of 1988, 21 U.S.C. 862.


Randy Ortanez
President



FCC ID: BEJMN240	 FCC Pt. 22/24/27 CDMA / EvDO MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0912182292.BEJ	Test Dates: December 22 - 23, 2009	EUT Type: Cellular/AWS/PCS CDMA/EvDO Phone with Bluetooth	Page 1 of 48

TABLE OF CONTENTS


FCC PART 22, 24 & 27 MEASUREMENT REPORT	3
1.0 INTRODUCTION	4
1.1 SCOPE	4
1.2 TESTING FACILITY	4
2.0 PRODUCT INFORMATION	5
2.1 EQUIPMENT DESCRIPTION	5
2.2 EMI SUPPRESSION DEVICE(S)/MODIFICATIONS	5
2.3 LABELING REQUIREMENTS	5
3.0 DESCRIPTION OF TESTS	6
3.1 MEASUREMENT PROCEDURE	6
3.2 OCCUPIED BANDWIDTH EMISSION LIMITS	6
3.3 CELLULAR - BASE FREQUENCY BLOCKS	6
3.4 CELLULAR - MOBILE FREQUENCY BLOCKS	7
3.5 AWS - BASE FREQUENCY BLOCKS	7
3.6 AWS - MOBILE FREQUENCY BLOCKS	7
3.7 PCS - BASE FREQUENCY BLOCKS	8
3.8 PCS - MOBILE FREQUENCY BLOCKS	8
3.9 SPURIOUS AND HARMONIC EMISSIONS AT ANTENNA TERMINAL	8
3.10 RADIATED POWER AND RADIATED SPURIOUS EMISSIONS	8
3.11 PEAK-AVERAGE RATIO	9
3.12 FREQUENCY STABILITY / TEMPERATURE VARIATION	9
4.0 TEST EQUIPMENT CALIBRATION DATA	10
5.0 SAMPLE CALCULATIONS	11
6.0 TEST RESULTS	12
6.1 SUMMARY	12
6.2 EFFECTIVE RADIATED POWER OUTPUT DATA	13
6.3 EQUIVALENT ISOTROPIC RADIATED POWER OUTPUT DATA	14
6.4 CELLULAR CDMA RADIATED MEASUREMENTS	15
6.5 AWS CDMA RADIATED MEASUREMENTS	18
6.6 PCS CDMA RADIATED MEASUREMENTS	21
6.7 CELLULAR CDMA FREQUENCY STABILITY MEASUREMENTS	24
6.8 AWS CDMA FREQUENCY STABILITY MEASUREMENTS	26
6.9 PCS CDMA FREQUENCY STABILITY MEASUREMENTS	28
7.0 PLOT(S) OF EMISSIONS	30
8.0 CONCLUSION	48

FCC ID: BEJMN240		FCC Pt. 22/24/27 CDMA / EvDO MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0912182292.BEJ	Test Dates: December 22 - 23, 2009	EUT Type: Cellular/AWS/PCS CDMA/EvDO Phone with Bluetooth		Page 2 of 48



MEASUREMENT REPORT

FCC Part 22 / 24 / 27



§2.1033 General Information

APPLICANT: LG Electronics USA
APPLICANT ADDRESS: 1000 Sylvan Avenue
 Englewood Cliffs, NJ 07632
TEST SITE: PCTEST ENGINEERING LABORATORY, INC.
TEST SITE ADDRESS: 6660-B Dobbin Road, Columbia, MD 21045 USA
FCC RULE PART(S): §2; §22(H), §24(E), §27(C)(L)
BASE MODEL: MN240
FCC ID: BEJMN240
FCC CLASSIFICATION: PCS Licensed Transmitter Held to Ear (PCE)
EMISSION DESIGNATOR(S): 1M28F9W (Cellular) / 1M28F9W (AWS) / 1M28F9W (PCS)
MODE: CDMA / EvDO
FREQUENCY TOLERANCE: $\pm 0.00025\%$ (2.5 ppm)
Test Device Serial No.: N/A ☐ Production ☒ Pre-Production ☐ Engineering
DATE(S) OF TEST: December 22 - 23, 2009
TEST REPORT S/N: 0912182292.BEJ

Test Facility / Accreditations

Measurements were performed at PCTEST Engineering Lab. located in Columbia, MD 21045, U.S.A.



- PCTEST facility is an FCC registered (PCTEST Reg. No. 90864) test facility with the site description report on file and has met all the requirements specified in Section 2.948 of the FCC Rules and Industry Canada (2451A-1).
- PCTEST Lab is accredited to ISO 17025 by U.S. National Institute of Standards and Technology (NIST) under the National Voluntary Laboratory Accreditation Program (NVLAP Lab code: 100431-0) in EMC, FCC and Telecommunications.
- PCTEST Lab is accredited to ISO 17025-2005 by the American Association for Laboratory Accreditation (A2LA) in Specific Absorption Rate (SAR) testing, Hearing Aid Compatibility (HAC) testing, CTIA Test Plans, and wireless testing for FCC and Industry Canada Rules.
- PCTEST Lab is a recognized U.S. Conformity Assessment Body (CAB) in EMC and R&TTE (n.b. 0982) under the U.S.-EU Mutual Recognition Agreement (MRA).
- PCTEST TCB is a Telecommunication Certification Body (TCB) accredited to ISO/IEC Guide 65 by the American National Standards Institute (ANSI) in all scopes of FCC Rules and Industry Canada Standards (RSS).
- PCTEST facility is an IC registered (2451A-1) test laboratory with the site description on file at Industry Canada.
- PCTEST is a CTIA Authorized Test Laboratory (CATL) for AMPS, CDMA, and EvDO wireless devices and for Over-the-Air (OTA) Antenna Performance testing for AMPS, CDMA, GSM, GPRS, EGPRS, UMTS (W-CDMA), CDMA 1xEVDO, and CDMA 1xRTT.

FCC ID: BEJMN240	 PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22/24/27 CDMA / EvDO MEASUREMENT REPORT (CERTIFICATION)	 LG	Reviewed by: Quality Manager
Test Report S/N: 0912182292.BEJ	Test Dates: December 22 - 23, 2009	EUT Type: Cellular/AWS/PCS CDMA/EvDO Phone with Bluetooth		Page 3 of 48

1.0 INTRODUCTION

1.1 Scope

Measurement and determination of electromagnetic emissions (EME) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission.

1.2 Testing Facility

The map below shows the location of the PCTEST LABORATORY, its proximity to the FCC Laboratory, the Columbia vicinity area, the Baltimore-Washington Intern't'l (BWI) airport, the city of Baltimore and the Washington, DC area. (See Figure 1-1).

These measurement tests were conducted at the PCTEST Engineering Laboratory, Inc. facility in New Concept Business Park, Guilford Industrial Park, Columbia, Maryland. The site address is 6660-B Dobbin Road, Columbia, MD 21045. The test site is one of the highest points in the Columbia area with an elevation of 390 feet above mean sea level. The site coordinates are 39° 11'15" N latitude and 76° 49'38" W longitude. The facility is 1.5 miles North of the FCC laboratory, and the ambient signal and ambient signal strength are approximately equal to those of the FCC laboratory. There are no FM or TV transmitters within 15 miles of the site. The detailed description of the measurement facility was found to be in compliance with the requirements of § 2.948 according to ANSI C63.4-2003 on January 28, 2009.




Figure 1-1. Map of the Greater Baltimore and Metropolitan Washington, D.C. area

FCC ID: BEJMN240	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22/24/27 CDMA / E/DO MEASUREMENT REPORT (CERTIFICATION)	LG	Reviewed by: Quality Manager
Test Report S/N: 0912182292.BEJ	Test Dates: December 22 - 23, 2009	EUT Type: Cellular/AWS/PCS CDMA/EvDO Phone with Bluetooth		Page 4 of 48

2.0 PRODUCT INFORMATION

2.1 Equipment Description

The Equipment Under Test (EUT) is the **LGE Cellular/AWS/PCS CDMA/EvDO Phone with Bluetooth FCC ID: BEJMN240**. The EUT consisted of the following component(s):

Trade Name / Base Model	FCC ID	Description
LGE / Model: MN240	BEJMN240	Cellular/AWS/PCS CDMA/EvDO Phone with Bluetooth

Table 2-1. EUT Equipment Description

2.2 EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and no modifications were made during testing.

2.3 Labeling Requirements

Per 2.925

The FCC identifier shall be permanently affixed to the equipment and shall be readily visible to the purchaser at the time of purchase.

Per 15.19; Docket 95-19

In addition to this requirement, a device subject to certification shall be labeled as follows:

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

The label shall be permanently affixed at a conspicuous location on the device; instruction manual or pamphlet supplied to the user and be readily visible to the purchaser at the time of purchase. However, when the device is so small wherein placement of the label with specified statement is not practical, only the trade name and FCC ID must be displayed on the device per Section 15.19(b)(2).

Please see attachment for FCC ID label and label location.

FCC ID: BEJMN240		FCC Pt. 22/24/27 CDMA / EvDO MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0912182292.BEJ	Test Dates: December 22 - 23, 2009	EUT Type: Cellular/AWS/PCS CDMA/EvDO Phone with Bluetooth		Page 5 of 48

3.0 DESCRIPTION OF TESTS

3.1 Measurement Procedure

The radiated spurious measurements were made outdoors at a 3-meter test range (See Figure 3-1). The equipment under test is placed on a wooden turntable 80cm above the ground plane and 3 meters from the receive antenna. The receive antenna height and turntable rotations were adjusted for the highest reading on the receive spectrum analyzer. This power level was recorded using a broadband average power meter. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This level is recorded with the power meter. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic antenna are taken into consideration.




Figure 3-1. Diagram of 3-meter outdoor test range


Deviation from Measurement Procedure.....None

3.2 Occupied Bandwidth Emission Limits

§2.1049, 22.917(a)(b), 24.238(a)(b), §27.53(g)(1)

- On any frequency outside a licensee's frequency block, the power of any emission shall be attenuated below the transmitter power (P) by at least $43 + 10 \log(P)$ dB.
- Compliance with these provisions is based on the use of measurement instrumentation employing a resolution bandwidth of 1 MHz or greater. However, in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emission are attenuated at least 26 dB below the transmitter power.

3.3 Cellular - Base Frequency Blocks



BLOCK 1: 869 – 880 MHz (A* Low + A)


BLOCK 3: 890 – 891.5 MHz (A* High)

BLOCK 2: 880 – 890 MHz (B)

BLOCK 4: 891.5 – 894 MHz (B*)

FCC ID: BEJMN240	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22/24/27 CDMA / EvDO MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0912182292.BEJ	Test Dates: December 22 - 23, 2009	EUT Type: Cellular/AWS/PCS CDMA/EvDO Phone with Bluetooth		Page 6 of 48

3.4 Cellular - Mobile Frequency Blocks



BLOCK 1: 824 – 835 MHz (A* Low + A)


BLOCK 3: 845 – 846.5 MHz (A* High)

BLOCK 2: 835 – 845 MHz (B)

BLOCK 4: 846.5 – 849 MHz (B*)

3.5 AWS - Base Frequency Blocks

§27.5(h)



BLOCK 1: 2110 – 2120 MHz (A)

BLOCK 4: 2135 – 2140 MHz (D)

BLOCK 2: 2120 – 2130 MHz (B)


BLOCK 5: 2140 – 2145 MHz (E)

BLOCK 3: 2130 – 2135 MHz (C)

BLOCK 6: 2145 – 2155 MHz (F)

3.6 AWS - Mobile Frequency Blocks

§27.5(h)



BLOCK 1: 1710 – 1720 MHz (A)

BLOCK 4: 1735 – 1740 MHz (D)

BLOCK 2: 1720 – 1730 MHz (B)


BLOCK 5: 1740 – 1745 MHz (E)

BLOCK 3: 1730 – 1735 MHz (C)

BLOCK 6: 1745 – 1755 MHz (F)

FCC ID: BEJMN240	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22/24/27 CDMA / EVDO MEASUREMENT REPORT (CERTIFICATION)	LG	Reviewed by: Quality Manager
Test Report S/N: 0912182292.BEJ	Test Dates: December 22 - 23, 2009	EUT Type: Cellular/AWS/PCS CDMA/EVDO Phone with Bluetooth		Page 7 of 48

3.7 PCS - Base Frequency Blocks



BLOCK 1: 1930 – 1945 MHz (A)

BLOCK 4: 1965 – 1970 MHz (E)


BLOCK 2: 1945 – 1950 MHz (D)

BLOCK 5: 1970 – 1975 MHz (F)

BLOCK 3: 1950 – 1965 MHz (B)

BLOCK 6: 1975 – 1990 MHz (C)

3.8 PCS - Mobile Frequency Blocks



BLOCK 1: 1850 – 1865 MHz (A)

BLOCK 4: 1885 – 1890 MHz (E)

BLOCK 2: 1865 – 1870 MHz (D)

BLOCK 5: 1890 – 1895 MHz (F)

BLOCK 3: 1870 – 1885 MHz (B)

BLOCK 6: 1895 – 1910 MHz (C)

3.9 Spurious and Harmonic Emissions at Antenna Terminal

§2.1051, 22.917(a), 24.238(a), §27.53(g)

The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer. The spectrum is scanned from the lowest frequency generated in the equipment up to a frequency including its 10th harmonic.

3.10 Radiated Power and Radiated Spurious Emissions

§2.1053, 22.917(a), 22., 24.232(c), 24.238(a), §27.53(g)

Radiated power and radiated spurious emissions are measured outdoors at our 3-meter test range. The equipment under test is placed on a wooden turntable 80cm above the ground plane and 3 meters from the receive antenna. The receive antenna height and turntable rotations were adjusted for the highest reading on the receive spectrum analyzer. This level is then measured with a broadband average power meter. The spectrum is scanned from the lowest frequency generated in the equipment up to a frequency including its 10th harmonic. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator with the level of the signal generator being adjusted to obtain the same receive average power meter reading. This spurious level is recorded with the power meter. For readings above 1 GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration. This device was tested under all R.C.s and S.O.s and the worst case is reported with RC3/SO55 with "All Up" power control bits.

FCC ID: BEJMN240		FCC Pt. 22/24/27 CDMA / EvDO MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0912182292.BEJ	Test Dates: December 22 - 23, 2009	EUT Type: Cellular/AWS/PCS CDMA/EvDO Phone with Bluetooth		Page 8 of 48

3.11 Peak-Average Ratio

§24.232(d), §27.50(d)(5)

A peak to average ratio measurement is performed at the conducted port of the EUT. For CDMA signals, the spectrum analyzers Complementary Cumulative Distribution Function (CCDF) measurement profile is used to determine the largest deviation between the average and the peak power of the EUT in a given bandwidth. The CCDF curve shows how much time the peak waveform spends at or above a given average power level. The percent of time the signal spends at or above the level defines the probability for that particular power level.

3.12 Frequency Stability / Temperature Variation

§2.1055, 22.355, 24.235, §27.54

The frequency stability of the transmitter is measured by:

- a.) **Temperature:** The temperature is varied from -30°C to +50°C in 10°C increments using an environmental chamber.
- b.) **Primary Supply Voltage:** The primary supply voltage is varied from 85% to 115% of the nominal value for non hand-carried battery and AC powered equipment. For hand-carried, battery-powered equipment, primary supply voltage is reduced to the battery operating end point which shall be specified by the manufacturer.

Specification – The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ (± 2.5 ppm) of the center frequency.

Time Period and Procedure:

1. The carrier frequency of the transmitter is measured at room temperature (20°C to provide a reference).
2. The equipment is turned on in a “standby” condition for one minute before applying power to the transmitter. Measurement of the carrier frequency of the transmitter is made within one minute after applying power to the transmitter.
3. Frequency measurements are made at 10°C intervals ranging from -30°C to +50°C. A sufficient stabilization period at each temperature shall be used prior to each frequency requirement.

FCC ID: BEJMN240		FCC Pt. 22/24/27 CDMA / EvDO MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0912182292.BEJ	Test Dates: December 22 - 23, 2009	EUT Type: Cellular/AWS/PCS CDMA/EvDO Phone with Bluetooth		Page 9 of 48

4.0 TEST EQUIPMENT CALIBRATION DATA

Test Equipment Calibration is traceable to the National Institute of Standards and Technology (NIST).

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
-	263-10dB	(DC-18GHz) 10 dB Attenuator	N/A		N/A	N/A
-	No.166	(1000-26500MHz) Microwave RF Cable	N/A		N/A	N/A
-	No.167	(100kHz - 100MHz) RG58 Coax Cable	N/A		N/A	N/A
Agilent	11713A	Attenuation/Switch Driver	12/2/2009	Annual	12/2/2010	3439A02645
Agilent	8449B	(1-26.5GHz) Pre-Amplifier	12/2/2009	Annual	12/2/2010	3008A00985
Agilent	8495A	(0-70dB) DC-4GHz Attenuator	N/A		N/A	N/A
Agilent	85650A	Quasi-Peak Adapter	12/2/2009	Annual	12/2/2010	3303A01872
Agilent	8566B	(100Hz-22GHz) Spectrum Analyzer	12/2/2009	Annual	12/2/2010	3638A08713
Agilent	E8257D	(250kHz-20GHz) Signal Generator	3/25/2009	Biennial	3/25/2011	MY45470194
Agilent	N9020A	MXA Signal Analyzer	10/22/2009	Annual	10/22/2010	US46470561
Emco	3115	Horn Antenna (1-18GHz)	10/14/2009	Biennial	10/14/2011	9704-5182
Espec	ESX-2CA	Environmental Chamber	3/30/2009	Annual	3/30/2010	17620
Gigatronics	80701A	(0.05-18GHz) Power Sensor	9/9/2009	Annual	9/9/2010	1833460
Gigatronics	8651A	Universal Power Meter	9/9/2009	Annual	9/9/2010	8650319
MiniCircuits	VHF-1300+	High Pass Filter	N/A		N/A	30716
MiniCircuits	VHF-3100+	High Pass Filter	N/A		N/A	30721
Pasternack	PE2208-6	Bidirectional Coupler	N/A		N/A	N/A
Rohde & Schwarz	CMU200	Base Station Simulator	9/11/2009	Annual	9/11/2010	836371/0079
Schwarzbeck	UHA9105	Dipole Antenna (400 - 1GHz) Rx	7/17/2009	Biennial	7/17/2011	9105-2404
Schwarzbeck	UHA9105	Dipole Antenna (400 - 1GHz) Tx	7/17/2009	Biennial	7/17/2011	9105-2403
Sunol	DRH-118	Horn Antenna (1 - 18GHz)	5/14/2009	Biennial	5/14/2011	A050307
Sunol	JB5	Bi-Log Antenna (30M - 5GHz)	7/17/2009	Biennial	7/17/2011	A051107

Table 4-1. Test Equipment

FCC ID: BEJMN240		FCC Pt. 22/24/27 CDMA / EvDO MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0912182292.BEJ	Test Dates: December 22 - 23, 2009	EUT Type: Cellular/AWS/PCS CDMA/EvDO Phone with Bluetooth		Page 10 of 48

5.0 SAMPLE CALCULATIONS

Emission Designator

Emission Designator = 1M25F9W

CDMA BW = 1.25 MHz

F = Frequency Modulation

9 = Composite Digital Info

W = Combination (Audio/Data) (Measured at the 99.75% power bandwidth)

Spurious Radiated Emission - PCS Band

Example: Channel 25 PCS Mode 2nd Harmonic (3702.50 MHz)

The average receive power meter reading at 3 meters with the EUT on the turntable was -81.0 dBm. The gain of the substituted antenna is 8.1 dBi. The signal generator connected to the substituted antenna terminals is adjusted to produce a reading of -81.0 dBm on the power meter. The loss of the cable between the signal generator and the terminals of the substituted antenna is 2.0 dB at 3702.50 MHz. So 6.1 dB is added to the signal generator reading of -30.9 dBm yielding -24.80 dBm. The fundamental EIRP was 25.501 dBm so this harmonic was 25.501 dBm - (-24.80) = 50.3 dBc.

FCC ID: BEJMN240		FCC Pt. 22/24/27 CDMA / EvDO MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0912182292.BEJ	Test Dates: December 22 - 23, 2009	EUT Type: Cellular/AWS/PCS CDMA/EvDO Phone with Bluetooth		Page 11 of 48

6.0 TEST RESULTS

6.1 Summary

Company Name: LG Electronics USA
 FCC ID: BEJMN240
 FCC Classification: PCS Licensed Transmitter Held to Ear (PCE)
 Mode(s): CDMA / EvDO

FCC Part Section(s)	Test Description	Test Limit	Test Condition	Test Result	Reference
TRANSMITTER MODE (TX)					
2.1049, 22.917(a), 24.238(a), 27.53(g)(1)	Occupied Bandwidth	N/A	CONDUCTED	PASS	Section 7.0
2.1051, 22.917(a), 24.238(a), 27.53(g)	Band Edge / Conducted Spurious Emissions	< 43 + 10log ₁₀ (P[Watts]) at Band Edge and for all out-of-band emissions		PASS	Section 7.0
24.232(d), 27.50(d)(5)	Peak-Average Ratio	< 13 dB		PASS	Section 7.0
2.1046	Transmitter Conducted Output Power	N/A		PASS	RF Exposure Report
22.913(a)(2)	Effective Radiated Power	< 7 Watts max. ERP	RADIATED	PASS	Section 6.2
24.232(c), 27.50(d)(2)	Equivalent Isotropic Radiated Power	< 2 Watts max. EIRP		PASS	Section 6.3
2.1053, 22.917(a), 24.238(a), 27.53(g)	Undesirable Emissions	< 43 + 10log ₁₀ (P[Watts]) for all out-of-band emissions		PASS	Sections 6.4, 6.5, 6.6
2.1055, 22.355, 24.235, 27.54	Frequency Stability	< 2.5 ppm		PASS	Sections 6.7, 6.8, 6.9

Table 6-1. Summary of Test Results

FCC ID: BEJMN240		FCC Pt. 22/24/27 CDMA / EvDO MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0912182292.BEJ	Test Dates: December 22 - 23, 2009	EUT Type: Cellular/AWS/PCS CDMA/EvDO Phone with Bluetooth	Page 12 of 48	

6.2 Effective Radiated Power Output Data

§22.913(a)(2)

Frequency [MHz]	Mode	Measured Level [dBm]	Substitute Level [dBm]	Antenna Gain [dBd]	Pol [H/V]	ERP [dBm]	ERP [Watts]	Battery Type
824.70	CDMA850	-13.500	24.62	0.00	H	24.62	0.290	Standard
836.52	CDMA850	-14.830	23.29	0.00	H	23.29	0.213	Standard
848.31	CDMA850	-13.910	24.21	0.00	H	24.21	0.264	Standard

Table 6-2. Effective Radiated Power Output Data (Cellular Band)

NOTES:

Effective Radiated Power Output Measurements by Substitution Method according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

The EUT was placed on a wooden turn table 80cm above the ground plane and 3 meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. Final power measurements are made with a broadband average power meter. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same spectrum analyzer reading. This level is recorded using the power meter. The conducted power at the terminals of the dipole is measured. The ERP is recorded.

This device was tested under all R.C.s and S.O.s and the worst case is reported with RC3/SO55 with "All Up" power control bits. This unit was tested with its standard battery. The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case test configuration was found in the slide up setup. The data reported in the table above was measured in this test setup.

FCC ID: BEJMN240		FCC Pt. 22/24/27 CDMA / EvDO MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0912182292.BEJ	Test Dates: December 22 - 23, 2009	EUT Type: Cellular/AWS/PCS CDMA/EvDO Phone with Bluetooth		Page 13 of 48

6.3 Equivalent Isotropic Radiated Power Output Data

§24.232(c), §27.50(d)(2)

Frequency [MHz]	Mode	Measured Level [dBm]	Substitute Level [dBm]	Antenna Gain [dBi]	Pol [H/V]	EIRP [dBm]	EIRP [Watts]	Battery Type
1711.25	CDMA1700	-15.710	16.23	8.00	H	24.23	0.265	Standard
1732.50	CDMA1700	-13.790	18.15	8.00	H	26.15	0.412	Standard
1753.75	CDMA1700	-15.140	16.80	8.00	H	24.80	0.302	Standard

Table 6-3. Equivalent Isotropic Radiated Power Output Data (AWS Band)

Frequency [MHz]	Mode	Measured Level [dBm]	Substitute Level [dBm]	Antenna Gain [dBi]	Pol [H/V]	EIRP [dBm]	EIRP [Watts]	Battery Type
1851.25	CDMA1900	-13.520	17.71	8.00	H	25.71	0.372	Standard
1880.00	CDMA1900	-12.560	18.67	8.00	H	26.67	0.465	Standard
1908.75	CDMA1900	-12.970	18.26	8.00	H	26.26	0.423	Standard

Table 6-4. Equivalent Isotropic Radiated Power Output Data (PCS Band)

NOTES:

Equivalent Isotropic Radiated Power Measurements by Substitution Method according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

The EUT was placed on a wooden turn table 80cm above the ground plane and 3 meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. Final power measurements are made with a broadband average power meter. A Horn antenna was substituted in place of the EUT. This Horn antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same spectrum analyzer reading. This level is recorded using the power meter. The conducted power at the terminals of the Horn antenna is measured. The difference between the gain of the horn and an isotropic antenna is taken into consideration and the EIRP is recorded.

This device was tested under all R.C.s and S.O.s and the worst case is reported with RC3/SO55 with "All Up" power control bits. This unit was tested with its standard battery. The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case test configuration was found in the slide up setup. The data reported in the table above was measured in this test setup.

FCC ID: BEJMN240		FCC Pt. 22/24/27 CDMA / EvDO MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0912182292.BEJ	Test Dates: December 22 - 23, 2009	EUT Type: Cellular/AWS/PCS CDMA/EvDO Phone with Bluetooth		Page 14 of 48

6.4 Cellular CDMA Radiated Measurements

§2.1053, 22.917(a)

Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 824.70 MHz
 CHANNEL: 1013
 MEASURED OUTPUT POWER: 24.620 dBm = 0.290 W
 MODULATION SIGNAL: CDMA (Internal)
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10}(W) =$ 37.62 dBc

FREQUENCY (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBd)	SPURIOUS EMISSION LEVEL (dBm)	POL (H/V)	(dBc)
1649.40	-51.77	6.08	-45.69	H	70.3
2474.10	-62.57	6.08	-56.49	H	81.1
3298.80	-72.16	6.53	-65.63	H	90.3
4123.50	-93.33	6.87	-86.46	H	111.1
4948.20	-91.05	7.21	-83.83	H	108.5

Table 6-5. Radiated Spurious Data (Cellular CDMA Mode – Ch. 1013)

NOTES:

Radiated Spurious Emission Measurements by Substitution Method according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

The EUT was placed on a wooden turn table 80cm above the ground plane and 3 meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. Final power measurements are made with a broadband average power meter. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same spectrum analyzer reading. This spurious level is recorded using the power meter. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

This device was tested under all R.C.s and S.O.s and the worst case is reported with RC3/SO55 with "All Up" power control bits. This unit was tested with its standard battery. The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case test configuration was found in the slide up setup. The data reported in the table above was measured in this test setup.

FCC ID: BEJMN240		FCC Pt. 22/24/27 CDMA / EVDO MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0912182292.BEJ	Test Dates: December 22 - 23, 2009	EUT Type: Cellular/AWS/PCS CDMA/EVDO Phone with Bluetooth		Page 15 of 48

Cellular CDMA Radiated Measurements (Cont'd)

§2.1053, 22.917(a)

Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 836.52 MHz
 CHANNEL: 384
 MEASURED OUTPUT POWER: 24.620 dBm = 0.290 W
 MODULATION SIGNAL: CDMA (Internal)
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10} (W) =$ 37.62 dBc

FREQUENCY (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBd)	SPURIOUS EMISSION LEVEL (dBm)	POL (H/V)	(dBc)
1673.04	-65.39	6.09	-59.30	H	83.9
2509.56	-69.71	6.55	-63.16	H	87.8
3346.08	-65.44	6.89	-58.55	H	83.2
4182.60	-91.23	7.43	-83.80	H	108.4
5019.12	-89.39	8.35	-81.04	H	105.7

Table 6-6. Radiated Spurious Data (Cellular CDMA Mode – Ch. 384)

NOTES:

Radiated Spurious Emission Measurements by Substitution Method according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

The EUT was placed on a wooden turn table 80cm above the ground plane and 3 meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. Final power measurements are made with a broadband average power meter. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same spectrum analyzer reading. This spurious level is recorded using the power meter. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

This device was tested under all R.C.s and S.O.s and the worst case is reported with RC3/SO55 with "All Up" power control bits. This unit was tested with its standard battery. The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case test configuration was found in the slide up setup. The data reported in the table above was measured in this test setup.

FCC ID: BEJMN240		FCC Pt. 22/24/27 CDMA / EvDO MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0912182292.BEJ	Test Dates: December 22 - 23, 2009	EUT Type: Cellular/AWS/PCS CDMA/EvDO Phone with Bluetooth		Page 16 of 48

Cellular CDMA Radiated Measurements (Cont'd)

§2.1053, 22.917(a)

Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 848.31 MHz
 CHANNEL: 777
 MEASURED OUTPUT POWER: 24.620 dBm = 0.290 W
 MODULATION SIGNAL: CDMA (Internal)
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10} (W) =$ 37.62 dBc

FREQUENCY (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBd)	SPURIOUS EMISSION LEVEL (dBm)	POL (H/V)	(dBc)
1696.62	-48.56	6.09	-42.47	H	67.1
2544.93	-65.40	6.57	-58.83	H	83.4
3393.24	-71.36	6.91	-64.45	H	89.1
4241.55	-91.41	7.65	-83.77	H	108.4
5089.86	-89.11	8.33	-80.78	H	105.4

Table 6-7. Radiated Spurious Data (Cellular CDMA Mode – Ch. 777)

NOTES:

Radiated Spurious Emission Measurements by Substitution Method according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

The EUT was placed on a wooden turn table 80cm above the ground plane and 3 meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. Final power measurements are made with a broadband average power meter. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same spectrum analyzer reading. This spurious level is recorded using the power meter. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

This device was tested under all R.C.s and S.O.s and the worst case is reported with RC3/SO55 with "All Up" power control bits. This unit was tested with its standard battery. The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case test configuration was found in the slide up setup. The data reported in the table above was measured in this test setup.

FCC ID: BEJMN240		FCC Pt. 22/24/27 CDMA / EvDO MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0912182292.BEJ	Test Dates: December 22 - 23, 2009	EUT Type: Cellular/AWS/PCS CDMA/EvDO Phone with Bluetooth		Page 17 of 48

6.5 AWS CDMA Radiated Measurements

§2.1053, 27.53(g)

Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 1711.25 MHz
 CHANNEL: 25
 MEASURED OUTPUT POWER: 26.150 dBm = 0.412 W
 MODULATION SIGNAL: CDMA (Internal)
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10}(W) =$ 39.15 dBc

FREQUENCY (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBi)	SPURIOUS EMISSION LEVEL (dBm)	POL (H/V)	(dBc)
3422.50	-47.00	9.07	-37.93	H	64.1
5133.75	-50.59	10.47	-40.12	H	66.3
6845.00	-52.18	10.28	-41.91	H	68.1
8556.25	-55.48	11.40	-44.08	H	70.2
10267.50	-45.81	12.11	-33.70	H	59.9

Table 6-8. Radiated Spurious Data (AWS CDMA Mode – Ch. 25)

NOTES:

Radiated Spurious Emission Measurements by Substitution Method according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

The EUT was placed on a wooden turn table 80cm above the ground plane and 3 meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. Final power measurements are made with a broadband average power meter. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same spectrum analyzer reading. This spurious level is recorded using the power meter. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

This device was tested under all R.C.s and S.O.s and the worst case is reported with RC3/SO55 with "All Up" power control bits. This unit was tested with its standard battery. The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case test configuration was found in the slide up setup. The data reported in the table above was measured in this test setup.

FCC ID: BEJMN240		FCC Pt. 22/24/27 CDMA / EvDO MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0912182292.BEJ	Test Dates: December 22 - 23, 2009	EUT Type: Cellular/AWS/PCS CDMA/EvDO Phone with Bluetooth		Page 18 of 48

AWS CDMA Radiated Measurements (Cont'd)

§2.1053, 27.53(g)

Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 1732.50 MHz
 CHANNEL: 450
 MEASURED OUTPUT POWER: 26.150 dBm = 0.412 W
 MODULATION SIGNAL: CDMA (Internal)
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10}(W) =$ 39.15 dBc

FREQUENCY (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBi)	SPURIOUS EMISSION LEVEL (dBm)	POL (H/V)	(dBc)
3465.00	-43.25	9.09	-34.16	H	60.3
5197.50	-46.86	10.46	-36.40	H	62.6
6930.00	-46.96	10.18	-36.78	H	62.9
8662.50	-56.16	11.56	-44.60	H	70.7
10395.00	-47.47	12.16	-35.31	H	61.5

Table 6-9. Radiated Spurious Data (AWS CDMA Mode – Ch. 450)

NOTES:

Radiated Spurious Emission Measurements by Substitution Method according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

The EUT was placed on a wooden turn table 80cm above the ground plane and 3 meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. Final power measurements are made with a broadband average power meter. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same spectrum analyzer reading. This spurious level is recorded using the power meter. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

This device was tested under all R.C.s and S.O.s and the worst case is reported with RC3/SO55 with "All Up" power control bits. This unit was tested with its standard battery. The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case test configuration was found in the slide up setup. The data reported in the table above was measured in this test setup.

FCC ID: BEJMN240		FCC Pt. 22/24/27 CDMA / EvDO MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0912182292.BEJ	Test Dates: December 22 - 23, 2009	EUT Type: Cellular/AWS/PCS CDMA/EvDO Phone with Bluetooth		Page 19 of 48

AWS CDMA Radiated Measurements (Cont'd)

§2.1053, 27.53(g)

Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 1753.75 MHz
 CHANNEL: 875
 MEASURED OUTPUT POWER: 26.150 dBm = 0.412 W
 MODULATION SIGNAL: CDMA (Internal)
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10}(W) =$ 39.15 dBc

FREQUENCY (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBi)	SPURIOUS EMISSION LEVEL (dBm)	POL (H/V)	(dBc)
3507.50	-40.48	9.10	-31.38	H	57.5
5261.25	-50.59	10.45	-40.14	H	66.3
7015.00	-48.46	10.11	-38.35	H	64.5
8768.75	-55.50	11.73	-43.77	H	69.9
10522.50	-47.34	12.22	-35.12	H	61.3

Table 6-10. Radiated Spurious Data (AWS CDMA Mode – Ch. 875)

NOTES:

Radiated Spurious Emission Measurements by Substitution Method according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

The EUT was placed on a wooden turn table 80cm above the ground plane and 3 meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. Final power measurements are made with a broadband average power meter. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same spectrum analyzer reading. This spurious level is recorded using the power meter. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

This device was tested under all R.C.s and S.O.s and the worst case is reported with RC3/SO55 with "All Up" power control bits. This unit was tested with its standard battery. The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case test configuration was found in the slide up setup. The data reported in the table above was measured in this test setup.

FCC ID: BEJMN240		FCC Pt. 22/24/27 CDMA / EvDO MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0912182292.BEJ	Test Dates: December 22 - 23, 2009	EUT Type: Cellular/AWS/PCS CDMA/EvDO Phone with Bluetooth		Page 20 of 48

6.6 PCS CDMA Radiated Measurements

§2.1053, 24.238(a)

Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 1851.25 MHz
 CHANNEL: 25
 MEASURED OUTPUT POWER: 26.670 dBm = 0.465 W
 MODULATION SIGNAL: CDMA (Internal)
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10} (W) =$ 39.67 dBc

FREQUENCY (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBi)	SPURIOUS EMISSION LEVEL (dBm)	POL (H/V)	(dBc)
3702.50	-39.90	9.02	-30.88	H	57.6
5553.75	-49.43	10.40	-39.03	H	65.7
7405.00	-44.66	10.51	-34.16	H	60.8
9256.25	-63.44	11.84	-51.60	H	78.3
11107.50	-59.70	12.76	-46.94	H	73.6

Table 6-11. Radiated Spurious Data (PCS CDMA Mode – Ch. 25)

NOTES:

Radiated Spurious Emission Measurements by Substitution Method according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

The EUT was placed on a wooden turn table 80cm above the ground plane and 3 meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. Final power measurements are made with a broadband average power meter. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same spectrum analyzer reading. This spurious level is recorded using the power meter. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

This device was tested under all R.C.s and S.O.s and the worst case is reported with RC3/SO55 with "All Up" power control bits. This unit was tested with its standard battery. The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case test configuration was found in the slide up setup. The data reported in the table above was measured in this test setup.

FCC ID: BEJMN240		FCC Pt. 22/24/27 CDMA / EVDO MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0912182292.BEJ	Test Dates: December 22 - 23, 2009	EUT Type: Cellular/AWS/PCS CDMA/EVDO Phone with Bluetooth		Page 21 of 48

PCS CDMA Radiated Measurements (Cont'd)

§2.1053, 24.238(a)

Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 1880.00 MHz
 CHANNEL: 600
 MEASURED OUTPUT POWER: 26.670 dBm = 0.465 W
 MODULATION SIGNAL: CDMA (Internal)
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10} (W) =$ 39.67 dBc

FREQUENCY (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBi)	SPURIOUS EMISSION LEVEL (dBm)	POL (H/V)	(dBc)
3760.00	-36.17	8.99	-27.18	H	53.9
5640.00	-48.23	10.40	-37.83	H	64.5
7520.00	-45.68	10.62	-35.06	H	61.7
9400.00	-63.10	11.70	-51.40	H	78.1
11280.00	-61.22	12.69	-48.53	H	75.2

Table 6-12. Radiated Spurious Data (PCS CDMA Mode – Ch. 600)

NOTES:

Radiated Spurious Emission Measurements by Substitution Method according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

The EUT was placed on a wooden turn table 80cm above the ground plane and 3 meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. Final power measurements are made with a broadband average power meter. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same spectrum analyzer reading. This spurious level is recorded using the power meter. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

This device was tested under all R.C.s and S.O.s and the worst case is reported with RC3/SO55 with "All Up" power control bits. This unit was tested with its standard battery. The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case test configuration was found in the slide up setup. The data reported in the table above was measured in this test setup.

FCC ID: BEJMN240		FCC Pt. 22/24/27 CDMA / EvDO MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0912182292.BEJ	Test Dates: December 22 - 23, 2009	EUT Type: Cellular/AWS/PCS CDMA/EvDO Phone with Bluetooth		Page 22 of 48

PCS CDMA Radiated Measurements (Cont'd)

§2.1053, 24.238(a)

Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 1908.75 MHz
 CHANNEL: 1175
 MEASURED OUTPUT POWER: 26.670 dBm = 0.465 W
 MODULATION SIGNAL: CDMA (Internal)
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10} (W) =$ 39.67 dBc

FREQUENCY (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBi)	SPURIOUS EMISSION LEVEL (dBm)	POL (H/V)	(dBc)
3817.50	-36.95	8.97	-27.98	H	54.7
5726.25	-52.07	10.40	-41.67	H	68.3
7635.00	-46.75	10.71	-36.04	H	62.7
9543.75	-64.35	11.64	-52.72	H	79.4
11452.50	-59.16	12.62	-46.54	H	73.2

Table 6-13. Radiated Spurious Data (PCS CDMA Mode – Ch. 1175)

NOTES:

Radiated Spurious Emission Measurements by Substitution Method according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

The EUT was placed on a wooden turn table 80cm above the ground plane and 3 meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. Final power measurements are made with a broadband average power meter. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same spectrum analyzer reading. This spurious level is recorded using the power meter. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

This device was tested under all R.C.s and S.O.s and the worst case is reported with RC3/SO55 with "All Up" power control bits. This unit was tested with its standard battery. The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case test configuration was found in the slide up setup. The data reported in the table above was measured in this test setup.

FCC ID: BEJMN240		FCC Pt. 22/24/27 CDMA / EvDO MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0912182292.BEJ	Test Dates: December 22 - 23, 2009	EUT Type: Cellular/AWS/PCS CDMA/EvDO Phone with Bluetooth		Page 23 of 48

6.7 Cellular CDMA Frequency Stability Measurements

§2.1055, 22.355

OPERATING FREQUENCY: 836,520,000 Hz

CHANNEL: 384

REFERENCE VOLTAGE: 3.7 VDC

DEVIATION LIMIT: ± 0.00025 % or 2.5 ppm

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	3.70	+ 20 (Ref)	836,520,004	4	0.000000
100 %		- 30	836,520,010	10	0.000001
100 %		- 20	836,519,981	-19	-0.000002
100 %		- 10	836,519,987	-13	-0.000002
100 %		0	836,520,011	11	0.000001
100 %		+ 10	836,519,988	-12	-0.000001
100 %		+ 20	836,520,018	18	0.000002
100 %		+ 30	836,520,012	12	0.000001
100 %		+ 40	836,520,005	5	0.000001
100 %		+ 50	836,520,014	14	0.000002
115 %	4.26	+ 20	836,520,009	9	0.000001
BATT. ENDPOINT	3.41	+ 20	836,520,022	22	0.000003

Table 6-14. Frequency Stability Data (Cellular CDMA Mode – Ch. 384)

FCC ID: BEJMN240		FCC Pt. 22/24/27 CDMA / EvDO MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0912182292.BEJ	Test Dates: December 22 - 23, 2009	EUT Type: Cellular/AWS/PCS CDMA/EvDO Phone with Bluetooth		Page 24 of 48

Cellular CDMA Frequency Stability Measurements (Cont'd)

§2.1055, 22.355




Figure 6-1. Frequency Stability Graph (Cellular CDMA Mode – Ch. 384)

FCC ID: BEJMN240	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22/24/27 CDMA / EvDO MEASUREMENT REPORT (CERTIFICATION)	LG	Reviewed by: Quality Manager
Test Report S/N: 0912182292.BEJ	Test Dates: December 22 - 23, 2009	EUT Type: Cellular/AWS/PCS CDMA/EvDO Phone with Bluetooth		Page 25 of 48

6.8 AWS CDMA Frequency Stability Measurements

§2.1055, 27.54

OPERATING FREQUENCY: 1,732,500,000 Hz

CHANNEL: 450

REFERENCE VOLTAGE: 3.7 VDC

DEVIATION LIMIT: ± 0.00025 % or 2.5 ppm

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	3.70	+ 20 (Ref)	1,732,500,003	3	0.000000
100 %		- 30	1,732,500,013	13	0.000001
100 %		- 20	1,732,500,020	20	0.000001
100 %		- 10	1,732,500,014	14	0.000001
100 %		0	1,732,500,013	13	0.000001
100 %		+ 10	1,732,499,979	-21	-0.000001
100 %		+ 20	1,732,499,990	-10	-0.000001
100 %		+ 30	1,732,500,016	16	0.000001
100 %		+ 40	1,732,500,012	12	0.000001
100 %		+ 50	1,732,500,010	10	0.000001
115 %	4.26	+ 20	1,732,499,980	-20	-0.000001
BATT. ENDPOINT	3.41	+ 20	1,732,499,987	-13	-0.000001

Table 6-15. Frequency Stability Data (AWS CDMA Mode – Ch. 450)

FCC ID: BEJMN240		FCC Pt. 22/24/27 CDMA / EvDO MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0912182292.BEJ	Test Dates: December 22 - 23, 2009	EUT Type: Cellular/AWS/PCS CDMA/EvDO Phone with Bluetooth		Page 26 of 48

AWS CDMA Frequency Stability Measurements (Cont'd)

§2.1055, 27.54




Figure 6-2. Frequency Stability Graph (AWS CDMA Mode – Ch. 450)

FCC ID: BEJMN240	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22/24/27 CDMA / EvDO MEASUREMENT REPORT (CERTIFICATION)	LG	Reviewed by: Quality Manager
Test Report S/N: 0912182292.BEJ	Test Dates: December 22 - 23, 2009	EUT Type: Cellular/AWS/PCS CDMA/EvDO Phone with Bluetooth		Page 27 of 48

6.9 PCS CDMA Frequency Stability Measurements

§2.1055, 24.235

OPERATING FREQUENCY: 1,880,000,000 Hz

CHANNEL: 600

REFERENCE VOLTAGE: 3.7 VDC

DEVIATION LIMIT: ± 0.00025 % or 2.5 ppm

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	3.70	+ 20 (Ref)	1,879,999,989	-11	-0.000001
100 %		- 30	1,879,999,994	-6	0.000000
100 %		- 20	1,879,999,996	-4	0.000000
100 %		- 10	1,880,000,007	7	0.000000
100 %		0	1,880,000,015	15	0.000001
100 %		+ 10	1,879,999,992	-8	0.000000
100 %		+ 20	1,880,000,006	6	0.000000
100 %		+ 30	1,879,999,987	-13	-0.000001
100 %		+ 40	1,880,000,005	5	0.000000
100 %		+ 50	1,880,000,018	18	0.000001
115 %	4.26	+ 20	1,880,000,006	6	0.000000
BATT. ENDPOINT	3.41	+ 20	1,879,999,998	-2	0.000000

Table 6-16. Frequency Stability Data (PCS CDMA Mode – Ch. 600)

FCC ID: BEJMN240		FCC Pt. 22/24/27 CDMA / EvDO MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0912182292.BEJ	Test Dates: December 22 - 23, 2009	EUT Type: Cellular/AWS/PCS CDMA/EvDO Phone with Bluetooth		Page 28 of 48

PCS CDMA Frequency Stability Measurements (Cont'd)

§2.1055, 24.235






Figure 6-3. Frequency Stability Graph (PCS CDMA Mode – Ch. 600)

FCC ID: BEJMN240	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22/24/27 CDMA / EvDO MEASUREMENT REPORT (CERTIFICATION)	LG	Reviewed by: Quality Manager
Test Report S/N: 0912182292.BEJ	Test Dates: December 22 - 23, 2009	EUT Type: Cellular/AWS/PCS CDMA/EvDO Phone with Bluetooth		Page 29 of 48

7.0 PLOT(S) OF EMISSIONS




Plot 7-1. Conducted Spurious Plot (Cellular CDMA Mode – Ch. 1013)




Plot 7-2. Conducted Spurious Plot (Cellular CDMA Mode – Ch. 1013)

FCC ID: BEJMN240	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22/24/27 CDMA / EVDO MEASUREMENT REPORT (CERTIFICATION)	LG	Reviewed by: Quality Manager
Test Report S/N: 0912182292.BEJ	Test Dates: December 22 - 23, 2009	EUT Type: Cellular/AWS/PCS CDMA/EVDO Phone with Bluetooth		Page 30 of 48




Plot 7-3. Band Edge Plot (Cellular CDMA Mode – Ch. 1013)




Plot 7-4. 4MHz Span Plot (Cellular CDMA Mode – Ch. 1013)

FCC ID: BEJMN240	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22/24/27 CDMA / EvDO MEASUREMENT REPORT (CERTIFICATION)	Reviewed by: Quality Manager
Test Report S/N: 0912182292.BEJ	Test Dates: December 22 - 23, 2009	EUT Type: Cellular/AWS/PCS CDMA/EvDO Phone with Bluetooth	Page 31 of 48




Plot 7-5. Conducted Spurious Plot (Cellular CDMA Mode – Ch. 384)




Plot 7-6. Conducted Spurious Plot (Cellular CDMA Mode – Ch. 384)

FCC ID: BEJMN240	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22/24/27 CDMA / EvDO MEASUREMENT REPORT (CERTIFICATION)	Reviewed by: Quality Manager
Test Report S/N: 0912182292.BEJ	Test Dates: December 22 - 23, 2009	EUT Type: Cellular/AWS/PCS CDMA/EvDO Phone with Bluetooth	Page 32 of 48




Plot 7-7. Occupied Bandwidth Plot (Cellular CDMA Mode – Ch. 384)




Plot 7-8. Conducted Spurious Plot (Cellular CDMA Mode – Ch. 777)

FCC ID: BEJMN240	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22/24/27 CDMA / EvDO MEASUREMENT REPORT (CERTIFICATION)	Reviewed by: Quality Manager
Test Report S/N: 0912182292.BEJ	Test Dates: December 22 - 23, 2009	EUT Type: Cellular/AWS/PCS CDMA/EvDO Phone with Bluetooth	Page 33 of 48



Plot 7-9. Conducted Spurious Plot (Cellular CDMA Mode – Ch. 777)




Plot 7-10. Band Edge Plot (Cellular CDMA Mode – Ch. 777)

FCC ID: BEJMN240	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22/24/27 CDMA / EvDO MEASUREMENT REPORT (CERTIFICATION)	Reviewed by: Quality Manager
Test Report S/N: 0912182292.BEJ	Test Dates: December 22 - 23, 2009	EUT Type: Cellular/AWS/PCS CDMA/EvDO Phone with Bluetooth	Page 34 of 48




Plot 7-11. 4MHz Span Plot (Cellular CDMA Mode – Ch. 777)




Plot 7-12. Conducted Spurious Plot (AWS CDMA Mode – Ch. 25)

FCC ID: BEJMN240	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22/24/27 CDMA / EvDO MEASUREMENT REPORT (CERTIFICATION)	Reviewed by: Quality Manager
Test Report S/N: 0912182292.BEJ	Test Dates: December 22 - 23, 2009	EUT Type: Cellular/AWS/PCS CDMA/EvDO Phone with Bluetooth	Page 35 of 48



Plot 7-13. Conducted Spurious Plot (AWS CDMA Mode – Ch. 25)




Plot 7-14. Band Edge Plot (AWS CDMA Mode – Ch. 25)

FCC ID: BEJMN240	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22/24/27 CDMA / EvDO MEASUREMENT REPORT (CERTIFICATION)	Reviewed by: Quality Manager
Test Report S/N: 0912182292.BEJ	Test Dates: December 22 - 23, 2009	EUT Type: Cellular/AWS/PCS CDMA/EvDO Phone with Bluetooth	Page 36 of 48




Plot 7-15. 4MHz Span Plot (AWS CDMA Mode – Ch. 25)




Plot 7-16. Conducted Spurious Plot (AWS CDMA Mode – Ch. 450)

FCC ID: BEJMN240	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22/24/27 CDMA / EvDO MEASUREMENT REPORT (CERTIFICATION)	Reviewed by: Quality Manager
Test Report S/N: 0912182292.BEJ	Test Dates: December 22 - 23, 2009	EUT Type: Cellular/AWS/PCS CDMA/EvDO Phone with Bluetooth	Page 37 of 48




Plot 7-17. Conducted Spurious Plot (AWS CDMA Mode – Ch. 450)




Plot 7-18. Occupied Bandwidth Plot (AWS CDMA Mode – Ch. 450)

FCC ID: BEJMN240	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22/24/27 CDMA / EvDO MEASUREMENT REPORT (CERTIFICATION)	LG	Reviewed by: Quality Manager
Test Report S/N: 0912182292.BEJ	Test Dates: December 22 - 23, 2009	EUT Type: Cellular/AWS/PCS CDMA/EvDO Phone with Bluetooth		Page 38 of 48




Plot 7-19. Peak-Average Ratio Plot (AWS CDMA Mode – Ch. 450)



Plot 7-20. Conducted Spurious Plot (AWS CDMA Mode – Ch. 875)

FCC ID: BEJMN240	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22/24/27 CDMA / EvDO MEASUREMENT REPORT (CERTIFICATION)	Reviewed by: Quality Manager
Test Report S/N: 0912182292.BEJ	Test Dates: December 22 - 23, 2009	EUT Type: Cellular/AWS/PCS CDMA/EvDO Phone with Bluetooth	Page 39 of 48




Plot 7-21. Conducted Spurious Plot (AWS CDMA Mode – Ch. 875)




Plot 7-22. Band Edge Plot (AWS CDMA Mode – Ch. 875)

FCC ID: BEJMN240	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22/24/27 CDMA / EvDO MEASUREMENT REPORT (CERTIFICATION)	Reviewed by: Quality Manager
Test Report S/N: 0912182292.BEJ	Test Dates: December 22 - 23, 2009	EUT Type: Cellular/AWS/PCS CDMA/EvDO Phone with Bluetooth	Page 40 of 48




Plot 7-23. 4MHz Span Plot (AWS CDMA Mode – Ch. 875)




Plot 7-24. Conducted Spurious Plot (PCS CDMA Mode – Ch. 25)

FCC ID: BEJMN240	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22/24/27 CDMA / EvDO MEASUREMENT REPORT (CERTIFICATION)	Reviewed by: Quality Manager
Test Report S/N: 0912182292.BEJ	Test Dates: December 22 - 23, 2009	EUT Type: Cellular/AWS/PCS CDMA/EvDO Phone with Bluetooth	Page 41 of 48




Plot 7-25. Conducted Spurious Plot (PCS CDMA Mode – Ch. 25)




Plot 7-26. Band Edge Plot (PCS CDMA Mode – Ch. 25)

FCC ID: BEJMN240	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22/24/27 CDMA / EvDO MEASUREMENT REPORT (CERTIFICATION)	Reviewed by: Quality Manager
Test Report S/N: 0912182292.BEJ	Test Dates: December 22 - 23, 2009	EUT Type: Cellular/AWS/PCS CDMA/EvDO Phone with Bluetooth	Page 42 of 48




Plot 7-27. 4MHz Span Plot (PCS CDMA Mode – Ch. 25)




Plot 7-28. Conducted Spurious Plot (PCS CDMA Mode – Ch. 600)

FCC ID: BEJMN240	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22/24/27 CDMA / EvDO MEASUREMENT REPORT (CERTIFICATION)	Reviewed by: Quality Manager
Test Report S/N: 0912182292.BEJ	Test Dates: December 22 - 23, 2009	EUT Type: Cellular/AWS/PCS CDMA/EvDO Phone with Bluetooth	Page 43 of 48




Plot 7-29. Conducted Spurious Plot (PCS CDMA Mode – Ch. 600)




Plot 7-30. Occupied Bandwidth Plot (PCS CDMA Mode – Ch. 600)

FCC ID: BEJMN240	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22/24/27 CDMA / EvDO MEASUREMENT REPORT (CERTIFICATION)	LG	Reviewed by: Quality Manager
Test Report S/N: 0912182292.BEJ	Test Dates: December 22 - 23, 2009	EUT Type: Cellular/AWS/PCS CDMA/EvDO Phone with Bluetooth		Page 44 of 48




Plot 7-31. Peak-Average Ratio Plot (PCS CDMA Mode – Ch. 600)



Plot 7-32. Conducted Spurious Plot (PCS CDMA Mode – Ch. 1175)

FCC ID: BEJMN240	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22/24/27 CDMA / EvDO MEASUREMENT REPORT (CERTIFICATION)	Reviewed by: Quality Manager
Test Report S/N: 0912182292.BEJ	Test Dates: December 22 - 23, 2009	EUT Type: Cellular/AWS/PCS CDMA/EvDO Phone with Bluetooth	Page 45 of 48




Plot 7-33. Conducted Spurious Plot (PCS CDMA Mode – Ch. 1175)



Plot 7-34. Band Edge Plot (PCS CDMA Mode – Ch. 1175)

FCC ID: BEJMN240	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22/24/27 CDMA / EvDO MEASUREMENT REPORT (CERTIFICATION)	Reviewed by: Quality Manager
Test Report S/N: 0912182292.BEJ	Test Dates: December 22 - 23, 2009	EUT Type: Cellular/AWS/PCS CDMA/EvDO Phone with Bluetooth	Page 46 of 48



Plot 7-35. 4MHz Span Plot (PCS CDMA Mode – Ch. 1175)

FCC ID: BEJMN240	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22/24/27 CDMA / EvDO MEASUREMENT REPORT (CERTIFICATION)	LG	Reviewed by: Quality Manager
Test Report S/N: 0912182292.BEJ	Test Dates: December 22 - 23, 2009	EUT Type: Cellular/AWS/PCS CDMA/EvDO Phone with Bluetooth		Page 47 of 48

8.0 CONCLUSION

The data collected relate only to the item(s) tested and show that the **LGE Cellular/AWS/PCS CDMA/EvDO Phone with Bluetooth FCC ID: BEJMN240** complies with all the requirements of Parts 2, 22, 24, and 27 of the FCC rules.

FCC ID: BEJMN240		FCC Pt. 22/24/27 CDMA / EvDO MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0912182292.BEJ	Test Dates: December 22 - 23, 2009	EUT Type: Cellular/AWS/PCS CDMA/EvDO Phone with Bluetooth		Page 48 of 48