

TABLE OF CONTENTS


A.1 CONDUCTED EMISSION	2
A.2 RADIATED EMISSION	4
A.2.1 Emissions within Restricted Frequency Bands.....	4
A.2.2 Emissions outside the frequency band:.....	58
A.2.3 Emissions in Non-restricted Frequency Bands:.....	61
A.3 6dB BANDWIDTH	62
A.3.1 6dB Bandwidth Result.....	62
A.3.2 Measurement Plots	63
A.4 MAXIMUM PEAK OUTPUT POWER	66
A.4.1 Peak Output Power	66
A.4.2 Average Output Power (Reporting only).....	68
A.4.3 Measurement Plots	70
A.5 EMISSION LIMITATIONS	71
A.6 POWER SPECTRAL DENSITY	90
A.6.1 Power Spectral Density Result	90
A.6.2 Measurement Plots	91

Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City 244, Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303

A.1 CONDUCTED EMISSION

Test Date	2017/11/30	Temp./Hum.	24°C/57%
Test Voltage	AC 120V, 60Hz (via AC Adapter)		



Site no. : No.7 Shielded Room Data no. : 2
Condition : ESH2-Z5 366(ADAPTER) Phase : NEUTRAL
Limit : FCC 15-C
Env. / Ins. : 24°C / 57% ESCI(1276) Engineer : Nick Du
EUT : 13Z980
Power Rating : 120Vac/60Hz
Test Mode : Operating

	Freq. (MHz)	AMN Factor (dB)	Cable Loss (dB)	Pulse Att. (dB)	Reading (dBμV)	Emission Level (dBμV)	Limits (dBμV)	Margin (dB)	Remark
1	0.154	0.19	0.03	9.86	25.62	35.70	55.78	20.08	Average
2	0.154	0.19	0.03	9.86	43.10	53.18	65.78	12.60	QP
3	0.191	0.17	0.04	9.86	25.63	35.70	53.98	18.28	Average
4	0.191	0.17	0.04	9.86	36.26	46.33	63.98	17.65	QP
5	0.246	0.18	0.04	9.86	14.88	24.96	51.91	26.95	Average
6	0.246	0.18	0.04	9.86	30.08	40.16	61.91	21.75	QP
7	0.305	0.18	0.04	9.86	17.18	27.26	50.10	22.84	Average
8	0.305	0.18	0.04	9.86	23.89	33.97	60.10	26.13	QP
9	3.943	0.32	0.17	9.87	20.87	31.23	46.00	14.77	Average
10	3.943	0.32	0.17	9.87	31.92	42.28	56.00	13.72	QP
11	21.715	0.97	0.31	9.95	11.72	22.95	50.00	27.05	Average
12	21.715	0.97	0.31	9.95	20.36	31.59	60.00	28.41	QP

Remarks: 1. Emission Level= AMN Factor + Cable Loss + Pulse Att. + Reading.
2. If the average limit is met when using a quasi-peak detector, the EUT shall be deemed to meet both limits and measurement with average detector is unnecessary.

Audix Technology Corp.


No. 53-11, Dingfu, Linkou, Dist.,

New Taipei City 244, Taiwan

Tel: +886 2 26099301

Fax: +886 2 26099303

Test Date	2017/11/30	Temp./Hum.	24°C/57%
Test Voltage	AC 120V, 60Hz (via AC Adapter)		



Site no. : No.7 Shielded Room Data no. : 1
Condition : ESH2-Z5 366(ADAPTER) Phase : LINE
Limit : FCC 15-C
Env. / Ins. : 24°C / 57% ESCI(1276) Engineer : Nick Du
EUT : 13Z980
Power Rating : 120Vac/60Hz
Test Mode : Operating

	Freq. (MHz)	AMN Factor (dB)	Cable Loss (dB)	Pulse Att. (dB)	Reading (dBμV)	Emission Level (dBμV)	Limits (dBμV)	Margin (dB)	Remark
1	0.154	0.18	0.03	9.86	27.81	37.88	55.78	17.90	Average
2	0.154	0.18	0.03	9.86	43.69	53.76	65.78	12.02	QP
3	0.183	0.17	0.04	9.86	30.50	40.57	54.33	13.76	Average
4	0.183	0.17	0.04	9.86	40.29	50.36	64.33	13.97	QP
5	0.239	0.17	0.04	9.86	20.83	30.90	52.13	21.23	Average
6	0.239	0.17	0.04	9.86	32.64	42.71	62.13	19.42	QP
7	0.303	0.17	0.04	9.86	15.09	25.16	50.15	24.99	Average
8	0.303	0.17	0.04	9.86	25.25	35.32	60.15	24.83	QP
9	3.943	0.33	0.17	9.87	23.83	34.20	46.00	11.80	Average
10	3.943	0.33	0.17	9.87	32.69	43.06	56.00	12.94	QP
11	17.944	1.04	0.29	9.93	12.88	24.14	50.00	25.86	Average
12	17.944	1.04	0.29	9.93	20.30	31.56	60.00	28.44	QP

Remarks: 1. Emission Level= AMN Factor + Cable Loss + Pulse Att. + Reading.
2. If the average limit is met when using a quasi-peak detector,
the EUT shall be deemed to meet both limits and measurement
with average detector is unnecessary.

A.2 RADIATED EMISSION

Test Date	2017/11/30	Temp./Hum.	24°C/51%
Test Voltage	AC 120V, 60Hz (via AC Adapter)		

A.2.1 Emissions within Restricted Frequency Bands

A.2.1.1 Frequency 9kHz~30MHz

The emissions (9kHz~30MHz) not reported for there is no emission be found.

A.2.1.2 Frequency Below 1 GHz

Mode	802.11n-HT20	Frequency	TX 2437MHz
------	--------------	-----------	------------

Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
144.46	17.47	2.77	20.63	40.87	43.50	2.63	Peak
209.45	16.44	3.44	20.37	40.25	43.50	3.25	Peak
279.29	19.36	4.11	17.31	40.78	46.00	5.22	Peak
488.81	23.04	6.34	12.77	42.15	46.00	3.85	Peak
720.64	25.12	7.20	7.03	39.35	46.00	6.65	Peak
890.39	26.73	8.12	4.59	39.44	46.00	6.56	Peak

Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
54.25	13.77	1.64	21.63	37.04	40.00	2.96	Peak
139.61	17.82	2.72	14.15	34.69	43.50	8.81	Peak
279.29	19.36	4.11	21.38	44.85	46.00	1.15	Peak
489.78	23.04	6.34	15.23	44.61	46.00	1.39	Peak
699.30	24.87	7.08	9.89	41.84	46.00	4.16	Peak
768.17	25.61	7.45	8.64	41.70	46.00	4.30	Peak

Mode	BLE	Frequency	TX 2440MHz
------	-----	-----------	------------

Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dB μ V)	Emission Level (dB μ V/m)	Limits (dB μ V/m)	Margin (dB)	Detector
81.41	14.15	2.03	21.55	37.73	40.00	2.27	Peak
139.61	17.82	2.72	19.28	39.82	43.50	3.68	Peak
288.02	19.41	4.19	18.09	41.69	46.00	4.31	Peak
488.81	23.04	6.34	12.04	41.42	46.00	4.58	Peak
801.15	25.94	7.62	7.47	41.03	46.00	4.97	Peak
890.39	26.73	8.12	6.23	41.08	46.00	4.92	Peak

Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dB μ V)	Emission Level (dB μ V/m)	Limits (dB μ V/m)	Margin (dB)	Detector
83.35	14.45	2.05	21.36	37.86	40.00	2.14	Peak
288.02	19.41	4.19	21.27	44.87	46.00	1.13	Peak
488.81	23.04	6.34	14.84	44.22	46.00	1.78	Peak
648.86	24.76	6.92	12.46	44.14	46.00	1.86	Peak
698.33	24.87	7.08	11.36	43.31	46.00	2.69	Peak
864.20	26.49	7.97	3.95	38.41	46.00	7.59	Peak


Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City244, Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303

A.2.1.3 Frequency Above 1 GHz to 10th harmonics


Band Edge:

Mode	802.11b	Frequency	TX 2412MHz
------	---------	-----------	------------



Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2384.64	32.13	6.55	9.48	48.16	74.00	25.84	Peak
2390.04	32.16	6.57	6.12	44.85	74.00	29.15	Peak
2413.08	32.18	6.59	63.20	101.97	---	---	Peak




Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2385.72	32.16	6.57	-0.20	38.53	54.00	15.47	Average
2390.04	32.16	6.57	-1.79	36.94	54.00	17.06	Average
2414.64	32.18	6.59	60.18	98.95	---	---	Average

Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City 244, Taiwan


Tel: +886 2 26099301
Fax: +886 2 26099303

Mode	802.11b	Frequency	TX 2412MHz
------	---------	-----------	------------



Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2388.24	32.16	6.57	10.55	49.28	74.00	24.72	Peak
2390.04	32.16	6.57	8.18	46.91	74.00	27.09	Peak
2413.08	32.18	6.59	65.42	104.19	---	---	Peak




Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2387.64	32.16	6.57	4.07	42.80	54.00	11.20	Average
2390.04	32.16	6.57	1.87	40.60	54.00	13.40	Average
2414.64	32.18	6.59	62.23	101.00	---	---	Average

Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City 244, Taiwan


Tel: +886 2 26099301
Fax: +886 2 26099303

Mode	802.11b	Frequency	TX 2417MHz
------	---------	-----------	------------



Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2389.80	32.16	6.57	10.60	49.33	74.00	24.67	Peak
2390.04	32.16	6.57	11.25	49.98	74.00	24.02	Peak
2418.00	32.18	6.59	63.41	102.18	---	---	Peak




Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2389.80	32.16	6.57	3.13	41.86	54.00	12.14	Average
2390.04	32.16	6.57	4.59	43.32	54.00	10.68	Average
2419.68	32.20	6.61	60.02	98.83	---	---	Average

Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City 244, Taiwan


Tel: +886 2 26099301
Fax: +886 2 26099303

Mode	802.11b	Frequency	TX 2417MHz
------	---------	-----------	------------



Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2389.68	32.16	6.57	13.06	51.79	74.00	22.21	Peak
2390.04	32.16	6.57	14.27	53.00	74.00	21.00	Peak
2418.00	32.18	6.59	64.83	103.60	---	---	Peak




Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2389.68	32.16	6.57	5.67	44.40	54.00	9.60	Average
2390.04	32.16	6.57	8.42	47.15	54.00	6.85	Average
2416.20	32.18	6.59	61.61	100.38	---	---	Average

Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City244, Taiwan


Tel: +886 2 26099301
Fax: +886 2 26099303

Mode	802.11b	Frequency	TX 2457MHz
------	---------	-----------	------------



Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2456.00	32.25	6.65	62.31	101.21	---	---	Peak
2483.52	32.28	6.67	11.80	50.75	74.00	23.25	Peak
2483.76	32.28	6.67	11.94	50.89	74.00	23.11	Peak




Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2456.24	32.25	6.65	59.21	98.11	---	---	Average
2483.52	32.28	6.67	5.36	44.31	54.00	9.69	Average
2483.68	32.28	6.67	5.29	44.24	54.00	9.76	Average

Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City244, Taiwan


Tel: +886 2 26099301
Fax: +886 2 26099303

Mode	802.11b	Frequency	TX 2457MHz
------	---------	-----------	------------



Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2455.92	32.25	6.65	62.22	101.12	---	---	Peak
2483.52	32.28	6.67	11.27	50.22	74.00	23.78	Peak
2483.76	32.28	6.67	10.01	48.96	74.00	25.04	Peak




Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2454.24	32.25	6.65	58.65	97.55	---	---	Average
2483.52	32.28	6.67	6.37	45.32	54.00	8.68	Average
2483.76	32.28	6.67	5.66	44.61	54.00	9.39	Average

Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City 244, Taiwan


Tel: +886 2 26099301
Fax: +886 2 26099303

Mode	802.11b	Frequency	TX 2462MHz
------	---------	-----------	------------



Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2460.96	32.25	6.65	63.08	101.98	---	---	Peak
2483.52	32.28	6.67	9.48	48.43	74.00	25.57	Peak
2487.52	32.30	6.69	11.53	50.52	74.00	23.48	Peak




Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2461.20	32.25	6.65	59.52	98.42	---	---	Average
2483.52	32.28	6.67	-2.89	36.06	54.00	17.94	Average
2488.72	32.30	6.69	1.41	40.40	54.00	13.60	Average

Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City 244, Taiwan


Tel: +886 2 26099301
Fax: +886 2 26099303

Mode	802.11b	Frequency	TX 2462MHz
------	---------	-----------	------------



Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2460.88	32.25	6.65	61.96	100.86	---	---	Peak
2483.52	32.28	6.67	7.89	46.84	74.00	27.16	Peak
2484.32	32.28	6.67	8.58	47.53	74.00	26.47	Peak




Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2461.20	32.25	6.65	58.65	97.55	---	---	Average
2483.52	32.28	6.67	1.12	40.07	54.00	13.93	Average
2483.84	32.28	6.67	0.08	39.03	54.00	14.97	Average

Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City 244, Taiwan


Tel: +886 2 26099301
Fax: +886 2 26099303

Mode	802.11b	Frequency	TX 2467MHz
------	---------	-----------	------------



Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2468.08	32.25	6.65	59.07	97.97	---	---	Peak
2483.52	32.28	6.67	16.08	55.03	74.00	18.97	Peak
2483.76	32.28	6.67	15.46	54.41	74.00	19.59	Peak




Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2466.24	32.25	6.65	55.79	94.69	---	---	Average
2483.52	32.28	6.67	6.17	45.12	54.00	8.88	Average
2484.32	32.28	6.67	9.48	48.43	54.00	5.57	Average

Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City 244, Taiwan


Tel: +886 2 26099301
Fax: +886 2 26099303

Mode	802.11b	Frequency	TX 2467MHz
------	---------	-----------	------------



Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2468.00	32.25	6.65	57.30	96.20	---	---	Peak
2483.52	32.28	6.67	16.05	55.00	74.00	19.00	Peak
2483.92	32.28	6.67	14.25	53.20	74.00	20.80	Peak




Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2466.24	32.25	6.65	54.10	93.00	---	---	Average
2483.52	32.28	6.67	4.74	43.69	54.00	10.31	Average
2484.24	32.28	6.67	8.06	47.01	54.00	6.99	Average

Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City244, Taiwan


Tel: +886 2 26099301
Fax: +886 2 26099303

Mode	802.11b	Frequency	TX 2472MHz
------	---------	-----------	------------



Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2470.88	32.28	6.67	51.02	89.97	---	---	Peak
2483.52	32.28	6.67	7.03	45.98	74.00	28.02	Peak
2484.80	32.28	6.67	8.85	47.80	74.00	26.20	Peak




Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2471.28	32.28	6.67	48.04	86.99	---	---	Average
2483.52	32.28	6.67	-2.92	36.03	54.00	17.97	Average
2484.72	32.28	6.67	1.31	40.26	54.00	13.74	Average

Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City244, Taiwan


Tel: +886 2 26099301
Fax: +886 2 26099303

Mode	802.11b	Frequency	TX 2472MHz
------	---------	-----------	------------



Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2473.04	32.28	6.67	49.11	88.06	---	---	Peak
2483.52	32.28	6.67	6.28	45.23	74.00	28.77	Peak
2485.76	32.28	6.67	8.75	47.70	74.00	26.30	Peak




Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2471.20	32.28	6.67	46.02	84.97	---	---	Average
2483.52	32.28	6.67	-3.79	35.16	54.00	18.84	Average
2484.72	32.28	6.67	-0.52	38.43	54.00	15.57	Average

Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City 244, Taiwan


Tel: +886 2 26099301
Fax: +886 2 26099303

Mode	802.11g	Frequency	TX 2412MHz
------	---------	-----------	------------



Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2389.44	32.16	6.57	15.84	54.57	74.00	19.43	Peak
2390.04	32.16	6.57	17.21	55.94	74.00	18.06	Peak
2416.20	32.18	6.59	65.06	103.83	---	---	Peak




Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2389.80	32.16	6.57	0.06	38.79	54.00	15.21	Average
2390.04	32.16	6.57	0.61	39.34	54.00	14.66	Average
2416.20	32.18	6.59	55.20	93.97	---	---	Average

Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City 244, Taiwan


Tel: +886 2 26099301
Fax: +886 2 26099303

Mode	802.11g	Frequency	TX 2412MHz
------	---------	-----------	------------



Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2389.44	32.16	6.57	17.69	56.42	74.00	17.58	Peak
2390.04	32.16	6.57	16.90	55.63	74.00	18.37	Peak
2415.60	32.18	6.59	66.95	105.72	---	---	Peak




Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2389.80	32.16	6.57	4.36	43.09	54.00	10.91	Average
2390.04	32.16	6.57	4.89	43.62	54.00	10.38	Average
2414.88	32.18	6.59	57.03	95.80	---	---	Average

Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City244, Taiwan


Tel: +886 2 26099301
Fax: +886 2 26099303

Mode	802.11g	Frequency	TX 2417MHz
------	---------	-----------	------------



Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2389.68	32.16	6.57	9.83	48.56	74.00	25.44	Peak
2390.04	32.16	6.57	9.09	47.82	74.00	26.18	Peak
2421.72	32.20	6.61	64.45	103.26	---	---	Peak




Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2389.80	32.16	6.57	-3.92	34.81	54.00	19.19	Average
2390.04	32.16	6.57	-3.62	35.11	54.00	18.89	Average
2420.28	32.20	6.61	54.10	92.91	---	---	Average

Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City244, Taiwan


Tel: +886 2 26099301
Fax: +886 2 26099303

Mode	802.11g	Frequency	TX 2417MHz
------	---------	-----------	------------



Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2389.56	32.16	6.57	12.65	51.38	74.00	22.62	Peak
2390.04	32.16	6.57	11.38	50.11	74.00	23.89	Peak
2420.04	32.20	6.61	65.28	104.09	---	---	Peak




Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2389.56	32.16	6.57	-1.49	37.24	54.00	16.76	Average
2390.04	32.16	6.57	-0.70	38.03	54.00	15.97	Average
2418.36	32.18	6.59	55.30	94.07	---	---	Average

Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City244, Taiwan


Tel: +886 2 26099301
Fax: +886 2 26099303

Mode	802.11g	Frequency	TX 2457MHz
------	---------	-----------	------------



Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2453.50	32.25	6.65	66.19	105.09	---	---	Peak
2483.50	32.28	6.67	21.96	60.91	74.00	13.09	Peak
2483.90	32.28	6.67	23.15	62.10	74.00	11.90	Peak




Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2453.60	32.25	6.65	56.28	95.18	---	---	Average
2483.50	32.28	6.67	7.33	46.28	54.00	7.72	Average
2484.00	32.28	6.67	6.86	45.81	54.00	8.19	Average

Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City244, Taiwan


Tel: +886 2 26099301
Fax: +886 2 26099303

Mode	802.11g	Frequency	TX 2457MHz
------	---------	-----------	------------



Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2454.40	32.25	6.65	65.60	104.50	---	---	Peak
2483.50	32.28	6.67	19.86	58.81	74.00	15.19	Peak
2484.80	32.28	6.67	18.43	57.38	74.00	16.62	Peak




Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2453.30	32.23	6.63	55.51	94.37	---	---	Average
2483.50	32.28	6.67	4.35	43.30	54.00	10.70	Average
2483.90	32.28	6.67	4.06	43.01	54.00	10.99	Average

Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City244, Taiwan


Tel: +886 2 26099301
Fax: +886 2 26099303

Mode	802.11g	Frequency	TX 2462MHz
------	---------	-----------	------------



Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2465.80	32.25	6.65	65.33	104.23	---	---	Peak
2483.50	32.28	6.67	24.78	63.73	74.00	10.27	Peak
2484.00	32.28	6.67	26.77	65.72	74.00	8.28	Peak




Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2465.30	32.25	6.65	55.22	94.12	---	---	Average
2483.50	32.28	6.67	11.34	50.29	54.00	3.71	Average
2484.00	32.28	6.67	10.67	49.62	54.00	4.38	Average

Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City244, Taiwan


Tel: +886 2 26099301
Fax: +886 2 26099303

Mode	802.11g	Frequency	TX 2462MHz
------	---------	-----------	------------



Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2458.40	32.25	6.65	64.47	103.37	---	---	Peak
2483.50	32.28	6.67	25.24	64.19	74.00	9.81	Peak
2484.00	32.28	6.67	26.01	64.96	74.00	9.04	Peak




Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2458.10	32.25	6.65	54.43	93.33	---	---	Average
2483.50	32.28	6.67	7.91	46.86	54.00	7.14	Average
2483.90	32.28	6.67	7.52	46.47	54.00	7.53	Average

Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City 244, Taiwan


Tel: +886 2 26099301
Fax: +886 2 26099303

Mode	802.11g	Frequency	TX 2467MHz
------	---------	-----------	------------



Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2468.20	32.25	6.65	59.31	98.21	---	---	Peak
2483.50	32.28	6.67	20.11	59.06	74.00	14.94	Peak
2484.50	32.28	6.67	21.45	60.40	74.00	13.60	Peak




Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2470.50	32.25	6.65	49.34	88.24	---	---	Average
2483.50	32.28	6.67	6.49	45.44	54.00	8.56	Average
2483.80	32.28	6.67	5.87	44.82	54.00	9.18	Average

Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City244, Taiwan


Tel: +886 2 26099301
Fax: +886 2 26099303

Mode	802.11g	Frequency	TX 2467MHz
------	---------	-----------	------------



Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2465.30	32.25	6.65	57.30	96.20	---	---	Peak
2483.50	32.28	6.67	20.17	59.12	74.00	14.88	Peak
2484.20	32.28	6.67	20.31	59.26	74.00	14.74	Peak




Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2463.60	32.25	6.65	47.70	86.60	---	---	Average
2483.50	32.28	6.67	2.84	41.79	54.00	12.21	Average
2484.00	32.28	6.67	1.86	40.81	54.00	13.19	Average

Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City244, Taiwan


Tel: +886 2 26099301
Fax: +886 2 26099303

Mode	802.11g	Frequency	TX 2472MHz
------	---------	-----------	------------



Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2469.80	32.25	6.65	43.32	82.22	---	---	Peak
2483.50	32.28	6.67	16.33	55.28	74.00	18.72	Peak
2484.00	32.28	6.67	16.37	55.32	74.00	18.68	Peak




Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2470.40	32.25	6.65	33.18	72.08	---	---	Average
2483.50	32.28	6.67	0.49	39.44	54.00	14.56	Average
2484.00	32.28	6.67	-0.42	38.53	54.00	15.47	Average

Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City 244, Taiwan


Tel: +886 2 26099301
Fax: +886 2 26099303

Mode	802.11g	Frequency	TX 2472MHz
------	---------	-----------	------------



Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2475.30	32.28	6.67	41.53	80.48	---	---	Peak
2483.50	32.28	6.67	16.01	54.96	74.00	19.04	Peak
2484.00	32.28	6.67	15.25	54.20	74.00	19.80	Peak




Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2475.60	32.28	6.67	31.40	70.35	---	---	Average
2483.50	32.28	6.67	-0.56	38.39	54.00	15.61	Average
2483.90	32.28	6.67	-1.29	37.66	54.00	16.34	Average

Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City244, Taiwan


Tel: +886 2 26099301
Fax: +886 2 26099303

Mode	802.11n-HT20	Frequency	TX 2412MHz
------	--------------	-----------	------------



Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2389.20	32.16	6.57	8.62	47.35	74.00	26.65	Peak
2390.04	32.16	6.57	10.16	48.89	74.00	25.11	Peak
2414.64	32.18	6.59	63.88	102.65	---	---	Peak




Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2389.44	32.16	6.57	-2.21	36.52	54.00	17.48	Average
2390.04	32.16	6.57	-1.16	37.57	54.00	16.43	Average
2416.44	32.18	6.59	54.60	93.37	---	---	Average

Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City244, Taiwan


Tel: +886 2 26099301
Fax: +886 2 26099303

Mode	802.11n-HT20	Frequency	TX 2412MHz
------	--------------	-----------	------------



Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2388.84	32.16	6.57	10.05	48.78	74.00	25.22	Peak
2390.04	32.16	6.57	10.06	48.79	74.00	25.21	Peak
2416.56	32.18	6.59	64.24	103.01	---	---	Peak




Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2389.56	32.16	6.57	-1.30	37.43	54.00	16.57	Average
2390.04	32.16	6.57	-0.44	38.29	54.00	15.71	Average
2414.28	32.18	6.59	54.68	93.45	---	---	Average

Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City244, Taiwan


Tel: +886 2 26099301
Fax: +886 2 26099303

Mode	802.11n-HT20	Frequency	TX 2417MHz
------	--------------	-----------	------------



Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2388.48	32.16	6.57	14.52	53.25	74.00	20.75	Peak
2390.04	32.16	6.57	14.41	53.14	74.00	20.86	Peak
2415.00	32.18	6.59	68.14	106.91	---	---	Peak




Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2389.68	32.16	6.57	1.91	40.64	54.00	13.36	Average
2390.04	32.16	6.57	2.58	41.31	54.00	12.69	Average
2419.08	32.18	6.59	58.23	97.00	---	---	Average

Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City244, Taiwan


Tel: +886 2 26099301
Fax: +886 2 26099303

Mode	802.11n-HT20	Frequency	TX 2417MHz
------	--------------	-----------	------------



Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2389.20	32.16	6.57	13.74	52.47	74.00	21.53	Peak
2390.04	32.16	6.57	13.76	52.49	74.00	21.51	Peak
2418.96	32.18	6.59	68.19	106.96	---	---	Peak




Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2389.44	32.16	6.57	2.07	40.80	54.00	13.20	Average
2390.04	32.16	6.57	3.06	41.79	54.00	12.21	Average
2419.56	32.20	6.61	58.48	97.29	---	---	Average

Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City 244, Taiwan


Tel: +886 2 26099301
Fax: +886 2 26099303

Mode	802.11n-HT20	Frequency	TX 2457MHz
------	--------------	-----------	------------



Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2452.50	32.23	6.63	68.18	107.04	---	---	Peak
2483.50	32.28	6.67	17.95	56.90	74.00	17.10	Peak
2485.60	32.28	6.67	19.04	57.99	74.00	16.01	Peak




Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2453.80	32.25	6.65	57.71	96.61	---	---	Average
2483.50	32.28	6.67	3.72	42.67	54.00	11.33	Average
2484.00	32.28	6.67	3.38	42.33	54.00	11.67	Average

Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City244, Taiwan


Tel: +886 2 26099301
Fax: +886 2 26099303

Mode	802.11n-HT20	Frequency	TX 2457MHz
------	--------------	-----------	------------



Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2453.90	32.25	6.65	67.43	106.33	---	---	Peak
2483.50	32.28	6.67	16.59	55.54	74.00	18.46	Peak
2488.80	32.30	6.69	17.68	56.67	74.00	17.33	Peak




Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2453.40	32.23	6.63	58.09	96.95	---	---	Average
2483.50	32.28	6.67	4.23	43.18	54.00	10.82	Average
2484.20	32.28	6.67	3.43	42.38	54.00	11.62	Average

Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City244, Taiwan


Tel: +886 2 26099301
Fax: +886 2 26099303

Mode	802.11n-HT20	Frequency	TX 2462MHz
------	--------------	-----------	------------



Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2464.20	32.25	6.65	65.65	104.55	---	---	Peak
2483.50	32.28	6.67	14.90	53.85	74.00	20.15	Peak
2484.00	32.28	6.67	15.66	54.61	74.00	19.39	Peak




Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2465.40	32.25	6.65	56.65	95.55	---	---	Average
2483.50	32.28	6.67	4.08	43.03	54.00	10.97	Average
2484.00	32.28	6.67	3.42	42.37	54.00	11.63	Average

Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City244, Taiwan


Tel: +886 2 26099301
Fax: +886 2 26099303

Mode	802.11n-HT20	Frequency	TX 2462MHz
------	--------------	-----------	------------



Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2463.90	32.25	6.65	66.83	105.73	---	---	Peak
2483.50	32.28	6.67	15.86	54.81	74.00	19.19	Peak
2484.30	32.28	6.67	17.02	55.97	74.00	18.03	Peak




Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2465.90	32.25	6.65	56.17	95.07	---	---	Average
2483.50	32.28	6.67	3.36	42.31	54.00	11.69	Average
2483.90	32.28	6.67	2.92	41.87	54.00	12.13	Average

Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City 244, Taiwan


Tel: +886 2 26099301
Fax: +886 2 26099303

Mode	802.11n-HT20	Frequency	TX 2467MHz
------	--------------	-----------	------------



Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2462.40	32.25	6.65	60.19	99.09	---	---	Peak
2483.50	32.28	6.67	17.08	56.03	74.00	17.97	Peak
2483.80	32.28	6.67	15.89	54.84	74.00	19.16	Peak




Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2465.50	32.25	6.65	50.07	88.97	---	---	Average
2483.50	32.28	6.67	1.88	40.83	54.00	13.17	Average
2483.80	32.28	6.67	1.04	39.99	54.00	14.01	Average

Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City 244, Taiwan


Tel: +886 2 26099301
Fax: +886 2 26099303

Mode	802.11n-HT20	Frequency	TX 2467MHz
------	--------------	-----------	------------



Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2468.10	32.25	6.65	59.38	98.28	---	---	Peak
2483.50	32.28	6.67	14.47	53.42	74.00	20.58	Peak
2484.30	32.28	6.67	15.32	54.27	74.00	19.73	Peak




Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2465.40	32.25	6.65	49.56	88.46	---	---	Average
2483.50	32.28	6.67	1.55	40.50	54.00	13.50	Average
2483.90	32.28	6.67	0.14	39.09	54.00	14.91	Average

Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City244, Taiwan


Tel: +886 2 26099301
Fax: +886 2 26099303

Mode	802.11n-HT20	Frequency	TX 2472MHz
------	--------------	-----------	------------



Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2467.70	32.25	6.65	47.46	86.36	---	---	Peak
2483.50	32.28	6.67	19.13	58.08	74.00	15.92	Peak
2483.90	32.28	6.67	20.52	59.47	74.00	14.53	Peak




Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2468.80	32.25	6.65	36.95	75.85	---	---	Average
2483.50	32.28	6.67	5.44	44.39	54.00	9.61	Average
2484.10	32.28	6.67	4.09	43.04	54.00	10.96	Average

Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City244, Taiwan


Tel: +886 2 26099301
Fax: +886 2 26099303

Mode	802.11n-HT20	Frequency	TX 2472MHz
------	--------------	-----------	------------



Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2469.60	32.25	6.65	46.39	85.29	---	---	Peak
2483.50	32.28	6.67	19.54	58.49	74.00	15.51	Peak
2483.80	32.28	6.67	19.33	58.28	74.00	15.72	Peak




Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2468.20	32.25	6.65	36.48	75.38	---	---	Average
2483.50	32.28	6.67	4.69	43.64	54.00	10.36	Average
2483.90	32.28	6.67	4.04	42.99	54.00	11.01	Average

Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City244, Taiwan


Tel: +886 2 26099301
Fax: +886 2 26099303

Mode	802.11n-HT40	Frequency	TX 2422MHz
------	--------------	-----------	------------



Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2389.10	32.16	6.57	12.65	51.38	74.00	22.62	Peak
2389.94	32.16	6.57	13.29	52.02	74.00	21.98	Peak
2430.68	32.20	6.61	62.20	101.01	---	---	Peak




Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2389.80	32.16	6.57	1.61	40.34	54.00	13.66	Average
2389.94	32.16	6.57	1.84	40.57	54.00	13.43	Average
2433.76	32.20	6.61	52.76	91.57	---	---	Average

Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City 244, Taiwan


Tel: +886 2 26099301
Fax: +886 2 26099303

Mode	802.11n-HT40	Frequency	TX 2422MHz
------	--------------	-----------	------------



Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2389.38	32.16	6.57	13.42	52.15	74.00	21.85	Peak
2389.94	32.16	6.57	14.76	53.49	74.00	20.51	Peak
2429.42	32.20	6.61	62.76	101.57	---	---	Peak




Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2389.66	32.16	6.57	3.13	41.86	54.00	12.14	Average
2389.94	32.16	6.57	3.06	41.79	54.00	12.21	Average
2433.90	32.20	6.61	52.80	91.61	---	---	Average

Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City 244, Taiwan


Tel: +886 2 26099301
Fax: +886 2 26099303

Mode	802.11n-HT40	Frequency	TX 2427MHz
------	--------------	-----------	------------



Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2389.52	32.16	6.57	12.22	50.95	74.00	23.05	Peak
2389.94	32.16	6.57	11.09	49.82	74.00	24.18	Peak
2433.90	32.20	6.61	64.43	103.24	---	---	Peak




Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2389.38	32.16	6.57	0.44	39.17	54.00	14.83	Average
2389.94	32.16	6.57	1.06	39.79	54.00	14.21	Average
2435.02	32.20	6.61	53.33	92.14	---	---	Average

Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City244, Taiwan


Tel: +886 2 26099301
Fax: +886 2 26099303

Mode	802.11n-HT40	Frequency	TX 2427MHz
------	--------------	-----------	------------



Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2389.24	32.16	6.57	11.86	50.59	74.00	23.41	Peak
2389.94	32.16	6.57	11.92	50.65	74.00	23.35	Peak
2437.96	32.23	6.63	63.06	101.92	---	---	Peak




Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2389.38	32.16	6.57	0.97	39.70	54.00	14.30	Average
2389.94	32.16	6.57	1.90	40.63	54.00	13.37	Average
2436.98	32.23	6.63	53.06	91.92	---	---	Average

Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City244, Taiwan


Tel: +886 2 26099301
Fax: +886 2 26099303

Mode	802.11n-HT40	Frequency	TX 2447MHz
------	--------------	-----------	------------



Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2438.90	32.23	6.63	62.41	101.27	---	---	Peak
2483.50	32.28	6.67	11.74	50.69	74.00	23.31	Peak
2484.00	32.28	6.67	11.75	50.70	74.00	23.30	Peak




Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2439.50	32.23	6.63	54.88	93.74	---	---	Average
2483.50	32.28	6.67	4.22	43.17	54.00	10.83	Average
2484.00	32.28	6.67	4.21	43.16	54.00	10.84	Average

Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City244, Taiwan


Tel: +886 2 26099301
Fax: +886 2 26099303

Mode	802.11n-HT40	Frequency	TX 2447MHz
------	--------------	-----------	------------



Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2440.80	32.23	6.63	64.52	103.38	---	---	Peak
2483.50	32.28	6.67	17.42	56.37	74.00	17.63	Peak
2483.80	32.28	6.67	15.54	54.49	74.00	19.51	Peak




Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2439.90	32.23	6.63	54.77	93.63	---	---	Average
2483.50	32.28	6.67	3.91	42.86	54.00	11.14	Average
2483.80	32.28	6.67	3.95	42.90	54.00	11.10	Average

Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City 244, Taiwan


Tel: +886 2 26099301
Fax: +886 2 26099303

Mode	802.11n-HT40	Frequency	TX 2452MHz
------	--------------	-----------	------------



Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2441.10	32.23	6.63	64.32	103.18	---	---	Peak
2483.50	32.28	6.67	18.30	57.25	74.00	16.75	Peak
2484.50	32.28	6.67	20.51	59.46	74.00	14.54	Peak




Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2440.00	32.23	6.63	54.63	93.49	---	---	Average
2483.50	32.28	6.67	7.71	46.66	54.00	7.34	Average
2484.10	32.28	6.67	7.84	46.79	54.00	7.21	Average

Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City 244, Taiwan


Tel: +886 2 26099301
Fax: +886 2 26099303

Mode	802.11n-HT40	Frequency	TX 2452MHz
------	--------------	-----------	------------



Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2441.30	32.23	6.63	65.43	104.29	---	---	Peak
2483.50	32.28	6.67	19.14	58.09	74.00	15.91	Peak
2484.00	32.28	6.67	21.44	60.39	74.00	13.61	Peak




Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2443.50	32.23	6.63	54.82	93.68	---	---	Average
2483.50	32.28	6.67	7.41	46.36	54.00	7.64	Average
2484.00	32.28	6.67	6.98	45.93	54.00	8.07	Average

Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City 244, Taiwan


Tel: +886 2 26099301
Fax: +886 2 26099303

Mode	802.11n-HT40	Frequency	TX 2457MHz
------	--------------	-----------	------------



Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2445.60	32.23	6.63	58.67	97.53	---	---	Peak
2483.50	32.28	6.67	15.50	54.45	74.00	19.55	Peak
2483.80	32.28	6.67	13.58	52.53	74.00	21.47	Peak




Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2445.10	32.23	6.63	48.80	87.66	---	---	Average
2483.50	32.28	6.67	4.24	43.19	54.00	10.81	Average
2483.80	32.28	6.67	3.41	42.36	54.00	11.64	Average

Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City244, Taiwan


Tel: +886 2 26099301
Fax: +886 2 26099303

Mode	802.11n-HT40	Frequency	TX 2457MHz
------	--------------	-----------	------------



Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2450.40	32.23	6.63	58.96	97.82	---	---	Peak
2483.50	32.28	6.67	13.79	52.74	74.00	21.26	Peak
2483.80	32.28	6.67	12.53	51.48	74.00	22.52	Peak




Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2446.20	32.23	6.63	49.00	87.86	---	---	Average
2483.50	32.28	6.67	3.34	42.29	54.00	11.71	Average
2483.80	32.28	6.67	2.34	41.29	54.00	12.71	Average

Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City244, Taiwan


Tel: +886 2 26099301
Fax: +886 2 26099303

Mode	802.11n-HT40	Frequency	TX 2462MHz
------	--------------	-----------	------------



Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2466.30	32.25	6.65	50.95	89.85	---	---	Peak
2483.50	32.28	6.67	23.35	62.30	74.00	11.70	Peak
2483.90	32.28	6.67	23.64	62.59	74.00	11.41	Peak




Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2467.70	32.25	6.65	40.91	79.81	---	---	Average
2483.50	32.28	6.67	12.81	51.76	54.00	2.24	Average
2483.90	32.28	6.67	11.70	50.65	54.00	3.35	Average

Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City244, Taiwan


Tel: +886 2 26099301
Fax: +886 2 26099303

Mode	802.11n-HT40	Frequency	TX 2462MHz
------	--------------	-----------	------------



Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2451.30	32.23	6.63	50.95	89.81	---	---	Peak
2483.50	32.28	6.67	22.27	61.22	74.00	12.78	Peak
2484.00	32.28	6.67	22.21	61.16	74.00	12.84	Peak




Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2450.40	32.23	6.63	41.11	79.97	---	---	Average
2483.50	32.28	6.67	12.19	51.14	54.00	2.86	Average
2483.90	32.28	6.67	10.86	49.81	54.00	4.19	Average

Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City 244, Taiwan


Tel: +886 2 26099301
Fax: +886 2 26099303

Mode	BLE	Frequency	TX 2402MHz
------	-----	-----------	------------



Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2345.52	32.08	6.51	7.18	45.77	74.00	28.23	Peak
2390.04	32.16	6.57	4.53	43.26	74.00	30.74	Peak
2402.28	32.16	6.57	56.34	95.07	---	---	Peak




Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2379.36	32.13	6.55	-4.59	34.09	54.00	19.91	Average
2390.04	32.16	6.57	-5.32	33.41	54.00	20.59	Average
2402.04	32.16	6.57	55.85	94.58	---	---	Average

Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City 244, Taiwan


Tel: +886 2 26099301
Fax: +886 2 26099303

Mode	BLE	Frequency	TX 2402MHz
------	-----	-----------	------------



Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2382.24	32.13	6.55	7.10	45.78	74.00	28.22	Peak
2390.04	32.16	6.57	5.03	43.76	74.00	30.24	Peak
2402.28	32.16	6.57	54.20	92.93	---	---	Peak




Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2384.04	32.13	6.55	-4.93	33.75	54.00	20.25	Average
2390.04	32.16	6.57	-5.21	33.52	54.00	20.48	Average
2401.92	32.16	6.57	53.33	92.06	---	---	Average

Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City 244, Taiwan


Tel: +886 2 26099301
Fax: +886 2 26099303

Mode	BLE	Frequency	TX 2480MHz
------	-----	-----------	------------



Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2479.70	32.28	6.67	53.10	92.05	---	---	Peak
2483.50	32.28	6.67	6.68	45.63	74.00	28.37	Peak
2489.90	32.30	6.69	9.10	48.09	74.00	25.91	Peak




Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2480.00	32.28	6.67	52.54	91.49	---	---	Average
2483.50	32.28	6.67	-4.62	34.33	54.00	19.67	Average
2489.80	32.30	6.69	-4.03	34.96	54.00	19.04	Average

Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City 244, Taiwan


Tel: +886 2 26099301
Fax: +886 2 26099303

Mode	BLE	Frequency	TX 2480MHz
------	-----	-----------	------------



Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2480.20	32.28	6.67	49.67	88.62	---	---	Peak
2483.50	32.28	6.67	5.25	44.20	74.00	29.80	Peak
2489.90	32.30	6.69	8.07	47.06	74.00	26.94	Peak



Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2480.10	32.28	6.67	48.90	87.85	---	---	Average
2483.50	32.28	6.67	-4.82	34.13	54.00	19.87	Average
2489.50	32.30	6.69	-4.01	34.98	54.00	19.02	Average

A.2.2 Emissions outside the frequency band:

The emissions (up to 25GHz) not reported for there is no emission be found.

Mode	802.11b	Frequency	TX 2437MHz
------	---------	-----------	------------

Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
4875.00	34.25	9.56	-1.90	41.91	54.00	12.09	Peak

Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
4875.00	34.25	9.56	-0.72	43.09	54.00	10.91	Peak

Mode	802.11g	Frequency	TX 2437MHz
------	---------	-----------	------------

Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
4875.00	34.25	9.56	-0.74	43.07	54.00	10.93	Peak

Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
4875.00	34.25	9.56	-0.77	43.04	54.00	10.96	Peak

Mode	802.11n-HT20	Frequency	TX 2437MHz
------	--------------	-----------	------------

Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dB μ V)	Emission Level (dB μ V/m)	Limits (dB μ V/m)	Margin (dB)	Detector
4880.00	34.25	9.56	-0.40	43.41	54.00	10.59	Peak

Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dB μ V)	Emission Level (dB μ V/m)	Limits (dB μ V/m)	Margin (dB)	Detector
4880.00	34.25	9.56	1.23	45.04	54.00	8.96	Peak

Mode	802.11n-HT40	Frequency	TX 2437MHz
------	--------------	-----------	------------

Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dB μ V)	Emission Level (dB μ V/m)	Limits (dB μ V/m)	Margin (dB)	Detector
4875.00	34.25	9.56	-0.79	43.02	54.00	10.98	Peak

Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dB μ V)	Emission Level (dB μ V/m)	Limits (dB μ V/m)	Margin (dB)	Detector
4875.00	34.25	9.56	-0.36	43.45	54.00	10.55	Peak

Mode	BLE	Frequency	TX 2402MHz
------	-----	-----------	------------

Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dB μ V)	Emission Level (dB μ V/m)	Limits (dB μ V/m)	Margin (dB)	Detector
4805.00	34.22	9.54	-1.42	42.34	54.00	11.66	Peak

Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dB μ V)	Emission Level (dB μ V/m)	Limits (dB μ V/m)	Margin (dB)	Detector
4805.00	34.22	9.54	-1.19	42.57	54.00	11.43	Peak

Mode	BLE	Frequency	TX 2440MHz
------	-----	-----------	------------

Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dB μ V)	Emission Level (dB μ V/m)	Limits (dB μ V/m)	Margin (dB)	Detector
4880.00	34.25	9.56	-0.38	43.43	54.00	10.57	Peak

Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dB μ V)	Emission Level (dB μ V/m)	Limits (dB μ V/m)	Margin (dB)	Detector
4880.00	34.25	9.56	-0.21	43.60	54.00	10.40	Peak

Mode	BLE	Frequency	TX 2480MHz
------	-----	-----------	------------

Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dB μ V)	Emission Level (dB μ V/m)	Limits (dB μ V/m)	Margin (dB)	Detector
4960.00	34.29	9.60	-2.20	41.69	54.00	12.31	Peak

Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dB μ V)	Emission Level (dB μ V/m)	Limits (dB μ V/m)	Margin (dB)	Detector
4960.00	34.29	9.60	-1.78	42.11	54.00	11.89	Peak

A.2.3 Emissions in Non-restricted Frequency Bands:

Pursuant to KDB 558074 D01 DTS Meas Guidance v04 that emission levels below the 15.209 general radiated emissions limits is not required.

A.3 6dB BANDWIDTH

Test Date	2017/11/23 ~ 30	Temp./Hum.	23~25°C /56~60%
Cable Loss	---	Test Voltage	AC 120V, 60Hz (via AC Adapter)

A.3.1 6dB Bandwidth Result

Mode	Centre Frequency (MHz)	6 dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz) (Reference only)	Limit
802.11b	2412	10.13	14.159	>500kHz
	2437	10.14	14.002	
	2462	10.13	13.720	
	2472	10.14	13.829	
802.11g	2412	15.12	16.467	
	2437	15.13	16.401	
	2462	15.45	16.388	
	2472	15.72	16.437	
802.11n-HT20	2412	15.17	17.606	
	2437	15.17	17.624	
	2462	15.48	17.594	
	2472	15.51	17.635	
802.11n-HT40	2422	35.08	35.979	
	2437	35.08	35.975	
	2452	35.12	35.997	
	2462	33.69	35.889	
BLE	2402	0.6451	1.0623	
	2440	0.6508	1.0604	
	2480	0.6572	1.0579	


Audix Technology Corp.

No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City 244, Taiwan

Tel: +886 2 26099301

Fax: +886 2 26099303


A.3.2 Measurement Plots




File Number: C1M1711303

Report Number: EM-F170755

This test report may be reproduced in full only. The document may only be updated by Audix Technology Corp. personnel. Any changes will be noted in the Document History section of the report.





A.4 MAXIMUM PEAK OUTPUT POWER

Test Date	2017/11/24	Temp./Hum.	23°C/55%
Cable Loss	---	Test Voltage	AC 120V, 60Hz (via AC Adapter)

A.4.1 Peak Output Power

Mode	Centre Frequency (MHz)	Peak Output Power (dBm)		Max. Peak Output Power		Antenna Gain (dBi)	Output Power (E.I.R.P.)		Limit
		Chain 0	Chain 1	(dBm)	(W)		(dBm)	(W)	
802.11b	2412	21.06	21.73	21.73	0.148936	2.91	24.64	0.291072	< 30dBm (1W) (Maximum Peak Output Power) < 36dBm (4W) (E.I.R.P)
	2417	21.31	21.63	21.63	0.145546		24.54	0.284446	
	2437	20.86	21.93	21.93	0.155955		24.84	0.304789	
	2457	21.23	21.48	21.48	0.140605		24.39	0.274789	
	2462	20.92	21.81	21.81	0.151705		24.72	0.296483	
	2467	17.38	17.44	17.44	0.055463		20.35	0.108393	
	2472	10.38	9.88	10.38	0.010914		13.29	0.021330	

Mode	Centre Frequency (MHz)	Peak Output Power (dBm)		Max. Peak Output Power		Antenna Gain (dBi)	Output Power (E.I.R.P.)		Limit
		Chain 0	Chain 1	(dBm)	(W)		(dBm)	(W)	
802.11g	2412	20.84	16.93	20.84	0.121339	2.91	23.75	0.237137	< 30dBm (1W) (Maximum Peak Output Power) < 36dBm (4W) (E.I.R.P)
	2417	19.03	21.96	21.96	0.157036		24.87	0.306902	
	2437	21.64	22.34	22.34	0.171396		25.25	0.334965	
	2457	21.46	22.15	22.15	0.164059		25.06	0.320627	
	2462	21.36	22.46	22.46	0.176198		25.37	0.344350	
	2467	14.84	14.82	14.84	0.030479		17.75	0.059566	
	2472	1.07	-1.2	1.07	0.001279		3.98	0.002500	

Mode	Centre Frequency (MHz)	Peak Output Power (dBm)		Max. Peak Output Power		Antenna Gain (dBi)	Output Power (E.I.R.P.)		Limit
		Chain 0	Chain 1	(dBm)	(W)		(dBm)	(W)	
802.11n-HT20	2412	19.3	19.15	22.24	0.167494	2.91	25.15	0.327341	< 30dBm (1W) (Maximum Peak Output Power) < 36dBm (4W) (E.I.R.P)
	2417	19.45	19.66	22.57	0.180717		25.48	0.353183	
	2437	19.55	19.72	22.65	0.184077		25.56	0.359749	
	2457	18.8	19.32	22.08	0.161436		24.99	0.315500	
	2462	18.69	18.53	21.62	0.145211		24.53	0.283792	
	2467	12.87	13	15.95	0.039355		18.86	0.076913	
	2472	2.07	0.41	4.33	0.002710		7.24	0.005297	

Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City 244, Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303

Mode	Centre Frequency (MHz)	Peak Output Power (dBm)		Max. Peak Output Power		Antenna Gain (dBi)	Output Power (E.I.R.P.)		Limit
		Chain 0	Chain 1	(dBm)	(W)		(dBm)	(W)	
802.11n-HT40	2422	15.71	15.84	18.79	0.075683	2.91	21.70	0.147911	< 30dBm (1W) (Maximum Peak Output Power) < 36dBm (4W) (E.I.R.P)
	2427	16.04	16.01	19.04	0.080168		21.95	0.156675	
	2437	17.89	17.76	20.84	0.121339		23.75	0.237137	
	2447	17.25	17.53	20.40	0.109648		23.31	0.214289	
	2452	16.55	16.64	19.61	0.091411		22.52	0.178649	
	2457	13.77	13.82	16.81	0.047973		19.72	0.093756	
	2462	0.68	-2.73	2.31	0.001702		5.22	0.003327	

Mode	Centre Frequency (MHz)	Peak Output Power (dBm)		Max. Peak Output Power		Antenna Gain (dBi)	Output Power (E.I.R.P.)		Limit
		Chain 0	Chain 1	(dBm)	(W)		(dBm)	(W)	
BLE	2400	2.44	--	2.44	0.001754	2.91	5.35	0.003428	< 30dBm (1W) (Maximum Peak Output Power) < 36dBm (4W) (E.I.R.P)
	2440	2.95	--	2.95	0.001972		5.86	0.003855	
	2480	1.60	--	1.60	0.001445		4.51	0.002825	

Note: The results have been included cable loss.

Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City244, Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303

A.4.2 Average Output Power (Reporting only)

Mode	Centre Frequency (MHz)	Average Output Power (dBm)		10log (1/X)	Max. Average Output Power		Antenna Gain (dBi)	Total Average Output Power (E.I.R.P.)		Limit
		Chain 0	Chain 1		(dBm)	(W)		(dBm)	(W)	
802.11b	2412	18.86	18.84	0	18.86	0.076913	2.91	21.77	0.150314	< 30dBm (1W) (Maximum Peak Output Power) < 36dBm (4W) (E.I.R.P)
	2417	18.92	18.68		18.92	0.077983		21.83	0.152405	
	2437	18.98	18.68		18.98	0.079068		21.89	0.154525	
	2457	18.53	18.42		18.53	0.071285		21.44	0.139316	
	2462	18.57	18.53		18.57	0.071945		21.48	0.140605	
	2467	15.08	15.00		15.08	0.032211		17.99	0.062951	
	2472	7.49	7.30		7.49	0.005610		10.40	0.010965	

Mode	Centre Frequency (MHz)	Average Output Power (dBm)		10log (1/X)	Max. Average Output Power		Antenna Gain (dBi)	Total Average Output Power (E.I.R.P.)		Limit
		Chain 0	Chain 1		(dBm)	(W)		(dBm)	(W)	
802.11g	2412	16.89	16.65	0	16.89	0.048865	2.91	19.80	0.095499	< 30dBm (1W) (Maximum Peak Output Power) < 36dBm (4W) (E.I.R.P)
	2417	18.6	18.55		18.60	0.072444		21.51	0.141579	
	2437	18.94	18.90		18.94	0.078343		21.85	0.153109	
	2457	16.42	16.38		16.42	0.043853		19.33	0.085704	
	2462	15.93	15.80		15.93	0.039174		18.84	0.076560	
	2467	8.98	8.88		8.98	0.007907		11.89	0.015453	
	2472	-3.98	-3.99		-3.98	0.000400		-1.07	0.000782	

Mode	Centre Frequency (MHz)	Average Output Power (dBm)		10log (1/X)	Max. Average Output Power		Antenna Gain (dBi)	Total Average Output Power (E.I.R.P.)		Limit
		Chain 0	Chain 1		(dBm)	(W)		(dBm)	(W)	
802.11n-HT20	2412	15.99	15.85	0.22	19.15	0.082224	2.91	22.06	0.160694	< 30dBm (1W) (Maximum Peak Output Power) < 36dBm (4W) (E.I.R.P)
	2417	16.28	16.82		19.79	0.095280		22.70	0.186209	
	2437	16.99	16.94		20.20	0.104713		23.11	0.204644	
	2457	16.98	16.93		20.19	0.104472		23.10	0.204174	
	2462	15.00	14.98		18.22	0.066374		21.13	0.129718	
	2467	8.99	8.97		12.21	0.016634		15.12	0.032509	
	2472	-6.45	-5.62		-2.78	0.000527		0.13	0.001030	

Note: The results have been included cable loss.

Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City 244, Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303


Mode	Centre Frequency (MHz)	Average Output Power (dBm)		10log (1/X)	Max. Average Output Power		Antenna Gain (dBi)	Total Average Output Power (E.I.R.P.)		Limit
		Chain 0	Chain 1		(dBm)	(W)		(dBm)	(W)	
802.11n-HT40	2422	14.08	13.74	0.18	17.10	0.051286	2.91	20.01	0.100231	< 30dBm (1W) (Maximum Peak Output Power) < 36dBm (4W) (E.I.R.P)
	2427	14.45	14.30		17.56	0.057016		20.47	0.111429	
	2437	15.94	15.87		19.09	0.081096		22.00	0.158489	
	2447	14.97	14.9		18.12	0.064863		21.03	0.126765	
	2452	13.94	13.87		17.09	0.051168		20.00	0.100000	
	2457	10.49	10.44		13.65	0.023174		16.56	0.045290	
	2462	0.60	-3.5		2.20	0.001660		5.11	0.003243	

Note: The results have been included cable loss.

Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City244, Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303

A.4.3 Measurement Plots




Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City244, Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303

A.5 EMISSION LIMITATIONS

Test Date	2017/11/23 ~ 24	Temp./Hum.	23~25°C/56~60%
Cable Loss	0.50dB	Test Voltage	AC 120V, 60Hz (via AC Adapter)
Mode	802.11b	Frequency	TX 2412MHz
Simultaneous Factor10 log(n) (Note: “n” is antenna number)	0		



Audix Technology Corp.





No. 53-11, Dingfu, Linkou, Dist.,

New Taipei City244, Taiwan

Tel: +886 2 26099301

Fax: +886 2 26099303

Test Date	2017/11/23 ~ 24	Temp./Hum.	23~25°C/56~60%
Cable Loss	0.50dB	Test Voltage	AC 120V, 60Hz (via AC Adapter)
Mode	802.11b	Frequency	TX 2437MHz
Simultaneous Factor10 log(n) (Note: “n” is antenna number)	0		



Audix Technology Corp.


No. 53-11, Dingfu, Linkou, Dist.,

New Taipei City244, Taiwan

Tel: +886 2 26099301

Fax: +886 2 26099303

Test Date	2017/11/30	Temp./Hum.	23°C/60%
Cable Loss	1.90dB	Test Voltage	AC 120V, 60Hz (via AC Adapter)
Mode	802.11b	Frequency	TX 2462MHz
Simultaneous Factor10 log(n) (Note: "n" is antenna number)	0		



File Number: C1M1711303

Report Number: EM-F170755

This test report may be reproduced in full only. The document may only be updated by Audix Technology Corp. personnel. Any changes will be noted in the Document History section of the report.

Audix Technology Corp.


No. 53-11, Dingfu, Linkou, Dist.,

New Taipei City244, Taiwan

Tel: +886 2 26099301

Fax: +886 2 26099303

Test Date	2017/11/23 ~ 24	Temp./Hum.	23~25°C/56~60%
Cable Loss	0.50dB	Test Voltage	AC 120V, 60Hz (via AC Adapter)
Mode	802.11b	Frequency	TX 2472MHz
Simultaneous Factor10 log(n) (Note: "n" is antenna number)	0		



Audix Technology Corp.


No. 53-11, Dingfu, Linkou, Dist.,

New Taipei City244, Taiwan

Tel: +886 2 26099301

Fax: +886 2 26099303

Test Date	2017/11/23 ~ 24	Temp./Hum.	23~25°C/56~60%
Cable Loss	0.50dB	Test Voltage	AC 120V, 60Hz (via AC Adapter)
Mode	802.11g	Frequency	TX 2412MHz
Simultaneous Factor10 log(n) (Note: "n" is antenna number)	0		



File Number: C1M1711303

Report Number: EM-F170755

This test report may be reproduced in full only. The document may only be updated by Audix Technology Corp. personnel. Any changes will be noted in the Document History section of the report.

Audix Technology Corp.





No. 53-11, Dingfu, Linkou, Dist.,

New Taipei City244, Taiwan

Tel: +886 2 26099301

Fax: +886 2 26099303

Test Date	2017/11/23 ~ 24	Temp./Hum.	23~25°C/56~60%
Cable Loss	0.50dB	Test Voltage	AC 120V, 60Hz (via AC Adapter)
Mode	802.11g	Frequency	TX 2437MHz
Simultaneous Factor10 log(n) (Note: “n” is antenna number)	0		



Audix Technology Corp.


No. 53-11, Dingfu, Linkou, Dist.,

New Taipei City244, Taiwan

Tel: +886 2 26099301

Fax: +886 2 26099303

Test Date	2017/11/30	Temp./Hum.	23°C/60%
Cable Loss	1.90dB	Test Voltage	AC 120V, 60Hz (via AC Adapter)
Mode	802.11g	Frequency	TX 2462MHz
Simultaneous Factor10 log(n) (Note: "n" is antenna number)	0		



File Number: C1M1711303

Report Number: EM-F170755

This test report may be reproduced in full only. The document may only be updated by Audix Technology Corp. personnel. Any changes will be noted in the Document History section of the report.

Audix Technology Corp.

No. 53-11, Dingfu, Linkou, Dist.,

New Taipei City244, Taiwan

Tel: +886 2 26099301

Fax: +886 2 26099303

Test Date	2017/11/23 ~ 24	Temp./Hum.	23~25°C/56~60%
Cable Loss	0.50dB	Test Voltage	AC 120V, 60Hz (via AC Adapter)
Mode	802.11g	Frequency	TX 2472MHz
Simultaneous Factor10 log(n) (Note: "n" is antenna number)	0		



File Number: C1M1711303

Report Number: EM-F170755

This test report may be reproduced in full only. The document may only be updated by Audix Technology Corp. personnel. Any changes will be noted in the Document History section of the report.


Audix Technology Corp.

No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City244, Taiwan

Tel: +886 2 26099301

Fax: +886 2 26099303

Test Date	2017/11/29	Temp./Hum.	23°C/60%
Cable Loss	1.9dB	Test Voltage	AC 120V, 60Hz (via AC Adapter)
Mode	802.11n-HT20	Frequency	TX 2412MHz
Simultaneous Factor	10 log(n) (Note: “n” is antenna number)		3



File Number: C1M1711303

Report Number: EM-F170755

This test report may be reproduced in full only. The document may only be updated by Audix Technology Corp. personnel. Any changes will be noted in the Document History section of the report.

Audix Technology Corp.




No. 53-11, Dingfu, Linkou, Dist.,

New Taipei City244, Taiwan

Tel: +886 2 26099301

Fax: +886 2 26099303

Test Date	2017/11/29	Temp./Hum.	23°C/60%
Cable Loss	1.9dB	Test Voltage	AC 120V, 60Hz (via AC Adapter)
Mode	802.11n-HT20	Frequency	TX 2437MHz
Simultaneous Factor10 log(n) (Note: "n" is antenna number)	3		




Audix Technology Corp.

No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City244, Taiwan

Tel: +886 2 26099301

Fax: +886 2 26099303

Test Date	2017/11/29	Temp./Hum.	23°C/60%
Cable Loss	1.9dB	Test Voltage	AC 120V, 60Hz (via AC Adapter)
Mode	802.11n-HT20	Frequency	TX 2462MHz
Simultaneous Factor	10 log(n) (Note: "n" is antenna number)		3



Audix Technology Corp.


No. 53-11, Dingfu, Linkou, Dist.,

New Taipei City244, Taiwan

Tel: +886 2 26099301

Fax: +886 2 26099303

Test Date	2017/11/29	Temp./Hum.	23°C/60%
Cable Loss	1.9dB	Test Voltage	AC 120V, 60Hz (via AC Adapter)
Mode	802.11n-HT20	Frequency	TX 2472MHz
Simultaneous Factor	10 log(n) (Note: “n” is antenna number)		3



File Number: C1M1711303

Report Number: EM-F170755

This test report may be reproduced in full only. The document may only be updated by Audix Technology Corp. personnel. Any changes will be noted in the Document History section of the report.

Audix Technology Corp.


No. 53-11, Dingfu, Linkou, Dist.,

New Taipei City244, Taiwan

Tel: +886 2 26099301

Fax: +886 2 26099303

Test Date	2017/11/29	Temp./Hum.	23°C/60%
Cable Loss	1.9dB	Test Voltage	AC 120V, 60Hz (via AC Adapter)
Mode	802.11n-HT20	Frequency	TX 2422MHz
Simultaneous Factor	10 log(n) (Note: "n" is antenna number)		3



File Number: C1M1711303

Report Number: EM-F170755

This test report may be reproduced in full only. The document may only be updated by Audix Technology Corp. personnel. Any changes will be noted in the Document History section of the report.

Audix Technology Corp.


No. 53-11, Dingfu, Linkou, Dist.,

New Taipei City244, Taiwan

Tel: +886 2 26099301

Fax: +886 2 26099303

Test Date	2017/11/29	Temp./Hum.	23°C/60%
Cable Loss	1.9dB	Test Voltage	AC 120V, 60Hz (via AC Adapter)
Mode	802.11n-HT20	Frequency	TX 2437MHz
Simultaneous Factor10 log(n) (Note: "n" is antenna number)	3		



File Number: C1M1711303

Report Number: EM-F170755

This test report may be reproduced in full only. The document may only be updated by Audix Technology Corp. personnel. Any changes will be noted in the Document History section of the report.

Audix Technology Corp.


No. 53-11, Dingfu, Linkou, Dist.,

New Taipei City244, Taiwan

Tel: +886 2 26099301

Fax: +886 2 26099303

Test Date	2017/11/29	Temp./Hum.	23°C/60%
Cable Loss	1.9dB	Test Voltage	AC 120V, 60Hz (via AC Adapter)
Mode	802.11n-HT40	Frequency	TX 2452MHz
Simultaneous Factor	10 log(n) (Note: "n" is antenna number)		3



File Number: C1M1711303

Report Number: EM-F170755

This test report may be reproduced in full only. The document may only be updated by Audix Technology Corp. personnel. Any changes will be noted in the Document History section of the report.

Audix Technology Corp.


No. 53-11, Dingfu, Linkou, Dist.,

New Taipei City244, Taiwan

Tel: +886 2 26099301

Fax: +886 2 26099303

Test Date	2017/11/29	Temp./Hum.	23°C/60%
Cable Loss	1.9dB	Test Voltage	AC 120V, 60Hz (via AC Adapter)
Mode	802.11n-HT40	Frequency	TX 2462MHz
Simultaneous Factor	10 log(n) (Note: "n" is antenna number)		3



File Number: C1M1711303

Report Number: EM-F170755

This test report may be reproduced in full only. The document may only be updated by Audix Technology Corp. personnel. Any changes will be noted in the Document History section of the report.

Audix Technology Corp.


No. 53-11, Dingfu, Linkou, Dist.,

New Taipei City244, Taiwan

Tel: +886 2 26099301

Fax: +886 2 26099303

Test Date	2017/11/24	Temp./Hum.	25°C/56%
Cable Loss	0.50dB	Test Voltage	AC 120V, 60Hz (via AC Adapter)
Mode	BLE	Frequency	TX 2402MHz
Simultaneous Factor10 log(n) (Note: "n" is antenna number)	0		



File Number: C1M1711303

Report Number: EM-F170755

This test report may be reproduced in full only. The document may only be updated by Audix Technology Corp. personnel. Any changes will be noted in the Document History section of the report.

Audix Technology Corp.


No. 53-11, Dingfu, Linkou, Dist.,

New Taipei City244, Taiwan

Tel: +886 2 26099301

Fax: +886 2 26099303

Test Date	2017/11/24	Temp./Hum.	25°C/56%
Cable Loss	0.50dB	Test Voltage	AC 120V, 60Hz (via AC Adapter)
Mode	BLE	Frequency	TX 2440MHz
Simultaneous Factor10 log(n) (Note: “n” is antenna number)	0		



File Number: C1M1711303

Report Number: EM-F170755

This test report may be reproduced in full only. The document may only be updated by Audix Technology Corp. personnel. Any changes will be noted in the Document History section of the report.

Audix Technology Corp.


No. 53-11, Dingfu, Linkou, Dist.,

New Taipei City244, Taiwan

Tel: +886 2 26099301

Fax: +886 2 26099303

Test Date	2017/11/24	Temp./Hum.	25°C/56%
Cable Loss	0.50dB	Test Voltage	AC 120V, 60Hz (via AC Adapter)
Mode	BLE	Frequency	TX 2480MHz
Simultaneous Factor10 log(n) (Note: "n" is antenna number)	0		



File Number: C1M1711303

Report Number: EM-F170755

This test report may be reproduced in full only. The document may only be updated by Audix Technology Corp. personnel. Any changes will be noted in the Document History section of the report.

A.6 POWER SPECTRAL DENSITY

Test Date	2017/11/24 ~ 30	Temp./Hum.	23~25°C/56~60%
Test Voltage	AC 120V, 60Hz (via AC Adapter)		
Cable Loss	WLAN: 1.9dB, BLE: 0.50dB		
Simultaneous Factor 10 log(n) (Note: "n" is antenna number)		802.11b/g/BLE: 0, 802.11n-HT20/40: 3	

A.6.1 Power Spectral Density Result

Mode	Centre Frequency (MHz)	Power Spectral Density (dBm)	Limit
802.11b	2412	-3.30	< 8 dBm/3kHz
	2437	-3.68	
	2462	-3.56	
	2472	-15.95	
802.11g	2412	-7.46	
	2437	-5.81	
	2462	-8.99	
	2472	-27.54	
802.11n-HT20	2412	-5.48	
	2437	-5.82	
	2462	-7.76	
	2472	-31.87	
802.11n-HT40	2422	-11.20	
	2437	-8.95	
	2452	-11.89	
	2462	-29.16	
BLE	2402	2.38	
	2440	2.86	
	2480	1.43	

Note: All results have been included cable loss and Simultaneous Factor.


Audix Technology Corp.

No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City 244, Taiwan

Tel: +886 2 26099301

Fax: +886 2 26099303

A.6.2 Measurement Plots




Note: All results have been included cable loss and Simultaneous Factor.

File Number: C1M1711303

Report Number: EM-F170755


This test report may be reproduced in full only. The document may only be updated by Audix Technology Corp. personnel. Any changes will be noted in the Document History section of the report.



Note: All results have been included cable loss and Simultaneous Factor.

Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City244, Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303



Note: All results have been included cable loss and Simultaneous Factor.