

FCC 15.247 & RSS-247 2.4 GHz Test Report

for

LG Electronics Inc.

**222, LG-ro Jinwi-myeon, Pyeongtaek-Si, Gyeonggi-Do,
451-713, Korea**

Product Name : Notebook Computer
Model Name : 14Z980
Brand : LG
FCC ID : BEJNT-14Z980
IC : 2703H-14Z980

**Prepared by: : AUDIX Technology Corporation,
EMC Department**



TABLE OF CONTENTS

Description	Page
TEST REPORT CERTIFICATION.....	4
1. REVISION RECORD OF TEST REPORT	5
2. SUMMARY OF TEST RESULTS	6
3. GENERAL INFORMATION	7
3.1. Description of Application	7
3.2. Description of EUT	8
3.3. Antenna Information	9
3.4. EUT Specifications Assessed in Current Report	10
3.5. Descriptions of Key Components.....	12
3.6. Data Rate Relative to Output Power.....	15
3.7. Test Configuration.....	16
3.8. Tested Supporting System List.....	19
3.9. Setup Configuration.....	19
3.10. Operating Condition of EUT	19
3.11. Description of Test Facility	20
3.12. Measurement Uncertainty	20
4. MEASUREMENT EQUIPMENT LIST	21
4.1. Conducted Emission Measurement	21
4.2. Radiated Emission Measurement	21
4.3. RF Conducted Measurement	21
5. CONDUCTED EMISSION.....	22
5.1. Block Diagram of Test Setup	22
5.2. Conducted Emission Limit	22
5.3. Test Procedure	22
5.4. Test Results	22
6. RADIATED EMISSION	23
6.1. Block Diagram of Test Setup	23
6.2. Radiated Emission Limits.....	24
6.3. Test Procedure	25
6.4. Measurement Result Explanation.....	26
6.5. Test Results	26
7. 6dB BANDWIDTH	27
7.1. Block Diagram of Test Setup	27
7.2. Specification Limits.....	27
7.3. Test Procedure	27
7.4. Test Results	27
8. MAXIMUM PEAK OUTPUT POWER.....	28
8.1. Block Diagram of Test Setup	28
8.2. Specification Limits.....	28
8.3. Test Procedure	28
8.4. Test Results	28
9. EMISSION LIMITATIONS	29
9.1. Block Diagram of Test Setup	29

Audix Technology Corp.

No. 53-11, Dingfu, Linkou, Dist.,

New Taipei City 244, Taiwan

Tel: +886 2 26099301**Fax: +886 2 26099303**

9.2. Specification Limits.....	29
9.3. Test Procedure	29
9.4. Test Results	30
10. POWER SPECTRAL DENSITY	31
10.1. Block Diagram of Test Setup	31
10.2. Specification Limits.....	31
10.3. Test Procedure	31
10.4. Test Results	31
11. DEVIATION TO TEST SPECIFICATIONS	32

APPENDIX A TEST DATA AND PLOTS

APPENDIX B TEST PHOTOGRAPHS

TEST REPORT CERTIFICATION

Applicant : LG Electronics Inc.
Factory : LG Electronics Nanjing New Technology Co., Ltd.
EUT Description
(1) Product : Notebook Computer
(2) Model : 14Z980
(3) Brand : LG
(4) Power Supply: DC 19V, 2.53A

Applicable Standards:

47 CFR FCC Part 15 Subpart C
RSS-Gen (Issue 4), November 2014
RSS-247 (Issue 2), February 2017
ANSI C63.10:2013
KDB 558074 D01 DTS Meas Guidance v04

Audix Technology Corp. tested the equipment mentioned in accordance with the requirements set forth in the above standards. Test results indicate that the equipment tested is capable of demonstrating compliance with the requirements as documented within this report.

Audix Technology Corp. does not assume responsibility for any conclusions and generalizations drawn from the test results with regard to other specimens and samples.

Date of Report: 2017. 11. 30

Reviewed by: Sabrina Wang (Sabrina Wang/Administrator)

Approved by: Ben Cheng (Ben Cheng/Manager)

1. REVISION RECORD OF TEST REPORT

Edition No	Issued Data	Revision Summary	Report Number
0	2017. 11. 30	Original Report	EM-F170741

2. SUMMARY OF TEST RESULTS

Rule		Description	Results
FCC	IC		
15.207	RSS-Gen §8.8	Conducted Emission	PASS
15.247(d)/ 15.205	RSS-Gen §8.9 RSS-247 §5.5	Radiated Band Edge and Radiated Spurious Emission	PASS
15.247(a)(2)	RSS-247 §5.2(1)	6dB Bandwidth	PASS
15.247(b)(3)	RSS-247 §5.4(4)	Maximum Peak Output	PASS
15.247(d)	RSS-247 §5.5	Conducted Band Edges and Conducted Spurious Emission	PASS
15.247 (e)	RSS-247 §5.2(2)	Peak Power Spectral Density	PASS
15.203	RSS-Gen §8.3	Antenna Requirement	Compliance

3. GENERAL INFORMATION

3.1. Description of Application

Applicant	LG Electronics Inc. 222, LG-ro Jinwi-myeon, Pyeongtaek-Si, Gyeonggi-Do, 451-713, Korea
Factory	LG Electronics Nanjing New Technology Co., Ltd. No.346,Yaoxin Road, Economic & Technical Development Zone, Nanjing, China.
Product	Notebook Computer
Model	14Z980
Brand	LG

3.2. Description of EUT

Test Model	14Z980	
Serial Number	N/A	
Power Rating	DC 19V, 2.53A	
RF Features	WLAN: 802.11 a/b/g/n/ac Bluetooth: BT and BLE	
Transmit Type	2.4 GHz	
	802.11b	1T1R
	802.11g	1T1R
	802.11n-HT20	2T2R
	802.11n-HT40	2T2R
	BT/BLE	1T1R
	UNII Bands	
	802.11a	1T1R
	802.11n-HT20/ 802.11ac-VHT20	2T2R
	802.11n-HT40/ 802.11ac-VHT40	2T2R
	802.11ac-VHT80	2T2R
Sample Status	Production	
Date of Receipt	2017. 11. 21	
Date of Test	2017. 11. 23 ~ 30	
Interface Ports of EUT	• One Micro SD Card Slot • One Earphone Port • Two USB 3.0 Ports • One USB Type C Port • One HDMI Port • One DC Input Port	
Accessories Supplied	• AC Adapter	

3.3. Antenna Information

2.4G Antenna					
No.	Antenna Part Number	Manufacture	Antenna Type	Frequency (MHz)	Max Gain (dBi)
1	WA-F-LBLB-04-058 (Main)	INPAQ	FPCB	2400	1.94
				2450	2.72
				2500	1.20
2	WA-F-LBLB-04-058 (AUX)	INPAQ	FPCB	2400	2.79
				2450	2.29
				2500	1.90

5G Antenna					
No.	Antenna Part Number	Manufacture	Antenna Type	Frequency (MHz)	Max Gain (dBi)
1	WA-F-LBLB-04-058 (Main)	INPAQ	FPCB	5100	1.35
				5400	3.06
				5800	2.10
2	WA-F-LBLB-04-058 (AUX)	INPAQ	FPCB	5100	2.82
				5400	1.12
				5800	0.58

3.4. EUT Specifications Assessed in Current Report

Mode	Fundamental Range (MHz)	Channel Number	Modulation	Data Rate (Mbps)
802.11b	2412-2472	13	DSSS (DBPSK/DQPSK/CCK)	Up to 11
802.11g		13	OFDM (BPSK/QPSK/16QAM/64QAM)	Up to 54
802.11n-HT20				Up to 144.4
802.11n-HT40	2422-2462	9		Up to 300
BLE	2402-2480	40	GFSK	1

Channel List			
802.11 b/g/n-HT20		802.11n-HT40	
Channel Number	Frequency (MHz)	Channel Number	Frequency (MHz)
1	2412	3	2422
2	2417	4	2427
3	2422	5	2432
4	2427	6	2437
5	2432	7	2442
6	2437	8	2447
7	2442	9	2452
8	2447	10	2457
9	2452	11	2462
10	2457		
11	2462		
12	2467		
13	2472		

Channel List							
BLE							
Channel Number	Frequency (MHz)	Channel Number	Frequency (MHz)	Channel Number	Frequency (MHz)	Channel Number	Frequency (MHz)
37	2402	09	2422	18	2442	28	2462
00	2404	10	2424	19	2444	29	2464
01	2406	38	2426	20	2446	30	2466
02	2408	11	2428	21	2448	31	2468
03	2410	12	2430	22	2450	32	2470
04	2412	13	2432	23	2452	33	2472
05	2414	14	2434	24	2454	34	2474
06	2416	15	2436	25	2456	35	2476
07	2418	16	2438	26	2458	36	2478
08	2420	17	2440	27	2460	39	2480

RMS Output Power (dBm)				
Channel	802.11b	802.11g	802.11n-HT20	802.11n-HT40
1	19	17	16	---
2	19	19	17	
3	19	19	17	14
4	19	19	17	14.5
5	19	19	17	16
6	19	19	17	16
7	19	19	17	16
8	19	19	17	16
9	19	19	17	14
10	19	19	17	10.5
11	19	16.5	15	-5.5
12	15.5	10.5	9	---
13	7.5	-3.5	-7	

3.5. Descriptions of Key Components

3.5.1. For the All Component Lists

Item	Supplier	Model / Type	Character
System	Microsoft	Win10 Home	---
Main Board	LG	14/15Z980 Main B/D PCB	(without Thunderbolt) Manufacturer: (1) Elec & Eltek Company (MCO) Limited (2) Hannstar Board Tech(Jiang Yin) Corp.,Ltd. (3) LG Innotek Co., Ltd.
	LG	14/15Z980 Main B/D PCB	(with Thunderbolt) Manufacturer: (1) Elec & Eltek Company (MCO) Limited (2) Hannstar Board Tech(Jiang Yin) Corp.,Ltd. (3) LG Innotek Co., Ltd.
SUB Board	LG	14Z980 WLAN SUB B/D	(without Finger Print) Manufacturer: (1) Hannstar Board Tech(Jiang Yin) Corp.,Ltd. (2) HYUNWOO
	LG	14Z980 WLAN SUB B/D	(with Finger Print) Manufacturer: (1) Hannstar Board Tech(Jiang Yin) Corp.,Ltd. (2) HYUNWOO
CPU (Socket: BGA1356)	Intel	i7-8550U	1.8GHz, up to 4.0GHz
	Intel	i5-8250U	1.6GHz, up to 3.4GHz
14" LCD Panel	LG Display	LP140WF5-SPG2	Resolution: 1920 x 1080, 60Hz FHD IPSW/ Touch (AIT Including touch)
	LG Display	LP140WF7-SPG1	Resolution: 1920 x 1080, 60Hz FHD IPS (Normal Non touch)
Storage (SSD)	SK hynix	HFS256G39TND-N210A BB	256GB (SATA)
	SK hynix	HFS512G39TND-N210A BB	512GB (SATA)
	Samsung	MZNLN256MHQ	256GB (SATA)
	Samsung	MZNLN512HMP	512GB (SATA)
Memory (RAM) (On Board)	Samsung	K4A8G165WB-BCRC	8Gbit DDR4 2400MHz (On Board) *4ea
	SK hynix	H5ANAG6NAMA UHC	4Gbit DDR4 2400MHz (On Board) *4ea
Memory (RAM)	Samsung	M471A5244CB0-CRC	4Gbit DDR4 2400MHz (On Card)
Battery Pack	LG	LBS1224E	DC 7.7V, 72Wh, Typ 9450mAh

Item	Supplier	Model / Type	Character
WLAN Combo Card	Intel	8265D2W	802.11a/b/g/n/ac 2.4GHz/5GHz + BT 4.2 BLE
WLAN Combo Antenna	LG (INPAQ)	WA-F-LBLB-04-058	FPCB Type Main: Black, Aux: Gray
Keyboard	LG	SN3871	Black: BL, White: BL 1
Finger Print	SUNTEL	SFPC-L0016A(White)	---
		SFPC-L0016B(Black)	---
		Above model have the same circuit and hardware. The model SFPC-L0016B(Black) is tested in this report.	
Web Camera	Lite-On	7BF109N2	With two MIC
LAN Gender (Type C to LAN)	LG	80-5946-111 (White)	10/100 Megabit Ethernet
		80-5946-101 (Black)	Manufacturer: SUZHOU MEC ELECTRONICS
		Above model have the same circuit and hardware. The model 80-5946-101 (Black) is tested in this report.	
	LG	GD-08MF-36-WH-LP05 (White)	10/100 Megabit Ethernet
		GD-08MF-36-BK-LP06 (Black)	Manufacturer: ARIN TECH CO. LTD
		Above model have the same circuit and hardware. The model GD-08MF-36-BK-LP06 (Black) is tested in this report.	
Type C to LAN: Shielded, Undetached, 0.12m			
AC Adapter (65W)	LG (Lite-on)	PA-1650-43	I/P: AC 100-240V, 50/60Hz, 1.6A, O/P: DC 19V, 3.42A
	DC Power Cord: Non-Shielded, Undetached, 1.8m, Bonded a ferrite core AC Power Cord: Non-Shielded, Detached, 1.0m (3C)		

Remark: For more detailed features description, please refer to the manufacturer's specifications or the user manual.

3.5.2. The EUT collocates with following worst components, which are used to establish a basic configuration of system during test:

SKU		#1
Main Board	LG, 14/15Z980 Main B/D PCB (with Thunderbolt)	V
SUB Board	LG, 14Z980 WLAN SUB B/D (with Finger Print)	V
CPU	Intel, i7-8550U	V
14" LCD Panel	LG Display, LP140WF5-SPG2/(AIT Including touch)	V
Storage (SSD)	512GB	V
Memory (RAM)	8Gbit (On Board)	V
Battery Pack	LG, LBS1224E	V
WLAN Combo Card	Intel, 8265D2W	V
WLAN Combo Antenna	LG (INPAQ), WA-F-LBLB-04-058	V
Keyboard	LG, SN3871	V
Finger Print	SUNTEL, SFPC-L0016B(Black)	V
Web Camera	Lite-On, 7BF109N2	V
AC Adapter	LG (Lite-on), PA-1650-43	V
LAN Gender (Type C to LAN)	LG, GD-08MF-36-BK-LP06 (Black), 100Mbps	V

3.6. Data Rate Relative to Output Power

802.11b			
Channel	Modulation	Date Rate(Mbps)	Power(dBm)
1	DBPSK	1	18.86
1	DQPSK	2	18.73
1	CCK	5.5	18.69
1	CCK	11	18.65

802.11g			
Channel	Modulation	Date Rate(Mbps)	Power(dBm)
1	BPSK	6	16.89
1	BPSK	9	16.85
1	QPSK	12	16.81
1	QPSK	18	16.78
1	16-QAM	24	16.75
1	16-QAM	36	16.61
1	64-QAM	48	16.57
1	64-QAM	54	16.53

802.11n-HT20				802.11n-HT40			
Channel	Modulation	Date Rate (Mbps)	Power (dBm)	Channel	Modulation	Date Rate (Mbps)	Power (dBm)
1	BPSK	MCS8	19.15	3	BPSK	MCS8	17.10
1	QPSK	MCS9	19.08	3	QPSK	MCS9	17.02
1	QPSK	MCS10	19.02	3	QPSK	MCS10	16.95
1	16-QAM	MCS11	18.98	3	16-QAM	MCS11	16.87
1	16-QAM	MCS12	18.93	3	16-QAM	MCS12	16.73
1	64-QAM	MCS13	18.85	3	64-QAM	MCS13	16.62
1	64-QAM	MCS14	18.80	3	64-QAM	MCS14	16.57
1	64-QAM	MCS15	17.88	3	64-QAM	MCS15	16.44

BLE			
Channel	Modulation	Date Rate(Mbps)	Power(dBm)
0	GFSK	1	2.44

Note: Above results are assessed in peak power..


3.7. Test Configuration

Mode	Duty Cycle (x)	T (ms)	Duty Cycle Factor (dB)
802.11b	1.00	12.25	0
802.11g	1.00	2.040	0
802.11n-HT20	0.95	1.899	0.22
802.11n-HT40	0.96	0.927	0.17
BLE	0.86	2.130	0.71

Note: When duty cycle is less than 98% (0.98) that duty cycle factor $10\log(1/x)$ is needed to add in conducted test items measured in average detector.

Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City244, Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303



AC Conduction	
Test Case	Normal operation

Item	Mode	Data Rate	Test Channel
Radiated Test Case	Radiated Band Edge ^{Note1}	802.11b	1/2/10/11/12/13
		802.11g	1/2/10/11/12/13
		802.11n-HT20	1/2/10/11/12/13
		802.11n-HT40	3/4/8/9/10/11
		BLE	37/39
	Radiated Spurious Emission ^{Note1 & 2}	802.11b	1/6/11
		802.11g	1/6/11
		802.11n-HT20	1/6/11
		802.11n-HT40	3/6/9
		BLE	37/17/39
Conducted Test Case	6dB Bandwidth	802.11b	1/6/11/13
		802.11g	1/6/11/13
		802.11n-HT20	1/6/11/13
		802.11n-HT40	3/6/9/11
		BLE	37/17/39
	Peak Output Power	802.11b	1/2/6/10/11/12/13
		802.11g	1/2/6/10/11/12/13
		802.11n-HT20	1/2/6/10/11/12/13
		802.11n-HT40	3/4/6/10/11
		BLE	37/17/39
	Band Edge	802.11b	1/11/13
		802.11g	1/11/13
		802.11n-HT20	1/11/13
		802.11n-HT40	3/9/11
		BLE	37/39
	Spurious Emission	802.11b	1/11/13
		802.11g	1/11/13
		802.11n-HT20	1/11/13
		802.11n-HT40	3/9/11
		BLE	37/17/39
	Peak Power Spectral Density	802.11b	1/6/11/13
		802.11g	1/6/11/13
		802.11n-HT20	1/6/11/13
		802.11n-HT40	3/6/9/11
		BLE	37/17/39

Note 1: ☒ Mobile Device

☐ Portable Device, and 3 axis were assessed. The worst scenario for Radiated Spurious Emission as follow: ☐ Lie ☐ Side ☐ Stand

Note 2: Low, mid, and high channels were measured, only the worst channel of each modulation was presented in this report.

3.8. Tested Supporting System List

3.8.1. Support Peripheral Unit


No.	Product	Brand	Model No.	Serial No.	Approval
1.	LCD Monitor	ASUS	VE228	N/A	FCC By DoC
2.	USB Mouse	Lenovo	45J4886	N/A	FCC By DoC
3.	Earphone	APPLE	N/A	N/A	FCC By DoC

3.8.2. Cable Lists


No.	Cable Description Of The Above Support Units
1.	HDMI Cable: Shielded, Detachable, 1.8m AC Power Cord: Unshielded, Detachable, 1.8m
2.	USB Cable: Unshielded, Undetachable, 1.8m
3.	Earphone Cable: Unshielded, Undetachable, 2.0m

3.9. Setup Configuration

3.9.1. EUT Configuration for Power Line & Radiated Emission



3.9.2. EUT Configuration for RF Conducted Test Items



3.10. Operating Condition of EUT

Test program “DRTU” is used for enabling EUT BT or WLAN function under continues transmitting and choosing data rate/ channel.

3.11. Description of Test Facility

Name of Test Firm	Audix Technology Corporation / EMC Department No. 53-11, Dingfu, Linkou Dist., New Taipei City 244, Taiwan Tel: +886-2-26092133 Fax: +886-2-26099303 Website : www.audixtech.com Contact e-mail: attemc_report@audixtech.com
Accreditations	The laboratory is accredited by following organizations under ISO/IEC 17025:2005 (1) NVLAP(USA) NVLAP Lab Code 200077-0 (2) TAF(Taiwan) No. 1724 (3) FCC OET Designation No. TW1004 & TW1090 & TW1724
Test Facilities	(1) No. 7 Shielding Room (2) Semi-Anechoic Chamber (IC Test Site Registration No.: 5183B-1) (3) Fully Anechoic Chamber (IC Test Site Registration No.: 5183B-4)

3.12. Measurement Uncertainty

Test Item	Frequency Range	Uncertainty
Conduction Test	150kHz~30MHz	±3.50dB
Radiation Test (Distance: 3m)	30MHz~1000MHz	± 3.68dB
	Above 1GHz	± 5.82dB

Remark : Uncertainty = $ku_c(y)$

Test Item	Uncertainty
6dB Bandwidth	± 0.05kHz
Maximum peak output power	± 0.33dB
Power spectral density	± 0.13dB
Conducted Emission Limitations	± 0.13dB

4. MEASUREMENT EQUIPMENT LIST

4.1. Conducted Emission Measurement

Item	Type	Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Interval
1.	Test Receiver	R&S	ESCI	101276	2017. 03. 23	1 Year
2.	A.M.N.	R&S	ESH2-Z5	100366	2017. 07. 20	1 Year
3.	L.I.S.N.	Kyoritsu	KNW-407	8-881-13	2016. 12. 28	1 Year
4.	Pulse Limiter	R&S	ESH3-Z2	101495	2017. 01. 16	1 Year
5.	Test Software	Audix	e3	V.120619C	N.C.R.	N.C.R.

4.2. Radiated Emission Measurement

Item	Type	Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Interval
1.	Spectrum Analyzer	Agilent	N9010A-526	MY53400071	2017. 09. 13	1 Year
2.	Spectrum Analyzer	Agilent	N9010A-526	MY52220368	2016. 12. 01	1 Year
3.	Test Receiver	R & S	ESCS30	100338	2017. 06. 19	1 Year
4.	Amplifier	HP	8447D	2944A06305	2017. 02. 16	1 Year
5.	Amplifier	Sonoma	310N	187161	2017. 06. 08	1 Year
6.	Bilog Antenna	CHASE	CBL6112D	33821	2017. 01. 21	1 Year
7.	Loop Antenna	R&S	HFH2-Z2	891847/27	2016. 12. 23	1 Year
8.	Double-Ridged Waveguide Horn	ETS-Lindgren	3117	00135902	2017. 03. 08	1 Year
9.	2.4GHz Notch Filter	K&L	7NSL10-244 1.5E130.5-00	1	2017. 07. 26	1 Year
10.	3GHz Notch Filter	Microwave	H3G018G1	484798	2017. 08. 25	1 Year
11.	Test Software	Audix	e3	V.6.110601	N.C.R.	N.C.R.

4.3. RF Conducted Measurement

Item	Type	Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Due
1.	Spectrum Analyzer	Keysight	N9010B-544	MY55460198	2017. 04. 18	1 Year
2.	Power Meter	Anritsu	ML2495A	1145008	2017. 11. 03	1 Year
3.	Power Sensor	Anritsu	MA2411B	1126096	2017. 11. 03	1 Year


5. CONDUCTED EMISSION

5.1. Block Diagram of Test Setup

5.1.1. Block Diagram of EUT

Indicated as section 3.9

5.1.2. Shielded Room Setup Diagram



5.2. Conducted Emission Limit

Frequency	Conducted Limit	
	Quasi-Peak Level	Average Level
150kHz ~ 500kHz	66 ~ 56 dB μ V	56 ~ 46 dB μ V
500kHz ~ 5MHz	56 dB μ V	46 dB μ V
5MHz ~ 30MHz	60 dB μ V	50 dB μ V

Remark 1.: If the average limit is met when using a Quasi-Peak detector, the measurement using the average detector is not required.

2.: The lower limit applies to the band edges.

5.3. Test Procedure

- 5.3.1. To set up the EUT as indicated in ANSI C 63.10. The EUT was placed on the table which has 80 cm height to the ground and 40 cm distance to the conducting wall.
- 5.3.2. Power supplier of the EUT was connected to the AC mains through an Artificial Mains Network (A.M.N.).
- 5.3.3. The AC power supplies to all peripheral devices must be provided through line impedance stabilization network (L.I.S.N.)
- 5.3.4. Checking frequency range from 150 kHz to 30 MHz and record the emission which does not have 20 dB below limit.

5.4. Test Results

Please refer to Appendix A.


6. RADIATED EMISSION

6.1. Block Diagram of Test Setup


6.1.1. Block Diagram of EUT

Indicated as section 3.9


6.1.2. Setup Diagram for 9kHz-30MHz



6.1.3. Setup Diagram for 30-1000 MHz



6.1.4. Setup Diagram for above 1GHz



6.2. Radiated Emission Limits

In any 100kHz bandwidth outside the frequency band, the radio frequency power produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level. In addition, radiated emissions which fall in restricted bands, as defined in Section 15.205/RSS-Gen Section 8.10 table 6, must also comply with the radiated emission limits specified as below.

Frequency (MHz)	Distance (m)	Limits	
		dBμV/m	μV/m
0.009 - 0.490	300	67.6	2400/kHz
0.490 - 1.705	30	87.6	24000/kHz
1.705 - 30	30	29.5	30
30 - 88	3	40.0	100
88- 216	3	43.5	150
216- 960	3	46.0	200
Above 960	3	54.0	500
Above 1000	3	74.0 dBμV/m (Peak) 54.0 dBμV/m (Average)	

Remark : (1) $\text{dB}\mu\text{V/m} = 20 \log (\mu\text{V/m})$

(2) The tighter limit applies to the edge between two frequency bands.

(3) Distance refers to the distance in meters between the measuring instrument antenna and the closed point of any part of the device or system.

(4) Fundamental and emission fall within operation band are exempted from this section.

(5) Pursuant to ANSI C63.10: 6.6.4.3, if the maximized peak measured value complies with the average limit, then it is unnecessary to perform an average measurement.

6.3. Test Procedure

Frequency Range 9kHz~30MHz:

The EUT setup on the turn table which has 0.8 m height to the ground. The turn table rotated 360 degrees and antenna fixed to 1 m to find the maximum emission level. In order to find the maximum emission, all of the interface cables were manipulated according to ANSI C63.10-2013 regulation.

- (1) RBW = 9kHz with peak and average detector.
- (2) Detector: average and peak (9kHz-490kHz)
Q.P. (490kHz-30MHz)

Frequency Range 30MHz ~ 25GHz:

The EUT setup on the turn find table which has 80 cm (for 30-1000 MHz) and 1.5m (for above 1GHz) height to the ground. The turn table rotated 360 degrees and antenna varied from 1 m to 4 m to find the maximum emission level. Both horizontal and vertical polarization are required. In order to find the maximum emission, all of the interface cables were manipulated according to ANSI C63.10-2013 regulation.

Frequency below 1 GHz:

Spectrum Analyzer is used for pre-testing with following setting:

- (1)RBW = 120KHz
- (2)VBW $\geq 3 \times$ RBW.
- (3)Detector = Peak.
- (4)Sweep time = auto.
- (5)Trace mode = max hold.
- (6)Allow sweeps to continue until the trace stabilizes.
- (7)When peak-detected value is lower than limit that the measurement using the Q.P. detector is not required. Otherwise using Q.P. for finally measurement.

Frequency above 1GHz to 10th harmonic (up to 25 GHz):

Peak Detector:

- (1)RBW = 1MHz
- (2)VBW $\geq 3 \times$ RBW.
- (3)Detector = Peak.
- (4)Sweep time = auto.
- (5)Trace mode = max hold.
- (6)Allow sweeps to continue until the trace stabilizes.
- (7)When peak-detected value is lower than limit that the measurement using the average detector is not required. Otherwise using average detector for finally measurement.

Average Detector:**■ Option 1:**

(1)RBW = 1MHz

(2)VBW $\geq 1/T$.

Modulation Type	T (ms)	1/ T (kHz)	VBW Setting (kHz)
BLE	12.25	0.081633	2.5kHz
802.11b	2.040	0.490196	10Hz
802.11g	1.899	0.526593	10Hz
802.11n-HT20	0.927	1.078749	1kHz
802.11n-HT40	2.130	0.469484	2kHz

N/A: 1/ T is not implemented when duty cycle presented in section 3.7 is $\geq 98\%$.

(1)Detector = Peak.

(2)Sweep time = auto.

(3)Trace mode = max hold.

(4)Allow sweeps to continue until the trace stabilizes.

□ Option 2:


Average Emission Level= Peak Emission Level+ D.C.C.F.

6.4. Measurement Result Explanation**■**Peak Emission Level=Antenna Factor + Cable Loss + Meter Reading**■**Average Emission Level l=Antenna Factor + Cable Loss + Meter Reading**□**Average Emission Level= Peak Emission Level+ DCCFDuty Cycle Correction Factor (DCCF)= $20\log(TX_{on}/TX_{on+off})$ presented in section 3.7**□**ERP= Peak Emission Level-95.2dB-2.14dB**6.5. Test Results**

Please refer to Appendix A.

7. 6dB BANDWIDTH

7.1. Block Diagram of Test Setup



7.2. Specification Limits

The minimum 6dB bandwidth shall be at least 500kHz.

7.3. Test Procedure

Following measurement procedure is reference to KDB 558074 D01 DTS Meas Guidance v04:

- (1) Set RBW = 100 kHz.
- (2) Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
- (3) Detector = Peak.
- (4) Trace mode = max hold.
- (5) Sweep = auto couple.
- (6) Allow the trace to stabilize.
- (7) Setting channel bandwidth function x dB to -6 dB to record the final bandwidth.

7.4. Test Results

Please refer to Appendix A

8. MAXIMUM PEAK OUTPUT POWER

8.1. Block Diagram of Test Setup



8.2. Specification Limits

The Limits of maximum Peak Output Power for digital modulation in 2400-2483.5MHz is : 1Watt. (30dBm), and E.I.R.P.: 4Watt (36dBm)

8.3. Test Procedure

Following measurement procedure is reference to KDB 558074 D01 DTS Meas Guidance v04:

■ PKPM1 Peak power meter method:

EUT is connected to power sensor and record the maximum output power.

☐ Method AVGPM (Measurement using an RF average power meter):

EUT is connected to power sensor and record the maximum average output power and duty cycle factor is added when duty cycle presented in section 3.7 is < 98%.

☐ Method AVGSA-2 (Spectrum channel power)


- (1) Set span to at least 1.5 times the OBW
- (2) Set RBW = 1 -5% of OBW
- (3) Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
- (4) Detector = RMS.
- (5) Trace mode = trace average at least 100 traces
- (6) Sweep = auto couple.
- (7) Compute power by integrating the spectrum across the OBW of the signal using the instrument's band power measurement function with band limits set equal to the OBW band edges.
- (8) Duty cycle factor is added when duty cycle presented in section 3.7 is < 98%.

8.4. Test Results

Please refer to Appendix A

9. EMISSION LIMITATIONS

9.1. Block Diagram of Test Setup



9.2. Specification Limits

In any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, that the required attenuation shall be 30 dB instead of 20 dB.

Attenuation below the general limits specified in Section 15.209(a)/RSS-Gen Section 8.9 table 4 is not required. In addition, radiated emissions which fall in restricted bands, as defined in Section 15.205(a)/RSS-Gen Section 8.10 table 6, must also comply with the radiated emission limits specified in Section 15.209(a)/RSS-Gen Section 8.9 table 4 (See Section 15.205(c)).

9.3. Test Procedure

Following measurement procedure is reference to KDB 558074 D01 DTS Meas Guidance v04:

■ Reference Level

- (1) Set analyzer center frequency to DTS channel center frequency.
- (2) Set the span to 1.5 times the DTS bandwidth.
- (3) Set the RBW to: 100 kHz.
- (4) Set the VBW $\geq 3 \times$ RBW.
- (5) Detector = peak.
- (6) Sweep time = auto couple.
- (7) Trace mode = max hold.
- (8) Allow trace to fully stabilize to find the max PSD as reference level.

■ Emission Level Measurement


- (1) Set analyzer center frequency to DTS channel center frequency.
- (2) Set the span to 1.5 times the DTS bandwidth.
- (3) Set the RBW to: 100 kHz.
- (4) Set the VBW $\geq 3 \times$ RBW.
- (5) Detector = peak.
- (6) Sweep time = auto couple.
- (7) Trace mode = max hold.
- (8) Allow trace to fully stabilize to find the max level.

9.4. Test Results

Please refer to Appendix A

10. POWER SPECTRAL DENSITY

10.1. Block Diagram of Test Setup



10.2. Specification Limits

The peak power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3kHz band.

10.3. Test Procedure

Following measurement procedure is reference to KDB 558074 D01 DTS Meas Guidance v04:

☒ Method PKPSD (peak PSD)

- (1) Set analyzer center frequency to DTS channel center frequency.
- (2) Set the span to 1.5 times the DTS bandwidth.
- (3) Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
- (4) Set the VBW $\geq 3 \times \text{RBW}$.
- (5) Detector = peak.
- (6) Sweep time = auto couple.
- (7) Trace mode = max hold.
- (8) Allow trace to fully stabilize.
- (9) Use the peak marker function to determine the maximum amplitude level.
- (10) If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

☐ Method AVGPSD-2

- (1) Using peak PSD procedure step 1 to step 4.
- (2) Detector = RMS detector
- (3) Sweep time = auto couple
- (4) Trace mode = trace averaging over a minimum of 100 traces
- (5) Use the peak marker function to determine the maximum amplitude level.
- (6) Duty cycle factor is added when duty cycle presented in section 3.7 < 98%.
- (7) If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

10.4. Test Results

Please refer to Appendix A

11.DEVIATION TO TEST SPECIFICATIONS

【NONE】