

FCC 15.247 & RSS-247 2.4 GHz Test Report

for

LG Electronics Inc.

**222, LG-ro Jinwi-myeon, Pyeongtaek-Si, Gyeonggi-Do,
451-713, Korea**

Product Name : Notebook Computer
Model Name : (1)15Z90N (2)15ZB90N
(3)15ZD90N (4)15ZG90N
(5)15ZC90N
Brand : LG
FCC ID : BEJNT-15Z90N
IC : 2703H-15Z90N

Prepared by: : AUDIX Technology Corporation,
EMC Department



The test report is based on a single evaluation of one sample of the above-mentioned products. It does not imply an assessment of the whole production and does not permit the use of the test lab logo. The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S. Government.

TABLE OF CONTENTS

Description	Page
TEST REPORT CERTIFICATION.....	4
1. REVISION RECORD OF TEST REPORT	5
2. SUMMARY OF TEST RESULTS	6
3. GENERAL INFORMATION	7
3.1. Description of Application	7
3.2. Description of EUT	8
3.3. Antenna Information	9
3.4. EUT Specifications Assessed in Current Report	12
3.5. Descriptions of Key Components	14
3.6. Test Configuration	16
3.7. Tested Supporting System List	22
3.8. Setup Configuration	22
3.9. Operating Condition of EUT	22
3.10. Description of Test Facility	23
3.11. Measurement Uncertainty	24
4. MEASUREMENT EQUIPMENT LIST	26
4.1. Conducted Emission Measurement	26
4.2. Radiated Emission Measurement	27
4.3. RF Conducted Measurement	27
5. CONDUCTED EMISSION	28
5.1. Block Diagram of Test Setup	28
5.2. Conducted Emission Limit	28
5.3. Test Procedure	28
5.4. Test Results	28
6. RADIATED EMISSION	29
6.1. Block Diagram of Test Setup	29
6.2. Radiated Emission Limits	30
6.3. Test Procedure	31
6.4. Measurement Result Explanation	32
6.5. Test Results	32
7. 6dB/OCCUPIED BANDWIDTH	33
7.1. Block Diagram of Test Setup	33
7.2. Specification Limits	33
7.3. Test Procedure	33
7.4. Test Results	33
8. MAXIMUM PEAK OUTPUT POWER	34
8.1. Block Diagram of Test Setup	34
8.2. Specification Limits	34
8.3. Test Procedure	35
8.4. Test Results	35
9. EMISSION LIMITATIONS	36
9.1. Block Diagram of Test Setup	36



Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City 244, Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303

9.2. Specification Limits	36
9.3. Test Procedure	36
9.4. Test Results	37
10. POWER SPECTRAL DENSITY	38
10.1. Block Diagram of Test Setup	38
10.2. Specification Limits	38
10.3. Test Procedure	38
10.4. Test Results	38
11. DEVIATION TO TEST SPECIFICATIONS	39

APPENDIX A TEST DATA AND PLOTS

APPENDIX B TEST PHOTOGRAPHS

TEST REPORT CERTIFICATION

Applicant : LG Electronics Inc.
Manufacturer : LG Electronics Inc.
Factory #1 : LG Electronics Nanjing New Technology Co., Ltd.
Factory #2 : SEO HEUNG ELECTRONICS CO LTD
EUT Description
(1) Product : Notebook Computer
(2) Model : (1)15Z90N (2)15ZB90N (3)15ZD90N (4)15ZG90N (5)15ZC90N
(3) Brand : LG
(4) Power Supply: DC 19V, 2.53A

Applicable Standards:

47 CFR FCC Part 15 Subpart C
RSS-Gen (Issue 5), April 2018
RSS-247 (Issue 2), February 2017
ANSI C63.10:2013

Audix Technology Corp. tested the equipment mentioned in accordance with the requirements set forth in the above standards. Test results indicate that the equipment tested is capable of demonstrating compliance with the requirements as documented within this report.

Audix Technology Corp. does not assume responsibility for any conclusions and generalizations drawn from the test results with regard to other specimens and samples.


Date of Report: 2019. 10. 04

Reviewed by:



(Annie Yu/Administrator)

Approved by:



(Johnny Hsueh/Section Manager)



Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City 244, Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303

1. REVISION RECORD OF TEST REPORT

Edition No	Issued Data	Revision Summary	Report Number
0	2019. 10. 04	Original Report	EM-F190339

2. SUMMARY OF TEST RESULTS

Rule		Description	Results
FCC	IC		
15.207	RSS-Gen §8.8	Conducted Emission	PASS
15.247(d)/ 15.205	RSS-Gen §8.9 RSS-247 §5.5	Radiated Band Edge and Radiated Spurious Emission	PASS
15.247(a)(2)	RSS-247 §5.2(1)	6dB/Occupied Bandwidth	PASS
15.247(b)(3)	RSS-247 §5.4(4)	Maximum Peak Output Power	PASS
15.247(d)	RSS-247 §5.5	Conducted Band Edges and Conducted Spurious Emission	PASS
15.247 (e)	RSS-247 §5.2(2)	Peak Power Spectral Density	PASS
15.203	RSS-Gen §8.3	Antenna Requirement	Compliance
Note: The uncertainties value is not used in determining the result.			

3. GENERAL INFORMATION

3.1. Description of Application

Applicant	LG Electronics Inc. 222, LG-ro Jinwi-myeon, Pyeongtaek-Si, Gyeonggi-Do, 451-713, Korea
Manufacturer	LG Electronics Inc. 222, LG-ro Jinwi-myeon, Pyeongtaek-Si, Gyeonggi-Do, 451-713, Korea
Factory #1	LG Electronics Nanjing New Technology Co., Ltd. No.346,Yaoxin Road, Economic & Technical Development Zone, Nanjing, China.
Factory #2	SEO HEUNG ELECTRONICS CO LTD 55 Asan valley Seo-ro, Dunpo-myeon, Asan-si, Chungcheongnam-do, 31409 Korea
Product	Notebook Computer The product has two colors (Dark Silver and White).
Model	(1)15Z90N (2)15ZB90N (3)15ZD90N (4)15ZG90N (5)15ZC90N The difference between all models is different in the sales customers.
Brand	LG

3.2. Description of EUT

Test Model	15Z90N																												
Serial Number	N/A																												
Power Rating	DC 19V, 2.53A																												
RF Features	WLAN: 802.11 a/b/g/n/ac/ax Bluetooth: BT and BLE (BT 5.0)																												
Transmit Type	<table><thead><tr><th colspan="2">2.4 GHz</th></tr></thead><tbody><tr><td>802.11b</td><td>1T1R</td></tr><tr><td>802.11g</td><td>1T1R</td></tr><tr><td>802.11n-HT20</td><td>2T2R</td></tr><tr><td>802.11n-HT40</td><td>2T2R</td></tr><tr><td>802.11ax-HE20</td><td>2T2R</td></tr><tr><td>802.11ax-HE40</td><td>2T2R</td></tr><tr><td>BT/BLE</td><td>1T1R</td></tr></tbody></table> <table><thead><tr><th colspan="2">UNII Bands</th></tr></thead><tbody><tr><td>802.11a</td><td>1T1R</td></tr><tr><td>802.11n-HT20/802.11ac-VHT20/802.11ax-HE20</td><td>2T2R</td></tr><tr><td>802.11n-HT40/802.11ac-VHT40/802.11ax-HE40</td><td>2T2R</td></tr><tr><td>802.11ac-VHT80/802.11ax-HE80</td><td>2T2R</td></tr><tr><td>802.11ac-VHT160/802.11ax-HE160</td><td>2T2R</td></tr></tbody></table>	2.4 GHz		802.11b	1T1R	802.11g	1T1R	802.11n-HT20	2T2R	802.11n-HT40	2T2R	802.11ax-HE20	2T2R	802.11ax-HE40	2T2R	BT/BLE	1T1R	UNII Bands		802.11a	1T1R	802.11n-HT20/802.11ac-VHT20/802.11ax-HE20	2T2R	802.11n-HT40/802.11ac-VHT40/802.11ax-HE40	2T2R	802.11ac-VHT80/802.11ax-HE80	2T2R	802.11ac-VHT160/802.11ax-HE160	2T2R
2.4 GHz																													
802.11b	1T1R																												
802.11g	1T1R																												
802.11n-HT20	2T2R																												
802.11n-HT40	2T2R																												
802.11ax-HE20	2T2R																												
802.11ax-HE40	2T2R																												
BT/BLE	1T1R																												
UNII Bands																													
802.11a	1T1R																												
802.11n-HT20/802.11ac-VHT20/802.11ax-HE20	2T2R																												
802.11n-HT40/802.11ac-VHT40/802.11ax-HE40	2T2R																												
802.11ac-VHT80/802.11ax-HE80	2T2R																												
802.11ac-VHT160/802.11ax-HE160	2T2R																												
Software Version	N/A																												
Sample Status	Mass production																												
Date of Receipt	2019. 09. 16																												
Date of Test	2019. 09. 24 ~ 10. 01																												
Interface Ports of EUT	• One Micro SD Card Slot • One Earphone Port • Three USB 3.0 Ports • One USB Type C Port • One HDMI Port • One DC Input Port																												
Accessories Supplied	• AC Adapter • LAN Gender																												

3.3. Antenna Information

2.4G Antenna					
No.	Antenna Part Number	Manufacture	Antenna Type	Frequency (MHz)	Max Gain (dBi)
1.	WA-P-LBLB-04-070 (Main)	INPAQ	Mono-pole	2400	2.78
				2410	2.30
				2420	2.22
				2430	2.38
				2440	2.38
				2450	2.75
				2460	3.23
				2470	3.63
				2480	3.80
				2490	3.98
				2500	4.16
2.	WA-P-LBLB-04-070 (AUX)	INPAQ	Mono-pole	2400	3.65
				2410	3.22
				2420	3.42
				2430	3.83
				2440	4.01
				2450	4.25
				2460	4.41
				2470	4.54
				2480	4.49
				2490	4.39
				2500	4.29
3.	L1LRF003-CS-H (Main)	LUXSHARE-ICT	Mono-pole	2400	4.4
				2450	4.4
				2500	4.2
4.	L1LRF003-CS-H (AUX)	LUXSHARE-ICT	Mono-pole	2400	4.4
				2450	4.5
				2500	4.1

5G Antenna					
No.	Antenna Part Number	Manufacture	Antenna Type	Frequency (MHz)	Max Gain (dBi)
1.	WA-P-LBLB-04-070 (Main)	INPAQ	Mono-pole	5100	1.54
				5150	1.62
				5200	1.37
				5250	1.76
				5300	2.70
				5350	3.52
				5400	3.37
				5450	3.30
				5500	2.39
				5550	2.13
				5600	1.82
				5650	3.25
				5700	4.30
				5750	5.27
				5800	4.14
2.	WA-P-LBLB-04-070 (AUX)	INPAQ	Mono-pole	5100	3.85
				5150	4.14
				5200	3.89
				5250	3.94
				5300	4.27
				5350	3.79
				5400	3.80
				5450	3.71
				5500	3.28
				5550	4.00
				5600	3.44
				5650	3.41
				5700	3.02
				5750	1.59
				5800	1.63

5G Antenna					
No.	Antenna Part Number	Manufacture	Antenna Type	Frequency (MHz)	Max Gain (dBi)
3.	L1LRF003-CS-H (Main)	LUXSHARE-ICT	Mono-pole	5150	3.0
				5250	4.3
				5350	3.3
				5470	4.6
				5600	3.7
				5725	4.3
				5785	4.2
				5800	4.2
				5850	4.1
4.	L1LRF003-CS-H (AUX)	LUXSHARE-ICT	Mono-pole	5150	3.6
				5250	4.0
				5350	2.8
				5470	3.3
				5600	3.0
				5725	3.0
				5785	2.7
				5800	2.2
				5850	2.5

3.4. EUT Specifications Assessed in Current Report

Mode	Fundamental Range (MHz)	Channel Number	Modulation	Data Rate (Mbps)
802.11b	2412-2472	13	DSSS (DBPSK/DQPSK/CCK)	Up to 11
802.11g		13	OFDM (BPSK/QPSK/16QAM/64QAM)	Up to 54
802.11n-HT20				Up to 144.4
802.11n-HT40	2422-2462	9	OFDM (BPSK/QPSK/16QAM/64QAM)	Up to 300
802.11ax-HE20	2412-2472	13	OFDMA (BPSK/ QPSK/ 16QAM/ 64QAM/ 256QAM/1024QAM)	Up to 144.4
802.11ax-HE40	2422-2462	9		Up to 300
BLE	2402-2480	40	GFSK (1M, 2M, PHY Coded S8, PHY Coded S2)	2

Channel List			
802.11 b/g/n-HT20/ax-HE20		802.11n-HT40/ax-HE40	
Channel Number	Frequency (MHz)	Channel Number	Frequency (MHz)
1	2412	3	2422
2	2417	4	2427
3	2422	5	2432
4	2427	6	2437
5	2432	7	2442
6	2437	8	2447
7	2442	9	2452
8	2447	10	2457
9	2452	11	2462
10	2457	---	
11	2462		
12	2467		
13	2472		

Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City 244, Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303

Channel List							
BLE							
Channel Number	Frequency (MHz)	Channel Number	Frequency (MHz)	Channel Number	Frequency (MHz)	Channel Number	Frequency (MHz)
37	2402	09	2422	18	2442	28	2462
00	2404	10	2424	19	2444	29	2464
01	2406	38	2426	20	2446	30	2466
02	2408	11	2428	21	2448	31	2468
03	2410	12	2430	22	2450	32	2470
04	2412	13	2432	23	2452	33	2472
05	2414	14	2434	24	2454	34	2474
06	2416	15	2436	25	2456	35	2476
07	2418	16	2438	26	2458	36	2478
08	2420	17	2440	27	2460	39	2480

RMS Output Power (dBm)						
Channel	802.11b	802.11g	802.11n-HT20	802.11ax-HE20	802.11n-HT40	802.11ax-HE40
1	19.35	16.91	17.13	17.03	---	---
2	19.96	17.94	18.43	18.26		
3	20.01	18.02	18.38	18.28	16.83	16.69
4	19.98	17.99	18.41	18.31	15.78	15.56
5	19.99	17.92	18.43	18.34	15.83	15.64
6	20.1	18.06	18.48	18.35	15.74	15.52
7	20.04	19.74	20.15	20.05	17.63	17.46
8	20.00	18.24	18.68	18.54	17.77	17.58
9	19.98	18.18	18.64	18.52	16.19	15.99
10	20.02	18.21	18.60	18.49	12.49	12.27
11	19.08	17.47	17.74	17.64	4.01	3.63
12	18.18	14.79	14.91	14.80	---	---
13	13.08	1.52	2.58	2.5		

3.5. Descriptions of Key Components

3.5.1. For the All Component Lists

Item	Supplier	Model / Type	Character
System	Microsoft	Win10 Home	---
Main Board	LG	1XZ90N MAIN B/D PCB	Manufacturer: #1 Hannstar Board Tech(Jiang Yin)Corp.,Ltd. #2 Elec & Eltek Company (MCO) Limited
WLAN SUB Board	LG	15Z90N WLAN SUB B/D	Manufacturer: #1 Hannstar Board Tech(Jiang Yin)Corp.,Ltd. #2 Elec & Eltek Company (MCO) Limited
CPU (Socket: FCBGA1526)	Intel	i5-1035G7	1.2GHz, up to 3.7GHz
	Intel	i7-1065G7	1.3GHz, up to 3.9GHz
15.6" LCD Panel	LG Display	LP156WFA(SP)(G1)	Resolution: 1920 x 1080, 60Hz FHD IPS Touch (Touch)
	LG Display	LP156WFC(SP)(Y1)	Resolution: 1920 x 1080, 60Hz FHD IPS (Normal Non touch)
Storage (SSD)	Samsung	MZ-VLB5120 (P/N MZVLB512HAJQ-00000)	512GB (M.2)
		MZ-VLB2560 (P/N MZVLB256HAHQ-00000)	256GB (M.2)
Memory (RAM)	Samsung	---	8GB DDR4(On Board)
	Samsung	---	8GB DDR4 3200MHz SODIMM (on Card)
	SK Hynix	---	8GB DDR4 3200MHz SODIMM (on Card)
Battery Pack	LG	LBV7227E	80Wh, DC 7.74V, 80Wh Typ 10336mAh
WLAN Combo Card	Intel	AX201D2W	WLAN and BT, 2x2 CNVi 1216 FCC ID: PD9AX201NG IC: 1000M-AX201NG NCC ID: CCAH18LP3410T5
WLAN Combo Antenna	LG (INPAQ)	WA-P-LBLB-04-070	PCB, Mono-pole Type Main: Black, Aux: Gray
	LG (LUXSHARE-ICT)	L1LRF003-CS-H	PCB, Mono-pole Typ Main: Black, Aux: Gray
Keyboard	TIC	KT01-18B9	P/N: KT01-18B9BS03USRA000 (White KBD)
		KT01-18B9	P/N: KT01-18B9AS03USRA000 (Black KBD)
	LITE ON	SN3870BL	P/N: SG-90930-XUA (White KBD)
		SN3870BL	P/N: SG-90920-XUA (Black KBD)

Item	Supplier	Model / Type	Character
Web Camera	Chicony	CKFIH2821005290LH	With two microphones
		CKFIH28-121005290LH	With One microphone
	Luxvisions	7BF109N2DC	With two microphones
		7BF109N2C	With One microphone
LAN Gender (Type C to LAN)	SUZHOU MEC ELECTRONICS	80-5946-200	(White) 10/100/1000 Megabit Ethernet
		80-5946-210	(Black) 10/100/1000 Megabit Ethernet
	Type C to LAN: Shielded, Undetached, 0.13m		
	SUZHOU MEC ELECTRONICS	80-5946-111	(White) 10/100Megabit Ethernet
		80-5946-101	(Black) 10/100 Megabit Ethernet
	Type C to LAN: Shielded, Undetached, 0.12m		
	ARIN TECH CO. LTD	GD-08MF-36-WH-LP10	(White) 10/100Megabit Ethernet
		GD-08MF-36-BK-LP11	(Black) 10/100 Megabit Ethernet
	Type C to LAN: Shielded, Undetached, 0.12m		
AC Adapter (48W)	LG (HONOR)	ADS-48MS-19-2 19048E	I/P: AC 100-240V, 50-60Hz, 1.5A, O/P: DC 19V, 2.53A
	DC Power Cord: Non-Shielded, Undetached, 1.5m		
	AC Power Cord: Non-Shielded, Detached, 1.0m (2C) (For Other Countries)		
	AC Power Cord: Non-Shielded, Detached, 1.55m (2C) (For US, Canada, Mexico)		

Remark: For more detailed features description, please refer to the manufacturer's specifications or the user manual.

3.5.2. The EUT collocates with following worst components, which are used to establish a basic configuration of system during test:

SKU (Mode) 1 ~ 2		1	2
Main Board	LG, 1XZ90N MAIN B/D PCB	V	V
WLAN SUB Board	LG, 15Z90N WLAN SUB B/D	V	V
CPU	Intel, i7-1065G7	V	
	Intel, i5-1035G7		V
15.6" LCD Panel	LG Display, LP156WFA(SP)(G1) (Touch)	V	
	LG Display, LP156WFC(SP)(Y1) (Normal Non touch)		V
Storage (SSD)	Samsung, 512GB *2	V	
	Samsung, 256GB *1		V
Memory (RAM)	Samsung, 8GB (On Board)	V	V
	Samsung, 8GB(On Card)	V	
	SK Hynix, 8GB (On Card)		V
Battery Pack	LG, LBV7227E	V	V
WLAN Combo Card	Intel, AX201D2W	V	V
WLAN Combo Antenna	LG (INPAQ), WA-P-LBLB-04-070	V	
	LG (LUXSHARE-ICT), L1LRF003-CS-H		V
Keyboard	TIC, KT01-18B9 (White KBD)	V	
	LITE ON, SN3870BL (White KBD)		V
Web Camera	Chicony, CKFIH2821005290LH	V	
	Luxvisions, 7BF109N2DC		V
LAN Gender	SUZHOU MEC ELECTRONICS, 80-5946-200	V	V
AC Adapter	LG (HONOR), ADS-48MS-19-2 19048E	V	V


3.6. Test Configuration

Mode	Duty Cycle (x)	T (ms)	Duty Cycle Factor (dB)
802.11b	1.00	8.35	N/A
802.11g	0.98	2.079	N/A
802.11n-HT20	0.99	3.97	N/A
802.11n-HT40	0.99	3.96	N/A
802.11ax-HE20	0.99	3.95	N/A
802.11ax-HE40	0.98	3.93	N/A
BLE	---	0.390	---

Note: When duty cycle is less than 98% (0.98) that duty cycle factor $10\log(1/x)$ is needed to add in conducted test items measured in average detector.



Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City 244, Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303



Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City 244, Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303



AC Conduction	
SKU #1	Normal operation
SKU #2	Normal operation

Item		SKU	Mode	Data Rate	Test Channel
Radiated Test Case	Radiated Band Edge ^{Note1}	#2	802.11b	1Mbps	1/2/10/11/12/13
			802.11g	6Mbps	1/2/10/11/12/13
			802.11n-HT20	MCS8	1/2/10/11/12/13
			802.11n-HT40	MCS8	3/4/8/9/10/11
			802.11ax-HE20	HE0	1/2/10/11/12/13
			802.11ax-HE40	HE0	3/4/8/9/10/11
			BLE	1Mbps	37/39
	Radiated Spurious Emission ^{Note1 & 2}	#2	802.11b	1Mbps	7
			802.11g	6Mbps	7
			802.11n-HT20	MCS8	7
			802.11n-HT40	MCS8	8
			802.11ax-HE20	HE0	7
			802.11ax-HE40	HE0	7
			BLE	1Mbps	37/17/39
		#1	802.11n-HT20	MCS8	7

Item		Antenna	Mode	RU Config	Test Channel
Radiated Test Case	Radiated Band Edge ^{Note1}	#2	802.11ax-HE20	26/0	1
				52/37	
				106/53	
				26/8	13
				52/40	
				106/54	
			802.11ax-HE40	242/61	3
				242/62	11

Item	Mode	Data Rate	Test Channel
Conducted Test Case	6dB/Occupied Bandwidth	802.11b	1Mbps
		802.11g	6Mbps
		802.11n-HT20	MCS8
		802.11n-HT40	MCS8
		802.11ax-HE20	HE0
		802.11ax-HE40	HE0
		BLE	1Mbps
	Peak Output Power	802.11b	1Mbps
		802.11g	6Mbps
		802.11n-HT20	MCS8
		802.11n-HT40	MCS8
		802.11ax-HE20	HE0
		802.11ax-HE40	HE0
		BLE	1Mbps
			2Mbps
			PHY Coded S2
			PHY Coded S8
	Band Edge	802.11b	1Mbps
		802.11g	6Mbps
		802.11n-HT20	MCS8
		802.11n-HT40	MCS8
		802.11ax-HE20	HE0
		802.11ax-HE40	HE0
		BLE	1Mbps
	Spurious Emission	802.11b	1Mbps
		802.11g	6Mbps
		802.11n-HT20	MCS8
		802.11n-HT40	MCS8
		802.11ax-HE20	HE0
		802.11ax-HE40	HE0
		BLE	1Mbps
	Peak Power Spectral Density	802.11b	1Mbps
		802.11g	6Mbps
		802.11n-HT20	MCS8
		802.11n-HT40	MCS8
		802.11ax-HE20	HE0
		802.11ax-HE40	HE0
		BLE	1Mbps

Item	Mode	RU Config	Test Channel
Conducted Test Case	6dB/Occupied Bandwidth	802.11ax-HE20	26/0
			52/37
			106/53
		802.11ax-HE40	26/8
			52/40
			106/54
	Peak Output Power	802.11ax-HE20	242/61
			242/62
			26/0
		802.11ax-HE40	52/37
			106/53
			26/8
	Peak Power Spectral Density	802.11ax-HE20	52/40
			106/54
		802.11ax-HE40	242/61
			242/62
			26/0
		802.11ax-HE20	52/37
			106/53
			26/8
		802.11ax-HE40	52/40
			106/54
			242/61
			242/62

Note 1: ☐ Mobile Device

☒ Portable Device, and 3 axis were assessed. The worst scenario for Radiated Spurious Emission as follow: ☒ Lie ☐ Side ☐ Stand

Note 2: Low, mid, and high channels were measured, only the worst channel of each modulation was presented in this report.

Note 3: Both of the antennas are the same type, and we presented the worst case in the report.

The max-gain condition with SISO (main port) and MIMO is SKU 2.

The MIMO is uncorrelated and supported SDM mode only.

Note 4: The modulation and bandwidth are similar for 802.11n mode for HT20/HT40 and 802.11ac mode for VHT20/VHT40, therefore investigated worst case to representative mode in the test report.

Note 5: The data rates were selected based on preliminary testing that identified those rate as the worst case for output power.

3.7. Tested Supporting System List

3.7.1. Support Peripheral Unit


No.	Product	Brand	Model No.	Serial No.	Approval
1.	LCD Monitor	LG	22LK330-DB	N/A	N/A
2.	USB Mouse	acer	MOBVUO	N/A	FCC By DoC
3.	Earphone	APPLE	N/A	N/A	N/A

3.7.2. Cable Lists


No.	Cable Description Of The Above Support Units
1.	HDMI Cable: Shielded, Detachable, 1.8m AC Power Cord: Unshielded, Detachable, 1.8m
2.	USB Cable: Unshielded, Undetachable, 1.8m
3.	Earphone Cable: Unshielded, Undetachable, 0.9m

3.8. Setup Configuration

3.8.1. EUT Configuration for Power Line & Radiated Emission



3.8.2. EUT Configuration for RF Conducted Test Items



3.9. Operating Condition of EUT

Test program “DRTU” is used for enabling EUT BT or WLAN function under continues transmitting and choosing data rate/ channel.

[Chain 0 is aux port (A Button in DRTU) Chain 1 is main port (B Button in DRTU)].

3.10. Description of Test Facility

Name of Test Firm	Audix Technology Corporation / EMC Department No. 53-11, Dingfu, Linkou Dist., New Taipei City 244, Taiwan Tel: +886-2-26092133 Fax: +886-2-26099303 Website : www.audixtech.com Contact e-mail: attemc_report@audixtech.com
Accreditations	The laboratory is accredited by following organizations under ISO/IEC 17025:2017 (1) NVLAP(USA) NVLAP Lab Code 200077-0 (2) TAF(Taiwan) No. 1724
Test Facilities	FCC OET Designation Number under APEC MRA by NCC is : TW1724 ISED CAB Identifier Number under APEC TEL MRA by NCC is TW1724 (1) No.8 Shielded Room (2) No.1 3m Semi Anechoic Chamber (3) Fully Anechoic Chamber

3.11.Measurement Uncertainty

Test Items/Facilities		Frequency Range	Uncertainty
Conduction Test		150kHz~30MHz	±3.50dB
Radiation Test	No.1 3m Semi Anechoic Chamber	30MHz-200MHz, 3m, Horizontal	±3.9dB
		200MHz-1000MHz, 3m, Horizontal	±4.3dB
		30MHz-200MHz, 3m, Vertical	±4.5dB
		200MHz-1000MHz, 3m, Vertical	±4.1dB
		1GHz-6GHz, 3m	±5.1dB
		6GHz-18GHz, 3m	±5.5dB
	No.3 3m Semi Anechoic Chamber	30MHz-200MHz, 3m, Horizontal	±4.7dB
		200MHz-1000MHz, 3m, Horizontal	±4.5dB
		30MHz-200MHz, 3m, Vertical	±4.3dB
		200MHz-1000MHz, 3m, Vertical	±4.1dB
	No.4 3m Semi Anechoic Chamber	30MHz-200MHz, 3m, Horizontal	±4.1dB
		200MHz-1000MHz, 3m, Horizontal	±4.4dB
		30MHz-200MHz, 3m, Vertical	±4.2dB
		200MHz-1000MHz, 3m, Vertical	±5.0dB
		1GHz-6GHz, 3m	±4.4dB
		6GHz-18GHz, 3m	±4.1dB
	No.5 3m Semi Anechoic Chamber	30MHz-200MHz, 3m, Horizontal	±4.0dB
		200MHz-1000MHz, 3m, Horizontal	±4.0dB
		30MHz-200MHz, 3m, Vertical	±4.2dB
		200MHz-1000MHz, 3m, Vertical	±4.4dB
		1GHz-6GHz, 3m	±4.3dB
		6GHz-18GHz, 3m	±4.6dB
	No.2 10m Semi Anechoic Chamber	30MHz-200MHz, 3m, Horizontal	±4.3dB
		200MHz-1000MHz, 3m, Horizontal	±4.3dB
		30MHz-200MHz, 3m, Vertical	±4.1dB
		200MHz-1000MHz, 3m, Vertical	±4.4dB
		1GHz-6GHz, 3m	±4.2dB
		6GHz-18GHz, 3m	±4.3dB
	Fully Anechoic Chamber	30MHz~1000MHz	±4.7dB
		1GHz~18GHz	±5.3dB

Remark : Uncertainty = $ku_c(y)$



Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City 244, Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303

Test Item	Uncertainty
6dB Bandwidth	$\pm 0.05\text{kHz}$
Maximum peak output power	$\pm 0.33\text{dB}$
Power spectral density	$\pm 0.13\text{dB}$
Conducted Emission Limitations	$\pm 0.13\text{dB}$

4. MEASUREMENT EQUIPMENT LIST

4.1. Conducted Emission Measurement

Item	Type	Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Interval
1.	Test Receiver	R&S	ESR3	101774	2019. 01. 23	1 Year
2.	A.M.N.	R&S	ENV4200	100169	2018. 11. 14	1 Year
3.	L.I.S.N.	Kyoritsu	KNW-407	8-855-9	2018. 12. 19	1 Year
4.	Pulse Limiter	R&S	ESH3-Z2	100354	2019. 01. 12	1 Year
5.	Digital Thermo-Hygro Meter	iMax	HTC-1	No.8 S/R	2019. 04. 20	1 Year
6.	Test Software	Audix	e3	V6.120619c	N.C.R.	N.C.R.

4.2. Radiated Emission Measurement

Item	Type	Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Interval
1.	Spectrum Analyzer	Agilent	N9010A-526	MY53400071	2019. 09. 11	1 Year
2.	Spectrum Analyzer	Keysight	N9010B-544	MY55460198	2019. 05. 06	1 Year
3.	Test Receiver	R & S	ESCS30	100338	2019. 06. 12	1 Year
4.	Amplifier	HP	8447D	2944A06305	2019. 01. 30	1 Year
5.	Amplifier	HP	8449B	3008A02678	2019. 03. 07	1 Year
6.	Amplifier	Keysight	83051A	MY53010042	2019. 08. 08	1 Year
7.	Bilog Antenna	TESEQ	CBL6112D	33821	2019. 01. 19	1 Year
8.	Loop Antenna	R&S	HFH2-Z2	891847/27	2017.12. 18	2 Years
9	Double-Ridged Waveguide Horn	ETS-Lindgren	3117	00135902	2019. 03. 13	1 Year
10.	Horn Antenna	COM-POWER	AH-840	101092	2019. 05. 14	1 Year
11.	2.4GHz Notch Filter	K&L	7NSL10-244 1.5/E130.5-O /O	1	2019. 07. 24	1 Year
12.	3GHz Notch Filter	Microwave	H3G018G1	484796	2019. 08. 21	1 Year
13.	Coaxial Cable	MIYAZAKI	5D2W	RE-11	2019. 02. 01	1 Year
14.	Coaxial Cable	HUBER+SUHNER	SUCOFLEX 104	RF CABLE-01	2019. 09. 20	1 Year
15.	Coaxial Cable	HUBER+SUHNER	SUCOFLEX 102	MY1493/2	2019. 09. 20	1 Year
16.	Digital Thermo-Hygro Meter	iMax	HTC-1	No.1 3m A/C	2019. 04. 20	1 Year
17.	Digital Thermo-Hygro Meter	EVERY DAY	E-512	RF-02	2019. 04. 20	1 Year
18.	Test Software	Audix	e3	V6.120619c	N.C.R.	N.C.R.
19.	Test Software	Audix	e3	V6.110601	N.C.R.	N.C.R.

4.3. RF Conducted Measurement

Item	Type	Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Interval
1.	Spectrum Analyzer	Keysight	N9020B-544	MY57120357	2019. 01. 17	1 Year
2.	Power Meter	Anritsu	ML2495A	1145008	2018. 11. 07	1 Year
3.	Power Sensor	Anritsu	MA2411B	1126096	2018. 11. 07	1 Year
4.	Digital Thermo-Hygro Meter	Shenzhen Datronn Electronics	KT-905	RF	2019. 04. 20	1 Year


5. CONDUCTED EMISSION

5.1. Block Diagram of Test Setup

5.1.1. Block Diagram of EUT

Indicated as section 3.8

5.1.2. Shielded Room Setup Diagram



5.2. Conducted Emission Limit

Frequency	Conducted Limit	
	Quasi-Peak Level	Average Level
150kHz ~ 500kHz	66 ~ 56 dBμV	56 ~ 46 dBμV
500kHz ~ 5MHz	56 dBμV	46 dBμV
5MHz ~ 30MHz	60 dBμV	50 dBμV

Remark 1.: If the average limit is met when using a Quasi-Peak detector, the measurement using the average detector is not required.

2.: The lower limit applies to the band edges.

5.3. Test Procedure

- 5.3.1. To set up the EUT as indicated in ANSI C 63.10. The EUT was placed on the table which has 80 cm height to the ground and 40 cm distance to the conducting wall.
- 5.3.2. Power supplier of the EUT was connected to the AC mains through an Artificial Mains Network (A.M.N.).
- 5.3.3. The AC power supplies to all peripheral devices must be provided through line impedance stabilization network (L.I.S.N.)
- 5.3.4. Checking frequency range from 150 kHz to 30 MHz and record the emission which does not have 20 dB below limit.

5.4. Test Results

Please refer to Appendix A.


6. RADIATED EMISSION

6.1. Block Diagram of Test Setup


6.1.1. Block Diagram of EUT

Indicated as section 3.8


6.1.2. Setup Diagram for 9kHz-30MHz



6.1.3. Setup Diagram for 30-1000 MHz



6.1.4. Setup Diagram for above 1GHz



6.2. Radiated Emission Limits

In any 100kHz bandwidth outside the frequency band, the radio frequency power produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level. In addition, radiated emissions which fall in restricted bands, as defined in Section 15.205/RSS-Gen Section 8.10 table 6, must also comply with the radiated emission limits specified as below.

Frequency (MHz)	Distance (m)	Limits	
		dBμV/m	μV/m
0.009 - 0.490	300	67.6-20 log f(kHz)	2400/f kHz
0.490 - 1.705	30	87.6-20 log f(kHz)	24000/f kHz
1.705 - 30	30	29.5	30
30 - 88	3	40.0	100
88- 216	3	43.5	150
216- 960	3	46.0	200
Above 960	3	54.0	500
Above 1000	3	74.0 dBμV/m (Peak) 54.0 dBμV/m (Average)	

Remark : (1) $\text{dB}\mu\text{V/m} = 20 \log (\mu\text{V/m})$

(2) The tighter limit applies to the edge between two frequency bands.

(3) Distance refers to the distance in meters between the measuring instrument antenna and the closed point of any part of the device or system.

(4) Fundamental and emission fall within operation band are exempted from this section.

(5) Pursuant to ANSI C63.10: 6.6.4.3, if the maximized peak measured value complies with the average limit, then it is unnecessary to perform an average measurement.

6.3. Test Procedure

Frequency Range 9kHz~30MHz:

The EUT setup on the turn table which has 0.8 m height to the ground. The turn table rotated 360 degrees and antenna fixed to 1 m to find the maximum emission level. In order to find the maximum emission, all of the interface cables were manipulated according to ANSI C63.10-2013 regulation.

- (1) RBW = 9kHz with peak and average detector.
- (2) Detector: average and peak (9kHz-490kHz)
Q.P. (490kHz-30MHz)

Frequency Range 30MHz ~ 25GHz:

The EUT setup on the turn table which has 80 cm (for 30-1000 MHz) and 1.5m (for above 1GHz) height to the ground. The turn table rotated 360 degrees and antenna varied from 1 m to 4 m (for 30-1000MHz) or antenna varied from 1 m to 3 m (for above 1GHz) to find the maximum emission level. Both horizontal and vertical polarization are required. In order to find the maximum emission, all of the interface cables were manipulated according to ANSI C63.10-2013 regulation.

Frequency below 1 GHz:

Spectrum Analyzer is used for pre-testing with following setting:

- (1) RBW = 120KHz
- (2) VBW $\geq 3 \times$ RBW.
- (3) Detector = Peak.
- (4) Sweep time = auto.
- (5) Trace mode = max hold.
- (6) Allow sweeps to continue until the trace stabilizes.

Note 1: When peak-detected value is lower than limit that the measurement using the Q.P. detector is not required, otherwise using Q.P. for final measurement.

Note 2: When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds.

Frequency above 1GHz to 10th harmonic (up to 25 GHz):

Peak Detector:

- (1) RBW = 1MHz
- (2) VBW $\geq 3 \times$ RBW.
- (3) Detector = Peak.
- (4) Sweep time = auto.
- (5) Trace mode = max hold.
- (6) Allow sweeps to continue until the trace stabilizes.

Note: When peak-detected value is lower than limit that the measurement using the average detector is not required, otherwise using average detector for final measurement.

Average Detector:**■ Option 1:**

(1) RBW = 1MHz

(2) VBW $\geq 1/T$.

Modulation Type	T (ms)	1/T (kHz)	VBW Setting (Hz)
BLE	0.90	1.111111	10Hz
802.11b	8.35	0.119760	10Hz
802.11g	2.079	0.481000	10Hz
802.11n-HT20	3.97	0.251889	10Hz
802.11n-HT40	3.96	0.252525	10Hz
802.11ax-HE20	3.95	0.253165	10Hz
802.11ax-HE40	3.93	0.254453	10Hz

N/A: 1/T is not implemented when duty cycle presented in section 3.6 is $\geq 98\%$.

(1) Detector = Peak.

(2) Sweep time = auto.

(3) Trace mode = max hold.

(4) Allow sweeps to continue until the trace stabilizes.

□ Option 2:


Average Emission Level = Peak Emission Level + D.C.C.F.

6.4. Measurement Result Explanation**■** Peak Emission Level = Antenna Factor + Cable Loss + Meter Reading (including Preamp factor if test used)**■** Average Emission Level = Antenna Factor + Cable Loss + Meter Reading (including Preamp factor if test used)**□** Average Emission Level = Peak Emission Level + DCCFDuty Cycle Correction Factor (DCCF) = $20\log(TX_{on}/TX_{on+off})$ presented in section 3.7**□** ERP = Peak Emission Level - 95.2dB - 2.14dB**6.5. Test Results**

Please refer to Appendix A.

7. 6dB/OCCUPIED BANDWIDTH

7.1. Block Diagram of Test Setup



7.2. Specification Limits

The minimum 6dB bandwidth shall be at least 500kHz.

7.3. Test Procedure

Following measurement procedure is reference to ANSI C63.10:2013:

- (1) Set RBW = 100 kHz.
- (2) Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
- (3) Detector = Peak.
- (4) Trace mode = max hold.
- (5) Sweep = auto couple.
- (6) Allow the trace to stabilize.
- (7) Setting channel bandwidth function x to -6dB or 99% power to record the final bandwidth.


7.4. Test Results

Please refer to Appendix A


8. MAXIMUM PEAK OUTPUT POWER

8.1. Block Diagram of Test Setup

- For WLAN Function



- For BLE Function



8.2. Specification Limits

The Limits of maximum Peak Output Power for digital modulation in 2400-2483.5MHz is : 1Watt. (30dBm), and E.I.R.P.: 4Watt (36dBm)

8.3. Test Procedure

Following measurement procedure is reference to ANSI C63.10:2013:

■ PKPM1 Peak power meter method:

EUT is connected to power sensor and record the maximum output power.

■ Maximum peak conducted output power method:

- (1) Set the RBW $\geq$ DTS bandwidth
- (2) Set VBW $\geq 3 \times$ RBW
- (3) Set span $\geq 3 \times$ RBW.
- (4) Sweep time = auto couple
- (5) Detector = peak.
- (6) Trace mode = max hold.
- (7) Allow trace to fully stabilize.
- (8) Use peak marker function to determine the peak amplitude level.

■ Method AVGPM (Measurement using an RF average power meter):

EUT is connected to power sensor and record the maximum average output power and duty cycle factor is added when duty cycle presented in section 3.7 is $< 98\%$.

□ Method AVGSA-2 (Spectrum channel power)


- (1) Set span to at least 1.5 times the OBW
- (2) Set RBW = 1 -5% of OBW
- (3) Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
- (4) Detector = RMS.
- (5) Trace mode = trace average at least 100 traces
- (6) Sweep = auto couple.
- (7) Compute power by integrating the spectrum across the OBW of the signal using the instrument's band power measurement function with band limits set equal to the OBW band edges.
- (8) Duty cycle factor is added when duty cycle presented in section 3.7 is $< 98\%$.

8.4. Test Results

Please refer to Appendix A

9. EMISSION LIMITATIONS

9.1. Block Diagram of Test Setup



9.2. Specification Limits

In any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, that the required attenuation shall be 30 dB instead of 20 dB.

Attenuation below the general limits specified in Section 15.209(a)/RSS-Gen Section 8.9 table 4 is not required. In addition, radiated emissions which fall in restricted bands, as defined in Section 15.205(a)/RSS-Gen Section 8.10 table 6, must also comply with the radiated emission limits specified in Section 15.209(a)/RSS-Gen Section 8.9 table 4 (See Section 15.205(c)).

9.3. Test Procedure

Following measurement procedure is reference to ANSI C63.10:2013:

■ Reference Level

- (1) Set analyzer center frequency to DTS channel center frequency.
- (2) Set the span to 1.5 times the DTS bandwidth.
- (3) Set the RBW to: 100 kHz.
- (4) Set the VBW $\geq 3 \times$ RBW.
- (5) Detector = peak.
- (6) Sweep time = auto couple.
- (7) Trace mode = max hold.
- (8) Allow trace to fully stabilize to find the max PSD as reference level.

■ Emission Level Measurement


- (1) Set analyzer center frequency to DTS channel center frequency.
- (2) Set the span to 1.5 times the DTS bandwidth.
- (3) Set the RBW to: 100 kHz.
- (4) Set the VBW $\geq 3 \times$ RBW.
- (5) Detector = peak.
- (6) Sweep time = auto couple.
- (7) Trace mode = max hold.
- (8) Allow trace to fully stabilize to find the max level.

9.4. Test Results

Please refer to Appendix A

10. POWER SPECTRAL DENSITY

10.1. Block Diagram of Test Setup



10.2. Specification Limits

The peak power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3kHz band.

10.3. Test Procedure

Following measurement procedure is reference to ANSI C63.10:2013:

■ Method PKPSD (peak PSD)

- (1) Set analyzer center frequency to DTS channel center frequency.
- (2) Set the span to 1.5 times the DTS bandwidth.
- (3) Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
- (4) Set the VBW $\geq 3 \times \text{RBW}$.
- (5) Detector = peak.
- (6) Sweep time = auto couple.
- (7) Trace mode = max hold.
- (8) Allow trace to fully stabilize.
- (9) Use the peak marker function to determine the maximum amplitude level.
- (10) If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

□ Method AVGPSD-2

- (1) Using peak PSD procedure step 1 to step 4.
- (2) Detector = RMS detector
- (3) Sweep time = auto couple
- (4) Trace mode = trace averaging over a minimum of 100 traces
- (5) Use the peak marker function to determine the maximum amplitude level.
- (6) Duty cycle factor is added when duty cycle presented in section 3.7 < 98%.
- (7) If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

10.4. Test Results

Please refer to Appendix A



Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City 244, Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303

11.DEVIATION TO TEST SPECIFICATIONS

【NONE】



Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City 244, Taiwan

APPENDIX A

Tel: +886 2 26099301
Fax: +886 2 26099303

APPDNDIX A

TEST DATA AND PLOTS

(Model: 15Z90N)



Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City 244, Taiwan

APPENDIX B

Tel: +886 2 26099301
Fax: +886 2 26099303

APPDNDIX B

TEST PHOTOGRAPHS

(Model: 15Z90N)

TABLE OF CONTENTS


A.1 CONDUCTED EMISSION.....	2
A.2 RADIATED EMISSION	6
A.2.1 Emissions within Restricted Frequency Bands.....	6
A.2.2 Emissions outside the frequency band:.....	102
A.2.3 Emissions in Non-restricted Frequency Bands:.....	106
A.3 6dB/OCCUPIED BANDWIDTH.....	107
A.3.1 Emission Bandwidth Result.....	107
A.3.2 Measurement Plots	109
A.4 MAXIMUM PEAK OUTPUT POWER	115
A.4.1 Peak Output Power	115
A.4.2 Average Output Power (Reporting only).....	123
A.4.3 Measurement Plots	129
A.5 EMISSION LIMITATIONS	131
A.6 POWER SPECTRAL DENSITY	158
A.6.1 Power Spectral Density Result	158
A.6.2 Measurement Plots	160

Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City 244, Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303

A.1 CONDUCTED EMISSION

Test Date	2019/10/01	Temp./Hum.	24°C/60%
Test Voltage	AC 120V 60Hz (Via AC Adapter)	Tested By	Chucky Chiu
Test SKU	SKU #1	Test Model	15Z90N



Site no. : No.8 Shielded Room Data no. : 8
Condition : ENV4200 100169 LISN Phase : NEUTRAL
Limit : FCC PART 15C
Env. / Ins. : 24°C / 60% ESR3 (1774) Engineer : Chucky Chiu
EUT : 15Z90N
Power Rating : 120Vac/60Hz
Test Mode : Operating


	Freq. (MHz)	AMN Factor (dB)	Cable Loss (dB)	Pulse Att. (dB)	Reading (dBμV)	Emission Level (dBμV)	Limits (dBμV)	Margin (dB)	Remark
1	0.192	10.63	0.04	9.86	4.59	25.12	53.93	28.81	Average
2	0.192	10.63	0.04	9.86	14.49	35.02	63.93	28.91	QP
3	0.928	10.47	0.05	9.86	-0.79	19.59	46.00	26.41	Average
4	0.928	10.47	0.05	9.86	6.56	26.94	56.00	29.06	QP
5	2.213	10.53	0.07	9.86	5.98	26.44	46.00	19.56	Average
6	2.213	10.53	0.07	9.86	14.76	35.22	56.00	20.78	QP
7	4.996	10.81	0.10	9.87	4.55	25.33	46.00	20.67	Average
8	4.996	10.81	0.10	9.87	14.65	35.43	56.00	20.57	QP
9	7.810	11.17	0.13	9.88	9.72	30.90	50.00	19.10	Average
10	7.810	11.17	0.13	9.88	19.04	40.22	60.00	19.78	QP
11	14.440	12.53	0.16	9.92	13.34	35.95	50.00	14.05	Average
12	14.440	12.53	0.16	9.92	19.98	42.59	60.00	17.41	QP

Remarks: 1. Emission Level= AMN Factor + Cable Loss + Pulse Att. + Reading.
2. If the average limit is met when using a quasi-peak detector,
the EUT shall be deemed to meet both limits and measurement
with average detector is unnecessary.

Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City244, Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303

Test Date	2019/10/01	Temp./Hum.	24°C/60%
Test Voltage	AC 120V 60Hz (Via AC Adapter)	Tested By	Chucky Chiu
Test SKU	SKU #1	Test Model	15Z90N



Site no. : No.8 Shielded Room Data no. : 7
Condition : ENV4200 100169 LISN Phase : LINE
Limit : FCC PART 15C
Env. / Ins. : 24°C / 60% ESR3 (1774) Engineer : Chucky Chiu
EUT : 15Z90N
Power Rating : 120Vac/60Hz
Test Mode : Operating


	Freq. (MHz)	AMN Factor (dB)	Cable Loss (dB)	Pulse Att. (dB)	Reading (dBμV)	Emission Level (dBμV)	Limits (dBμV)	Margin (dB)	Remark
1	0.193	10.55	0.04	9.86	6.40	26.85	53.89	27.04	Average
2	0.193	10.55	0.04	9.86	14.23	34.68	63.89	29.21	QP
3	0.658	10.43	0.05	9.86	-1.98	18.36	46.00	27.64	Average
4	0.658	10.43	0.05	9.86	7.83	28.17	56.00	27.83	QP
5	2.321	10.47	0.07	9.86	7.77	28.17	46.00	17.83	Average
6	2.321	10.47	0.07	9.86	15.68	36.08	56.00	19.92	QP
7	4.848	10.68	0.10	9.87	5.26	25.91	46.00	20.09	Average
8	4.848	10.68	0.10	9.87	15.06	35.71	56.00	20.29	QP
9	7.368	10.95	0.12	9.88	12.76	33.71	50.00	16.29	Average
10	7.368	10.95	0.12	9.88	21.34	42.29	60.00	17.71	QP
11	14.288	12.16	0.16	9.92	12.73	34.97	50.00	15.03	Average
12	14.288	12.16	0.16	9.92	19.12	41.36	60.00	18.64	QP

Remarks: 1. Emission Level= AMN Factor + Cable Loss + Pulse Att. + Reading.
2. If the average limit is met when using a quasi-peak detector,
the EUT shall be deemed to meet both limits and measurement
with average detector is unnecessary.

Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City 244, Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303

Test Date	2019/10/01	Temp./Hum.	24°C/60%
Test Voltage	AC 120V 60Hz (Via AC Adapter)	Tested By	Chucky Chiu
Test SKU	SKU #2	Test Model	15Z90N



Site no. : No.8 Shielded Room Data no. : 4
Condition : ENV4200 100169 LISN Phase : NEUTRAL
Limit : FCC PART 15C
Env. / Ins. : 24°C / 60% ESR3 (1774) Engineer : Chucky Chiu
EUT : 15Z90N
Power Rating : 120Vac/60Hz
Test Mode : Operating


	Freq. (MHz)	AMN Factor (dB)	Cable Loss (dB)	Pulse Att. (dB)	Reading (dBμV)	Emission Level (dBμV)	Limits (dBμV)	Margin (dB)	Remark
1	0.194	10.63	0.04	9.86	4.57	25.10	53.84	28.74	Average
2	0.194	10.63	0.04	9.86	14.00	34.53	63.84	29.31	QP
3	0.866	10.47	0.05	9.86	-2.66	17.72	46.00	28.28	Average
4	0.866	10.47	0.05	9.86	6.62	27.00	56.00	29.00	QP
5	2.321	10.54	0.07	9.86	7.13	27.60	46.00	18.40	Average
6	2.321	10.54	0.07	9.86	15.21	35.68	56.00	20.32	QP
7	4.999	10.82	0.10	9.87	5.46	26.25	46.00	19.75	Average
8	4.999	10.82	0.10	9.87	16.16	36.95	56.00	19.05	QP
9	7.566	11.14	0.13	9.88	13.23	34.38	50.00	15.62	Average
10	7.566	11.14	0.13	9.88	22.43	43.58	60.00	16.42	QP
11	14.517	12.55	0.16	9.92	13.25	35.88	50.00	14.12	Average
12	14.517	12.55	0.16	9.92	19.02	41.65	60.00	18.35	QP

Remarks: 1. Emission Level= AMN Factor + Cable Loss + Pulse Att. + Reading.
2. If the average limit is met when using a quasi-peak detector,
the EUT shall be deemed to meet both limits and measurement
with average detector is unnecessary.

Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City 244, Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303

Test Date	2019/10/01	Temp./Hum.	24°C/60%
Test Voltage	AC 120V 60Hz (Via AC Adapter)	Tested By	Chucky Chiu
Test SKU	SKU #2	Test Model	15Z90N



Site no. : No.8 Shielded Room Data no. : 3
Condition : ENV4200 100169 LISN Phase : LINE
Limit : FCC PART 15C
Env. / Ins. : 24°C / 60% ESR3 (1774) Engineer : Chucky Chiu
EUT : 15Z90N
Power Rating : 120Vac/60Hz
Test Mode : Operating

	Freq. (MHz)	AMN Factor (dB)	Cable Loss (dB)	Pulse Att. (dB)	Reading (dBμV)	Emission Level (dBμV)	Limits (dBμV)	Margin (dB)	Remark
1	0.152	10.62	0.04	9.86	-0.98	19.54	55.91	36.37	Average
2	0.152	10.62	0.04	9.86	13.58	34.10	65.91	31.81	QP
3	0.454	10.45	0.04	9.86	-1.31	19.04	46.80	27.76	Average
4	0.454	10.45	0.04	9.86	8.14	28.49	56.80	28.31	QP
5	1.166	10.43	0.05	9.86	1.61	21.95	46.00	24.05	Average
6	1.166	10.43	0.05	9.86	9.68	30.02	56.00	25.98	QP
7	2.435	10.48	0.08	9.86	6.12	26.54	46.00	19.46	Average
8	2.435	10.48	0.08	9.86	15.34	35.76	56.00	20.24	QP
9	7.025	10.92	0.12	9.88	4.79	25.71	50.00	24.29	Average
10	7.025	10.92	0.12	9.88	12.96	33.88	60.00	26.12	QP
11	14.364	12.18	0.16	9.92	12.66	34.92	50.00	15.08	Average
12	14.364	12.18	0.16	9.92	19.29	41.55	60.00	18.45	QP

Remarks: 1. Emission Level= AMN Factor + Cable Loss + Pulse Att. + Reading.
2. If the average limit is met when using a quasi-peak detector, the EUT shall be deemed to meet both limits and measurement with average detector is unnecessary.

A.2 RADIATED EMISSION

Test Date	2019/09/24 ~ 10/01	Temp./Hum.	23 ~ 24°C / 50 ~ 54%
Test Voltage	AC 120V 60Hz (Via AC Adapter)	Tested By	Kuper Hsu
		Test Model	15Z90N

A.2.1 Emissions within Restricted Frequency Bands

A.2.1.1 Frequency 9kHz~30MHz

The emissions (9kHz~30MHz) not reported for there is no emission be found.

A.2.1.2 Frequency Below 1GHz

Test SKU: SKU #2

Mode	802.11n-HT20	Frequency	TX 2442MHz
------	--------------	-----------	------------

Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
36.79	21.37	1.33	10.71	33.41	40.00	6.59	Peak
127.00	18.24	2.61	15.88	36.73	43.50	6.77	Peak
235.64	18.14	3.79	16.10	38.03	46.00	7.97	Peak
371.44	21.71	5.46	17.71	44.88	46.00	1.12	Peak
697.36	25.42	7.35	7.95	40.72	46.00	5.28	Peak
809.88	26.58	7.95	5.11	39.64	46.00	6.36	Peak

Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
57.16	13.09	1.68	22.26	37.03	40.00	2.97	Peak
119.24	18.63	2.52	16.67	37.82	43.50	5.68	Peak
243.40	18.50	3.87	19.69	42.06	46.00	3.94	Peak
296.75	19.66	4.40	14.72	38.78	46.00	7.22	Peak
505.30	23.76	6.76	5.57	36.09	46.00	9.91	Peak
972.84	27.87	8.88	3.00	39.75	54.00	14.25	Peak

Audix Technology Corp.

No. 53-11, Dingfu, Linkou, Dist.,

New Taipei City 244, Taiwan

Tel: +886 2 26099301**Fax: +886 2 26099303**

Mode	BLE	Frequency	TX 2440MHz
------	-----	-----------	------------

Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
126.03	18.31	2.60	15.49	36.40	43.50	7.10	Peak
237.58	18.22	3.81	16.10	38.13	46.00	7.87	Peak
371.44	21.71	5.46	17.71	44.88	46.00	1.12	Peak
697.36	25.42	7.35	8.64	41.41	46.00	4.59	Peak
880.69	27.16	8.34	6.33	41.83	46.00	4.17	Peak
965.08	27.82	8.83	2.81	39.46	54.00	14.54	Peak

Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
58.13	12.87	1.70	24.62	39.19	40.00	0.81	Peak
117.30	18.50	2.50	16.10	37.10	43.50	6.40	Peak
244.37	18.54	3.88	17.93	40.35	46.00	5.65	Peak
371.44	21.71	5.46	10.35	37.52	46.00	8.48	Peak
505.30	23.76	6.76	5.68	36.20	46.00	9.80	Peak
971.87	27.87	8.87	2.42	39.16	54.00	14.84	Peak

Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City 244, Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303

Test SKU: SKU #1

Mode	802.11n-HT20	Frequency	TX 2442MHz
------	--------------	-----------	------------

Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
35.82	21.86	1.31	10.30	33.47	40.00	6.53	Peak
125.06	18.36	2.59	16.62	37.57	43.50	5.93	Peak
237.58	18.22	3.81	22.86	44.89	46.00	1.11	Peak
296.75	19.66	4.40	19.85	43.91	46.00	2.09	Peak
697.36	25.42	7.35	8.48	41.25	46.00	4.75	Peak
793.39	26.43	7.86	6.40	40.69	46.00	5.31	Peak

Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
59.10	12.69	1.71	24.24	38.64	40.00	1.36	Peak
120.21	18.63	2.53	16.35	37.51	43.50	5.99	Peak
244.37	18.54	3.88	18.52	40.94	46.00	5.06	Peak
296.75	19.66	4.40	14.37	38.43	46.00	7.57	Peak
697.36	25.42	7.35	5.51	38.28	46.00	7.72	Peak
810.85	26.58	7.96	3.42	37.96	46.00	8.04	Peak

Audix Technology Corp.

No. 53-11, Dingfu, Linkou, Dist.,

New Taipei City 244, Taiwan

Tel: +886 2 26099301**Fax: +886 2 26099303**

Mode	BLE	Frequency	TX 2440MHz
------	-----	-----------	------------

Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
36.79	21.37	1.33	9.58	32.28	40.00	7.72	Peak
127.00	18.24	2.61	13.40	34.25	43.50	9.25	Peak
241.46	18.42	3.85	22.01	44.28	46.00	1.72	Peak
371.44	21.71	5.46	13.05	40.22	46.00	5.78	Peak
697.36	25.42	7.35	8.76	41.53	46.00	4.47	Peak
880.69	27.16	8.34	3.77	39.27	46.00	6.73	Peak

Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
59.10	12.69	1.71	24.11	38.51	40.00	1.49	Peak
119.24	18.63	2.52	14.62	35.77	43.50	7.73	Peak
244.37	18.54	3.88	18.31	40.73	46.00	5.27	Peak
296.75	19.66	4.40	14.59	38.65	46.00	7.35	Peak
697.36	25.42	7.35	5.92	38.69	46.00	7.31	Peak
954.41	27.74	8.77	2.91	39.42	46.00	6.58	Peak

Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City 244, Taiwan


Tel: +886 2 26099301
Fax: +886 2 26099303

A.2.1.3 Frequency Above 1 GHz to 10th harmonics

Test SKU: SKU #2


Band Edge:

Mode	802.11b	Frequency	TX 2412MHz
------	---------	-----------	------------



Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2375.40	32.00	8.17	8.90	49.07	74.00	24.93	Peak
2390.04	32.00	8.17	5.87	46.04	74.00	27.96	Peak
@ 2410.56	32.23	8.18	58.99	99.40	---	---	Peak




Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2374.68	32.00	8.17	0.36	40.53	54.00	13.47	Average
2390.04	32.00	8.17	-3.88	36.29	54.00	17.71	Average
@ 2411.28	32.23	8.18	55.68	96.09	---	---	Average


Remark: The "@" means fundamental frequency, it is ignored in this section.

Mode	802.11b	Frequency	TX 2412MHz
------	---------	-----------	------------



Antenna at Vertical Polarization


Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2385.96	32.00	8.17	10.89	51.06	74.00	22.94	Peak
2390.04	32.00	8.17	8.51	48.68	74.00	25.32	Peak
@ 2413.32	32.23	8.18	63.13	103.54	---	---	Peak



Antenna at Vertical Polarization


Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2385.72	32.00	8.17	4.38	44.55	54.00	9.45	Average
2390.04	32.00	8.17	0.39	40.56	54.00	13.44	Average
@ 2411.16	32.23	8.18	59.70	100.11	---	---	Average

Remark: The “@” means fundamental frequency, it is ignored in this section.



Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2389.68	32.00	8.17	10.30	50.47	74.00	23.53	Peak
2390.04	32.00	8.17	10.17	50.34	74.00	23.66	Peak
@ 2418.24	32.23	8.18	60.90	101.31	---	---	Peak



Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2389.68	32.00	8.17	1.84	42.01	54.00	11.99	Average
2390.04	32.00	8.17	4.35	44.52	54.00	9.48	Average
@ 2416.32	32.23	8.18	57.69	98.10	---	---	Average

Remark: The “@” means fundamental frequency, it is ignored in this section.


Audix Technology Corp.

No. 53-11, Dingfu, Linkou, Dist.,

New Taipei City244, Taiwan


Tel: +886 2 26099301

Fax: +886 2 26099303



Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2389.44	32.00	8.17	12.11	52.28	74.00	21.72	Peak
2390.04	32.00	8.17	13.08	53.25	74.00	20.75	Peak
@ 2415.48	32.23	8.18	64.38	104.79	---	---	Peak




Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2389.68	32.00	8.17	3.42	43.59	54.00	10.41	Average
2390.04	32.00	8.17	6.00	46.17	54.00	7.83	Average
@ 2416.20	32.23	8.18	60.23	100.64	---	---	Average

Remark: The “@” means fundamental frequency, it is ignored in this section.


Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City244, Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303



Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
@ 2458.30	32.63	8.20	57.47	98.30	---	---	Peak
2483.50	32.57	8.20	7.19	47.96	74.00	26.04	Peak
2484.00	32.57	8.20	7.64	48.41	74.00	25.59	Peak



Antenna at Horizontal Polarization


Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
@ 2456.30	32.63	8.20	54.08	94.91	---	---	Average
2483.50	32.57	8.20	-0.99	39.78	54.00	14.22	Average
2483.80	32.57	8.20	-1.47	39.30	54.00	14.70	Average

Remark: The "@" means fundamental frequency, it is ignored in this section.

Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City244, Taiwan


Tel: +886 2 26099301
Fax: +886 2 26099303

Mode	802.11b	Frequency	TX 2457MHz
------	---------	-----------	------------



Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
@ 2458.40	32.63	8.20	64.02	104.85	---	---	Peak
2483.50	32.57	8.20	12.78	53.55	74.00	20.45	Peak
2483.90	32.57	8.20	11.72	52.49	74.00	21.51	Peak




Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
@ 2456.30	32.63	8.20	60.42	101.25	---	---	Average
2483.50	32.57	8.20	5.96	46.73	54.00	7.27	Average
2483.80	32.57	8.20	5.26	46.03	54.00	7.97	Average

Remark: The "@" means fundamental frequency, it is ignored in this section.


Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City244, Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303



Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
@ 2463.40	32.63	8.20	56.78	97.61	---	---	Peak
2483.50	32.57	8.20	5.61	46.38	74.00	27.62	Peak
2487.60	32.50	8.21	8.65	49.36	74.00	24.64	Peak




Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
@ 2461.30	32.63	8.20	53.33	94.16	---	---	Average
2483.50	32.57	8.20	-2.85	37.92	54.00	16.08	Average
2487.50	32.50	8.21	-1.26	39.45	54.00	14.55	Average

Remark: The “@” means fundamental frequency, it is ignored in this section.


Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City244, Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303



Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
@ 2463.40	32.63	8.20	62.41	103.24	---	---	Peak
2483.50	32.57	8.20	9.65	50.42	74.00	23.58	Peak
2488.90	32.50	8.21	11.12	51.83	74.00	22.17	Peak




Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
@ 2461.20	32.63	8.20	58.64	99.47	---	---	Average
2483.50	32.57	8.20	3.57	44.34	54.00	9.66	Average
2483.80	32.57	8.20	2.12	42.89	54.00	11.11	Average

Remark: The "@" means fundamental frequency, it is ignored in this section.


Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City244, Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303



Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
@ 2468.30	32.63	8.20	56.17	97.00	---	---	Peak
2483.50	32.57	8.20	12.50	53.27	74.00	20.73	Peak
2483.80	32.57	8.20	11.87	52.64	74.00	21.36	Peak




Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
@ 2466.30	32.63	8.20	52.78	93.61	---	---	Average
2483.50	32.57	8.20	4.18	44.95	54.00	9.05	Average
2484.20	32.57	8.20	4.44	45.21	54.00	8.79	Average

Remark: The "@" means fundamental frequency, it is ignored in this section.


Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City244, Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303



Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
@ 2465.50	32.63	8.20	60.61	101.44	---	---	Peak
2483.50	32.57	8.20	16.90	57.67	74.00	16.33	Peak
2483.80	32.57	8.20	16.01	56.78	74.00	17.22	Peak




Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
@ 2466.30	32.63	8.20	57.96	98.79	---	---	Average
2483.50	32.57	8.20	9.26	50.03	54.00	3.97	Average
2484.40	32.57	8.20	10.12	50.89	54.00	3.11	Average

Remark: The “@” means fundamental frequency, it is ignored in this section.


Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City244, Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303



Antenna at Horizontal Polarization


Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
@ 2473.40	32.57	8.20	51.41	92.18	---	---	Peak
2483.50	32.57	8.20	7.81	48.58	74.00	25.42	Peak
2486.60	32.57	8.20	10.82	51.59	74.00	22.41	Peak



Antenna at Horizontal Polarization


Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
@ 2471.20	32.57	8.20	47.81	88.58	---	---	Average
2483.50	32.57	8.20	-0.73	40.04	54.00	13.96	Average
2487.10	32.57	8.20	4.57	45.34	54.00	8.66	Average

Remark: The "@" means fundamental frequency, it is ignored in this section.



Antenna at Vertical Polarization


Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
@ 2470.60	32.57	8.20	57.16	97.93	---	---	Peak
2483.50	32.57	8.20	14.22	54.99	74.00	19.01	Peak
2484.90	32.57	8.20	16.08	56.85	74.00	17.15	Peak



Antenna at Vertical Polarization


Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
@ 2471.20	32.57	8.20	53.73	94.50	---	---	Average
2483.50	32.57	8.20	5.17	45.94	54.00	8.06	Average
2485.70	32.57	8.20	10.83	51.60	54.00	2.40	Average

Remark: The "@" means fundamental frequency, it is ignored in this section.



Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2389.32	32.00	8.17	22.77	62.94	74.00	11.06	Peak
2390.04	32.00	8.17	19.52	59.69	74.00	14.31	Peak
@ 2414.04	32.23	8.18	58.74	99.15	---	---	Peak




Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2389.68	32.00	8.17	7.01	47.18	54.00	6.82	Average
2390.04	32.00	8.17	7.14	47.31	54.00	6.69	Average
@ 2417.28	32.23	8.18	49.10	89.51	---	---	Average

Remark: The "@" means fundamental frequency, it is ignored in this section.


Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City 244, Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303



Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2389.32	32.00	8.17	26.38	66.55	74.00	7.45	Peak
2390.04	32.00	8.17	26.32	66.49	74.00	7.51	Peak
@ 2418.84	32.23	8.18	62.15	102.56	---	---	Peak




Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2389.68	32.00	8.17	11.76	51.93	54.00	2.07	Average
2390.04	32.00	8.17	12.11	52.28	54.00	1.72	Average
@ 2415.96	32.23	8.18	52.55	92.96	---	---	Average

Remark: The "@" means fundamental frequency, it is ignored in this section.


Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City244, Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303



Antenna at Horizontal Polarization


Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2388.48	32.00	8.17	19.24	59.41	74.00	14.59	Peak
2390.04	32.00	8.17	18.39	58.56	74.00	15.44	Peak
@ 2423.64	32.47	8.19	60.20	100.86	---	---	Peak



Antenna at Horizontal Polarization


Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2389.68	32.00	8.17	4.83	45.00	54.00	9.00	Average
2390.04	32.00	8.17	5.12	45.29	54.00	8.71	Average
@ 2419.80	32.47	8.19	49.99	90.65	---	---	Average

Remark: The "@" means fundamental frequency, it is ignored in this section.



Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2388.84	32.00	8.17	23.31	63.48	74.00	10.52	Peak
2390.04	32.00	8.17	23.91	64.08	74.00	9.92	Peak
@ 2423.04	32.47	8.19	63.23	103.89	---	---	Peak




Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2389.68	32.00	8.17	9.33	49.50	54.00	4.50	Average
2390.04	32.00	8.17	9.48	49.65	54.00	4.35	Average
@ 2421.48	32.47	8.19	53.58	94.24	---	---	Average

Remark: The “@” means fundamental frequency, it is ignored in this section.


Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City244, Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303



Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
@ 2454.30	32.63	8.20	55.72	96.55	---	---	Peak
2483.50	32.57	8.20	12.32	53.09	74.00	20.91	Peak
2486.50	32.57	8.20	13.12	53.89	74.00	20.11	Peak



Antenna at Horizontal Polarization


Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
@ 2454.90	32.63	8.20	45.49	86.32	---	---	Average
2483.50	32.57	8.20	0.92	41.69	54.00	12.31	Average
2484.20	32.57	8.20	0.84	41.61	54.00	12.39	Average

Remark: The “@” means fundamental frequency, it is ignored in this section.

Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City 244, Taiwan


Tel: +886 2 26099301
Fax: +886 2 26099303

Mode	802.11g	Frequency	TX 2457MHz
------	---------	-----------	------------



Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector
@ 2454.20	32.63	8.20	64.40	105.23	---	---	Peak
2483.50	32.57	8.20	19.68	60.45	74.00	13.55	Peak
2484.70	32.57	8.20	22.09	62.86	74.00	11.14	Peak




Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector
@ 2453.60	32.63	8.20	54.84	95.67	---	---	Average
2483.50	32.57	8.20	7.70	48.47	54.00	5.53	Average
2483.90	32.57	8.20	7.76	48.53	54.00	5.47	Average

Remark: The "@" means fundamental frequency, it is ignored in this section.


Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City244, Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303



Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
@ 2456.40	32.63	8.20	54.71	95.54	---	---	Peak
2483.50	32.57	8.20	15.13	55.90	74.00	18.10	Peak
2485.00	32.57	8.20	16.16	56.93	74.00	17.07	Peak




Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
@ 2456.60	32.63	8.20	45.01	85.84	---	---	Average
2483.50	32.57	8.20	2.94	43.71	54.00	10.29	Average
2483.90	32.57	8.20	2.43	43.20	54.00	10.80	Average

Remark: The "@" means fundamental frequency, it is ignored in this section.


Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City 244, Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303



Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
@ 2457.10	32.63	8.20	63.95	104.78	---	---	Peak
2483.50	32.57	8.20	22.46	63.23	74.00	10.77	Peak
2484.10	32.57	8.20	24.77	65.54	74.00	8.46	Peak




Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
@ 2459.00	32.63	8.20	53.91	94.74	---	---	Average
2483.50	32.57	8.20	10.57	51.34	54.00	2.66	Average
2483.80	32.57	8.20	10.19	50.96	54.00	3.04	Average

Remark: The "@" means fundamental frequency, it is ignored in this section.


Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City244, Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303



Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
@ 2473.70	32.57	8.20	51.62	92.39	---	---	Peak
2483.50	32.57	8.20	18.47	59.24	74.00	14.76	Peak
2485.90	32.57	8.20	17.24	58.01	74.00	15.99	Peak




Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
@ 2460.90	32.63	8.20	41.97	82.80	---	---	Average
2483.50	32.57	8.20	4.81	45.58	54.00	8.42	Average
2484.10	32.57	8.20	4.66	45.43	54.00	8.57	Average

Remark: The "@" means fundamental frequency, it is ignored in this section.


Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City 244, Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303



Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
@ 2464.20	32.63	8.20	61.00	101.83	---	---	Peak
2483.50	32.57	8.20	23.55	64.32	74.00	9.68	Peak
2485.40	32.57	8.20	26.39	67.16	74.00	6.84	Peak




Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
@ 2464.50	32.63	8.20	38.83	79.66	---	---	Average
2483.50	32.57	8.20	11.95	52.72	54.00	1.28	Average
2483.80	32.57	8.20	11.86	52.63	54.00	1.37	Average

Remark: The "@" means fundamental frequency, it is ignored in this section.


Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City 244, Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303



Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
@ 2475.70	32.57	8.20	38.78	79.55	---	---	Peak
2483.50	32.57	8.20	6.04	46.81	74.00	27.19	Peak
2509.50	32.30	8.22	7.69	48.21	74.00	25.79	Peak




Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
@ 2467.60	32.63	8.20	29.58	70.41	---	---	Average
2483.50	32.57	8.20	-6.14	34.63	54.00	19.37	Average
2484.10	32.57	8.20	-5.94	34.83	54.00	19.17	Average

Remark: The "@" means fundamental frequency, it is ignored in this section.


Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City244, Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303



Antenna at Vertical Polarization


Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
@ 2465.80	32.63	8.20	47.89	88.72	---	---	Peak
2483.50	32.57	8.20	11.63	52.40	74.00	21.60	Peak
2483.80	32.57	8.20	10.06	50.83	74.00	23.17	Peak



Antenna at Vertical Polarization


Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
@ 2477.80	32.57	8.20	38.13	78.90	---	---	Average
2483.50	32.57	8.20	-5.36	35.41	54.00	18.59	Average
2488.30	32.50	8.21	-5.60	35.11	54.00	18.89	Average

Remark: The “@” means fundamental frequency, it is ignored in this section.



Antenna at Horizontal Polarization


Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2389.56	32.00	8.17	15.31	55.48	74.00	18.52	Peak
2390.04	32.00	8.17	14.21	54.38	74.00	19.62	Peak
@ 2414.40	32.23	8.18	61.61	102.02	---	---	Peak



Antenna at Horizontal Polarization


Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2388.96	32.00	8.17	3.98	44.15	54.00	9.85	Average
2390.04	32.00	8.17	4.24	44.41	54.00	9.59	Average
@ 2416.92	32.23	8.18	50.15	90.56	---	---	Average

Remark: The “@” means fundamental frequency, it is ignored in this section.



Antenna at Vertical Polarization


Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2389.68	32.00	8.17	17.13	57.30	74.00	16.70	Peak
2390.04	32.00	8.17	14.64	54.81	74.00	19.19	Peak
@ 2418.60	32.23	8.18	63.67	104.08	---	---	Peak



Antenna at Vertical Polarization


Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2389.44	32.00	8.17	4.34	44.51	54.00	9.49	Average
2390.04	32.00	8.17	4.81	44.98	54.00	9.02	Average
@ 2413.56	32.23	8.18	52.63	93.04	---	---	Average

Remark: The “@” means fundamental frequency, it is ignored in this section.



Antenna at Horizontal Polarization


Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2367.00	32.00	8.16	14.97	55.13	74.00	18.87	Peak
2390.04	32.00	8.17	13.35	53.52	74.00	20.48	Peak
@ 2413.56	32.23	8.18	62.07	102.48	---	---	Peak



Antenna at Horizontal Polarization


Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2389.08	32.00	8.17	2.23	42.40	54.00	11.60	Average
2390.04	32.00	8.17	2.20	42.37	54.00	11.63	Average
@ 2409.96	32.23	8.18	51.27	91.68	---	---	Average

Remark: The "@" means fundamental frequency, it is ignored in this section.



Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2387.40	32.00	8.17	15.73	55.90	74.00	18.10	Peak
2390.04	32.00	8.17	13.91	54.08	74.00	19.92	Peak
@ 2419.44	32.23	8.18	64.85	105.26	---	---	Peak




Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2389.68	32.00	8.17	2.76	42.93	54.00	11.07	Average
2390.04	32.00	8.17	2.91	43.08	54.00	10.92	Average
@ 2419.56	32.47	8.19	53.53	94.19	---	---	Average

Remark: The “@” means fundamental frequency, it is ignored in this section.


Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City244, Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303



Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
@ 2462.70	32.63	8.20	58.86	99.69	---	---	Peak
2483.50	32.57	8.20	5.92	46.69	74.00	27.31	Peak
2485.70	32.57	8.20	7.42	48.19	74.00	25.81	Peak



Antenna at Horizontal Polarization


Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
@ 2459.50	32.63	8.20	48.28	89.11	---	---	Average
2483.50	32.57	8.20	-4.22	36.55	54.00	17.45	Average
2483.90	32.57	8.20	-4.33	36.44	54.00	17.56	Average

Remark: The “@” means fundamental frequency, it is ignored in this section.

Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City244, Taiwan


Tel: +886 2 26099301
Fax: +886 2 26099303

Mode	802.11n-HT20	Frequency	TX 2457MHz
------	--------------	-----------	------------



Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
@ 2449.80	32.70	8.19	64.35	105.24	---	---	Peak
2483.50	32.57	8.20	8.99	49.76	74.00	24.24	Peak
2483.80	32.57	8.20	11.44	52.21	74.00	21.79	Peak




Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
@ 2461.80	32.63	8.20	53.09	93.92	---	---	Average
2483.50	32.57	8.20	-0.90	39.87	54.00	14.13	Average
2484.00	32.57	8.20	-1.13	39.64	54.00	14.36	Average

Remark: The “@” means fundamental frequency, it is ignored in this section.


Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City244, Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303



Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
@ 2455.50	32.63	8.20	58.21	99.04	---	---	Peak
2483.50	32.57	8.20	12.18	52.95	74.00	21.05	Peak
2485.10	32.57	8.20	12.66	53.43	74.00	20.57	Peak




Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
@ 2467.10	32.63	8.20	47.66	88.49	---	---	Average
2483.50	32.57	8.20	-0.99	39.78	54.00	14.22	Average
2483.80	32.57	8.20	-1.15	39.62	54.00	14.38	Average

Remark: The "@" means fundamental frequency, it is ignored in this section.


Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City244, Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303



Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
@ 2469.60	32.63	8.20	64.07	104.90	---	---	Peak
2483.50	32.57	8.20	16.18	56.95	74.00	17.05	Peak
2486.40	32.57	8.20	18.98	59.75	74.00	14.25	Peak




Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
@ 2468.60	32.63	8.20	52.35	93.18	---	---	Average
2483.50	32.57	8.20	3.99	44.76	54.00	9.24	Average
2483.80	32.57	8.20	3.93	44.70	54.00	9.30	Average

Remark: The “@” means fundamental frequency, it is ignored in this section.


Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City244, Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303



Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
@ 2470.70	32.57	8.20	55.32	96.09	---	---	Peak
2483.50	32.57	8.20	8.71	49.48	74.00	24.52	Peak
2484.10	32.57	8.20	8.76	49.53	74.00	24.47	Peak




Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
@ 2473.10	32.57	8.20	44.42	85.19	---	---	Average
2483.50	32.57	8.20	-1.72	39.05	54.00	14.95	Average
2483.80	32.57	8.20	-2.34	38.43	54.00	15.57	Average

Remark: The “@” means fundamental frequency, it is ignored in this section.


Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City244, Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303



Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
@ 2472.50	32.57	8.20	61.07	101.84	---	---	Peak
2483.50	32.57	8.20	15.18	55.95	74.00	18.05	Peak
2484.30	32.57	8.20	14.02	54.79	74.00	19.21	Peak




Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
@ 2474.80	32.57	8.20	49.51	90.28	---	---	Average
2483.50	32.57	8.20	2.84	43.61	54.00	10.39	Average
2483.80	32.57	8.20	1.79	42.56	54.00	11.44	Average

Remark: The “@” means fundamental frequency, it is ignored in this section.


Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City244, Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303



Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
@ 2479.50	32.57	8.20	42.88	83.65	---	---	Peak
2483.50	32.57	8.20	13.55	54.32	74.00	19.68	Peak
2484.90	32.57	8.20	8.61	49.38	74.00	24.62	Peak




Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
@ 2479.20	32.57	8.20	32.39	73.16	---	---	Average
2483.50	32.57	8.20	-6.01	34.76	54.00	19.24	Average
2483.90	32.57	8.20	-6.06	34.71	54.00	19.29	Average

Remark: The “@” means fundamental frequency, it is ignored in this section.


Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City244, Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303



Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
@ 2469.50	32.63	8.20	47.39	88.22	---	---	Peak
2483.50	32.57	8.20	13.81	54.58	74.00	19.42	Peak
2486.60	32.57	8.20	14.80	55.57	74.00	18.43	Peak




Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
@ 2477.90	32.57	8.20	36.43	77.20	---	---	Average
2483.50	32.57	8.20	-4.82	35.95	54.00	18.05	Average
2483.90	32.57	8.20	-5.35	35.42	54.00	18.58	Average

Remark: The “@” means fundamental frequency, it is ignored in this section.


Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City244, Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303



Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2385.46	32.00	8.17	16.38	56.55	74.00	17.45	Peak
2389.94	32.00	8.17	13.10	53.27	74.00	20.73	Peak
@ 2405.20	32.23	8.18	56.95	97.36	---	---	Peak




Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2389.52	32.00	8.17	2.36	42.53	54.00	11.47	Average
2389.94	32.00	8.17	2.55	42.72	54.00	11.28	Average
@ 2414.72	32.23	8.18	46.53	86.94	---	---	Average

Remark: The “@” means fundamental frequency, it is ignored in this section.


Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City244, Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303



Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2386.16	32.00	8.17	17.62	57.79	74.00	16.21	Peak
2389.94	32.00	8.17	15.30	55.47	74.00	18.53	Peak
@ 2410.52	32.23	8.18	60.37	100.78	---	---	Peak




Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2389.24	32.00	8.17	3.74	43.91	54.00	10.09	Average
2389.94	32.00	8.17	3.49	43.66	54.00	10.34	Average
@ 2417.94	32.23	8.18	49.03	89.44	---	---	Average

Remark: The “@” means fundamental frequency, it is ignored in this section.


Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City244, Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303



Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2386.02	32.00	8.17	12.18	52.35	74.00	21.65	Peak
2389.94	32.00	8.17	9.62	49.79	74.00	24.21	Peak
@ 2420.46	32.47	8.19	55.97	96.63	---	---	Peak




Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2389.24	32.00	8.17	-0.54	39.63	54.00	14.37	Average
2389.94	32.00	8.17	-0.11	40.06	54.00	13.94	Average
@ 2421.44	32.47	8.19	45.23	85.89	---	---	Average

Remark: The “@” means fundamental frequency, it is ignored in this section.


Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City244, Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303



Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2385.04	32.00	8.17	12.55	52.72	74.00	21.28	Peak
2389.94	32.00	8.17	11.10	51.27	74.00	22.73	Peak
@ 2422.70	32.47	8.19	58.83	99.49	---	---	Peak




Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2387.42	32.00	8.17	-0.04	40.13	54.00	13.87	Average
2389.94	32.00	8.17	-0.09	40.08	54.00	13.92	Average
@ 2418.64	32.23	8.18	47.75	88.16	---	---	Average

Remark: The “@” means fundamental frequency, it is ignored in this section.


Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City 244, Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303



Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
@ 2439.90	32.70	8.19	55.94	96.83	---	---	Peak
2483.50	32.57	8.20	11.16	51.93	74.00	22.07	Peak
2484.50	32.57	8.20	13.50	54.27	74.00	19.73	Peak




Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
@ 2431.80	32.47	8.19	45.97	86.63	---	---	Average
2483.50	32.57	8.20	0.71	41.48	54.00	12.52	Average
2484.20	32.57	8.20	0.94	41.71	54.00	12.29	Average

Remark: The "@" means fundamental frequency, it is ignored in this section.


Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City244, Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303



Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
@ 2431.40	32.47	8.19	61.81	102.47	---	---	Peak
2483.50	32.57	8.20	16.47	57.24	74.00	16.76	Peak
2483.80	32.57	8.20	18.34	59.11	74.00	14.89	Peak




Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
@ 2433.70	32.47	8.19	50.46	91.12	---	---	Average
2483.50	32.57	8.20	5.95	46.72	54.00	7.28	Average
2484.40	32.57	8.20	5.52	46.29	54.00	7.71	Average

Remark: The "@" means fundamental frequency, it is ignored in this section.


Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City244, Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303



Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
@ 2435.00	32.47	8.19	55.06	95.72	---	---	Peak
2483.50	32.57	8.20	8.30	49.07	74.00	24.93	Peak
2488.20	32.50	8.21	9.76	50.47	74.00	23.53	Peak




Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
@ 2442.80	32.70	8.19	43.82	84.71	---	---	Average
2483.50	32.57	8.20	-2.46	38.31	54.00	15.69	Average
2484.00	32.57	8.20	-2.41	38.36	54.00	15.64	Average

Remark: The “@” means fundamental frequency, it is ignored in this section.


Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City244, Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303



Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
@ 2434.50	32.47	8.19	60.05	100.71	---	---	Peak
2483.50	32.57	8.20	11.92	52.69	74.00	21.31	Peak
2486.40	32.57	8.20	13.45	54.22	74.00	19.78	Peak




Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
@ 2439.10	32.70	8.19	48.03	88.92	---	---	Average
2483.50	32.57	8.20	1.05	41.82	54.00	12.18	Average
2484.10	32.57	8.20	0.78	41.55	54.00	12.45	Average

Remark: The "@" means fundamental frequency, it is ignored in this section.


Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City244, Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303



Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
@ 2445.00	32.70	8.19	51.18	92.07	---	---	Peak
2483.50	32.57	8.20	7.58	48.35	74.00	25.65	Peak
2483.90	32.57	8.20	8.24	49.01	74.00	24.99	Peak




Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
@ 2443.90	32.70	8.19	40.03	80.92	---	---	Average
2483.50	32.57	8.20	-2.49	38.28	54.00	15.72	Average
2483.80	32.57	8.20	-2.76	38.01	54.00	15.99	Average

Remark: The “@” means fundamental frequency, it is ignored in this section.


Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City244, Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303



Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
@ 2439.80	32.70	8.19	56.38	97.27	---	---	Peak
2483.50	32.57	8.20	12.03	52.80	74.00	21.20	Peak
2483.80	32.57	8.20	11.72	52.49	74.00	21.51	Peak




Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
@ 2446.50	32.70	8.19	44.40	85.29	---	---	Average
2483.50	32.57	8.20	1.31	42.08	54.00	11.92	Average
2483.80	32.57	8.20	0.62	41.39	54.00	12.61	Average

Remark: The “@” means fundamental frequency, it is ignored in this section.


Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City244, Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303



Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
@ 2446.10	32.70	8.19	42.37	83.26	---	---	Peak
2483.50	32.57	8.20	6.43	47.20	74.00	26.80	Peak
2484.10	32.57	8.20	6.66	47.43	74.00	26.57	Peak



Antenna at Horizontal Polarization


Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
@ 2447.40	32.70	8.19	32.20	73.09	---	---	Average
2483.50	32.57	8.20	-5.85	34.92	54.00	19.08	Average
2483.80	32.57	8.20	-6.18	34.59	54.00	19.41	Average

Remark: The “@” means fundamental frequency, it is ignored in this section.

Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City 244, Taiwan


Tel: +886 2 26099301
Fax: +886 2 26099303

Mode	802.11n-HT40	Frequency	TX 2462MHz
------	--------------	-----------	------------



Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
@ 2444.60	32.70	8.19	47.95	88.84	---	---	Peak
2483.50	32.57	8.20	8.67	49.44	74.00	24.56	Peak
2483.90	32.57	8.20	9.35	50.12	74.00	23.88	Peak




Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
@ 2446.00	32.70	8.19	36.26	77.15	---	---	Average
2483.50	32.57	8.20	-4.39	36.38	54.00	17.62	Average
2483.80	32.57	8.20	-4.52	36.25	54.00	17.75	Average


Remark: The "@" means fundamental frequency, it is ignored in this section.

Mode	802.11ax-HE20	Frequency	TX 2412MHz
------	---------------	-----------	------------



Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2388.84	32.00	8.17	15.31	55.48	74.00	18.52	Peak
2390.04	32.00	8.17	13.63	53.80	74.00	20.20	Peak
@ 2415.60	32.23	8.18	59.49	99.90	---	---	Peak




Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2389.44	32.00	8.17	3.41	43.58	54.00	10.42	Average
2390.04	32.00	8.17	3.26	43.43	54.00	10.57	Average
@ 2418.12	32.23	8.18	48.32	88.73	---	---	Average

Remark: The "@" means fundamental frequency, it is ignored in this section.


Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City244, Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303



Antenna at Vertical Polarization


Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2388.96	32.00	8.17	17.63	57.80	74.00	16.20	Peak
2390.04	32.00	8.17	15.65	55.82	74.00	18.18	Peak
@ 2407.44	32.23	8.18	64.48	104.89	---	---	Peak



Antenna at Vertical Polarization


Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2389.44	32.00	8.17	5.38	45.55	54.00	8.45	Average
2390.04	32.00	8.17	5.42	45.59	54.00	8.41	Average
@ 2414.88	32.23	8.18	52.87	93.28	---	---	Average

Remark: The “@” means fundamental frequency, it is ignored in this section.



Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2363.28	32.00	8.16	14.93	55.09	74.00	18.91	Peak
2390.04	32.00	8.17	13.84	54.01	74.00	19.99	Peak
@ 2421.48	32.47	8.19	61.12	101.78	---	---	Peak




Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2389.68	32.00	8.17	2.07	42.24	54.00	11.76	Average
2390.04	32.00	8.17	2.28	42.45	54.00	11.55	Average
@ 2419.80	32.47	8.19	49.64	90.30	---	---	Average

Remark: The “@” means fundamental frequency, it is ignored in this section.


Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City244, Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303



Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2313.00	32.00	8.15	15.41	55.56	74.00	18.44	Peak
2390.04	32.00	8.17	14.74	54.91	74.00	19.09	Peak
@ 2423.28	32.47	8.19	64.71	105.37	---	---	Peak




Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2389.68	32.00	8.17	3.56	43.73	54.00	10.27	Average
2390.04	32.00	8.17	3.63	43.80	54.00	10.20	Average
@ 2410.44	32.23	8.18	53.95	94.36	---	---	Average

Remark: The "@" means fundamental frequency, it is ignored in this section.


Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City244, Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303



Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
@ 2465.30	32.63	8.20	59.84	100.67	---	---	Peak
2483.50	32.57	8.20	13.43	54.20	74.00	19.80	Peak
2484.90	32.57	8.20	14.81	55.58	74.00	18.42	Peak



Antenna at Horizontal Polarization


Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
@ 2463.50	32.63	8.20	48.27	89.10	---	---	Average
2483.50	32.57	8.20	1.74	42.51	54.00	11.49	Average
2483.80	32.57	8.20	1.58	42.35	54.00	11.65	Average

Remark: The “@” means fundamental frequency, it is ignored in this section.

Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City244, Taiwan


Tel: +886 2 26099301
Fax: +886 2 26099303

Mode	802.11ax-HE20	Frequency	TX 2457MHz
------	---------------	-----------	------------



Antenna at Vertical Polarization


Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
@ 2463.30	32.63	8.20	64.30	105.13	---	---	Peak
2483.50	32.57	8.20	15.75	56.52	74.00	17.48	Peak
2483.90	32.57	8.20	16.47	57.24	74.00	16.76	Peak



Antenna at Vertical Polarization


Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
@ 2458.90	32.63	8.20	52.30	93.13	---	---	Average
2483.50	32.57	8.20	2.72	43.49	54.00	10.51	Average
2483.90	32.57	8.20	2.79	43.56	54.00	10.44	Average

Remark: The “@” means fundamental frequency, it is ignored in this section.



Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
@ 2467.20	32.63	8.20	58.85	99.68	---	---	Peak
2483.50	32.57	8.20	13.67	54.44	74.00	19.56	Peak
2483.90	32.57	8.20	15.24	56.01	74.00	17.99	Peak




Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
@ 2465.30	32.63	8.20	47.62	88.45	---	---	Average
2483.50	32.57	8.20	2.38	43.15	54.00	10.85	Average
2484.50	32.57	8.20	2.50	43.27	54.00	10.73	Average


Remark: The “@” means fundamental frequency, it is ignored in this section.

Mode	802.11ax-HE20	Frequency	TX 2462MHz
------	---------------	-----------	------------



Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
@ 2463.70	32.63	8.20	63.93	104.76	---	---	Peak
2483.50	32.57	8.20	17.41	58.18	74.00	15.82	Peak
2484.30	32.57	8.20	18.24	59.01	74.00	14.99	Peak




Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
@ 2468.40	32.63	8.20	50.21	91.04	---	---	Average
2483.50	32.57	8.20	4.71	45.48	54.00	8.52	Average
2483.80	32.57	8.20	4.64	45.41	54.00	8.59	Average


Remark: The "@" means fundamental frequency, it is ignored in this section.

Mode	802.11ax-HE20	Frequency	TX 2467MHz
------	---------------	-----------	------------



Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
@ 2462.90	32.63	8.20	55.89	96.72	---	---	Peak
2483.50	32.57	8.20	13.91	54.68	74.00	19.32	Peak
2489.90	32.50	8.21	15.10	55.81	74.00	18.19	Peak




Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
@ 2474.40	32.57	8.20	44.65	85.42	---	---	Average
2483.50	32.57	8.20	2.66	43.43	54.00	10.57	Average
2483.80	32.57	8.20	2.29	43.06	54.00	10.94	Average

Remark: The “@” means fundamental frequency, it is ignored in this section.


Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City244, Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303



Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
@ 2475.10	32.57	8.20	60.06	100.83	---	---	Peak
2483.50	32.57	8.20	16.81	57.58	74.00	16.42	Peak
2483.80	32.57	8.20	15.27	56.04	74.00	17.96	Peak




Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
@ 2468.80	32.63	8.20	48.35	89.18	---	---	Average
2483.50	32.57	8.20	4.60	45.37	54.00	8.63	Average
2483.90	32.57	8.20	4.01	44.78	54.00	9.22	Average

Remark: The "@" means fundamental frequency, it is ignored in this section.


Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City244, Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303



Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
@ 2474.60	32.57	8.20	45.61	86.38	---	---	Peak
2483.50	32.57	8.20	13.17	53.94	74.00	20.06	Peak
2509.10	32.30	8.22	14.56	55.08	74.00	18.92	Peak



Antenna at Horizontal Polarization


Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
@ 2470.10	32.63	8.20	33.40	74.23	---	---	Average
2483.50	32.57	8.20	1.32	42.09	54.00	11.91	Average
2500.10	32.50	8.21	1.49	42.20	54.00	11.80	Average

Remark: The “@” means fundamental frequency, it is ignored in this section.

Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City244, Taiwan


Tel: +886 2 26099301
Fax: +886 2 26099303

Mode	802.11ax-HE20	Frequency	TX 2472MHz
------	---------------	-----------	------------



Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
@ 2474.70	32.57	8.20	48.97	89.74	---	---	Peak
2483.50	32.57	8.20	14.91	55.68	74.00	18.32	Peak
2485.90	32.57	8.20	15.29	56.06	74.00	17.94	Peak




Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
@ 2478.60	32.57	8.20	37.23	78.00	---	---	Average
2483.50	32.57	8.20	2.11	42.88	54.00	11.12	Average
2484.10	32.57	8.20	1.73	42.50	54.00	11.50	Average

Remark: The "@" means fundamental frequency, it is ignored in this section.


Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City 244, Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303



Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2387.84	32.00	8.17	13.70	53.87	74.00	20.13	Peak
2389.94	32.00	8.17	12.31	52.48	74.00	21.52	Peak
@ 2415.56	32.23	8.18	57.00	97.41	---	---	Peak




Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2388.96	32.00	8.17	1.91	42.08	54.00	11.92	Average
2389.94	32.00	8.17	1.77	41.94	54.00	12.06	Average
@ 2419.06	32.23	8.18	45.54	85.95	---	---	Average

Remark: The "@" means fundamental frequency, it is ignored in this section.


Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City 244, Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303



Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2388.40	32.00	8.17	18.12	58.29	74.00	15.71	Peak
2389.94	32.00	8.17	15.68	55.85	74.00	18.15	Peak
@ 2409.12	32.23	8.18	62.15	102.56	---	---	Peak



Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2385.60	32.00	8.17	5.48	45.65	54.00	8.35	Average
2389.94	32.00	8.17	5.96	46.13	54.00	7.87	Average
@ 2405.90	32.23	8.18	50.01	90.42	---	---	Average

Remark: The "@" means fundamental frequency, it is ignored in this section.

Audix Technology Corp.


No. 53-11, Dingfu, Linkou, Dist.,

New Taipei City 244, Taiwan

Tel: +886 2 26099301


Fax: +886 2 26099303

Mode	802.11ax-HE40	Frequency	TX 2427MHz
------	---------------	-----------	------------



Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBUV)	Emission Level (dBUV/m)	Limits (dBUV/m)	Margin (dB)	Detector
2387.14	32.00	8.17	10.15	50.32	74.00	23.68	Peak
2389.94	32.00	8.17	8.21	48.38	74.00	25.62	Peak
@ 2420.60	32.47	8.19	55.76	96.42	---	---	Peak



Antenna at Horizontal Polarization


Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBUV)	Emission Level (dBUV/m)	Limits (dBUV/m)	Margin (dB)	Detector
2389.52	32.00	8.17	-1.52	38.65	54.00	15.35	Average
2389.94	32.00	8.17	-1.71	38.46	54.00	15.54	Average
@ 2416.26	32.23	8.18	44.55	84.96	---	---	Average

Remark: The "@" means fundamental frequency, it is ignored in this section.

Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City244, Taiwan


Tel: +886 2 26099301
Fax: +886 2 26099303

Mode	802.11ax-HE40	Frequency	TX 2427MHz
------	---------------	-----------	------------



Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2385.74	32.00	8.17	12.92	53.09	74.00	20.91	Peak
2389.94	32.00	8.17	13.60	53.77	74.00	20.23	Peak
@ 2438.24	32.70	8.19	59.92	100.81	---	---	Peak




Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2389.52	32.00	8.17	1.19	41.36	54.00	12.64	Average
2389.94	32.00	8.17	1.12	41.29	54.00	12.71	Average
@ 2418.92	32.23	8.18	48.90	89.31	---	---	Average

Remark: The “@” means fundamental frequency, it is ignored in this section.


Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City244, Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303



Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
@ 2442.70	32.70	8.19	57.58	98.47	---	---	Peak
2483.50	32.57	8.20	9.73	50.50	74.00	23.50	Peak
2484.70	32.57	8.20	12.73	53.50	74.00	20.50	Peak



Antenna at Horizontal Polarization


Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
@ 2430.00	32.47	8.19	45.99	86.65	---	---	Average
2483.50	32.57	8.20	1.26	42.03	54.00	11.97	Average
2483.80	32.57	8.20	1.21	41.98	54.00	12.02	Average

Remark: The “@” means fundamental frequency, it is ignored in this section.

Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City244, Taiwan


Tel: +886 2 26099301
Fax: +886 2 26099303

Mode	802.11ax-HE40	Frequency	TX 2447MHz
------	---------------	-----------	------------



Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
@ 2444.60	32.70	8.19	61.10	101.99	---	---	Peak
2483.50	32.57	8.20	14.93	55.70	74.00	18.30	Peak
2484.90	32.57	8.20	18.61	59.38	74.00	14.62	Peak




Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
@ 2435.20	32.47	8.19	49.81	90.47	---	---	Average
2483.50	32.57	8.20	4.81	45.58	54.00	8.42	Average
2483.80	32.57	8.20	5.00	45.77	54.00	8.23	Average

Remark: The “@” means fundamental frequency, it is ignored in this section.


Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City 244, Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303



Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
@ 2438.70	32.70	8.19	57.41	98.30	---	---	Peak
2483.50	32.57	8.20	6.13	46.90	74.00	27.10	Peak
2492.50	32.50	8.21	8.44	49.15	74.00	24.85	Peak




Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
@ 2443.60	32.70	8.19	44.01	84.90	---	---	Average
2483.50	32.57	8.20	-3.25	37.52	54.00	16.48	Average
2483.90	32.57	8.20	-3.16	37.61	54.00	16.39	Average

Remark: The “@” means fundamental frequency, it is ignored in this section.


Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City244, Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303



Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
@ 2447.30	32.70	8.19	60.13	101.02	---	---	Peak
2483.50	32.57	8.20	13.43	54.20	74.00	19.80	Peak
2494.40	32.50	8.21	12.92	53.63	74.00	20.37	Peak




Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
@ 2439.60	32.70	8.19	47.91	88.80	---	---	Average
2483.50	32.57	8.20	0.31	41.08	54.00	12.92	Average
2484.20	32.57	8.20	0.11	40.88	54.00	13.12	Average

Remark: The "@" means fundamental frequency, it is ignored in this section.


Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City244, Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303



Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
@ 2452.60	32.70	8.19	51.53	92.42	---	---	Peak
2483.50	32.57	8.20	9.33	50.10	74.00	23.90	Peak
2483.90	32.57	8.20	9.22	49.99	74.00	24.01	Peak




Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
@ 2442.40	32.70	8.19	40.47	81.36	---	---	Average
2483.50	32.57	8.20	-1.80	38.97	54.00	15.03	Average
2483.80	32.57	8.20	-2.61	38.16	54.00	15.84	Average

Remark: The “@” means fundamental frequency, it is ignored in this section.


Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City244, Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303



Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
@ 2446.00	32.70	8.19	55.69	96.58	---	---	Peak
2483.50	32.57	8.20	14.47	55.24	74.00	18.76	Peak
2484.00	32.57	8.20	12.58	53.35	74.00	20.65	Peak




Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
@ 2443.90	32.70	8.19	44.23	85.12	---	---	Average
2483.50	32.57	8.20	2.01	42.78	54.00	11.22	Average
2483.80	32.57	8.20	1.04	41.81	54.00	12.19	Average

Remark: The "@" means fundamental frequency, it is ignored in this section.


Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City244, Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303



Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
@ 2446.10	32.70	8.19	43.80	84.69	---	---	Peak
2483.50	32.57	8.20	7.67	48.44	74.00	25.56	Peak
2492.50	32.50	8.21	7.25	47.96	74.00	26.04	Peak




Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
@ 2446.20	32.70	8.19	32.20	73.09	---	---	Average
2483.50	32.57	8.20	-6.05	34.72	54.00	19.28	Average
2483.90	32.57	8.20	-6.28	34.49	54.00	19.51	Average

Remark: The “@” means fundamental frequency, it is ignored in this section.


Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City 244, Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303



Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
@ 2449.40	32.70	8.19	48.00	88.89	---	---	Peak
2483.50	32.57	8.20	10.97	51.74	74.00	22.26	Peak
2483.80	32.57	8.20	11.64	52.41	74.00	21.59	Peak



Antenna at Vertical Polarization


Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
@ 2445.60	32.70	8.19	36.23	77.12	---	---	Average
2483.50	32.57	8.20	-4.55	36.22	54.00	17.78	Average
2483.90	32.57	8.20	-4.77	36.00	54.00	18.00	Average

Remark: The "@" means fundamental frequency, it is ignored in this section.

Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City244, Taiwan


Tel: +886 2 26099301
Fax: +886 2 26099303

Mode	802.11ax-HE20	Frequency	TX 2412MHz
		RU Config	26/0



Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2388.60	32.00	8.17	19.86	60.03	74.00	13.97	Peak
2390.04	32.00	8.17	12.54	52.71	74.00	21.29	Peak
@ 2403.72	32.23	8.18	68.97	109.38	---	---	Peak



Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2387.16	32.00	8.17	1.91	42.08	54.00	11.92	Average
2390.04	32.00	8.17	2.75	42.92	54.00	11.08	Average
@ 2403.48	32.23	8.18	60.10	100.51	---	---	Average


Remark: The “@” means fundamental frequency, it is ignored in this section.

File Number: CIM1909186

Report Number: EM-F190339


This test report may be reproduced in full only. The document may only be updated by Audix Technology Corp. personnel. Any changes will be noted in the Document History section of the report.

Mode	802.11ax-HE20	Frequency	TX 2412MHz
		RU Config	26/0



Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2388.48	32.00	8.17	23.13	63.30	74.00	10.70	Peak
2390.04	32.00	8.17	16.16	56.33	74.00	17.67	Peak
@ 2403.72	32.23	8.18	73.11	113.52	---	---	Peak



Antenna at Vertical Polarization


Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2387.04	32.00	8.17	2.99	43.16	54.00	10.84	Average
2390.04	32.00	8.17	4.38	44.55	54.00	9.45	Average
@ 2403.72	32.23	8.18	64.26	104.67	---	---	Average

Remark: The "@" means fundamental frequency, it is ignored in this section.

Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City 244, Taiwan


Tel: +886 2 26099301
Fax: +886 2 26099303

Mode	802.11ax-HE20	Frequency	TX 2412MHz
		RU Config	52/37



Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2377.32	32.00	8.17	29.85	70.02	74.00	3.98	Peak
2390.04	32.00	8.17	25.96	66.13	74.00	7.87	Peak
@ 2403.36	32.23	8.18	69.97	110.38	---	---	Peak



Antenna at Horizontal Polarization


Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2389.56	32.00	8.17	2.19	42.36	54.00	11.64	Average
2390.04	32.00	8.17	2.28	42.45	54.00	11.55	Average
@ 2404.80	32.23	8.18	55.70	96.11	---	---	Average

Remark: The "@" means fundamental frequency, it is ignored in this section.

Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City 244, Taiwan


Tel: +886 2 26099301
Fax: +886 2 26099303

Mode	802.11ax-HE20	Frequency	TX 2412MHz
		RU Config	52/37



Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2374.92	32.00	8.17	31.80	71.97	74.00	2.03	Peak
2390.04	32.00	8.17	29.55	69.72	74.00	4.28	Peak
@ 2403.60	32.23	8.18	73.65	114.06	---	---	Peak



Antenna at Vertical Polarization


Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2389.68	32.00	8.17	2.58	42.75	54.00	11.25	Average
2390.04	32.00	8.17	3.63	43.80	54.00	10.20	Average
@ 2405.28	32.23	8.18	60.14	100.55	---	---	Average

Remark: The "@" means fundamental frequency, it is ignored in this section.

Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City 244, Taiwan


Tel: +886 2 26099301
Fax: +886 2 26099303

Mode	802.11ax-HE20	Frequency	TX 2412MHz
		RU Config	106/53



Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2365.56	32.00	8.16	14.88	55.04	74.00	18.96	Peak
2390.04	32.00	8.17	13.63	53.80	74.00	20.20	Peak
@ 2410.20	32.23	8.18	64.10	104.51	---	---	Peak



Antenna at Horizontal Polarization


Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2389.56	32.00	8.17	2.22	42.39	54.00	11.61	Average
2390.04	32.00	8.17	2.43	42.60	54.00	11.40	Average
@ 2404.80	32.23	8.18	52.93	93.34	---	---	Average

Remark: The "@" means fundamental frequency, it is ignored in this section.

Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City 244, Taiwan


Tel: +886 2 26099301
Fax: +886 2 26099303

Mode	802.11ax-HE20	Frequency	TX 2412MHz
		RU Config	106/53



Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2388.96	32.00	8.17	19.16	59.33	74.00	14.67	Peak
2390.04	32.00	8.17	14.40	54.57	74.00	19.43	Peak
@ 2409.24	32.23	8.18	68.64	109.05	---	---	Peak



Antenna at Vertical Polarization


Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2389.56	32.00	8.17	3.12	43.29	54.00	10.71	Average
2390.04	32.00	8.17	3.48	43.65	54.00	10.35	Average
@ 2409.24	32.23	8.18	57.50	97.91	---	---	Average

Remark: The "@" means fundamental frequency, it is ignored in this section.

Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City244, Taiwan


Tel: +886 2 26099301
Fax: +886 2 26099303

Mode	802.11ax-HE20	Frequency	TX 2472MHz
		RU Config	26/8



Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
@ 2480.20	32.57	8.20	47.00	87.77	---	---	Peak
2483.50	32.57	8.20	9.02	49.79	74.00	24.21	Peak
2508.90	32.30	8.22	7.44	47.96	74.00	26.04	Peak



Antenna at Horizontal Polarization


Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
@ 2480.30	32.57	8.20	36.48	77.25	---	---	Average
2483.50	32.57	8.20	-5.69	35.08	54.00	18.92	Average
2485.00	32.57	8.20	-5.87	34.90	54.00	19.10	Average

Remark: The "@" means fundamental frequency, it is ignored in this section.

Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City 244, Taiwan


Tel: +886 2 26099301
Fax: +886 2 26099303

Mode	802.11ax-HE20	Frequency	TX 2472MHz
		RU Config	26/8



Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
@ 2479.90	32.57	8.20	53.77	94.54	---	---	Peak
2483.50	32.57	8.20	16.14	56.91	74.00	17.09	Peak
2501.80	32.50	8.21	15.17	55.88	74.00	18.12	Peak



Antenna at Vertical Polarization


Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
@ 2480.20	32.57	8.20	42.46	83.23	---	---	Average
2483.50	32.57	8.20	2.45	43.22	54.00	10.78	Average
2483.80	32.57	8.20	2.14	42.91	54.00	11.09	Average

Remark: The "@" means fundamental frequency, it is ignored in this section.

Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City244, Taiwan


Tel: +886 2 26099301
Fax: +886 2 26099303

Mode	802.11ax-HE20	Frequency	TX 2472MHz
		RU Config	52/40



Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
@ 2478.40	32.57	8.20	46.94	87.71	---	---	Peak
2483.50	32.57	8.20	6.35	47.12	74.00	26.88	Peak
2518.70	32.30	8.22	7.87	48.39	74.00	25.61	Peak




Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
@ 2479.40	32.57	8.20	34.14	74.91	---	---	Average
2483.50	32.57	8.20	-5.85	34.92	54.00	19.08	Average
2489.70	32.50	8.21	-5.76	34.95	54.00	19.05	Average


Remark: The "@" means fundamental frequency, it is ignored in this section.

Mode	802.11ax-HE20	Frequency	TX 2472MHz
		RU Config	52/40



Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
@ 2480.20	32.57	8.20	51.63	92.40	---	---	Peak
2483.50	32.57	8.20	12.96	53.73	74.00	20.27	Peak
2484.20	32.57	8.20	8.56	49.33	74.00	24.67	Peak




Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
@ 2479.70	32.57	8.20	39.59	80.36	---	---	Average
2483.50	32.57	8.20	-4.95	35.82	54.00	18.18	Average
2483.80	32.57	8.20	-5.63	35.14	54.00	18.86	Average


Remark: The "@" means fundamental frequency, it is ignored in this section.

Mode	802.11ax-HE20	Frequency	TX 2472MHz
		RU Config	106/54



Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
@ 2476.20	32.57	8.20	44.97	85.74	---	---	Peak
2483.50	32.57	8.20	5.08	45.85	74.00	28.15	Peak
2504.90	32.30	8.22	6.54	47.06	74.00	26.94	Peak



Antenna at Horizontal Polarization


Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
@ 2474.80	32.57	8.20	33.60	74.37	---	---	Average
2483.50	32.57	8.20	-6.42	34.35	54.00	19.65	Average
2490.80	32.50	8.21	-6.54	34.17	54.00	19.83	Average

Remark: The "@" means fundamental frequency, it is ignored in this section.

Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City244, Taiwan


Tel: +886 2 26099301
Fax: +886 2 26099303

Mode	802.11ax-HE20	Frequency	TX 2472MHz
		RU Config	106/54



Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
@ 2477.80	32.57	8.20	48.52	89.29	---	---	Peak
2483.50	32.57	8.20	11.67	52.44	74.00	21.56	Peak
2484.10	32.57	8.20	8.55	49.32	74.00	24.68	Peak



Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
@ 2478.90	32.57	8.20	36.84	77.61	---	---	Average
2483.50	32.57	8.20	-5.54	35.23	54.00	18.77	Average
2513.30	32.30	8.22	-5.87	34.65	54.00	19.35	Average

Remark: The “@” means fundamental frequency, it is ignored in this section.

File Number: CIM1909186


Report Number: EM-F190339

This test report may be reproduced in full only. The document may only be updated by Audix Technology Corp. personnel. Any changes will be noted in the Document History section of the report.

Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City244, Taiwan


Tel: +886 2 26099301
Fax: +886 2 26099303

Mode	802.11ax-HE40	Frequency	TX 2422MHz
		RU Config	242/61



Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2389.24	32.00	8.17	25.46	65.63	74.00	8.37	Peak
2389.94	32.00	8.17	25.35	65.52	74.00	8.48	Peak
@ 2417.10	32.23	8.18	62.81	103.22	---	---	Peak



Antenna at Horizontal Polarization


Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2389.24	32.00	8.17	1.93	42.10	54.00	11.90	Average
2389.94	32.00	8.17	2.18	42.35	54.00	11.65	Average
@ 2413.74	32.23	8.18	49.32	89.73	---	---	Average

Remark: The "@" means fundamental frequency, it is ignored in this section.

Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City 244, Taiwan


Tel: +886 2 26099301
Fax: +886 2 26099303

Mode	802.11ax-HE40	Frequency	TX 2422MHz
		RU Config	242/61



Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2389.38	32.00	8.17	26.49	66.66	74.00	7.34	Peak
2389.94	32.00	8.17	27.23	67.40	74.00	6.60	Peak
@ 2412.20	32.23	8.18	66.58	106.99	---	---	Peak




Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2389.52	32.00	8.17	5.87	46.04	54.00	7.96	Average
2389.94	32.00	8.17	6.24	46.41	54.00	7.59	Average
@ 2416.12	32.23	8.18	53.92	94.33	---	---	Average


Remark: The "@" means fundamental frequency, it is ignored in this section.

Mode	802.11ax-HE40	Frequency	TX 2462MHz
		RU Config	242/62



Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
@ 2470.60	32.57	8.20	45.10	85.87	---	---	Peak
2483.50	32.57	8.20	12.60	53.37	74.00	20.63	Peak
2485.70	32.57	8.20	16.36	57.13	74.00	16.87	Peak



Antenna at Horizontal Polarization


Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
@ 2470.10	32.63	8.20	34.17	75.00	---	---	Average
2483.50	32.57	8.20	1.20	41.97	54.00	12.03	Average
2491.20	32.50	8.21	1.59	42.30	54.00	11.70	Average

Remark: The "@" means fundamental frequency, it is ignored in this section.

Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City 244, Taiwan


Tel: +886 2 26099301
Fax: +886 2 26099303

Mode	802.11ax-HE40	Frequency	TX 2462MHz
		RU Config	242/62



Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
@ 2466.00	32.63	8.20	49.45	90.28	---	---	Peak
2483.50	32.57	8.20	23.17	63.94	74.00	10.06	Peak
2483.90	32.57	8.20	21.44	62.21	74.00	11.79	Peak



Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
@ 2467.20	32.63	8.20	37.72	78.55	---	---	Average
2483.50	32.57	8.20	1.97	42.74	54.00	11.26	Average
2483.90	32.57	8.20	1.75	42.52	54.00	11.48	Average

Remark: The "@" means fundamental frequency, it is ignored in this section.


File Number: CIM1909186

Report Number: EM-F190339

This test report may be reproduced in full only. The document may only be updated by Audix Technology Corp. personnel. Any changes will be noted in the Document History section of the report.


Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City244, Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303



Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2351.16	32.00	8.16	8.28	48.44	74.00	25.56	Peak
2390.04	32.00	8.17	6.07	46.24	74.00	27.76	Peak
@ 2401.68	32.00	8.17	50.49	90.66	---	---	Peak




Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2317.20	32.00	8.15	-4.01	36.14	54.00	17.86	Average
2390.04	32.00	8.17	-4.86	35.31	54.00	18.69	Average
@ 2402.04	32.00	8.17	50.08	90.25	---	---	Average

Remark: The “@” means fundamental frequency, it is ignored in this section.


Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City244, Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303



Antenna at Vertical Polarization


Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2339.76	32.00	8.16	8.50	48.66	74.00	25.34	Peak
2390.04	32.00	8.17	6.11	46.28	74.00	27.72	Peak
@ 2402.28	32.00	8.17	54.32	94.49	---	---	Peak



Antenna at Vertical Polarization


Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2314.20	32.00	8.15	-4.00	36.15	54.00	17.85	Average
2390.04	32.00	8.17	-4.71	35.46	54.00	18.54	Average
@ 2402.04	32.00	8.17	53.80	93.97	---	---	Average

Remark: The “@” means fundamental frequency, it is ignored in this section.



Antenna at Horizontal Polarization


Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
@ 2480.20	32.57	8.20	48.63	89.40	---	---	Peak
2483.50	32.57	8.20	5.25	46.02	74.00	27.98	Peak
2495.50	32.50	8.21	7.35	48.06	74.00	25.94	Peak



Antenna at Horizontal Polarization


Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
@ 2480.00	32.57	8.20	47.85	88.62	---	---	Average
2483.50	32.57	8.20	-5.48	35.29	54.00	18.71	Average
2496.40	32.50	8.21	-5.14	35.57	54.00	18.43	Average

Remark: The "@" means fundamental frequency, it is ignored in this section.



Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
@ 2480.20	32.57	8.20	55.02	95.79	---	---	Peak
2483.50	32.57	8.20	6.69	47.46	74.00	26.54	Peak
2487.40	32.57	8.20	7.70	48.47	74.00	25.53	Peak



Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
@ 2480.00	32.57	8.20	54.48	95.25	---	---	Average
2483.50	32.57	8.20	-3.91	36.86	54.00	17.14	Average
2487.40	32.57	8.20	-4.44	36.33	54.00	17.67	Average

Remark: The "@" means fundamental frequency, it is ignored in this section.

A.2.2 Emissions outside the frequency band:

The emissions (up to 25GHz) not reported for there is no emission be found.

Test SKU: SKU #2

Mode	802.11b	Frequency	TX 2442MHz
------	---------	-----------	------------

Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
4884.00	34.37	10.38	-3.05	41.70	54.00	12.30	Peak

Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
4884.00	34.37	10.38	-0.55	44.20	54.00	9.80	Peak

Mode	802.11g	Frequency	TX 2442MHz
------	---------	-----------	------------

Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
4884.00	34.37	10.38	-3.17	41.58	54.00	12.42	Peak

Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
4884.00	34.37	10.38	-3.05	41.70	54.00	12.30	Peak

Mode	802.11n-HT20	Frequency	TX 2442MHz
------	--------------	-----------	------------

Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
4884.00	34.37	10.38	-2.43	42.32	54.00	11.68	Peak

Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
4884.00	34.37	10.38	-1.66	43.09	54.00	10.91	Peak

Mode	802.11n-HT40	Frequency	TX 2447MHz
------	--------------	-----------	------------

Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
4894.00	34.50	10.40	-3.18	41.72	54.00	12.28	Peak

Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
4894.00	34.50	10.40	-2.31	42.59	54.00	11.41	Peak

Mode	802.11ax-HE20	Frequency	TX 2442MHz
------	---------------	-----------	------------

Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
4884.00	34.37	10.38	-3.69	41.06	54.00	12.94	Peak

Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
4884.00	34.37	10.38	-2.19	42.56	54.00	11.44	Peak

Audix Technology Corp.

No. 53-11, Dingfu, Linkou, Dist.,

New Taipei City 244, Taiwan

Tel: +886 2 26099301**Fax: +886 2 26099303**

Mode	802.11ax-HE40	Frequency	TX 2442MHz
------	---------------	-----------	------------

Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
4884.00	34.37	10.38	-3.06	41.69	54.00	12.31	Peak

Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
4884.00	34.37	10.38	-3.41	41.34	54.00	12.66	Peak

Mode	BLE	Frequency	TX 2402MHz
------	-----	-----------	------------

Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
4804.00	33.90	10.32	-2.42	41.80	54.00	12.20	Peak

Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
4804.00	33.90	10.32	-2.66	41.56	54.00	12.44	Peak

Mode	BLE	Frequency	TX 2440MHz
------	-----	-----------	------------

Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
4880.00	34.37	10.38	-3.32	41.43	54.00	12.57	Peak

Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
4880.00	34.37	10.38	-1.94	42.81	54.00	11.19	Peak

Mode	BLE	Frequency	TX 2480MHz
------	-----	-----------	------------

Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
4960.00	34.27	10.46	-1.12	43.61	54.00	10.39	Peak

Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
4960.00	34.27	10.46	-1.74	42.99	54.00	11.01	Peak

Test SKU: SKU #1

Mode	802.11n-HT20	Frequency	TX 2442MHz
------	--------------	-----------	------------

Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
4884.00	34.37	10.38	-2.05	42.70	54.00	11.30	Peak

Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
4884.00	34.37	10.38	-1.63	43.12	54.00	10.88	Peak

Mode	BLE	Frequency	TX 2440MHz
------	-----	-----------	------------

Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
4880.00	34.37	10.38	-3.66	41.09	54.00	12.91	Peak

Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
4880.00	34.37	10.38	-2.98	41.77	54.00	12.23	Peak

A.2.3 Emissions in Non-restricted Frequency Bands:

Pursuant to ANSI C63.10:2013 that emission levels below the FCC 15.209(a)/RSS-Gen Section 8.9 table 4 general radiated emissions limits is not required.

A.3 6dB/OCCUPIED BANDWIDTH

Test Date	2019/09/19 ~ 25	Temp./Hum.	24~25°C/50~54%
Test Voltage	AC 120V, 60Hz (via AC Adapter)	Tested By	Martin Chen
Cable Loss	0.5dB	Test Model	15Z90N

A.3.1 Emission Bandwidth Result

Mode	Centre Frequency (MHz)	6 dB Bandwidth (MHz)	Occupied (99%) Bandwidth (MHz)	Limit
802.11b	2412	10.14	13.386	>500kHz
	2442	10.14	13.444	
	2462	10.14	13.398	
	2472	10.14	13.854	
802.11g	2412	16.38	16.607	
	2442	16.40	16.800	
	2462	16.38	16.678	
	2472	16.38	16.370	
802.11n-HT20	2412	17.62	17.781	
	2442	17.62	17.812	
	2462	17.62	17.794	
	2472	17.62	17.594	
802.11n-HT40	2422	36.40	36.208	
	2442	36.40	36.231	
	2452	36.36	36.187	
	2462	36.36	36.106	
802.11ax-HE20	2412	18.98	18.978	
	2442	18.85	18.988	
	2462	18.85	19.011	
	2472	18.63	18.708	
802.11ax-HE40	2422	38.01	37.753	
	2442	38.02	37.729	
	2452	38.03	37.740	
	2462	37.77	37.474	

Audix Technology Corp.

No. 53-11, Dingfu, Linkou, Dist.,

New Taipei City 244, Taiwan

Tel: +886 2 26099301**Fax: +886 2 26099303**

Mode	RU Config	Centre Frequency (MHz)	6 dB Bandwidth (MHz)	Occupied (99%) Bandwidth (MHz)	Limit
802.11ax-HE20	26/0	2412	2.063	18.272	>500kHz
	52/37		14.48	18.129	
	106/53		17.19	18.198	
	26/8	2472	2.032	18.036	
	52/40		16.96	17.940	
	106/54		17.04	17.965	
802.11ax-HE40	242/61	2422	18.88	18.740	
	242/62	2462	18.58	18.513	

Mode	Centre Frequency (MHz)	6 dB Bandwidth (MHz)	Occupied (99%) Bandwidth (MHz)	Limit
BLE	2402	0.6760	1.0648	>500kHz
	2440	0.6844	1.0613	
	2480	0.6956	1.0633	

A.3.2 Measurement Plots

