

客戶名稱：**LG 15Z90RT**
CUSTOMER

Document No.:
Approval Sheet Rev.: P1
Spec. Rev. : P2

承認書

APPROVAL SHEET

Product Model No. : **WA-P-LELE-04-044**

LGE P/N. : **EAA65983501**

Maker P/N: **15Z90RT**

产品描述/Product Model No.: **WIFI Antenna**

发行日期/ Issue Date : **2022/12/19**

承認日期/ Approved Date : **2022/12/19**

Approved by customer: (signing or stamping here)



佳邦科技股份有限公司
INPAQ TECHNOLOGY CO., LTD.

■ 350 苗栗縣竹南鎮公義里11鄰科義街11號 □ 428 台中市大雅區科雅路27號4樓

電話：037-585-555

電話：04-2560-6555

傳真：037-585-511

傳真：04-2560-5151

No. 11, Ke-Yi St., Chunan, Miaoli 350,
Taiwan, R.O.C.

4F, No. 27, Keya Road, Daya Dist., Taichung City
428, Taiwan, R.O.C.

Tel. : +886-37-585-555

Tel. : +886-4-25606555

Fax : +886-37-585-511

Fax : +886-4-25605151

WA-P-LELE-04-044 Specification

1. Explanation of part number :

WA - P - LELE - 04 - 044
(1) (2) (3) (4) (5)

(1) Product Type : Wireless Antenna

(2) PCB: PCB+CABLE

(3) Frequency : 2400~2500MHz&5100~5800MHz&5925~7125MHz

(4) Coaxial Cable Type : With ϕ 0.81 Main Black / AUX Gray

(5) Suffix : 044

2. Storage Condition:

Temperature -40 to +85°C

Humidity 20 to 90% RH

Recommended storage condition :

Store in room condition as listed below: Temperature -20°C~+45°C, Humidity 80% Max

3. Operating Condition:

Temperature -40 to +70°C

Humidity 10 to 85 %RH

4. Electrical Specification :

Those specifications were specially defined for LG 14Z90RS WIFI model, and all characteristics were measured under the model's handset testing jig .

4-1. Frequency Band:

Frequency Band	MHz
WIFI\BT	2400~2500 & 5100~5800 & 5925~7125

UNLESS OTHER SPECIFIED TOLERANCES ON :

X = $\pm$ X.X = $\pm$ X.XX = $\pm$

ANGLES = $\pm$ HOLEDIA = $\pm$

SCALE : UNIT : mm

DRAWN BY: 尹猛 CHECKED BY: 李志强

DESIGNED BY: 钱龙 APPROVED BY: 唐龙

TITLE : WA-P-LELE-04-044 Specification



佳邦科技股份有限公司
INPAQ TECHNOLOGY CO., LTD.

THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF INPAQ TECHNOLOGY CO.,LTD.AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION

DOCUMENT
NO.

PAGE REV.
P2

4-2. Impedance

50 ohm nominal

4-3. Matching circuit

None

4-4. VSWR

4-4.1 Measuring Method

1.A 50Ωcoaxial cable is connected to the antenna. Then this cable is connected to a network analyzer to measure the VSWR

2.Keeping this jig away from metal at least 20cm

4-4.2 Measurement frequency points and VSWR value

VSWR	Frequency (Unit MHz)	Spec	1
Main Antenna	2400	≤ 3.0	1.3
	2500	≤ 3.0	2.3
	5150	≤ 4.0	1.5
	7125	≤ 4.0	1.8
	Judgement		ok
Aux Antenna	2400	≤ 3.0	1.7
	2500	≤ 3.0	1.7
	5150	≤ 4.0	2.0
	7125	≤ 4.0	1.5
	Judgement		ok

UNLESS OTHER SPECIFIED TOLERANCES ON :

X = ± X.X = ± X.XX = ±

ANGLES = ± HOLEDIA = ±

SCALE : UNIT : mm

DRAWN BY: 尹猛 CHECKED BY: 李志强

DESIGNED BY: 钱龙 APPROVED BY: 唐龙



佳邦科技股份有限公司

INPAQ TECHNOLOGY CO., LTD.


THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF INPAQ TECHNOLOGY CO.,LTD.AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION

TITLE : WA-P-LELE-04-044 Specification


DOCUMENT
NO.

PAGE REV.
P2

Main Antenna-1



AUX Antenna-1




4-5. Efficiency and Gain

4-5.1 Measure method

1. Using a low loss coaxial cable to link a standard handset jig
2. Fixed this handset jig on chamber's rotator plane
3. Linking jig into network analyzer port and using a probing horn antenna to collect data.
4. Using another standard gain horn antenna to calibrated those data

4-5.2 Chamber definition



1. An anechoic chamber

(8mx4mx3.5m) which satisfied far-field condition was applied to avoid multi-path effect

2. The quite room region is 40cmx40cmx40cm at the center of rotator
3. The distance between DUT and standard antenna is 4.38 m
4. Probing antenna (9120D horn antenna) and standard gain horn antenna (BBHA9120 LPF 700MHz ~6GHz)

UNLESS OTHER SPECIFIED TOLERANCES ON :

X = ±

X.X = ±

X.XX = ±

ANGLES = ±

HOLEDIA = ±

SCALE :

UNIT : mm

DRAWN BY: 尹猛

CHECKED BY: 李志强

DESIGNED BY: 钱龙

APPROVED BY: 唐龙

TITLE : WA-P-LELE-04-044 Specification



佳邦科技股份有限公司
INPAQ TECHNOLOGY CO., LTD.

THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF INPAQ TECHNOLOGY CO.,LTD.AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION

DOCUMENT
NO.

PAGE REV.
P2

4-5.3 Efficiency and Gain

Antenna gain is marked (dBi) and is based on STANDARD HORN antenna. The data shows Peak Gain and Average Gain.

4-5-3-1 Electrical specification

Frequency (MHz)	Average Efficiency (%)
2400~2500	>40
5100~5825	>30
5925~7125	>20

4-5.3-2 Efficiency and Gain Test Data

Frequency (MHz)	Main-Antenna-1		
	Efficiency (%)	Efficiency (dBi)	Peak Gain (dBi)
2400	56	-2.5	3.2
2450	56.8	-2.5	3.6
2500	47.4	-3.2	3.3
5150	42.5	-3.7	1.9
5470	31.6	-5	2.7
5850	30.1	-5.2	1.3
5925	37.2	-4.3	1.6
6525	25.4	-6	-0.5
7125	45.8	-3.4	3.9

Frequency (MHz)	Aux-Antenna-1		
	Efficiency (%)	Efficiency (dBi)	Peak Gain (dBi)
2400	50	-3	3.7
2450	51.8	-2.9	3.9
2500	46.3	-3.3	4.2
5150	31.4	-5	2.4
5470	38.9	-4.1	1.1
5850	33.2	-4.8	1.1
5925	37.2	-4.3	1.6
6525	24.7	-6.1	0.3
7125	39.4	-4	3

UNLESS OTHER SPECIFIED TOLERANCES ON :

X = $\pm$ X.X = $\pm$ X.XX = $\pm$

ANGLES = $\pm$ HOLEDIA = $\pm$

SCALE : UNIT : mm

DRAWN BY: 尹猛 CHECKED BY: 李志强

DESIGNED BY: 钱龙 APPROVED BY: 唐龙

TITLE : WA-P-LELE-04-044 Specification



佳邦科技股份有限公司
INPAQ TECHNOLOGY CO., LTD.

THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF INPAQ TECHNOLOGY CO.,LTD.AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION


DOCUMENT
NO.

PAGE REV.
P2


2. Antenna Test Results

2.4 Antenna Radiation Pattern


Main Antenna-1



2450MHz



5470MHz




6525MHz


2. Antenna Test Results

2.4 Antenna Radiation Pattern


AUX Antenna-1



2450MHz



5470MHz



6525MHz