

A.6 POWER SPECTRAL DENSITY

Test Date	2025/02/06~24	Temp./Hum.	19~20°C/55~65%
Cable Loss	2.35dB	Tested By	Sean Wang
Test Voltage	AC 120V 60Hz (Via AC Adapter)		

A.6.1 Power Spectral Density Result

Mode	Centre Frequency (MHz)	Power Spectral Density (dBm)		MAX. Power Spectral Density (dBm) ^{Note 2}	Limit
		AUX	Main		
802.11b	2412	-6.16	-5.51	-5.51	<8 dBm/3kHz
	2442	-6.06	-5.50	-5.50	
	2462	-6.02	-5.65	-5.65	
	2472	-6.10	-5.67	-5.67	
802.11g	2412	-7.42	-6.24	-6.24	
	2442	-7.52	-5.95	-5.95	
	2462	-7.18	-6.39	-6.39	
	2472	-11.58	-9.58	-9.58	

Note: 1. All results have been included cable loss.

2. MAX. Power Spectral Density (dBm) = Max of each Power Spectral Density (dBm).

3. We only presented max result (worst case) plots for each test mode.

Audix Technology Corp.
No. 491, Zhongfu Rd., Linkou Dist.,
New Taipei City 244, Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303

Mode	Centre Frequency (MHz)	Power Spectral Density (dBm)		Total Power Spectral Density (dBm) ^{Note 2}	Limit
		AUX	Main		
802.11n-HT20	2412	-7.20	-6.17	-3.64	<8 dBm/3kHz
	2442	-7.11	-7.23	-4.16	
	2462	-7.21	-7.74	-4.46	
	2472	-12.84	-12.75	-9.78	
802.11n-HT40	2422	-9.43	-8.97	-6.18	
	2442	-9.57	-9.12	-6.33	
	2452	-9.10	-9.99	-6.51	
	2462	-14.26	-13.80	-11.01	
802.11ax-HE20	2412	-8.33	-7.59	-4.93	
	2442	-6.99	-7.50	-4.23	
	2462	-8.69	-7.40	-4.99	
	2472	-13.48	-14.12	-10.78	
802.11ax-HE40	2422	-9.87	-9.42	-6.63	
	2442	-9.77	-10.03	-6.89	
	2452	-9.78	-9.28	-6.51	
	2462	-14.38	-15.28	-11.80	
802.11be-EHT20	2412	-7.23	-6.58	-3.88	
	2442	-7.53	-6.13	-3.76	
	2462	-8.68	-7.35	-4.95	
	2472	-12.99	-13.21	-10.09	
802.11be-EHT40	2422	-10.00	-10.22	-7.10	
	2442	-9.46	-11.06	-7.18	
	2452	-9.42	-9.86	-6.62	
	2462	-14.88	-15.31	-12.08	

Note: 1. All results have been included cable loss.

2. According to KDB 662911 D01 E)2)a), Total Power Spectral Density (dBm) = Sum to individual Power Spectral Density (dBm).

3. We only presented max result (worst case) plots for each test mode.

Audix Technology Corp.
No. 491, Zhongfu Rd., Linkou Dist.,
New Taipei City244, Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303

Mode	Centre Frequency (MHz)	RU Config	Power Spectral Density (dBm)		Total Power Spectral Density (dBm) ^{Note 2}	Limit
			AUX	Main		
802.11ax-HE20	2412	26/0	0.59	1.27	3.95	<8 dBm/3kHz
		52/37	-1.64	-0.79	1.82	
		106/53	-4.98	-4.31	-1.62	
	2472	26/8	-12.94	-13.10	-10.01	
		52/40	-15.70	-17.47	-13.49	
		106/54	-12.57	-13.26	-9.89	
802.11ax-HE40	2422	242/61	-7.00	-6.85	-3.91	
	2462	242/62	-12.50	-13.49	-9.96	
802.11be-EHT20	2412	26/0	0.28	1.05	3.69	
		52/37	-1.40	-2.09	1.28	
		106/53	-5.03	-5.13	-2.07	
	2472	26/8	-11.63	-13.13	-9.31	
		52/40	-16.01	-15.82	-12.90	
		106/54	-13.00	-13.47	-10.22	
802.11be-EHT20	2422	242/61	-7.15	-7.40	-4.26	
	2462	242/62	-13.53	-13.15	-10.33	

Note: 1. All results have been included cable loss.

2. According to KDB 662911 D01 E)2)a), Total Power Spectral Density (dBm) = Sum to individual Power Spectral Density (dBm).

3. We only presented max result (worst case) plots for each test mode.

Mode	Center Frequency (MHz)	Power Spectral Density (dBm)	Limit
BLE (2Mbps)	2402	-4.14	<8 dBm/3kHz
	2440	-3.82	
	2480	-3.87	


Note: 1. All results have been included cable loss.

2. We only presented max result (worst case) plots for this test mode.


Audix Technology Corp.
No. 491, Zhongfu Rd., Linkou Dist.,
New Taipei City244, Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303


A.6.2 Measurement Plots



Note: All results have been included cable loss.




Note: All results have been included cable loss.



Note: All results have been included cable loss.

Audix Technology Corp.
No. 491, Zhongfu Rd., Linkou Dist.,
New Taipei City244, Taiwan


Tel: +886 2 26099301
Fax: +886 2 26099303



Note: All results have been included cable loss.

Audix Technology Corp.
No. 491, Zhongfu Rd., Linkou Dist.,
New Taipei City244, Taiwan


Tel: +886 2 26099301
Fax: +886 2 26099303



Note: All results have been included cable loss.

Audix Technology Corp.
No. 491, Zhongfu Rd., Linkou Dist.,
New Taipei City244, Taiwan


Tel: +886 2 26099301
Fax: +886 2 26099303




Note: All results have been included cable loss.

Audix Technology Corp.
No. 491, Zhongfu Rd., Linkou Dist.,
New Taipei City244, Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303



Note: All results have been included cable loss.



Note: All results have been included cable loss.