




Audix Technology Corp.
No. 491, Zhongfu Rd., Linkou Dist.,
New Taipei City244, Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303









Audix Technology Corp.
No. 491, Zhongfu Rd., Linkou Dist.,
New Taipei City244, Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303






Audix Technology Corp.
No. 491, Zhongfu Rd., Linkou Dist.,
New Taipei City244, Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303

Antenna: LUXSHARE-ICT

AUX




Audix Technology Corp.


No. 491, Zhongfu Rd., Linkou Dist.,

New Taipei City244, Taiwan

Tel: +886 2 26099301


Fax: +886 2 26099303






Audix Technology Corp.
No. 491, Zhongfu Rd., Linkou Dist.,
New Taipei City244, Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303




Audix Technology Corp.
No. 491, Zhongfu Rd., Linkou Dist.,
New Taipei City244, Taiwan


Tel: +886 2 26099301
Fax: +886 2 26099303



Audix Technology Corp.
No. 491, Zhongfu Rd., Linkou Dist.,
New Taipei City244, Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303






Audix Technology Corp.

No. 491, Zhongfu Rd., Linkou Dist.,

New Taipei City244, Taiwan

Tel: +886 2 26099301

Fax: +886 2 26099303



Audix Technology Corp.
No. 491, Zhongfu Rd., Linkou Dist.,
New Taipei City244, Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303

A.8 CONTENTION BASED PROTOCOL

Test Date	2024/11/14 ~ 19	Temp./Hum.	24°C/55 ~ 60%
Cable Loss	N/A	Tested By	Sam Chang
Test Voltage	AC 120V 60Hz (Via AC Adapter)		

A.8.1 Contention-based Protocol

- Contention-based Protocol Threshold Incumbent Signal & Mini. Detection level

Antenna: INPAQ

Mode	U-NII Band	EUT Frequency (MHz)	AWGN Frequency (MHz)	Injected AWGN Power (dBm)	Min. Antenna Gain (Include path loss) (dBi) *Note1	Adjusted Power (dBm)	Detection Limit (dBm)	EUT Tx Status
802.11be-EHT20	5	6135	6135	-79.78	1.00	-80.78	-62	OFF
			6135	-87.78	1.00	-88.78	-62	Minimum
			6135	-89.78	1.00	-90.78	-62	ON
	6	6455	6455	-77.30	1.00	-78.30	-62	OFF
			6455	-85.30	1.00	-86.30	-62	Minimum
			6455	-87.30	1.00	-88.30	-62	ON
	7	6695	6695	-76.84	1.00	-77.84	-62	OFF
			6695	-82.84	1.00	-83.84	-62	Minimum
			6695	-83.84	1.00	-84.84	-62	ON
	8	7015	7015	-77.92	1.00	-78.92	-62	OFF
			7015	-84.92	1.00	-85.92	-62	Minimum
			7015	-86.92	1.00	-87.92	-62	ON

Note 1: the listed Min. gain of EUT was included path loss.

Note 2: Detected level (Adjusted Power) = Injected AWGN Power (dBm) – (Antenna Gain (dBi) + Path loss (dB)) *Note1.

Note 3: The AWGN level is reported for the following conditions:

- OFF = AWGN level at which no transmission is detected, consistently for a minimum period of 10 seconds.
- Minimal: AWGN level at which the system begins to trigger the transmission switch-off, albeit not being kept off consistently.
- ON = AWGN level at which no impact on the transmission is detected, consistently for a minimum period of 10 seconds.

Note 4: The EUT don't support channel puncturing or BW reduction mechanism.

Note 5: Per FCC TCB workshop April 2022, The Injected AWGN power is actual power of AWGN injected into the antenna port.

Audix Technology Corp.
No. 491, Zhongfu Rd., Linkou Dist.,
New Taipei City244, Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303

Mode	U-NII Band	EUT Frequency (MHz)	AWGN Frequency (MHz)	Injected AWGN Power (dBm)	Min. Antenna Gain (Include path loss) (dBi) *Note1	Adjusted Power (dBm)	Detection Limit (dBm)	EUT Tx Status
802.11be-EHT320	5	6105	5950	-77.96	1.00	-78.96	-62	OFF
			5950	-81.96	1.00	-82.96	-62	Minimum
			5950	-82.96	1.00	-83.96	-62	ON
			6105	-78.63	1.00	-79.63	-62	OFF
			6105	-82.63	1.00	-83.63	-62	Minimum
			6105	-83.63	1.00	-84.63	-62	ON
			6260	-80.23	1.00	-81.23	-62	OFF
			6260	-83.23	1.00	-84.23	-62	Minimum
	5/6/7	6425	6260	-84.23	1.00	-85.23	-62	ON
			6270	-75.98	1.00	-76.98	-62	OFF
			6270	-79.98	1.00	-80.98	-62	Minimum
			6270	-80.98	1.00	-81.98	-62	ON
			6425	-73.96	1.00	-74.96	-62	OFF
			6425	-79.96	1.00	-80.96	-62	Minimum
			6425	-80.96	1.00	-81.96	-62	ON
			6580	-76.51	1.00	-77.51	-62	OFF
	7/8	6745	6580	-79.51	1.00	-80.51	-62	Minimum
			6580	-81.51	1.00	-82.51	-62	ON
			6590	-79.55	1.00	-80.55	-62	OFF
			6590	-82.55	1.00	-83.55	-62	Minimum
			6590	-84.55	1.00	-85.55	-62	ON
			6745	-75.91	1.00	-76.91	-62	OFF
			6745	-80.91	1.00	-81.91	-62	Minimum
			6745	-81.91	1.00	-82.91	-62	ON
	7/8	6905	6900	-76.67	1.00	-77.67	-62	OFF
			6900	-79.67	1.00	-80.67	-62	Minimum
			6900	-80.67	1.00	-81.67	-62	ON
			6750	-77.94	1.00	-78.94	-62	OFF
			6750	-81.94	1.00	-82.94	-62	Minimum
			6750	-82.94	1.00	-83.94	-62	ON
			6905	-74.67	1.00	-75.67	-62	OFF
			6905	-78.67	1.00	-79.67	-62	Minimum
			6905	-80.67	1.00	-81.67	-62	ON
			7060	-76.91	1.00	-77.91	-62	OFF
			7060	-79.91	1.00	-80.91	-62	Minimum
			7060	-80.91	1.00	-81.91	-62	ON

Note 1: the listed Min. gain of EUT was included path loss.

Note 2: Detected level (Adjusted Power) = Injected AWGN Power (dBm) – (Antenna Gain (dBi) + Path loss (dB)) *Note1.

Note 3: The AWGN level is reported for the following conditions:

- OFF = AWGN level at which no transmission is detected, consistently for a minimum period of 10 seconds.
- Minimal: AWGN level at which the system begins to trigger the transmission switch-off, albeit not being kept off consistently.
- ON = AWGN level at which no impact on the transmission is detected, consistently for a minimum period of 10 seconds.

Note 4: The EUT don't support channel puncturing or BW reduction mechanism.

Note 5: Per FCC TCB workshop April 2022, The Injected AWGN power is actual power of AWGN injected into the antenna port.

Audix Technology Corp.
No. 491, Zhongfu Rd., Linkou Dist.,
New Taipei City244, Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303

Antenna: LUXSHARE-ICT

Mode	U-NII Band	EUT Frequency (MHz)	AWGN Frequency (MHz)	Injected AWGN Power (dBm)	Min. Antenna Gain (Include path loss) (dBi) *Note1	Adjusted Power (dBm)	Detection Limit (dBm)	EUT Tx Status
802.11be-EHT20	5	6135	6135	-79.78	-3.80	-75.98	-62	OFF
			6135	-87.78	-3.80	-83.98	-62	Minimum
			6135	-89.78	-3.80	-85.98	-62	ON
	6	6455	6455	-77.30	-3.80	-73.50	-62	OFF
			6455	-85.30	-3.80	-81.50	-62	Minimum
			6455	-87.30	-3.80	-83.50	-62	ON
	7	6695	6695	-76.84	-3.80	-73.04	-62	OFF
			6695	-82.84	-3.80	-79.04	-62	Minimum
			6695	-83.84	-3.80	-80.04	-62	ON
	8	7015	7015	-77.92	-3.80	-74.12	-62	OFF
			7015	-84.92	-3.80	-81.12	-62	Minimum
			7015	-86.92	-3.80	-83.12	-62	ON

Note 1: the listed Min. gain of EUT was included path loss.

Note 2: Detected level (Adjusted Power) = Injected AWGN Power (dBm) – (Antenna Gain (dBi) + Path loss (dB)) *Note1.

Note 3: The AWGN level is reported for the following conditions:

- OFF = AWGN level at which no transmission is detected, consistently for a minimum period of 10 seconds.
- Minimal: AWGN level at which the system begins to trigger the transmission switch-off, albeit not being kept off consistently.
- ON = AWGN level at which no impact on the transmission is detected, consistently for a minimum period of 10 seconds.

Note 4: The EUT don't support channel puncturing or BW reduction mechanism.

Note 5: Per FCC TCB workshop April 2022, The Injected AWGN power is actual power of AWGN injected into the antenna port.

Audix Technology Corp.
No. 491, Zhongfu Rd., Linkou Dist.,
New Taipei City244, Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303

Mode	U-NII Band	EUT Frequency (MHz)	AWGN Frequency (MHz)	Injected AWGN Power (dBm)	Min. Antenna Gain (Include path loss) (dBi) *Note1	Adjusted Power (dBm)	Detection Limit (dBm)	EUT Tx Status
802.11be-EHT320	5	6105	5950	-77.96	-3.80	-74.16	-62	OFF
			5950	-81.96	-3.80	-78.16	-62	Minimum
			5950	-82.96	-3.80	-79.16	-62	ON
			6105	-78.63	-3.80	-74.83	-62	OFF
			6105	-82.63	-3.80	-78.83	-62	Minimum
			6105	-84.63	-3.80	-80.83	-62	ON
			6260	-79.23	-3.80	-75.43	-62	OFF
			6260	-83.23	-3.80	-79.43	-62	Minimum
			6260	-84.23	-3.80	-80.43	-62	ON
	5/6/7	6425	6270	-75.98	-3.80	-72.18	-62	OFF
			6270	-79.98	-3.80	-76.18	-62	Minimum
			6270	-80.98	-3.80	-77.18	-62	ON
			6425	-73.96	-3.80	-70.16	-62	OFF
			6425	-79.96	-3.80	-76.16	-62	Minimum
			6425	-80.96	-3.80	-77.16	-62	ON
			6580	-76.51	-3.80	-72.71	-62	OFF
			6580	-79.51	-3.80	-75.71	-62	Minimum
			6580	-81.51	-3.80	-77.71	-62	ON
	7/8	6745	6590	-79.55	-3.80	-75.75	-62	OFF
			6590	-82.55	-3.80	-78.75	-62	Minimum
			6590	-84.55	-3.80	-80.75	-62	ON
			6745	-75.91	-3.80	-72.11	-62	OFF
			6745	-80.91	-3.80	-77.11	-62	Minimum
			6745	-81.91	-3.80	-78.11	-62	ON
			6900	-76.67	-3.80	-72.87	-62	OFF
			6900	-79.67	-3.80	-75.87	-62	Minimum
			6900	-80.67	-3.80	-76.87	-62	ON
	7/8	6905	6750	-77.94	-3.80	-74.14	-62	OFF
			6750	-81.94	-3.80	-78.14	-62	Minimum
			6750	-82.94	-3.80	-79.14	-62	ON
			6905	-74.67	-3.80	-70.87	-62	OFF
			6905	-78.67	-3.80	-74.87	-62	Minimum
			6905	-80.67	-3.80	-76.87	-62	ON
			7060	-76.91	-3.80	-73.11	-62	OFF
			7060	-79.91	-3.80	-76.11	-62	Minimum
			7060	-80.91	-3.80	-77.11	-62	ON

Note 1: the listed Min. gain of EUT was included path loss.

Note 2: Detected level (Adjusted Power) = Injected AWGN Power (dBm) – (Antenna Gain (dBi) + Path loss (dB)) *Note1.

Note 3: The AWGN level is reported for the following conditions:

- OFF = AWGN level at which no transmission is detected, consistently for a minimum period of 10 seconds.
- Minimal: AWGN level at which the system begins to trigger the transmission switch-off, albeit not being kept off consistently.
- ON = AWGN level at which no impact on the transmission is detected, consistently for a minimum period of 10 seconds.

Note 4: The EUT don't support channel puncturing or BW reduction mechanism.

Note 5: Per FCC TCB workshop April 2022, The Injected AWGN power is actual power of AWGN injected into the antenna port.

Audix Technology Corp.
No. 491, Zhongfu Rd., Linkou Dist.,
New Taipei City244, Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303

● Summary table

Antenna: INPAQ

Mode	U-NII Band	Centre Frequency (MHz)	Incumbent Frequency (MHz)	1	2	3	4	5	6	7	8	9	10	Detection Possibility (%)	Limit (%)
802.11be-EHT20	5	6135	6135	1	1	1	1	1	1	1	1	1	1	100	90
	6	6455	6455	1	1	1	1	1	1	1	1	1	1	100	90
	7	6695	6695	1	1	1	1	1	1	1	1	1	1	100	90
	8	7015	7015	1	1	1	1	1	1	1	1	1	1	100	90
802.11be-EHT320	5	6105	5950	1	1	1	1	1	1	1	1	1	1	100	90
			6105	1	1	1	1	1	1	1	1	1	1	100	90
			6260	1	1	1	1	1	1	1	1	1	1	100	90
	5/6/7	6425	6270	1	1	1	1	1	1	1	1	1	1	100	90
			6425	1	1	1	1	1	1	1	1	1	1	100	90
			6580	1	1	1	1	1	1	1	1	1	1	100	90
	7/8	6745	6590	1	1	1	1	1	1	1	1	1	1	100	90
			6745	1	1	1	1	1	1	1	1	1	1	100	90
			6900	1	1	1	1	1	1	1	1	1	1	100	90
	7/8	6905	6750	1	1	1	1	1	1	1	1	1	1	100	90
			6905	1	1	1	1	1	1	1	1	1	1	100	90
			7060	1	1	1	1	1	1	1	1	1	1	100	90

Note: CBP Detection Trials (1= Detection, 0= No Detection)

Antenna: LUXSHARE-ICT

Mode	U-NII Band	Centre Frequency (MHz)	Incumbent Frequency (MHz)	1	2	3	4	5	6	7	8	9	10	Detection Possibility (%)	Limit (%)
802.11be-EHT20	5	6135	6135	1	1	1	1	1	1	1	1	1	1	100	90
	6	6455	6455	1	1	1	1	1	1	1	1	1	1	100	90
	7	6695	6695	1	1	1	1	1	1	1	1	1	1	100	90
	8	7015	7015	1	1	1	1	1	1	1	1	1	1	100	90
802.11be-EHT320	5	6105	6094	1	1	1	1	1	1	1	1	1	1	100	90
			6105	1	1	1	1	1	1	1	1	1	1	100	90
			6260	1	1	1	1	1	1	1	1	1	1	100	90
	5/6/7	6425	6270	1	1	1	1	1	1	1	1	1	1	100	90
			6425	1	1	1	1	1	1	1	1	1	1	100	90
			6580	1	1	1	1	1	1	1	1	1	1	100	90
	7/8	6745	6590	1	1	1	1	1	1	1	1	1	1	100	90
			6745	1	1	1	1	1	1	1	1	1	1	100	90
			6900	1	1	1	1	1	1	1	1	1	1	100	90
	7/8	6905	6750	1	1	1	1	1	1	1	1	1	1	100	90
			6905	1	1	1	1	1	1	1	1	1	1	100	90
			7060	1	1	1	1	1	1	1	1	1	1	100	90

Note: CBP Detection Trials (1= Detection, 0= No Detection)

Audix Technology Corp.



No. 491, Zhongfu Rd., Linkou Dist.,

New Taipei City 244, Taiwan

Tel: +886 2 26099301


Fax: +886 2 26099303

A.8.2 Measurement Plots



Audix Technology Corp.
No. 491, Zhongfu Rd., Linkou Dist.,
New Taipei City244, Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303



Audix Technology Corp.
No. 491, Zhongfu Rd., Linkou Dist.,
New Taipei City244, Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303

