

# SAR TEST REPORT

HCT CO., LTD

|                                                  |                                                                                                                                                                                                                                                                         |                                                                                                                                                    |
|--------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------|
| EUT Type:                                        | Cellular/PCS GSM/GPRS/EDGE/WCDMA/HSPA Phone with BT & WLAN<br>GPRS Class12 and GPRS mode class B(GPRS and GSM, but not simultaneously)                                                                                                                                  |                                                                                                                                                    |
| FCC ID:                                          | BEJP970H                                                                                                                                                                                                                                                                |                                                                                                                                                    |
| Model:                                           | LG-P970h                                                                                                                                                                                                                                                                |                                                                                                                                                    |
| Additional Model:                                | P970h                                                                                                                                                                                                                                                                   |                                                                                                                                                    |
| Date of Issue:                                   | Mar.17, 2011                                                                                                                                                                                                                                                            |                                                                                                                                                    |
| Test report No.:                                 | HCTA1102FS05-01                                                                                                                                                                                                                                                         |                                                                                                                                                    |
| Test Laboratory:                                 | <b>HCT CO., LTD.</b><br>SAN 136-1, AMI-RI, BUBAL-EUP, ICHEON-SI, KYOUNGKI-DO, 467-701, KOREA<br>TEL: +82 31 639 8565 FAX: +82 31 639 8525                                                                                                                               |                                                                                                                                                    |
| Applicant :                                      | <b>LG Electronics, Inc.</b><br>60-39, Gasan-Dong, Gumchon-Gu, Seoul 153-023, Korea<br>Tel: +82-2-2033-1113 Fax: +82-2-2033-1222                                                                                                                                         |                                                                                                                                                    |
| Testing has been carried out in accordance with: | RSS-102 Issue 4; Health Canada Safety Code 6<br>47CFR §2.1093<br>FCC OET Bulletin 65(Edition 97-01), Supplement C (Edition 01-01)<br>ANSI/ IEEE C95.1 – 2005<br>IEEE 1528-2003                                                                                          |                                                                                                                                                    |
| Test result:                                     | The tested device complies with the requirements in respect of all parameters subject to the test. The test results and statements relate only to the items tested. The test report shall not be reproduced except in full, without written approval of the laboratory. |                                                                                                                                                    |
| Signature                                        | <br><hr/> Report prepared by<br>: Young-Soo Jang<br>Test Engineer of SAR Part                                                                                                        | <br><hr/> Approved by<br>: Jae-Sang So<br>Manager of SAR Part |

# Table of Contents

|                                                                                                            |       |
|------------------------------------------------------------------------------------------------------------|-------|
| <b><u>1. INTRODUCTION</u></b> .....                                                                        | 3     |
| <b><u>2. DESCRIPTION OF DEVICE</u></b> .....                                                               | 4     |
| <b><u>3. DESCRIPTION OF TEST EQUIPMENT</u></b> .....                                                       | 5     |
| <b><u>4. SAR MEASUREMENT PROCEDURE</u></b> .....                                                           | 1 2   |
| <b><u>5. DESCRIPTION OF TEST POSITION</u></b> .....                                                        | 1 3   |
| 5.1 HEAD POSITION .....                                                                                    | 1 3   |
| 5.2 Body Holster/Belt Clip Configurations .....                                                            | 1 4   |
| <b><u>6. MEASUREMENT UNCERTAINTY</u></b> .....                                                             | 1 5   |
| <b><u>7. ANSI/ IEEE C95.1 - 2005 RF EXPOSURE LIMITS</u></b> .....                                          | 1 6   |
| <b><u>8. SYSTEM VERIFICATION</u></b> .....                                                                 | 1 7   |
| 8.1 Tissue Verification .....                                                                              | 1 7   |
| 8.2 System Validation .....                                                                                | 1 7   |
| <b><u>9. SAR Testing with IEEE 802.11 a/b/g Transmitters</u></b> .....                                     | 1 8   |
| <b><u>10. RF CONDUCTED POWER</u></b> .....                                                                 | 1 9   |
| 10.1 Procedures Used to Establish RF Signal for SAR .....                                                  | 1 9   |
| 10.2 SAR Measurement Conditions for UMTS .....                                                             | 1 9   |
| <b><u>11. Mobile Hotspot Side for SAR Testing</u></b> .....                                                | 2 2   |
| <b><u>12. SAR Evaluation Considerations for Handsets with Multiple Transmitters and Antennas</u></b> ..... | 2 3   |
| <b><u>13. SAR TEST DATA SUMMARY</u></b> .....                                                              | 2 5   |
| 13.1 Measurement Results (GSM850 Head SAR) .....                                                           | 2 5   |
| 13.2 Measurement Results (GSM1900 Head SAR) .....                                                          | 2 6   |
| 13.3 Measurement Results (WCDMA850 Head SAR) .....                                                         | 2 7   |
| 13.4 Measurement Results (WCDMA1900 Head SAR) .....                                                        | 2 8   |
| 13.5 Measurement Results (802.11b/g/n Module Head) .....                                                   | 2 9   |
| 13.6 Measurement Results (GSM850 Hotspot Body SAR) .....                                                   | 3 0   |
| 13.7 Measurement Results (GSM1900 Hotspot Body SAR) .....                                                  | 3 1   |
| 13.8 Measurement Results (WCDMA850 Hotspot Body SAR) .....                                                 | 3 2   |
| 13.9 Measurement Results (WCDMA1900 Hotspot Body SAR) .....                                                | 3 3   |
| 13.10 Measurement Results (802.11b/g/n Module Body SAR) .....                                              | 3 4   |
| <b><u>14. CONCLUSION</u></b> .....                                                                         | 3 5   |
| <b><u>15. REFERENCES</u></b> .....                                                                         | 3 6   |
| <b>Attachment 1. – SAR Test Plots</b> .....                                                                | 3 7   |
| <b>Attachment 2. – Dipole Validation Plots</b> .....                                                       | 1 1 7 |
| <b>Attachment 3. – Probe Calibration Data</b> .....                                                        | 1 1 7 |
| <b>Attachment 4. – Dipole Calibration Data</b> .....                                                       | 1 4 4 |

## 1. INTRODUCTION

The FCC has adopted the guidelines for evaluating the environmental effects of radio frequency radiation in ET Docket 93-62 on Aug. 6, 1996 to protect the public and workers from the potential hazards of RF emissions due to FCC-regulated portable devices.

The safety limits used for the environmental evaluation measurements are based on the criteria published by the American National Standards Institute (ANSI) for localized specific absorption rate (SAR) in IEEE/ANSI C95.1-2005 Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz. 1992 by the Institute of Electrical and Electronics Engineers, Inc., New York, New York 10017. The measurement procedure described in IEEE/ANSI C95.3-1992 Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields - RF and Microwave is used for guidance in measuring SAR due to the RF radiation exposure from the Equipment Under Test (EUT). These criteria for SAR evaluation are similar to those recommended by the National Council on Radiation Protection and Measurements (NCRP) in Biological Effects and Exposure Criteria for Radio frequency Electromagnetic Fields," NCRP Report No. 86 NCRP, 1986, Bethesda, MD 20814. SAR is a measure of the rate of energy absorption due to exposure to an RF transmitting source. SAR values have been related to threshold levels for potential biological hazards.

### SAR Definition

Specific Absorption Rate (SAR) is defined as the time derivative of the incremental electromagnetic energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dV) of a given density (ρ). It is also defined as the rate of RF energy absorption per unit mass at a point in an absorbing body.

$$SAR = \frac{d}{dt} \left( \frac{dU}{dm} \right) = \frac{d}{dt} \left( \frac{dU}{\rho dV} \right)$$

**Figure 2. SAR Mathematical Equation**

**SAR is expressed in units of Watts per Kilogram (W/kg).**

$$SAR = \sigma E^2 / \rho$$

where:

|          |   |                                                                   |
|----------|---|-------------------------------------------------------------------|
| $\sigma$ | = | conductivity of the tissue-simulant material (S/m)                |
| $\rho$   | = | mass density of the tissue-simulant material (kg/m <sup>3</sup> ) |
| $E$      | = | Total RMS electric field strength (V/m)                           |

NOTE: The primary factors that control rate of energy absorption were found to be the wavelength of the incident field in relations to the dimensions and geometry of the irradiated organism, the orientation of the organism in relation to the polarity of field vectors, the presence of reflecting surfaces, and whether conductive contact is made by the organism with a ground plane.

## 2. DESCRIPTION OF DEVICE

Environmental evaluation measurements of specific absorption rate (SAR) distributions in emulated human head and body tissues exposed to radio frequency (RF) radiation from wireless portable devices for compliance with the rules and regulations of the U.S. Federal Communications Commission (FCC).

|                                        |                                                                                                                                                                                                                                                                                                                             |                  |    |
|----------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------|----|
| EUT Type                               | Cellular/PCS GSM/GPRS/EDGE/WCDMA/HSPA Phone with BT & WLAN<br>GPRS Class 12and GPRS mode class B(GPRS and GSM, but not simultaneously)                                                                                                                                                                                      |                  |    |
| FCC ID:                                | BEJP970H                                                                                                                                                                                                                                                                                                                    |                  |    |
| Model:                                 | LG-P970h                                                                                                                                                                                                                                                                                                                    |                  |    |
| Additional Model:                      | P970h                                                                                                                                                                                                                                                                                                                       |                  |    |
| Trade Name                             | LG                                                                                                                                                                                                                                                                                                                          | Serial Number(s) | #1 |
| Application Type                       | Certification                                                                                                                                                                                                                                                                                                               |                  |    |
| Mode(s) of Operation                   | GSM850/GSM1900/ WCDMA 850/ WCDMA1900/802.11b/g/n                                                                                                                                                                                                                                                                            |                  |    |
| Tx Frequency                           | 824.20 - 848.80 MHz (GSM850)<br>1 850.20 – 1 909.80 MHz (GSM1900)<br>826.4~846.6 MHz (WCDMA850)<br>1 852.4 – 1 907.6 MHz (WCDMA1900)<br>2 412- 2 462 MHz (DSSS/ OFDM)                                                                                                                                                       |                  |    |
| Rx Frequency                           | 869.20 - 893.80 MHz (GSM850)<br>1 930.20 – 1 989.80 MHz (GSM1900)<br>871.4 - 891.6 MHz (WCDMA850)<br>1 932.4 – 1 987.6 MHz (WCDMA1900)<br>2 412- 2 462 MHz (DSSS/ OFDM)                                                                                                                                                     |                  |    |
| FCC Classification                     | Licensed Portable Transmitter Held to Ear (PCE)                                                                                                                                                                                                                                                                             |                  |    |
| Production Unit or Identical Prototype | Prototype                                                                                                                                                                                                                                                                                                                   |                  |    |
| Max SAR                                | 0.512 W/kg GSM850 Head SAR / 1.11 W/kg GSM850 Body SAR<br>0.669 W/kg GSM1900 Head SAR / 0.567 W/kg GSM1900 Body SAR<br>0.477 W/kg WCDMA850 Head SAR / 0.946 W/kg WCDMA850 Body SAR<br>0.991 W/kg WCDMA1900 Head SAR / 1.23 W/kg WCDMA1900 Body SAR<br>0.487 W/kg Wi-Fi 802.11b Head SAR / 0.201 W/kg Wi-Fi 802.11b Body SAR |                  |    |
| Date(s) of Tests                       | Feb. 23, 2011, Mar.14, 2011~ Mar.15, 2011                                                                                                                                                                                                                                                                                   |                  |    |
| Antenna Type                           | Intenna                                                                                                                                                                                                                                                                                                                     |                  |    |

## 3. DESCRIPTION OF TEST EQUIPMENT

### 3.1 SAR MEASUREMENT SETUP

These measurements are performed using the DASY4 automated dosimetric assessment system. It is made by Schmid & Partner Engineering AG (SPEAG) in Zurich, Switzerland. It consists of high precision robotics system (Staubli), robot controller, Pentium III computer, near-field probe, probe alignment sensor, and the generic twin phantom containing the brain equivalent material. The robot is a six-axis industrial robot performing precise movements to position the probe to the location (points) of maximum electromagnetic field (EMF) (see Figure.3.1).

A cell controller system contains the power supply, robot controller, teach pendant (Joystick), and remote control, is used to drive the robot motors. The PC consists of the HP Pentium IV 3.0 GHz computer with Windows XP system and SAR Measurement Software DASY4, A/D interface card, monitor, mouse, and keyboard. The Staubli Robot is connected to the cell controller to allow software manipulation of the robot. A data acquisition electronic (DAE) circuit performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. is connected to the Electro-optical coupler (EOC). The EOC performs the conversion from the optical into digital electric signal of the DAE and transfers data to the PC plug-in card.




Figure 3.1 HCT SAR Lab. Test Measurement Set-up

The DAE4 consists of a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD-converter and a command decoder and control logic unit. Transmission to the PC-card is accomplished through an optical downlink for data and status information and an optical uplink for commands and clock lines. The mechanical probe mounting device includes two different sensor systems for frontal and sidewise probe contacts. They are also used for mechanical surface detection and probe collision detection. The robot uses its own controller with a built in VME-bus computer. The system is described in detail in.

## 3.2 DASY4 E-FIELD PROBE SYSTEM

### 3.1 ES3DV3 Probe Specification

|               |                                                                                                                                                                                 |
|---------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Construction  | Symmetrical design with triangular core Interleaved sensors<br>Built-in shielding against static charges<br>PEEK enclosure material (resistant to organic solvents, e.g., DGBE) |
| Calibration   | Basic Broad Band Calibration in air<br>Conversion Factors (CF) for HSL 900 and HSL 1810<br>Additional CF for other liquids and frequencies upon request                         |
| Frequency     | 10 MHz to 4 GHz; Linearity: $\pm 0.2$ dB (30 MHz to 4 GHz)                                                                                                                      |
| Directivity   | $\pm 0.2$ dB in HSL (rotation around probe axis)<br>$\pm 0.3$ dB in tissue material (rotation normal to probe axis)                                                             |
| Dynamic Range | 5 $\mu$ W/g to > 100 mW/g; Linearity: $\pm 0.2$ dB                                                                                                                              |
| Dimensions    | Overall length: 330 mm (Tip: 20 mm)<br>Tip diameter: 3.9 mm (Body: 12 mm)<br>Distance from probe tip to dipole centers: 2.0 mm                                                  |
| Application   | General dosimetry up to 4 GHz<br>Dosimetry in strong gradient fields<br>Compliance tests of mobile phones                                                                       |




Figure 3.1 Photograph of the probe and the Phantom



Figure3.2 ES3DV3 E-field Probe

The SAR measurements were conducted with the dosimetric probe ES3DV3, designed in the classical triangular configuration and optimized for dosimetric evaluation. The probe is constructed using the thick film technique; with printed resistive lines on ceramic substrates. The probe is equipped with an optical multifiber line ending at the front of the probe tip. It is connected to the EOC box on the robot arm and provides an automatic detection of the phantom surface. Half of the fibers are connected to a pulsed infrared transmitter, the other half to a synchronized receiver. As the probe approaches the surface, the reflection from the surface produces a coupling from the transmitting to the receiving fibers. This reflection increases first during the approach, reaches a maximum and then decreases. If the probe is flatly touching the surface, the coupling is zero. The distance of the coupling maximum to the surface is independent of the surface reflectivity and largely independent of the surface to probe angle. The DASY4 software reads the reflection during a software approach and looks for the maximum using a 2<sup>nd</sup> order fitting. The approach is stopped at reaching the maximum.

## 3.3 PROBE CALIBRATION PROCESS

### 3.3.1 E-Probe Calibration

Each probe is calibrated according to a dosimetric assessment procedure with an accuracy better than  $\pm 10 \%$ . The spherical isotropy was evaluated with the proper procedure and found to be better than  $\pm 0.25$  dB. The sensitivity parameters (NormX, NormY, NormZ), the diode compression parameter (DCP) and the conversion factor (ConvF) of the probe is tested.

The free space E-field from amplified probe outputs is determined in a test chamber. This is performed in a TEM cell for frequencies below 1 GHz, and in a waveguide above 1 GHz for free space. For the free space calibration, the probe is placed in the volumetric center of the cavity and at the proper orientation with the field. The probe is then rotated 360 degrees.

E-field temperature correlation calibration is performed in a flat phantom filled with the appropriate simulated brain tissue. The measured free space E-field in the medium correlates to temperature rise in a dielectric medium. For temperature correlation calibration a RF transparent thermistor-based temperature probe is used in conjunction with the E-field probe.

$$SAR = C \frac{\Delta T}{\Delta t}$$

where:

- $\Delta t$  = exposure time (30 seconds),
- $C$  = heat capacity of tissue (brain or muscle),
- $\Delta T$  = temperature increase due to RF exposure.

SAR is proportional to  $\Delta T / \Delta t$ , the initial rate of tissue heating, before thermal diffusion takes place. Now it's possible to quantify the electric field in the simulated tissue by equating the thermally derived SAR to the E- field;

$$SAR = \frac{|E|^2 \cdot \sigma}{\rho}$$

where:

- $\sigma$  = simulated tissue conductivity,
- $\rho$  = Tissue density (1.25 g/cm<sup>3</sup> for brain tissue)




Figure 3.4 E-Field and Temperature measurements at 900 MHz




Figure 3.5 E-Field and temperature measurements at 1.8 GHz

### 3.3.2 Data Extrapolation

The DASY4 software automatically executes the following procedures to calculate the field units from the microvolt readings at the probe connector. The first step of the evaluation is a linearization of the filtered input signal to account for the compression characteristics of the detector diode. The compensation depends on the input signal, the diode type and the DC-transmission factor from the diode to the evaluation electronics. If the exciting field is pulsed, the crest factor of the signal must be known to correctly compensate for peak power. The formula for each channel can be given like below;

$$V_i = U_i + U_i^2 \cdot \frac{cf}{dcp_i}$$

with  $V_i$  = compensated signal of channel i (i=x,y,z)  
 $U_i$  = input signal of channel i (i=x,y,z)  
 $cf$  = crest factor of exciting field (DASY parameter)  
 $dcp_i$  = diode compression point (DASY parameter)

From the compensated input signals the primary field data for each channel can be evaluated:

E-field probes:

$$E_i = \sqrt{\frac{V_i}{Norm_i \cdot ConvF}}$$

with  $V_i$  = compensated signal of channel i (i = x,y,z)  
 $Norm_i$  = sensor sensitivity of channel i (i = x,y,z)  
 $\mu V/(V/m)^2$  for E-field probes  
 $ConvF$  = sensitivity of enhancement in solution  
 $E_i$  = electric field strength of channel i in V/m

The RSS value of the field components gives the total field strength (Hermetian magnitude):

$$E_{tot} = \sqrt{E_x^2 + E_y^2 + E_z^2}$$

The primary field data are used to calculate the derived field units.

$$SAR = E_{tot}^2 \cdot \frac{\sigma}{\rho \cdot 1000}$$

with  $SAR$  = local specific absorption rate in W/g  
 $E_{tot}$  = total field strength in V/m  
 $\sigma$  = conductivity in [mho/m] or [Siemens/m]  
 $\rho$  = equivalent tissue density in g/cm<sup>3</sup>

The power flow density is calculated assuming the excitation field to be a free space field.

$$P_{pwe} = \frac{E_{tot}^2}{3770}$$

with  $P_{pwe}$  = equivalent power density of a plane wave in W/cm<sup>2</sup>  
 $E_{tot}$  = total electric field strength in V/m

### **3.4 SAM Phantom**

The SAM Phantom is constructed of a fiberglass shell integrated in a wooden table. The shape of the shell is based on data from an anatomical study designed to determine the maximum exposure in at least 90 % of all users. It enables the dosimetric evaluation of left and right hand phone usage as well as body mounted usage at the flat phantom region. A cover prevents the evaporation of the liquid. Reference markings on the Phantom allow the complete setup of all predefined phantom positions and measurement grids by manually teaching three points in the robot.




Figure 3.6 SAM Phantom

|                 |                                        |
|-----------------|----------------------------------------|
| Shell Thickness | 2.0 mm                                 |
| Filling Volume  | about 30 L                             |
| Dimensions      | 810 mm x 1 000 mm x 500 mm (H x L x W) |

### **3.5 Device Holder for Transmitters**

In combination with the SAM Phantom V 4.0, the Mounting Device (POM) enables the rotation of the mounted transmitter in spherical coordinates whereby the rotation points is the ear opening. The devices can be easily, accurately, and repeatably positioned according to the FCC and CENELEC specifications. The device holder can be locked at different phantom locations (left head, right head, flat phantom).

Note: A simulating human hand is not used due to the complex anatomical and geometrical structure of the hand that may produced infinite number of configurations. To produce the Worst-case condition (the hand absorbs antenna output power), the hand is omitted during the tests.



Figure 3.7 Device Holder

### 3.6 Brain & Muscle Simulating Mixture Characterization

The brain and muscle mixtures consist of a viscous gel using hydrox-ethyl cellulose (HEC) gelling agent and saline solution (see Table 3.1). Preservation with a bactericide is added and visual inspection is made to make sure air bubbles are not trapped during the mixing process. The mixture is calibrated to obtain proper dielectric constant (permittivity) and conductivity of the desired tissue. The mixture characterizations used for the brain and muscle tissue simulating liquids are according to the data by C. Gabriel and G. Hartsgrove.

| Ingredients<br>(% by weight) | Frequency (MHz) |       |       |      |       |       |       |      |       |      |
|------------------------------|-----------------|-------|-------|------|-------|-------|-------|------|-------|------|
|                              | 450             |       | 835   |      | 915   |       | 1 900 |      | 2 450 |      |
| Tissue Type                  | Head            | Body  | Head  | Body | Head  | Body  | Head  | Body | Head  | Body |
| Water                        | 38.56           | 51.16 | 41.45 | 52.4 | 41.05 | 56.0  | 54.9  | 40.4 | 62.7  | 73.2 |
| Salt (NaCl)                  | 3.95            | 1.49  | 1.45  | 1.4  | 1.35  | 0.76  | 0.18  | 0.5  | 0.5   | 0.04 |
| Sugar                        | 56.32           | 46.78 | 56.0  | 45.0 | 56.5  | 41.76 | 0.0   | 58.0 | 0.0   | 0.0  |
| HEC                          | 0.98            | 0.52  | 1.0   | 1.0  | 1.0   | 1.21  | 0.0   | 1.0  | 0.0   | 0.0  |
| Bactericide                  | 0.19            | 0.05  | 0.1   | 0.1  | 0.1   | 0.27  | 0.0   | 0.1  | 0.0   | 0.0  |
| Triton X-100                 | 0.0             | 0.0   | 0.0   | 0.0  | 0.0   | 0.0   | 0.0   | 0.0  | 36.8  | 0.0  |
| DGBE                         | 0.0             | 0.0   | 0.0   | 0.0  | 0.0   | 0.0   | 44.92 | 0.0  | 0.0   | 26.7 |

|                           |                                                                    |        |                        |
|---------------------------|--------------------------------------------------------------------|--------|------------------------|
| Salt:                     | 99 % Pure Sodium Chloride                                          | Sugar: | 98 % Pure Sucrose      |
| Water:                    | De-ionized, 16M resistivity                                        | HEC:   | Hydroxyethyl Cellulose |
| DGBE:                     | 99 % Di(ethylene glycol) butyl ether,[2-(2-butoxyethoxy) ethanol]  |        |                        |
| Triton X-100(ultra pure): | Polyethylene glycol mono[4-(1,1,3,3-tetramethylbutyl)phenyl] ether |        |                        |

**Table 3.1 Composition of the Tissue Equivalent Matter**

### 3.7 SAR TEST EQUIPMENT

| Manufacturer | Type / Model                | S/N             | Calib. Date   | Calib.Interval | Calib.Due     |
|--------------|-----------------------------|-----------------|---------------|----------------|---------------|
| SPEAG        | SAM Phantom                 | -               | N/A           | N/A            | N/A           |
| Staubli      | Robot RX90L                 | F01/5K09A1/A/01 | N/A           | N/A            | N/A           |
| Staubli      | Robot ControllerCS7MB       | F99/5A82A1/C/01 | N/A           | N/A            | N/A           |
| HP           | Pavilion t000_puffer        | KRJ51201TV      | N/A           | N/A            | N/A           |
| SPEAG        | Light Alignment Sensor      | 265             | N/A           | N/A            | N/A           |
| Staubli      | Teach Pendant (Joystick)    | D221340.01      | N/A           | N/A            | N/A           |
| SPEAG        | DAE4                        | 869             | Sep 18, 2010  | Annual         | Sep 18, 2011  |
| SPEAG        | E-Field Probe ET3DV6        | 1630            | May 25, 2010  | Annual         | May 25, 2011  |
| SPEAG        | E-Field Probe ES3DV3        | 3161            | Mar 22, 2010  | Annual         | Mar 22, 2011  |
| SPEAG        | Validation Dipole D835V2    | 441             | May 21, 2010  | Annual         | May 21, 2011  |
| SPEAG        | Validation Dipole D1900V2   | 5d032           | July 16, 2010 | Annual         | July 16, 2011 |
| SPEAG        | Validation Dipole D2450V2   | 743             | Aug. 25, 2010 | Biennial       | Aug. 27, 2012 |
| Agilent      | Power Meter(F) E4419B       | MY41291386      | Nov. 05, 2010 | Annual         | Nov. 05, 2011 |
| Agilent      | Power Sensor(G) 8481        | MY41090870      | Nov. 05, 2010 | Annual         | Nov. 05, 2011 |
| HP           | Dielectric Probe Kit 85070C | 00721521        | N/A           | N/A            | N/A           |
| HP           | Dual Directional Coupler    | 16072           | Nov. 05, 2010 | Annual         | Nov. 05, 2011 |
| R&S          | Base Station CMU200         | 110740          | July 26, 2010 | Annual         | July 26, 2011 |
| Agilent      | Base Station E5515C         | GB44400269      | Feb. 10, 2011 | Annual         | Feb. 10, 2012 |
| HP           | Signal Generator E4438C     | MY42082646      | Nov. 11, 2010 | Annual         | Nov. 11, 2011 |
| HP           | Network Analyzer 8753ES     | MY4000025       | Sep. 02, 2010 | Annual         | Sep. 02, 2011 |

**NOTE:**

The E-field probe was calibrated by SPEAG, by the waveguide technique procedure. Dipole Validation measurement is performed by HCT Lab. before each test. The brain simulating material is calibrated by HCT using the dielectric probe system and network analyzer to determine the conductivity and permittivity (dielectric constant) of the brain-equivalent material.

## 4. SAR MEASUREMENT PROCEDURE

---

The evaluation was performed with the following procedure:

1. The SAR value at a fixed location above the ear point was measured and was used as a reference value for assessing the power drop.
2. The SAR distribution at the exposed side of the head was measured at a distance of 3.9 mm from the inner surface of the shell. The area covered the entire dimension of the head and the horizontal grid spacing was 20 mm x 20 mm. Based on this data, the area of the maximum absorption was determined by spline interpolation.
3. Around this point, a volume of 32 mm x 32 mm x 30 mm was assessed by measuring 5 x 5 x 7 points. On this basis of this data set, the spatial peak SAR value was evaluated with the following procedure:
  - a. The data at the surface were extrapolated, since the center of the dipoles is 2.7 mm away from the tip of the probe and the distance between the surface and the lowest measuring point is 1.2 mm. The extrapolation was based on a least square algorithm. A polynomial of the fourth order was calculated through the points in z-axes. This polynomial was then used to evaluate the points between the surface and the probe tip.
  - b. The maximum interpolated value was searched with a straight-forward algorithm. Around this maximum the SAR values averaged over the spatial volumes (1 g or 10 g) were computed using the 3D-Spline interpolation algorithm. The 3D-spline is composed of three one-dimensional splines with the "Not a knot" condition (in x, y, and z directions. The volume was integrated with the trapezoidal algorithm. One thousand points (10 x 10 x 10) were interpolated to calculate the average.
  - c. All neighboring volumes were evaluated until no neighboring volume with a higher average value was found.
4. The SAR value, at the same location as procedure #1, was re-measured. If the value changed by more than 5 %, the evaluation is repeated.




Figure 4.1 SAR Measurement Point in Area Scan

## 5. DESCRIPTION OF TEST POSITION

### 5.1 HEAD POSITION

The device was placed in a normal operating position with the Point A on the device, as illustrated in following drawing, aligned with the location of the RE(ERP) on the phantom. With the ear-piece pressed against the head, the vertical center line of the body of the handset was aligned with an imaginary plane consisting of the RE, LE and M. While maintaining these alignments, the body of the handset was gradually moved towards the cheek until any point on the mouth-piece or keypad contacted the cheek. This is a cheek/touch position. For ear/tilt position, while maintain the device aligned with the BM and FN lines, the device was pivot against ERP back for 15° or until the device antenna touch the phantom. Please refer to IEEE 1528-2003 illustration below.




Figure 5.1 Side view of the phantom




Figure 5.2 Handset vertical and horizontal reference lines

## **5.2 Body Holster/Belt Clip Configurations**

Body-worn operating configurations are tested with the belt-clips and holsters attached to the device and positioned against a flat phantom in a normal use configuration. A device with a headset output is tested with a headset connected to the device. Body dielectric parameters are used.

Accessories for Body-worn operation configurations are divided into two categories: those that do not contain metallic components and those that contain metallic components. When multiple accessories that do not contain metallic components are supplied with the device, the device is tested with only the accessory that dictates the closest spacing to the body. Then multiple accessories that contain metallic components are tested with each accessory. If multiple accessory share an identical metallic component (i.e. the same metallic belt-clip used with different holsters with no other metallic components) only the accessory that dictates the closest spacing to the body is tested.

Body-worn accessories may not always be supplied or available as options for some Devices intended to be authorized for body-worn use. In this case, a test configuration with a separation distance between the back of the device and the flat phantom is used.

Since this EUT does not supply any body worn accessory to the end user a distance of 1.0 cm from the EUT back surface to the liquid interface is configured for the generic test.

"See the Test SET-UP Photo"

Transmitters that are designed to operate in front of a person's face, as in push-to-talk configurations, are tested for SAR compliance with the front of the device positioned to face the flat phantom. For devices that are carried next to the body such as a shoulder, waist or chest-worn transmitters, SAR compliance is tested with the accessory(ies), including headsets and microphones, attached to the device and positioned against a flat phantom in a normal use configuration.

In all cases SAR measurements are performed to investigate the worst-case positioning. Worstcase positioning is then documented and used to perform Body SAR testing.

## 6. MEASUREMENT UNCERTAINTY

| Error Description                   | Tol<br>( $\pm$ %) | Prob.<br>dist. | Div. | $C_i$ | Standard<br>Uncertainty<br>( $\pm$ %) | $v_{eff}$ |
|-------------------------------------|-------------------|----------------|------|-------|---------------------------------------|-----------|
| <b>1. Measurement System</b>        |                   |                |      |       |                                       |           |
| Probe Calibration                   | 5.50              | N              | 1    | 1     | 5.50                                  | $\infty$  |
| Axial Isotropy                      | 4.70              | R              | 1.73 | 0.7   | 1.90                                  | $\infty$  |
| Hemispherical Isotropy              | 9.60              | R              | 1.73 | 0.7   | 3.88                                  | $\infty$  |
| Boundary Effects                    | 1.00              | R              | 1.73 | 1     | 0.58                                  | $\infty$  |
| Linearity                           | 4.70              | R              | 1.73 | 1     | 2.71                                  | $\infty$  |
| System Detection Limits             | 1.00              | R              | 1.73 | 1     | 0.58                                  | $\infty$  |
| Readout Electronics                 | 0.30              | N              | 1.00 | 1     | 0.30                                  | $\infty$  |
| Response Time                       | 0.8               | R              | 1.73 | 1     | 0.46                                  | $\infty$  |
| Integration Time                    | 2.6               | R              | 1.73 | 1     | 1.50                                  | $\infty$  |
| RF Ambient Noise                    | 3.00              | R              | 1.73 | 1     | 1.73                                  | $\infty$  |
| RF Ambient Reflection               | 3.00              | R              | 1.73 | 1     | 1.73                                  | $\infty$  |
| Probe Positioner                    | 0.40              | R              | 1.73 | 1     | 0.23                                  | $\infty$  |
| Probe Positioning                   | 2.90              | R              | 1.73 | 1     | 1.67                                  | $\infty$  |
| Max SAR Eval                        | 1.00              | R              | 1.73 | 1     | 0.58                                  | $\infty$  |
| <b>2. Test Sample Related</b>       |                   |                |      |       |                                       |           |
| Device Positioning                  | 1.80              | N              | 1.00 | 1     | 1.80                                  | 9         |
| Device Holder                       | 3.60              | N              | 1.00 | 1     | 3.60                                  | 5         |
| Power Drift                         | 5.00              | R              | 1.73 | 1     | 2.89                                  | $\infty$  |
| <b>3. Phantom and Setup</b>         |                   |                |      |       |                                       |           |
| Phantom Uncertainty                 | 4.00              | R              | 1.73 | 1     | 2.31                                  | $\infty$  |
| Liquid Conductivity(target)         | 5.00              | R              | 1.73 | 0.64  | 1.85                                  | $\infty$  |
| Liquid Conductivity(meas.)          | 2.07              | N              | 1    | 0.64  | 1.32                                  | 9         |
| Liquid Permittivity(target)         | 5.00              | R              | 1.73 | 0.6   | 1.73                                  | $\infty$  |
| Liquid Permittivity(meas.)          | 5.02              | N              | 1    | 0.6   | 3.01                                  | 9         |
| <b>Combine Standard Uncertainty</b> |                   |                |      |       | 10.76                                 |           |
| <b>Coverage Factor for 95 %</b>     |                   |                |      |       | $k=2$                                 |           |
| <b>Expanded STD Uncertainty</b>     |                   |                |      |       | 21.53                                 |           |

Table 6.1 Uncertainty (800 MHz- 2450 MHz)

## 7. ANSI/ IEEE C95.1 - 2005 RF EXPOSURE LIMITS

| HUMAN EXPOSURE                                         | UNCONTROLLED ENVIRONMENT<br>General Population<br>(W/kg) or (mW/g) | CONTROLLED ENVIRONMENT<br>Occupational<br>(W/kg) or (mW/g) |
|--------------------------------------------------------|--------------------------------------------------------------------|------------------------------------------------------------|
| SPATIAL PEAK SAR *<br>(Brain)                          | 1.60                                                               | 8.00                                                       |
| SPATIAL AVERAGE SAR **<br>(Whole Body)                 | 0.08                                                               | 0.40                                                       |
| SPATIAL PEAK SAR ***<br>(Hands / Feet / Ankle / Wrist) | 4.00                                                               | 20.00                                                      |

**Table 7.1 Safety Limits for Partial Body Exposure**

### NOTES:

\* The Spatial Peak value of the SAR averaged over any 1 g of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.

\*\* The Spatial Average value of the SAR averaged over the whole-body.

\*\*\* The Spatial Peak value of the SAR averaged over any 10 g of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.

**Uncontrolled Environments** are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure.

**Controlled Environments** are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e.as a result of employment or occupation).

## 8. SYSTEM VERIFICATION

### 8.1 Tissue Verification

| Freq. [MHz] | Date         | Liquid | Liquid Temp. [°C] | Parameters   | Target Value | Measured Value | Deviation [%] | Limit [%] |
|-------------|--------------|--------|-------------------|--------------|--------------|----------------|---------------|-----------|
| 835         | Mar.14, 2011 | Head   | 21.1              | $\epsilon_r$ | 41.5         | 43             | + 3.61        | $\pm 5$   |
|             |              |        |                   | $\sigma$     | 0.90         | 0.876          | - 2.67        | $\pm 5$   |
| 835         | Mar.14, 2011 | Body   | 21.1              | $\epsilon_r$ | 55.2         | 56.8           | + 2.90        | $\pm 5$   |
|             |              |        |                   | $\sigma$     | 0.97         | 0.98           | + 1.03        | $\pm 5$   |
| 1 900       | Mar.15, 2011 | Head   | 21.1              | $\epsilon_r$ | 40.0         | 41             | + 2.50        | $\pm 5$   |
|             |              |        |                   | $\sigma$     | 1.40         | 1.4            | 0.00          | $\pm 5$   |
| 1 900       | Mar.15, 2011 | Body   | 21.1              | $\epsilon_r$ | 53.3         | 52             | - 2.44        | $\pm 5$   |
|             |              |        |                   | $\sigma$     | 1.52         | 1.56           | + 2.63        | $\pm 5$   |
| 2 450       | Feb.23, 2011 | Head   | 21.1              | $\epsilon_r$ | 39.2         | 38.2           | - 2.55        | $\pm 5$   |
|             |              |        |                   | $\sigma$     | 1.80         | 1.87           | + 3.89        | $\pm 5$   |
| 2 450       | Feb.23, 2011 | Body   | 21.1              | $\epsilon_r$ | 52.7         | 51.6           | - 2.09        | $\pm 5$   |
|             |              |        |                   | $\sigma$     | 1.95         | 1.96           | + 0.51        | $\pm 5$   |

### 8.2 System Validation

Prior to assessment, the system is verified to the  $\pm 10\%$  of the specifications at 835 MHz / 1 900 MHz/ 2 450 MHz by using the system validation kit. (Graphic Plots Attached)

\* Input Power: 100 m W

| Freq. [MHz] | Date         | Liquid | Liquid Temp. [°C] | SAR Average | Target Value (SPEAG) (mW/g) | *Measured Value (mW/g) | Deviation [%] | Limit [%] |
|-------------|--------------|--------|-------------------|-------------|-----------------------------|------------------------|---------------|-----------|
| 835         | Mar.14, 2011 | Head   | 21.1              | 1 g         | 9.66                        | 0.974                  | + 0.83        | $\pm 10$  |
| 835         | Mar.14, 2011 | Body   | 21.1              | 1 g         | 9.92                        | 1.0                    | + 0.81        | $\pm 10$  |
| 1 900       | Mar.15, 2011 | Head   | 21.1              | 1 g         | 39.9                        | 4.04                   | + 1.25        | $\pm 10$  |
| 1 900       | Mar.15, 2011 | Body   | 21.1              | 1 g         | 41.5                        | 4.24                   | + 2.17        | $\pm 10$  |
| 2 450       | Feb.23, 2011 | Head   | 21.1              | 1 g         | 54                          | 5.57                   | + 3.15        | $\pm 10$  |
| 2 450       | Feb.23, 2011 | Body   | 21.1              | 1 g         | 54                          | 5.39                   | - 0.19        | $\pm 10$  |

## 9. SAR Testing with IEEE 802.11 a/b/g Transmitters

Normal Network operating configurations are not suitable for measuring the SAR of 802.11 a/b/g transmitters. Unpredictable fluctuations in network traffic and antenna diversity conditions can introduce undesirable variations in SAR results. The SAR for these devices should be measured using chipset based test mode software to ensure the results are consistent and reliable.

### 9.1 General Device Setup

Chipset based test mode software is hardware dependent and generally varies among manufacturers. The device operating parameters established in test mode for SAR measurements must be identical to those programmed in production units, including output power levels, amplifier gain settings and other RF performance tuning parameters. The test frequencies should correspond to actual channel frequencies defined for domestic use. SAR for devices with switched diversity should be measured with only one antenna transmitting at a time during each SAR measurement, according to a fixed modulation and data rate. The same data pattern should be used for all measurements.

### 9.2 Frequency Channel Configurations

80.11 a/b/g and 4.9 GHz operating modes are tested independently according to the service requirements in each frequency band. 80.211 b/g modes are tested on channels 1, 6 and 11. 802.11a is tested for UNII operations on channels 36 and 48 in the 5.15-5.25 GHz band; channels 52 and 64 in the 5.25-5.35 GHz band; Channels 104, 116, 124 and 136 in the 5.470-5.725 GHz band; and channels 149 and 161 in the 5.8 GHz band. When 5.8 GHz § 15.247 is also available, channels 149, 157 and 165 should be tested instead of the UNII channels. 4.9 GHz is tested on channels 1, 10 and 5 or 6, whichever has the higher output power, for 5 MHz channels; channels 11,15 and 19 for 10 MHz channels; and channels 21 and 25 for 20 MHz channels.

These are referred to as the "default test channels". 802.11g mode was evaluated only if the output power was 0.25 dB higher than the 802.11b mode.

| Mode                  | GHz     | Channel | Turbo Channel  | "Default Test Channels" |      |   |   |
|-----------------------|---------|---------|----------------|-------------------------|------|---|---|
|                       |         |         |                | §15.247                 | UNII |   |   |
| 802.11 b/g            | 2.412   | 1       |                | √                       | ▽    |   |   |
|                       | 2.437   | 6       | 6              | √                       | ▽    |   |   |
|                       | 2.462   | 11      |                | √                       | ▽    |   |   |
| 802.11a               | 5.18    | 36      |                |                         |      | √ |   |
|                       | 5.20    | 40      | 42 (5.21 GHz)  |                         |      |   | * |
|                       | 5.22    | 44      |                |                         |      |   | * |
|                       | 5.24    | 48      | 50 (5.25 GHz)  |                         |      | √ |   |
|                       | 5.26    | 52      |                |                         |      | √ |   |
|                       | 5.28    | 56      | 58 (5.29 GHz)  |                         |      |   | * |
|                       | 5.30    | 60      |                |                         |      |   | * |
|                       | 5.32    | 64      |                |                         |      | √ |   |
|                       | 5.500   | 100     | Unknown        |                         |      |   | * |
|                       | 5.520   | 104     |                |                         |      | √ |   |
|                       | 5.540   | 108     |                |                         |      |   | * |
|                       | 5.560   | 112     |                |                         |      |   | * |
|                       | 5.580   | 116     |                |                         |      | √ |   |
|                       | 5.600   | 120     |                |                         |      |   | * |
|                       | 5.620   | 124     |                |                         |      | √ |   |
|                       | 5.640   | 128     |                |                         |      |   | * |
|                       | 5.660   | 132     |                |                         |      |   | * |
|                       | 5.680   | 136     |                |                         |      | √ |   |
|                       | 5.700   | 140     |                |                         |      |   | * |
| UNII<br>or<br>§15.247 | 5.745   | 149     |                | √                       |      | √ |   |
|                       | 5.765   | 153     | 152 (5.76 GHz) |                         | *    |   | * |
|                       | 5.785   | 157     |                | √                       |      |   | * |
|                       | 5.805   | 161     | 160 (5.80 GHz) |                         | *    | √ |   |
|                       | §15.247 | 5.825   | 165            | √                       |      |   |   |

802.11 Test Channels per FCC Requirements

## 10. RF CONDUCTED POWER

Power measurements were performed using a base station simulator under digital average power

### 10.1 Procedures Used to Establish RF Signal for SAR

The handset was placed into a simulated call using a base station simulator in a shielded chamber. Such test signals offer a consistent means for testing SAR and are recommended for evaluation SAR[4] SAR measurements were taken with a fully charged battery. In order to verify that the device was tested and maintained at full power, this was configured with the base station simulator. The SAR measurement Software calculates a reference point at the start and end of the test to check for power drifts. If conducted Power deviations of more than 5 % occurred, the tests were repeated.

### 10.2 SAR Measurement Conditions for UMTS

Body SAR is not required for handsets with HSDPA capabilities when the maximum average output of each RF channel with HSDPA active is less than ¼ dB higher than that measured without HSDPA using 12.2 kbps RMC and the maximum SAR for 12.2 kbps RMC is  $\leq 75\%$  of the SAR limit. Otherwise, SAR is Measured for HSDPA, using an FRC with H-Set 1 in Sub-test 1 and a 12.2 kbps RMC configured in Test Loop Mode 1, using the highest body SAR configuration in 12.2 kbps RMC without HSDPA, on the maximum output channel with the body exposure configuration that results in the highest SAR in 12.2 kbps RMC for that RF channel.

#### 10.2.1 Output Power Verification

Maximum output power is verified on the High, Middle and Low channels according to the general descriptions in section 5.2 of 3 GPP TS 34.121, using the appropriate RMC or AMR with TPC(transmit power control) set to all "1s"

#### 10.2.2 Head SAR Measurements

SAR for head exposure configurations is measured using the 12.2 kbps RMC with TPC bits configured to all "1s". SAR in AMR configurations is not required when the maximum average output of each RF channel for 12.2 kbps AMR is less than ¼ dB higher than that measured in 12.2 kbps RMC. Otherwise, SAR is measured on the maximum output channel in 12.2 AMR with a 3.4 kbps SRB (signaling radio bearer) using the exposure configuration that results in the highest SAR for that RF channel in 12.2 RMC.

#### 10.2.3 Body SAR Measurement

SAR for body exposure configurations is measured using the 12.2 kbps RMC with the TPC bits all "1s".

#### 10.2.4 Handsets with Release 5 HSDPA

Body SAR is not required for handsets with HSDPA capabilities when the maximum average output of each RF channel with HSDPA active is less than ¼ dB higher than that measured without HSDPA using 12.2 kbps RMC and the maximum SAR for 12.2 kbps RMC is  $\leq 75\%$  of the SAR limit. Otherwise, SAR is Measured for HSDPA, using an FRC with H-Set 1 in Sub-test 1 and a 12.2 kbps RMC configured in Test Loop Mode 1, using the highest body SAR configuration in 12.2 kbps RMC without HSDPA, on the maximum output channel with the body exposure configuration that results in the highest SAR in 12.2 kbps RMC for that RF channel.

**Sub-Test 1 Setup for Release 5 HSDPA**

| Sub-test | $\beta_c$            | $\beta_d$            | $\beta_d$<br>(SF) | $\beta_c/\beta_d$    | $\beta_{hs}^{(1)}$ | CM (dB) <sup>(2)</sup> |
|----------|----------------------|----------------------|-------------------|----------------------|--------------------|------------------------|
| 1        | 2/15                 | 15/15                | 64                | 2/15                 | 4/15               | 0.0                    |
| 2        | 12/15 <sup>(3)</sup> | 15/15 <sup>(3)</sup> | 64                | 12/15 <sup>(3)</sup> | 24/15              | 1.0                    |
| 3        | 15/15                | 8/15                 | 64                | 15/8                 | 30/15              | 1.5                    |
| 4        | 15/15                | 4/15                 | 64                | 15/4                 | 30/15              | 1.5                    |

Note 1:  $\Delta_{ACK}$ ,  $\Delta_{NACK}$  and  $\Delta_{CQI} = 8 \Leftrightarrow A_{hs} = \beta_{hs}/\beta_c = 30/15 \Leftrightarrow \beta_{hs} = 30/15 * \beta_c$

Note 2: CM = 1 for  $\beta_c/\beta_d = 12/15$ ,  $\beta_{hs}/\beta_c = 24/15$ .

Note 3: For subtest 2 the  $\beta_c/\beta_d$  ratio of 12/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signaled gain factors for the reference TFC (TF1, TF1) to  $\beta_c = 11/15$  and  $\beta_d = 15/15$ .

## 10.2.5 Handsets with Release 6 HSPA (HSDPA/HSUPA)

Body SAR is not required for handsets with HSPA capabilities when the maximum average output of each RF channel with HSUPA/HSDPA active is less than ¼ dB higher than that measured without HSUPA/HSDPA using 12.2 kbps RMC and the maximum SAR for 12.2 kbps RMC is  $\leq 75\%$  of the SAR limit. Body SAR for HSPA is measured with E-DCH Sub-test 5, using H-Set 1 and QPSK for FRC and a 12.2 kbps RMC configured in Test Loop Mode 1 with power control algorithm 2, according to the highest body SAR configuration in 12.1 kbps RMC without HSPA. When VOIP is applicable for head exposure, SAR is not required when the maximum output of each RF channel with HSPA is less than ¼ dB higher than that measured using 12.2 kbps RMC; otherwise, the same HSPA configuration used for body measurement should be used to test for head exposure.

| Sub-test | $\beta_c$            | $\beta_d$            | $\beta_d$ (SF) | $\beta_c/\beta_d$    | $\beta_{hs}^{(1)}$ | $\beta_{ec}$ | $\beta_{ed}$                                 | $\beta_{ed}$ (SF) | $\beta_{ed}$ (codes) | CM <sup>(2)</sup> (dB) | MPR (dB) | AG <sup>(4)</sup> Index | E-TFCI |
|----------|----------------------|----------------------|----------------|----------------------|--------------------|--------------|----------------------------------------------|-------------------|----------------------|------------------------|----------|-------------------------|--------|
| 1        | 11/15 <sup>(3)</sup> | 15/15 <sup>(3)</sup> | 64             | 11/15 <sup>(3)</sup> | 22/15              | 209/225      | 1039/225                                     | 4                 | 1                    | 1.0                    | 0.0      | 20                      | 75     |
| 2        | 6/15                 | 15/15                | 64             | 6/15                 | 12/15              | 12/15        | 94/75                                        | 4                 | 1                    | 3.0                    | 2.0      | 12                      | 67     |
| 3        | 15/15                | 9/15                 | 64             | 15/9                 | 30/15              | 30/15        | $\beta_{ed1}: 47/15$<br>$\beta_{ed2}: 47/15$ | 4                 | 2                    | 2.0                    | 1.0      | 15                      | 92     |
| 4        | 2/15                 | 15/15                | 64             | 2/15                 | 4/15               | 2/15         | 56/75                                        | 4                 | 1                    | 3.0                    | 2.0      | 17                      | 71     |
| 5        | 15/15 <sup>(4)</sup> | 15/15 <sup>(4)</sup> | 64             | 15/15 <sup>(4)</sup> | 30/15              | 24/15        | 134/15                                       | 4                 | 1                    | 1.0                    | 0.0      | 21                      | 81     |

Note 1:  $\Delta_{ACK}$ ,  $\Delta_{NACK}$  and  $\Delta_{CQI} = 8 \Leftrightarrow A_{hs} = \beta_{hs}/\beta_c = 30/15 \Leftrightarrow \beta_{hs} = 30/15 * \beta_c$ .  
Note 2: CM = 1 for  $\beta_c/\beta_d = 12/15$ ,  $\beta_{hs}/\beta_c = 24/15$ . For all other combinations of DPDCH, DPCCCH, HS-DPCCH, E-DPDCH and E-DPCCH the MPR is based on the relative CM difference.  
Note 3: For subtest 1 the  $\beta_c/\beta_d$  ratio of 11/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signaled gain factors for the reference TFC (TF1, TF1) to  $\beta_c = 10/15$  and  $\beta_d = 15/15$ .  
Note 4: For subtest 5 the  $\beta_c/\beta_d$  ratio of 15/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signaled gain factors for the reference TFC (TF1, TF1) to  $\beta_c = 14/15$  and  $\beta_d = 15/15$ .  
Note 5: Testing UE using E-DPDCH Physical Layer category 1 Sub-test 3 is not required according to TS 25.306 Table 5.1g.  
Note 6:  $\beta_{ed}$  can not be set directly; it is set by Absolute Grant Value.

| Band     | Channel | Voice | GPRS Data       |                 |                 |                 | EDGE Data       |                 |                 |                 |
|----------|---------|-------|-----------------|-----------------|-----------------|-----------------|-----------------|-----------------|-----------------|-----------------|
|          |         | GSM   | GPRS            | GPRS            | GPRS            | GPRS            | EDGE            | EDGE            | EDGE            | EDGE            |
|          |         | (dBm) | 1 TX Slot (dBm) | 2 TX Slot (dBm) | 3 TX Slot (dBm) | 4 TX Slot (dBm) | 1 TX Slot (dBm) | 2 TX Slot (dBm) | 3 TX Slot (dBm) | 4 TX Slot (dBm) |
| GSM 850  | 128     | 32.62 | 32.61           | 29.66           | 27.9            | 26.81           | 27.05           | 27.08           | 26.2            | 25              |
|          | 190     | 32.61 | 32.6            | 29.6            | 27.87           | 27.11           | 27.01           | 27              | 26.14           | 24.91           |
|          | 251     | 32.61 | 32.6            | 29.61           | 27.88           | 26.81           | 27.06           | 27.05           | 26.21           | 24.97           |
| GSM 1900 | 512     | 29.62 | 29.61           | 26.68           | 24.89           | 24.01           | 26.01           | 25.96           | 24.9            | 23.64           |
|          | 661     | 29.64 | 29.62           | 26.69           | 24.93           | 24.14           | 25.83           | 25.8            | 24.91           | 23.66           |
|          | 810     | 29.66 | 29.64           | 26.69           | 24.91           | 23.98           | 25.64           | 25.68           | 24.87           | 23.68           |

Table 1. GSM Conducted output powers

| 3GPP Release Version | Mode  | 3GPP 34.121   | Cellular Band [dBm] |                    |                    | PCS Band [dBm]      |                     |                     | MPR |
|----------------------|-------|---------------|---------------------|--------------------|--------------------|---------------------|---------------------|---------------------|-----|
|                      |       | Subtest       | UL 4132<br>(826.4)  | UL 4183<br>(836.6) | UL 4233<br>(846.6) | UL 9262<br>(1852.4) | UL 9400<br>(1880.0) | UL 9538<br>(1907.6) |     |
| 99                   | WCDMA | 12.2kbps(RMC) | 22.31               | 22.31              | 22.31              | 22.80               | 22.65               | 22.6                | -   |
| 5                    | HSDPA | Subtest1      | 22.26               | 22.24              | 22.22              | 22.77               | 22.54               | 22.51               | 0   |
| 5                    |       | Subtest2      | 22.16               | 22.12              | 22.15              | 22.44               | 22.43               | 22.32               | 0   |
| 5                    |       | Subtest3      | 21.73               | 21.48              | 21.46              | 22.14               | 21.92               | 21.9                | 0.5 |
| 5                    |       | Subtest4      | 21.76               | 21.7               | 21.52              | 22.01               | 21.82               | 21.89               | 0.5 |
| 5                    | HSUPA | Subtest1      | 22.27               | 22.24              | 22.27              | 22.67               | 22.55               | 22.57               | 0   |
| 5                    |       | Subtest2      | 20.57               | 20.44              | 20.3               | 20.82               | 20.75               | 20.55               | 2   |
| 5                    |       | Subtest3      | 21.39               | 21.37              | 21.29              | 21.73               | 21.65               | 21.58               | 1   |
| 5                    |       | Subtest4      | 20.43               | 20.33              | 20.33              | 20.76               | 20.63               | 20.65               | 2   |
| 5                    |       | Subtest5      | 22.32               | 22.3               | 22.09              | 22.42               | 22.3                | 22.25               | 0   |

Table 2. WCDMA Conducted output powers

| Band         | Channel | Mbps  |       |       |       |
|--------------|---------|-------|-------|-------|-------|
|              |         | 1     | 2     | 5.5   | 11    |
| IEEE 802.11b | 1       | 12.21 | 12.09 | 11.93 | 11.81 |
|              | 6       | 12.73 | 12.57 | 12.47 | 12.45 |
|              | 11      | 13.12 | 13.10 | 13.07 | 12.84 |

Table 3. Average IEEE 802.11b Conducted output power

| Band         | Channel | Mbps |      |      |      |      |      |      |      |
|--------------|---------|------|------|------|------|------|------|------|------|
|              |         | 6    | 9    | 12   | 18   | 24   | 36   | 48   | 54   |
| IEEE 802.11g | 1       | 8.23 | 8.04 | 8.07 | 7.91 | 8.02 | 7.75 | 6.97 | 7.36 |
|              | 6       | 8.70 | 8.69 | 8.42 | 8.27 | 8.09 | 7.63 | 7.59 | 7.69 |
|              | 11      | 9.25 | 9.04 | 8.87 | 8.73 | 8.64 | 8.34 | 7.89 | 8.23 |

Table 4. Average IEEE 802.11g Conducted output power

| Band                 | Channel | Mbps |      |      |      |      |      |      |      |
|----------------------|---------|------|------|------|------|------|------|------|------|
|                      |         | 6.5  | 13   | 20   | 26   | 39   | 52   | 58   | 65   |
| IEEE 802.11n (HT-20) | 1       | 8.35 | 8.17 | 8.04 | 7.90 | 7.61 | 7.32 | 7.09 | 6.99 |
|                      | 6       | 8.53 | 8.37 | 8.14 | 8.06 | 7.66 | 7.53 | 7.38 | 7.31 |
|                      | 11      | 9.24 | 9.04 | 8.80 | 8.47 | 8.22 | 7.97 | 7.78 | 7.61 |

Table 5. Average IEEE 802.11n Conducted output power


## 11. Mobile Hotspot Side for SAR Testing

### 11.1 SAR Test configurations

| Mode      | Back | Front | EDGE A | EDGE B | EDGE C | EDGE D |
|-----------|------|-------|--------|--------|--------|--------|
| 850 GPRS  | Yes  | Yes   | Yes    | Yes    | Yes    | No     |
| 1900 GPRS | Yes  | Yes   | Yes    | Yes    | Yes    | No     |
| WCDMA850  | Yes  | Yes   | Yes    | Yes    | Yes    | No     |
| WCDMA1900 | Yes  | Yes   | Yes    | Yes    | Yes    | No     |
| WLAN      | Yes  | Yes   | No     | Yes    | No     | Yes    |

### 11.2 Antenna and Device Information

- This device has power back-off capabilities.



**Note;**

Per Oct.2010 TCB Workshop guidance, we performed the SAR testing at 1 cm from the top & bottom surfaces and also from side edges with a transmitting antenna  $\leq 2.5$  cm from an edge.

## 12. SAR Evaluation Considerations for Handsets with Multiple Transmitters and Antennas

### 12.1 SAR Evaluation Considerations

These procedures were followed according to FCC "SAR Evaluation Considerations for Handsets with Multiple Transmitters and Antennas", May 2008. The procedures are applicable to phones with built-in unlicensed transmitters, such as 802.11 a/b/g and Bluetooth devices.

|           | 2.45 | 5.15 - 5.35 | 5.47 - 5.85 | GHz |
|-----------|------|-------------|-------------|-----|
| $P_{Ref}$ | 12   | 6           | 5           | mW  |

Device output power should be rounded to the nearest mW to compare with values specified in this

Table. 12.1 Output Power Thresholds for Unlicensed Transmitters

|                         | Individual Transmitter                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | Simultaneous Transmission                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
|-------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Licensed Transmitters   | <u>Routine evaluation required</u>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | <u>SAR not required:</u><br><u>Unlicensed only</u><br><ul style="list-style-type: none"> <li>when stand-alone 1-g SAR is not required and antenna is <math>\geq 5</math> cm from other antennas</li> </ul> <u>Licensed &amp; Unlicensed</u><br><ul style="list-style-type: none"> <li>when the sum of the 1-g SAR is <math>&lt; 1.6</math> W/kg for all simultaneous transmitting antennas</li> <li>when SAR to peak location separation ratio of simultaneous transmitting antenna pair is <math>&lt; 0.3</math></li> </ul> <u>SAR required:</u><br><u>Licensed &amp; Unlicensed</u><br>antenna pairs with SAR to peak location separation ratio $\geq 0.3$ ; test is only required for the configuration that results in the highest SAR in stand-alone configuration for each wireless mode and exposure condition<br><u>Note: simultaneous transmission exposure conditions for head and body can be different for different style phones; therefore, different test requirements may apply</u> |
| Unlicensed Transmitters | <u>When there is no simultaneous transmission –</u> <ul style="list-style-type: none"> <li>output <math>\leq 60</math> f: SAR not required</li> <li>output <math>&gt; 60</math> f: stand-alone SAR required</li> </ul> <u>When there is simultaneous transmission –</u><br><u>Stand-alone SAR not required when</u> <ul style="list-style-type: none"> <li>output <math>\leq 2 \cdot P_{Ref}</math> and antenna is <math>\geq 5.0</math> cm from other antennas</li> <li>output <math>\leq P_{Ref}</math> and antenna is <math>\geq 2.5</math> cm from other antennas</li> <li>output <math>\leq P_{Ref}</math> and antenna is <math>&lt; 2.5</math> cm from other antennas, each with either output power <math>\leq P_{Ref}</math> or 1-g SAR <math>&lt; 1.2</math> W/kg</li> </ul> <u>Otherwise stand-alone SAR is required</u><br><u>When stand-alone SAR is required</u> <ul style="list-style-type: none"> <li>test SAR on highest output channel for each wireless mode and exposure condition</li> <li>if SAR for highest output channel is <math>&gt; 50\%</math> of SAR limit, evaluate all channels according to normal procedures</li> </ul> |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| Jaw, Mouth and Nose     | <u>Flat phantom SAR required</u> <ul style="list-style-type: none"> <li>when measurement is required in tight regions of SAM and it is not feasible or the results can be questionable due to probe tilt, calibration, positioning and orientation issues</li> <li>position rectangular and clam-shell phones according to flat phantom procedures and conduct SAR measurements for these specific locations</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | When simultaneous transmission SAR testing is required, contact the FCC Laboratory for interim guidance.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |

Table. 12.2 SAR Evaluation Requirements for Cellphones with Multiple Transmitters

FCC ID: BEJP970H / BT Max. RF output power: 7.38 mW

Antenna separation distance between Main and BT/ WLAN: 97 mm

WLAN Max. RF output power: Wi-Fi 802.11b(13.12 dBm) / Wi-Fi 802.11g (9.25 dBm)

## 12.2 Conclusion

Because the conducted output power level of the BT transmitter is less than  $2 \cdot P_{ref}$ , and the BT antenna is more than 5 cm from the Main antenna, neither simultaneous SAR nor stand-alone BT SAR are required for the EUT.

### Simultaneous Transmission Summation for Held to Ear Voice Call With Hotspot

| Simultaneous TX | configuration | 850 GSM SAR(W/kg)   | WIFI SAR (W/kg) | $\Sigma$ SAR (W/kg) | Simultaneous TX | configuration | 1900 GSM SAR(W/kg)   | WIFI SAR (W/kg) | $\Sigma$ SAR (W/kg) |
|-----------------|---------------|---------------------|-----------------|---------------------|-----------------|---------------|----------------------|-----------------|---------------------|
| Head SAR        | Right Cheek   | 0.512               | 0.197           | 0.709               | Head SAR        | Right Cheek   | 0.41                 | 0.197           | 0.607               |
|                 | Right Tilt    | 0.29                | 0.155           | 0.445               |                 | Right Tilt    | 0.25                 | 0.155           | 0.405               |
|                 | Left Cheek    | 0.424               | 0.487           | 0.911               |                 | Left Cheek    | 0.669                | 0.487           | 1.156               |
|                 | Left Tilt     | 0.252               | 0.278           | 0.53                |                 | Left Tilt     | 0.254                | 0.278           | 0.532               |
| Simultaneous TX | configuration | 850 WCDMA SAR(W/kg) | WIFI SAR (W/kg) | $\Sigma$ SAR (W/kg) | Simultaneous TX | configuration | 1900 WCDMA SAR(W/kg) | WIFI SAR (W/kg) | $\Sigma$ SAR (W/kg) |
| Head SAR        | Right Cheek   | 0.477               | 0.197           | 0.674               | Head SAR        | Right Cheek   | 0.991                | 0.197           | 1.188               |
|                 | Right Tilt    | 0.267               | 0.155           | 0.422               |                 | Right Tilt    | 0.341                | 0.155           | 0.496               |
|                 | Left Cheek    | 0.39                | 0.487           | 0.877               |                 | Left Cheek    | 0.949                | 0.487           | 1.436               |
|                 | Left Tilt     | 0.242               | 0.278           | 0.52                |                 | Left Tilt     | 0.499                | 0.278           | 0.777               |

### Simultaneous Transmission Summation for 2G/3G Hotspot Data and WIFI Hotspot

| Simultaneous TX | configuration | 850 GSM SAR(W/kg)   | WIFI SAR (W/kg) | $\Sigma$ SAR (W/kg) | Simultaneous TX | configuration | 1900 GSM SAR(W/kg)   | WIFI SAR (W/kg) | $\Sigma$ SAR (W/kg) |
|-----------------|---------------|---------------------|-----------------|---------------------|-----------------|---------------|----------------------|-----------------|---------------------|
| Body SAR        | Back          | 1.11                | 0.175           | 1.285               | Body SAR        | Back          | 0.558                | 0.175           | 0.733               |
|                 | Front         | 0.671               | 0.141           | 0.812               |                 | Front         | 0.526                | 0.141           | 0.667               |
|                 | Right Edge    | 0.778               | 0.201           | 0.979               |                 | Right Edge    | 0.157                | 0.201           | 0.358               |
|                 | Left Edge     | 0.554               | -               | 0.554               |                 | Left Edge     | 0.214                | -               | 0.214               |
|                 | Top Edge      | -                   | 0.109           | 0.109               |                 | Top Edge      | -                    | 0.109           | 0.109               |
|                 | Bottom Edge   | 0.187               | -               | 0.187               |                 | Bottom Edge   | 0.567                | -               | 0.567               |
| Simultaneous TX | configuration | 850 WCDMA SAR(W/kg) | WIFI SAR (W/kg) | $\Sigma$ SAR (W/kg) | Simultaneous TX | configuration | 1900 WCDMA SAR(W/kg) | WIFI SAR (W/kg) | $\Sigma$ SAR (W/kg) |
| Body SAR        | Back          | 0.946               | 0.175           | 1.121               | Body SAR        | Back          | 1.23                 | 0.175           | 1.405               |
|                 | Front         | 0.607               | 0.141           | 0.748               |                 | Front         | 0.714                | 0.141           | 0.855               |
|                 | Right Edge    | 0.671               | 0.201           | 0.872               |                 | Right Edge    | 0.312                | 0.201           | 0.513               |
|                 | Left Edge     | 0.61                | -               | 0.61                |                 | Left Edge     | 0.456                | -               | 0.456               |
|                 | Top Edge      | -                   | 0.109           | 0.109               |                 | Top Edge      | -                    | 0.109           | 0.109               |
|                 | Bottom Edge   | 0.173               | -               | 0.173               |                 | Bottom Edge   | 0.89                 | -               | 0.89                |

Note: WLAN DATA was measured at 1.0cm representing worst-case scenario

## 13. SAR TEST DATA SUMMARY

### 13.1 Measurement Results (GSM850 Head SAR)

| Frequency                                                                                          |           | Modulation | Conducted Power (dBm) |       | Battery  | Phantom Position                                | Antenna Type | SAR(mW/g) |
|----------------------------------------------------------------------------------------------------|-----------|------------|-----------------------|-------|----------|-------------------------------------------------|--------------|-----------|
| MHz                                                                                                | Channel   |            | Begin                 | End   |          |                                                 |              |           |
| 836.6                                                                                              | 190 (Mid) | GSM850     | 32.61                 | 32.41 | Standard | Left Ear                                        | Intenna      | 0.424     |
| 836.6                                                                                              | 190 (Mid) | GSM850     | 32.61                 | 32.49 | Standard | Left Tilt 15°                                   | Intenna      | 0.252     |
| 836.6                                                                                              | 190 (Mid) | GSM850     | 32.61                 | 32.55 | Standard | Right Ear                                       | Intenna      | 0.512     |
| 836.6                                                                                              | 190 (Mid) | GSM850     | 32.61                 | 32.64 | Standard | Right Tilt 15°                                  | Intenna      | 0.290     |
| ANSI/ IEEE C95.1 - 2005– Safety Limit<br>Spatial Peak<br>Uncontrolled Exposure/ General Population |           |            |                       |       |          | Head<br>1.6 W/kg (mW/g)<br>Averaged over 1 gram |              |           |

#### NOTES:

- The test data reported are the worst-case SAR value with the antenna-head position set in a typical configuration. Test procedures used are according to FCC/OET Bulletin 65, Supplement C [July 2001].
- All modes of operation were investigated and the worst-case are reported.
- Measured Depth of Simulating Tissue is 15.0 cm ± 0.2 cm.
- Tissue parameters and temperatures are listed on the SAR plot.
- Battery Type ☒ Standard ☐ Extended ☐ Slim  
Batteries are fully charged for all readings.
- Test Signal Call Mode ☐ Manual Test cord ☒ Base Station Simulator
- Justification for reduced test configurations: per FCC/OET Supplement C (July, 2001), if the SAR measured at the middle channel for each test configuration (Left, right, cheek/touch, tilt/ear, extended and retracted) is at least 3.0 dB lower than the SAR limit, testing at the high and low channels is optional for such test configuration(s).

## 13.2 Measurement Results (GSM1900 Head SAR)

| Frequency                                                                                          |           | Modulation | Conducted Power (dBm) |       | Battery  | Phantom Position                                | Antenna Type | SAR(mW/g) |
|----------------------------------------------------------------------------------------------------|-----------|------------|-----------------------|-------|----------|-------------------------------------------------|--------------|-----------|
| MHz                                                                                                | Channel   |            | Begin                 | End   |          |                                                 |              |           |
| 1 880.0                                                                                            | 661 (Mid) | GSM1900    | 29.64                 | 29.67 | Standard | Left Ear                                        | Intenna      | 0.669     |
| 1 880.0                                                                                            | 661 (Mid) | GSM1900    | 29.64                 | 29.57 | Standard | Left Tilt 15°                                   | Intenna      | 0.254     |
| 1 880.0                                                                                            | 661 (Mid) | GSM1900    | 29.64                 | 29.58 | Standard | Right Ear                                       | Intenna      | 0.410     |
| 1 880.0                                                                                            | 661 (Mid) | GSM1900    | 29.64                 | 29.57 | Standard | Right Tilt 15°                                  | Intenna      | 0.250     |
| ANSI/ IEEE C95.1 - 2005– Safety Limit<br>Spatial Peak<br>Uncontrolled Exposure/ General Population |           |            |                       |       |          | Head<br>1.6 W/kg (mW/g)<br>Averaged over 1 gram |              |           |

### NOTES:

- The test data reported are the worst-case SAR value with the antenna-head position set in a typical configuration. Test procedures used are according to FCC/OET Bulletin 65, Supplement C [July 2001].
- All modes of operation were investigated and the worst-case are reported.
- Measured Depth of Simulating Tissue is 15.0 cm ± 0.2 cm.
- Tissue parameters and temperatures are listed on the SAR plot.
- Battery Type ☒ Standard ☐ Extended ☐ Slim  
Batteries are fully charged for all readings.
- Test Signal Call Mode ☐ Manual Test cord ☒ Base Station Simulator
- Justification for reduced test configurations: per FCC/OET Supplement C (July, 2001), if the SAR measured at the middle channel for each test configuration (Left, right, cheek/touch, tilt/ear, extended and retracted) is at least 3.0 dB lower than the SAR limit, testing at the high and low channels is optional for such test configuration(s).

### 13.3 Measurement Results (WCDMA850 Head SAR)

| Frequency                                                                                                              |            | Modulation | Conducted Power (dBm) |       | Battery  | Phantom Position                                                             | Antenna Type | SAR(mW/g) |
|------------------------------------------------------------------------------------------------------------------------|------------|------------|-----------------------|-------|----------|------------------------------------------------------------------------------|--------------|-----------|
| MHz                                                                                                                    | Channel    |            | Begin                 | End   |          |                                                                              |              |           |
| 836.6                                                                                                                  | 4183 (Mid) | WCDMA850   | 22.31                 | 22.12 | Standard | Left Ear                                                                     | Intenna      | 0.390     |
| 836.6                                                                                                                  | 4183 (Mid) | WCDMA850   | 22.31                 | 22.22 | Standard | Left Tilt 15°                                                                | Intenna      | 0.242     |
| 836.6                                                                                                                  | 4183 (Mid) | WCDMA850   | 22.31                 | 22.25 | Standard | Right Ear                                                                    | Intenna      | 0.477     |
| 836.6                                                                                                                  | 4183 (Mid) | WCDMA850   | 22.31                 | 22.22 | Standard | Right Tilt 15°                                                               | Intenna      | 0.267     |
| <b>ANSI/ IEEE C95.1 2005 – Safety Limit</b><br><b>Spatial Peak</b><br><b>Uncontrolled Exposure/ General Population</b> |            |            |                       |       |          | <b>Head</b><br><b>1.6 W/kg (mW/g)</b><br><small>Averaged over 1 gram</small> |              |           |

#### NOTES:

- The test data reported are the worst-case SAR value with the antenna-head position set in a typical configuration. Test procedures used are according to FCC/OET Bulletin 65, Supplement C [July 2001].
- All modes of operation were investigated and the worst-case are reported.
- Measured Depth of Simulating Tissue is 15.0 cm ± 0.2 cm.
- Tissue parameters and temperatures are listed on the SAR plot.
- Battery Type ☒ Standard ☐ Extended ☐ Slim  
Batteries are fully charged for all readings.
- Test Signal Call Mode ☐ Manual Test cord ☒ Base Station Simulator
- Justification for reduced test configurations: per FCC/OET Supplement C (July, 2001), if the SAR measured at the middle channel for each test configuration (Left, right, cheek/touch, tilt/ear, extended and retracted) is at least 3.0 dB lower than the SAR limit, testing at the high and low channels is optional for such test configuration(s).
- WCDMA Mode was tested under RMC 12.2 kbps and HSPA Inactive.

## 13.4 Measurement Results (WCDMA1900 Head SAR)

| Frequency                                                                                          |             | Modulation | Conducted Power (dBm) |       | Battery  | Phantom Position                                | Antenna Type | SAR(mW/g) |
|----------------------------------------------------------------------------------------------------|-------------|------------|-----------------------|-------|----------|-------------------------------------------------|--------------|-----------|
| MHz                                                                                                | Channel     |            | Begin                 | End   |          |                                                 |              |           |
| 1 852.4                                                                                            | 9262 (Low)  | WCDMA1900  | 22.80                 | 22.80 | Standard | Left Ear                                        | Intenna      | 0.934     |
| 1 880.0                                                                                            | 9400 (Mid)  | WCDMA1900  | 22.65                 | 22.69 | Standard | Left Ear                                        | Intenna      | 0.949     |
| 1 907.6                                                                                            | 9538 (High) | WCDMA1900  | 22.60                 | 22.67 | Standard | Left Ear                                        | Intenna      | 0.902     |
| 1 880.0                                                                                            | 9400 (Mid)  | WCDMA1900  | 22.65                 | 22.70 | Standard | Left Tilt 15°                                   | Intenna      | 0.499     |
| 1 852.4                                                                                            | 9262 (Low)  | WCDMA1900  | 22.80                 | 22.76 | Standard | Right Ear                                       | Intenna      | 0.991     |
| 1 880.0                                                                                            | 9400 (Mid)  | WCDMA1900  | 22.65                 | 22.62 | Standard | Right Ear                                       | Intenna      | 0.906     |
| 1 907.6                                                                                            | 9538 (High) | WCDMA1900  | 22.60                 | 22.46 | Standard | Right Ear                                       | Intenna      | 0.643     |
| 1 880.0                                                                                            | 9400 (Mid)  | WCDMA1900  | 22.65                 | 22.71 | Standard | Right Tilt 15                                   | Intenna      | 0.341     |
| ANSI/ IEEE C95.1 - 2005– Safety Limit<br>Spatial Peak<br>Uncontrolled Exposure/ General Population |             |            |                       |       |          | Head<br>1.6 W/kg (mW/g)<br>Averaged over 1 gram |              |           |

### NOTES:

- The test data reported are the worst-case SAR value with the antenna-head position set in a typical configuration. Test procedures used are according to FCC/OET Bulletin 65, Supplement C [July 2001].
- All modes of operation were investigated and the worst-case are reported.
- Measured Depth of Simulating Tissue is 15.0 cm ± 0.2 cm.
- Tissue parameters and temperatures are listed on the SAR plot.
- Battery Type ☒ Standard ☐ Extended ☐ Slim  
Batteries are fully charged for all readings.
- Test Signal Call Mode ☐ Manual Test cord ☒ Base Station Simulator
- WCDMA Mode was tested under RMC 12.2 kbps and HSPA Inactive.

## 13.5 Measurement Results (802.11b/g/n Module Head)

| Frequency                                                                                          |           | Modulation | Conducted Power (dBm) |       | Battery  | Phantom Position                                | Antenna Type | SAR(mW/g) |
|----------------------------------------------------------------------------------------------------|-----------|------------|-----------------------|-------|----------|-------------------------------------------------|--------------|-----------|
| MHz                                                                                                | Channel   |            | Begin                 | End   |          |                                                 |              |           |
| 2 462                                                                                              | 11 (High) | 802.11b    | 13.12                 | 13.01 | Standard | Left Ear                                        | Intenna      | 0.487     |
| 2 462                                                                                              | 11 (High) | 802.11b    | 13.12                 | 13.07 | Standard | Left Tilt 15°                                   | Intenna      | 0.278     |
| 2 462                                                                                              | 11 (High) | 802.11b    | 13.12                 | 13.22 | Standard | Right Ear                                       | Intenna      | 0.197     |
| 2 462                                                                                              | 11 (High) | 802.11b    | 13.12                 | 13.12 | Standard | Right Tilt 15                                   | Intenna      | 0.155     |
| ANSI/ IEEE C95.1 - 2005– Safety Limit<br>Spatial Peak<br>Uncontrolled Exposure/ General Population |           |            |                       |       |          | Head<br>1.6 W/kg (mW/g)<br>Averaged over 1 gram |              |           |

### NOTES:

- The test data reported are the worst-case SAR value with the antenna-head position set in a typical configuration. Test procedures used are according to FCC/OET Bulletin 65, Supplement C [July 2001].
- All modes of operation were investigated and the worst-case are reported.
- Measured Depth of Simulating Tissue is 15.0 cm ± 0.2 cm.
- Tissue parameters and temperatures are listed on the SAR plot.
- Battery Type ☒ Standard ☐ Extended ☐ Slim  
Batteries are fully charged for all readings.
- Test Signal Call Mode ☐ Manual Test cord ☒ Base Station Simulator
- IEEE 802.11g(including 802.11n) SAR testing is required when the conducted powers are equal to or greater than 0.25 dB Than the conducted powers in IEEE 802.11b.

## 13.6 Measurement Results (GSM850 Hotspot Body SAR)

| Frequency                                                                                          |            | Modulation | Conducted Power (dBm) |       | Configuration | Separation Distance                             | SAR(mW/g) |
|----------------------------------------------------------------------------------------------------|------------|------------|-----------------------|-------|---------------|-------------------------------------------------|-----------|
| MHz                                                                                                | Channel    |            | Begin                 | End   |               |                                                 |           |
| 836.6                                                                                              | 190 (Mid)  | GPRS 4Tx   | 27.11                 | 27.16 | Front         | 1.0 cm                                          | 0.671     |
| 824.2                                                                                              | 128 (Low)  | GPRS 4Tx   | 26.81                 | 26.76 | Rear          | 1.0 cm                                          | 0.933     |
| 836.6                                                                                              | 190 (Mid)  | GPRS 4Tx   | 27.11                 | 27.00 | Rear          | 1.0 cm                                          | 1.01      |
| 848.8                                                                                              | 251 (High) | GPRS 4Tx   | 26.81                 | 26.84 | Rear          | 1.0 cm                                          | 1.11      |
| 836.6                                                                                              | 190 (Mid)  | GPRS 4Tx   | 27.11                 | 27.18 | Edge A        | 1.0 cm                                          | 0.554     |
| 836.6                                                                                              | 190 (Mid)  | GPRS 4Tx   | 27.11                 | 27.07 | Edge B        | 1.0 cm                                          | 0.778     |
| 836.6                                                                                              | 190 (Mid)  | GPRS 4Tx   | 27.11                 | 27.04 | Edge C        | 1.0 cm                                          | 0.187     |
| ANSI/ IEEE C95.1 - 2005– Safety Limit<br>Spatial Peak<br>Uncontrolled Exposure/ General Population |            |            |                       |       |               | Body<br>1.6 W/kg (mW/g)<br>Averaged over 1 gram |           |

### NOTES:

- The test data reported are the worst-case SAR value with the antenna-head position set in a typical configuration. Test procedures used are according to FCC/OET Bulletin 65, Supplement C [July 2001].
- All modes of operation were investigated and the worst-case are reported.
- Measured Depth of Simulating Tissue is 15.0 cm ± 0.2 cm.
- Tissue parameters and temperatures are listed on the SAR plot.
- Battery Type ☒ Standard ☐ Extended ☐ Slim  
Batteries are fully charged for all readings.
- Test Signal Call Mode ☐ Manual Test cord ☒ Base Station Simulator
- Both side of the phone were tested and the worst-case side is reported.
- Test Configuration ☐ With Holster ☒ Without Holster
- Justification for reduced test configurations: per FCC/OET Supplement C (July, 2001), if the SAR measured at the middle channel for each test configuration (Left, right, cheek/touch, tilt/ear, extended and retracted) is at least 3.0 dB lower than the SAR limit, testing at the high and low channels is optional for such test configuration(s).

## 13.7 Measurement Results (GSM1900 Hotspot Body SAR)

| Frequency                                                                                          |           | Modulation | Conducted Power (dBm) |       | Configuration | Separation Distance                             | SAR(mW/g) |
|----------------------------------------------------------------------------------------------------|-----------|------------|-----------------------|-------|---------------|-------------------------------------------------|-----------|
| MHz                                                                                                | Channel   |            | Begin                 | End   |               |                                                 |           |
| 1 880.0                                                                                            | 661 (Mid) | GPRS 4Tx   | 24.14                 | 24.12 | Front         | 1.0 cm                                          | 0.526     |
| 1 880.0                                                                                            | 661 (Mid) | GPRS 4Tx   | 24.14                 | 24.12 | Rear          | 1.0 cm                                          | 0.558     |
| 1 880.0                                                                                            | 661 (Mid) | GPRS 4Tx   | 24.14                 | 24.10 | Edge A        | 1.0 cm                                          | 0.214     |
| 1 880.0                                                                                            | 661 (Mid) | GPRS 4Tx   | 24.14                 | 24.22 | Edge B        | 1.0 cm                                          | 0.157     |
| 1 880.0                                                                                            | 661 (Mid) | GPRS 4Tx   | 24.14                 | 24.20 | Edge C        | 1.0 cm                                          | 0.567     |
| ANSI/ IEEE C95.1 - 2005– Safety Limit<br>Spatial Peak<br>Uncontrolled Exposure/ General Population |           |            |                       |       |               | Body<br>1.6 W/kg (mW/g)<br>Averaged over 1 gram |           |

### NOTES:

- The test data reported are the worst-case SAR value with the antenna-head position set in a typical configuration. Test procedures used are according to FCC/OET Bulletin 65, Supplement C [July 2001].
- All modes of operation were investigated and the worst-case are reported.
- Measured Depth of Simulating Tissue is 15.0 cm  $\pm$  0.2 cm.
- Tissue parameters and temperatures are listed on the SAR plot.
- Battery Type ☒ Standard ☐ Extended ☐ Slim  
Batteries are fully charged for all readings.
- Test Signal Call Mode ☐ Manual Test cord ☒ Base Station Simulator
- Both side of the phone were tested and the worst-case side is reported.
- Test Configuration ☐ With Holster ☒ Without Holster
- Justification for reduced test configurations: per FCC/OET Supplement C (July, 2001), if the SAR measured at the middle channel for each test configuration (Left, right, cheek/touch, tilt/ear, extended and retracted) is at least 3.0 dB lower than the SAR limit, testing at the high and low channels is optional for such test configuration(s).

## 13.8 Measurement Results (WCDMA850 Hotspot Body SAR)

| Frequency                                                                                          |             | Modulation | Conducted Power (dBm) |       | Configuration | Separation Distance                             | SAR(mW/g) |
|----------------------------------------------------------------------------------------------------|-------------|------------|-----------------------|-------|---------------|-------------------------------------------------|-----------|
| MHz                                                                                                | Channel     |            | Begin                 | End   |               |                                                 |           |
| 836.6                                                                                              | 4183 (Mid)  | WCDMA850   | 22.31                 | 22.35 | Front         | 1.0 cm                                          | 0.607     |
| 826.4                                                                                              | 4132 (Low)  | WCDMA850   | 22.31                 | 22.35 | Rear          | 1.0 cm                                          | 0.936     |
| 836.6                                                                                              | 4183 (Mid)  | WCDMA850   | 22.31                 | 22.12 | Rear          | 1.0 cm                                          | 0.890     |
| 846.4                                                                                              | 4283 (High) | WCDMA850   | 22.31                 | 22.26 | Rear          | 1.0 cm                                          | 0.946     |
| 836.6                                                                                              | 4183 (Mid)  | WCDMA850   | 22.31                 | 22.31 | Edge A        | 1.0 cm                                          | 0.610     |
| 836.6                                                                                              | 4183 (Mid)  | WCDMA850   | 22.31                 | 22.37 | Edge B        | 1.0 cm                                          | 0.671     |
| 836.6                                                                                              | 4183 (Mid)  | WCDMA850   | 22.31                 | 22.31 | Edge C        | 1.0 cm                                          | 0.173     |
| ANSI/ IEEE C95.1 - 2005– Safety Limit<br>Spatial Peak<br>Uncontrolled Exposure/ General Population |             |            |                       |       |               | Body<br>1.6 W/kg (mW/g)<br>Averaged over 1 gram |           |

- The test data reported are the worst-case SAR value with the antenna-head position set in a typical configuration. Test procedures used are according to FCC/OET Bulletin 65, Supplement C [July 2001].
- All modes of operation were investigated and the worst-case are reported.
  - Measured Depth of Simulating Tissue is 15.0 cm ± 0.2 cm.
  - Tissue parameters and temperatures are listed on the SAR plot.
  - Battery Type ☒ Standard ☐ Extended ☐ Slim  
Batteries are fully charged for all readings.
  - Test Signal Call Mode ☐ Manual Test cord ☒ Base Station Simulator
  - Both side of the phone were tested and the worst-case side is reported.
  - Test Configuration ☐ With Holster ☒ Without Holster
  - Justification for reduced test configurations: per FCC/OET Supplement C (July, 2001), if the SAR measured at the middle channel for each test configuration (Left, right, cheek/touch, tilt/ear, extended and retracted) is at least 3.0 dB lower than the SAR limit, testing at the high and low channels is optional for such test configuration(s).
  - WCDMA Mode was tested under RMC 12.2 kbps and HSPA Inactive.

## 13.9 Measurement Results (WCDMA1900 Hotspot Body SAR)

| Frequency                                                                                                               |             | Modulation | Conducted Power (dBm) |       | Configuration | Separation Distance                                           | SAR(mW/g) |
|-------------------------------------------------------------------------------------------------------------------------|-------------|------------|-----------------------|-------|---------------|---------------------------------------------------------------|-----------|
| MHz                                                                                                                     | Channel     |            | Begin                 | End   |               |                                                               |           |
| 1 880.0                                                                                                                 | 9400 (Mid)  | WCDMA1900  | 22.65                 | 22.59 | Front         | 1.0 cm                                                        | 0.714     |
| 1 852.4                                                                                                                 | 9262 (Low)  | WCDMA1900  | 22.80                 | 22.77 | Rear          | 1.0 cm                                                        | 1.23      |
| 1 880.0                                                                                                                 | 9400 (Mid)  | WCDMA1900  | 22.65                 | 22.69 | Rear          | 1.0 cm                                                        | 1.12      |
| 1 907.6                                                                                                                 | 9538 (High) | WCDMA1900  | 22.60                 | 22.59 | Rear          | 1.0 cm                                                        | 0.852     |
| 1 880.0                                                                                                                 | 9400 (Mid)  | WCDMA1900  | 22.65                 | 22.61 | Edge A        | 1.0 cm                                                        | 0.456     |
| 1 880.0                                                                                                                 | 9400 (Mid)  | WCDMA1900  | 22.65                 | 22.72 | Edge B        | 1.0 cm                                                        | 0.312     |
| 1 852.4                                                                                                                 | 9262 (Low)  | WCDMA1900  | 22.80                 | 22.82 | Edge C        | 1.0 cm                                                        | 0.717     |
| 1 880.0                                                                                                                 | 9400 (Mid)  | WCDMA1900  | 22.65                 | 22.58 | Edge C        | 1.0 cm                                                        | 0.866     |
| 1 907.6                                                                                                                 | 9538 (High) | WCDMA1900  | 22.60                 | 22.57 | Edge C        | 1.0 cm                                                        | 0.890     |
| <b>ANSI/ IEEE C95.1 - 2005– Safety Limit</b><br><b>Spatial Peak</b><br><b>Uncontrolled Exposure/ General Population</b> |             |            |                       |       |               | <b>Body</b><br><b>1.6 W/kg (mW/g)</b><br>Averaged over 1 gram |           |

- The test data reported are the worst-case SAR value with the antenna-head position set in a typical configuration. Test procedures used are according to FCC/OET Bulletin 65, Supplement C [July 2001].
- All modes of operation were investigated and the worst-case are reported.
- Measured Depth of Simulating Tissue is 15.0 cm ± 0.2 cm.
- Tissue parameters and temperatures are listed on the SAR plot.
- Battery Type ☒ Standard ☐ Extended ☐ Slim  
Batteries are fully charged for all readings.
- Test Signal Call Mode ☐ Manual Test cord ☒ Base Station Simulator
- Test Configuration ☐ With Holster ☒ Without Holster
- Justification for reduced test configurations: per FCC/OET Supplement C (July, 2001), if the SAR measured at the middle channel for each test configuration (Left, right, cheek/touch, tilt/ear, extended and retracted) is at least 3.0 dB lower than the SAR limit, testing at the high and low channels is optional for such test configuration(s).
- WCDMA Mode was tested under RMC 12.2 kbps and HSPA Inactive.

## 13.10 Measurement Results (802.11b/g/n Module Body SAR)

| Frequency                                                                                                              |           | Modulation | Conducted Power (dBm) |       | Configuration | Separation Distance                                                          | Data Rate | SAR(mW/g) |
|------------------------------------------------------------------------------------------------------------------------|-----------|------------|-----------------------|-------|---------------|------------------------------------------------------------------------------|-----------|-----------|
| MHz                                                                                                                    | Channel   |            | Begin                 | End   |               |                                                                              |           |           |
| 2 462                                                                                                                  | 11 (High) | 802.11b    | 13.12                 | 13.16 | Rear          | 1.0 cm                                                                       | 1 Mbps    | 0.175     |
| 2 462                                                                                                                  | 11 (High) | 802.11b    | 13.12                 | 13.10 | Front         | 1.0 cm                                                                       | 1 Mbps    | 0.141     |
| 2 462                                                                                                                  | 11 (High) | 802.11b    | 13.12                 | 13.17 | Edge B        | 1.0 cm                                                                       | 1 Mbps    | 0.201     |
| 2 462                                                                                                                  | 11 (High) | 802.11b    | 13.12                 | 13.17 | Edge D        | 1.0 cm                                                                       | 1 Mbps    | 0.109     |
| <b>ANSI/ IEEE C95.1 1992 – Safety Limit</b><br><b>Spatial Peak</b><br><b>Uncontrolled Exposure/ General Population</b> |           |            |                       |       |               | <b>Body</b><br><b>1.6 W/kg (mW/g)</b><br><small>Averaged over 1 gram</small> |           |           |

### NOTES:

- The test data reported are the worst-case SAR value with the antenna-head position set in a typical configuration. Test procedures used are according to FCC/OET Bulletin 65, Supplement C [July 2001].
- All modes of operation were investigated and the worst-case are reported.
- Measured Depth of Simulating Tissue is 15.0 cm  $\pm$  0.2 cm.
- Tissue parameters and temperatures are listed on the SAR plot.
- Battery Type ☒ Standard ☐ Extended ☐ Slim  
Batteries are fully charged for all readings.
- Test Signal Call Mode ☒ Manual Test code ☐ Base Station Simulator
- IEEE 802.11g(including 802.11n) SAR testing is required when the conducted powers are equal to or greater than 0.25 dB Than the conducted powers in IEEE 802.11b.

## **14. CONCLUSION**

---

The SAR measurement indicates that the EUT complies with the RF radiation exposure limits of the ANSI/IEEE C95.1 2005.

These measurements are taken to simulate the RF effects exposure under worst-case conditions. Precise laboratory measures were taken to assure repeatability of the tests.

## 15. REFERENCES

---

- [1] Federal Communications Commission, OET Bulletin 65 (Edition 97-01), Supplement C (Edition 01-01), Evaluating Compliance with FCC Guidelines for Human Exposure to Radio frequency Electromagnetic Fields, July 2001.
- [2] IEEE Standards Coordinating Committee 34 – IEEE Std. 1528-2003, IEE Recommended Practice or Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Body from Wireless Communications Devices.
- [3] Federal Communications Commission, ET Docket 93-62, Guidelines for Evaluating the Environmental Effects of Radio frequency Radiation, Aug. 1996.
- [4] ANSI/IEEE C95.1 - 1991, American National Standard safety levels with respect to human exposure to radio frequency electromagnetic fields, 300 kHz to 100 GHz, New York: IEEE, Aug. 1992
- [5] ANSI/IEEE C95.3 - 1991, IEEE Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields - RF and Microwave, New York: IEEE, 1992.
- [6] NCRP, National Council on Radiation Protection and Measurements, Biological Effects and Exposure Criteria for Radio Frequency Electromagnetic Fields, NCRP Report No. 86, 1986. Reprinted Feb. 1995.
- [7] T. Schmid, O. Egger, N. Kuster, Automated E-field scanning system for dosimetric assessments, IEEE Transaction on Microwave Theory and Techniques, vol. 44, Jan. 1996, pp. 105-113.
- [8] K. Pokovic, T. Schmid, N. Kuster, Robust setup for precise calibration of E-field probes in tissue simulating liquids at mobile communications frequencies, ICECOM97, Oct. 1997, pp. 120-124.
- [9] K. Poković, T. Schmid, and N. Kuster, E-field Probe with improved isotropy in brain simulating liquids, Proceedings of the ELMAR, Zadar, Croatia, June 23-25, 1996, pp. 172-175.
- [10] Schmid & Partner Engineering AG, Application Note: Data Storage and Evaluation, June 1998, p2.
- [11] V. Hombach, K. Meier, M. Burkhardt, E. Kuhn, N. Kuster, The Dependence of EM Energy Absorption upon Human Head Modeling at 900 MHz, IEEE Transaction on Microwave Theory and Techniques, vol. 44 no. 10, Oct. 1996, pp. 1865-1873.
- [12] N. Kuster and Q. Balzano, Energy absorption mechanism by biological bodies in the near field of dipole antennas above 300 MHz, IEEE Transaction on Vehicular Technology, vol. 41, no. 1, Feb. 1992, pp. 17-23.
- [13] G. Hartsgrrove, A. Kraszewski, A. Surowiec, Simulated Biological Materials for Electromagnetic Radiation Absorption Studies, University of Ottawa, Bioelectro magnetics, Canada: 1987, pp. 29-36.
- [14] Q. Balzano, O. Garay, T. Manning Jr., Electromagnetic Energy Exposure of Simulated Users of Portable Cellular Telephones, IEEE Transactions on Vehicular Technology, vol. 44, no.3, Aug. 1995.
- [15] W. Gander, Computer mathematick, Birkhaeuser, Basel, 1992.
- [16] W.H. Press, S.A. Teukolsky, W.T. Vetterling, and B.P. Flannery, Numerical Recepies in C, The Art of Scientific Computing, Second edition, Cambridge University Press, 1992.
- [17] Federal Communications Commission, OET Bulletin 65, Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields. Supplement C, Dec. 1997.
- [18] N. Kuster, R. Kastle, T. Schmid, Dosimetric evaluation of mobile communications equipment with known precision, IEEE Transaction on Communications, vol. E80-B, no. 5, May 1997, pp. 645-652.
- [19] CENELEC CLC/SC111B, European Prestandard (prENV 50166-2), Human Exposure to Electromagnetic Fields High-frequency: 10 kHz-300 GHz, Jan. 1995.
- [20] Prof. Dr. Niels Kuster, ETH, EidgenØssische Technische Hoschschule ZØrich, Dosimetric Evaluation of the Cellular Phone.
- [21] SAR Evaluation of Handsets with Multiple Transmitters and Antennas #648474.
- [22] SAR Measurement Procedure for 802.11 a/b/g Transmitters #KDB 248227.

## Attachment 1. – SAR Test Plots

Test Laboratory: HCT CO., LTD  
EUT Type: Cellular/PCS GSM/GPRS/EDGE/WCDMA/HSPA Phone with BT & WLAN  
GPRS Class12 and GPRS mode class B(GPRS and GSM, but not simultaneously)  
Liquid Temperature: 21.1 °C  
Ambient Temperature: 21.3 °C  
Test Date: Mar.14, 2011

**DUT: LG-P970h; Type: bar; Serial: #1**

Communication System: GSM 850; Frequency: 836.6 MHz; Duty Cycle: 1:8.3  
Medium parameters used (interpolated):  $f = 836.6 \text{ MHz}$ ;  $\sigma = 0.877 \text{ mho/m}$ ;  $\epsilon_r = 42.9$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Left Section ; Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 184

DASY4 Configuration:

- Probe: ET3DV6 - SN1630; ConvF(6.25, 6.25, 6.25); Calibrated: 2010-05-25
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn869; Calibrated: 2010-09-21
- Phantom: 835/900 Phantom ; Type: SAM

**Left touch 190/Area Scan (51x91x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (interpolated) = 0.439 mW/g

**Left touch 190/Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$


Reference Value = 10.2 V/m; Power Drift = -0.182 dB

Peak SAR (extrapolated) = 0.553 W/kg

**SAR(1 g) = 0.424 mW/g; SAR(10 g) = 0.306 mW/g**

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.477 mW/g



0 dB = 0.477mW/g

Test Laboratory: HCT CO., LTD  
 EUT Type: Cellular/PCS GSM/GPRS/EDGE/WCDMA/HSPA Phone with BT & WLAN  
 GPRS Class12 and GPRS mode class B(GPRS and GSM, but not simultaneously)  
 Liquid Temperature: 21.1 °C  
 Ambient Temperature: 21.3 °C  
 Test Date: Mar.14, 2011

**DUT: LG-P970h; Type: bar; Serial: #1**

Communication System: GSM 850; Frequency: 836.6 MHz; Duty Cycle: 1:8.3  
 Medium parameters used (interpolated):  $f = 836.6 \text{ MHz}$ ;  $\sigma = 0.877 \text{ mho/m}$ ;  $\epsilon_r = 42.9$ ;  $\rho = 1000 \text{ kg/m}^3$   
 Phantom section: Left Section ; Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 184

DASY4 Configuration:

- Probe: ET3DV6 - SN1630; ConvF(6.25, 6.25, 6.25); Calibrated: 2010-05-25
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn869; Calibrated: 2010-09-21
- Phantom: 835/900 Phantom ; Type: SAM

**Left tilt 190/Area Scan (51x91x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (interpolated) = 0.268 mW/g

**Left tilt 190/Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$


Reference Value = 14.7 V/m; Power Drift = -0.101 dB

Peak SAR (extrapolated) = 0.298 W/kg

**SAR(1 g) = 0.252 mW/g; SAR(10 g) = 0.195 mW/g**

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.261 mW/g



0 dB = 0.261mW/g

Test Laboratory: HCT CO., LTD  
EUT Type: Cellular/PCS GSM/GPRS/EDGE/WCDMA/HSPA Phone with BT & WLAN  
GPRS Class12 and GPRS mode class B(GPRS and GSM, but not simultaneously)  
Liquid Temperature: 21.1 °C  
Ambient Temperature: 21.3 °C  
Test Date: Mar.14, 2011

**DUT: LG-P970h; Type: bar; Serial: #1**

Communication System: GSM 850; Frequency: 836.6 MHz; Duty Cycle: 1:8.3  
Medium parameters used (interpolated):  $f = 836.6 \text{ MHz}$ ;  $\sigma = 0.877 \text{ mho/m}$ ;  $\epsilon_r = 42.9$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Right Section ; Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 184

DASY4 Configuration:

- Probe: ET3DV6 - SN1630; ConvF(6.25, 6.25, 6.25); Calibrated: 2010-05-25
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn869; Calibrated: 2010-09-21
- Phantom: 835/900 Phantom ; Type: SAM

**Right touch 190/Area Scan (51x91x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (interpolated) = 0.540 mW/g


**Right touch 190/Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$

Reference Value = 10.6 V/m; Power Drift = -0.045 dB

Peak SAR (extrapolated) = 0.663 W/kg

**SAR(1 g) = 0.512 mW/g; SAR(10 g) = 0.376 mW/g**

Maximum value of SAR (measured) = 0.546 mW/g



0 dB = 0.546mW/g

Test Laboratory: HCT CO., LTD  
EUT Type: Cellular/PCS GSM/GPRS/EDGE/WCDMA/HSPA Phone with BT & WLAN  
GPRS Class12 and GPRS mode class B(GPRS and GSM, but not simultaneously)  
Liquid Temperature: 21.1 °C  
Ambient Temperature: 21.3 °C  
Test Date: Mar.14, 2011

**DUT: LG-P970h; Type: bar; Serial: #1**

Communication System: GSM 850; Frequency: 836.6 MHz; Duty Cycle: 1:8.3  
Medium parameters used (interpolated):  $f = 836.6$  MHz;  $\sigma = 0.877$  mho/m;  $\epsilon_r = 42.9$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
Phantom section: Right Section ; Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 184

DASY4 Configuration:

- Probe: ET3DV6 - SN1630; ConvF(6.25, 6.25, 6.25); Calibrated: 2010-05-25
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn869; Calibrated: 2010-09-21
- Phantom: 835/900 Phantom ; Type: SAM

**Right tilt 190/Area Scan (51x91x1):** Measurement grid: dx=15mm, dy=15mm

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (interpolated) = 0.305 mW/g

**Right tilt 190/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm


Reference Value = 15.3 V/m; Power Drift = 0.047 dB

Peak SAR (extrapolated) = 0.346 W/kg

**SAR(1 g) = 0.290 mW/g; SAR(10 g) = 0.223 mW/g**

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.302 mW/g



0 dB = 0.302mW/g

Test Laboratory: HCT CO., LTD  
EUT Type: Cellular/PCS GSM/GPRS/EDGE/WCDMA/HSPA Phone with BT & WLAN  
GPRS Class12 and GPRS mode class B(GPRS and GSM, but not simultaneously)  
Liquid Temperature: 21.1 °C  
Ambient Temperature: 21.3 °C  
Test Date: Mar.15, 2011

**DUT: LG-P970h; Type: bar; Serial: #1**


Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3  
Medium parameters used:  $f = 1880 \text{ MHz}$ ;  $\sigma = 1.38 \text{ mho/m}$ ;  $\epsilon_r = 41.1$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Left Section ; Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 184

DASY4 Configuration:

- Probe: ET3DV6 - SN1630; ConvF(5.12, 5.12, 5.12); Calibrated: 2010-05-25
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn869; Calibrated: 2010-09-21
- Phantom: SAM 1800/1900 MHz; Type: SAM

**Left touch 661/Area Scan (61x101x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$   
Maximum value of SAR (interpolated) = 0.746 mW/g

**Left touch 661/Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$   
Reference Value = 7.84 V/m; Power Drift = 0.029 dB  
Peak SAR (extrapolated) = 1.06 W/kg  
**SAR(1 g) = 0.669 mW/g; SAR(10 g) = 0.386 mW/g**  
Maximum value of SAR (measured) = 0.742 mW/g



0 dB = 0.742mW/g

Test Laboratory: HCT CO., LTD  
 EUT Type: Cellular/PCS GSM/GPRS/EDGE/WCDMA/HSPA Phone with BT & WLAN  
 GPRS Class12 and GPRS mode class B(GPRS and GSM, but not simultaneously)  
 Liquid Temperature: 21.1 °C  
 Ambient Temperature: 21.3 °C  
 Test Date: Mar.15, 2011

**DUT: LG-P970h; Type: bar; Serial: #1**


Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3  
 Medium parameters used:  $f = 1880 \text{ MHz}$ ;  $\sigma = 1.38 \text{ mho/m}$ ;  $\epsilon_r = 41.1$ ;  $\rho = 1000 \text{ kg/m}^3$   
 Phantom section: Left Section ; Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 184

DASY4 Configuration:

- Probe: ET3DV6 - SN1630; ConvF(5.12, 5.12, 5.12); Calibrated: 2010-05-25
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn869; Calibrated: 2010-09-21
- Phantom: SAM 1800/1900 MHz; Type: SAM

**Left tilt 661/Area Scan (61x101x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$   
 Maximum value of SAR (interpolated) = 0.308 mW/g

**Left tilt 661/Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$   
 Reference Value = 14.1 V/m; Power Drift = -0.033 dB  
 Peak SAR (extrapolated) = 0.374 W/kg  
**SAR(1 g) = 0.254 mW/g; SAR(10 g) = 0.158 mW/g**  
 Maximum value of SAR (measured) = 0.270 mW/g



0 dB = 0.270mW/g

Test Laboratory: HCT CO., LTD  
EUT Type: Cellular/PCS GSM/GPRS/EDGE/WCDMA/HSPA Phone with BT & WLAN  
GPRS Class12 and GPRS mode class B(GPRS and GSM, but not simultaneously)  
Liquid Temperature: 21.1 °C  
Ambient Temperature: 21.3 °C  
Test Date: Mar.15, 2011

**DUT: LG-P970h; Type: bar; Serial: #1**


Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3  
Medium parameters used:  $f = 1880 \text{ MHz}$ ;  $\sigma = 1.38 \text{ mho/m}$ ;  $\epsilon_r = 41.1$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Right Section ; Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 184

DASY4 Configuration:

- Probe: ET3DV6 - SN1630; ConvF(5.12, 5.12, 5.12); Calibrated: 2010-05-25
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn869; Calibrated: 2010-09-21
- Phantom: SAM 1800/1900 MHz; Type: SAM

**Right touch 661/Area Scan (61x101x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$   
Maximum value of SAR (interpolated) = 0.449 mW/g

**Right touch 661/Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$   
Reference Value = 8.45 V/m; Power Drift = -0.018 dB  
Peak SAR (extrapolated) = 0.625 W/kg  
**SAR(1 g) = 0.410 mW/g; SAR(10 g) = 0.248 mW/g**  
Maximum value of SAR (measured) = 0.442 mW/g



0 dB = 0.442mW/g

Test Laboratory: HCT CO., LTD  
 EUT Type: Cellular/PCS GSM/GPRS/EDGE/WCDMA/HSPA Phone with BT & WLAN  
 GPRS Class12 and GPRS mode class B(GPRS and GSM, but not simultaneously)  
 Liquid Temperature: 21.1 °C  
 Ambient Temperature: 21.3 °C  
 Test Date: Mar.15, 2011

**DUT: LG-P970h; Type: bar; Serial: #1**


Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3  
 Medium parameters used:  $f = 1880 \text{ MHz}$ ;  $\sigma = 1.38 \text{ mho/m}$ ;  $\epsilon_r = 41.1$ ;  $\rho = 1000 \text{ kg/m}^3$   
 Phantom section: Right Section ; Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 184

DASY4 Configuration:

- Probe: ET3DV6 - SN1630; ConvF(5.12, 5.12, 5.12); Calibrated: 2010-05-25
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn869; Calibrated: 2010-09-21
- Phantom: SAM 1800/1900 MHz; Type: SAM

**Right tilt 661/Area Scan (61x101x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$   
 Maximum value of SAR (interpolated) = 0.284 mW/g

**Right tilt 661/Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$   
 Reference Value = 13.7 V/m; Power Drift = -0.035 dB  
 Peak SAR (extrapolated) = 0.383 W/kg  
**SAR(1 g) = 0.250 mW/g; SAR(10 g) = 0.145 mW/g**  
 Maximum value of SAR (measured) = 0.274 mW/g



0 dB = 0.274mW/g

Test Laboratory: HCT CO., LTD  
EUT Type: Cellular/PCS GSM/GPRS/EDGE/WCDMA/HSPA Phone with BT & WLAN  
GPRS Class12 and GPRS mode class B(GPRS and GSM, but not simultaneously)  
Liquid Temperature: 21.1 °C  
Ambient Temperature: 21.3 °C  
Test Date: Mar.14, 2011

**DUT: LG-P970h; Type: bar; Serial: #1**

Communication System: WCDMA850; Frequency: 836.6 MHz; Duty Cycle: 1:1  
Medium parameters used (interpolated):  $f = 836.6$  MHz;  $\sigma = 0.877$  mho/m;  $\epsilon_r = 42.9$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
Phantom section: Left Section ; Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 184

DASY4 Configuration:

- Probe: ET3DV6 - SN1630; ConvF(6.25, 6.25, 6.25); Calibrated: 2010-05-25
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn869; Calibrated: 2010-09-21
- Phantom: 835/900 Phantom ; Type: SAM

**Left touch 4183/Area Scan (61x101x1):** Measurement grid: dx=15mm, dy=15mm

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (interpolated) = 0.419 mW/g


**Left touch 4183/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 9.06 V/m; Power Drift = -0.195 dB

Peak SAR (extrapolated) = 0.492 W/kg

**SAR(1 g) = 0.390 mW/g; SAR(10 g) = 0.279 mW/g**

Maximum value of SAR (measured) = 0.412 mW/g



0 dB = 0.412mW/g

Test Laboratory: HCT CO., LTD  
EUT Type: Cellular/PCS GSM/GPRS/EDGE/WCDMA/HSPA Phone with BT & WLAN  
GPRS Class12 and GPRS mode class B(GPRS and GSM, but not simultaneously)  
Liquid Temperature: 21.1 °C  
Ambient Temperature: 21.3 °C  
Test Date: Mar.14, 2011

**DUT: LG-P970h; Type: bar; Serial: #1**

Communication System: WCDMA850; Frequency: 836.6 MHz; Duty Cycle: 1:1  
Medium parameters used (interpolated):  $f = 836.6$  MHz;  $\sigma = 0.877$  mho/m;  $\epsilon_r = 42.9$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
Phantom section: Left Section ; Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 184

DASY4 Configuration:

- Probe: ET3DV6 - SN1630; ConvF(6.25, 6.25, 6.25); Calibrated: 2010-05-25
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn869; Calibrated: 2010-09-21
- Phantom: 835/900 Phantom ; Type: SAM

**Left tilt 4183/Area Scan (61x101x1):** Measurement grid: dx=15mm, dy=15mm

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (interpolated) = 0.249 mW/g

**Left tilt 4183/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm


Reference Value = 13.3 V/m; Power Drift = -0.091 dB

Peak SAR (extrapolated) = 0.282 W/kg

**SAR(1 g) = 0.242 mW/g; SAR(10 g) = 0.189 mW/g**

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.254 mW/g



0 dB = 0.254mW/g

Test Laboratory: HCT CO., LTD  
EUT Type: Cellular/PCS GSM/GPRS/EDGE/WCDMA/HSPA Phone with BT & WLAN  
GPRS Class12 and GPRS mode class B(GPRS and GSM, but not simultaneously)  
Liquid Temperature: 21.1 °C  
Ambient Temperature: 21.3 °C  
Test Date: Mar.14, 2011

**DUT: LG-P970h; Type: bar; Serial: #1**

Communication System: WCDMA850; Frequency: 836.6 MHz; Duty Cycle: 1:1  
Medium parameters used (interpolated):  $f = 836.6 \text{ MHz}$ ;  $\sigma = 0.877 \text{ mho/m}$ ;  $\epsilon_r = 42.9$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Right Section ; Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 184

DASY4 Configuration:

- Probe: ET3DV6 - SN1630; ConvF(6.25, 6.25, 6.25); Calibrated: 2010-05-25
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn869; Calibrated: 2010-09-21
- Phantom: 835/900 Phantom ; Type: SAM

**Right touch 4183/Area Scan (61x101x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (interpolated) = 0.496 mW/g


**Right touch 4183/Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$

Reference Value = 9.92 V/m; Power Drift = -0.064 dB

Peak SAR (extrapolated) = 0.620 W/kg

**SAR(1 g) = 0.477 mW/g; SAR(10 g) = 0.346 mW/g**

Maximum value of SAR (measured) = 0.501 mW/g



0 dB = 0.501mW/g

Test Laboratory: HCT CO., LTD  
EUT Type: Cellular/PCS GSM/GPRS/EDGE/WCDMA/HSPA Phone with BT & WLAN  
GPRS Class12 and GPRS mode class B(GPRS and GSM, but not simultaneously)  
Liquid Temperature: 21.1 °C  
Ambient Temperature: 21.3 °C  
Test Date: Mar.14, 2011

**DUT: LG-P970h; Type: bar; Serial: #1**

Communication System: WCDMA850; Frequency: 836.6 MHz; Duty Cycle: 1:1  
Medium parameters used (interpolated):  $f = 836.6 \text{ MHz}$ ;  $\sigma = 0.877 \text{ mho/m}$ ;  $\epsilon_r = 42.9$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Right Section ; Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 184

DASY4 Configuration:

- Probe: ET3DV6 - SN1630; ConvF(6.25, 6.25, 6.25); Calibrated: 2010-05-25
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn869; Calibrated: 2010-09-21
- Phantom: 835/900 Phantom ; Type: SAM

**Right tilt 4183/Area Scan (61x101x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (interpolated) = 0.270 mW/g

**Right tilt 4183/Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$


Reference Value = 14.0 V/m; Power Drift = -0.093 dB

Peak SAR (extrapolated) = 0.328 W/kg

**SAR(1 g) = 0.267 mW/g; SAR(10 g) = 0.206 mW/g**

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.278 mW/g



0 dB = 0.278mW/g

Test Laboratory: HCT CO., LTD  
EUT Type: Cellular/PCS GSM/GPRS/EDGE/WCDMA/HSPA Phone with BT & WLAN  
GPRS Class12 and GPRS mode class B(GPRS and GSM, but not simultaneously)  
Liquid Temperature: 21.1 °C  
Ambient Temperature: 21.3 °C  
Test Date: Mar.15, 2011

**DUT: LG-P970h; Type: bar; Serial: #1**

Communication System: WCDMA1900; Frequency: 1852.4 MHz; Duty Cycle: 1:1  
Medium parameters used (interpolated):  $f = 1852.4 \text{ MHz}$ ;  $\sigma = 1.36 \text{ mho/m}$ ;  $\epsilon_r = 41.3$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Left Section ; Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 184

DASY4 Configuration:

- Probe: ET3DV6 - SN1630; ConvF(5.12, 5.12, 5.12); Calibrated: 2010-05-25
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn869; Calibrated: 2010-09-21
- Phantom: SAM 1800/1900 MHz; Type: SAM

**Left touch 9262/Area Scan (51x101x1):** Measurement grid: dx=15mm, dy=15mm

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (interpolated) = 1.08 mW/g

**Left touch 9262/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm


Reference Value = 19.3 V/m; Power Drift = 0.003 dB

Peak SAR (extrapolated) = 1.42 W/kg

**SAR(1 g) = 0.934 mW/g; SAR(10 g) = 0.583 mW/g**

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 1.00 mW/g



0 dB = 1.00mW/g

Test Laboratory: HCT CO., LTD  
EUT Type: Cellular/PCS GSM/GPRS/EDGE/WCDMA/HSPA Phone with BT & WLAN  
GPRS Class12 and GPRS mode class B(GPRS and GSM, but not simultaneously)  
Liquid Temperature: 21.1 °C  
Ambient Temperature: 21.3 °C  
Test Date: Mar.15, 2011

**DUT: LG-P970h; Type: bar; Serial: #1**


Communication System: WCDMA1900; Frequency: 1880 MHz; Duty Cycle: 1:1  
Medium parameters used:  $f = 1880$  MHz;  $\sigma = 1.38$  mho/m;  $\epsilon_r = 41.1$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
Phantom section: Left Section ; Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 184

DASY4 Configuration:

- Probe: ET3DV6 - SN1630; ConvF(5.12, 5.12, 5.12); Calibrated: 2010-05-25
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn869; Calibrated: 2010-09-21
- Phantom: SAM 1800/1900 MHz; Type: SAM

**Left touch 9400/Area Scan (51x101x1):** Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (interpolated) = 1.08 mW/g

**Left touch 9400/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm  
Reference Value = 18.9 V/m; Power Drift = 0.042 dB  
Peak SAR (extrapolated) = 1.46 W/kg  
**SAR(1 g) = 0.949 mW/g; SAR(10 g) = 0.581 mW/g**  
Maximum value of SAR (measured) = 1.03 mW/g



0 dB = 1.03mW/g

Test Laboratory: HCT CO., LTD  
EUT Type: Cellular/PCS GSM/GPRS/EDGE/WCDMA/HSPA Phone with BT & WLAN  
GPRS Class12 and GPRS mode class B(GPRS and GSM, but not simultaneously)  
Liquid Temperature: 21.1 °C  
Ambient Temperature: 21.3 °C  
Test Date: Mar.15, 2011

**DUT: LG-P970h; Type: bar; Serial: #1**

Communication System: WCDMA1900; Frequency: 1907.6 MHz; Duty Cycle: 1:1  
Medium parameters used (interpolated):  $f = 1907.6 \text{ MHz}$ ;  $\sigma = 1.4 \text{ mho/m}$ ;  $\epsilon_r = 40.9$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Left Section ; Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 184

DASY4 Configuration:

- Probe: ET3DV6 - SN1630; ConvF(5.12, 5.12, 5.12); Calibrated: 2010-05-25
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn869; Calibrated: 2010-09-21
- Phantom: SAM 1800/1900 MHz; Type: SAM

**Left touch 9538/Area Scan (51x101x1):** Measurement grid: dx=15mm, dy=15mm

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (interpolated) = 1.03 mW/g

**Left touch 9538/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm


Reference Value = 18.0 V/m; Power Drift = 0.066 dB

Peak SAR (extrapolated) = 1.38 W/kg

**SAR(1 g) = 0.902 mW/g; SAR(10 g) = 0.557 mW/g**

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.986 mW/g



0 dB = 0.986mW/g

Test Laboratory: HCT CO., LTD  
EUT Type: Cellular/PCS GSM/GPRS/EDGE/WCDMA/HSPA Phone with BT & WLAN  
GPRS Class12 and GPRS mode class B(GPRS and GSM, but not simultaneously)  
Liquid Temperature: 21.1 °C  
Ambient Temperature: 21.3 °C  
Test Date: Mar.15, 2011

**DUT: LG-P970h; Type: bar; Serial: #1**


Communication System: WCDMA1900; Frequency: 1880 MHz; Duty Cycle: 1:1  
Medium parameters used:  $f = 1880 \text{ MHz}$ ;  $\sigma = 1.38 \text{ mho/m}$ ;  $\epsilon_r = 41.1$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Left Section ; Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 184

DASY4 Configuration:

- Probe: ET3DV6 - SN1630; ConvF(5.12, 5.12, 5.12); Calibrated: 2010-05-25
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn869; Calibrated: 2010-09-21
- Phantom: SAM 1800/1900 MHz; Type: SAM

**Left touch 9400/Area Scan (51x101x1):** Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (interpolated) = 0.627 mW/g

**Left touch 9400/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm  
Reference Value = 11.6 V/m; Power Drift = 0.053 dB  
Peak SAR (extrapolated) = 0.772 W/kg  
**SAR(1 g) = 0.499 mW/g; SAR(10 g) = 0.312 mW/g**  
Maximum value of SAR (measured) = 0.532 mW/g



0 dB = 0.532mW/g

Test Laboratory: HCT CO., LTD  
 EUT Type: Cellular/PCS GSM/GPRS/EDGE/WCDMA/HSPA Phone with BT & WLAN  
 GPRS Class12 and GPRS mode class B(GPRS and GSM, but not simultaneously)  
 Liquid Temperature: 21.1 °C  
 Ambient Temperature: 21.3 °C  
 Test Date: Mar.15, 2011

**DUT: LG-P970h; Type: bar; Serial: #1**

Communication System: WCDMA1900; Frequency: 1852.4 MHz; Duty Cycle: 1:1  
 Medium parameters used (interpolated):  $f = 1852.4 \text{ MHz}$ ;  $\sigma = 1.36 \text{ mho/m}$ ;  $\epsilon_r = 41.3$ ;  $\rho = 1000 \text{ kg/m}^3$   
 Phantom section: Right Section ; Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 184

DASY4 Configuration:

- Probe: ET3DV6 - SN1630; ConvF(5.12, 5.12, 5.12); Calibrated: 2010-05-25
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn869; Calibrated: 2010-09-21
- Phantom: SAM 1800/1900 MHz; Type: SAM

**Right touch 9262/Area Scan (51x101x1):** Measurement grid: dx=15mm, dy=15mm

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (interpolated) = 1.08 mW/g

**Right touch 9262/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 19.8 V/m; Power Drift = -0.040 dB

Peak SAR (extrapolated) = 1.42 W/kg

**SAR(1 g) = 0.991 mW/g; SAR(10 g) = 0.614 mW/g**

Maximum value of SAR (measured) = 1.07 mW/g


**Right touch 9262/Zoom Scan (5x5x7)/Cube 1:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 19.8 V/m; Power Drift = -0.040 dB

Peak SAR (extrapolated) = 0.963 W/kg

**SAR(1 g) = 0.663 mW/g; SAR(10 g) = 0.422 mW/g**

Maximum value of SAR (measured) = 0.725 mW/g



0 dB = 0.725mW/g

Test Laboratory: HCT CO., LTD  
 EUT Type: Cellular/PCS GSM/GPRS/EDGE/WCDMA/HSPA Phone with BT & WLAN  
 GPRS Class12 and GPRS mode class B(GPRS and GSM, but not simultaneously)  
 Liquid Temperature: 21.1 °C  
 Ambient Temperature: 21.3 °C  
 Test Date: Mar.15, 2011

**DUT: LG-P970h; Type: bar; Serial: #1**


Communication System: WCDMA1900; Frequency: 1880 MHz;Duty Cycle: 1:1  
 Medium parameters used:  $f = 1880 \text{ MHz}$ ;  $\sigma = 1.38 \text{ mho/m}$ ;  $\epsilon_r = 41.1$ ;  $\rho = 1000 \text{ kg/m}^3$   
 Phantom section: Right Section ; Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 184

DASY4 Configuration:  
 - Probe: ET3DV6 - SN1630; ConvF(5.12, 5.12, 5.12); Calibrated: 2010-05-25  
 - Sensor-Surface: 4mm (Mechanical Surface Detection)  
 - Electronics: DAE4 Sn869; Calibrated: 2010-09-21  
 - Phantom: SAM 1800/1900 MHz; Type: SAM

**Right touch 9400/Area Scan (51x101x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$   
 Maximum value of SAR (interpolated) = 1.00 mW/g

**Right touch 9400/Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$   
 Reference Value = 20.1 V/m; Power Drift = -0.031 dB  
 Peak SAR (extrapolated) = 1.29 W/kg  
**SAR(1 g) = 0.906 mW/g; SAR(10 g) = 0.558 mW/g**  
 Maximum value of SAR (measured) = 0.987 mW/g

**Right touch 9400/Zoom Scan (5x5x7)/Cube 1:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$   
 Reference Value = 20.1 V/m; Power Drift = -0.031 dB  
 Peak SAR (extrapolated) = 1.01 W/kg  
**SAR(1 g) = 0.692 mW/g; SAR(10 g) = 0.438 mW/g**  
 Maximum value of SAR (measured) = 0.760 mW/g



0 dB = 0.760mW/g

Test Laboratory: HCT CO., LTD  
 EUT Type: Cellular/PCS GSM/GPRS/EDGE/WCDMA/HSPA Phone with BT & WLAN  
 GPRS Class12 and GPRS mode class B(GPRS and GSM, but not simultaneously)  
 Liquid Temperature: 21.1 °C  
 Ambient Temperature: 21.3 °C  
 Test Date: Mar.15, 2011

**DUT: LG-P970h; Type: bar; Serial: #1**

Communication System: WCDMA1900; Frequency: 1907.6 MHz; Duty Cycle: 1:1  
 Medium parameters used (interpolated):  $f = 1907.6 \text{ MHz}$ ;  $\sigma = 1.4 \text{ mho/m}$ ;  $\epsilon_r = 40.9$ ;  $\rho = 1000 \text{ kg/m}^3$   
 Phantom section: Right Section ; Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 184

DASY4 Configuration:

- Probe: ET3DV6 - SN1630; ConvF(5.12, 5.12, 5.12); Calibrated: 2010-05-25
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn869; Calibrated: 2010-09-21
- Phantom: SAM 1800/1900 MHz; Type: SAM

**Right touch 9538/Area Scan (51x101x1):** Measurement grid: dx=15mm, dy=15mm

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (interpolated) = 0.710 mW/g

**Right touch 9538/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 17.2 V/m; Power Drift = -0.136 dB

Peak SAR (extrapolated) = 0.937 W/kg

**SAR(1 g) = 0.643 mW/g; SAR(10 g) = 0.392 mW/g**

Maximum value of SAR (measured) = 0.702 mW/g


**Right touch 9538/Zoom Scan (5x5x7)/Cube 1:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 17.2 V/m; Power Drift = -0.136 dB

Peak SAR (extrapolated) = 0.747 W/kg

**SAR(1 g) = 0.511 mW/g; SAR(10 g) = 0.319 mW/g**

Maximum value of SAR (measured) = 0.548 mW/g



0 dB = 0.548mW/g

Test Laboratory: HCT CO., LTD  
 EUT Type: Cellular/PCS GSM/GPRS/EDGE/WCDMA/HSPA Phone with BT & WLAN  
 GPRS Class12 and GPRS mode class B(GPRS and GSM, but not simultaneously)  
 Liquid Temperature: 21.1 °C  
 Ambient Temperature: 21.3 °C  
 Test Date: Mar.15, 2011


**DUT: LG-P970h; Type: bar; Serial: #1**

Communication System: WCDMA1900; Frequency: 1880 MHz;Duty Cycle: 1:1  
 Medium parameters used:  $f = 1880 \text{ MHz}$ ;  $\sigma = 1.38 \text{ mho/m}$ ;  $\epsilon_r = 41.1$ ;  $\rho = 1000 \text{ kg/m}^3$   
 Phantom section: Right Section ; Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 184

DASY4 Configuration:  
 - Probe: ET3DV6 - SN1630; ConvF(5.12, 5.12, 5.12); Calibrated: 2010-05-25  
 - Sensor-Surface: 4mm (Mechanical Surface Detection)  
 - Electronics: DAE4 Sn869; Calibrated: 2010-09-21  
 - Phantom: SAM 1800/1900 MHz; Type: SAM

**Right tilt 9400/Area Scan (51x101x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$   
 Maximum value of SAR (interpolated) = 0.376 mW/g

**Right tilt 9400/Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$   
 Reference Value = 10.0 V/m; Power Drift = 0.064 dB  
 Peak SAR (extrapolated) = 0.522 W/kg  
**SAR(1 g) = 0.341 mW/g; SAR(10 g) = 0.198 mW/g**  
 Maximum value of SAR (measured) = 0.378 mW/g



0 dB = 0.378mW/g

Test Laboratory: HCT CO., LTD  
EUT Type: Cellular/PCS GSM/GPRS/EDGE/WCDMA/HSPA Phone with BT & WLAN  
GPRS Class12 and GPRS mode class B(GPRS and GSM, but not simultaneously)  
Liquid Temperature: 21.1 °C  
Ambient Temperature: 21.3 °C  
Test Date: Feb.23, 2011

**DUT: LG-P970h; Type: bar; Serial: #1**

Communication System: 2450MHz FCC; Frequency: 2462 MHz; Duty Cycle: 1:1  
Medium parameters used (interpolated):  $f = 2462 \text{ MHz}$ ;  $\sigma = 1.91 \text{ mho/m}$ ;  $\epsilon_r = 38.2$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Left Section ; Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 184

DASY4 Configuration:

- Probe: ES3DV3 - SN3161; ConvF(4.26, 4.26, 4.26); Calibrated: 2010-03-22
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn869; Calibrated: 2010-09-21
- Phantom: SAM 1800/1900 MHz; Type: SAM

**Left touch 11/Area Scan (61x101x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (interpolated) = 0.520 mW/g

**Left touch 11/Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$


Reference Value = 8.10 V/m; Power Drift = -0.108 dB

Peak SAR (extrapolated) = 1.21 W/kg

**SAR(1 g) = 0.487 mW/g; SAR(10 g) = 0.216 mW/g**

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.529 mW/g



0 dB = 0.529mW/g

Test Laboratory: HCT CO., LTD  
EUT Type: Cellular/PCS GSM/GPRS/EDGE/WCDMA/HSPA Phone with BT & WLAN  
GPRS Class12 and GPRS mode class B(GPRS and GSM, but not simultaneously)  
Liquid Temperature: 21.1 °C  
Ambient Temperature: 21.3 °C  
Test Date: Feb.23, 2011

**DUT: LG-P970h; Type: bar; Serial: #1**

Communication System: 2450MHz FCC; Frequency: 2462 MHz;Duty Cycle: 1:1  
Medium parameters used (interpolated):  $f = 2462 \text{ MHz}$ ;  $\sigma = 1.91 \text{ mho/m}$ ;  $\epsilon_r = 38.2$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Left Section ; Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 184

DASY4 Configuration:

- Probe: ES3DV3 - SN3161; ConvF(4.26, 4.26, 4.26); Calibrated: 2010-03-22
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn869; Calibrated: 2010-09-21
- Phantom: SAM 1800/1900 MHz; Type: SAM

**Left tilt 11/Area Scan (61x101x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (interpolated) = 0.324 mW/g

**Left tilt 11/Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$


Reference Value = 9.05 V/m; Power Drift = -0.047 dB

Peak SAR (extrapolated) = 0.672 W/kg

**SAR(1 g) = 0.278 mW/g; SAR(10 g) = 0.126 mW/g**

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.310 mW/g



Test Laboratory: HCT CO., LTD  
EUT Type: Cellular/PCS GSM/GPRS/EDGE/WCDMA/HSPA Phone with BT & WLAN  
GPRS Class12 and GPRS mode class B(GPRS and GSM, but not simultaneously)  
Liquid Temperature: 21.1 °C  
Ambient Temperature: 21.3 °C  
Test Date: Feb.23, 2011

**DUT: LG-P970h; Type: bar; Serial: #1**

Communication System: 2450MHz FCC; Frequency: 2462 MHz; Duty Cycle: 1:1  
Medium parameters used (interpolated):  $f = 2462 \text{ MHz}$ ;  $\sigma = 1.91 \text{ mho/m}$ ;  $\epsilon_r = 38.2$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Right Section ; Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 184

DASY4 Configuration:

- Probe: ES3DV3 - SN3161; ConvF(4.26, 4.26, 4.26); Calibrated: 2010-03-22
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn869; Calibrated: 2010-09-21
- Phantom: SAM 1800/1900 MHz; Type: SAM

**Right touch 11/Area Scan (61x101x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (interpolated) = 0.222 mW/g

**Right touch 11/Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$


Reference Value = 9.43 V/m; Power Drift = 0.098 dB

Peak SAR (extrapolated) = 0.414 W/kg

**SAR(1 g) = 0.197 mW/g; SAR(10 g) = 0.101 mW/g**

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.211 mW/g



Test Laboratory: HCT CO., LTD  
 EUT Type: Cellular/PCS GSM/GPRS/EDGE/WCDMA/HSPA Phone with BT & WLAN  
 GPRS Class12 and GPRS mode class B(GPRS and GSM, but not simultaneously)  
 Liquid Temperature: 21.1 °C  
 Ambient Temperature: 21.3 °C  
 Test Date: Feb.23, 2011

**DUT: LG-P970h; Type: bar; Serial: #1**

Communication System: 2450MHz FCC; Frequency: 2462 MHz;Duty Cycle: 1:1  
 Medium parameters used (interpolated):  $f = 2462 \text{ MHz}$ ;  $\sigma = 1.91 \text{ mho/m}$ ;  $\epsilon_r = 38.2$ ;  $\rho = 1000 \text{ kg/m}^3$   
 Phantom section: Right Section ; Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 184

DASY4 Configuration:  
 - Probe: ES3DV3 - SN3161; ConvF(4.26, 4.26, 4.26); Calibrated: 2010-03-22  
 - Sensor-Surface: 4mm (Mechanical Surface Detection)  
 - Electronics: DAE4 Sn869; Calibrated: 2010-09-21  
 - Phantom: SAM 1800/1900 MHz; Type: SAM

**Right tilt 11/Area Scan (61x101x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (interpolated) = 0.185 mW/g

**Right tilt 11/Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$


Reference Value = 9.55 V/m; Power Drift = -0.004 dB

Peak SAR (extrapolated) = 0.314 W/kg

**SAR(1 g) = 0.155 mW/g; SAR(10 g) = 0.080 mW/g**

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.169 mW/g



0 dB = 0.169mW/g

Test Laboratory: HCT CO., LTD  
EUT Type: Cellular/PCS GSM/GPRS/EDGE/WCDMA/HSPA Phone with BT & WLAN  
GPRS Class12 and GPRS mode class B(GPRS and GSM, but not simultaneously)  
Liquid Temperature: 21.1 °C  
Ambient Temperature: 21.3 °C  
Test Date: Mar.14, 2011

**DUT: LG-P970h; Type: bar; Serial: #1**

Communication System: GSM 850; Frequency: 836.6 MHz; Duty Cycle: 1:2.075  
Medium parameters used (interpolated):  $f = 836.6$  MHz;  $\sigma = 0.982$  mho/m;  $\epsilon_r = 56.8$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
Phantom section: Flat Section ; Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8  
Build 184

DASY4 Configuration:

- Probe: ET3DV6 - SN1630; ConvF(6.17, 6.17, 6.17); Calibrated: 2010-05-25
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn869; Calibrated: 2010-09-21
- Phantom: 835/900 Phantom ; Type: SAM

**Body 190/Area Scan (61x101x1):** Measurement grid: dx=15mm, dy=15mm

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (interpolated) = 0.710 mW/g

**Body 190/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm


Reference Value = 12.6 V/m; Power Drift = 0.048 dB

Peak SAR (extrapolated) = 0.818 W/kg

**SAR(1 g) = 0.671 mW/g; SAR(10 g) = 0.505 mW/g**

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.708 mW/g



0 dB = 0.708mW/g

Test Laboratory: HCT CO., LTD  
 EUT Type: Cellular/PCS GSM/GPRS/EDGE/WCDMA/HSPA Phone with BT & WLAN  
 GPRS Class12 and GPRS mode class B(GPRS and GSM, but not simultaneously)  
 Liquid Temperature: 21.1 °C  
 Ambient Temperature: 21.3 °C  
 Test Date: Mar.14, 2011

**DUT: LG-P970h; Type: bar; Serial: #1**


Communication System: GSM 850; Frequency: 824.2 MHz; Duty Cycle: 1:2.075  
 Medium parameters used:  $f = 825 \text{ MHz}$ ;  $\sigma = 0.97 \text{ mho/m}$ ;  $\epsilon_r = 56.9$ ;  $\rho = 1000 \text{ kg/m}^3$   
 Phantom section: Flat Section ; Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 184

DASY4 Configuration:

- Probe: ET3DV6 - SN1630; ConvF(6.17, 6.17, 6.17); Calibrated: 2010-05-25
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn869; Calibrated: 2010-09-21
- Phantom: 835/900 Phantom ; Type: SAM

**Body 128/Area Scan (61x101x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$   
 Maximum value of SAR (interpolated) = 0.992 mW/g

**Body 128/Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$   
 Reference Value = 14.5 V/m; Power Drift = -0.051 dB  
 Peak SAR (extrapolated) = 1.17 W/kg  
**SAR(1 g) = 0.933 mW/g; SAR(10 g) = 0.695 mW/g**  
 Maximum value of SAR (measured) = 0.982 mW/g



0 dB = 0.982mW/g

Test Laboratory: HCT CO., LTD  
 EUT Type: Cellular/PCS GSM/GPRS/EDGE/WCDMA/HSPA Phone with BT & WLAN  
 GPRS Class12 and GPRS mode class B(GPRS and GSM, but not simultaneously)  
 Liquid Temperature: 21.1 °C  
 Ambient Temperature: 21.3 °C  
 Test Date: Mar.14, 2011

**DUT: LG-P970h; Type: bar; Serial: #1**

Communication System: GSM 850; Frequency: 836.6 MHz; Duty Cycle: 1:2.075  
 Medium parameters used (interpolated):  $f = 836.6 \text{ MHz}$ ;  $\sigma = 0.982 \text{ mho/m}$ ;  $\epsilon_r = 56.8$ ;  $\rho = 1000 \text{ kg/m}^3$   
 Phantom section: Flat Section ; Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8  
 Build 184

DASY4 Configuration:  
 - Probe: ET3DV6 - SN1630; ConvF(6.17, 6.17, 6.17); Calibrated: 2010-05-25  
 - Sensor-Surface: 4mm (Mechanical Surface Detection)  
 - Electronics: DAE4 Sn869; Calibrated: 2010-09-21  
 - Phantom: 835/900 Phantom ; Type: SAM

**Body 190/Area Scan (61x101x1):** Measurement grid: dx=15mm, dy=15mm

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (interpolated) = 1.08 mW/g

**Body 190/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm


Reference Value = 15.3 V/m; Power Drift = -0.111 dB

Peak SAR (extrapolated) = 1.25 W/kg

**SAR(1 g) = 1.01 mW/g; SAR(10 g) = 0.750 mW/g**

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 1.06 mW/g



0 dB = 1.06mW/g

Test Laboratory: HCT CO., LTD  
EUT Type: Cellular/PCS GSM/GPRS/EDGE/WCDMA/HSPA Phone with BT & WLAN  
GPRS Class12 and GPRS mode class B(GPRS and GSM, but not simultaneously)  
Liquid Temperature: 21.1 °C  
Ambient Temperature: 21.3 °C  
Test Date: Mar.14, 2011

**DUT: LG-P970h; Type: bar; Serial: #1**

Communication System: GSM 850; Frequency: 848.8 MHz; Duty Cycle: 1:2.075  
Medium parameters used (interpolated):  $f = 848.8 \text{ MHz}$ ;  $\sigma = 0.992 \text{ mho/m}$ ;  $\epsilon_r = 56.7$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Flat Section ; Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 184

DASY4 Configuration:

- Probe: ET3DV6 - SN1630; ConvF(6.17, 6.17, 6.17); Calibrated: 2010-05-25
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn869; Calibrated: 2010-09-21
- Phantom: 835/900 Phantom ; Type: SAM

**Body 251/Area Scan (61x101x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (interpolated) = 1.18 mW/g

**Body 251/Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$


Reference Value = 19.8 V/m; Power Drift = 0.025 dB

Peak SAR (extrapolated) = 1.39 W/kg

**SAR(1 g) = 1.11 mW/g; SAR(10 g) = 0.821 mW/g**

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 1.17 mW/g



0 dB = 1.17mW/g

Test Laboratory: HCT CO., LTD  
EUT Type: Cellular/PCS GSM/GPRS/EDGE/WCDMA/HSPA Phone with BT & WLAN  
GPRS Class12 and GPRS mode class B(GPRS and GSM, but not simultaneously)  
Liquid Temperature: 21.1 °C  
Ambient Temperature: 21.3 °C  
Test Date: Mar.14, 2011  
Option: Edge A

**DUT: LG-P970h(side); Type: bar; Serial: #1**

Communication System: GSM 850; Frequency: 836.6 MHz; Duty Cycle: 1:2.075  
Medium parameters used (interpolated):  $f = 836.6$  MHz;  $\sigma = 0.982$  mho/m;  $\epsilon_r = 56.8$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
Phantom section: Flat Section ; Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 184

DASY4 Configuration:

- Probe: ET3DV6 - SN1630; ConvF(6.17, 6.17, 6.17); Calibrated: 2010-05-25
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn869; Calibrated: 2010-09-21
- Phantom: 835/900 Phantom ; Type: SAM

**Body 190/Area Scan (31x91x1):** Measurement grid: dx=15mm, dy=15mm

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (interpolated) = 0.598 mW/g

**Body 190/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm


Reference Value = 17.9 V/m; Power Drift = 0.070 dB

Peak SAR (extrapolated) = 0.759 W/kg

**SAR(1 g) = 0.554 mW/g; SAR(10 g) = 0.382 mW/g**

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.589 mW/g



0 dB = 0.589mW/g

Test Laboratory: HCT CO., LTD  
EUT Type: Cellular/PCS GSM/GPRS/EDGE/WCDMA/HSPA Phone with BT & WLAN  
GPRS Class12 and GPRS mode class B(GPRS and GSM, but not simultaneously)  
Liquid Temperature: 21.1 °C  
Ambient Temperature: 21.3 °C  
Test Date: Mar.14, 2011  
Option: Edge B

**DUT: LG-P970h(side); Type: bar; Serial: #1**

Communication System: GSM 850; Frequency: 836.6 MHz; Duty Cycle: 1:2.075  
Medium parameters used (interpolated):  $f = 836.6 \text{ MHz}$ ;  $\sigma = 0.982 \text{ mho/m}$ ;  $\epsilon_r = 56.8$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Flat Section ; Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 184

DASY4 Configuration:

- Probe: ET3DV6 - SN1630; ConvF(6.17, 6.17, 6.17); Calibrated: 2010-05-25
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn869; Calibrated: 2010-09-21
- Phantom: 835/900 Phantom ; Type: SAM

**Body 190/Area Scan (31x91x1):** Measurement grid: dx=15mm, dy=15mm

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (interpolated) = 0.835 mW/g

**Body 190/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm


Reference Value = 20.7 V/m; Power Drift = -0.045 dB

Peak SAR (extrapolated) = 1.08 W/kg

**SAR(1 g) = 0.778 mW/g; SAR(10 g) = 0.542 mW/g**

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.831 mW/g



0 dB = 0.831mW/g

Test Laboratory: HCT CO., LTD  
 EUT Type: Cellular/PCS GSM/GPRS/EDGE/WCDMA/HSPA Phone with BT & WLAN  
 GPRS Class12 and GPRS mode class B(GPRS and GSM, but not simultaneously)  
 Liquid Temperature: 21.1 °C  
 Ambient Temperature: 21.3 °C  
 Test Date: Mar.14, 2011  
 Option: Edge C

**DUT: LG-P970h; Type: Top; Serial: #1**

Communication System: GSM 850; Frequency: 836.6 MHz; Duty Cycle: 1:2.075  
 Medium parameters used (interpolated):  $f = 836.6 \text{ MHz}$ ;  $\sigma = 0.982 \text{ mho/m}$ ;  $\epsilon_r = 56.8$ ;  $\rho = 1000 \text{ kg/m}^3$   
 Phantom section: Flat Section ; Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 184

DASY4 Configuration:  
 - Probe: ET3DV6 - SN1630; ConvF(6.17, 6.17, 6.17); Calibrated: 2010-05-25  
 - Sensor-Surface: 4mm (Mechanical Surface Detection)  
 - Electronics: DAE4 Sn869; Calibrated: 2010-09-21  
 - Phantom: 835/900 Phantom ; Type: SAM

**Body 190/Area Scan (41x61x1):** Measurement grid: dx=15mm, dy=15mm

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (interpolated) = 0.187 mW/g


**Body 190/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 7.84 V/m; Power Drift = -0.07 dB

Peak SAR (extrapolated) = 0.657 W/kg

**SAR(1 g) = 0.187 mW/g; SAR(10 g) = 0.101 mW/g**

Maximum value of SAR (measured) = 0.229 mW/g



0 dB = 0.229mW/g

Test Laboratory: HCT CO., LTD  
 EUT Type: Cellular/PCS GSM/GPRS/EDGE/WCDMA/HSPA Phone with BT & WLAN  
 GPRS Class12 and GPRS mode class B(GPRS and GSM, but not simultaneously)  
 Liquid Temperature: 21.1 °C  
 Ambient Temperature: 21.3 °C  
 Test Date: Mar.15, 2011

**DUT: LG-P970h; Type: bar; Serial: #1**


Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:2.075  
 Medium parameters used:  $f = 1880 \text{ MHz}$ ;  $\sigma = 1.54 \text{ mho/m}$ ;  $\epsilon_r = 52.1$ ;  $\rho = 1000 \text{ kg/m}^3$   
 Phantom section: Flat Section ; Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 184

DASY4 Configuration:

- Probe: ET3DV6 - SN1630; ConvF(4.55, 4.55, 4.55); Calibrated: 2010-05-25
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn869; Calibrated: 2010-09-21
- Phantom: SAM 1800/1900 MHz; Type: SAM

**Body 661/Area Scan (51x101x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$   
 Maximum value of SAR (interpolated) = 0.791 mW/g

**Body 661/Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$   
 Reference Value = 11.0 V/m; Power Drift = -0.021 dB  
 Peak SAR (extrapolated) = 0.828 W/kg  
**SAR(1 g) = 0.526 mW/g; SAR(10 g) = 0.310 mW/g**  
 Maximum value of SAR (measured) = 0.584 mW/g



0 dB = 0.584mW/g

Test Laboratory: HCT CO., LTD  
EUT Type: Cellular/PCS GSM/GPRS/EDGE/WCDMA/HSPA Phone with BT & WLAN  
GPRS Class12 and GPRS mode class B(GPRS and GSM, but not simultaneously)  
Liquid Temperature: 21.1 °C  
Ambient Temperature: 21.3 °C  
Test Date: Mar.15, 2011

**DUT: LG-P970h; Type: bar; Serial: #1**

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:2.075  
Medium parameters used:  $f = 1880 \text{ MHz}$ ;  $\sigma = 1.54 \text{ mho/m}$ ;  $\epsilon_r = 52.1$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Flat Section ; Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 184


DASY4 Configuration:

- Probe: ET3DV6 - SN1630; ConvF(4.55, 4.55, 4.55); Calibrated: 2010-05-25
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn869; Calibrated: 2010-09-21
- Phantom: SAM 1800/1900 MHz; Type: SAM

**Body 661/Area Scan (51x101x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$   
Maximum value of SAR (interpolated) = 0.593 mW/g

**Body 661/Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$   
Reference Value = 11.9 V/m; Power Drift = -0.017 dB  
Peak SAR (extrapolated) = 0.842 W/kg  
**SAR(1 g) = 0.558 mW/g; SAR(10 g) = 0.331 mW/g**  
Maximum value of SAR (measured) = 0.609 mW/g

**Body 661/Zoom Scan (5x5x7)/Cube 1:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$   
Reference Value = 11.9 V/m; Power Drift = -0.017 dB  
Peak SAR (extrapolated) = 0.865 W/kg  
**SAR(1 g) = 0.534 mW/g; SAR(10 g) = 0.288 mW/g**  
Maximum value of SAR (measured) = 0.619 mW/g



0 dB = 0.619mW/g

Test Laboratory: HCT CO., LTD  
EUT Type: Cellular/PCS GSM/GPRS/EDGE/WCDMA/HSPA Phone with BT & WLAN  
GPRS Class12 and GPRS mode class B(GPRS and GSM, but not simultaneously)  
Liquid Temperature: 21.1 °C  
Ambient Temperature: 21.3 °C  
Test Date: Mar.15, 2011  
Option: Edge A

**DUT: LG-P970h(side); Type: bar; Serial: #1**


Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:2.075  
Medium parameters used:  $f = 1880$  MHz;  $\sigma = 1.54$  mho/m;  $\epsilon_r = 52.1$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
Phantom section: Flat Section ; Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 184

**DASY4 Configuration:**

- Probe: ET3DV6 - SN1630; ConvF(4.55, 4.55, 4.55); Calibrated: 2010-05-25
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn869; Calibrated: 2010-09-21
- Phantom: SAM 1800/1900 MHz; Type: SAM

**Body 661/Area Scan (31x101x1):** Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (interpolated) = 0.242 mW/g

**Body 661/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm  
Reference Value = 9.19 V/m; Power Drift = -0.039 dB  
Peak SAR (extrapolated) = 0.335 W/kg  
**SAR(1 g) = 0.214 mW/g; SAR(10 g) = 0.123 mW/g**  
Maximum value of SAR (measured) = 0.236 mW/g



0 dB = 0.236mW/g

Test Laboratory: HCT CO., LTD  
EUT Type: Cellular/PCS GSM/GPRS/EDGE/WCDMA/HSPA Phone with BT & WLAN  
GPRS Class12 and GPRS mode class B(GPRS and GSM, but not simultaneously)  
Liquid Temperature: 21.1 °C  
Ambient Temperature: 21.3 °C  
Test Date: Mar.15, 2011  
Option: Edge B

**DUT: LG-P970h(side); Type: bar; Serial: #1**


Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:2.075  
Medium parameters used:  $f = 1880 \text{ MHz}$ ;  $\sigma = 1.54 \text{ mho/m}$ ;  $\epsilon_r = 52.1$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Flat Section ; Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 184

DASY4 Configuration:

- Probe: ET3DV6 - SN1630; ConvF(4.55, 4.55, 4.55); Calibrated: 2010-05-25
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn869; Calibrated: 2010-09-21
- Phantom: SAM 1800/1900 MHz; Type: SAM

**Body 661/Area Scan (31x101x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$   
Maximum value of SAR (interpolated) = 0.178 mW/g

**Body 661/Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$   
Reference Value = 10.5 V/m; Power Drift = 0.075 dB  
Peak SAR (extrapolated) = 0.241 W/kg  
**SAR(1 g) = 0.157 mW/g; SAR(10 g) = 0.092 mW/g**  
Maximum value of SAR (measured) = 0.171 mW/g



0 dB = 0.171mW/g

Test Laboratory: HCT CO., LTD  
EUT Type: Cellular/PCS GSM/GPRS/EDGE/WCDMA/HSPA Phone with BT & WLAN  
GPRS Class12 and GPRS mode class B(GPRS and GSM, but not simultaneously)  
Liquid Temperature: 21.1 °C  
Ambient Temperature: 21.3 °C  
Test Date: Mar.15, 2011  
Option Edge C


**DUT: LG-P970h; Type: Top; Serial: #1**

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:2.075  
Medium parameters used:  $f = 1880 \text{ MHz}$ ;  $\sigma = 1.54 \text{ mho/m}$ ;  $\epsilon_r = 52.1$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Flat Section ; Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 184

DASY4 Configuration:  
- Probe: ET3DV6 - SN1630; ConvF(4.55, 4.55, 4.55); Calibrated: 2010-05-25  
- Sensor-Surface: 4mm (Mechanical Surface Detection)  
- Electronics: DAE4 Sn869; Calibrated: 2010-09-21  
- Phantom: SAM 1800/1900 MHz; Type: SAM

**Body 661/Area Scan (31x61x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$   
Maximum value of SAR (interpolated) = 0.659 mW/g

**Body 661/Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$   
Reference Value = 17.3 V/m; Power Drift = 0.063 dB  
Peak SAR (extrapolated) = 0.923 W/kg  
**SAR(1 g) = 0.567 mW/g; SAR(10 g) = 0.299 mW/g**  
Maximum value of SAR (measured) = 0.664 mW/g



0 dB = 0.664mW/g

Test Laboratory: HCT CO., LTD  
EUT Type: Cellular/PCS GSM/GPRS/EDGE/WCDMA/HSPA Phone with BT & WLAN  
GPRS Class12 and GPRS mode class B(GPRS and GSM, but not simultaneously)  
Liquid Temperature: 21.1 °C  
Ambient Temperature: 21.3 °C  
Test Date: Mar.14, 2011

**DUT: LG-P970h; Type: bar; Serial: #1**

Communication System: WCDMA850; Frequency: 836.6 MHz; Duty Cycle: 1:1  
Medium parameters used (interpolated):  $f = 836.6 \text{ MHz}$ ;  $\sigma = 0.982 \text{ mho/m}$ ;  $\epsilon_r = 56.8$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Flat Section ; Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8  
Build 184

DASY4 Configuration:

- Probe: ET3DV6 - SN1630; ConvF(6.17, 6.17, 6.17); Calibrated: 2010-05-25
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn869; Calibrated: 2010-09-21
- Phantom: 835/900 Phantom ; Type: SAM

**Body 4183/Area Scan (51x101x1):** Measurement grid: dx=15mm, dy=15mm

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (interpolated) = 0.646 mW/g

**Body 4183/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm


Reference Value = 11.6 V/m; Power Drift = 0.040 dB

Peak SAR (extrapolated) = 0.740 W/kg

**SAR(1 g) = 0.607 mW/g; SAR(10 g) = 0.458 mW/g**

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.637 mW/g



0 dB = 0.637mW/g

Test Laboratory: HCT CO., LTD  
EUT Type: Cellular/PCS GSM/GPRS/EDGE/WCDMA/HSPA Phone with BT & WLAN  
GPRS Class12 and GPRS mode class B(GPRS and GSM, but not simultaneously)  
Liquid Temperature: 21.1 °C  
Ambient Temperature: 21.3 °C  
Test Date: Mar.14, 2011

**DUT: LG-P970h; Type: bar; Serial: #1**

Communication System: WCDMA850; Frequency: 826.4 MHz; Duty Cycle: 1:1  
Medium parameters used (interpolated):  $f = 826.4$  MHz;  $\sigma = 0.972$  mho/m;  $\epsilon_r = 56.9$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
Phantom section: Flat Section ; Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 184

DASY4 Configuration:

- Probe: ET3DV6 - SN1630; ConvF(6.17, 6.17, 6.17); Calibrated: 2010-05-25
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn869; Calibrated: 2010-09-21
- Phantom: 835/900 Phantom ; Type: SAM

**Body 4132/Area Scan (51x101x1):** Measurement grid: dx=15mm, dy=15mm

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (interpolated) = 0.996 mW/g

**Body 4132/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm


Reference Value = 17.1 V/m; Power Drift = 0.039 dB

Peak SAR (extrapolated) = 1.16 W/kg

**SAR(1 g) = 0.936 mW/g; SAR(10 g) = 0.695 mW/g**

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.988 mW/g



0 dB = 0.988mW/g

Test Laboratory: HCT CO., LTD  
EUT Type: Cellular/PCS GSM/GPRS/EDGE/WCDMA/HSPA Phone with BT & WLAN  
GPRS Class12 and GPRS mode class B(GPRS and GSM, but not simultaneously)  
Liquid Temperature: 21.1 °C  
Ambient Temperature: 21.3 °C  
Test Date: Mar.14, 2011

**DUT: LG-P970h; Type: bar; Serial: #1**

Communication System: WCDMA850; Frequency: 836.6 MHz; Duty Cycle: 1:1  
Medium parameters used (interpolated):  $f = 836.6 \text{ MHz}$ ;  $\sigma = 0.982 \text{ mho/m}$ ;  $\epsilon_r = 56.8$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Flat Section ; Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 184

DASY4 Configuration:

- Probe: ET3DV6 - SN1630; ConvF(6.17, 6.17, 6.17); Calibrated: 2010-05-25
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn869; Calibrated: 2010-09-21
- Phantom: 835/900 Phantom ; Type: SAM

**Body 4183/Area Scan (51x101x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (interpolated) = 0.958 mW/g

**Body 4183/Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$


Reference Value = 14.8 V/m; Power Drift = -0.194 dB

Peak SAR (extrapolated) = 1.11 W/kg

**SAR(1 g) = 0.890 mW/g; SAR(10 g) = 0.660 mW/g**

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.939 mW/g



0 dB = 0.939mW/g

Test Laboratory: HCT CO., LTD  
 EUT Type: Cellular/PCS GSM/GPRS/EDGE/WCDMA/HSPA Phone with BT & WLAN  
 GPRS Class12 and GPRS mode class B(GPRS and GSM, but not simultaneously)  
 Liquid Temperature: 21.1 °C  
 Ambient Temperature: 21.3 °C  
 Test Date: Mar.14, 2011

**DUT: LG-P970h; Type: bar; Serial: #1**

Communication System: WCDMA850; Frequency: 846.4 MHz; Duty Cycle: 1:1  
 Medium parameters used (interpolated):  $f = 846.4 \text{ MHz}$ ;  $\sigma = 0.99 \text{ mho/m}$ ;  $\epsilon_r = 56.7$ ;  $\rho = 1000 \text{ kg/m}^3$   
 Phantom section: Flat Section ; Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 184


DASY4 Configuration:  
 - Probe: ET3DV6 - SN1630; ConvF(6.17, 6.17, 6.17); Calibrated: 2010-05-25  
 - Sensor-Surface: 4mm (Mechanical Surface Detection)  
 - Electronics: DAE4 Sn869; Calibrated: 2010-09-21  
 - Phantom: 835/900 Phantom ; Type: SAM

**Body 4233/Area Scan (51x101x1):** Measurement grid: dx=15mm, dy=15mm

[Info: Interpolated medium parameters used for SAR evaluation.](#)  
 Maximum value of SAR (interpolated) = 1.01 mW/g

**Body 4233/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm  
 Reference Value = 15.2 V/m; Power Drift = -0.051 dB  
 Peak SAR (extrapolated) = 1.18 W/kg  
**SAR(1 g) = 0.946 mW/g; SAR(10 g) = 0.700 mW/g**

[Info: Interpolated medium parameters used for SAR evaluation.](#)  
 Maximum value of SAR (measured) = 0.999 mW/g



0 dB = 0.999mW/g

Test Laboratory: HCT CO., LTD  
EUT Type: Cellular/PCS GSM/GPRS/EDGE/WCDMA/HSPA Phone with BT & WLAN  
GPRS Class12 and GPRS mode class B(GPRS and GSM, but not simultaneously)  
Liquid Temperature: 21.1 °C  
Ambient Temperature: 21.3 °C  
Test Date: Mar.14, 2011  
Option Edge A

**DUT: LG-P970h(side); Type: bar; Serial: #1**

Communication System: WCDMA850; Frequency: 836.6 MHz; Duty Cycle: 1:1  
Medium parameters used (interpolated):  $f = 836.6 \text{ MHz}$ ;  $\sigma = 0.982 \text{ mho/m}$ ;  $\epsilon_r = 56.8$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Flat Section ; Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 184

DASY4 Configuration:

- Probe: ET3DV6 - SN1630; ConvF(6.17, 6.17, 6.17); Calibrated: 2010-05-25
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn869; Calibrated: 2010-09-21
- Phantom: 835/900 Phantom ; Type: SAM

**Body 4183/Area Scan (31x91x1):** Measurement grid: dx=15mm, dy=15mm

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (interpolated) = 0.659 mW/g

**Body 4183/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm


Reference Value = 20.0 V/m; Power Drift = 0.003 dB

Peak SAR (extrapolated) = 0.836 W/kg

**SAR(1 g) = 0.610 mW/g; SAR(10 g) = 0.421 mW/g**

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.646 mW/g



0 dB = 0.646mW/g

Test Laboratory: HCT CO., LTD  
EUT Type: Cellular/PCS GSM/GPRS/EDGE/WCDMA/HSPA Phone with BT & WLAN  
GPRS Class12 and GPRS mode class B(GPRS and GSM, but not simultaneously)  
Liquid Temperature: 21.1 °C  
Ambient Temperature: 21.3 °C  
Test Date: Mar.14, 2011  
Option: Edge B

**DUT: LG-P970h(side); Type: bar; Serial: #1**

Communication System: WCDMA850; Frequency: 836.6 MHz; Duty Cycle: 1:1  
Medium parameters used (interpolated):  $f = 836.6 \text{ MHz}$ ;  $\sigma = 0.982 \text{ mho/m}$ ;  $\epsilon_r = 56.8$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Flat Section ; Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 184

DASY4 Configuration:

- Probe: ET3DV6 - SN1630; ConvF(6.17, 6.17, 6.17); Calibrated: 2010-05-25
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn869; Calibrated: 2010-09-21
- Phantom: 835/900 Phantom ; Type: SAM

**Body 4183/Area Scan (31x91x1):** Measurement grid: dx=15mm, dy=15mm

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (interpolated) = 0.723 mW/g

**Body 4183/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm


Reference Value = 18.1 V/m; Power Drift = 0.062 dB

Peak SAR (extrapolated) = 0.906 W/kg

**SAR(1 g) = 0.671 mW/g; SAR(10 g) = 0.467 mW/g**

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.712 mW/g



0 dB = 0.712mW/g

Test Laboratory: HCT CO., LTD  
 EUT Type: Cellular/PCS GSM/GPRS/EDGE/WCDMA/HSPA Phone with BT & WLAN  
 GPRS Class12 and GPRS mode class B(GPRS and GSM, but not simultaneously)  
 Liquid Temperature: 21.1 °C  
 Ambient Temperature: 21.3 °C  
 Test Date: Mar.14, 2011  
 Option: Edge C

**DUT: LG-P970h; Type: Top; Serial: #1**

Communication System: WCDMA850; Frequency: 836.6 MHz; Duty Cycle: 1:1  
 Medium parameters used (interpolated):  $f = 836.6 \text{ MHz}$ ;  $\sigma = 0.982 \text{ mho/m}$ ;  $\epsilon_r = 56.8$ ;  $\rho = 1000 \text{ kg/m}^3$   
 Phantom section: Flat Section ; Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 184

DASY4 Configuration:  
 - Probe: ET3DV6 - SN1630; ConvF(6.17, 6.17, 6.17); Calibrated: 2010-05-25  
 - Sensor-Surface: 4mm (Mechanical Surface Detection)  
 - Electronics: DAE4 Sn869; Calibrated: 2010-09-21  
 - Phantom: 835/900 Phantom ; Type: SAM

**Body 4183/Area Scan (31x61x1):** Measurement grid: dx=15mm, dy=15mm

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (interpolated) = 0.215 mW/g


**Body 4183/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 7.74 V/m; Power Drift = 0.000 dB

Peak SAR (extrapolated) = 0.573 W/kg

**SAR(1 g) = 0.173 mW/g; SAR(10 g) = 0.095 mW/g**

Maximum value of SAR (measured) = 0.202 mW/g



0 dB = 0.202mW/g

Test Laboratory: HCT CO., LTD  
EUT Type: Cellular/PCS GSM/GPRS/EDGE/WCDMA/HSPA Phone with BT & WLAN  
GPRS Class12 and GPRS mode class B(GPRS and GSM, but not simultaneously)  
Liquid Temperature: 21.1 °C  
Ambient Temperature: 21.3 °C  
Test Date: Mar.15, 2011

**DUT: LG-P970h; Type: bar; Serial: #1**


Communication System: WCDMA1900; Frequency: 1880 MHz; Duty Cycle: 1:1  
Medium parameters used:  $f = 1880 \text{ MHz}$ ;  $\sigma = 1.54 \text{ mho/m}$ ;  $\epsilon_r = 52.1$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Flat Section ; Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 184

DASY4 Configuration:

- Probe: ET3DV6 - SN1630; ConvF(4.55, 4.55, 4.55); Calibrated: 2010-05-25
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn869; Calibrated: 2010-09-21
- Phantom: SAM 1800/1900 MHz; Type: SAM

**Body 9400/Area Scan (51x101x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$   
Maximum value of SAR (interpolated) = 1.00 mW/g

**Body 9400/Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$   
Reference Value = 15.3 V/m; Power Drift = 0.058 dB  
Peak SAR (extrapolated) = 1.08 W/kg  
**SAR(1 g) = 0.714 mW/g; SAR(10 g) = 0.431 mW/g**  
Maximum value of SAR (measured) = 0.776 mW/g



0 dB = 0.776mW/g

Test Laboratory: HCT CO., LTD  
EUT Type: Cellular/PCS GSM/GPRS/EDGE/WCDMA/HSPA Phone with BT & WLAN  
GPRS Class12 and GPRS mode class B(GPRS and GSM, but not simultaneously)  
Liquid Temperature: 21.1 °C  
Ambient Temperature: 21.3 °C  
Test Date: Mar.15, 2011

**DUT: LG-P970h; Type: bar; Serial: #1**

Communication System: WCDMA1900; Frequency: 1852.4 MHz; Duty Cycle: 1:1  
Medium parameters used (interpolated):  $f = 1852.4$  MHz;  $\sigma = 1.51$  mho/m;  $\epsilon_r = 52.2$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
Phantom section: Flat Section ; Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 184

DASY4 Configuration:

- Probe: ET3DV6 - SN1630; ConvF(4.55, 4.55, 4.55); Calibrated: 2010-05-25
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn869; Calibrated: 2010-09-21
- Phantom: SAM 1800/1900 MHz; Type: SAM

**Body 9262/Area Scan (51x101x1):** Measurement grid: dx=15mm, dy=15mm

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (interpolated) = 1.38 mW/g

**Body 9262/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm


Reference Value = 16.9 V/m; Power Drift = -0.031 dB

Peak SAR (extrapolated) = 1.80 W/kg

**SAR(1 g) = 1.23 mW/g; SAR(10 g) = 0.736 mW/g**

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 1.35 mW/g



0 dB = 1.35mW/g

Test Laboratory: HCT CO., LTD  
EUT Type: Cellular/PCS GSM/GPRS/EDGE/WCDMA/HSPA Phone with BT & WLAN  
GPRS Class12 and GPRS mode class B(GPRS and GSM, but not simultaneously)  
Liquid Temperature: 21.1 °C  
Ambient Temperature: 21.3 °C  
Test Date: Mar.15, 2011

**DUT: LG-P970h; Type: bar; Serial: #1**

Communication System: WCDMA1900; Frequency: 1880 MHz; Duty Cycle: 1:1  
Medium parameters used:  $f = 1880 \text{ MHz}$ ;  $\sigma = 1.54 \text{ mho/m}$ ;  $\epsilon_r = 52.1$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Flat Section ; Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 184


DASY4 Configuration:

- Probe: ET3DV6 - SN1630; ConvF(4.55, 4.55, 4.55); Calibrated: 2010-05-25
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn869; Calibrated: 2010-09-21
- Phantom: SAM 1800/1900 MHz; Type: SAM

**Body 9400/Area Scan (51x101x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$   
Maximum value of SAR (interpolated) = 1.24 mW/g

**Body 9400/Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$   
Reference Value = 15.0 V/m; Power Drift = 0.040 dB  
Peak SAR (extrapolated) = 1.66 W/kg  
**SAR(1 g) = 1.12 mW/g; SAR(10 g) = 0.666 mW/g**  
Maximum value of SAR (measured) = 1.22 mW/g

**Body 9400/Zoom Scan (5x5x7)/Cube 1:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$   
Reference Value = 15.0 V/m; Power Drift = 0.040 dB  
Peak SAR (extrapolated) = 1.68 W/kg  
SAR(1 g) = 0.980 mW/g; SAR(10 g) = 0.516 mW/g  
Maximum value of SAR (measured) = 1.21 mW/g



Test Laboratory: HCT CO., LTD  
 EUT Type: Cellular/PCS GSM/GPRS/EDGE/WCDMA/HSPA Phone with BT & WLAN  
 GPRS Class12 and GPRS mode class B(GPRS and GSM, but not simultaneously)  
 Liquid Temperature: 21.1 °C  
 Ambient Temperature: 21.3 °C  
 Test Date: Mar.15, 2011

**DUT: LG-P970h; Type: bar; Serial: #1**

Communication System: WCDMA1900; Frequency: 1907.6 MHz; Duty Cycle: 1:1  
 Medium parameters used (interpolated):  $f = 1907.6 \text{ MHz}$ ;  $\sigma = 1.57 \text{ mho/m}$ ;  $\epsilon_r = 52.1$ ;  $\rho = 1000 \text{ kg/m}^3$   
 Phantom section: Flat Section ; Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 184

DASY4 Configuration:

- Probe: ET3DV6 - SN1630; ConvF(4.55, 4.55, 4.55); Calibrated: 2010-05-25
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn869; Calibrated: 2010-09-21
- Phantom: SAM 1800/1900 MHz; Type: SAM

**Body 9538/Area Scan (51x101x1):** Measurement grid: dx=15mm, dy=15mm

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (interpolated) = 0.952 mW/g

**Body 9538/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 12.5 V/m; Power Drift = -0.012 dB

Peak SAR (extrapolated) = 1.28 W/kg

**SAR(1 g) = 0.852 mW/g; SAR(10 g) = 0.507 mW/g**

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.930 mW/g


**Body 9538/Zoom Scan (5x5x7)/Cube 1:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 12.5 V/m; Power Drift = -0.012 dB

Peak SAR (extrapolated) = 1.32 W/kg

**SAR(1 g) = 0.789 mW/g; SAR(10 g) = 0.435 mW/g**

Maximum value of SAR (measured) = 0.938 mW/g



0 dB = 0.938mW/g

Test Laboratory: HCT CO., LTD  
EUT Type: Cellular/PCS GSM/GPRS/EDGE/WCDMA/HSPA Phone with BT & WLAN  
GPRS Class12 and GPRS mode class B(GPRS and GSM, but not simultaneously)  
Liquid Temperature: 21.1 °C  
Ambient Temperature: 21.3 °C  
Test Date: Mar.15, 2011  
Option Edge A

**DUT: LG-P970h(side); Type: bar; Serial: #1**


Communication System: WCDMA1900; Frequency: 1880 MHz; Duty Cycle: 1:1  
Medium parameters used:  $f = 1880 \text{ MHz}$ ;  $\sigma = 1.54 \text{ mho/m}$ ;  $\epsilon_r = 52.1$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Flat Section ; Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 184

DASY4 Configuration:

- Probe: ET3DV6 - SN1630; ConvF(4.55, 4.55, 4.55); Calibrated: 2010-05-25
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn869; Calibrated: 2010-09-21
- Phantom: SAM 1800/1900 MHz; Type: SAM

**Body 9400/Area Scan (31x101x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$   
Maximum value of SAR (interpolated) = 0.515 mW/g

**Body 9400/Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$   
Reference Value = 13.6 V/m; Power Drift = -0.245 dB  
Peak SAR (extrapolated) = 0.715 W/kg  
**SAR(1 g) = 0.456 mW/g; SAR(10 g) = 0.261 mW/g**  
Maximum value of SAR (measured) = 0.500 mW/g



Test Laboratory: HCT CO., LTD  
 EUT Type: Cellular/PCS GSM/GPRS/EDGE/WCDMA/HSPA Phone with BT & WLAN  
 GPRS Class12 and GPRS mode class B(GPRS and GSM, but not simultaneously)  
 Liquid Temperature: 21.1 °C  
 Ambient Temperature: 21.3 °C  
 Test Date: Mar.15, 2011  
 Option: Edge B

**DUT: LG-P970h(side); Type: bar; Serial: #1**


Communication System: WCDMA1900; Frequency: 1880 MHz; Duty Cycle: 1:1  
 Medium parameters used:  $f = 1880 \text{ MHz}$ ;  $\sigma = 1.54 \text{ mho/m}$ ;  $\epsilon_r = 52.1$ ;  $\rho = 1000 \text{ kg/m}^3$   
 Phantom section: Flat Section ; Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 184

DASY4 Configuration:

- Probe: ET3DV6 - SN1630; ConvF(4.55, 4.55, 4.55); Calibrated: 2010-05-25
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn869; Calibrated: 2010-09-21
- Phantom: SAM 1800/1900 MHz; Type: SAM

**Body 9400/Area Scan (31x101x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$   
 Maximum value of SAR (interpolated) = 0.353 mW/g

**Body 9400/Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$   
 Reference Value = 16.1 V/m; Power Drift = 0.065 dB  
 Peak SAR (extrapolated) = 0.460 W/kg  
**SAR(1 g) = 0.312 mW/g; SAR(10 g) = 0.182 mW/g**  
 Maximum value of SAR (measured) = 0.344 mW/g



0 dB = 0.344mW/g

Test Laboratory: HCT CO., LTD  
EUT Type: Cellular/PCS GSM/GPRS/EDGE/WCDMA/HSPA Phone with BT & WLAN  
GPRS Class12 and GPRS mode class B(GPRS and GSM, but not simultaneously)  
Liquid Temperature: 21.1 °C  
Ambient Temperature: 21.3 °C  
Test Date: Mar.15, 2011  
Option Edge C

**DUT: LG-P970h; Type: Top; Serial: #1**

Communication System: WCDMA1900; Frequency: 1852.4 MHz; Duty Cycle: 1:1  
Medium parameters used (interpolated):  $f = 1852.4$  MHz;  $\sigma = 1.51$  mho/m;  $\epsilon_r = 52.2$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
Phantom section: Flat Section ; Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 184

DASY4 Configuration:

- Probe: ET3DV6 - SN1630; ConvF(4.55, 4.55, 4.55); Calibrated: 2010-05-25
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn869; Calibrated: 2010-09-21
- Phantom: SAM 1800/1900 MHz; Type: SAM

**Body 9262/Area Scan (31x61x1):** Measurement grid: dx=15mm, dy=15mm

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (interpolated) = 0.831 mW/g

**Body 9262/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm


Reference Value = 21.8 V/m; Power Drift = 0.019 dB

Peak SAR (extrapolated) = 1.11 W/kg

**SAR(1 g) = 0.717 mW/g; SAR(10 g) = 0.403 mW/g**

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.821 mW/g



0 dB = 0.821mW/g

Test Laboratory: HCT CO., LTD  
EUT Type: Cellular/PCS GSM/GPRS/EDGE/WCDMA/HSPA Phone with BT & WLAN  
GPRS Class12 and GPRS mode class B(GPRS and GSM, but not simultaneously)  
Liquid Temperature: 21.1 °C  
Ambient Temperature: 21.3 °C  
Test Date: Mar.15, 2011  
Option: Edge C

**DUT: LG-P970h; Type: Top; Serial: #1**


Communication System: WCDMA1900; Frequency: 1880 MHz; Duty Cycle: 1:1  
Medium parameters used:  $f = 1880$  MHz;  $\sigma = 1.54$  mho/m;  $\epsilon_r = 52.1$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
Phantom section: Flat Section ; Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 184

DASY4 Configuration:

- Probe: ET3DV6 - SN1630; ConvF(4.55, 4.55, 4.55); Calibrated: 2010-05-25
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn869; Calibrated: 2010-09-21
- Phantom: SAM 1800/1900 MHz; Type: SAM

**Body 9400/Area Scan (31x61x1):** Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (interpolated) = 1.02 mW/g

**Body 9400/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm  
Reference Value = 22.3 V/m; Power Drift = -0.069 dB  
Peak SAR (extrapolated) = 1.34 W/kg  
**SAR(1 g) = 0.866 mW/g; SAR(10 g) = 0.476 mW/g**  
Maximum value of SAR (measured) = 0.998 mW/g



0 dB = 0.998mW/g

Test Laboratory: HCT CO., LTD  
EUT Type: Cellular/PCS GSM/GPRS/EDGE/WCDMA/HSPA Phone with BT & WLAN  
GPRS Class12 and GPRS mode class B(GPRS and GSM, but not simultaneously)  
Liquid Temperature: 21.1 °C  
Ambient Temperature: 21.3 °C  
Test Date: Mar.15, 2011  
Option Edge C

**DUT: LG-P970h; Type: Top; Serial: #1**

Communication System: WCDMA1900; Frequency: 1907.6 MHz; Duty Cycle: 1:1  
Medium parameters used (interpolated):  $f = 1907.6 \text{ MHz}$ ;  $\sigma = 1.57 \text{ mho/m}$ ;  $\epsilon_r = 52.1$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Flat Section ; Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 184

DASY4 Configuration:

- Probe: ET3DV6 - SN1630; ConvF(4.55, 4.55, 4.55); Calibrated: 2010-05-25
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn869; Calibrated: 2010-09-21
- Phantom: SAM 1800/1900 MHz; Type: SAM

**Body 9538/Area Scan (31x61x1):** Measurement grid: dx=15mm, dy=15mm

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (interpolated) = 1.03 mW/g

**Body 9538/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm


Reference Value = 21.0 V/m; Power Drift = -0.034 dB

Peak SAR (extrapolated) = 1.41 W/kg

**SAR(1 g) = 0.890 mW/g; SAR(10 g) = 0.478 mW/g**

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 1.02 mW/g



0 dB = 1.02mW/g

Test Laboratory: HCT CO., LTD  
EUT Type: Cellular/PCS GSM/GPRS/EDGE/WCDMA/HSPA Phone with BT & WLAN  
GPRS Class12 and GPRS mode class B(GPRS and GSM, but not simultaneously)  
Liquid Temperature: 21.1 °C  
Ambient Temperature: 21.3 °C  
Test Date: Feb.23, 2011

**DUT: LG-P970h; Type: bar; Serial: #1**

Communication System: 2450MHz FCC; Frequency: 2462 MHz;Duty Cycle: 1:1  
Medium parameters used (interpolated):  $f = 2462 \text{ MHz}$ ;  $\sigma = 1.98 \text{ mho/m}$ ;  $\epsilon_r = 51.5$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Flat Section ; Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 184

DASY4 Configuration:

- Probe: ES3DV3 - SN3161; ConvF(4.17, 4.17, 4.17); Calibrated: 2010-03-22
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn869; Calibrated: 2010-09-21
- Phantom: SAM 1800/1900 MHz; Type: SAM

**Body 11/Area Scan (51x101x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (interpolated) = 0.202 mW/g

**Body 11/Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$


Reference Value = 7.62 V/m; Power Drift = 0.040 dB

Peak SAR (extrapolated) = 0.333 W/kg

**SAR(1 g) = 0.175 mW/g; SAR(10 g) = 0.080 mW/g**

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.193 mW/g



0 dB = 0.193mW/g

Test Laboratory: HCT CO., LTD  
EUT Type: Cellular/PCS GSM/GPRS/EDGE/WCDMA/HSPA Phone with BT & WLAN  
GPRS Class12 and GPRS mode class B(GPRS and GSM, but not simultaneously)  
Liquid Temperature: 21.1 °C  
Ambient Temperature: 21.3 °C  
Test Date: Feb.23, 2011

**DUT: LG-P970h; Type: bar; Serial: #1**

Communication System: 2450MHz FCC; Frequency: 2462 MHz; Duty Cycle: 1:1  
Medium parameters used (interpolated):  $f = 2462 \text{ MHz}$ ;  $\sigma = 1.98 \text{ mho/m}$ ;  $\epsilon_r = 51.5$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Flat Section ; Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 184

DASY4 Configuration:

- Probe: ES3DV3 - SN3161; ConvF(4.17, 4.17, 4.17); Calibrated: 2010-03-22
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn869; Calibrated: 2010-09-21
- Phantom: SAM 1800/1900 MHz; Type: SAM

**Body 11/Area Scan (51x101x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (interpolated) = 0.189 mW/g

**Body 11/Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$


Reference Value = 7.72 V/m; Power Drift = -0.018 dB

Peak SAR (extrapolated) = 0.194 W/kg

**SAR(1 g) = 0.141 mW/g; SAR(10 g) = 0.064 mW/g**

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.176 mW/g



0 dB = 0.176mW/g

Test Laboratory: HCT CO., LTD  
EUT Type: Cellular/PCS GSM/GPRS/EDGE/WCDMA/HSPA Phone with BT & WLAN  
GPRS Class12 and GPRS mode class B(GPRS and GSM, but not simultaneously)  
Liquid Temperature: 21.1 °C  
Ambient Temperature: 21.3 °C  
Test Date: Feb.23, 2011  
Option: Edge B

**DUT: LG-P970h(side); Type: bar; Serial: #1**

Communication System: 2450MHz FCC; Frequency: 2462 MHz;Duty Cycle: 1:1  
Medium parameters used (interpolated):  $f = 2462$  MHz;  $\sigma = 1.98$  mho/m;  $\epsilon_r = 51.5$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
Phantom section: Flat Section ; Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 184

DASY4 Configuration:

- Probe: ES3DV3 - SN3161; ConvF(4.17, 4.17, 4.17); Calibrated: 2010-03-22
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn869; Calibrated: 2010-09-21
- Phantom: SAM 1800/1900 MHz; Type: SAM

**Body 11/Area Scan (31x101x1):** Measurement grid: dx=15mm, dy=15mm

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (interpolated) = 0.241 mW/g

**Body 11/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm


Reference Value = 9.69 V/m; Power Drift = 0.051 dB

Peak SAR (extrapolated) = 0.460 W/kg

**SAR(1 g) = 0.201 mW/g; SAR(10 g) = 0.095 mW/g**

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.220 mW/g



0 dB = 0.220mW/g

Test Laboratory: HCT CO., LTD  
EUT Type: Cellular/PCS GSM/GPRS/EDGE/WCDMA/HSPA Phone with BT & WLAN  
GPRS Class12 and GPRS mode class B(GPRS and GSM, but not simultaneously)  
Liquid Temperature: 21.1 °C  
Ambient Temperature: 21.3 °C  
Test Date: Feb.23, 2011  
Option: Edge D

**DUT: LG-P970h(Top); Type: bar; Serial: #1**

Communication System: 2450MHz FCC; Frequency: 2462 MHz;Duty Cycle: 1:1  
Medium parameters used (interpolated):  $f = 2462 \text{ MHz}$ ;  $\sigma = 1.98 \text{ mho/m}$ ;  $\epsilon_r = 51.5$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Flat Section ; Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 184

DASY4 Configuration:

- Probe: ES3DV3 - SN3161; ConvF(4.17, 4.17, 4.17); Calibrated: 2010-03-22
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn869; Calibrated: 2010-09-21
- Phantom: SAM 1800/1900 MHz; Type: SAM

**Body 11/Area Scan (61x31x1):** Measurement grid: dx=15mm, dy=15mm

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (interpolated) = 0.134 mW/g

**Body 11/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm


Reference Value = 6.95 V/m; Power Drift = 0.050 dB

Peak SAR (extrapolated) = 0.237 W/kg

**SAR(1 g) = 0.109 mW/g; SAR(10 g) = 0.047 mW/g**

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.131 mW/g



0 dB = 0.131mW/g

Test Laboratory: HCT CO., LTD  
 EUT Type: Cellular/PCS GSM/GPRS/EDGE/WCDMA/HSPA Phone with BT & WLAN  
 GPRS Class12 and GPRS mode class B(GPRS and GSM, but not simultaneously)  
 Liquid Temperature: 21.1 °C  
 Ambient Temperature: 21.3 °C  
 Test Date: Mar.14, 2011

**DUT: LG-P970h; Type: bar; Serial: #1**

Communication System: GSM 850; Frequency: 836.6 MHz; Duty Cycle: 1:8.3  
 Medium parameters used (interpolated):  $f = 836.6 \text{ MHz}$ ;  $\sigma = 0.877 \text{ mho/m}$ ;  $\epsilon_r = 42.9$ ;  $\rho = 1000 \text{ kg/m}^3$   
 Phantom section: Right Section ; Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 184

DASY4 Configuration:  
 - Probe: ET3DV6 - SN1630; ConvF(6.25, 6.25, 6.25); Calibrated: 2010-05-25  
 - Sensor-Surface: 4mm (Mechanical Surface Detection)  
 - Electronics: DAE4 Sn869; Calibrated: 2010-09-21  
 - Phantom: 835/900 Phantom ; Type: SAM

**Right touch 190/Area Scan (51x91x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (interpolated) = 0.540 mW/g


**Right touch 190/Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$

Reference Value = 10.6 V/m; Power Drift = -0.045 dB

Peak SAR (extrapolated) = 0.663 W/kg

**SAR(1 g) = 0.512 mW/g; SAR(10 g) = 0.376 mW/g**

Maximum value of SAR (measured) = 0.546 mW/g



Test Laboratory: HCT CO., LTD  
 EUT Type: Cellular/PCS GSM/GPRS/EDGE/WCDMA/HSPA Phone with BT & WLAN  
 GPRS Class12 and GPRS mode class B(GPRS and GSM, but not simultaneously)  
 Liquid Temperature: 21.1 °C  
 Ambient Temperature: 21.3 °C  
 Test Date: Mar.14, 2011

**DUT: LG-P970h; Type: bar; Serial: #1**

Communication System: GSM 850; Frequency: 848.8 MHz; Duty Cycle: 1:2.075  
 Medium parameters used (interpolated):  $f = 848.8 \text{ MHz}$ ;  $\sigma = 0.992 \text{ mho/m}$ ;  $\epsilon_r = 56.7$ ;  $\rho = 1000 \text{ kg/m}^3$   
 Phantom section: Flat Section ; Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 184

DASY4 Configuration:

- Probe: ET3DV6 - SN1630; ConvF(6.17, 6.17, 6.17); Calibrated: 2010-05-25
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn869; Calibrated: 2010-09-21
- Phantom: 835/900 Phantom ; Type: SAM

**Body 251/Area Scan (61x101x1):** Measurement grid: dx=15mm, dy=15mm

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (interpolated) = 1.18 mW/g

**Body 251/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 19.8 V/m; Power Drift = 0.025 dB

Peak SAR (extrapolated) = 1.39 W/kg

**SAR(1 g) = 1.11 mW/g; SAR(10 g) = 0.821 mW/g**

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 1.17 mW/g



Test Laboratory: HCT CO., LTD  
 EUT Type: Cellular/PCS GSM/GPRS/EDGE/WCDMA/HSPA Phone with BT & WLAN  
 GPRS Class12 and GPRS mode class B(GPRS and GSM, but not simultaneously)  
 Liquid Temperature: 21.1 °C  
 Ambient Temperature: 21.3 °C  
 Test Date: Mar.15, 2011

**DUT: LG-P970h; Type: bar; Serial: #1**


Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3  
 Medium parameters used:  $f = 1880 \text{ MHz}$ ;  $\sigma = 1.38 \text{ mho/m}$ ;  $\epsilon_r = 41.1$ ;  $\rho = 1000 \text{ kg/m}^3$   
 Phantom section: Left Section ; Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 184

DASY4 Configuration:

- Probe: ET3DV6 - SN1630; ConvF(5.12, 5.12, 5.12); Calibrated: 2010-05-25
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn869; Calibrated: 2010-09-21
- Phantom: SAM 1800/1900 MHz; Type: SAM

**Left touch 661/Area Scan (61x101x1):** Measurement grid: dx=15mm, dy=15mm  
 Maximum value of SAR (interpolated) = 0.746 mW/g

**Left touch 661/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm  
 Reference Value = 7.84 V/m; Power Drift = 0.029 dB  
 Peak SAR (extrapolated) = 1.06 W/kg  
**SAR(1 g) = 0.669 mW/g; SAR(10 g) = 0.386 mW/g**  
 Maximum value of SAR (measured) = 0.742 mW/g



Test Laboratory: HCT CO., LTD  
EUT Type: Cellular/PCS GSM/GPRS/EDGE/WCDMA/HSPA Phone with BT & WLAN  
GPRS Class12 and GPRS mode class B(GPRS and GSM, but not simultaneously)  
Liquid Temperature: 21.1 °C  
Ambient Temperature: 21.3 °C  
Test Date: Mar.15, 2011

**DUT: LG-P970h; Type: Top; Serial: #1**


Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:2.075  
Medium parameters used:  $f = 1880 \text{ MHz}$ ;  $\sigma = 1.54 \text{ mho/m}$ ;  $\epsilon_r = 52.1$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Flat Section ; Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 184

DASY4 Configuration:

- Probe: ET3DV6 - SN1630; ConvF(4.55, 4.55, 4.55); Calibrated: 2010-05-25
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn869; Calibrated: 2010-09-21
- Phantom: SAM 1800/1900 MHz; Type: SAM

**Body 661/Area Scan (31x61x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$   
Maximum value of SAR (interpolated) = 0.659 mW/g

**Body 661/Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$   
Reference Value = 17.3 V/m; Power Drift = 0.063 dB  
Peak SAR (extrapolated) = 0.923 W/kg  
**SAR(1 g) = 0.567 mW/g; SAR(10 g) = 0.299 mW/g**  
Maximum value of SAR (measured) = 0.664 mW/g



Test Laboratory: HCT CO., LTD  
EUT Type: Cellular/PCS GSM/GPRS/EDGE/WCDMA/HSPA Phone with BT & WLAN  
GPRS Class12 and GPRS mode class B(GPRS and GSM, but not simultaneously)  
Liquid Temperature: 21.1 °C  
Ambient Temperature: 21.3 °C  
Test Date: Mar.14, 2011

**DUT: LG-P970h; Type: bar; Serial: #1**

Communication System: WCDMA850; Frequency: 836.6 MHz; Duty Cycle: 1:1  
Medium parameters used (interpolated):  $f = 836.6 \text{ MHz}$ ;  $\sigma = 0.877 \text{ mho/m}$ ;  $\epsilon_r = 42.9$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Right Section ; Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 184

DASY4 Configuration:

- Probe: ET3DV6 - SN1630; ConvF(6.25, 6.25, 6.25); Calibrated: 2010-05-25
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn869; Calibrated: 2010-09-21
- Phantom: 835/900 Phantom ; Type: SAM

**Right touch 4183/Area Scan (61x101x1):** Measurement grid: dx=15mm, dy=15mm

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (interpolated) = 0.496 mW/g


**Right touch 4183/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 9.92 V/m; Power Drift = -0.064 dB

Peak SAR (extrapolated) = 0.620 W/kg

**SAR(1 g) = 0.477 mW/g; SAR(10 g) = 0.346 mW/g**

Maximum value of SAR (measured) = 0.501 mW/g



Test Laboratory: HCT CO., LTD  
EUT Type: Cellular/PCS GSM/GPRS/EDGE/WCDMA/HSPA Phone with BT & WLAN  
GPRS Class12 and GPRS mode class B(GPRS and GSM, but not simultaneously)  
Liquid Temperature: 21.1 °C  
Ambient Temperature: 21.3 °C  
Test Date: Mar.14, 2011

**DUT: LG-P970h; Type: bar; Serial: #1**

Communication System: WCDMA850; Frequency: 846.4 MHz; Duty Cycle: 1:1  
Medium parameters used (interpolated):  $f = 846.4$  MHz;  $\sigma = 0.99$  mho/m;  $\epsilon_r = 56.7$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
Phantom section: Flat Section ; Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 184


DASY4 Configuration:  
- Probe: ET3DV6 - SN1630; ConvF(6.17, 6.17, 6.17); Calibrated: 2010-05-25  
- Sensor-Surface: 4mm (Mechanical Surface Detection)  
- Electronics: DAE4 Sn869; Calibrated: 2010-09-21  
- Phantom: 835/900 Phantom ; Type: SAM

**Body 4233/Area Scan (51x101x1):** Measurement grid: dx=15mm, dy=15mm

[Info: Interpolated medium parameters used for SAR evaluation.](#)  
Maximum value of SAR (interpolated) = 1.01 mW/g

**Body 4233/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm  
Reference Value = 15.2 V/m; Power Drift = -0.051 dB  
Peak SAR (extrapolated) = 1.18 W/kg  
**SAR(1 g) = 0.946 mW/g; SAR(10 g) = 0.700 mW/g**

[Info: Interpolated medium parameters used for SAR evaluation.](#)  
Maximum value of SAR (measured) = 0.999 mW/g



Test Laboratory: HCT CO., LTD  
EUT Type: Cellular/PCS GSM/GPRS/EDGE/WCDMA/HSPA Phone with BT & WLAN  
GPRS Class12 and GPRS mode class B(GPRS and GSM, but not simultaneously)  
Liquid Temperature: 21.1 °C  
Ambient Temperature: 21.3 °C  
Test Date: Mar.15, 2011

**DUT: LG-P970h; Type: bar; Serial: #1**

Communication System: WCDMA1900; Frequency: 1852.4 MHz; Duty Cycle: 1:1  
Medium parameters used (interpolated):  $f = 1852.4 \text{ MHz}$ ;  $\sigma = 1.36 \text{ mho/m}$ ;  $\epsilon_r = 41.3$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Right Section ; Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 184

DASY4 Configuration:

- Probe: ET3DV6 - SN1630; ConvF(5.12, 5.12, 5.12); Calibrated: 2010-05-25
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn869; Calibrated: 2010-09-21
- Phantom: SAM 1800/1900 MHz; Type: SAM

**Right touch 9262/Area Scan (51x101x1):** Measurement grid: dx=15mm, dy=15mm

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (interpolated) = 1.08 mW/g

**Right touch 9262/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 19.8 V/m; Power Drift = -0.040 dB

Peak SAR (extrapolated) = 1.42 W/kg

**SAR(1 g) = 0.991 mW/g; SAR(10 g) = 0.614 mW/g**

Maximum value of SAR (measured) = 1.07 mW/g


**Right touch 9262/Zoom Scan (5x5x7)/Cube 1:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 19.8 V/m; Power Drift = -0.040 dB

Peak SAR (extrapolated) = 0.963 W/kg

**SAR(1 g) = 0.663 mW/g; SAR(10 g) = 0.422 mW/g**

Maximum value of SAR (measured) = 0.725 mW/g



Test Laboratory: HCT CO., LTD  
EUT Type: Cellular/PCS GSM/GPRS/EDGE/WCDMA/HSPA Phone with BT & WLAN  
GPRS Class12 and GPRS mode class B(GPRS and GSM, but not simultaneously)  
Liquid Temperature: 21.1 °C  
Ambient Temperature: 21.3 °C  
Test Date: Mar.15, 2011

**DUT: LG-P970h; Type: bar; Serial: #1**

Communication System: WCDMA1900; Frequency: 1852.4 MHz; Duty Cycle: 1:1  
Medium parameters used (interpolated):  $f = 1852.4$  MHz;  $\sigma = 1.51$  mho/m;  $\epsilon_r = 52.2$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
Phantom section: Flat Section ; Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 184

DASY4 Configuration:

- Probe: ET3DV6 - SN1630; ConvF(4.55, 4.55, 4.55); Calibrated: 2010-05-25
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn869; Calibrated: 2010-09-21
- Phantom: SAM 1800/1900 MHz; Type: SAM

**Body 9262/Area Scan (51x101x1):** Measurement grid: dx=15mm, dy=15mm

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (interpolated) = 1.38 mW/g

**Body 9262/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm


Reference Value = 16.9 V/m; Power Drift = -0.031 dB

Peak SAR (extrapolated) = 1.80 W/kg

**SAR(1 g) = 1.23 mW/g; SAR(10 g) = 0.736 mW/g**

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 1.35 mW/g



Test Laboratory: HCT CO., LTD  
EUT Type: Cellular/PCS GSM/GPRS/EDGE/WCDMA/HSPA Phone with BT & WLAN  
GPRS Class12 and GPRS mode class B(GPRS and GSM, but not simultaneously)  
Liquid Temperature: 21.1 °C  
Ambient Temperature: 21.3 °C  
Test Date: Feb.23, 2011

**DUT: LG-P970h; Type: bar; Serial: #1**

Communication System: 2450MHz FCC; Frequency: 2462 MHz; Duty Cycle: 1:1  
Medium parameters used (interpolated):  $f = 2462 \text{ MHz}$ ;  $\sigma = 1.91 \text{ mho/m}$ ;  $\epsilon_r = 38.2$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Left Section ; Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 184

DASY4 Configuration:

- Probe: ES3DV3 - SN3161; ConvF(4.26, 4.26, 4.26); Calibrated: 2010-03-22
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn869; Calibrated: 2010-09-21
- Phantom: SAM 1800/1900 MHz; Type: SAM

**Left touch 6/Area Scan (61x101x1):** Measurement grid: dx=15mm, dy=15mm

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (interpolated) = 0.520 mW/g

**Left touch 6/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm


Reference Value = 8.10 V/m; Power Drift = -0.108 dB

Peak SAR (extrapolated) = 1.21 W/kg

**SAR(1 g) = 0.487 mW/g; SAR(10 g) = 0.216 mW/g**

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.529 mW/g



Test Laboratory: HCT CO., LTD  
EUT Type: Cellular/PCS GSM/GPRS/EDGE/WCDMA/HSPA Phone with BT & WLAN  
GPRS Class12 and GPRS mode class B(GPRS and GSM, but not simultaneously)  
Liquid Temperature: 21.1 °C  
Ambient Temperature: 21.3 °C  
Test Date: Feb.23, 2011

**DUT: LG-P970h(side); Type: bar; Serial: #1**

Communication System: 2450MHz FCC; Frequency: 2462 MHz;Duty Cycle: 1:1  
Medium parameters used (interpolated):  $f = 2462$  MHz;  $\sigma = 1.98$  mho/m;  $\epsilon_r = 51.5$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
Phantom section: Flat Section ; Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 184

DASY4 Configuration:

- Probe: ES3DV3 - SN3161; ConvF(4.17, 4.17, 4.17); Calibrated: 2010-03-22
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn869; Calibrated: 2010-09-21
- Phantom: SAM 1800/1900 MHz; Type: SAM

**Body 11/Area Scan (31x101x1):** Measurement grid: dx=15mm, dy=15mm

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (interpolated) = 0.241 mW/g

**Body 11/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm


Reference Value = 9.69 V/m; Power Drift = 0.051 dB

Peak SAR (extrapolated) = 0.460 W/kg

**SAR(1 g) = 0.201 mW/g; SAR(10 g) = 0.095 mW/g**

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.220 mW/g



## Attachment 2. – Dipole Validation Plots

## ■ Validation Data (835 MHz Head)

Test Laboratory: HCT CO., LTD  
Input Power 100 mW (20 dBm)  
Liquid Temp: 21.3 °C  
Test Date: Mar.14, 2011

DUT: Dipole 835 MHz; Type: D835V2; Serial: D835V2 – SN:441


Communication System: CW; Frequency: 835 MHz; Duty Cycle: 1:1  
Medium parameters used:  $f = 835 \text{ MHz}$ ;  $\sigma = 0.876 \text{ mho/m}$ ;  $\epsilon_r = 43$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Flat Section ; Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 184

DASY4 Configuration:

- Probe: ET3DV6 – SN1630; ConvF(6.25, 6.25, 6.25); Calibrated: 2010-05-25
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn869; Calibrated: 2010-09-21
- Phantom: SAM 1800/1900 MHz; Type: SAM

**Validation 835MHz/Area Scan (61x61x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$   
Maximum value of SAR (interpolated) = 1.06 mW/g

**Validation 835MHz/Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$   
Reference Value = 36.1 V/m; Power Drift = -0.018 dB  
Peak SAR (extrapolated) = 1.46 W/kg  
**SAR(1 g) = 0.974 mW/g; SAR(10 g) = 0.624 mW/g**  
Maximum value of SAR (measured) = 1.06 mW/g



0 dB = 1.06mW/g

## ■ Validation Data (1900 MHz Head)

Test Laboratory: HCT CO., LTD  
Input Power 100 mW (20 dBm)  
Liquid Temp: 21.3 °C  
Test Date: Mar.15, 2011

**DUT: Dipole 1900 MHz; Type: D1900V2; Serial: D1900V2 – SN:5d032**


Communication System: CW; Frequency: 1900 MHz; Duty Cycle: 1:1  
Medium parameters used:  $f = 1900 \text{ MHz}$ ;  $\sigma = 1.4 \text{ mho/m}$ ;  $\epsilon_r = 41$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Flat Section ; Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 184

DASY4 Configuration:

- Probe: ET3DV6 – SN1630; ConvF(5.12, 5.12, 5.12); Calibrated: 2010-05-25
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn869; Calibrated: 2010-09-21
- Phantom: SAM 835/900 MHz; Type: SAM

**Dipole 1900MHz Validation/Area Scan (61x61x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$   
Maximum value of SAR (interpolated) = 4.54 mW/g

**Dipole 1900MHz Validation/Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$   
Reference Value = 59.6 V/m; Power Drift = -0.027 dB  
Peak SAR (extrapolated) = 6.81 W/kg  
**SAR(1 g) = 4.04 mW/g; SAR(10 g) = 2.25 mW/g**  
Maximum value of SAR (measured) = 4.47 mW/g



0 dB = 4.47mW/g

## ■ Validation Data (2450 MHz Head)

Test Laboratory: HCT CO., LTD  
Input Power 100 mW (20 dBm)  
Liquid Temp: 21.1 °C  
Test Date: Feb.23, 2011

DUT: Dipole 2450 MHz; Type: D2450V2; Serial: D2450V2 – SN:743


Communication System: CW; Frequency: 2450 MHz; Duty Cycle: 1:1  
Medium parameters used:  $f = 2450 \text{ MHz}$ ;  $\sigma = 1.87 \text{ mho/m}$ ;  $\epsilon_r = 38.2$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Flat Section ; Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 184

DASY4 Configuration:

- Probe: ES3DV3 – SN3161; ConvF(4.26, 4.26, 4.26); Calibrated: 2010-03-22
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn869; Calibrated: 2010-09-21
- Phantom: SAM 1800/1900 MHz; Type: SAM

**Validation 2450MHz/Area Scan (61x61x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$   
Maximum value of SAR (interpolated) = 6.63 mW/g

**Validation 2450MHz/Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$   
Reference Value = 57.2 V/m; Power Drift = 0.012 dB  
Peak SAR (extrapolated) = 13.8 W/kg  
**SAR(1 g) = 5.57 mW/g; SAR(10 g) = 2.47 mW/g**  
Maximum value of SAR (measured) = 6.09 mW/g



0 dB = 6.09mW/g

## ■ Validation Data (835 MHz Body)

Test Laboratory: HCT CO., LTD  
Input Power 100 mW (20 dBm)  
Liquid Temp: 21.3 °C  
Test Date: Mar.14, 2011

**DUT: Dipole 835 MHz; Type: D835V2; Serial: D835V2 – SN:441**


Communication System: CW; Frequency: 835 MHz; Duty Cycle: 1:1  
Medium parameters used:  $f = 835$  MHz;  $\sigma = 0.98$  mho/m;  $\epsilon_r = 56.8$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
Phantom section: Flat Section ; Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 184

DASY4 Configuration:

- Probe: ET3DV6 – SN1630; ConvF(6.17, 6.17, 6.17); Calibrated: 2010-05-25
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn869; Calibrated: 2010-09-21
- Phantom: SAM 1800/1900 MHz; Type: SAM

**Validation 835MHz/Area Scan (61x61x1):** Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (interpolated) = 1.09 mW/g

**Validation 835MHz/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm  
Reference Value = 34.4 V/m; Power Drift = -0.025 dB  
Peak SAR (extrapolated) = 1.48 W/kg  
**SAR(1 g) = 1.000 mW/g; SAR(10 g) = 0.644 mW/g**  
Maximum value of SAR (measured) = 1.09 mW/g



0 dB = 1.09mW/g

## ■ Validation Data (1900 MHz Body)

Test Laboratory: HCT CO., LTD  
Input Power 100 mW (20 dBm)  
Liquid Temp: 21.3 °C  
Test Date: Mar.15, 2011

DUT: Dipole 1900 MHz; Type: D1900V2; Serial: D1900V2 – SN:5d032


Communication System: CW; Frequency: 1900 MHz; Duty Cycle: 1:1  
Medium parameters used:  $f = 1900 \text{ MHz}$ ;  $\sigma = 1.56 \text{ mho/m}$ ;  $\epsilon_r = 52$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Flat Section ; Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 184

DASY4 Configuration:

- Probe: ET3DV6 – SN1630; ConvF(4.55, 4.55, 4.55); Calibrated: 2010-05-25
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn869; Calibrated: 2010-09-21
- Phantom: SAM 1800/1900 MHz; Type: SAM

Dipole 1900MHz Validation/Area Scan (61x61x1): Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$   
Maximum value of SAR (interpolated) = 4.95 mW/g

Dipole 1900MHz Validation/Zoom Scan (5x5x7)/Cube 0: Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$   
Reference Value = 58.9 V/m; Power Drift = -0.014 dB  
Peak SAR (extrapolated) = 6.78 W/kg  
**SAR(1 g) = 4.24 mW/g; SAR(10 g) = 2.23 mW/g**  
Maximum value of SAR (measured) = 4.82 mW/g



0 dB = 4.82mW/g

## ■ Validation Data (2450 MHz Body)

Test Laboratory: HCT CO., LTD  
Input Power 100 mW (20 dBm)  
Liquid Temp: 21.1 °C  
Test Date: Feb.23, 2011

DUT: Dipole 2450 MHz; Type: D2450V2; Serial: D2450V2 – SN:743


Communication System: CW; Frequency: 2450 MHz; Duty Cycle: 1:1  
Medium parameters used:  $f = 2450$  MHz;  $\sigma = 1.96$  mho/m;  $\epsilon_r = 51.6$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
Phantom section: Flat Section ; Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 184

DASY4 Configuration:

- Probe: ET3DV6 – SN1630; ConvF(4.15, 4.15, 4.15); Calibrated: 2010-05-25
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn869; Calibrated: 2010-09-21
- Phantom: SAM 1800/1900 MHz; Type: SAM

**Validation 2450MHz/Area Scan (61x61x1):** Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (interpolated) = 6.45 mW/g

**Validation 2450MHz/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm  
Reference Value = 55.8 V/m; Power Drift = 0.004 dB  
Peak SAR (extrapolated) = 13.0 W/kg  
**SAR(1 g) = 5.39 mW/g; SAR(10 g) = 2.4 mW/g**  
Maximum value of SAR (measured) = 5.93 mW/g



0 dB = 5.93mW/g

**■ Dielectric Parameter (835 MHz Head)**

Title LG-P970h  
SubTitle GSM850(Head)  
Test Date Mar.14, 2011

| Frequency      | e'      | e''     |
|----------------|---------|---------|
| 800000000.0000 | 43.2270 | 18.6732 |
| 805000000.0000 | 43.2300 | 18.6967 |
| 810000000.0000 | 43.2276 | 18.7374 |
| 815000000.0000 | 43.1607 | 18.7368 |
| 820000000.0000 | 43.1217 | 18.8299 |
| 825000000.0000 | 43.0801 | 18.8538 |
| 830000000.0000 | 43.0575 | 18.8298 |
| 835000000.0000 | 42.9634 | 18.8477 |
| 840000000.0000 | 42.9202 | 18.8195 |
| 845000000.0000 | 42.8614 | 18.8066 |
| 850000000.0000 | 42.8272 | 18.8387 |
| 855000000.0000 | 42.7324 | 18.7850 |
| 860000000.0000 | 42.6445 | 18.7508 |
| 865000000.0000 | 42.5821 | 18.7300 |
| 870000000.0000 | 42.4983 | 18.6854 |
| 875000000.0000 | 42.4324 | 18.6463 |
| 880000000.0000 | 42.3775 | 18.6246 |
| 885000000.0000 | 42.3271 | 18.5818 |
| 890000000.0000 | 42.2324 | 18.5880 |
| 895000000.0000 | 42.1946 | 18.5322 |
| 900000000.0000 | 42.1184 | 18.5433 |

**■ Dielectric Parameter (835 MHz Body)**

Title LG-P970h  
SubTitle GSM850(Body)  
Test Date Mar.14, 2011

| Frequency      | e'      | e''     |
|----------------|---------|---------|
| 800000000.0000 | 57.0714 | 21.2888 |
| 805000000.0000 | 57.0101 | 21.2567 |
| 810000000.0000 | 56.9947 | 21.2556 |
| 815000000.0000 | 56.9280 | 21.1998 |
| 820000000.0000 | 56.9450 | 21.1859 |
| 825000000.0000 | 56.9023 | 21.1362 |
| 830000000.0000 | 56.8552 | 21.1259 |
| 835000000.0000 | 56.8351 | 21.0962 |
| 840000000.0000 | 56.7546 | 21.0779 |
| 845000000.0000 | 56.7324 | 21.0321 |
| 850000000.0000 | 56.7082 | 20.9967 |
| 855000000.0000 | 56.6143 | 20.9788 |
| 860000000.0000 | 56.5556 | 20.8791 |
| 865000000.0000 | 56.4624 | 20.9114 |
| 870000000.0000 | 56.3734 | 20.8708 |
| 875000000.0000 | 56.3094 | 20.7946 |
| 880000000.0000 | 56.2464 | 20.7716 |
| 885000000.0000 | 56.1980 | 20.7713 |
| 890000000.0000 | 56.1281 | 20.7840 |
| 895000000.0000 | 56.0445 | 20.7485 |
| 900000000.0000 | 56.0276 | 20.7351 |

**■ Dielectric Parameter (1900 MHz Head)**

Title LG-P970h  
SubTitle WCDMA1900(Head)  
Test Date Mar.15, 2011

| Frequency       | e'      | e''     |
|-----------------|---------|---------|
| 1800000000.0000 | 41.4223 | 12.9700 |
| 1810000000.0000 | 41.4052 | 12.9995 |
| 1820000000.0000 | 41.3807 | 13.0583 |
| 1830000000.0000 | 41.3606 | 13.1170 |
| 1840000000.0000 | 41.3226 | 13.1505 |
| 1850000000.0000 | 41.3048 | 13.1891 |
| 1860000000.0000 | 41.2024 | 13.1947 |
| 1870000000.0000 | 41.1752 | 13.2152 |
| 1880000000.0000 | 41.1055 | 13.2064 |
| 1890000000.0000 | 41.0109 | 13.2176 |
| 1900000000.0000 | 40.9713 | 13.2230 |
| 1910000000.0000 | 40.9186 | 13.2344 |
| 1920000000.0000 | 40.8947 | 13.2598 |
| 1930000000.0000 | 40.8675 | 13.2965 |
| 1940000000.0000 | 40.8460 | 13.3263 |
| 1950000000.0000 | 40.8513 | 13.3585 |
| 1960000000.0000 | 40.8704 | 13.3961 |
| 1970000000.0000 | 40.8566 | 13.4232 |
| 1980000000.0000 | 40.8634 | 13.4567 |
| 1990000000.0000 | 40.8034 | 13.5040 |
| 2000000000.0000 | 40.7393 | 13.5306 |

**■ Dielectric Parameter (1900 MHz Body)**

Title LG-P970h  
SubTitle WCDMA1900(Body)  
Test Date Mar.15, 2011

| Frequency       | e'      | e''     |
|-----------------|---------|---------|
| 1850000000.0000 | 52.2100 | 14.6403 |
| 1855000000.0000 | 52.2179 | 14.6518 |
| 1860000000.0000 | 52.1621 | 14.6724 |
| 1865000000.0000 | 52.1754 | 14.6684 |
| 1870000000.0000 | 52.1662 | 14.7203 |
| 1875000000.0000 | 52.1372 | 14.7248 |
| 1880000000.0000 | 52.1397 | 14.7519 |
| 1885000000.0000 | 52.1295 | 14.7724 |
| 1890000000.0000 | 52.0712 | 14.7745 |
| 1895000000.0000 | 52.0817 | 14.7766 |
| 1900000000.0000 | 52.0488 | 14.7781 |
| 1905000000.0000 | 52.0610 | 14.8253 |
| 1910000000.0000 | 52.0440 | 14.8235 |
| 1915000000.0000 | 52.0312 | 14.8178 |
| 1920000000.0000 | 52.0264 | 14.8445 |
| 1925000000.0000 | 51.9894 | 14.8431 |
| 1930000000.0000 | 51.9845 | 14.8843 |
| 1935000000.0000 | 51.9713 | 14.8686 |
| 1940000000.0000 | 51.9412 | 14.9007 |
| 1945000000.0000 | 51.9536 | 14.9082 |
| 1950000000.0000 | 51.9233 | 14.9624 |

## ■ Dielectric Parameter (2 450 MHz Head)

|           |                |
|-----------|----------------|
| Title     | LG-P970h       |
| SubTitle  | 2450MHz (Head) |
| Test Date | Feb.23, 2011   |

| Frequency       | e'      | e''     |
|-----------------|---------|---------|
| 2400000000.0000 | 38.6514 | 13.6928 |
| 2405000000.0000 | 38.6121 | 13.6498 |
| 2410000000.0000 | 38.5921 | 13.6148 |
| 2415000000.0000 | 38.5138 | 13.5871 |
| 2420000000.0000 | 38.4523 | 13.5676 |
| 2425000000.0000 | 38.3853 | 13.5439 |
| 2430000000.0000 | 38.3448 | 13.5451 |
| 2435000000.0000 | 38.2915 | 13.5454 |
| 2440000000.0000 | 38.2437 | 13.6089 |
| 2445000000.0000 | 38.2230 | 13.6729 |
| 2450000000.0000 | 38.2156 | 13.7493 |
| 2455000000.0000 | 38.1987 | 13.8089 |
| 2460000000.0000 | 38.2186 | 13.8831 |
| 2465000000.0000 | 38.2007 | 13.9711 |
| 2470000000.0000 | 38.2169 | 14.0418 |
| 2475000000.0000 | 38.2337 | 14.0944 |
| 2480000000.0000 | 38.2503 | 14.1238 |
| 2485000000.0000 | 38.2561 | 14.1854 |
| 2490000000.0000 | 38.3381 | 14.2186 |
| 2495000000.0000 | 38.3403 | 14.1930 |
| 2500000000.0000 | 38.3568 | 14.1756 |

**■ Dielectric Parameter (2450 MHz Body)**

Title LG-P970h  
SubTitle 2450MHz (Body)  
Test Date Feb.23, 2011

| Frequency       | e'      | e''     |
|-----------------|---------|---------|
| 2400000000.0000 | 51.9128 | 14.1138 |
| 2405000000.0000 | 51.8718 | 14.1199 |
| 2410000000.0000 | 51.8277 | 14.1411 |
| 2415000000.0000 | 51.7744 | 14.1368 |
| 2420000000.0000 | 51.7498 | 14.1790 |
| 2425000000.0000 | 51.7284 | 14.1877 |
| 2430000000.0000 | 51.6575 | 14.2399 |
| 2435000000.0000 | 51.6482 | 14.2636 |
| 2440000000.0000 | 51.6421 | 14.2984 |
| 2445000000.0000 | 51.5641 | 14.3381 |
| 2450000000.0000 | 51.5684 | 14.3714 |
| 2455000000.0000 | 51.5661 | 14.4170 |
| 2460000000.0000 | 51.5334 | 14.4265 |
| 2465000000.0000 | 51.5363 | 14.4547 |
| 2470000000.0000 | 51.4931 | 14.4553 |
| 2475000000.0000 | 51.5062 | 14.4820 |
| 2480000000.0000 | 51.5312 | 14.5237 |
| 2485000000.0000 | 51.4867 | 14.5079 |
| 2490000000.0000 | 51.4503 | 14.5272 |
| 2495000000.0000 | 51.4577 | 14.5540 |
| 2500000000.0000 | 51.4772 | 14.5579 |