

FCC EVALUATION REPORT FOR CERTIFICATION


FCC Class B (Class II Permissive Change)

Applicant: LG Electronics Inc.**19-1, Cheongho-ri, Jinwi-myeon,****Pyeongteak-si, Gyeonggi-do, Korea.****Attn: Mr. Do-Hyung Kim, Chief research engineer****Date of Issue: February 27, 2013****Order Number: GETEC-C1-13-078****Test Report Number: GETEC-E3-13-016****Test Site: GUMI COLLEGE EMC CENTER****FCC Registration Number: (100749, 443957)****FCC ID. : BEJPB60GJE****Applicant : LG Electronics Inc.**

Rule Part(s)	: FCC Part 15 Subpart B
Equipment Class	: Class B computing device peripheral (JBP)
EUT Type	: DLP PROJECTOR
Type of Authority	: Certification
Model Name	: PB60G-JE
Trade Name	: LG
Class II Change(s)	: With alternate adapter

This equipment has been shown to be in compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.4 (2009) / Canadian standard ICES-003

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

Tested by,**Reviewed by,**
Hyun Kim / Engineer
GUMI COLLEGE EMC CENTER
Jae-Hoon Jeong, Technical Manager
GUMI COLLEGE EMC CENTER



CONTENTS

1. GENERAL INFORMATION	3
2. INTRODUCTION	4
3. PRODUCT INFORMATION	5
3.1 DESCRIPTION OF EUT.....	5
3.2 SUPPORT EQUIPMENT / CABLES USED	6
3.3 MODIFICATION ITEM(S)	7
4. DESCRIPTION OF TESTS.....	8
4.1 TEST CONDITION.....	8
4.2 CONDUCTED EMISSION	9
4.3 RADIATED EMISSION.....	10
5. CONDUCTED EMISSION.....	11
5.1 OPERATING ENVIRONMENT	11
5.2 TEST SET-UP	11
5.3 MEASUREMENT UNCERTAINTY.....	11
5.4 LIMIT	12
5.5 TEST EQUIPMENT USED.....	12
5.6 TEST DATA FOR CONDUCTED EMISSION	12
6. RADIATED EMISSION	15
6.1 OPERATING ENVIRONMENT	15
6.2 TEST SET-UP	15
6.3 MEASUREMENT UNCERTAINTY.....	15
6.4 LIMIT	16
6.5 TEST EQUIPMENT USED.....	16
6.6 TEST DATA FOR RADIATED EMISSION	16
7. SAMPLE CALCULATIONS.....	21
7.1 EXAMPLE 1 :	21
7.2 EXAMPLE 2 :	21
8. RECOMMENDATION & CONCLUSION.....	22

APPENDIX A – INFORMATION OF CLASS II PERMISSIVE CHANGE

APPENDIX B – TEST SET-UP PHOTOGRAPHS





Scope: Measurement and determination of electromagnetic emissions (EME) of radio frequency devices including intentional and / or unintentional radiators for compliance with technical rules and regulations of the Federal Communications Commission.

1. General Information

Applicant: LG Electronics Inc.

Applicant Address: 19-1, Cheongho-ri, Jinwi-myeon, Pyeongteak-si, Gyeonggi-do, Korea.

Manufacturer: LG Electronics Inc.

Manufacturer Address: 19-1, Cheongho-ri, Jinwi-myeon, Pyeongteak-si, Gyeonggi-do, Korea.

Contact Person: Mr. Do-Hyung Kim, Chief research engineer

Tel Number: +82-31-610-9623

- **FCC ID.** BEJPB60GJE
- **EUT Type** DLP PROJECTOR
- **Model Name** PB60G-JE
- **Trade Name** LG
- **Serial Number** Prototype
- **Rule Part(s)** FCC Part 15 Subpart B
- **Type of Authority** Certification
- **Test Procedure(s)** ANSI C63.4 (2009) / Canadian standard ICES-003
- **Dates of Test** February 12 ~ 16, 2013
- **Place of Test** **GUMI COLLEGE EMC CENTER** (FCC Registration Number: 100749, 443957)
37, Yaeun-ro, Gumi-si, Gyeongsangbuk-do, 730-711, Republic of Korea
- **Test Report Number** GETEC-E3-13-016
- **Dates of Issue** February 27, 2013
- **Class II Change(s)** With alternate adapter

EUT Type: DLP PROJECTOR

FCC ID.: BEJPB60GJE





2. Introduction

The measurement procedure described in American National Standard for Methods of Measurement of Radio-Nose Emissions From Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz (ANSI C63.4-2009) was used in determining radiated and conducted emissions emanating from **LG Electronics Inc.**

DLP PROJECTOR (Model Name: PB60G-JE)

These measurement tests were conducted at **GUMI COLLEGE EMC CENTER**

The site address is 37, Yaeun-ro, Gumi-si, Gyeongsangbuk-do, 730-711, Republic of Korea

This test site is one of the highest point of Gumi 1 college at about 200 km away from Seoul city and 40 km away from Daegu city. It is located in the valley surrounded by mountains in all directions where ambient radio signal conditions are quiet and a favorable area to measure the radio frequency interference on open field test site for the computing and ISM devices manufactures. The detailed description of the measurement facility was found to be in compliance with the requirements of §2.948 according to ANSI C63.4 (2009)




Fig 1. The map above shows the Gumi College in vicinity area.





3. Product Information

3.1 Description of EUT

The Equipment under Test (EUT) is the **LG Electronics Inc.**

DLP PROJECTOR (Model Name: PB60G-JE) FCC ID.: BEJPB60GJE

MODELS	PB60G (PB60G-JE)
Resolution (Pixel)	1280 (Horizontal) × 800 (Vertical)
Aspect ratio	16:10 (Horizontal:Vertical)
Panel size (mm)	11.623
Projection distance (Video size)	0.80 m - 3.25 m (63.5 cm - 254.0 cm)
Ratio of upward projection	100 %
Working range of the remote control	6 m
Video Input	NTSC M / PAL-B, D, G, H, I / PAL M / PAL N / PAL 60
Audio Output	1W + 1W
Height (mm)	33.8 (without foot), 38.3 (with foot)
Width (mm)	158
Depth (mm)	101.5
Weight (g)	445
USB Device	5 V, 0.5 A (Max.)
Operation environ- ment	Temperature
	Operation 0°C - 40°C
	Storage -20°C - 60°C
	Relative Humidity
	Operation 0 % - 80%
	Storage 0 % - 85%

-. Maximum Frequency Range : 667 MHz

EUT Type: DLP PROJECTOR

FCC ID.: BEJPB60GJE





3.2 Support Equipment / Cables used

3.2.1 Used Support Equipment

Description	Manufacturer	Model Name	S/N & FCC ID.
PC(Main board)	ASUSTEK COMPUTER INC.	P8H61	S/N: 0BG084-02014-MIBFE0-A05 FCC ID.: DoC
Video card	Digital Greentech Co., Ltd.	VX4850	S/N: LG1112056668 FCC ID.: DoC
PS2 keyboard	COMPAQ	166516-AD6	S/N: B13BBOR391006D FCC ID.: AQ6-23K15
USB mouse	Microsoft Corporation	1484	S/N: 0352700289761 FCC ID: DoC
DVD player	ILIKE ELECTRONICS CO., LTD.	CVX-3800 Full-HD	S/N: CVX380020110110493 FCC ID.: Verification
Headset	PHILIPS	SBC HL140	S/N: None. FCC ID.: N/A
USB memory stick	SAMSUNG	SUM-PSB4	S/N: TBBB202478F FCC ID.: N/A

See “Appendix D – Test Setup Photographs” for actual system test set-up

3.2.2 System configuration

Description	Manufacturer	Model Name	S/N & FCC ID.
Adapter ¹⁾	LG Innotek Co., Ltd.	PSAB-L206B	S/N: None. FCC ID.: N/A
IR remote controller	LG Electronics Inc.	MKJ50025108	S/N: None. FCC ID.: N/A

1) Input ratings: AC (100 – 240) V~, (50/60) Hz, 1.4 A / Output ratings: DC 19 V, 3.42 A





3.2.3 Used Cable(s)

Cable Name	Condition	Description
Power cable	Connected to the adapter	1.00 m unshielded
Adapter cable	Connected to the EUT and adapter	1.80 m shielded with a ferrite core
RGB (Analog) in cable	Connected to the EUT and PC	1.80 m shielded with two ferrite cores
HDMI (Digital) in cable	Connected to the EUT and PC	2.00 m shielded
AV in cable	Connected to the EUT and DVD player	3.00 m shielded
Headset cable	Connected to the EUT and headset	1.20 m shielded

3.3 Modification Item(s)

- None





4. Description of tests

4.1 Test Condition

The EUT was installed, arranged and operated in a manner that is most representative of equipment as typically used. The measurements were carried out while varying operating modes and cable positions within typically arrangement to determine maximum emission level.

The representative and worst test mode(s) were noted in the test report.

The test conditions of the noted test mode(s) in this test report are;

- Test Voltage / Frequency : AC 120 V / 60 Hz
- Test Mode(s)
 - **Projection resolution mode**
 - . 1 680 × 1 050 / 60 Hz (RGB: Analog, HDMI: Digital)
 - **Operating test pattern**
 - . “H” character scrolling mode (Font size: 10)
 - . Black background white character
 - . Brightness and contrast was adjusted as maximum level
 - . Continuous playback of 1 kHz audio file with winamp player
 - . USB memory stick was connected to the USB port

“The verification report for TV/AV mode would be issued by LG Electronics Inc.”





4.2 Conducted Emission

The Line conducted emission test facility is inside a 4 m × 8 m × 2.5 m shielded enclosure. (FCC Registration No.: 100749)

The EUT was placed on a non-conducting 1.0 m by 1.5 m table, which is 0.8 m in height and 0.4 m away from the vertical wall of the shielded enclosure.

The EUT is powered from the Rohde & Schwarz LISN (ESH2-Z5) and the support equipment is powered from the Rohde & Schwarz LISN (ESH3-Z5). Powers to the LISN are filtered by high-current high insertion loss power line filter.

Sufficient time for EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition.

The RF output of the LISN was connected to the EMI test receiver (Rohde & Schwarz, ESCS30).

Exploratory measurements were conducted to identify the highest emission by operating the EUT in a range of typical modes of operation, cable positions, system configuration and arrangement.

Based on exploratory measurements, the final measurements were conducted at the worst test conditions.

Exploratory measurements were scanned using Peak mode of EMI Test receiver from 150 kHz to 30 MHz with 20 ms sweep time. The final measurements were measured with Quasi-Peak and Average mode.

The bandwidth of EMI Test Receiver was set to 9 kHz. Interface cables were connected to the available interface ports of the test unit. Excess cable lengths were bundled at center with 30 cm ~ 40 cm.




Fig 2. Impedance of LISN





4.3 Radiated Emission

Exploratory Radiated measurements were conducted at the 3m semi anechoic chamber in order to identify the highest emission by operating the EUT in a range of typical modes of operation, cable positions, system configuration and arrangement.

Based on exploratory measurements, the final measurements were conducted at the worst test conditions.

Final measurements of below 1GHz were made at 3m Chamber (FCC Registration No.: 443957) or Open area test site (FCC Registration No.: 100749) that complies with CISPR 16/ANSI C63.4.

Above 1GHz final measurements were conducted at the 3m Chamber (FCC Registration No.: 443957) only.

For measurements above 1GHz, the bottom side of 3m chamber was installed with absorbers in order to meet SVSWR Limit.

Exploratory measurements were scanned using Peak mode of EMI Test receiver and final measurements were measured with Quasi-Peak mode (Below 1GHz) and Peak & Average mode (Above 1GHz).

The measurements were performed by rotating the EUT 360° and adjusting the receive antenna height from 1.0 m to 4.0 m. All frequencies were investigated in both horizontal and vertical antenna polarity.




Fig 3. Dimensions of test site (Below 1GHz)




Fig 4. Dimensions of test site (Above 1GHz)





5. Conducted Emission

5.1 Operating Environment

Temperature : 24.0 °C
Relative Humidity : 40.0 % R.H.

5.2 Test Set-up

The conducted emission measurements were performed in the shielded room.

The EUT was placed on wooden table, 0.8 m heights above the floor, 0.4 m from the reference ground plane (GRP) wall and 0.8 m from AMN & ISN.

AMN is bonded on horizontal reference ground plane.

The ground plane, which was electrically bonded to the shield room, ground system and all power lines entering the shield room, were filtered.

5.3 Measurement Uncertainty

The measurement uncertainty was calculated in accordance with ISO "Guide to the expression of uncertainty in measurement."

The measurement uncertainty was given with a confidence of 95 %.

Test Items	Uncertainty	Remark
Conducted emission (9 kHz ~ 150 kHz)	± 2.74 dB	Confidence level of approximately 95 % ($k = 2$)
Conducted emission (150 kHz ~ 30 MHz)	± 4.25 dB	Confidence level of approximately 95 % ($k = 2$)





5.4 Limit

RFI Conducted	FCC Limit(dB μ V/m) Class B	
Freq. Range	Quasi-Peak	Average
150 kHz ~ 0.5 MHz	66 ~ 56*	56 ~ 46*
0.5 MHz ~ 5 MHz	56	46
5 MHz ~ 30 MHz	60	50
*Limits decreases linearly with the logarithm of frequency.		

5.5 Test Equipment used

Model Name	Manufacturer	Description	Serial Number	Due to Calibration
■ - ESCS30	Rohde & Schwarz	EMI Test Receiver	839809/003	05. 22. 2013
■ - ESH3-Z5	Rohde & Schwarz	LISN	838979/020	05. 23. 2013
■ - ESH2-Z5	Rohde & Schwarz	LISN	829991/009	05. 23. 2013
□ - ISN T8	TESEQ.GmbH	ISN	24568	07. 04. 2013


5.6 Test data for Conducted Emission

- Test Date : February 12, 2013
- Resolution Bandwidth : 9 kHz
- Frequency Range : 0.15 MHz ~ 30 MHz
- Line : L1: Live, N: Neutral





- Operating condition: 1 680 × 1 050 / 60 Hz (RGB: Analog)



Final Result 1

Frequency (MHz)	QuasiPeak (dBμV)	Meas. Time (ms)	Bandwidth (kHz)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.178000	52.1	1000.0	9.000	GND	L1	10.1	12.5	64.6	
0.560000	41.0	1000.0	9.000	GND	N	10.1	15.0	56.0	
0.584000	39.9	1000.0	9.000	GND	N	10.1	16.1	56.0	
2.044000	34.9	1000.0	9.000	GND	N	10.1	21.1	56.0	
3.340000	41.1	1000.0	9.000	GND	L1	10.1	14.9	56.0	
22.828000	52.0	1000.0	9.000	GND	N	10.5	8.0	60.0	

Final Result 2


Frequency (MHz)	CAverage (dBμV)	Meas. Time (ms)	Bandwidth (kHz)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.178000	40.7	1000.0	9.000	GND	L1	10.1	13.8	54.6	
0.560000	28.9	1000.0	9.000	GND	N	10.1	17.1	46.0	
0.584000	27.3	1000.0	9.000	GND	N	10.1	18.7	46.0	
2.044000	25.1	1000.0	9.000	GND	N	10.1	20.9	46.0	
3.340000	27.8	1000.0	9.000	GND	L1	10.1	18.2	46.0	
22.828000	44.9	1000.0	9.000	GND	N	10.5	5.1	50.0	

< Fig 5. Conducted emission result >





- Operating condition: 1 680 × 1 050 / 60 Hz (HDMI: Digital)



Final Result 1

Frequency (MHz)	QuasiPeak (dBμV)	Meas. Time (ms)	Bandwidth (kHz)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.174000	51.2	1000.0	9.000	GND	L1	10.1	13.6	64.8	
0.568000	41.0	1000.0	9.000	GND	N	10.1	15.0	56.0	
0.568000	41.2	1000.0	9.000	GND	N	10.1	14.8	56.0	
1.532000	35.2	1000.0	9.000	GND	N	10.1	20.8	56.0	
3.368000	40.2	1000.0	9.000	GND	L1	10.1	15.8	56.0	
22.900000	52.4	1000.0	9.000	GND	N	10.5	7.6	60.0	

Final Result 2

Frequency (MHz)	CAverage (dBμV)	Meas. Time (ms)	Bandwidth (kHz)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.174000	39.9	1000.0	9.000	GND	L1	10.1	14.9	54.8	
0.568000	28.0	1000.0	9.000	GND	N	10.1	18.0	46.0	
0.568000	28.1	1000.0	9.000	GND	N	10.1	17.9	46.0	
1.532000	24.5	1000.0	9.000	GND	N	10.1	21.5	46.0	
3.368000	27.7	1000.0	9.000	GND	L1	10.1	18.3	46.0	
22.900000	45.3	1000.0	9.000	GND	N	10.5	4.7	50.0	

< Fig 6. Conducted emission result >





6. Radiated Emission

6.1 Operating Environment

Temperature : 23.0 °C
Relative Humidity : 42.0 % R.H.

6.2 Test Set-up

A preliminary scan with peak mode was performed in the semi anechoic chamber and found frequency for test site. The formal radiated emission was measured at 10 m distance open area test site and 3 m distance anechoic chamber. The EUT was placed on a non-conductive turntable approximately 0.8 m above the ground plane. The turntable with EUT was rotated 360°, and the antenna was varied in height between 1.0 m and 4.0 m in order to determine the maximum emission levels. This procedure was performed for both horizontal and vertical polarization of the receiving antenna.

6.3 Measurement Uncertainty

The measurement uncertainty was calculated in accordance with ISO “Guide to the expression of uncertainty in measurement”.

The measurement uncertainty was given with a confidence of 95 %.

Test Items (Anechoic Chamber)	Uncertainty	Remark
Radiated emission (30 MHz ~ 300 MHz, 3 m, Vertical)	± 4.35 dB	Confidence level of approximately 95 % ($k = 2$)
Radiated emission (30 MHz ~ 300 MHz, 3 m, Horizontal)	± 4.29 dB	Confidence level of approximately 95 % ($k = 2$)
Radiated emission (300 MHz ~ 1 000 MHz, 3 m, Vertical)	± 4.43 dB	Confidence level of approximately 95 % ($k = 2$)
Radiated emission (300 MHz ~ 1 000 MHz, 3 m, Horizontal)	± 4.21 dB	Confidence level of approximately 95 % ($k = 2$)





6.4 Limit

Frequency (MHz)	FCC Limit @ 3 m. dB μ V/m	CISPR Limit @ 10 m. dB μ V/m
30 ~ 88	40.0	30.0
88 ~ 216	43.5	30.0
216 ~ 230	46.0	30.0
230 ~ 960	46.0	37.0
960 ~ 1 000	54.0	37.0
> 1 000	54.0	No Specified limit

6.5 Test Equipment used

Model Name	Manufacturer	Description	Serial Number	Due to Calibration
■ - ESIB26	Rohde & Schwarz	EMI Test Receiver	830482/010	05. 23. 2013
■ - VULB9160	Schwarzbeck	Broadband Test Antenna	3193	03. 14. 2014
■ - BBHA9120D	Schwarzbeck	Horn Antenna	207	01. 29. 2014
■ - MCU066	maturo GmbH	Position Controller	1390306	N/A
■ - TT2.5SI	maturo GmbH	Turntable	1390307	N/A
■ - AM 4.0	maturo GmbH	Antenna Mast	1390308	N/A
■ - AFS 44 00101800-25-10P-44	MITEQ	Preamplifier	1258943	11. 12. 2013

6.6 Test data for Radiated Emission


- Test Date : February 13 ~ 16, 2013
- Measurement Distance : 3 m
- Note : The highest frequency of the internal source of the EUT is between 500 MHz and 1 000 MHz (667 MHz). The measurement was made up to 5 000 MHz
- Measurement

Frequency range	30 MHz ~ 1 GHz	Above 1 GHz
Detector mode	Quasi peak	Peak / Average
Resolution bandwidth	120 kHz	1 MHz





- Operating condition: 1 680 × 1 050 / 60 Hz (RGB: Analog)



Final Result 1


Frequency (MHz)	QuasiPeak (dBμV/m)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBμV/m)
48.752500	27.8	1000.0	120.000	135.0	V	29.0	13.0	12.2	40.0
56.771250	23.4	1000.0	120.000	131.0	V	306.0	12.9	16.6	40.0
118.997500	36.5	1000.0	120.000	196.0	H	68.0	12.3	7.0	43.5
194.981250	34.5	1000.0	120.000	117.0	H	246.0	11.2	9.0	43.5
308.785000	41.2	1000.0	120.000	110.0	H	127.0	15.4	4.8	46.0
314.180000	44.0	1000.0	120.000	123.0	H	271.0	15.5	3.0	46.0
476.120000	35.9	1000.0	120.000	200.0	H	-8.0	19.9	10.1	46.0

< Fig 7. Radiated emission result (30 MHz ~ 1 000 MHz) >





- Operating condition: 1 680 × 1 050 / 60 Hz (HDMI: Digital)



Final Result 1


Frequency (MHz)	QuasiPeak (dBμV/m)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBμV/m)
59.610000	24.3	1000.0	120.000	100.0	V	312.0	12.8	15.7	40.0
121.037500	35.8	1000.0	120.000	195.0	H	274.0	12.5	7.7	43.5
224.000000	35.4	1000.0	120.000	165.0	H	272.0	11.9	10.6	46.0
313.651250	40.8	1000.0	120.000	165.0	H	273.0	15.5	5.2	46.0
316.515000	37.1	1000.0	120.000	165.0	H	285.0	15.6	8.9	46.0
476.120000	37.4	1000.0	120.000	200.0	H	358.0	19.9	8.6	46.0
877.498750	36.4	1000.0	120.000	100.0	V	127.0	28.0	9.6	46.0

< Fig 8. Radiated emission result (30 MHz ~ 1 000 MHz) >





- Operating condition: 1 680 × 1 050 / 60 Hz (RGB: Analog)
- Green marker: Average detector, Blue marker: Peak detector



Final Result 1

Frequency (MHz)	MaxPeak (dBμV/m)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBμV/m)
1353.700000	51.0	1000.0	1000.000	100.0	H	170.0	-9.4	23.0	74.0
1500.200000	49.0	1000.0	1000.000	100.0	V	3.0	-8.7	25.0	74.0
1750.080000	52.5	1000.0	1000.000	100.0	V	320.0	-7.9	21.5	74.0
2026.420000	50.1	1000.0	1000.000	119.0	H	224.0	-7.5	23.9	74.0
2454.360000	42.2	1000.0	1000.000	100.0	V	217.0	-5.5	31.8	74.0
3000.420000	46.4	1000.0	1000.000	194.0	V	281.0	-4.2	27.6	74.0
3369.740000	44.9	1000.0	1000.000	110.0	H	160.0	-3.4	29.1	74.0

Final Result 2


Frequency (MHz)	CAverage (dBμV/m)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBμV/m)
1353.700000	34.2	1000.0	1000.000	100.0	H	170.0	-9.4	19.8	54.0
1500.200000	42.1	1000.0	1000.000	100.0	V	3.0	-8.7	11.9	54.0
1750.080000	29.3	1000.0	1000.000	100.0	V	320.0	-7.9	24.7	54.0
2026.420000	33.3	1000.0	1000.000	119.0	H	224.0	-7.5	20.7	54.0
2454.360000	27.8	1000.0	1000.000	100.0	V	217.0	-5.5	26.2	54.0
3000.420000	35.2	1000.0	1000.000	194.0	V	281.0	-4.2	18.8	54.0
3369.740000	30.1	1000.0	1000.000	110.0	H	160.0	-3.4	23.9	54.0

< Fig 9. Radiated emission result (1 000 MHz ~ 5 000 MHz) >





- Operating condition: 1 680 × 1 050 / 60 Hz (HDMI: Digital)
- Green marker: Average detector, Blue marker: Peak detector



Final Result 1

Frequency (MHz)	MaxPeak (dBμV/m)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBμV/m)
1032.080000	52.0	1000.0	1000.000	100.0	H	222.0	-11.2	22.0	74.0
1353.640000	49.7	1000.0	1000.000	110.0	V	191.0	-9.4	24.3	74.0
1500.080000	50.7	1000.0	1000.000	125.0	V	0.0	-8.7	23.3	74.0
1710.320000	48.2	1000.0	1000.000	100.0	H	206.0	-8.0	25.8	74.0
2022.080000	51.9	1000.0	1000.000	125.0	V	108.0	-7.5	22.1	74.0
2765.220000	41.8	1000.0	1000.000	119.0	V	108.0	-4.6	32.2	74.0
4051.220000	46.2	1000.0	1000.000	100.0	H	194.0	-1.5	27.8	74.0

Final Result 2

Frequency (MHz)	CAverage (dBμV/m)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBμV/m)
1032.080000	25.7	1000.0	1000.000	100.0	H	222.0	-11.2	28.3	54.0
1353.640000	33.4	1000.0	1000.000	110.0	V	191.0	-9.4	20.6	54.0
1500.080000	40.0	1000.0	1000.000	125.0	V	0.0	-8.7	14.0	54.0
1710.320000	27.2	1000.0	1000.000	100.0	H	206.0	-8.0	26.8	54.0
2022.080000	36.2	1000.0	1000.000	125.0	V	108.0	-7.5	17.8	54.0
2765.220000	28.0	1000.0	1000.000	119.0	V	108.0	-4.6	26.0	54.0
4051.220000	31.1	1000.0	1000.000	100.0	H	194.0	-1.5	22.9	54.0

< Fig 10. Radiated emission result (1 000 MHz ~ 5 000 MHz) >





7. Sample Calculations

$$\begin{aligned} \text{dB}\mu\text{V} &= 20 \text{ Log}_{10}(\mu\text{V}/\text{m}) \\ \text{dB}\mu\text{V} &= \text{dBm} + 107 \\ \mu\text{V} &= 10^{(\text{dB}\mu\text{V}/20)} \end{aligned}$$

7.1 Example 1 :

■ 20.3 MHz

Class B Limit	= 250 μV = 48 dB μV
Reading	= 39.2 dB μV
$10^{(39.2\text{dB}\mu\text{V}/20)}$	= 91.2 μV
Margin	= 48 dB μV - 39.2 dB μV = 8.8 dB

7.2 Example 2 :

■ 66.7 MHz

Class B Limit	= 100 $\mu\text{V}/\text{m}$ = 40.0 dB $\mu\text{V}/\text{m}$
Reading	= 31.0 dB μV
Antenna Factor + Cable Loss	= 5.8 dB
Total	= 36.8 dB $\mu\text{V}/\text{m}$
Margin	= 40.0 dB $\mu\text{V}/\text{m}$ - 36.8 dB $\mu\text{V}/\text{m}$ = 3.2 dB





8. Recommendation & Conclusion

The data collected shows that the **LG Electronics Inc. DLP PROJECTOR (Model Name: PB60G-JE)** was complies with §15.107 and 15.109 of the FCC Rules.

- The end -

