

# FCC 47 CFR PART 18

## TEST REPORT

**Test Report No.** : OT-25O-RED-054  
**Reception No.** : 2510003448  
**Applicant** : LG Electronics USA, Inc.  
**Address** : 111 Sylvan Avenue, North Building, Englewood Cliffs, New Jersey, 07632, United States  
**Manufacturer** : LG Electronics USA, Inc.  
**Address** : 170, Seongsanpaechong-ro, Seongsan-gu, Changwon-si, Gyeongsangnam-do 51533 Korea  
**Type of Equipment** : HOUSEHOLD ELECTRIC RANGE  
**Model Name** : LSIL633TFE  
**Multiple Model Name** : LSIL633\*\*E  
**FCC ID.** : BEJS471111A  
**Serial number** : N/A  
**Total page of Report** : 8 pages (including this page)  
**Date of Incoming** : September 23, 2025  
**Date of Issuing** : October 24, 2025

### summary

The equipment complies with the requirement of **FCC CFR 47 PART 18( § 18.313)**.

This test report contains only the results of a single test of the sample supplied for the examination.

It is not a general valid assessment of the features of the respective products of the mass-production.


This report is not correlated with the "KS Q ISO/IEC 17025 and KOLAS accreditation" of Korean Laboratory Accreditation Scheme.

Reviewed by:



Sun-Teak, Oh / Manager  
EMC Testing Div.  
ONETECH Corp.

Approved by:



Seung-Hyun, Park / Senior Manager  
EMC Testing Div.  
ONETECH Corp.

## CONTENTS

**PAGE**

|                                                                                 |          |
|---------------------------------------------------------------------------------|----------|
| <b>1. VERIFICATION OF COMPLIANCE .....</b>                                      | <b>4</b> |
| <b>2. GENERAL INFORMATION.....</b>                                              | <b>5</b> |
| <b>2.1 PRODUCT DESCRIPTION.....</b>                                             | <b>5</b> |
| <b>2.2 ALTERNATIVE TYPE(S)/MODEL(S); ALSO COVERED BY THIS TEST REPORT. ....</b> | <b>5</b> |
| <b>2.3 TEST CONDITION.....</b>                                                  | <b>5</b> |
| <b>3. EUT MODIFICATIONS.....</b>                                                | <b>5</b> |
| <b>4. SUMMARY OF TEST RESULTS .....</b>                                         | <b>6</b> |
| <b>4.1 TEST EQUIPMENT USED.....</b>                                             | <b>6</b> |

**Revision History**

| Rev. No. | Issue Report No. | Issued Date       | Revisions                                      | Section Affected |
|----------|------------------|-------------------|------------------------------------------------|------------------|
| 0        | OT-242-RED-124   | February 29, 2024 | Initial Release                                | All              |
| 1        | OT-25O-RED-054   | October 24, 2025  | Changed the RF Module<br>(LCWB-001 → LCWB-008) | All              |
|          |                  |                   |                                                |                  |

\* Please contact us (e-mail: [info@onetech.co.kr](mailto:info@onetech.co.kr)) for verification of this test report.

## 1. VERIFICATION OF COMPLIANCE

|              |                                                                                                                      |
|--------------|----------------------------------------------------------------------------------------------------------------------|
| APPLICANT    | LG Electronics USA, Inc.<br>111 Sylvan Avenue, North Building, Englewood Cliffs, New Jersey,<br>07632, United States |
| MANUFACTURER | LG Electronics USA, Inc.<br>170, Seongsanpaechong-ro, Seongsan-gu, Changwon-si,<br>Gyeongsangnam-do 51533 Korea      |
| FACTORY      | LG Electronics USA, Inc.<br>170, Seongsanpaechong-ro, Seongsan-gu, Changwon-si,<br>Gyeongsangnam-do 51533 Korea      |

|                                                         |                             |
|---------------------------------------------------------|-----------------------------|
| E.U.T. DESCRIPTION                                      | HOUSEHOLD ELECTRIC RANGE    |
| MEASUREMENT PROCEDURES                                  | MP-5: 1986                  |
| TYPE OF EQUIPMENT TESTED                                | Pre-Production              |
| KIND OF EQUIPMENT<br>AUTHORIZATION REQUESTED            | Certification               |
| STANDARDS                                               | FCC Part 18, Section 18.313 |
| MODIFICATIONS ON THE EQUIPMENT<br>TO ACHIEVE COMPLIANCE | None                        |
| FINAL TEST WAS CONDUCTED ON                             | 10 m semi anechoic chamber  |

ONETECH Corp. tested the above equipment in accordance with the requirements set forth in the above standard. The test results show that equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

## 2. GENERAL INFORMATION

### 2.1 Product Description

The LG Electronics USA, Inc., Model LSIL633TFE (referred to as the EUT in this report) is a HOUSEHOLD ELECTRIC RANGE. The product specification described herein was obtained from product data sheet or user's manual.

|                                                                     |                                                                                                                                                                                     |
|---------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| CHASSIS TYPE                                                        | Metal & Plastic                                                                                                                                                                     |
| Temperature Range                                                   | -40 °C ~ +85 °C                                                                                                                                                                     |
| LIST OF EACH OSC. or CRY. FREQ.<br>(FREQ. >= 1 MHz)                 | 10 MHz                                                                                                                                                                              |
| RF OPERATING FREQUENCY                                              | Wi-Fi (2 412 – 2 462 MHz), Bluetooth (2 402 – 2 480 MHz)<br>(Wi-Fi Module Model: LCWB-008)<br>* Wi-Fi Module FCC ID : BEJ-LCWB008<br>* Wireless module redundancy(LCWB001, LCWB008) |
| NUMBER OF PCB LAYERS                                                | -                                                                                                                                                                                   |
| P. C. Board name                                                    | -                                                                                                                                                                                   |
| Induction cooking range<br>Operating frequency (ISM frequency band) | 20 kHz ~ 75 kHz                                                                                                                                                                     |
| ELECTRICAL RATING                                                   | 240 V, 11.4 kW Or 208 V, 9.45 kW/ 60 Hz                                                                                                                                             |
| EXTERNAL CONNECTOR                                                  | AC IN                                                                                                                                                                               |

### 2.2 Alternative type(s)/model(s); also covered by this test report.

| LSIL633TFE, LSIL633**E |                   |                   |
|------------------------|-------------------|-------------------|
| Variable               | Range of variable | Content           |
| 1st '*'                | T or 2            | Door              |
| 2nd '*'                | A to Z            | Cosmetic features |

### 2.3 Test Condition

The test conditions of the noted test mode(s) in this test report are;

-. Test Mode: After applying AC power to the EUT, it was tested by checking the cook mode operation and wireless operation after connecting wirelessly to the smartphone application.

## 3. EUT MODIFICATIONS

-. None

## 4. Summary of Test Results

Test Date: October 24, 2025

### 4.1 Test Equipment used

|     | Model Number | Manufacturer       | Description       | Serial Number | Last Cal. (Interval) |
|-----|--------------|--------------------|-------------------|---------------|----------------------|
| ■ - | ESW 44       | Rohde & Schwarz    | EMI Test Receiver | 101851        | Mar. 05, 2025 (1Y)   |
| ■ - | CO3000       | Innco Systems GmbH | Controller        | N/A           | N/A                  |
| ■ - | DT5000       | Innco Systems GmbH | Turn Table        | N/A           | N/A                  |
| ■ - | HLA 6121     | TESEQ              | Loop Antenna      | 50841         | Apr. 27, 2024 (2Y)   |

All test equipment used is calibrated on a regular basis.

## -. 18.313 Radio frequency exposure requirements

### 1.1307 (b)(3)(ii)(A)

The available maximum time-averaged power of each source is no more than 1 mW and there is a separation distance of two centimeters between any portion of a radiating structure operating and the nearest portion of any other radiating structure in the same device, except if the sum of multiple sources is less than 1 mW during the time-averaging period, in which case they may be treated as a single source (separation is not required). This exemption may not be used in conjunction with other exemption criteria other than those is paragraph (b)(3)(i)(A) of this section. Medical implant devices may only use this exemption and that in paragraph (b)(3)(i)(A).

## -. 447498 D04 Interim General RF Exposure Guidance v01

### 2.2.1 1-mW Test Exemption for Multiple Sources

As discussed in § 1.1307(b)(3)(ii)(A), the 1 mW exemption intended for single transmitters may be also applied to simultaneous transmission conditions, within the same host device, according one of the following criteria:

- When maximum available power each individual transmitting antenna within the same time averaging period is  $\leq 1$  mW, and the nearest parts of the antenna structures of the simultaneously operating transmitters are separated by at least 2 cm.
- When the aggregate maximum available power of all transmitting antennas is  $\leq 1$  mW in the same time-averaging period. This exemption may not be combined with any other exemption.

| Elements                                                                                                 | Highest Emissions<br>@ 10m [dBuV/m] | EIRP [dBm] | EIRP [mW] |
|----------------------------------------------------------------------------------------------------------|-------------------------------------|------------|-----------|
| Element 1                                                                                                | 78.9                                | -5.87      | 0.259     |
| Element 2                                                                                                | 65.8                                | -18.97     | 0.013     |
| Element 3                                                                                                | 68.9                                | -15.87     | 0.026     |
| Element 4                                                                                                | 68.9                                | -15.87     | 0.026     |
| These values are most conservative values based on measured emission regardless voltage and polarization |                                     |            |           |

$$\text{EIRP[dBm]} = E [\text{dB}\mu\text{V/m}] + 20 \log (10 [\text{m}]) - 104.77$$

$$\text{Aggregated maximum power} = 0.259 + 0.013 + 0.026 + 0.026 = 0.324 \text{ mW}$$

Therefore, 1mW test exemption can be applied and this device complies 18.313 requirement in accordance with 1.1307(b)(3)(ii)(A).

## Output power into antenna & RF exposure evaluation distance

### WLAN (2.4 G)

#### - Maximum tune up tolerance

| Operating Frequency (MHz) | Output Average Power to Antenna (dBm) | Antenna gain (dBi) | Power Density at 20 cm (mW/cm <sup>2</sup> ) | Limits (mW/cm <sup>2</sup> ) |
|---------------------------|---------------------------------------|--------------------|----------------------------------------------|------------------------------|
| 2412 ~ 2462               | 16.32                                 | -1.70              | 0.005 764                                    | 1                            |

#### Note:

- The power density Pd (5th column) at a distance of 20 cm calculated from the friis transmission formula is far below the limit of 1 mW/cm<sup>2</sup>.
- This equipment complies with FCC radiation exposure limits set forth for an uncontrolled environment.
- This equipment should be installed and operated with minimum 20 cm between the radiator and your body.
- The antenna gain of this transmitter is less than 6 dBi and must not be collocated or operating in conjunction with any other antenna or transmitter unless authorized to do so by the FCC.

### Conclusion: No SAR is required.

### Simultaneous transmission of RF Exposure test exclusion for worst case configuration.

Element: the ratio is 0.385 / 1

WLAN: the ratio is 0.005 764 / 1

Confirm the sum result of individual MPEs ratio is  $\leq 1.0$ ;

Element + WLAN:  $(0.385 / 1) + (0.005 764 / 1) = 0.391 \leq 1.0$

So, this device meets the KDB447498 D01 v06 section 7.2 requirement of "Simultaneous transmission MPE test exclusion".