



683-3, Yubang-Dong, Yongin-Si, Kyunggi-Do, Korea. 449-080
Tel: +82-31-321-2664 Fax: +82-31-321-1664
<http://www.digitalemc.com>

FCC Test Report

FCC ID : BEJT500

Applicant : LG Electronics Inc.

Model Number : LG-T500

Additional Model(s) : T500

Manufacturer : LG Electronics Inc.

ANSI C 63.4:2003

Test Standard : FCC Part 15 Subpart B

(Type of Device : Class B Computing Device Peripheral (JBP))

Date of Tests : January 27 ~ February 7, 2011

Date of Issue : February 7, 2011

Tested by : M.J.SONG Manager

Reviewed by : Y.K.SHIN/Manager

A handwritten signature in black ink, appearing to be "M.J. Song", written over a horizontal line.

A handwritten signature in black ink, appearing to be "Y.K. Shin", written over a horizontal line.

This test result only responds to the tested sample.

It is not allowed to copy this report even partly without the allowance of the test laboratory.

CONTENTS

1. General Remarks	3
2. Test Laboratory	3
3. General Information of EUT	4
3.1 Product Description.....	4
3.2 Product Information.....	4
4. Test Summary	5
4.1 Summary of tests	5
5. Test Set-up and operation mode	6
5.1 Principle of Configuration Selection	6
5.2 Test Operation Mode.....	6
5.3 Support Equipment Used	6
6. Test Results : Emission	7
6.1 Conducted Emission	7
6.2 Radiated Emission	11

1. General Remarks

This Report describes the emission characteristics of the tested product.

If the product will be used with additional equipment other than those mentioned in this report or if the tested product will be used against the manufacture's specifications, the compliance with the relevant standards for the system has to be ensured.

2. Test Laboratory

Digital EMC Co., Ltd. has been accredited / filed / authorized by the agencies listed in the following table;

Certificate	Nation	Agency	Code	Mark
Accreditation	Korea	KOLAS	393	ISO/IEC 17025
Site Filing	USA	FCC	101842	Test Facility list & NSA Data
	Japan	VCCI	C-1427 R-1364, R-3385 T-1442	Test Facility list & NSA Data
Certification	Korea	KCC	KR0034	Test Facility list & NSA Data
	Germany	TUV	ROK1028C	ISO/IEC 17025

Quality control in the testing laboratory is implemented as per ISO/IEC 17025 which is the "General requirements for the competents of calibration and testing laboratory".

DIGITAL EMC CO., LTD.

Address: 683-3, Yubang-Dong, Yongin-Si, Kyunggi-Do, Korea. 449-080

<http://www.digitalemc.com>

Tel: +82-31-321-2664 Fax: +82-31-321-1664

3. General Information of EUT

3.1 Product Description

Equipment Under Test (E.U.T) is Cellular/PCS GSM/GPRS Phone with Bluetooth and EDGE RX

Model: LG-T500 manufactured by LG Electronics Inc. Its basic purpose is used for communications.

3.2 Product Information

Model No.	LG-T500
Add Model No.	T500
EUT Type	Cellular/PCS GSM/GPRS Phone with Bluetooth and EDGE RX
Serial No	NONE
FCC ID	BEJT500
Type of Sample Tested	Pre-Production
High Frequency	208MHz
Supplied Power for Test	AC120V, 60Hz
Applicant	LG Electronics Inc. 60-39, Gasan-dong, Gumchon-gu, Seoul, 153-023, Korea
TX Frequency	824.20 MHz to 848.80 MHz (GSM850) 1850.20 MHz to 1909.80 MHz (GSM1900)
RX Frequency	869.20 MHz to 893.80 MHz (GSM850) 1930.20 MHz to 1989.80 MHz (GSM1900)
Date of Receipt of Sample	2011-01-24

Related Submittal(s) / Grant(s)

Original submittal only.

4. Test Summary

4.1 Summary of tests

The applied standards to evaluate the compliance of requirements is 47CFR Part 15, Subpart B and the measurement procedures specified in ANSI C63.4 are performed.

Test Items	Applied Standards	Status
Emission		
Conducted Emission	FCC Part 15 Subpart B	C
Radiated Emission	FCC Part 15 Subpart B	C
Note 1: C=Conform NC=Not Conform NT=Not Tested NA=Not Applicable		

5. Test Set-up and operation mode

5.1 Principle of Configuration Selection

Emission : The equipment under test (EUT) was configured to measure its highest possible radiation level. The test modes were adapted accordingly in reference to the instructions for use.


5.2 Test Operation Mode

- PC link mode(The measurement was made of the maximized by: Write/Delete the “H” pattern mode; data exchange speed; moving the cable)

5.3 Support Equipment Used

Unit	Model No.	Serial No.	Manufacturer	CABLE			Backshell	FCC ID
				Connect type	Length (m)	shield		
NOTE PC	LGX14	F022040	LG	USB	1.0	Shield	Plastic	DOC
				DC POWER	1.6	Shield	Plastic	
				USB	1.4	Shield	Plastic	
MOUSE	OMS3CB	OMS3CBGGD RT	SAMSUNG ELECTRO-MECHANICS	USB	1.4	Shield	Plastic	DOC
ADAPTER	ADP-40PH	6T1094	DELTA ELECTRONICS,INC.	AC POWER	1.2	Shield	Plastic	-
EARMIC	A187	N/A	CRESYN	Stereo	1.2	Shield	Plastic	-
USB CABLE	8501	N/A	N/A	USB	1.4	Shield	Plastic	-

(Configuration of Tested System)



6. Test Results : Emission

6.1 Conducted Emission

RESULT : COMPLY

6.1.1 Measurement Procedure

In the range of 0.15MHz to 30MHz, the conducted emission was measured and set-up was made accordance with **ANSI C63.4:2003**.

If the EUT is table top equipment, it was placed on a wooden table with a height of 0.8m above the reference ground plane and 0.4m from the conducting wall of the shielded room.

Also if the EUT is floor-standing equipment, it was placed on a non-conducted support with a height up to 0.15m above the reference ground plane.

Connect the EUT's power source lines to the appropriate power mains / peripherals through the LISN. All the other peripherals are connected to the 2nd LISN, if any.

Unused measuring port of the LISN was resistively terminated by 50 ohm terminator.

The measuring port of the LISN for EUT was connected to spectrum analyzer.

Using TSJ conducted emission test software, the emissions were scanned from 150KHz to 30MHz with peak detector mode.

After scanning over the frequency range, suspected emissions were selected to perform final measurement. When performing final measurement, the receiver was used which has Quasi-Peak detector and Average detector.

By varying the configuration of the test sample and the cable routing it was attempted to maximize the emission.

For further description of the configuration refer to the picture of the test set-up.

6.1.2 List of Test and Measurement Instruments

Name of Instrument	Model No.	Serial No.	Manufacturer	Cal. Date	Next Cal. Date
EMI TEST RECEIVER	ESCI	100364	R&S	2010.05.12	2011.05.12
DC BLOCK	KFL-007	7-1581-5	Hyuplip	-	-
LISN	LISN1600	197204	TTI	2010.07.02	2011.07.02
LISN(EUT)	ESH2-Z5	828739/006	R&S	2010.10.01	2011.10.01
50 ohm Terminator	CT-01	N/A	TME	2011.01.10	2012.01.10

6.1.3 Limit for Conducted Emission

(1) Conducted Emission at mains ports of class A

Frequency range (MHz)	Limits dB(μ V)	
	Quasi-peak	Average
0.15 to 0.50	79	66
0.50 to 30	73	60
Note The lower limit shall apply at the transition frequencies.		

(2) Conducted Emission at mains ports of class B

Frequency range (MHz)	Limits dB(μ V)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56	56 to 46
0.50 to 5	56	46
5 to 30	60	50
Note 1 The lower limit shall apply at the transition frequencies.		
Note 2 The limit decreases linearly with the logarithm of the frequency in the range 0.15MHz to 0.5MHz.		

6.1.4 Test Result

Test date	January 27, 2011
Ambient Temperature	21 °C
Relative Humidity	36 % R.H.

Result : For the measurement data, see next page.

- Note) 1. Emission Level = Reading Value + Correction Factor.
 2. Correction Factor = Cable Loss + Insertion Loss of LISN
 3. Margin = Limit - Emission level
 4. Passed by 8.3 dB

Power Line Conducted Emissions			FCC PART 15b Class B		
Frequency (MHz)	Amplitude (dB μ V)	Conductor	Detector	Limit (dB μ V)	Margin (dB)
0.150	57.7	N	Quasi-Peak	66.0	8.3
0.186	54.3	N	Quasi-Peak	64.2	9.9



Test Result



Results of Conducted Emission

Digital EMC
Date : 2011/01/27

Model No.	: LG-T500	Reference No.	:	
Type	:	Power Supply	:	120V 60Hz
Serial No.	:	Temp/Humi.	:	21 °C 36 % R.H.
Test Condition	: DATA MODE	Operator	:	
Memo	: USB CABLE : KSD/SGDY0018501			
LIMIT	: CISPR22_B QP CISPR22_B AV			



Results of Conducted Emission

Digital EMC
Date : 2011/01/27

Model No. : LG-T500
Type :
Serial No. :
Test Condition : DATA MODE
Reference No. :
Power Supply : 120V 60Hz
Temp/Humi. : 21 °C 36 % R.H.
Operator :

Memo : USB CABLE : KSD/SGDY0018501

LIMIT : CISPR22_B QP
CISPR22_B AV

NO	FREQ [MHz]	READING		C.FACTOR [dB]	RESULT		LIMIT		MARGIN		PHASE
		QP [dBuV]	AV [dBuV]		QP [dBuV]	AV [dBuV]	QP [dBuV]	AV [dBuV]	QP [dBuV]	AV [dBuV]	
1	0.15039	57.6	26.9	0.1	57.7	27.0	66.0	56.0	8.3	29.0	N
2	0.18595	54.2	36.6	0.1	54.3	36.7	64.2	54.2	9.9	17.5	N
3	0.20350	50.8	22.1	0.1	50.9	22.2	63.5	53.5	12.6	31.3	N
4	0.51193	32.2	14.5	0.2	32.4	14.7	56.0	46.0	23.6	31.3	N
5	0.25769	45.9	21.3	0.1	46.0	21.4	61.5	51.5	15.5	30.1	L1
6	1.85250	37.3	27.4	0.3	37.6	27.7	56.0	46.0	18.4	18.3	L1
7	4.27800	21.5	14.6	0.4	21.9	15.0	56.0	46.0	34.1	31.0	L1
8	14.86700	27.5	21.5	0.8	28.3	22.3	60.0	50.0	31.7	27.7	L1
9	26.38450	22.6	16.2	1.1	23.7	17.3	60.0	50.0	36.3	32.7	L1
10	29.03100	24.5	18.3	1.3	25.8	19.6	60.0	50.0	34.2	30.4	L1

6.2 Radiated Emission

RESULT : COMPLY

6.2.1 Measurement Procedure

The radiated emission was measured and set-up was made accordance with **ANSI C63.4:2003**.

If the EUT is tabletop equipment, it was placed on a wooden table with a height of 0.8m above the reference ground plane and 3m away from the interference receiving antenna in the **10m semi-anechoic chamber**.

Also if the EUT is floor-standing equipment, it was placed on a non-conducted support with a height up to 0.15m above the reference ground plane.

Rotate the EUT from 0° to 360° and position the receiving antenna at heights from 1 to 4m above the reference ground plane continuously to determine associated with higher emission levels and record them.

The measurement was made in both the vertical and horizontal polarization, and the maximum value is presented in the report.

For below 1GHz frequency range, Quasi-Peak detector with 120kHz RBW was used.

Also Peak and Average detector with 1MHz RBW were used for above 1GHz frequency range.

For further description of the configuration refer to the picture of the test set-up.

6.2.2 List of Test and Measurement Instruments

Radiated Emission (10m Chamber)					
Name of Instrument	Model No.	Serial No.	Manufacturer	Cal. Date	Next Cal. Date
EMI Test Receiver	ESU	100014	R&S	2011.01.20	2012.01.20
Bilog Antenna	CBL6112B	2737	SCHAFFNER	2010.07.14	2011.07.14
Horn Antenna	BBHA9120A	322	SCHWARZBECK	2010.04.13	2011.04.13
Amplifier(22dB)	8447E	2945A02865	H/P	2011.01.11	2012.01.11
Low Noise Preamplifier	MLA-00108-B02-36	1518831	TSJ	2011.01.11	2012.01.11
Controller	5905A	N/A	TOKIN	-	-
ANT.master	N/A	N/A	TOKIN	-	-

6.2.3 Limit of Radiated Emission

- The test frequency range of Radiated Emission measurements are listed below.

Highest frequency generated or used in the device or on which the device operates or tunes (MHz)	Upper frequency of measurement range (MHz)
Below 108	1000
108 – 500	2000
500 – 1000	5000
Above 1000	5 th harmonic of the highest frequency or 40GHz, whichever is lower

(1) Limit for Radiated Emission below 1000MHz

Frequency range (MHz)	Class A Equipment (10m distance)	Class B Equipment (3m distance)
	Quasi-peak limits (dB μ V/m)	Quasi-peak limits (dB μ V/m)
30 to 88	39.1	40
88 to 216	43.5	43.5
216 to 960	46.4	46
960 to 1000	49.5	54
Note 1 The lower limit shall apply at the transition frequency. Note 2 Additional provisions may be required for cases where interference occurs. Note 3 According to 15.109(g), as an alternative to the radiated emission limit shown above, digital devices may be shown to comply with the standards(CISPR), Pub. 22 shown as below.		
30 to 230	40	30
230 to 1000	47	37

(2) Limits for Radiated Emission in the frequency range 1000 - 2000MHz at a measuring distance of 10m

Frequency (GHz)	Class A Equipment		Class B Equipment	
	peak (dB μ V/m)	peak (dB μ V/m)	peak (dB μ V/m)	Average (dB μ V/m)
1 to 2	69.5	49.5	63.5	43.5

(3) Limits for Radiated Emission above 1000MHz at a measuring distance of 3m

Frequency (GHz)	Class A Equipment		Class B Equipment	
	peak (dB μ V/m)	peak (dB μ V/m)	peak (dB μ V/m)	Average (dB μ V/m)
1 to 40	80	60	74	54

6.2.4 Test Result

Test date	February 7, 2011
Ambient Temperature	20 °C
Relative Humidity	34 % R.H.

Result : For the measurement data, see next page

Note) 1. Emission Level = Reading Value + Correction Factor.

2. Correction Factor = Cable loss - Amp gain + Antenna Factor

3. Margin = Limit - Emission level

Frequency [MHz]	Pol.	Reading [dB μ V]	C.F. [dB(1/m)]	Result [dB(μ V/m)]	Limit [dB(μ V/m)]	Margin [dB]
756.638	H	37.80	-0.7	37.10	46.00	8.90

Radiated emission Test Data

Test Result**- 30MHz-1GHz****RADIATED EMISSION**


Date : 2011-02-07

Model Name : LG-T500
Model No. :
Serial No. :
Test Condition :

Reference No. :
Power Supply : 120V 60Hz
Temp/Humi : 20°C 34 % R. H.
Operator :

Memo : USB CABLE : KSD/SGDY0018501

LIMIT : FCC Part15 Subpart.B Class B (3m)
MARGIN: 3 dB



RADIATED EMISSION

Date : 2011-02-07

Model Name	:	LG-T500	Reference No.	:	
Model No.	:		Power Supply	:	120V 60Hz
Serial No.	:		Temp/Humi	:	20°C 34 % R. H.
Test Condition	:		Operator	:	

Memo : USB CABLE : KSD/SGDY0018501

LIMIT : FCC Part15 Subpart B Class B (3m)
MARGIN: 3 dB

No.	FREQ	READING	ANT	LOSS	GAIN	RESULT	LIMIT	MARGIN	ANTENNA	TABLE
	[MHz]	QP [dBuV]	FACTOR [dB]	[dB]	[dB]	[dBuV/m]	[dBuV/m]	[dB]	[cm]	[DEG]
----- Horizontal -----										
1	331.979	34.5	14.5	2.1	24.0	27.1	46.0	18.9	100	108
2	756.638	37.8	19.7	3.4	23.8	37.1	46.0	8.9	185	1
----- Vertical -----										
3	40.057	33.8	13.9	0.8	22.6	25.9	40.0	14.1	338	154
4	97.418	35.6	10.3	1.2	22.7	24.4	43.5	19.1	100	200
5	159.464	37.9	10.2	1.4	23.1	26.4	43.5	17.1	100	217

- 1GHz - 2.5GHz_PEAK




RADIATED EMISSION

Date : 2011-02-07

Model Name	: LG-T500	Reference No.	:	
Model No.	:	Power Supply	:	120V 60Hz
Serial No.	:	Temp/Humi	:	20°C 34 % R. H.
Test Condition	:	Operator	:	

Memo : USB CABLE : KSD/SGDY0018501

LIMIT : FCC Part15 Subpart.B Class B (3m) - 18G(Peak)
FCC Part15 Subpart.B Class B (3m) - 18G(Avg)



RADIATED EMISSION

Date : 2011-02-07

Model Name	:	LG-T500	Reference No.	:	
Model No.	:		Power Supply	:	120V 60Hz
Serial No.	:		Temp/Humi	:	20°C 34 % R. H.
Test Condition	:		Operator	:	

Memo : USB CABLE : KSD/SGDY0018501

LIMIT : FCC Part15 Subpart B Class B (3m) - 18G(Peak)
FCC Part15 Subpart B Class B (3m) - 18G(Avg)

No.	FREQ [MHz]	READING PEAK [dBuV]	ANT FACTOR [dB]	LOSS [dB]	GAIN [dB]	RESULT [dBuV/m]	LIMIT [dBuV/m]	MARGIN [dB]	ANTENNA [cm]	TABLE [DEG]
----- Horizontal -----										
1	1007.212	57.4	23.6	4.8	41.8	44.0	74.0	30	100	148
2	1656.240	59.6	25.2	6.3	41.9	49.2	74.0	24.8	100	1
3	1665.856	59.7	25.2	6.3	41.9	49.3	74.0	24.7	100	1
4	1673.067	56.9	25.2	6.3	41.9	46.5	74.0	27.5	100	109
5	1990.370	56.7	25.2	7.0	42.0	46.9	74.0	27.1	100	146
----- Vertical -----										
6	1329.322	59.8	24.6	5.6	41.9	48.1	74.0	25.9	100	91
7	1569.703	60.4	25.1	6.1	41.9	49.7	74.0	24.3	100	358
8	1591.338	61.2	25.2	6.1	41.9	50.6	74.0	23.4	100	309
9	1596.145	61.3	25.2	6.2	41.9	50.8	74.0	23.2	100	358
10	1615.376	62.8	25.2	6.2	41.9	52.3	74.0	21.7	100	358
11	1665.856	65.4	25.2	6.3	41.9	55.0	74.0	19	100	296
12	1677.875	60.1	25.2	6.3	41.9	49.7	74.0	24.3	100	287
13	1697.105	59.5	25.2	6.4	41.9	49.2	74.0	24.8	100	132
14	1725.951	60.6	25.2	6.4	41.9	50.3	74.0	23.7	100	116
15	1757.200	58.0	25.2	6.5	42.0	47.7	74.0	26.3	100	358
16	1769.219	56.3	25.2	6.5	42.0	46.0	74.0	28	100	128
17	1805.276	57.0	25.2	6.6	42.0	46.8	74.0	27.2	100	358
18	1995.177	65.5	25.2	7.0	42.0	55.7	74.0	18.3	100	280

- 1GHz - 2.5GHz_AV





RADIATED EMISSION

Date : 2011-02-07

Model Name	: LG-T500	Reference No.	:	
Model No.	:	Power Supply	:	120V 60Hz
Serial No.	:	Temp/Humi	:	20°C 34 % R. H.
Test Condition	:	Operator	:	

Memo : USB CABLE : KSD/SGDY0018501

LIMIT : FCC Part15 Subpart.B Class B (3m) - 18G(Avg)
FCC Part15 Subpart.B Class B (3m) - 18G(Peak)



RADIATED EMISSION

Date : 2011-02-07

Model Name	:	LG-T500	Reference No.	:	
Model No.	:		Power Supply	:	120V 60Hz
Serial No.	:		Temp/Humi	:	20°C 34 % R. H.
Test Condition	:		Operator	:	

Memo : USB CABLE : KSD/SGDY0018501

LIMIT : FCC Part15 Subpart B Class B (3m) - 18G(Avg)
FCC Part15 Subpart B Class B (3m) - 18G(Peak)

No.	FREQ	READING	ANT	LOSS	GAIN	RESULT	LIMIT	MARGIN	ANTENNA	TABLE
	[MHz]	AV	FACTOR							
		[dBuV]	[dB]	[dB]	[dB]	[dBuV/m]	[dBuV/m]	[dB]	[cm]	[DEG]
----- Horizontal -----										
1	1008.639	35.1	23.6	4.8	41.8	21.7	54.0	32.3	100	252
----- Vertical -----										
2	1331.228	36.8	24.6	5.6	41.9	25.1	54.0	28.9	100	105
3	1663.428	38.9	25.2	6.3	41.9	28.5	54.0	25.5	100	131
4	1991.538	37.5	25.2	7.0	42.0	27.7	54.0	26.3	100	200