



HCT CO.,LTD. 74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, 17383, Rep. of KOREA
TEL: +82-31-645-6300 FAX: +82-31-645-6401

FCC MPE REPORT

Certification

Applicant Name:
LG Electronics Inc.

Address:
222, LG-ro, Jinwi-myeon, Pyeongtaek-si,
451-713 Gyeonggi-do, South Korea

Date of Issue:

December 07, 2016

Test Site/Location:

HCT CO., LTD., 74, Seoicheon-ro 578beon-gil,
Majang-myeon, Icheon-si, Gyeonggi-do, 17383,
Rep. of KOREA

Report No.: HCT-R-1612-E001

HCT FRN: 0005866421

FCC ID: BEJTL3TNBN

APPLICANT: LG Electronics Inc.

Model(s): TL3TNB-N

EUT Type: Car Telematics Device

The measurements shown in this report were made in accordance with the procedures specified in §2.947. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them.

HCT CO., LTD. Certifies that no party to this application has subject to a denial of Federal benefits that includes FCC benefits pursuant to section 5301 of the Anti-Drug Abuse Act of 1998, 21 U.S.C. 853(a)

Report prepared by
: Seoul Ki Lee
Test engineer of RF Team

Approved by
: Jong Seok Lee
Manager of RF Team

This report only responds to the tested sample and may not be reproduced, except in full, without written approval of the HCT Co., Ltd.

Version

TEST REPORT NO.	DATE	DESCRIPTION
HCT-R-1612-E001	December 07, 2016	- First Approval Report

RF Exposure Statement

1. LIMITS

According to §1.1310 and §2.1091 RF exposure is calculated.

(B) Limits for General Population/Uncontrolled Exposures

Frequency range (MHz)	Electric field Strength (V/m)	Magnetic field Strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
0.3 - 1.34.....	614	1.63	*(100)	30
1.34 - 30.....	824/f	2.19/f	*(180/ f ²)	30
30 - 300.....	27.5	0.073	0.2	30
300 - 1500.....			f/1500	30
1500 - 100.000.....			1.0	30

F = frequency in MHz

* = Plane-wave equivalent power density

2. MAXIMUM PERMISSIBLE EXPOSURE Prediction

Prediction of MPE limit at a given distance

$$S = PG/4\pi R^2$$

S = Power density

P = power input to antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

3.RESULTS

3-1. GSM 850 BAND

Average Peak output Power at antenna input terminal	33.500	dBm
Average Peak output Power at antenna input terminal	2238.721	mW
Prediction distance	20.000	cm
Prediction frequency	824.200	MHz
Antenna Gain(typical)	-3.250	dBi
Antenna Gain(numeric)	0.473	-
Power density at prediction frequency(S)	0.211	mW/cm ²
MPE limit for uncontrolled exposure at prediction frequency	0.549	mW/cm ²

3-2. GSM 1900 BAND

Average Peak output Power at antenna input terminal	30.500	dBm
Average Peak output Power at antenna input terminal	1122.018	mW
Prediction distance	20.000	cm
Prediction frequency	1850.200	MHz
Antenna Gain(typical)	1.260	dBi
Antenna Gain(numeric)	1.337	-
Power density at prediction frequency(S)	0.298	mW/cm ²
MPE limit for uncontrolled exposure at prediction frequency	1.000	mW/cm ²

3-3. WCDMA 850 BAND

Average Peak output Power at antenna input terminal	24.200	dBm
Average Peak output Power at antenna input terminal	263.027	mW
Prediction distance	20.000	cm
Prediction frequency	826.400	MHz
Antenna Gain(typical)	-3.250	dBi
Antenna Gain(numeric)	0.473	-
Power density at prediction frequency(S)	0.025	mW/cm ²
MPE limit for uncontrolled exposure at prediction frequency	0.551	mW/cm ²

3-4. WCDMA 1900 BAND

Average Peak output Power at antenna input terminal	24.200	dBm
Average Peak output Power at antenna input terminal	263.027	mW
Prediction distance	20.000	cm
Prediction frequency	1852.400	MHz
Antenna Gain(typical)	1.260	dBi
Antenna Gain(numeric)	1.337	-
Power density at prediction frequency(S)	0.070	mW/cm ²
MPE limit for uncontrolled exposure at prediction frequency	1.000	mW/cm ²

3-5. WCDMA 1700 BAND

Average Peak output Power at antenna input terminal	24.200	dBm
Average Peak output Power at antenna input terminal	263.027	mW
Prediction distance	20.000	cm
Prediction frequency	1712.400	MHz
Antenna Gain(typical)	-0.130	dBi
Antenna Gain(numeric)	0.971	-
Power density at prediction frequency(S)	0.051	mW/cm ²
MPE limit for uncontrolled exposure at prediction frequency	1.000	mW/cm ²

3-6. LTE BAND 2

Average Peak output Power at antenna input terminal	26.200	dBm
Average Peak output Power at antenna input terminal	416.869	mW
Prediction distance	20.000	cm
Prediction frequency	1850.700	MHz
Antenna Gain(typical)	1.260	dBi
Antenna Gain(numeric)	1.337	-
Power density at prediction frequency(S)	0.111	mW/cm ²
MPE limit for uncontrolled exposure at prediction frequency	1.000	mW/cm ²

3-7. LTE BAND 5

Average Peak output Power at antenna input terminal	26.200	dBm
Average Peak output Power at antenna input terminal	416.869	mW
Prediction distance	20.000	cm
Prediction frequency	824.700	MHz
Antenna Gain(typical)	-3.250	dBi
Antenna Gain(numeric)	0.473	-
Power density at prediction frequency(S)	0.039	mW/cm ²
MPE limit for uncontrolled exposure at prediction frequency	0.550	mW/cm ²

3-8. LTE BAND 4

Average Peak output Power at antenna input terminal	26.200	dBm
Average Peak output Power at antenna input terminal	416.869	mW
Prediction distance	20.000	cm
Prediction frequency	1710.700	MHz
Antenna Gain(typical)	-0.130	dBi
Antenna Gain(numeric)	0.971	-
Power density at prediction frequency(S)	0.080	mW/cm ²
MPE limit for uncontrolled exposure at prediction frequency	1.000	mW/cm ²

3-9. LTE BAND 17

Average Peak output Power at antenna input terminal	26.200	dBm
Average Peak output Power at antenna input terminal	416.869	mW
Prediction distance	20.000	cm
Prediction frequency	706.500	MHz
Antenna Gain(typical)	-3.030	dBi
Antenna Gain(numeric)	0.498	-
Power density at prediction frequency(S)	0.041	mW/cm ²
MPE limit for uncontrolled exposure at prediction frequency	0.471	mW/cm ²

3-10. LTE BAND 7

Average Peak output Power at antenna input terminal	26.200	dBm
Average Peak output Power at antenna input terminal	416.869	mW
Prediction distance	20.000	cm
Prediction frequency	2502.500	MHz
Antenna Gain(typical)	-0.220	dBi
Antenna Gain(numeric)	0.951	-
Power density at prediction frequency(S)	0.079	mW/cm ²
MPE limit for uncontrolled exposure at prediction frequency	1.000	mW/cm ²

3-11. BT LE

Max Peak output Power at antenna input terminal	0.000	dBm
Max Peak output Power at antenna input terminal	1.000	mW
Prediction distance	20.000	cm
Prediction frequency	2402.000	MHz
Antenna Gain(typical)	4.030	dBi
Antenna Gain(numeric)	2.529	-
Power density at prediction frequency(S)	0.001	mW/cm ²
MPE limit for uncontrolled exposure at prediction frequency	1.000	mW/cm ²

1. The power density level at 20 cm is **0.298 mW/cm²**, which is below the uncontrolled exposure limit of **1.0 mW/cm² at GSM 1900**
2. The power density level at 20 cm is **0.001 mW/cm²**, which is below the uncontrolled exposure limit of **1.0 mW/cm² at BT LE**

->Simultaneous MPE 20cm is $(0.298 / 1.0) + (0.001 / 1.0) < 1$

* The Worst case GSM 1900: 30.5 dBm , BT LE: 0 dBm is Highest Power