

# FCC SAR TEST REPORT

**Test File No : F690501-RF-SAR000264-A1**

|                             |                                                  |
|-----------------------------|--------------------------------------------------|
| <b>Equipment Under Test</b> | Car Telematics Modem                             |
| <b>Model Name</b>           | TM04ANNABM2                                      |
| <b>Applicant</b>            | LG Electronics Inc.                              |
| <b>Address of Applicant</b> | 10, Magokjungang 10-ro, Gangseo-gu, Seoul, Korea |
| <b>FCC ID</b>               | BEJTM04ANNABM2                                   |
| <b>Exposure Category</b>    | General Population/Uncontrolled Exposure         |
| <b>Standards</b>            | FCC 47 CFR Part 2 (2.1093)<br>IEEE 1528, 2013    |
| <b>Receipt No.</b>          | GPRI2204000278SR                                 |
| <b>Date of Receipt</b>      | 2022-04-25                                       |
| <b>Date of Test(s)</b>      | 2022-06-11 ~2022-08-11                           |
| <b>Date of Issue</b>        | 2022-09-01                                       |
| <b>Test Result</b>          | Refer to the Page 6                              |

In the configuration tested, the EUT complied with the standards specified above.

This test report does not assure KOLAS accreditation.

## Remarks:

- 1) The results of this test report are effective only to the items tested.
- 2) The SGS Korea is not responsible for the sampling, the results of this test report apply to the sample as received.



**Report prepared by /**  
**Jongho Park**  
**Test Engineer**



**Approved by /**  
**Matthew Park**  
**Technical Manager**

Report File No : F690501-RF-SAR000264-A1

Date of Issue : 2022-09-01

(All SGS services are rendered in accordance with the applicable SGS conditions of service available on request and accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx>.)

**Revision history**

| Revision | Date of issue      | Revisions                                                | Revised By  |
|----------|--------------------|----------------------------------------------------------|-------------|
| -        | August 19, 2022    | Initial issue                                            | -           |
| A1       | September 01, 2022 | Revision Update<br>- Added statement for TDD Duty Factor | Jongho Park |

### Contents

|                 |                                                           |    |
|-----------------|-----------------------------------------------------------|----|
| 1               | Testing Laboratory                                        | 5  |
| 2               | Details of Manufacturer                                   | 5  |
| 3               | Description of EUT(s)                                     | 5  |
| 4               | The Highest Reported SAR Values                           | 6  |
| 5               | Test Methodology                                          | 7  |
| 6               | Test Environment                                          | 7  |
| 7               | Specific Absorption Rate (SAR)                            | 8  |
| 7.1             | Introduction                                              | 8  |
| 7.2             | SAR Definition                                            | 8  |
| 7.3             | Test Standards and Limits                                 | 8  |
| 8               | The SAR Measurement System                                | 10 |
| 9               | System Components                                         | 11 |
| 9.1             | Probe                                                     | 11 |
| 9.2             | SAM Phantom                                               | 11 |
| 9.3             | Device Holder                                             | 12 |
| 10              | SAR Measurement Procedures                                | 13 |
| 10.1            | Normal SAR Measurement Procedure                          | 13 |
| 11              | Definition of Reference                                   | 14 |
| 11.1            | Other Consumer Devices                                    | 15 |
| 12              | SAR System Verification                                   | 16 |
| 13              | Tissue Simulant Fluid for the Frequency Band              | 18 |
| 14              | Justification for Extended SAR Dipole Calibration         | 21 |
| 15              | Instruments List                                          | 23 |
| 16              | FCC Power Measurement Procedures                          | 24 |
| 17              | Measured and Reported SAR                                 | 24 |
| 18              | Maximum Output Power Specifications                       | 25 |
| 19              | RF Conducted Power Measurement                            | 26 |
| 19.1            | GSM                                                       | 26 |
| 19.2            | WCDMA                                                     | 26 |
| 19.2.1          | Output Power Verification                                 | 26 |
| 19.2.2          | Body SAR Measurements                                     | 26 |
| 19.2.3          | Procedures Used to Establish RF Signal for SAR HSDPA Data | 26 |
| 19.2.4          | SAR Measurements for Conditions for HSUPA Data Devices    | 27 |
| 19.3            | LTE                                                       | 28 |
| 19.3.1          | SAR measurement Conditions for LTE                        | 28 |
| 19.3.2          | Spectrum Plots for RB Configurations                      | 28 |
| 19.3.3          | MPR                                                       | 28 |
| 19.3.4          | A-MPR                                                     | 28 |
| 19.3.5          | Required RB Size and RB Offsets for SAR Testing           | 28 |
| 20              | DUT Antenna Locations                                     | 56 |
| 21              | SAR Test Exclusion Applied                                | 57 |
| 22              | SAR Data Summary                                          | 58 |
| 22.1            | SAR data                                                  | 58 |
| 23              | SAR Measurement Variability                               | 66 |
| 23.1            | Measurement Variability                                   | 66 |
| 23.2            | Measurement Uncertainty                                   | 66 |
| Appendixes List |                                                           | 67 |
| Appendixes A.1  | Verification Test Plots for 750MHz                        | 68 |
| Appendixes A.2  | Verification Test Plots for 835MHz                        | 72 |
| Appendixes A.3  | Verification Test Plots for 1800MHz                       | 77 |
| Appendixes A.4  | Verification Test Plots for 1900MHz                       | 80 |
| Appendixes A.5  | Verification Test Plots for 2600MHz                       | 84 |
| Appendixes A.6  | SAR Test Plot for GSM850                                  | 88 |

|                 |                                     |     |
|-----------------|-------------------------------------|-----|
| Appendixes A.7  | SAR Test Plot for GSM1900_____      | 89  |
| Appendixes A.8  | SAR Test Plots for WCDMA II_____    | 90  |
| Appendixes A.9  | SAR Test Plots for WCDMA IV_____    | 91  |
| Appendixes A.10 | SAR Test Plots for WCDMA V_____     | 92  |
| Appendixes A.11 | SAR Test Plots for LTE Band 5_____  | 93  |
| Appendixes A.12 | SAR Test Plots for LTE Band 7_____  | 94  |
| Appendixes A.13 | SAR Test Plots for LTE Band 12_____ | 95  |
| Appendixes A.14 | SAR Test Plots for LTE Band 13_____ | 96  |
| Appendixes A.15 | SAR Test Plots for LTE Band 25_____ | 97  |
| Appendixes A.16 | SAR Test Plots for LTE Band 41_____ | 98  |
| Appendixes A.17 | SAR Test Plots for LTE Band 66_____ | 99  |
| Appendixes A.18 | SAR Test Plots for LTE Band 71_____ | 100 |
| Appendixes B.1  | Uncertainty Analysis_____           | 101 |
| -THE END-       | _____                               | 101 |

## 1 Testing Laboratory

|                     |                                                                      |
|---------------------|----------------------------------------------------------------------|
| <b>Company Name</b> | SGS Korea Co., Ltd. (Gunpo Laboratory)                               |
| <b>Address</b>      | 4, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, 15807 Republic of Korea |
| <b>Telephone</b>    | +82 +31 428 5700                                                     |
| <b>FAX</b>          | +82 +31 427 2371                                                     |

## 2 Details of Manufacturer

|                  |                                                              |
|------------------|--------------------------------------------------------------|
| <b>Applicant</b> | LG Electronics Inc.                                          |
| <b>Address</b>   | 10, Magokjungang 10-ro, Gangseo-gu, Seoul, Korea             |
| <b>Email</b>     | <a href="mailto:seungho.hur@lge.com">seungho.hur@lge.com</a> |
| <b>Phone No.</b> | 010-2468-2972                                                |

## 3 Description of EUT(s)

|                           |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
|---------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>EUT Type</b>           | Car Telematics Modem                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| <b>Model Name</b>         | TM04ANNABM2                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| <b>Serial Number</b>      | N-128                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| <b>Mode of Operation</b>  | GSM850 / GSM1900 / WCDMA II / WCDMA IV / WCDMA V / LTE Band 2 / LTE Band 4 / LTE Band 5 / LTE Band 7 / LTE Band 12 / LTE Band 13 / LTE Band 17 / LTE Band 25 / LTE Band 41 / LTE Band 66 / LTE Band 71                                                                                                                                                                                                                                                                                                                                                                |
| <b>Tx Frequency Range</b> | GSM850 : 824.0 ~ 849.0 MHz<br>GSM1900 : 1850.0 ~ 1910.0 MHz<br>WCDMA II : 1850.0 ~ 1910 MHz<br>WCDMA IV : 1710.0 ~ 1755.0 MHz<br>WCDMA V : 824.0 ~ 849.0 MHz<br>LTE Band 2 : 1850.0 ~ 1910.0 MHz<br>LTE Band 4 : 1710.0 ~ 1755.0 MHz<br>LTE Band 5 : 824.0 ~ 849.0 MHz<br>LTE Band 7 : 2500.0 ~ 2570.0 MHz<br>LTE Band 12 : 699.0 ~ 716.0 MHz<br>LTE Band 13 : 777.0 ~ 787.0 MHz<br>LTE Band 17 : 704.0 ~ 716.0 MHz<br>LTE Band 25 : 1850.0 ~ 1915.0 MHz<br>LTE Band 41 : 2496.0 ~ 2690.0 MHz<br>LTE Band 66 : 1710.0 ~ 1780.0 MHz<br>LTE Band 71 : 663.0 ~ 698.0 MHz |

#### 4. The Highest Reported SAR Values

| Equipment Class | Band        | Highest Reported SAR<br>1g (W/kg) |
|-----------------|-------------|-----------------------------------|
| PCE             | GSM850      | 0.022                             |
| PCE             | GSM1900     | 0.211                             |
| PCE             | WCDMA II    | <b>0.427</b>                      |
| PCE             | WCDMA IV    | 0.414                             |
| PCE             | WCDMA V     | 0.022                             |
| PCE             | LTE Band 2  | N/A                               |
| PCE             | LTE Band 4  | N/A                               |
| PCE             | LTE Band 5  | 0.017                             |
| PCE             | LTE Band 7  | 0.257                             |
| PCE             | LTE Band 12 | 0.083                             |
| PCE             | LTE Band 13 | 0.057                             |
| PCE             | LTE Band 17 | N/A                               |
| PCE             | LTE Band 25 | 0.361                             |
| PCE             | LTE Band 41 | 0.063                             |
| PCE             | LTE Band 66 | 0.354                             |
| PCE             | LTE Band 71 | 0.074                             |

## 5 Test Methodology

ANSI/IEEE C95.1-1999: IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz. It specifies the maximum exposure limit of 1.6 W/kg as averaged over any 1 gram of tissue for portable devices being used within 20 cm of the user in the uncontrolled environment.

Test tests documented in this report were performed in accordance with IEEE Standard 1528-2013 and the following published KDB procedures.

In additions;

|                                     |                             |                                                                                                    |
|-------------------------------------|-----------------------------|----------------------------------------------------------------------------------------------------|
| <input checked="" type="checkbox"/> | <b>KDB 865664 D01v01r04</b> | <b>SAR Measurement Requirements for 100 MHz to 6 GHz</b>                                           |
| <input checked="" type="checkbox"/> | <b>KDB 865664 D02v01r02</b> | <b>RF Exposure Compliance Reporting and Documentation Considerations</b>                           |
| <input checked="" type="checkbox"/> | <b>KDB 447498 D01v06</b>    | <b>Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies</b>     |
| <input type="checkbox"/>            | KDB 447498 D02v02r01        | SAR Measurement Procedures for USB Dongle Transmitters                                             |
| <input type="checkbox"/>            | KDB 248227 D01v02r02        | SAR Guidance For IEEE 802.11 (Wi-Fi) Transmitters                                                  |
| <input type="checkbox"/>            | KDB 615223 D01v01r01        | 802.16e/WiMax SAR Measurement Guidance                                                             |
| <input type="checkbox"/>            | KDB 616217 D04v01r02        | SAR Evaluation Considerations for Laptop, Notebook, Netbook and Tablet Computers                   |
| <input type="checkbox"/>            | KDB 643646 D01v01r03        | SAR Test Considerations for Occupational PTT Radios                                                |
| <input type="checkbox"/>            | KDB 648474 D03v01r04        | Evaluation and Approval Considerations for Handsets with Specific Wireless Charging Battery Covers |
| <input type="checkbox"/>            | KDB 648474 D04v01r03        | SAR Evaluation Considerations for Wireless Handsets                                                |
| <input type="checkbox"/>            | KDB 680106 D01v03r01        | RF Exposure Considerations for Low Power Consumer Wireless Power Transfer Applications             |
| <input checked="" type="checkbox"/> | <b>KDB 941225 D01v03r01</b> | <b>3G SAR Measurement Procedures</b>                                                               |
| <input checked="" type="checkbox"/> | <b>KDB 941225 D05v02r05</b> | <b>SAR Evaluation Considerations for LTE Devices</b>                                               |
| <input type="checkbox"/>            | KDB 941225 D06v02r01        | SAR Evaluation Procedures for Portable Devices with Wireless Router Capabilities                   |
| <input type="checkbox"/>            | KDB 941225 D07v01r02        | SAR Evaluation Procedures for UMPC Mini-Tablet Devices                                             |

## 6 Testing Environment

|                                       |                |
|---------------------------------------|----------------|
| Ambient temperature                   | : 18°C ~ 25°C  |
| Relative humidity                     | : 30% ~ 70%    |
| Liquid temperature of during the test | : <± 2°C       |
| Ambient noise & Reflection            | : < 0.012 W/kg |

## 7 Specific Absorption Rate (SAR)

### 7.1 Introduction

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled

### 7.2 SAR Definition

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density ( $\rho$ ). The equation description is as below:

$$\text{SAR} = \frac{d}{dt} \left( \frac{dW}{dm} \right) = \frac{d}{dt} \left( \frac{dW}{\rho dv} \right)$$

SAR is expressed in units of Watts per kilogram (W/kg)

SAR measurement can be either related to the temperature elevation in tissue by

$$\text{SAR} = C \left( \frac{\delta T}{\delta t} \right)$$

Where: C is the specific heat capacity,  $\delta T$  is the temperature rise and  $\delta t$  is the exposure duration, or related to the electrical field in the tissue by

$$\text{SAR} = \frac{\sigma |E|^2}{\rho}$$

Where:  $\sigma$  is the conductivity of the tissue,  $\rho$  is the mass density of the tissue and E is the RMS electrical field strength.

However for evaluating SAR of low power transmitter, electrical field measurement is typically applied.

### 7.3 Test Standards and Limits

According to FCC 47CFR §2.1093(d) The limits to be used for evaluation are based generally on criteria published by the American National Standards Institute (ANSI) for localized specific absorption rate ("SAR") in Section 4.2 of "IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz," ANSI/IEEE C95.3-2003, Copyright 2003 by the Institute of Electrical and Electronics Engineers, Inc., New York, New York 10017. These criteria for SAR evaluation are similar to those recommended by the National Council on Radiation Protection and Measurements (NCRP) in "Biological Effects and Exposure Criteria for Radio frequency Electromagnetic Fields," NCRP Report No. 86, Section 17.4.5. Copyright NCRP, 1986, Bethesda, Maryland 20814. SAR is a measure of the rate of energy absorption due to exposure to an RF transmitting

source. SAR values have been related to threshold levels for potential biological hazards. The criteria to be used are specified in paragraphs (d)(1) and (d)(2) of this section and shall apply for portable devices transmitting in the frequency range from 100 kHz to 6 GHz. Portable devices that transmit at frequencies above 6 GHz are to be evaluated in terms of the MPE limits specified in § 1.1310 of this chapter. Measurements and calculations to demonstrate compliance with MPE field strength or power density limits for devices operating above 6 GHz should be made at a minimum distance of 5 cm from the radiating source.

(1) Limits for Occupational/Controlled exposure: 0.4 W/kg as averaged over the whole-body and spatial peak SAR not exceeding 8 W/kg as averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube). Exceptions are the hands, wrists, feet and ankles where the spatial peak SAR shall not exceed 20 W/kg, as averaged over an 10 grams of tissue (defined as a tissue volume in the shape of a cube). Occupational/Controlled limits apply when persons are exposed as a consequence of their employment provided these persons are fully aware of and exercise control over their exposure. Awareness of exposure can be accomplished by use of warning labels or by specific training or education through appropriate means, such as an RF safety program in a work environment.

(2) Limits for General Population/Uncontrolled exposure: 0.08 W/kg as averaged over the whole-body and spatial peak SAR not exceeding 1.6 W/kg as averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube). Exceptions are the hands, wrists, feet and ankles where the spatial peak SAR shall not exceed 4 W/kg, as averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube). General Population/Uncontrolled limits apply when the general public may be exposed, or when persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or do not exercise control over their exposure. Warning labels placed on consumer devices such as cellular telephones will not be sufficient reason to allow these devices to be evaluated subject to limits for occupational/controlled exposure in paragraph (d)(1) of this section.

| Human Exposure                                      | Uncontrolled Environment<br>General Population | Controlled Environment<br>Occupational |
|-----------------------------------------------------|------------------------------------------------|----------------------------------------|
| <b>Partial Peak SAR</b><br>(Partial)                | 1.60 mW/g                                      | 8.00 mW/g                              |
| <b>Partial Average SAR</b><br>(Whole Body)          | 0.08 mW/g                                      | 0.40 mW/g                              |
| <b>Partial Peak SAR</b><br>(Hands/Feet/Ankle/Wrist) | 4.00 mW/g                                      | 20.00 mW/g                             |

1. The spatial Peak value of the SAR averaged over any 1g gram of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.
2. The spatial Average value of the SAR averaged over the whole body.
3. The Spatial Peak value of the SAR averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.

## 8 The SAR Measurement System

A block diagram of the SAR measurement System is given in Fig. 1. This SAR Measurement System uses a Computer-controlled 3-D stepper motor system (SPEAG DASY system). The model EX3DV4 field probe is used to determine the internal electric fields. The SAR can be obtained from the equation  $SAR = \sigma (|E_i|^2) / \rho$  where  $\sigma$  and  $\rho$  are the conductivity and mass density of the tissue-simulant.

The DASY system for performing compliance tests consists of the following items:

- A standard high precision 6-axis robot (Staubli TX family) with controller, teach pendant and software. An arm extension is for accommodating the data acquisition electronics (DAE).
- A dosimeter probe, i.e., an isotropic E-field probe optimized and calibrated for usage in tissue simulating liquid. The probe is equipped with an optical surface detector system.
- Data acquisition electronics (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.




Fig a. The microwave circuit arrangement used for SAR system verification

- The Electro-optical converter (EOC) performs the conversion between optical and electrical of the signals for the digital communication to the DAE and for the analog signal from the optical surface detection. The EOC is connected to the measurement server.
- The function of the measurement server is to perform the time critical tasks such as signal filtering, control of the robot operation and fast movement interrupts.
- A probe alignment unit which improves the (absolute) accuracy of the probe positioning.
- A computer operating Windows.
- DASY software.
- Remote control with teach pendant and additional circuitry for robot safety such as warning lamps, etc.
- The SAM twin phantom enabling testing left-hand and right-hand usage.
- The device holder for handheld mobile phones.
- Tissue simulating liquid mixed according to the given recipes.
- Verification dipole kits allowing to validate the proper functioning of the system.

## 9 System Components

### 9.1 Probe

|                      |                                                                                                                                                                                                             |
|----------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Construction</b>  | : Symmetrical design with triangular core.<br>Built-in shielding against static charges.<br>PEEK enclosure material (resistant to organic solvents, e.g., DGBE)                                             |
| <b>Calibration</b>   | : Basic Broad Band Calibration in air Conversion Factors (CF) for HSL 835 and HSL1900.<br>Additional CF-Calibration for other liquids and frequencies upon request.                                         |
| <b>Frequency</b>     | : 10 MHz to 6 GHz; Linearity: $\pm 0.2$ dB (30 MHz to 6 GHz)                                                                                                                                                |
| <b>Directivity</b>   | : $\pm 0.3$ dB in HSL (rotation around probe axis)<br>$\pm 0.5$ dB in tissue material (rotation normal to probe axis)                                                                                       |
| <b>Dynamic Range</b> | : $10\mu\text{W/g}$ to $> 100$ mW/g;<br>Linearity: $\pm 0.2$ dB(noise: typically $< 1\mu\text{W/g}$ )                                                                                                       |
| <b>Dimensions</b>    | : Overall length: 337 mm (Tip length: 20 mm)<br>Tip diameter: 2.5 mm (Body diameter: 12 mm)<br>Distance from probe tip to dipole centers: 1 mm                                                              |
| <b>Application</b>   | : High precision dosimetric measurements in any exposure scenario (e.g., very strong gradient fields). Only probe which enables compliance testing for frequencies up to 6 GHz with precision of better 30% |



EX3DV4 E-Field Probe

#### NOTE:

1. The Probe parameters have been calibrated by the SPEAG. Please reference “APPENDIX C” for the Calibration Certification Report.

### 9.2 ELI Phantom

|                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
|---------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Construction</b> | : Phantom for compliance testing of handheld and bodymounted wireless devices in the frequency range of 30 MHz to 6 GHz. ELI is fully compatible with the IEC 62209-2 standard and all known tissue simulating liquids. ELI has been optimized regarding its performance and can be integrated into our standard phantom tables. A cover prevents evaporation of the liquid. Reference markings on the phantom allow installation of the complete setup, including all predefined phantom positions and measurement grids, by teaching three points. The phantom is compatible with all SPEAG dosimetric probes and dipoles. |
|---------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

ELI V5.0 has the same shell geometry and is manufactured from the same material as ELI4, but has reinforced top structure



ELI Phantom

|                        |                                              |
|------------------------|----------------------------------------------|
| <b>Shell Thickness</b> | : 2.0 mm $\pm$ 0.1 mm                        |
| <b>Dimensions</b>      | : Major axis : 600 mm<br>Minor axis : 400 mm |

### 9.3 Device Holder

Construction: : In combination with the Twin SAM PhantomV4.0/V4.0C or Twin SAM, the Mounting Device (made from POM) enables the rotation of the mounted transmitter in spherical coordinates, whereby the rotation point is the ear opening. The devices can be easily and accurately positioned according to IEC, IEEE, CENELEC, FCC or other specifications. The device holder can be locked at different phantom locations (left head, right head, flat phantom).



Device Holder

## 10 SAR Measurement Procedures

### 10.1 Normal SAR Measurement Procedure

#### Step 1: Power Reference Measurement

The Power Reference Measurement and Power Drift Measurements are for monitoring the power drift of the device under test in the batch process. The Minimum distance of probe sensors to surface determines the closest measurement point to phantom surface. The minimum distance of probe sensors to surface is 1.4 mm. This distance cannot be smaller than the Distance of sensor calibration points to probe tip as defined in the probe properties.

#### Step 2 and 3: Area Scan & Zoom Scan Procedures

The entire evaluation of the spatial peak values is performed within the Post-processing engine (SEMCAD). The system always gives the maximum values for the 1 g and 10 g cubes. The algorithm to find the cube with highest averaged SAR is divided into the following stages:

1. The extraction of the measured data (grid and values) from the Zoom Scan.
2. The calculation of the SAR value at every measurement point based on all stored data (A/D values and measurement parameters)
3. The generation of a high-resolution mesh within the measured volume
4. The interpolation of all measured values from the measurement grid to the high-resolution grid
5. The extrapolation of the entire 3-D field distribution to the phantom surface over the distance from sensor to surface
6. The calculation of the averaged SAR within masses of 1 g and 10 g.

#### Step 4: Power drift measurement

The Power Drift Measurement measures the field at the same location as the most recent power reference measurement within the same procedure, and with the same settings. The Power Drift Measurement gives the field difference in dB from the reading conducted within the last Power Reference Measurement. This allows a user to monitor the power drift of the device under test within a batch process. The measurement procedure is the same as Step 1. SAR drift shall be kept within  $\pm 5\%$  and if it without  $\pm 5\%$ , SAR retest according to measurement procedure step 1~4.


< Area and Zoom Scan Resolutions per FCC KDB Publication 865664 D01v01r04 >

|                                                                                                                                                                                                                                                                                                                                                           |                                           |                                                                                             | $\leq 3 \text{ GHz}$                                                                                                                                                                                                                                                   | $> 3 \text{ GHz}$                                                                                                             |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------|---------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------|
| Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface                                                                                                                                                                                                                                                    |                                           |                                                                                             | $5 \text{ mm} \pm 1 \text{ mm}$                                                                                                                                                                                                                                        | $\frac{1}{2} \cdot \delta \cdot \ln(2) \text{ mm} \pm 0.5 \text{ mm}$                                                         |
| Maximum probe angle from probe axis to phantom surface normal at the measurement location                                                                                                                                                                                                                                                                 |                                           |                                                                                             | $30^\circ \pm 1^\circ$                                                                                                                                                                                                                                                 | $20^\circ \pm 1^\circ$                                                                                                        |
| Maximum area scan spatial resolution: $\Delta x_{\text{Area}}, \Delta y_{\text{Area}}$                                                                                                                                                                                                                                                                    |                                           |                                                                                             | $\leq 2 \text{ GHz}: \leq 15 \text{ mm}$<br>$2 - 3 \text{ GHz}: \leq 12 \text{ mm}$                                                                                                                                                                                    | $3 - 4 \text{ GHz}: \leq 12 \text{ mm}$<br>$4 - 6 \text{ GHz}: \leq 10 \text{ mm}$                                            |
|                                                                                                                                                                                                                                                                                                                                                           |                                           |                                                                                             | When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be $\leq$ the corresponding x or y dimension of the test device with at least one measurement point on the test device. |                                                                                                                               |
| Maximum zoom scan spatial resolution: $\Delta x_{\text{Zoom}}, \Delta y_{\text{Zoom}}$                                                                                                                                                                                                                                                                    |                                           |                                                                                             | $\leq 2 \text{ GHz}: \leq 8 \text{ mm}$<br>$2 - 3 \text{ GHz}: \leq 5 \text{ mm}^*$                                                                                                                                                                                    | $3 - 4 \text{ GHz}: \leq 5 \text{ mm}^*$<br>$4 - 6 \text{ GHz}: \leq 4 \text{ mm}^*$                                          |
| Maximum zoom scan spatial resolution, normal to phantom surface                                                                                                                                                                                                                                                                                           | uniform grid: $\Delta z_{\text{Zoom}}(n)$ |                                                                                             | $\leq 5 \text{ mm}$                                                                                                                                                                                                                                                    | $3 - 4 \text{ GHz}: \leq 4 \text{ mm}$<br>$4 - 5 \text{ GHz}: \leq 3 \text{ mm}$<br>$5 - 6 \text{ GHz}: \leq 2 \text{ mm}$    |
|                                                                                                                                                                                                                                                                                                                                                           | graded grid                               | $\Delta z_{\text{Zoom}}(1)$ : between 1 <sup>st</sup> two points closest to phantom surface | $\leq 4 \text{ mm}$                                                                                                                                                                                                                                                    | $3 - 4 \text{ GHz}: \leq 3 \text{ mm}$<br>$4 - 5 \text{ GHz}: \leq 2.5 \text{ mm}$<br>$5 - 6 \text{ GHz}: \leq 2 \text{ mm}$  |
|                                                                                                                                                                                                                                                                                                                                                           |                                           | $\Delta z_{\text{Zoom}}(n>1)$ : between subsequent points                                   | $\leq 1.5 \cdot \Delta z_{\text{Zoom}}(n-1) \text{ mm}$                                                                                                                                                                                                                |                                                                                                                               |
| Minimum zoom scan volume                                                                                                                                                                                                                                                                                                                                  | x, y, z                                   |                                                                                             | $\geq 30 \text{ mm}$                                                                                                                                                                                                                                                   | $3 - 4 \text{ GHz}: \geq 28 \text{ mm}$<br>$4 - 5 \text{ GHz}: \geq 25 \text{ mm}$<br>$5 - 6 \text{ GHz}: \geq 22 \text{ mm}$ |
| Note: $\delta$ is the penetration depth of a plane-wave at normal incidence to the tissue medium; see IEEE Std 1528-2013 for details.                                                                                                                                                                                                                     |                                           |                                                                                             |                                                                                                                                                                                                                                                                        |                                                                                                                               |
| * When zoom scan is required and the <u>reported</u> SAR from the <u>area scan based 1-g SAR estimation</u> procedures of KDB Publication 447498 is $\leq 1.4 \text{ W/kg}$ , $\leq 8 \text{ mm}$ , $\leq 7 \text{ mm}$ and $\leq 5 \text{ mm}$ zoom scan resolution may be applied, respectively, for 2 GHz to 3 GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz. |                                           |                                                                                             |                                                                                                                                                                                                                                                                        |                                                                                                                               |

## 11 Definition of Reference

### 11.1 Other consumer electronic devices

The exposure conditions of transmitters and modules incorporated in certain consumer electronic devices, such as printers, cameras, and camcorders may vary according to the installation and operating configurations required by the host products. Details of the transmitter and antenna configurations, antenna to user test separation distance, device operating configurations, etc., are required to determine SAR test exclusion or SAR measurement requirements for each host product. When SAR tests are required, a KDB inquiry is recommended to confirm the test setup. Unless the transmitter is used in a specific/dedicated host device, the standalone and simultaneous transmission SAR procedures for transmitters and modules should be applied. These must be fully explained in the permissive change documentation or equipment approval filing, whichever is applicable. This device is mounted on the saddle of the vehicle, and the physical distance from the saddle is 47mm. By manufacturer declaration, the test distance is 45mm.



※ Photo of the device mounted on the vehicle

## 12. SAR System Verification

The microwave circuit arrangement for system verification is sketched in Fig 1. The daily system accuracy verification occurs within the flat section of the SAM phantom. A SAR measurement was performed to see if the measured SAR was within  $\pm 10\%$  from the target SAR values. These tests were done at 750 / 835 / 1800 / 1900 / 2600 MHz. The tests were conducted on the same days as the measurement of the DUT. The obtained results from the system accuracy verification are displayed in the table 1. (SAR values are normalized to 1W forward power delivered to the dipole). During the tests, the ambient temperature of the laboratory was in the range  $(22 \pm 2) ^\circ \text{C}$ , the relative humidity was in the range  $(55 \pm 5) \% \text{ R.H}$  and the liquid depth above the ear reference points was  $\geq 15 \text{ cm} \pm 5 \text{ mm}$  (frequency  $\leq 3 \text{ GHz}$ ) or  $\geq 10 \text{ cm} \pm 5 \text{ mm}$  (frequency  $> 3 \text{ GHz}$ ) in all the cases. It is seen that the system is operating within its specification, as the results are within acceptable tolerance of the reference values.




Fig 1. The microwave circuit arrangement used for SAR system verification

- A. Signal Generator
- B. RF Amplifier
- C. Power Meter
- D. Power Sensor
- E. Dual Directional Coupler
- F. Reference dipole Antenna



Photo of the dipole Antenna

**SAR System Verification**

| Verification Kit    | Probe S/N | Tissue (MHz) | Target SAR 1 g from Standard (1 W) | Normalized SAR 1 g (1 W) | 1g Deviation (%) | Date       | Liquid Temp. (°C) |
|---------------------|-----------|--------------|------------------------------------|--------------------------|------------------|------------|-------------------|
| D750V3<br>SN:1085   | 7412      | 750          | 8.46                               | 8.43                     | -0.35            | 2022-06-15 | 22.1              |
| D750V3<br>SN:1085   | 7412      | 750          | 8.46                               | 8.10                     | -4.26            | 2022-06-16 | 22.2              |
| D750V3<br>SN:1085   | 7412      | 750          | 8.46                               | 8.64                     | 2.13             | 2022-06-17 | 22.3              |
| D750V3<br>SN:1085   | 7412      | 750          | 8.46                               | 8.61                     | 1.77             | 2022-08-10 | 22.5              |
| D835V2<br>SN:490    | 7412      | 835          | 9.60                               | 9.44                     | -1.67            | 2022-06-27 | 22.3              |
| D835V2<br>SN:490    | 7412      | 835          | 9.60                               | 9.56                     | -0.42            | 2022-06-28 | 22.1              |
| D835V2<br>SN:490    | 7412      | 835          | 9.60                               | 9.42                     | -1.88            | 2022-07-07 | 22.3              |
| D835V2<br>SN:490    | 7412      | 835          | 9.60                               | 8.96                     | -6.67            | 2022-07-25 | 22.0              |
| D835V2<br>SN:490    | 7412      | 835          | 9.60                               | 9.18                     | -4.38            | 2022-08-10 | 22.5              |
| D1800V2<br>SN:2d193 | 7412      | 1800         | 38.50                              | 39.40                    | 2.34             | 2022-07-01 | 22.3              |
| D1800V2<br>SN:2d193 | 7412      | 1800         | 38.50                              | 37.60                    | -2.34            | 2022-07-04 | 21.9              |
| D1800V2<br>SN:2d074 | 7412      | 1800         | 39.00                              | 41.00                    | 5.13             | 2022-08-11 | 21.9              |
| D1900V2<br>SN:5d158 | 7412      | 1900         | 41.00                              | 41.60                    | 1.46             | 2022-06-11 | 21.9              |
| D1900V2<br>SN:5d033 | 7412      | 1900         | 39.30                              | 38.00                    | -3.31            | 2022-07-11 | 22.1              |
| D1900V2<br>SN:5d033 | 7412      | 1900         | 39.30                              | 41.80                    | 6.36             | 2022-07-25 | 22.1              |
| D1900V2<br>SN:5d033 | 7412      | 1900         | 39.30                              | 39.20                    | -0.25            | 2022-08-11 | 22.0              |
| D2600V2<br>SN:1038  | 7412      | 2600         | 57.90                              | 59.70                    | 3.11             | 2022-06-21 | 21.8              |
| D2600V2<br>SN:1038  | 7412      | 2600         | 57.90                              | 56.70                    | -2.07            | 2022-06-22 | 21.9              |
| D2600V2<br>SN:1038  | 7412      | 2600         | 57.90                              | 56.60                    | -2.25            | 2022-06-24 | 22.2              |
| D2600V2<br>SN:1038  | 7412      | 2600         | 57.90                              | 54.20                    | -6.39            | 2022-08-11 | 21.9              |

Table 1 Results system verification

### 13 Tissue Simulant Fluid for the Frequency Band

The dielectric properties for this simulant fluid were measured by using the Speag Model DAK-3.5 Dielectric Probe in conjunction with Agilent E5071C Network Analyzer (300 kHz - 6 GHz) by using a procedure detailed in Section V.

| f (MHz) | Tissue type   | Limits / Measured    | Dielectric Parameters |              |                           |
|---------|---------------|----------------------|-----------------------|--------------|---------------------------|
|         |               |                      | Permittivity          | Conductivity | Simulated Tissue Temp(°C) |
| 750.0   | Body          | Measured, 2022-06-15 | 42.58                 | 0.89         | 22.1                      |
|         |               | Target Tissue        | 41.90                 | 0.89         |                           |
|         |               | Deviation (%)        | 1.62                  | 0.00         |                           |
| 704.0   |               | Measured, 2022-06-15 | 43.47                 | 0.86         |                           |
|         |               | Deviation (%)        | 3.75                  | -3.37        |                           |
| 782.0   |               | Measured, 2022-06-15 | 42.38                 | 0.93         |                           |
|         | Deviation (%) | 1.15                 | 4.49                  |              |                           |
| 750.0   | Body          | Measured, 2022-06-16 | 42.48                 | 0.87         | 22.2                      |
|         |               | Target Tissue        | 41.90                 | 0.89         |                           |
|         |               | Deviation (%)        | 1.38                  | -2.25        |                           |
| 782.0   |               | Measured, 2022-06-16 | 42.07                 | 0.90         |                           |
|         |               | Deviation (%)        | 0.41                  | 1.12         |                           |
| 750.0   | Body          | Measured, 2022-06-17 | 42.29                 | 0.93         | 22.3                      |
|         |               | Target Tissue        | 41.90                 | 0.89         |                           |
|         |               | Deviation (%)        | 0.93                  | 4.49         |                           |
| 673.0   |               | Measured, 2022-06-17 | 43.40                 | 0.85         |                           |
|         |               | Deviation (%)        | 3.58                  | -4.49        |                           |
| 680.5   |               | Measured, 2022-06-17 | 43.29                 | 0.86         |                           |
|         | Deviation (%) | 3.32                 | -3.37                 |              |                           |
| 750.0   | Body          | Measured, 2022-08-10 | 41.96                 | 0.92         | 22.5                      |
|         |               | Target Tissue        | 41.90                 | 0.89         |                           |
|         |               | Deviation (%)        | 0.14                  | 3.37         |                           |
| 673.0   |               | Measured, 2022-08-10 | 42.26                 | 0.89         |                           |
|         |               | Deviation (%)        | 0.86                  | 0.00         |                           |
| 782.0   |               | Measured, 2022-08-10 | 41.84                 | 0.93         |                           |
|         | Deviation (%) | -0.14                | 4.49                  |              |                           |
| 835.0   | Body          | Measured, 2022-06-27 | 41.79                 | 0.90         | 22.3                      |
|         |               | Target Tissue        | 41.50                 | 0.90         |                           |
|         |               | Deviation (%)        | 0.70                  | 0.00         |                           |
| 844.0   |               | Measured, 2022-06-27 | 41.70                 | 0.91         |                           |
|         |               | Deviation (%)        | 0.48                  | 1.11         |                           |
| 835.0   | Body          | Measured, 2022-06-28 | 41.47                 | 0.89         | 22.1                      |
|         |               | Target Tissue        | 41.50                 | 0.90         |                           |
|         |               | Deviation (%)        | -0.07                 | -1.11        |                           |
| 826.4   |               | Measured, 2022-06-28 | 41.56                 | 0.89         |                           |
|         |               | Deviation (%)        | 0.14                  | -1.11        |                           |
| 835.0   | Body          | Measured, 2022-07-07 | 42.17                 | 0.91         | 22.3                      |
|         |               | Target Tissue        | 41.50                 | 0.90         |                           |
|         |               | Deviation (%)        | 1.61                  | 1.11         |                           |
| 824.2   |               | Measured, 2022-07-07 | 42.29                 | 0.90         |                           |
|         |               | Deviation (%)        | 1.90                  | 0.00         |                           |

| f (MHz) | Tissue type | Limits / Measured    | Dielectric Parameters |              |                           |
|---------|-------------|----------------------|-----------------------|--------------|---------------------------|
|         |             |                      | Permittivity          | Conductivity | Simulated Tissue Temp(°C) |
| 835.0   | Body        | Measured, 2022-07-25 | 41.95                 | 0.91         | 22.0                      |
|         |             | Target Tissue        | 41.50                 | 0.90         |                           |
|         |             | Deviation (%)        | 1.08                  | 1.11         |                           |
| 824.2   |             | Measured, 2022-07-25 | 42.09                 | 0.90         |                           |
|         |             | Deviation (%)        | 1.42                  | 0.00         |                           |
| 835.0   | Body        | Measured, 2022-08-10 | 39.90                 | 0.91         | 22.5                      |
|         |             | Target Tissue        | 41.50                 | 0.90         |                           |
|         |             | Deviation (%)        | -3.86                 | 1.11         |                           |
| 824.2   |             | Measured, 2022-08-10 | 39.95                 | 0.91         |                           |
|         |             | Deviation (%)        | -3.73                 | 1.11         |                           |
| 844.0   |             | Measured, 2022-08-10 | 39.87                 | 0.91         |                           |
|         |             | Deviation (%)        | -3.93                 | 1.11         |                           |
| 1800.0  | Body        | Measured, 2022-07-01 | 39.56                 | 1.46         | 22.3                      |
|         |             | Target Tissue        | 40.00                 | 1.40         |                           |
|         |             | Deviation (%)        | -1.10                 | 4.29         |                           |
| 1712.4  |             | Measured, 2022-07-01 | 39.85                 | 1.38         |                           |
|         |             | Deviation (%)        | -0.37                 | -1.43        |                           |
| 1800.0  | Body        | Measured, 2022-07-04 | 38.76                 | 1.42         | 21.9                      |
|         |             | Target Tissue        | 40.00                 | 1.40         |                           |
|         |             | Deviation (%)        | -3.10                 | 1.43         |                           |
| 1720.0  |             | Measured, 2022-07-04 | 38.92                 | 1.37         |                           |
|         |             | Deviation (%)        | -2.70                 | -2.14        |                           |
| 1800.0  | Body        | Measured, 2022-08-11 | 39.15                 | 1.46         | 21.9                      |
|         |             | Target Tissue        | 40.00                 | 1.40         |                           |
|         |             | Deviation (%)        | -2.13                 | 4.29         |                           |
| 1712.4  |             | Measured, 2022-08-11 | 39.23                 | 1.40         |                           |
|         |             | Deviation (%)        | -1.93                 | 0.00         |                           |
| 1720.0  |             | Measured, 2022-08-11 | 39.22                 | 1.41         |                           |
|         |             | Deviation (%)        | -1.95                 | 0.71         |                           |
| 1900.0  | Body        | Measured, 2022-06-11 | 39.93                 | 1.39         | 21.9                      |
|         |             | Target Tissue        | 40.00                 | 1.40         |                           |
|         |             | Deviation (%)        | -0.18                 | -0.71        |                           |
| 1880.0  |             | Measured, 2022-06-11 | 40.00                 | 1.37         |                           |
|         |             | Deviation (%)        | 0.00                  | -2.14        |                           |
| 1905.0  |             | Measured, 2022-06-11 | 39.91                 | 1.39         |                           |
|         |             | Deviation (%)        | -0.23                 | -0.71        |                           |
| 1900.0  | Body        | Measured, 2022-07-11 | 39.36                 | 1.40         | 22.1                      |
|         |             | Target Tissue        | 40.00                 | 1.40         |                           |
|         |             | Deviation (%)        | -1.60                 | 0.00         |                           |
| 1850.2  |             | Measured, 2022-07-11 | 39.57                 | 1.35         |                           |
|         |             | Deviation (%)        | -1.08                 | -3.57        |                           |

| f (MHz) | Tissue type | Limits / Measured    | Dielectric Parameters |              |                           |
|---------|-------------|----------------------|-----------------------|--------------|---------------------------|
|         |             |                      | Permittivity          | Conductivity | Simulated Tissue Temp(°C) |
| 1900.0  | Body        | Measured, 2022-07-25 | 41.74                 | 1.40         | 22.1                      |
|         |             | Target Tissue        | 40.00                 | 1.40         |                           |
|         |             | Deviation (%)        | 4.35                  | 0.00         |                           |
| 1850.2  |             | Measured, 2022-07-25 | 41.99                 | 1.35         |                           |
|         |             | Deviation (%)        | 4.98                  | -3.57        |                           |
| 1900.0  | Body        | Measured, 2022-08-11 | 41.42                 | 1.40         | 22.0                      |
|         |             | Target Tissue        | 40.00                 | 1.40         |                           |
|         |             | Deviation (%)        | 3.55                  | 0.00         |                           |
| 1850.2  |             | Measured, 2022-08-11 | 41.43                 | 1.37         |                           |
|         |             | Deviation (%)        | 3.58                  | -2.14        |                           |
| 1905.0  |             | Measured, 2022-08-11 | 41.41                 | 1.40         |                           |
|         |             | Deviation (%)        | 3.52                  | 0.00         |                           |
| 2600.0  | Body        | Measured, 2022-06-21 | 37.35                 | 2.02         | 21.8                      |
|         |             | Target Tissue        | 39.00                 | 1.96         |                           |
|         |             | Deviation (%)        | -4.23                 | 3.06         |                           |
| 2560.0  |             | Measured, 2022-06-21 | 37.46                 | 1.98         |                           |
|         |             | Deviation (%)        | -3.95                 | 1.02         |                           |
| 2600.0  | Body        | Measured, 2022-06-22 | 38.30                 | 1.97         | 21.9                      |
|         |             | Target Tissue        | 39.00                 | 1.96         |                           |
|         |             | Deviation (%)        | -1.79                 | 0.51         |                           |
| 2560.0  |             | Measured, 2022-06-22 | 38.47                 | 1.93         |                           |
|         |             | Deviation (%)        | -1.36                 | -1.53        |                           |
| 2680.0  |             | Measured, 2022-06-22 | 37.92                 | 2.05         |                           |
|         |             | Deviation (%)        | -2.77                 | 4.59         |                           |
| 2600.0  | Body        | Measured, 2022-06-24 | 37.34                 | 1.97         | 22.2                      |
|         |             | Target Tissue        | 39.00                 | 1.96         |                           |
|         |             | Deviation (%)        | -4.26                 | 0.51         |                           |
| 2680.0  |             | Measured, 2022-06-24 | 37.05                 | 2.05         |                           |
|         |             | Deviation (%)        | -5.00                 | 4.59         |                           |
| 2600.0  | Body        | Measured, 2022-08-11 | 38.10                 | 1.97         | 21.9                      |
|         |             | Target Tissue        | 39.00                 | 1.96         |                           |
|         |             | Deviation (%)        | -2.31                 | 0.51         |                           |
| 2560.0  |             | Measured, 2022-08-11 | 38.15                 | 1.94         |                           |
|         |             | Deviation (%)        | -2.18                 | -1.02        |                           |
| 2680.0  |             | Measured, 2022-08-11 | 37.99                 | 2.04         |                           |
|         |             | Deviation (%)        | -2.59                 | 4.08         |                           |

The brain mixtures consist of a viscous gel using hydroxyethyl cellulose(HEC) gelling agent and saline solution. Preservation with a bactericide is added and visual inspection is made to make sure air bubbles are not trapped during the mixing process. The mixture is calibrated to obtain proper dielectric constant (permittivity) and conductivity of the desired tissue. The composition of ingredients may be modified accordingly to achieve the desired target tissue parameters required for routine SAR evaluation. The dielectric properties of the liquid material required to fill the phantom shell shall be target

| Frequency (MHz)                                                         | 450         | 835   | 900   | 1800-2000                   | 2450  | 2600  |
|-------------------------------------------------------------------------|-------------|-------|-------|-----------------------------|-------|-------|
| Tissue Type                                                             | Head & Body |       |       |                             |       |       |
| Ingredient (% by weight)                                                |             |       |       |                             |       |       |
| Water                                                                   | 38.91       | 40.29 | 40.29 | 55.24                       | 45.0  | 45.0  |
| Salt (NaCl)                                                             | 3.79        | 1.38  | 1.38  | 0.31                        | 0     | 0     |
| Sugar                                                                   | 56.93       | 57.90 | 57.90 | 0                           | 0     | 0     |
| HEC                                                                     | 0.25        | 0.24  | 0.24  | 0                           | 0     | 0     |
| Bactericide                                                             | 0.12        | 0.18  | 0.18  | 0                           | 0     | 0     |
| Triton X-100                                                            | 0           | 0     | 0     | 0                           | 0     | 0     |
| DGBE                                                                    | 0           | 0     | 0     | 44.45                       | 55.00 | 55.00 |
| Tissue parameter target by IEEE 1528-2013                               |             |       |       |                             |       |       |
| Dielectric Constant                                                     | 43.50       | 41.50 | 41.50 | 40.00                       | 39.20 | 39.00 |
| Conductivity (S/m)                                                      | 0.87        | 0.90  | 0.97  | 1.40                        | 1.80  | 1.96  |
| Salt: 99+% Pure Sodium Chloride                                         |             |       |       | Sucrose: 98+% Pure Sucrose  |       |       |
| Water: De-ionized, 16 M <sup>+</sup> resistivity                        |             |       |       | HEC: Hydroxyethyl Cellulose |       |       |
| DGBE: 99+% Di(ethylene glycol) butyl ether, [2-(2-butoxyethoxy)ethanol] |             |       |       |                             |       |       |

## 14 Justification for Extended SAR Dipole Calibrations

Usage of SAR dipoles calibrated less than 3 years ago but more than 1 year ago were confirmed in maintaining return loss (< -20 dB, within 20 % of prior calibration) and impedance (within 5 ohm from prior calibration) requirements per extended calibrations in KDB publication 865664 D01V01r04:

| 750V3 Head (SN : 1085) |                  |      |               |       |
|------------------------|------------------|------|---------------|-------|
| 750 GHz                |                  |      |               |       |
| Measurement Date       | Return Loss (dB) | Δ%   | Impedance (Ω) | ΔΩ    |
| 2022-02-24             | -29.42           | 6.10 | 51.53         | -1.69 |

| 1800V2 Head (SN : 2d193) |                  |        |               |      |
|--------------------------|------------------|--------|---------------|------|
| 1800 GHz                 |                  |        |               |      |
| Measurement Date         | Return Loss (dB) | Δ%     | Impedance (Ω) | ΔΩ   |
| 2021-08-09               | -26.14           | -10.90 | 47.54         | 0.89 |

| 1900V2 Head (SN : 5d158) |                  |            |                        |                |
|--------------------------|------------------|------------|------------------------|----------------|
| 1900 GHz                 |                  |            |                        |                |
| Measurement Date         | Return Loss (dB) | $\Delta\%$ | Impedance ( $\Omega$ ) | $\Delta\Omega$ |
| 2022-04-13               | -24.74           | 14.13      | 55.46                  | 3.17           |

| 2600V2 Head (SN : 1038) |                  |            |                        |                |
|-------------------------|------------------|------------|------------------------|----------------|
| 2600 GHz                |                  |            |                        |                |
| Measurement Date        | Return Loss (dB) | $\Delta\%$ | Impedance ( $\Omega$ ) | $\Delta\Omega$ |
| 2022-05-19              | -30.15           | 15.93      | 51.49                  | 3.50           |

## 15 Instruments List

|                              |                                                   |                      |                 |                     |                |
|------------------------------|---------------------------------------------------|----------------------|-----------------|---------------------|----------------|
| <b>Test Platform</b>         | SPEAG DASY System                                 |                      |                 |                     |                |
| <b>Manufacture</b>           | SPEAG                                             |                      |                 |                     |                |
| <b>Description</b>           | SAR Test System (Frequency range 300 MHz - 6 GHz) |                      |                 |                     |                |
| <b>Software Reference</b>    | DASY52: 52.10.4(1527)<br>SEMCAD X: 14.6.14(7483)  |                      |                 |                     |                |
| <b>Equipment</b>             | <b>Type</b>                                       | <b>Serial Number</b> | <b>Cal Date</b> | <b>Cal Interval</b> | <b>Cal Due</b> |
| Phantom                      | ELI Phantom                                       | TP-1244              | N/A             | N/A                 | N/A            |
| Verification Dipole          | D750V3                                            | 1085                 | 2021-03-17      | Biennial            | 2023-03-17     |
| Verification Dipole          | D835V2                                            | 490                  | 2022-05-25      | Biennial            | 2024-05-25     |
| Verification Dipole          | D1800V2                                           | 2d193                | 2020-08-20      | Biennial            | 2022-08-20     |
| Verification Dipole          | D1800V2                                           | 2d074                | 2022-07-18      | Biennial            | 2024-07-18     |
| Verification Dipole          | D1900V2                                           | 5d158                | 2021-04-22      | Biennial            | 2023-04-22     |
| Verification Dipole          | D1900V2                                           | 5d033                | 2022-05-30      | Biennial            | 2024-05-30     |
| Verification Dipole          | D2600V2                                           | 1038                 | 2021-05-27      | Biennial            | 2023-05-27     |
| DAE                          | DAE4                                              | 1595                 | 2022-01-24      | Annual              | 2023-01-24     |
| E-Field Probe                | EX3DV4                                            | 7412                 | 2022-04-29      | Annual              | 2023-04-29     |
| Dielectric Assessment Kit    | DAK-3.5                                           | 1228                 | 2021-11-23      | Annual              | 2022-11-23     |
| Network Analyzer             | E5071C                                            | MY46111535           | 2022-04-19      | Annual              | 2023-04-19     |
| Power Meter                  | E4419B                                            | GB43311125           | 2022-04-20      | Annual              | 2023-04-20     |
| Power Meter                  | E4419B                                            | GB43311715           | 2022-03-03      | Annual              | 2023-03-03     |
| Power Sensor                 | E9300H                                            | MY41495307           | 2022-04-20      | Annual              | 2023-04-20     |
| Power Sensor                 | E9300H                                            | MY41495314           | 2022-04-20      | Annual              | 2023-04-20     |
| Signal Generator             | E8247C                                            | MY43321024           | 2022-06-09      | Annual              | 2023-06-09     |
| RF Amplifier                 | AMP2027ADB                                        | 10001                | 2021-12-08      | Annual              | 2022-12-08     |
| Dual Directional Coupler     | 778D                                              | MY52180497           | 2022-03-04      | Annual              | 2023-03-04     |
| Dual Directional Coupler     | 772D                                              | MY52180226           | 2022-03-04      | Annual              | 2023-03-04     |
| LP Filter                    | LA-15N                                            | LF02                 | 2022-03-03      | Annual              | 2023-03-03     |
| LP Filter                    | LA-30N                                            | LF03                 | 2022-03-03      | Annual              | 2023-03-03     |
| Attenuator                   | 05AS102-K03                                       | A1                   | 2021-12-06      | Annual              | 2022-12-06     |
| Attenuator                   | 05AS102-K20                                       | A4                   | 2021-12-06      | Annual              | 2022-12-06     |
| Attenuator                   | RFHB1210NC2                                       | A5                   | 2022-06-09      | Annual              | 2023-06-09     |
| Hygro-Thermometer            | BJ5478                                            | 12091382-1           | 2022-06-04      | Annual              | 2023-06-04     |
| Digital Thermometer          | SDT25                                             | 19041500179          | 2021-09-17      | Annual              | 2022-09-17     |
| Radio Communication Analyzer | MT8821C                                           | 6261760829           | 2022-02-25      | Annual              | 2023-02-25     |

## **16 FCC Power Measurement Procedures**

The SAR measurement Software calculates a reference point at the start and end of the test to check for power drifts. If conducted power deviations of more than 5 % occurred, the tests were repeated.

## **17 Measured and Reported SAR**

Per FCC KDB Publication 447498 D01v06, When SAR is not measured at the maximum power level allowed for production units, the results must be scaled to the maximum tune-up tolerance limit according to the power applied to the individual channels tested to determine compliance. For simultaneous transmission, the measured aggregate SAR must be scaled according to the sum of the differences between the maximum tune-up tolerance and actual power used to test each transmitter. When SAR is measured at or scaled to the maximum tune-up tolerance limit, the results are referred to as reported SAR. Test highest reported SAR results are identified on the grant of equipment authorization according to procedures in KDB 690783 D01v01r03.

## 18 Maximum Output Power Specifications

This device operates using the following maximum output power specifications. SAR values were scaled to the maximum allowed power to determine compliance per KDB Publication 447498 D01v06

### GSM Maximum Power

| Band     | Maximum/<br>Normal | Maximum Output Power (dBm) |              |              |              |              |
|----------|--------------------|----------------------------|--------------|--------------|--------------|--------------|
|          |                    | GSM<br>Voice               | GPRS         |              | EGPRS        |              |
|          |                    |                            | 1Tx          | 2Tx          | 1Tx          | 2Tx          |
| GSM 850  | <b>Maximum</b>     | <b>34.00</b>               | <b>34.00</b> | <b>34.00</b> | <b>28.00</b> | <b>28.00</b> |
|          | Normal             | 33.00                      | 33.00        | 33.00        | 27.00        | 27.00        |
| GSM 1900 | <b>Maximum</b>     | <b>30.50</b>               | <b>30.50</b> | <b>30.50</b> | <b>26.50</b> | <b>26.50</b> |
|          | Normal             | 30.00                      | 30.00        | 30.00        | 26.00        | 26.00        |

### WCDMA Maximum Power

| Mode     | Maximum/Normal | Maximum Output Power (dBm) |              |              |                  |
|----------|----------------|----------------------------|--------------|--------------|------------------|
|          |                | 3GPP WCDMA<br>AMR / RMC    | 3GPP HSDPA   | 3GPP HSUPA   | 3GPP<br>DC-HSDPA |
| WCDMA II | <b>Maximum</b> | <b>25.00</b>               | <b>24.00</b> | <b>24.00</b> | <b>23.00</b>     |
|          | Normal         | 24.00                      | 23.00        | 23.00        | 22.00            |
| WCDMA IV | <b>Maximum</b> | <b>25.00</b>               | <b>24.00</b> | <b>24.00</b> | <b>23.00</b>     |
|          | Normal         | 24.00                      | 23.00        | 23.00        | 22.00            |
| WCDMA V  | <b>Maximum</b> | <b>25.00</b>               | <b>24.00</b> | <b>24.00</b> | <b>23.00</b>     |
|          | Normal         | 24.00                      | 23.00        | 23.00        | 22.00            |

### LTE Maximum Power

| Mode / Band |                | Modulated Average |
|-------------|----------------|-------------------|
| LTE Band 2  | <b>Maximum</b> | <b>24.00</b>      |
|             | Nominal        | 23.00             |
| LTE Band 4  | <b>Maximum</b> | <b>24.00</b>      |
|             | Nominal        | 23.00             |
| LTE Band 5  | <b>Maximum</b> | <b>24.00</b>      |
|             | Nominal        | 23.00             |
| LTE Band 7  | <b>Maximum</b> | <b>24.00</b>      |
|             | Nominal        | 23.00             |
| LTE Band 12 | <b>Maximum</b> | <b>24.00</b>      |
|             | Nominal        | 23.00             |
| LTE Band 13 | <b>Maximum</b> | <b>24.00</b>      |
|             | Nominal        | 23.00             |
| LTE Band 17 | <b>Maximum</b> | <b>24.00</b>      |
|             | Nominal        | 23.00             |
| LTE Band 25 | <b>Maximum</b> | <b>24.00</b>      |
|             | Nominal        | 23.00             |
| LTE Band 41 | <b>Maximum</b> | <b>24.00</b>      |
|             | Nominal        | 23.00             |
| LTE Band 66 | <b>Maximum</b> | <b>24.00</b>      |
|             | Nominal        | 23.00             |
| LTE Band 71 | <b>Maximum</b> | <b>24.00</b>      |
|             | Nominal        | 23.00             |

## **19 RF Conducted Power Measurement**

### **19.1 GSM**

The device in LTE was controlled by using a Communication tester. The EUT was set to maximum power level during all tests. The DASY system measures power drift during SAR testing by comparing e-field in the same location at the beginning and at the end of measurement.

1. Both burst-averaged and calculated frame-averaged powers are included. Frame-averaged power was calculated from the measured burst-averaged power by converting the slot powers into linear units and calculating the energy over 8 timeslots.
2. The source-based frame-averaged output power was evaluated for 1Tx, 2Tx slot configurations. The configuration with the highest target frame averaged output power was evaluated for Car Telematics Modem SAR. When the maximum frame-averaged powers are equivalent across two or more slots (within 0.25 dB), the configuration with the most number of time slots were tested.
3. GPRS output powers were measured with coding scheme setting of 1(CS1) on the base station simulator. CS1 was configured to measure GPRS output power measurements and SAR to ensure GMSK modulation in the signal. Our investigation has shown that CS1 – CS4 settings do not have any impact on the output levels or modulations in the GPRS modes.
4. EGPRS output powers were measured with coding scheme setting of 5(CS5) on the base station simulator. CS5 was configured to measure EGPRS output power measurements and SAR to ensure 8PSK modulation in the signal. Our investigation has shown that CS5 – CS9 settings do not have any impact on the output levels or modulations in the GPRS modes.
5. For body SAR testing, the EUT was set in GPRS multi-slot class 12 with 2uplink slots for GSM850&GSM1900 due to maximum source-based time-averaged output power.

### **19.2 WCDMA**

#### **19.2.1 Output Power Verification**

Maximum output power is measured on the High, Middle and Low channels for each applicable transmission band according to the general descriptions in section 5.2 of 3GPP TS 34.121, using the appropriate RMC or AMR with TPC (transmit power control) set to all “1s”.

#### **19.2.2 Body SAR Measurements**

SAR for body exposure configurations is measured using the 12.2 kbps RMC with the TPC bits all “1s”.

#### **19.2.3 Procedures Used to Establish RF Signal for SAR HSDPA Data Devices**

Body SAR is not required for handsets with HSDPA capabilities when the maximum average output of each RF channel with HSDPA active is less than ¼ dB higher than that measured without HSDPA using 12.2 kbps RMC and the maximum SAR for 12.2 kbps RMC is  $\leq 75\%$  of the SAR limit. Otherwise, SAR is Measured for HSDPA, using an

FRC with H-Set 1 in Sub-test 1 and a 12.2 kbps RMC configured in Test Loop Mode 1, using the highest body SAR configuration in 12.2 kbps RMC without HSDPA, on the maximum output channel with the body exposure configuration that results in the highest SAR in 12.2 kbps RMC for that RF channel.

**Sub-Test 1 Setup for Release 5 HSDPA**

| Sub-test | $\beta_c$            | $\beta_d$            | $\beta_d$<br>(SF) | $\beta_c/\beta_d$    | $\beta_{hs}^{(2)}$ | CM (dB) <sup>(2)</sup> |
|----------|----------------------|----------------------|-------------------|----------------------|--------------------|------------------------|
| 1        | 2/15                 | 15/15                | 64                | 2/15                 | 4/15               | 0.0                    |
| 2        | 12/15 <sup>(3)</sup> | 15/15 <sup>(3)</sup> | 64                | 12/15 <sup>(3)</sup> | 24/15              | 1.0                    |
| 3        | 15/15                | 8/15                 | 64                | 15/8                 | 30/15              | 1.5                    |
| 4        | 15/15                | 4/15                 | 64                | 15/4                 | 30/15              | 1.5                    |

Note 1:  $\Delta_{ACK}$ ,  $\Delta_{NACK}$  and  $\Delta_{CQI} = 8 \Leftrightarrow A_{hs} = \beta_{hs}/\beta_c = 30/15 \Leftrightarrow \beta_{hs} = 30/15 * \beta_c$   
 Note 2: CM = 1 for  $\beta_c/\beta_d = 12/15$ ,  $\beta_{hs}/\beta_c = 24/15$ .  
 Note 3: For subtest 2 the  $\beta_c/\beta_d$  ratio of 12/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signaled gain factors for the reference TFC (TF1, TF1) to  $\beta_c = 11/15$  and  $\beta_d = 15/15$ .

#### 19.2.4 SAR Measurements for Conditions for HSUPA Data Devices

Body SAR is not required for handsets with HSPA capabilities when the maximum average output of each RF channel with HSUPA/HSDPA active is less than ¼ dB higher than that measured without HSUPA/HSDPA using 12.2 kbps RMC and the maximum SAR for 12.2 kbps RMC is ≤ 75 % of the SAR limit. Body SAR for HSPA is measured with E-DCH Sub-test 5, using H-Set 1 and QPSK for FRC and a 12.2 kbps RMC configured in Test Loop Mode 1 with power control algorithm 2, according to the highest body SAR configuration in 12.1 kbps RMC without HSPA. When VOIP is applicable for head exposure, SAR is not required when the maximum output of each RF channel with HSPA is less than ¼ dB higher than that measured using 12.2 kbps RMC; otherwise, the same HSPA configuration used for body measurement should be used to test for head exposure.

| Sub-test | $\beta_c$            | $\beta_d$            | $\beta_d$<br>(SF) | $\beta_c/\beta_d$    | $\beta_{hs}^{(1)}$ | $\beta_{ec}$ | $\beta_{ed}$                                 | $\beta_{ed}$<br>(SF) | $\beta_{ed}$<br>(codes) | CM <sup>(2)</sup><br>(dB) | MPR<br>(dB) | AG <sup>(4)</sup><br>Index | E-<br>TFCI |
|----------|----------------------|----------------------|-------------------|----------------------|--------------------|--------------|----------------------------------------------|----------------------|-------------------------|---------------------------|-------------|----------------------------|------------|
| 1        | 11/15 <sup>(3)</sup> | 15/15 <sup>(3)</sup> | 64                | 11/15 <sup>(3)</sup> | 22/15              | 209/225      | 1039/225                                     | 4                    | 1                       | 1.0                       | 0.0         | 20                         | 75         |
| 2        | 6/15                 | 15/15                | 64                | 6/15                 | 12/15              | 12/15        | 94/75                                        | 4                    | 1                       | 3.0                       | 2.0         | 12                         | 67         |
| 3        | 15/15                | 9/15                 | 64                | 15/9                 | 30/15              | 30/15        | $\beta_{ed1}: 47/15$<br>$\beta_{ed2}: 47/15$ | 4                    | 2                       | 2.0                       | 1.0         | 15                         | 92         |
| 4        | 2/15                 | 15/15                | 64                | 2/15                 | 4/15               | 2/15         | 56/75                                        | 4                    | 1                       | 3.0                       | 2.0         | 17                         | 71         |
| 5        | 15/15 <sup>(4)</sup> | 15/15 <sup>(4)</sup> | 64                | 15/15 <sup>(4)</sup> | 30/15              | 24/15        | 134/15                                       | 4                    | 1                       | 1.0                       | 0.0         | 21                         | 81         |

Note 1:  $\Delta_{ACK}$ ,  $\Delta_{NACK}$  and  $\Delta_{CQI} = 8 \Leftrightarrow A_{hs} = \beta_{hs}/\beta_c = 30/15 \Leftrightarrow \beta_{hs} = 30/15 * \beta_c$ .  
 Note 2: CM = 1 for  $\beta_c/\beta_d = 12/15$ ,  $\beta_{hs}/\beta_c = 24/15$ . For all other combinations of DPDCH, DPCCCH, HS-DPCCH, E-DPDCH and E-DPCCH the MPR is based on the relative CM difference.  
 Note 3: For subtest 1 the  $\beta_c/\beta_d$  ratio of 11/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signaled gain factors for the reference TFC (TF1, TF1) to  $\beta_c = 10/15$  and  $\beta_d = 15/15$ .  
 Note 4: For subtest 5 the  $\beta_c/\beta_d$  ratio of 15/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signaled gain factors for the reference TFC (TF1, TF1) to  $\beta_c = 14/15$  and  $\beta_d = 15/15$ .  
 Note 5: Testing UE using E-DPDCH Physical Layer category 1 Sub-test 3 is not required according to TS 25.306 Table 5.1g.  
 Note 6:  $\beta_{ed}$  can not be set directly; it is set by Absolute Grant Value.

## **19.3 LTE**

### **19.3.1 SAR measurement Conditions for LTE**

LTE modes were tested according to FCC KDB 941225 D05v02r05 publication. Please see notes after the tabulated SAR data for required test configurations. Establishing connections with base station simulators ensure a consistent means for testing SAR and are recommended for evaluation SAR. Anritsu MT8820C was used for LTE output power measurements and SAR testing. Closed loop power control was used so the UE transmits with maximum output power during SAR testing. SAR tests were performed with the same number of RB and RB offsets transmitting on all TTI frames (maximum TTI).

### **19.3.2 Spectrum Plots for RB Configurations**

A properly configured base station simulator was used for SAR tests and power measurements. Therefore, spectrum plots for RB configurations were not required to be included in this report.

### **19.3.3 MPR**

MPR is permanently implemented for this device by the manufacture. The specific manufacturer target MPR is indicated alongside the SAR results. MPR is enabled for this device, according to 3GPP TS36.101 Section 6.2.3 – 6.2.5 under Table 6.2.3.-1

### **19.3.4 A-MPR**

A-MPR (Additional MPR) has been disabled for all SAR tests by setting NS=01 on the base station simulator.

### **19.3.5 Required RB Size and RB Offsets for SAR Testing**

According to FCC KDB 941225 D05V02r05

- a. Per Section 5.2.1, SAR is required for QPSK 1 RB Allocation for the largest bandwidth
  - i. The required channel and offset combination with the highest maximum output power is required for SAR.
  - ii. When the reported SAR is  $\leq 0.8$  W/kg, testing of the remaining RB offset configurations and required test channels is not required. Otherwise, SAR is required for the remaining required test channels using the RB offset configuration with highest output power for that channel
  - iii. When the reported SAR for a required test channel is  $> 1.45$  W/kg, SAR is required for all RB offset configurations for that channel.
- b. Per Section 5.2.2, SAR is required for 50% RB allocation using the largest bandwidth following the same procedures outlined in Section 5.2.1.
- c. Per Section 5.2.3, QPSK SAR is not required for the 100% allocation when the highest maximum output power for the 100% allocation is less than the highest maximum output power of the 1 RB and 50% RB allocations and the reported SAR for the 1 RB and 50% RB allocations is  $< 0.8$  W/kg.
- d. Per Section 5.2.4 and 5.3, SAR tests for higher order modulations and lower bandwidths configurations are not required when the conducted power of the required test configurations determined by Section 5.2.1, through 5.2.3 is less than or equal to 1/2 dB higher than the equivalent configuration using QPSK modulation and when the QPSK SAR for those configurations is  $< 1.45$  W/kg.

### 19.3.6 TDD

LTE TDD testing is performed using the SAR test guidance provided in FCC KDB 941225 D05V02r04.

TDD is tested at the highest duty factor using UL-DL configuration 0 with special subframe configuration 6 and applying the FDD LTE procedures in KDB 941225 D05v02r04. SAR testing is performed using the extended cyclic prefix listed in 3GPP TS 36.211 Section 4.

### GSM Conducted power

| Mode    |         | Burst-Conducted Average Power(dBm) |       |       |       |       |
|---------|---------|------------------------------------|-------|-------|-------|-------|
|         |         | GSM                                | GPRS  |       | EGPRS |       |
|         |         | Voice                              | 1Tx   | 2Tx   | 1Tx   | 2Tx   |
| GSM850  | Maximum | 34.00                              | 34.00 | 34.00 | 28.00 | 28.00 |
|         | 128     | 33.18                              | 33.14 | 33.16 | 27.21 | 26.85 |
|         | 190     | 33.08                              | 33.12 | 33.10 | 26.76 | 26.21 |
|         | 251     | 32.94                              | 33.08 | 33.03 | 26.42 | 26.62 |
| GSM1900 | Maximum | 31.00                              | 30.50 | 30.50 | 26.50 | 26.50 |
|         | 512     | 29.86                              | 29.81 | 29.78 | 25.94 | 25.27 |
|         | 661     | 29.85                              | 29.79 | 29.70 | 25.89 | 25.44 |
|         | 810     | 29.82                              | 29.76 | 29.68 | 25.71 | 25.09 |
| Mode    |         | Frame-Conducted Average Power(dBm) |       |       |       |       |
|         |         | GSM                                | GPRS  |       | EGPRS |       |
|         |         | Voice                              | 1Tx   | 2Tx   | 1Tx   | 2Tx   |
| GSM850  | Maximum | 24.97                              | 24.97 | 27.98 | 18.97 | 21.98 |
|         | 128     | 24.15                              | 24.11 | 27.14 | 18.18 | 20.83 |
|         | 190     | 24.05                              | 24.09 | 27.08 | 17.73 | 20.19 |
|         | 251     | 23.91                              | 24.05 | 27.01 | 17.39 | 20.60 |
| GSM1900 | Maximum | 21.47                              | 21.47 | 24.48 | 17.47 | 20.48 |
|         | 512     | 20.83                              | 20.78 | 23.76 | 16.91 | 19.25 |
|         | 661     | 20.82                              | 20.76 | 23.68 | 16.86 | 19.42 |
|         | 810     | 20.79                              | 20.73 | 23.66 | 16.68 | 19.07 |

**WCDMA Conducted power**

| Mode<br>Channel | 3GPP 34.121<br>Subtest | Normal Power (dBm) |              |       |
|-----------------|------------------------|--------------------|--------------|-------|
|                 |                        | 9262               | 9400         | 9538  |
| WCDMA II        | 12.2 Kbps AMR          | 23.28              | 23.29        | 23.24 |
|                 | 12.2 Kbps RMC          | 23.06              | <b>23.30</b> | 23.01 |
| HSDPA           | Subtest 1              | 22.03              | 22.35        | 22.06 |
|                 | Subtest 2              | 22.05              | 22.34        | 22.06 |
|                 | Subtest 3              | 21.53              | 21.77        | 21.56 |
|                 | Subtest 4              | 21.53              | 21.81        | 21.59 |
| HSUPA           | Subtest 1              | 22.11              | 22.39        | 22.14 |
|                 | Subtest 2              | 20.13              | 20.36        | 20.14 |
|                 | Subtest 3              | 21.11              | 21.36        | 21.14 |
|                 | Subtest 4              | 20.12              | 20.38        | 20.17 |
|                 | Subtest 5              | 22.11              | 22.43        | 22.14 |
| DC-HSDPA        | Subtest 1              | 22.28              | 22.31        | 22.02 |
|                 | Subtest 2              | 22.28              | 22.29        | 22.02 |
|                 | Subtest 3              | 21.68              | 21.78        | 21.11 |
|                 | Subtest 4              | 21.70              | 21.80        | 21.07 |
| Mode<br>Channel | 3GPP 34.121<br>Subtest | Normal Power (dBm) |              |       |
|                 |                        | 1312               | 1413         | 1513  |
| WCDMA IV        | 12.2 Kbps AMR          | 23.59              | 23.36        | 23.13 |
|                 | 12.2 Kbps RMC          | <b>23.67</b>       | 23.44        | 23.32 |
| HSDPA           | Subtest 1              | 22.60              | 22.48        | 22.36 |
|                 | Subtest 2              | 22.59              | 22.43        | 22.31 |
|                 | Subtest 3              | 22.08              | 21.91        | 21.83 |
|                 | Subtest 4              | 22.01              | 21.92        | 21.8  |
| HSUPA           | Subtest 1              | 22.55              | 22.64        | 22.62 |
|                 | Subtest 2              | 20.51              | 20.58        | 20.55 |
|                 | Subtest 3              | 21.52              | 21.55        | 21.51 |
|                 | Subtest 4              | 20.56              | 20.63        | 20.52 |
|                 | Subtest 5              | 22.41              | 22.39        | 22.41 |
| DC-HSDPA        | Subtest 1              | 21.03              | 21.11        | 21.01 |
|                 | Subtest 2              | 21.12              | 21.23        | 21.03 |
|                 | Subtest 3              | 20.54              | 20.61        | 20.52 |
|                 | Subtest 4              | 20.59              | 20.69        | 20.58 |

| Mode     | 3GPP 34.121   | Normal Power (dBm) |       |       |
|----------|---------------|--------------------|-------|-------|
| Channel  | Subtest       | 4132               | 4183  | 4233  |
| WCDMA V  | 12.2 Kbps AMR | 23.39              | 23.20 | 23.34 |
|          | 12.2 Kbps RMC | <b>24.12</b>       | 23.97 | 23.85 |
| HSDPA    | Subtest 1     | 22.86              | 22.80 | 22.84 |
|          | Subtest 2     | 22.88              | 22.80 | 22.84 |
|          | Subtest 3     | 22.37              | 22.28 | 22.34 |
|          | Subtest 4     | 22.38              | 22.29 | 22.33 |
| HSUPA    | Subtest 1     | 22.88              | 22.93 | 22.89 |
|          | Subtest 2     | 21.03              | 20.90 | 20.94 |
|          | Subtest 3     | 21.97              | 21.92 | 21.95 |
|          | Subtest 4     | 21.04              | 20.96 | 20.98 |
|          | Subtest 5     | 23.00              | 22.98 | 22.95 |
| DC-HSDPA | Subtest 1     | 21.92              | 21.85 | 22.02 |
|          | Subtest 2     | 21.98              | 21.84 | 22.01 |
|          | Subtest 3     | 21.42              | 21.35 | 21.49 |
|          | Subtest 4     | 21.40              | 21.31 | 21.62 |

**Note**

1. WCDMA SAR was tested under RMC 12.2 kbps with HSPA inactive per KDB Publication 941225 D02v01. HSPA SAR was not required since the average output power of the HSPA subtests was not more than 0.25 dB higher than the RMC level and SAR was less than 1.2 W/kg

**LTE Conducted power**

**-LTE Band 2**

| LTE Band2 1.4MHz Bandwidth |         |           |                 |               |               |                          |
|----------------------------|---------|-----------|-----------------|---------------|---------------|--------------------------|
| Modulation                 | RB Size | RB Offset | Low Channel     | Mid Channel   | High Channel  | MPR Allowed Per 3GPP[dB] |
|                            |         |           | 18607           | 18900         | 19193         |                          |
|                            |         |           | (1 850.7 MHz)   | (1 880.0 MHz) | (1 909.3 MHz) |                          |
|                            |         |           | Conducted Power |               |               |                          |
|                            |         |           | [dBm]           | [dBm]         | [dBm]         |                          |
| QPSK                       | 1       | 0         | 22.01           | 22.40         | 22.14         | 0                        |
|                            | 1       | 2         | 22.07           | 22.50         | 22.26         |                          |
|                            | 1       | 5         | 22.12           | 22.41         | 22.15         |                          |
|                            | 3       | 0         | 22.17           | 22.45         | 22.19         |                          |
|                            | 3       | 2         | 22.19           | 22.47         | 22.22         |                          |
|                            | 3       | 3         | 22.18           | 22.41         | 22.16         |                          |
|                            | 6       | 0         | 21.12           | 21.41         | 21.13         | 0-1                      |
| 16QAM                      | 1       | 0         | 21.44           | 21.69         | 21.35         | 0-1                      |
|                            | 1       | 2         | 21.62           | 21.77         | 21.46         |                          |
|                            | 1       | 5         | 21.39           | 21.72         | 21.42         |                          |
|                            | 3       | 0         | 21.26           | 21.55         | 21.27         |                          |
|                            | 3       | 2         | 21.35           | 21.58         | 21.25         |                          |
|                            | 3       | 3         | 21.25           | 21.55         | 21.26         |                          |
|                            | 6       | 0         | 20.21           | 20.48         | 20.19         | 0-2                      |

| LTE Band2 3MHz Bandwidth |         |           |                 |               |               |                          |
|--------------------------|---------|-----------|-----------------|---------------|---------------|--------------------------|
| Modulation               | RB Size | RB Offset | Low Channel     | Mid Channel   | High Channel  | MPR Allowed Per 3GPP[dB] |
|                          |         |           | 18615           | 18900         | 19185         |                          |
|                          |         |           | (1 851.5 MHz)   | (1 880.0 MHz) | (1 908.5 MHz) |                          |
|                          |         |           | Conducted Power |               |               |                          |
|                          |         |           | [dBm]           | [dBm]         | [dBm]         |                          |
| QPSK                     | 1       | 0         | 22.23           | 22.49         | 22.44         | 0                        |
|                          | 1       | 7         | 22.27           | 22.54         | 22.50         |                          |
|                          | 1       | 14        | 22.23           | 22.45         | 22.37         |                          |
|                          | 8       | 0         | 21.21           | 21.48         | 21.40         | 0-1                      |
|                          | 8       | 4         | 21.24           | 21.51         | 21.43         |                          |
|                          | 8       | 7         | 21.18           | 21.46         | 21.41         |                          |
|                          | 15      | 0         | 21.19           | 21.48         | 21.39         |                          |
| 16QAM                    | 1       | 0         | 21.49           | 21.80         | 21.73         | 0-1                      |
|                          | 1       | 7         | 21.63           | 21.85         | 21.78         |                          |
|                          | 1       | 14        | 21.50           | 21.67         | 21.85         |                          |
|                          | 8       | 0         | 20.30           | 20.54         | 20.55         | 0-2                      |
|                          | 8       | 4         | 20.33           | 20.57         | 20.60         |                          |
|                          | 8       | 7         | 20.26           | 20.52         | 20.56         |                          |
|                          | 15      | 0         | 20.24           | 20.54         | 20.54         |                          |

| LTE Band2 5MHz Bandwidth |         |           |                 |               |               |                                   |
|--------------------------|---------|-----------|-----------------|---------------|---------------|-----------------------------------|
| Modulation               | RB Size | RB Offset | Low Channel     | Mid Channel   | High Channel  | MPR<br>Allowed<br>Per<br>3GPP[dB] |
|                          |         |           | 18625           | 18900         | 19175         |                                   |
|                          |         |           | (1 852.5 MHz)   | (1 880.0 MHz) | (1 907.5 MHz) |                                   |
|                          |         |           | Conducted Power |               |               |                                   |
|                          |         |           | [dBm]           | [dBm]         | [dBm]         |                                   |
| QPSK                     | 1       | 0         | 22.28           | 22.51         | 22.38         | 0                                 |
|                          | 1       | 12        | 22.21           | 22.46         | 22.40         |                                   |
|                          | 1       | 24        | 22.34           | 22.42         | 22.42         |                                   |
|                          | 12      | 0         | 21.24           | 21.49         | 21.44         | 0-1                               |
|                          | 12      | 6         | 21.23           | 21.53         | 21.44         |                                   |
|                          | 12      | 13        | 21.20           | 21.52         | 21.42         |                                   |
|                          | 25      | 0         | 21.22           | 21.52         | 21.50         |                                   |
| 16QAM                    | 1       | 0         | 21.58           | 21.80         | 21.76         | 0-1                               |
|                          | 1       | 12        | 21.53           | 21.80         | 21.86         |                                   |
|                          | 1       | 24        | 21.61           | 21.72         | 21.87         |                                   |
|                          | 12      | 0         | 20.27           | 20.56         | 20.60         | 0-2                               |
|                          | 12      | 6         | 20.26           | 20.58         | 20.57         |                                   |
|                          | 12      | 13        | 20.29           | 20.57         | 20.58         |                                   |
|                          | 25      | 0         | 20.25           | 20.57         | 20.55         |                                   |

| LTE Band2 10MHz Bandwidth |         |           |                 |               |               |                                   |
|---------------------------|---------|-----------|-----------------|---------------|---------------|-----------------------------------|
| Modulation                | RB Size | RB Offset | Low Channel     | Mid Channel   | High Channel  | MPR<br>Allowed<br>Per<br>3GPP[dB] |
|                           |         |           | 18650           | 18900         | 19150         |                                   |
|                           |         |           | (1 855.0 MHz)   | (1 880.0 MHz) | (1 905.0 MHz) |                                   |
|                           |         |           | Conducted Power |               |               |                                   |
|                           |         |           | [dBm]           | [dBm]         | [dBm]         |                                   |
| QPSK                      | 1       | 0         | 22.53           | 22.76         | 22.50         | 0                                 |
|                           | 1       | 25        | 22.28           | 22.48         | 22.33         |                                   |
|                           | 1       | 49        | 22.53           | 22.51         | 22.45         |                                   |
|                           | 25      | 0         | 21.28           | 21.52         | 21.39         | 0-1                               |
|                           | 25      | 12        | 21.39           | 21.55         | 21.35         |                                   |
|                           | 25      | 25        | 21.34           | 21.44         | 21.46         |                                   |
|                           | 50      | 0         | 21.37           | 21.53         | 21.46         |                                   |
| 16QAM                     | 1       | 0         | 21.75           | 22.04         | 21.81         | 0-1                               |
|                           | 1       | 25        | 21.54           | 21.73         | 21.65         |                                   |
|                           | 1       | 49        | 21.83           | 21.83         | 21.70         |                                   |
|                           | 25      | 0         | 20.32           | 20.58         | 20.45         | 0-2                               |
|                           | 25      | 12        | 20.39           | 20.61         | 20.45         |                                   |
|                           | 25      | 25        | 20.39           | 20.45         | 20.44         |                                   |
|                           | 50      | 0         | 20.42           | 20.58         | 20.46         |                                   |

| LTE Band2 15MHz Bandwidth |         |           |                 |               |               |                          |
|---------------------------|---------|-----------|-----------------|---------------|---------------|--------------------------|
| Modulation                | RB Size | RB Offset | Low Channel     | Mid Channel   | High Channel  | MPR Allowed Per 3GPP[dB] |
|                           |         |           | 18675           | 18900         | 19125         |                          |
|                           |         |           | (1 857.5 MHz)   | (1 880.0 MHz) | (1 902.5 MHz) |                          |
|                           |         |           | Conducted Power |               |               |                          |
|                           |         |           | [dBm]           | [dBm]         | [dBm]         |                          |
| QPSK                      | 1       | 0         | 22.38           | 22.61         | 22.58         | 0                        |
|                           | 1       | 36        | 22.30           | 22.47         | 22.33         |                          |
|                           | 1       | 74        | 22.35           | 22.34         | 22.48         |                          |
|                           | 36      | 0         | 21.39           | 21.55         | 21.51         | 0-1                      |
|                           | 36      | 18        | 21.37           | 21.57         | 21.41         |                          |
|                           | 36      | 37        | 21.34           | 21.45         | 21.45         |                          |
|                           | 75      | 0         | 21.39           | 21.47         | 21.47         |                          |
| 16QAM                     | 1       | 0         | 21.59           | 21.88         | 21.85         | 0-1                      |
|                           | 1       | 36        | 21.58           | 21.79         | 21.60         |                          |
|                           | 1       | 74        | 21.69           | 21.64         | 21.76         |                          |
|                           | 36      | 0         | 20.45           | 20.62         | 20.57         | 0-2                      |
|                           | 36      | 18        | 20.40           | 20.59         | 20.42         |                          |
|                           | 36      | 37        | 20.40           | 20.50         | 20.48         |                          |
|                           | 75      | 0         | 20.40           | 20.47         | 20.50         |                          |

| LTE Band2 20MHz Bandwidth |         |           |                 |               |               |                          |
|---------------------------|---------|-----------|-----------------|---------------|---------------|--------------------------|
| Modulation                | RB Size | RB Offset | Low Channel     | Mid Channel   | High Channel  | MPR Allowed Per 3GPP[dB] |
|                           |         |           | 18700           | 18900         | 19100         |                          |
|                           |         |           | (1 860.0 MHz)   | (1 880.0 MHz) | (1 900.0 MHz) |                          |
|                           |         |           | Conducted Power |               |               |                          |
|                           |         |           | [dBm]           | [dBm]         | [dBm]         |                          |
| QPSK                      | 1       | 0         | 22.58           | 22.73         | 22.59         | 0                        |
|                           | 1       | 50        | 22.29           | 22.45         | 22.44         |                          |
|                           | 1       | 99        | 22.47           | 22.50         | 22.47         |                          |
|                           | 50      | 0         | 21.42           | 21.58         | 21.53         | 0-1                      |
|                           | 50      | 25        | 21.39           | 21.58         | 21.46         |                          |
|                           | 50      | 13        | 21.35           | 21.46         | 21.45         |                          |
|                           | 100     | 0         | 21.40           | 21.47         | 21.52         |                          |
| 16QAM                     | 1       | 0         | 21.78           | 22.14         | 21.92         | 0-1                      |
|                           | 1       | 50        | 21.58           | 21.75         | 21.75         |                          |
|                           | 1       | 99        | 21.70           | 21.72         | 21.77         |                          |
|                           | 50      | 0         | 20.46           | 20.66         | 20.55         | 0-2                      |
|                           | 50      | 25        | 20.43           | 20.59         | 20.49         |                          |
|                           | 50      | 50        | 20.39           | 20.50         | 20.45         |                          |
|                           | 100     | 0         | 20.40           | 20.49         | 20.55         |                          |

**-LTE Band 4**

| LTE Band4 1.4MHz Bandwidth |         |           |                 |               |               |                                   |
|----------------------------|---------|-----------|-----------------|---------------|---------------|-----------------------------------|
| Modulation                 | RB Size | RB Offset | Low Channel     | Mid Channel   | High Channel  | MPR<br>Allowed<br>Per<br>3GPP[dB] |
|                            |         |           | 19957           | 20175         | 20393         |                                   |
|                            |         |           | (1 710.7 MHz)   | (1 732.5 MHz) | (1 754.3 MHz) |                                   |
|                            |         |           | Conducted Power |               |               |                                   |
|                            |         |           | [dBm]           | [dBm]         | [dBm]         |                                   |
| QPSK                       | 1       | 0         | 22.45           | 22.40         | 22.27         | 0                                 |
|                            | 1       | 2         | 22.65           | 22.49         | 22.31         |                                   |
|                            | 1       | 5         | 22.47           | 22.42         | 22.27         |                                   |
|                            | 3       | 0         | 22.54           | 22.41         | 22.25         |                                   |
|                            | 3       | 2         | 22.60           | 22.43         | 22.34         |                                   |
|                            | 3       | 3         | 22.56           | 22.42         | 22.27         |                                   |
|                            | 6       | 0         | 21.51           | 21.38         | 21.27         | 0-1                               |
| 16QAM                      | 1       | 0         | 21.75           | 21.71         | 21.54         | 0-1                               |
|                            | 1       | 2         | 21.92           | 21.71         | 21.64         |                                   |
|                            | 1       | 5         | 21.83           | 21.62         | 21.51         |                                   |
|                            | 3       | 0         | 21.65           | 21.51         | 21.38         |                                   |
|                            | 3       | 2         | 21.67           | 21.59         | 21.38         |                                   |
|                            | 3       | 3         | 21.64           | 21.54         | 21.38         |                                   |
|                            | 6       | 0         | 20.56           | 20.48         | 20.33         | 0-2                               |

| LTE Band4 3MHz Bandwidth |         |           |                 |               |               |                                   |
|--------------------------|---------|-----------|-----------------|---------------|---------------|-----------------------------------|
| Modulation               | RB Size | RB Offset | Low Channel     | Mid Channel   | High Channel  | MPR<br>Allowed<br>Per<br>3GPP[dB] |
|                          |         |           | 19965           | 20175         | 20385         |                                   |
|                          |         |           | (1 711.5 MHz)   | (1 732.5 MHz) | (1 753.5 MHz) |                                   |
|                          |         |           | Conducted Power |               |               |                                   |
|                          |         |           | [dBm]           | [dBm]         | [dBm]         |                                   |
| QPSK                     | 1       | 0         | 22.61           | 22.48         | 22.24         | 0                                 |
|                          | 1       | 7         | 22.57           | 22.59         | 22.40         |                                   |
|                          | 1       | 14        | 22.52           | 22.51         | 22.32         |                                   |
|                          | 8       | 0         | 21.59           | 21.50         | 21.25         | 0-1                               |
|                          | 8       | 4         | 21.53           | 21.51         | 21.35         |                                   |
|                          | 8       | 7         | 21.48           | 21.48         | 21.34         |                                   |
|                          | 15      | 0         | 21.47           | 21.45         | 21.30         |                                   |
| 16QAM                    | 1       | 0         | 21.86           | 21.75         | 21.54         | 0-1                               |
|                          | 1       | 7         | 21.80           | 21.88         | 21.70         |                                   |
|                          | 1       | 14        | 21.73           | 21.67         | 21.63         |                                   |
|                          | 8       | 0         | 20.64           | 20.53         | 20.30         | 0-2                               |
|                          | 8       | 4         | 20.59           | 20.57         | 20.40         |                                   |
|                          | 8       | 7         | 20.54           | 20.55         | 20.37         |                                   |
|                          | 15      | 0         | 20.52           | 20.50         | 20.39         |                                   |

| LTE Band4 5MHz Bandwidth |         |           |                 |               |               |                          |
|--------------------------|---------|-----------|-----------------|---------------|---------------|--------------------------|
| Modulation               | RB Size | RB Offset | Low Channel     | Mid Channel   | High Channel  | MPR Allowed Per 3GPP[dB] |
|                          |         |           | 19975           | 20175         | 20375         |                          |
|                          |         |           | (1 712.5 MHz)   | (1 732.5 MHz) | (1 752.5 MHz) |                          |
|                          |         |           | Conducted Power |               |               |                          |
|                          |         |           | [dBm]           | [dBm]         | [dBm]         |                          |
| QPSK                     | 1       | 0         | 22.67           | 22.52         | 22.45         | 0                        |
|                          | 1       | 12        | 22.51           | 22.51         | 22.50         |                          |
|                          | 1       | 24        | 22.47           | 22.48         | 22.45         |                          |
|                          | 12      | 0         | 21.61           | 21.48         | 21.52         | 0-1                      |
|                          | 12      | 6         | 21.54           | 21.51         | 21.50         |                          |
|                          | 12      | 13        | 21.49           | 21.50         | 21.48         |                          |
|                          | 25      | 0         | 21.50           | 21.49         | 21.51         |                          |
| 16QAM                    | 1       | 0         | 21.91           | 21.80         | 21.68         | 0-1                      |
|                          | 1       | 12        | 21.66           | 21.72         | 21.76         |                          |
|                          | 1       | 24        | 21.80           | 21.80         | 21.71         |                          |
|                          | 12      | 0         | 20.64           | 20.53         | 20.55         | 0-2                      |
|                          | 12      | 6         | 20.62           | 20.58         | 20.56         |                          |
|                          | 12      | 13        | 20.54           | 20.53         | 20.54         |                          |
|                          | 25      | 0         | 20.54           | 20.51         | 20.56         |                          |

| LTE Band4 10MHz Bandwidth |         |           |                  |               |               |                                |
|---------------------------|---------|-----------|------------------|---------------|---------------|--------------------------------|
| Modulation                | RB Size | RB Offset | Low Channel      | Mid Channel   | High Channel  | MPR Allowed<br>Per<br>3GPP[dB] |
|                           |         |           | 20000            | 20175         | 20350         |                                |
|                           |         |           | (1 715.0<br>MHz) | (1 732.5 MHz) | (1 750.0 MHz) |                                |
|                           |         |           | Conducted Power  |               |               |                                |
|                           |         |           | [dBm]            | [dBm]         | [dBm]         |                                |
| QPSK                      | 1       | 0         | 22.66            | 22.57         | 22.44         | 0                              |
|                           | 1       | 25        | 22.49            | 22.52         | 22.32         |                                |
|                           | 1       | 49        | 22.47            | 22.46         | 22.36         |                                |
|                           | 25      | 0         | 21.55            | 21.53         | 21.49         | 0-1                            |
|                           | 25      | 12        | 21.54            | 21.55         | 21.35         |                                |
|                           | 25      | 25        | 21.51            | 21.50         | 21.27         |                                |
|                           | 50      | 0         | 21.53            | 21.52         | 21.34         |                                |
| 16QAM                     | 1       | 0         | 21.99            | 21.80         | 21.69         | 0-1                            |
|                           | 1       | 25        | 21.72            | 21.81         | 21.64         |                                |
|                           | 1       | 49        | 21.78            | 21.63         | 21.64         |                                |
|                           | 25      | 0         | 20.58            | 20.53         | 20.52         | 0-2                            |
|                           | 25      | 12        | 20.54            | 20.54         | 20.43         |                                |
|                           | 25      | 25        | 20.51            | 20.52         | 20.32         |                                |
|                           | 50      | 0         | 20.56            | 20.53         | 20.41         |                                |

| LTE Band4 15MHz Bandwidth |         |           |                 |               |               |                          |
|---------------------------|---------|-----------|-----------------|---------------|---------------|--------------------------|
| Modulation                | RB Size | RB Offset | Low Channel     | Mid Channel   | High Channel  | MPR Allowed Per 3GPP[dB] |
|                           |         |           | 20025           | 20175         | 20325         |                          |
|                           |         |           | (1 717.5 MHz)   | (1 732.5 MHz) | (1 747.5 MHz) |                          |
|                           |         |           | Conducted Power |               |               |                          |
|                           |         |           | [dBm]           | [dBm]         | [dBm]         |                          |
| QPSK                      | 1       | 0         | 22.77           | 22.61         | 22.58         | 0                        |
|                           | 1       | 36        | 22.46           | 22.53         | 22.31         |                          |
|                           | 1       | 74        | 22.42           | 22.51         | 22.43         |                          |
|                           | 36      | 0         | 21.57           | 21.58         | 21.41         | 0-1                      |
|                           | 36      | 18        | 21.53           | 21.57         | 21.38         |                          |
|                           | 36      | 37        | 21.42           | 21.42         | 21.38         |                          |
|                           | 75      | 0         | 21.54           | 21.54         | 21.40         |                          |
| 16QAM                     | 1       | 0         | 21.98           | 21.88         | 21.90         | 0-1                      |
|                           | 1       | 36        | 21.77           | 21.80         | 21.63         |                          |
|                           | 1       | 74        | 21.70           | 21.75         | 21.65         |                          |
|                           | 36      | 0         | 20.57           | 20.59         | 20.46         | 0-2                      |
|                           | 36      | 18        | 20.56           | 20.59         | 20.44         |                          |
|                           | 36      | 37        | 20.45           | 20.47         | 20.44         |                          |
|                           | 75      | 0         | 20.56           | 20.57         | 20.45         |                          |

| LTE Band4 20MHz Bandwidth |         |           |                 |               |               |                          |
|---------------------------|---------|-----------|-----------------|---------------|---------------|--------------------------|
| Modulation                | RB Size | RB Offset | Low Channel     | Mid Channel   | High Channel  | MPR Allowed Per 3GPP[dB] |
|                           |         |           | 20050           | 20175         | 20300         |                          |
|                           |         |           | (1 720.0 MHz)   | (1 732.5 MHz) | (1 745.0 MHz) |                          |
|                           |         |           | Conducted Power |               |               |                          |
|                           |         |           | [dBm]           | [dBm]         | [dBm]         |                          |
| QPSK                      | 1       | 0         | 22.83           | 22.55         | 22.45         | 0                        |
|                           | 1       | 50        | 22.90           | 22.59         | 22.56         |                          |
|                           | 1       | 99        | 22.66           | 22.50         | 22.46         |                          |
|                           | 50      | 0         | 22.79           | 22.54         | 22.50         | 0-1                      |
|                           | 50      | 25        | 22.67           | 22.59         | 22.49         |                          |
|                           | 50      | 13        | 22.62           | 22.59         | 22.48         |                          |
|                           | 100     | 0         | 22.80           | 22.56         | 21.47         |                          |
| 16QAM                     | 1       | 0         | 22.02           | 21.87         | 21.77         | 0-1                      |
|                           | 1       | 50        | 22.11           | 21.95         | 21.86         |                          |
|                           | 1       | 99        | 21.88           | 21.83         | 21.80         |                          |
|                           | 50      | 0         | 21.93           | 21.63         | 21.58         | 0-2                      |
|                           | 50      | 25        | 21.86           | 21.67         | 21.54         |                          |
|                           | 50      | 50        | 21.77           | 21.63         | 21.55         |                          |
|                           | 100     | 0         | 21.82           | 21.62         | 20.49         |                          |

**-LTE Band 5**

| LTE Band5 1.4MHz Bandwidth |         |           |                 |             |              |                          |
|----------------------------|---------|-----------|-----------------|-------------|--------------|--------------------------|
| Modulation                 | RB Size | RB Offset | Low Channel     | Mid Channel | High Channel | MPR Allowed Per 3GPP[dB] |
|                            |         |           | 20407           | 20525       | 20643        |                          |
|                            |         |           | (824.7 MHz)     | (836.5 MHz) | (848.3 MHz)  |                          |
|                            |         |           | Conducted Power |             |              |                          |
|                            |         |           | [dBm]           | [dBm]       | [dBm]        |                          |
| QPSK                       | 1       | 0         | 22.57           | 22.80       | 22.59        | 0                        |
|                            | 1       | 2         | 22.63           | 22.86       | 22.65        |                          |
|                            | 1       | 5         | 22.64           | 22.76       | 22.72        |                          |
|                            | 3       | 0         | 22.53           | 22.78       | 22.63        |                          |
|                            | 3       | 2         | 22.59           | 22.83       | 22.64        |                          |
|                            | 3       | 3         | 22.68           | 22.78       | 22.69        |                          |
|                            | 6       | 0         | 21.61           | 21.76       | 21.58        | 0-1                      |
| 16QAM                      | 1       | 0         | 21.93           | 22.09       | 22.03        | 0-1                      |
|                            | 1       | 2         | 22.01           | 22.23       | 22.11        |                          |
|                            | 1       | 5         | 21.96           | 22.05       | 22.04        |                          |
|                            | 3       | 0         | 21.81           | 21.88       | 21.83        |                          |
|                            | 3       | 2         | 21.81           | 21.94       | 21.89        |                          |
|                            | 3       | 3         | 21.85           | 21.92       | 21.87        |                          |
|                            | 6       | 0         | 20.73           | 20.80       | 20.76        | 0-2                      |

| LTE Band5 3MHz Bandwidth |         |           |                 |             |              |                          |
|--------------------------|---------|-----------|-----------------|-------------|--------------|--------------------------|
| Modulation               | RB Size | RB Offset | Low Channel     | Mid Channel | High Channel | MPR Allowed Per 3GPP[dB] |
|                          |         |           | 20415           | 20525       | 20635        |                          |
|                          |         |           | (825.5 MHz)     | (836.5 MHz) | (847.5 MHz)  |                          |
|                          |         |           | Conducted Power |             |              |                          |
|                          |         |           | [dBm]           | [dBm]       | [dBm]        |                          |
| QPSK                     | 1       | 0         | 22.72           | 22.88       | 23.00        | 0                        |
|                          | 1       | 7         | 22.82           | 22.93       | 22.84        |                          |
|                          | 1       | 14        | 22.79           | 22.83       | 22.71        |                          |
|                          | 8       | 0         | 21.83           | 21.85       | 21.81        | 0-1                      |
|                          | 8       | 4         | 21.86           | 21.87       | 21.82        |                          |
|                          | 8       | 7         | 21.82           | 21.81       | 21.80        |                          |
|                          | 15      | 0         | 21.82           | 21.82       | 21.83        |                          |
| 16QAM                    | 1       | 0         | 22.05           | 22.12       | 22.07        | 0-1                      |
|                          | 1       | 7         | 22.25           | 22.25       | 22.21        |                          |
|                          | 1       | 14        | 22.06           | 22.12       | 22.02        |                          |
|                          | 8       | 0         | 20.92           | 20.88       | 22.87        | 0-2                      |
|                          | 8       | 4         | 20.93           | 20.90       | 22.92        |                          |
|                          | 8       | 7         | 20.87           | 20.87       | 20.81        |                          |
|                          | 15      | 0         | 20.84           | 20.85       | 20.84        |                          |

| LTE Band5 5MHz Bandwidth |         |           |                 |             |              |                          |
|--------------------------|---------|-----------|-----------------|-------------|--------------|--------------------------|
| Modulation               | RB Size | RB Offset | Low Channel     | Mid Channel | High Channel | MPR Allowed Per 3GPP[dB] |
|                          |         |           | 20425           | 20525       | 20625        |                          |
|                          |         |           | (826.5 MHz)     | (836.5 MHz) | (846.5 MHz)  |                          |
|                          |         |           | Conducted Power |             |              |                          |
|                          |         |           | [dBm]           | [dBm]       | [dBm]        |                          |
| QPSK                     | 1       | 0         | 22.66           | 22.86       | 22.71        | 0                        |
|                          | 1       | 12        | 22.79           | 22.84       | 22.82        |                          |
|                          | 1       | 24        | 22.77           | 22.84       | 22.83        |                          |
|                          | 12      | 0         | 21.85           | 21.83       | 21.84        | 0-1                      |
|                          | 12      | 6         | 21.84           | 21.86       | 21.86        |                          |
|                          | 12      | 13        | 21.81           | 21.80       | 21.80        |                          |
|                          | 25      | 0         | 21.81           | 21.84       | 21.79        |                          |
| 16QAM                    | 1       | 0         | 22.12           | 22.16       | 22.10        | 0-1                      |
|                          | 1       | 12        | 22.14           | 22.05       | 22.13        |                          |
|                          | 1       | 24        | 22.01           | 22.10       | 22.08        |                          |
|                          | 12      | 0         | 20.89           | 20.91       | 20.90        | 0-2                      |
|                          | 12      | 6         | 20.90           | 20.84       | 20.85        |                          |
|                          | 12      | 13        | 20.84           | 20.88       | 20.86        |                          |
|                          | 25      | 0         | 20.81           | 20.88       | 20.87        |                          |

| LTE Band5 10MHz Bandwidth |         |           |                 |             |              |                                |
|---------------------------|---------|-----------|-----------------|-------------|--------------|--------------------------------|
| Modulation                | RB Size | RB Offset | Low Channel     | Mid Channel | High Channel | MPR Allowed<br>Per<br>3GPP[dB] |
|                           |         |           | 20450           | 20525       | 20600        |                                |
|                           |         |           | (829.0 MHz)     | (836.5 MHz) | (844.0 MHz)  |                                |
|                           |         |           | Conducted Power |             |              |                                |
|                           |         |           | [dBm]           | [dBm]       | [dBm]        |                                |
| QPSK                      | 1       | 0         | 22.72           | 22.84       | 22.89        | 0                              |
|                           | 1       | 25        | 22.78           | 22.82       | 22.94        |                                |
|                           | 1       | 49        | 22.89           | 22.87       | 22.86        |                                |
|                           | 25      | 0         | 22.72           | 22.84       | 22.92        | 0-1                            |
|                           | 25      | 12        | 22.79           | 22.87       | 22.95        |                                |
|                           | 25      | 25        | 22.85           | 22.85       | 22.92        |                                |
|                           | 50      | 0         | 22.80           | 21.83       | 21.88        |                                |
| 16QAM                     | 1       | 0         | 22.03           | 22.17       | 22.34        | 0-1                            |
|                           | 1       | 25        | 22.10           | 22.20       | 22.27        |                                |
|                           | 1       | 49        | 22.17           | 22.16       | 22.12        |                                |
|                           | 25      | 0         | 21.78           | 21.90       | 21.96        | 0-2                            |
|                           | 25      | 12        | 21.95           | 21.92       | 21.95        |                                |
|                           | 25      | 25        | 21.96           | 21.91       | 21.95        |                                |
|                           | 50      | 0         | 21.90           | 20.87       | 20.95        |                                |

**-LTE Band 7**

| LTE Band7 5MHz Bandwidth |         |           |                 |               |               |                          |
|--------------------------|---------|-----------|-----------------|---------------|---------------|--------------------------|
| Modulation               | RB Size | RB Offset | Low Channel     | Mid Channel   | High Channel  | MPR Allowed Per 3GPP[dB] |
|                          |         |           | 20775           | 21100         | 21425         |                          |
|                          |         |           | (2 502.5 MHz)   | (2 535.0 MHz) | (2 567.5 MHz) |                          |
|                          |         |           | Conducted Power |               |               |                          |
|                          |         |           | [dBm]           | [dBm]         | [dBm]         |                          |
| QPSK                     | 1       | 0         | 22.22           | 22.48         | 22.40         | 0                        |
|                          | 1       | 12        | 22.16           | 22.43         | 22.34         |                          |
|                          | 1       | 24        | 22.10           | 22.46         | 22.24         |                          |
|                          | 12      | 0         | 21.30           | 21.55         | 21.32         | 0-1                      |
|                          | 12      | 6         | 21.29           | 21.53         | 21.34         |                          |
|                          | 12      | 13        | 21.25           | 21.47         | 21.28         |                          |
|                          | 25      | 0         | 21.26           | 21.48         | 21.28         |                          |
| 16QAM                    | 1       | 0         | 21.65           | 21.92         | 21.64         | 0-1                      |
|                          | 1       | 12        | 21.57           | 21.81         | 21.60         |                          |
|                          | 1       | 24        | 21.54           | 21.81         | 21.58         |                          |
|                          | 12      | 0         | 20.33           | 20.58         | 20.39         | 0-2                      |
|                          | 12      | 6         | 20.36           | 20.57         | 20.38         |                          |
|                          | 12      | 13        | 20.28           | 20.53         | 20.34         |                          |
|                          | 25      | 0         | 20.32           | 20.53         | 20.33         |                          |

| LTE Band7 10MHz Bandwidth |         |           |                 |               |               |                          |
|---------------------------|---------|-----------|-----------------|---------------|---------------|--------------------------|
| Modulation                | RB Size | RB Offset | Low Channel     | Mid Channel   | High Channel  | MPR Allowed Per 3GPP[dB] |
|                           |         |           | 20800           | 21100         | 21400         |                          |
|                           |         |           | (2 505.0 MHz)   | (2 535.0 MHz) | (2 565.0 MHz) |                          |
|                           |         |           | Conducted Power |               |               |                          |
|                           |         |           | [dBm]           | [dBm]         | [dBm]         |                          |
| QPSK                      | 1       | 0         | 22.24           | 22.60         | 22.59         | 0                        |
|                           | 1       | 25        | 22.12           | 22.52         | 22.35         |                          |
|                           | 1       | 49        | 22.06           | 22.44         | 22.18         |                          |
|                           | 25      | 0         | 21.31           | 21.58         | 21.52         | 0-1                      |
|                           | 25      | 12        | 21.27           | 21.57         | 21.36         |                          |
|                           | 25      | 25        | 21.17           | 21.45         | 21.26         |                          |
|                           | 50      | 0         | 21.26           | 21.53         | 21.33         |                          |
| 16QAM                     | 1       | 0         | 21.71           | 22.02         | 21.90         | 0-1                      |
|                           | 1       | 25        | 21.60           | 21.82         | 21.60         |                          |
|                           | 1       | 49        | 21.43           | 21.77         | 21.44         |                          |
|                           | 25      | 0         | 20.32           | 20.58         | 20.53         | 0-2                      |
|                           | 25      | 12        | 20.29           | 20.57         | 20.36         |                          |
|                           | 25      | 25        | 20.20           | 20.51         | 20.31         |                          |
|                           | 50      | 0         | 20.27           | 20.52         | 20.38         |                          |

| LTE Band7 15MHz Bandwidth |         |           |                        |               |               |                                   |
|---------------------------|---------|-----------|------------------------|---------------|---------------|-----------------------------------|
| Modulation                | RB Size | RB Offset | Low Channel            | Mid Channel   | High Channel  | MPR<br>Allowed<br>Per<br>3GPP[dB] |
|                           |         |           | 20825                  | 21100         | 21375         |                                   |
|                           |         |           | (2 507.5 MHz)          | (2 535.0 MHz) | (2 562.5 MHz) |                                   |
|                           |         |           | Conducted Output Power |               |               |                                   |
|                           |         |           | (dB m)                 | (dB m)        | (dB m)        |                                   |
| QPSK                      | 1       | 0         | 22.44                  | 22.66         | 22.69         | 0                                 |
|                           | 1       | 36        | 22.23                  | 22.53         | 22.47         |                                   |
|                           | 1       | 74        | 22.22                  | 22.40         | 22.22         |                                   |
|                           | 36      | 0         | 21.33                  | 21.59         | 21.57         | 0-1                               |
|                           | 36      | 18        | 21.25                  | 21.59         | 21.51         |                                   |
|                           | 36      | 37        | 21.15                  | 21.49         | 21.29         |                                   |
|                           | 75      | 0         | 21.24                  | 21.51         | 21.51         |                                   |
| 16QAM                     | 1       | 0         | 21.75                  | 21.89         | 22.08         | 0-1                               |
|                           | 1       | 36        | 21.49                  | 21.89         | 21.77         |                                   |
|                           | 1       | 74        | 21.67                  | 21.79         | 21.49         |                                   |
|                           | 36      | 0         | 20.51                  | 20.64         | 20.60         | 0-2                               |
|                           | 36      | 18        | 20.41                  | 20.56         | 20.55         |                                   |
|                           | 36      | 37        | 20.30                  | 20.47         | 20.29         |                                   |
|                           | 75      | 0         | 20.35                  | 20.56         | 20.52         |                                   |

| LTE Band7 20MHz Bandwidth |         |           |                 |               |               |                                |
|---------------------------|---------|-----------|-----------------|---------------|---------------|--------------------------------|
| Modulation                | RB Size | RB Offset | Low Channel     | Mid Channel   | High Channel  | MPR Allowed<br>Per<br>3GPP[dB] |
|                           |         |           | 20850           | 21100         | 21350         |                                |
|                           |         |           | (2 510.0 MHz)   | (2 535.0 MHz) | (2 560.0 MHz) |                                |
|                           |         |           | Conducted Power |               |               |                                |
|                           |         |           | [dBm]           | [dBm]         | [dBm]         |                                |
| QPSK                      | 1       | 0         | 22.73           | 22.72         | 22.75         | 0                              |
|                           | 1       | 50        | 22.15           | 22.54         | 22.50         |                                |
|                           | 1       | 99        | 22.29           | 22.49         | 22.26         |                                |
|                           | 50      | 0         | 21.71           | 21.70         | 21.73         | 0-1                            |
|                           | 50      | 25        | 21.33           | 21.54         | 21.54         |                                |
|                           | 50      | 13        | 21.32           | 21.46         | 21.32         |                                |
|                           | 100     | 0         | 21.47           | 21.56         | 21.43         |                                |
| 16QAM                     | 1       | 0         | 21.89           | 21.94         | 22.10         | 0-1                            |
|                           | 1       | 50        | 21.79           | 21.84         | 21.80         |                                |
|                           | 1       | 99        | 21.66           | 21.74         | 21.57         |                                |
|                           | 50      | 0         | 20.48           | 20.68         | 20.68         | 0-2                            |
|                           | 50      | 25        | 20.39           | 20.61         | 20.55         |                                |
|                           | 50      | 50        | 20.34           | 20.48         | 20.33         |                                |
|                           | 100     | 0         | 20.47           | 20.58         | 20.44         |                                |

**-LTE Band 12**

| LTE Band12 1.4MHz Bandwidth |         |           |                 |             |              |                          |
|-----------------------------|---------|-----------|-----------------|-------------|--------------|--------------------------|
| Modulation                  | RB Size | RB Offset | Low Channel     | Mid Channel | High Channel | MPR Allowed Per 3GPP[dB] |
|                             |         |           | 23017           | 23095       | 23173        |                          |
|                             |         |           | (699.7 MHz)     | (707.5 MHz) | (715.3 MHz)  |                          |
|                             |         |           | Conducted Power |             |              |                          |
|                             |         |           | [dBm]           | [dBm]       | [dBm]        |                          |
| QPSK                        | 1       | 0         | 22.82           | 22.91       | 22.83        | 0                        |
|                             | 1       | 2         | 23.00           | 22.96       | 22.83        |                          |
|                             | 1       | 5         | 22.92           | 22.87       | 22.62        |                          |
|                             | 3       | 0         | 22.88           | 22.93       | 22.78        | 0-1                      |
|                             | 3       | 2         | 22.99           | 22.93       | 22.75        |                          |
|                             | 3       | 3         | 22.91           | 22.88       | 22.69        |                          |
|                             | 6       | 0         | 21.95           | 21.89       | 21.76        |                          |
| 16QAM                       | 1       | 0         | 22.08           | 22.17       | 22.15        | 0-1                      |
|                             | 1       | 2         | 22.30           | 22.23       | 22.10        |                          |
|                             | 1       | 5         | 22.19           | 22.12       | 21.99        |                          |
|                             | 3       | 0         | 21.96           | 22.03       | 21.90        | 0-2                      |
|                             | 3       | 2         | 22.10           | 22.03       | 21.85        |                          |
|                             | 3       | 3         | 22.13           | 21.97       | 21.79        |                          |
|                             | 6       | 0         | 21.08           | 20.95       | 20.89        |                          |

| LTE Band12 3MHz Bandwidth |         |           |                 |             |              |                          |
|---------------------------|---------|-----------|-----------------|-------------|--------------|--------------------------|
| Modulation                | RB Size | RB Offset | Low Channel     | Mid Channel | High Channel | MPR Allowed Per 3GPP[dB] |
|                           |         |           | 23025           | 23095       | 23655        |                          |
|                           |         |           | (700.5 MHz)     | (707.5 MHz) | (714.5 MHz)  |                          |
|                           |         |           | Conducted Power |             |              |                          |
|                           |         |           | [dBm]           | [dBm]       | [dBm]        |                          |
| QPSK                      | 1       | 0         | 22.88           | 22.92       | 22.91        | 0                        |
|                           | 1       | 7         | 23.24           | 23.02       | 23.12        |                          |
|                           | 1       | 14        | 22.96           | 22.91       | 22.95        |                          |
|                           | 8       | 0         | 22.09           | 22.00       | 22.05        | 0-1                      |
|                           | 8       | 4         | 22.15           | 22.00       | 22.13        |                          |
|                           | 8       | 7         | 22.02           | 21.97       | 21.98        |                          |
|                           | 15      | 0         | 22.03           | 21.98       | 22.01        |                          |
| 16QAM                     | 1       | 0         | 22.30           | 22.22       | 22.26        | 0-1                      |
|                           | 1       | 7         | 22.49           | 22.30       | 22.42        |                          |
|                           | 1       | 14        | 22.24           | 22.24       | 22.22        |                          |
|                           | 8       | 0         | 21.19           | 21.09       | 21.16        | 0-2                      |
|                           | 8       | 4         | 21.21           | 21.08       | 21.19        |                          |
|                           | 8       | 7         | 21.05           | 21.00       | 21.03        |                          |
|                           | 15      | 0         | 21.05           | 21.05       | 21.04        |                          |

| LTE Band12 5MHz Bandwidth |         |           |                 |             |              |                                   |
|---------------------------|---------|-----------|-----------------|-------------|--------------|-----------------------------------|
| Modulation                | RB Size | RB Offset | Low Channel     | Mid Channel | High Channel | MPR<br>Allowed<br>Per<br>3GPP[dB] |
|                           |         |           | 23035           | 23095       | 23155        |                                   |
|                           |         |           | (701.5 MHz)     | (707.5 MHz) | (713.5 MHz)  |                                   |
|                           |         |           | Conducted Power |             |              |                                   |
|                           |         |           | [dBm]           | [dBm]       | [dBm]        |                                   |
| QPSK                      | 1       | 0         | 22.83           | 22.91       | 22.89        | 0                                 |
|                           | 1       | 12        | 23.21           | 23.03       | 23.13        |                                   |
|                           | 1       | 24        | 22.95           | 22.92       | 22.94        |                                   |
|                           | 12      | 0         | 22.10           | 21.98       | 22.04        | 0-1                               |
|                           | 12      | 6         | 22.13           | 22.06       | 22.12        |                                   |
|                           | 12      | 13        | 22.00           | 21.96       | 21.97        |                                   |
|                           | 25      | 0         | 22.04           | 21.98       | 22.00        |                                   |
| 16QAM                     | 1       | 0         | 22.29           | 22.24       | 22.22        | 0-1                               |
|                           | 1       | 12        | 22.48           | 22.25       | 22.39        |                                   |
|                           | 1       | 24        | 22.31           | 22.21       | 22.18        |                                   |
|                           | 12      | 0         | 21.21           | 21.05       | 21.11        | 0-2                               |
|                           | 12      | 6         | 21.18           | 21.07       | 21.17        |                                   |
|                           | 12      | 13        | 21.06           | 20.98       | 21.02        |                                   |
|                           | 25      | 0         | 21.02           | 21.05       | 21.01        |                                   |

| LTE Band12 10MHz Bandwidth |         |           |                 |             |              |                          |
|----------------------------|---------|-----------|-----------------|-------------|--------------|--------------------------|
| Modulation                 | RB Size | RB Offset | Low Channel     | Mid Channel | High Channel | MPR Allowed Per 3GPP[dB] |
|                            |         |           | 23060           | 23095       | 23130        |                          |
|                            |         |           | (704.0 MHz)     | (707.5 MHz) | (711.0 MHz)  |                          |
|                            |         |           | Conducted Power |             |              |                          |
|                            |         |           | [dBm]           | [dBm]       | [dBm]        |                          |
| QPSK                       | 1       | 0         | 23.01           | 22.92       | 22.88        | 0                        |
|                            | 1       | 25        | 23.19           | 23.04       | 23.11        |                          |
|                            | 1       | 49        | 22.96           | 22.93       | 22.96        |                          |
|                            | 25      | 0         | 22.08           | 21.95       | 22.03        | 0-1                      |
|                            | 25      | 12        | 22.11           | 22.05       | 22.13        |                          |
|                            | 25      | 25        | 22.04           | 21.94       | 21.95        |                          |
|                            | 50      | 0         | 22.03           | 21.95       | 22.04        |                          |
| 16QAM                      | 1       | 0         | 22.28           | 22.26       | 22.21        | 0-1                      |
|                            | 1       | 25        | 22.47           | 22.24       | 22.35        |                          |
|                            | 1       | 49        | 22.29           | 22.25       | 22.15        |                          |
|                            | 25      | 0         | 21.22           | 21.01       | 21.13        | 0-2                      |
|                            | 25      | 12        | 21.14           | 22.05       | 21.14        |                          |
|                            | 25      | 25        | 21.05           | 20.95       | 21.05        |                          |
|                            | 50      | 0         | 21.03           | 21.04       | 21.03        |                          |

**-LTE Band 13**

| LTE Band13 5MHz Bandwidth |         |           |                 |             |              |                          |
|---------------------------|---------|-----------|-----------------|-------------|--------------|--------------------------|
| Modulation                | RB Size | RB Offset | Low Channel     | Mid Channel | High Channel | MPR Allowed Per 3GPP[dB] |
|                           |         |           | 23205           | 23230       | 23255        |                          |
|                           |         |           | (779.5 MHz)     | (782.0 MHz) | (784.5 MHz)  |                          |
|                           |         |           | Conducted Power |             |              |                          |
|                           |         |           | [dBm]           | [dBm]       | [dBm]        |                          |
| QPSK                      | 1       | 0         | 23.32           | 23.27       | 23.33        | 0                        |
|                           | 1       | 12        | 23.31           | 23.29       | 23.30        |                          |
|                           | 1       | 24        | 23.17           | 23.27       | 23.31        |                          |
|                           | 12      | 0         | 22.31           | 22.25       | 22.50        | 0-1                      |
|                           | 12      | 6         | 22.36           | 22.21       | 22.31        |                          |
|                           | 12      | 13        | 22.25           | 22.23       | 22.21        |                          |
|                           | 25      | 0         | 22.37           | 22.24       | 22.35        |                          |
| 16QAM                     | 1       | 0         | 22.56           | 22.59       | 22.85        | 0-1                      |
|                           | 1       | 12        | 22.58           | 22.59       | 22.51        |                          |
|                           | 1       | 24        | 22.44           | 22.60       | 22.55        |                          |
|                           | 12      | 0         | 21.34           | 21.27       | 21.32        | 0-2                      |
|                           | 12      | 6         | 21.35           | 21.23       | 21.30        |                          |
|                           | 12      | 13        | 21.27           | 21.27       | 21.33        |                          |
|                           | 25      | 0         | 21.33           | 21.28       | 21.21        |                          |

| LTE Band13 10MHz Bandwidth |         |           |                 |                          |
|----------------------------|---------|-----------|-----------------|--------------------------|
| Modulation                 | RB Size | RB Offset | Mid Channel     | MPR Allowed Per 3GPP[dB] |
|                            |         |           | 23230           |                          |
|                            |         |           | (782.0 MHz)     |                          |
|                            |         |           | Conducted Power |                          |
|                            |         |           | [dBm]           |                          |
| QPSK                       | 1       | 0         | 23.42           | 0                        |
|                            | 1       | 25        | 23.23           |                          |
|                            | 1       | 49        | 23.20           |                          |
|                            | 25      | 0         | 22.44           | 0-1                      |
|                            | 25      | 12        | 22.24           |                          |
|                            | 25      | 25        | 22.18           |                          |
|                            | 50      | 0         | 22.26           |                          |
| 16QAM                      | 1       | 0         | 22.59           | 0-1                      |
|                            | 1       | 25        | 22.48           |                          |
|                            | 1       | 49        | 22.48           |                          |
|                            | 25      | 0         | 21.35           | 0-2                      |
|                            | 25      | 12        | 21.31           |                          |
|                            | 25      | 25        | 21.21           |                          |
|                            | 50      | 0         | 21.23           |                          |

**-LTE Band 17**

| LTE Band17 5MHz Bandwidth |         |           |                 |             |              |                          |
|---------------------------|---------|-----------|-----------------|-------------|--------------|--------------------------|
| Modulation                | RB Size | RB Offset | Low Channel     | Mid Channel | High Channel | MPR Allowed Per 3GPP[dB] |
|                           |         |           | 23755           | 23790       | 23825        |                          |
|                           |         |           | (706.5 MHz)     | (710.0 MHz) | (713.5 MHz)  |                          |
|                           |         |           | Conducted Power |             |              |                          |
|                           |         |           | [dBm]           | [dBm]       | [dBm]        |                          |
| QPSK                      | 1       | 0         | 22.77           | 22.90       | 22.44        | 0                        |
|                           | 1       | 12        | 22.81           | 22.89       | 22.41        |                          |
|                           | 1       | 24        | 22.84           | 22.89       | 22.33        |                          |
|                           | 12      | 0         | 21.94           | 21.85       | 22.67        | 0-1                      |
|                           | 12      | 6         | 21.95           | 21.86       | 22.40        |                          |
|                           | 12      | 13        | 21.87           | 21.82       | 22.52        |                          |
|                           | 25      | 0         | 21.82           | 21.82       | 22.42        |                          |
| 16QAM                     | 1       | 0         | 22.05           | 22.19       | 22.62        | 0-1                      |
|                           | 1       | 12        | 22.07           | 22.22       | 22.72        |                          |
|                           | 1       | 24        | 22.16           | 22.11       | 22.23        |                          |
|                           | 12      | 0         | 20.97           | 20.89       | 22.69        | 0-2                      |
|                           | 12      | 6         | 20.98           | 20.93       | 22.63        |                          |
|                           | 12      | 13        | 20.91           | 20.85       | 22.63        |                          |
|                           | 25      | 0         | 20.94           | 20.86       | 22.59        |                          |

| LTE Band17 10MHz Bandwidth |         |           |                 |             |              |                          |
|----------------------------|---------|-----------|-----------------|-------------|--------------|--------------------------|
| Modulation                 | RB Size | RB Offset | Low Channel     | Mid Channel | High Channel | MPR Allowed Per 3GPP[dB] |
|                            |         |           | 23780           | 23790       | 23800        |                          |
|                            |         |           | (709.0 MHz)     | (710.0 MHz) | (711.0 MHz)  |                          |
|                            |         |           | Conducted Power |             |              |                          |
|                            |         |           | [dBm]           | [dBm]       | [dBm]        |                          |
| QPSK                       | 1       | 0         | 22.88           | 22.97       | 22.78        | 0                        |
|                            | 1       | 25        | 22.92           | 22.92       | 22.27        |                          |
|                            | 1       | 49        | 22.96           | 22.75       | 22.63        |                          |
|                            | 25      | 0         | 21.56           | 21.92       | 21.98        | 0-1                      |
|                            | 25      | 12        | 21.48           | 21.86       | 22.36        |                          |
|                            | 25      | 25        | 21.38           | 21.79       | 22.60        |                          |
|                            | 50      | 0         | 21.93           | 21.85       | 22.71        |                          |
| 16QAM                      | 1       | 0         | 22.14           | 22.24       | 22.35        | 0-1                      |
|                            | 1       | 25        | 22.25           | 22.25       | 22.54        |                          |
|                            | 1       | 49        | 22.32           | 22.00       | 22.50        |                          |
|                            | 25      | 0         | 22.01           | 20.92       | 22.52        | 0-2                      |
|                            | 25      | 12        | 21.99           | 20.91       | 22.77        |                          |
|                            | 25      | 25        | 21.98           | 20.79       | 22.42        |                          |
|                            | 50      | 0         | 20.95           | 20.85       | 22.11        |                          |

**-LTE Band 25**

| LTE Band25 1.4MHz Bandwidth |         |           |                 |               |               |                                   |
|-----------------------------|---------|-----------|-----------------|---------------|---------------|-----------------------------------|
| Modulation                  | RB Size | RB Offset | Low Channel     | Mid Channel   | High Channel  | MPR<br>Allowed<br>Per<br>3GPP[dB] |
|                             |         |           | 26047           | 26365         | 26683         |                                   |
|                             |         |           | (1 850.7 MHz)   | (1 882.5 MHz) | (1 914.3 MHz) |                                   |
|                             |         |           | Conducted Power |               |               |                                   |
|                             |         |           | [dBm]           | [dBm]         | [dBm]         |                                   |
| QPSK                        | 1       | 0         | 22.56           | 22.97         | 22.79         | 0                                 |
|                             | 1       | 2         | 22.71           | 22.85         | 22.84         |                                   |
|                             | 1       | 5         | 22.58           | 23.05         | 22.82         |                                   |
|                             | 3       | 0         | 22.66           | 22.98         | 22.86         | 0-1                               |
|                             | 3       | 2         | 22.71           | 23.06         | 22.93         |                                   |
|                             | 3       | 3         | 22.67           | 22.97         | 22.91         |                                   |
|                             | 6       | 0         | 21.70           | 23.02         | 22.80         |                                   |
| 16QAM                       | 1       | 0         | 21.85           | 22.20         | 22.09         | 0-1                               |
|                             | 1       | 2         | 21.96           | 22.22         | 22.11         |                                   |
|                             | 1       | 5         | 21.98           | 22.28         | 22.14         |                                   |
|                             | 3       | 0         | 21.74           | 22.22         | 22.10         | 0-2                               |
|                             | 3       | 2         | 21.80           | 22.20         | 22.18         |                                   |
|                             | 3       | 3         | 21.81           | 22.40         | 22.09         |                                   |
|                             | 6       | 0         | 20.70           | 22.16         | 22.00         |                                   |

| LTE Band25 3MHz Bandwidth |         |           |                 |               |               |                          |
|---------------------------|---------|-----------|-----------------|---------------|---------------|--------------------------|
| Modulation                | RB Size | RB Offset | Low Channel     | Mid Channel   | High Channel  | MPR Allowed Per 3GPP[dB] |
|                           |         |           | 26055           | 26365         | 26675         |                          |
|                           |         |           | (1 851.5 MHz)   | (1 882.5 MHz) | (1 913.5 MHz) |                          |
|                           |         |           | Conducted Power |               |               |                          |
|                           |         |           | [dBm]           | [dBm]         | [dBm]         |                          |
| QPSK                      | 1       | 0         | 22.87           | 22.81         | 22.82         | 0                        |
|                           | 1       | 7         | 22.89           | 22.89         | 22.98         |                          |
|                           | 1       | 14        | 22.76           | 22.78         | 22.96         |                          |
|                           | 8       | 0         | 22.73           | 21.81         | 21.90         | 0-1                      |
|                           | 8       | 4         | 22.75           | 21.80         | 21.77         |                          |
|                           | 8       | 7         | 22.80           | 21.80         | 21.78         |                          |
|                           | 15      | 0         | 21.70           | 21.79         | 21.78         |                          |
| 16QAM                     | 1       | 0         | 21.90           | 22.03         | 22.10         | 0-1                      |
|                           | 1       | 7         | 22.06           | 22.15         | 22.10         |                          |
|                           | 1       | 14        | 22.00           | 22.09         | 22.13         |                          |
|                           | 8       | 0         | 21.90           | 20.86         | 20.86         | 0-2                      |
|                           | 8       | 4         | 21.92           | 20.89         | 20.84         |                          |
|                           | 8       | 7         | 21.92           | 20.86         | 20.82         |                          |
|                           | 15      | 0         | 20.80           | 20.84         | 20.84         |                          |

| LTE Band25 5MHz Bandwidth |         |           |                 |               |               |                          |
|---------------------------|---------|-----------|-----------------|---------------|---------------|--------------------------|
| Modulation                | RB Size | RB Offset | Low Channel     | Mid Channel   | High Channel  | MPR Allowed Per 3GPP[dB] |
|                           |         |           | 26065           | 26365         | 26665         |                          |
|                           |         |           | (1 852.5 MHz)   | (1 882.5 MHz) | (1 912.5 MHz) |                          |
|                           |         |           | Conducted Power |               |               |                          |
|                           |         |           | [dBm]           | [dBm]         | [dBm]         |                          |
| QPSK                      | 1       | 0         | 22.78           | 22.87         | 22.98         | 0                        |
|                           | 1       | 12        | 22.93           | 22.88         | 22.93         |                          |
|                           | 1       | 24        | 22.88           | 22.90         | 22.86         |                          |
|                           | 12      | 0         | 22.75           | 22.79         | 21.83         | 0-1                      |
|                           | 12      | 6         | 22.74           | 22.85         | 21.85         |                          |
|                           | 12      | 13        | 22.70           | 22.83         | 21.83         |                          |
|                           | 25      | 0         | 22.73           | 21.81         | 21.84         |                          |
| 16QAM                     | 1       | 0         | 22.04           | 22.05         | 22.20         | 0-1                      |
|                           | 1       | 12        | 22.03           | 22.07         | 22.05         |                          |
|                           | 1       | 24        | 22.04           | 22.09         | 22.13         |                          |
|                           | 12      | 0         | 21.79           | 21.87         | 20.86         | 0-2                      |
|                           | 12      | 6         | 21.85           | 21.92         | 20.88         |                          |
|                           | 12      | 13        | 21.90           | 21.91         | 20.88         |                          |
|                           | 25      | 0         | 21.84           | 20.86         | 20.85         |                          |

| LTE Band25 10MHz Bandwidth |         |           |                 |               |               |                          |
|----------------------------|---------|-----------|-----------------|---------------|---------------|--------------------------|
| Modulation                 | RB Size | RB Offset | Low Channel     | Mid Channel   | High Channel  | MPR Allowed Per 3GPP[dB] |
|                            |         |           | 26090           | 26365         | 26640         |                          |
|                            |         |           | (1 855.0 MHz)   | (1 882.5 MHz) | (1 910.0 MHz) |                          |
|                            |         |           | Conducted Power |               |               |                          |
|                            |         |           | [dBm]           | [dBm]         | [dBm]         |                          |
| QPSK                       | 1       | 0         | 22.76           | 22.79         | 22.82         | 0                        |
|                            | 1       | 25        | 22.68           | 22.83         | 22.74         |                          |
|                            | 1       | 49        | 22.87           | 22.89         | 22.90         |                          |
|                            | 25      | 0         | 22.78           | 22.84         | 22.82         | 0-1                      |
|                            | 25      | 12        | 22.81           | 22.86         | 22.80         |                          |
|                            | 25      | 25        | 22.78           | 22.84         | 22.88         |                          |
|                            | 50      | 0         | 22.81           | 21.84         | 21.77         |                          |
| 16QAM                      | 1       | 0         | 22.07           | 22.05         | 22.04         | 0-1                      |
|                            | 1       | 25        | 21.95           | 21.99         | 22.02         |                          |
|                            | 1       | 49        | 22.26           | 22.03         | 22.08         |                          |
|                            | 25      | 0         | 21.87           | 21.89         | 21.84         | 0-2                      |
|                            | 25      | 12        | 21.90           | 21.94         | 21.88         |                          |
|                            | 25      | 25        | 21.90           | 21.91         | 21.94         |                          |
|                            | 50      | 0         | 21.84           | 20.91         | 20.79         |                          |

| LTE Band25 15MHz Bandwidth |         |           |                 |               |               |                          |
|----------------------------|---------|-----------|-----------------|---------------|---------------|--------------------------|
| Modulation                 | RB Size | RB Offset | Low Channel     | Mid Channel   | High Channel  | MPR Allowed Per 3GPP[dB] |
|                            |         |           | 26115           | 26365         | 26615         |                          |
|                            |         |           | (1 857.5 MHz)   | (1 882.5 MHz) | (1 907.5 MHz) |                          |
|                            |         |           | Conducted Power |               |               |                          |
|                            |         |           | [dBm]           | [dBm]         | [dBm]         |                          |
| QPSK                       | 1       | 0         | 22.93           | 22.89         | 23.10         | 0                        |
|                            | 1       | 36        | 22.87           | 22.97         | 23.04         |                          |
|                            | 1       | 74        | 22.82           | 22.93         | 23.06         |                          |
|                            | 36      | 0         | 22.89           | 22.92         | 23.08         | 0-1                      |
|                            | 36      | 18        | 22.83           | 22.89         | 23.05         |                          |
|                            | 36      | 37        | 22.81           | 22.89         | 22.97         |                          |
|                            | 75      | 0         | 22.85           | 22.86         | 22.06         |                          |
| 16QAM                      | 1       | 0         | 21.98           | 22.17         | 22.36         | 0-1                      |
|                            | 1       | 36        | 22.10           | 22.28         | 22.28         |                          |
|                            | 1       | 74        | 22.07           | 22.15         | 22.26         |                          |
|                            | 36      | 0         | 21.96           | 22.00         | 22.14         | 0-2                      |
|                            | 36      | 18        | 21.98           | 21.99         | 22.12         |                          |
|                            | 36      | 37        | 21.90           | 21.95         | 22.02         |                          |
|                            | 75      | 0         | 22.00           | 21.93         | 21.05         |                          |

| LTE Band25 20MHz Bandwidth |         |           |                 |               |               |                          |
|----------------------------|---------|-----------|-----------------|---------------|---------------|--------------------------|
| Modulation                 | RB Size | RB Offset | Low Channel     | Mid Channel   | High Channel  | MPR Allowed Per 3GPP[dB] |
|                            |         |           | 26140           | 26365         | 26590         |                          |
|                            |         |           | (1 860.0 MHz)   | (1 882.5 MHz) | (1 905.0 MHz) |                          |
|                            |         |           | Conducted Power |               |               |                          |
|                            |         |           | [dBm]           | [dBm]         | [dBm]         |                          |
| QPSK                       | 1       | 0         | 22.92           | 22.87         | 23.15         | 0                        |
|                            | 1       | 50        | 22.97           | 22.89         | 23.11         |                          |
|                            | 1       | 99        | 22.84           | 22.90         | 23.07         |                          |
|                            | 50      | 0         | 22.86           | 22.88         | 22.98         | 0-1                      |
|                            | 50      | 25        | 22.88           | 22.91         | 22.90         |                          |
|                            | 50      | 13        | 22.81           | 22.89         | 22.87         |                          |
|                            | 100     | 0         | 22.81           | 22.93         | 22.10         |                          |
| 16QAM                      | 1       | 0         | 22.12           | 22.15         | 22.42         | 0-1                      |
|                            | 1       | 50        | 22.15           | 22.21         | 22.45         |                          |
|                            | 1       | 99        | 22.11           | 22.20         | 22.42         |                          |
|                            | 50      | 0         | 21.95           | 21.94         | 22.21         | 0-2                      |
|                            | 50      | 25        | 21.96           | 22.01         | 22.15         |                          |
|                            | 50      | 50        | 21.96           | 22.03         | 22.14         |                          |
|                            | 100     | 0         | 21.92           | 21.95         | 21.12         |                          |

**-LTE Band 41**

| LTE Band41 5MHz Bandwidth |         |           |                 |                 |               |                  |               |                           |
|---------------------------|---------|-----------|-----------------|-----------------|---------------|------------------|---------------|---------------------------|
| Modulation                | RB Size | RB Offset | Low Channel     | Low-Mid Channel | Mid Channel   | Mid-High Channel | High Channel  | MPR Allowed Per 3GPP [dB] |
|                           |         |           | 39675           | 40148           | 40620         | 41093            | 41565         |                           |
|                           |         |           | (2 498.5 MHz)   | (2 545.8 MHz)   | (2 593.0 MHz) | (2 640.3 MHz)    | (2 687.5 MHz) |                           |
|                           |         |           | Conducted Power |                 |               |                  |               |                           |
|                           |         |           | [dBm]           | [dBm]           | [dBm]         | [dBm]            | [dBm]         |                           |
| QPSK                      | 1       | 0         | 22.64           | 22.75           | 22.78         | 22.72            | 22.74         | 0                         |
|                           | 1       | 12        | 22.69           | 22.76           | 22.70         | 22.66            | 22.68         |                           |
|                           | 1       | 24        | 22.60           | 22.71           | 22.65         | 22.58            | 22.67         |                           |
|                           | 12      | 0         | 21.53           | 21.82           | 21.77         | 21.68            | 21.76         | 0-1                       |
|                           | 12      | 6         | 21.58           | 21.84           | 21.76         | 21.65            | 21.73         |                           |
|                           | 12      | 13        | 21.51           | 21.67           | 21.73         | 21.61            | 21.67         |                           |
|                           | 25      | 0         | 21.56           | 21.77           | 21.78         | 21.64            | 21.71         |                           |
| 16QAM                     | 1       | 0         | 21.52           | 22.08           | 21.80         | 21.99            | 21.81         | 0-1                       |
|                           | 1       | 12        | 21.57           | 22.09           | 21.74         | 21.87            | 21.82         |                           |
|                           | 1       | 24        | 21.47           | 22.04           | 21.64         | 21.77            | 21.70         |                           |
|                           | 12      | 0         | 20.52           | 20.81           | 20.78         | 20.72            | 20.77         | 0-2                       |
|                           | 12      | 6         | 20.63           | 20.84           | 20.80         | 20.68            | 20.73         |                           |
|                           | 12      | 13        | 20.54           | 20.87           | 20.74         | 20.64            | 20.65         |                           |
|                           | 25      | 0         | 20.53           | 20.79           | 20.75         | 20.69            | 20.73         |                           |

| LTE Band41 10MHz Bandwidth |         |           |                 |                 |               |                  |               |                           |
|----------------------------|---------|-----------|-----------------|-----------------|---------------|------------------|---------------|---------------------------|
| Modulation                 | RB Size | RB Offset | Low Channel     | Low-Mid Channel | Mid Channel   | Mid-High Channel | High Channel  | MPR Allowed Per 3GPP [dB] |
|                            |         |           | 39700           | 40160           | 40620         | 41080            | 41540         |                           |
|                            |         |           | (2 501.0 MHz)   | (2 547.0 MHz)   | (2 593.0 MHz) | (2 639.0 MHz)    | (2 685.0 MHz) |                           |
|                            |         |           | Conducted Power |                 |               |                  |               |                           |
|                            |         |           | [dBm]           | [dBm]           | [dBm]         | [dBm]            | [dBm]         |                           |
| QPSK                       | 1       | 0         | 22.62           | 22.76           | 22.77         | 22.79            | 22.78         | 0                         |
|                            | 1       | 25        | 22.56           | 22.80           | 22.74         | 22.65            | 22.69         |                           |
|                            | 1       | 49        | 22.41           | 22.64           | 22.72         | 22.44            | 22.71         |                           |
|                            | 25      | 0         | 21.57           | 21.88           | 21.81         | 21.72            | 21.96         | 0-1                       |
|                            | 25      | 12        | 21.62           | 21.84           | 21.75         | 21.65            | 21.78         |                           |
|                            | 25      | 25        | 21.53           | 21.71           | 21.67         | 21.61            | 21.84         |                           |
|                            | 50      | 0         | 21.49           | 21.79           | 21.76         | 21.64            | 21.89         |                           |
| 16QAM                      | 1       | 0         | 21.55           | 22.04           | 21.84         | 22.09            | 22.27         | 0-1                       |
|                            | 1       | 25        | 21.54           | 22.01           | 21.74         | 21.94            | 21.70         |                           |
|                            | 1       | 49        | 21.46           | 21.98           | 21.81         | 21.88            | 22.19         |                           |
|                            | 25      | 0         | 20.56           | 20.90           | 20.82         | 20.77            | 20.93         | 0-2                       |
|                            | 25      | 12        | 20.56           | 20.81           | 20.77         | 20.73            | 20.79         |                           |
|                            | 25      | 25        | 20.51           | 20.75           | 20.70         | 20.61            | 20.82         |                           |
|                            | 50      | 0         | 20.50           | 20.83           | 20.78         | 20.69            | 20.92         |                           |

| LTE Band41 15MHz Bandwidth |         |           |                 |                 |               |                  |               |                           |
|----------------------------|---------|-----------|-----------------|-----------------|---------------|------------------|---------------|---------------------------|
| Modulation                 | RB Size | RB Offset | Low Channel     | Low-Mid Channel | Mid Channel   | Mid-High Channel | High Channel  | MPR Allowed Per 3GPP [dB] |
|                            |         |           | 39725           | 40173           | 40620         | 41068            | 41515         |                           |
|                            |         |           | (2 503.5 MHz)   | (2 548.3 MHz)   | (2 593.0 MHz) | (2 637.8 MHz)    | (2 682.5 MHz) |                           |
|                            |         |           | Conducted Power |                 |               |                  |               |                           |
|                            |         |           | [dBm]           | [dBm]           | [dBm]         | [dBm]            | [dBm]         |                           |
| QPSK                       | 1       | 0         | 22.71           | 22.83           | 22.79         | 22.87            | 22.81         | 0                         |
|                            | 1       | 36        | 22.59           | 22.84           | 22.68         | 22.75            | 22.68         |                           |
|                            | 1       | 74        | 22.55           | 22.70           | 22.66         | 22.55            | 22.52         |                           |
|                            | 36      | 0         | 21.65           | 22.01           | 21.75         | 21.86            | 21.79         | 0-1                       |
|                            | 36      | 18        | 21.71           | 21.90           | 21.74         | 21.77            | 21.76         |                           |
|                            | 36      | 37        | 21.61           | 21.79           | 21.74         | 21.68            | 21.68         |                           |
|                            | 75      | 0         | 21.60           | 21.91           | 21.71         | 21.82            | 21.73         |                           |
| 16QAM                      | 1       | 0         | 21.74           | 21.83           | 21.89         | 21.95            | 21.81         | 0-1                       |
|                            | 1       | 36        | 21.62           | 21.86           | 21.77         | 21.77            | 21.75         |                           |
|                            | 1       | 74        | 21.65           | 21.70           | 21.67         | 21.68            | 21.52         |                           |
|                            | 36      | 0         | 20.67           | 21.00           | 20.72         | 20.93            | 20.76         | 0-2                       |
|                            | 36      | 18        | 20.68           | 20.88           | 20.77         | 20.78            | 20.77         |                           |
|                            | 36      | 37        | 20.61           | 20.82           | 20.73         | 20.72            | 20.68         |                           |
|                            | 75      | 0         | 20.58           | 20.86           | 20.74         | 20.77            | 20.78         |                           |

| LTE Band41 20MHz Bandwidth |         |           |                 |                 |               |                  |               |                          |
|----------------------------|---------|-----------|-----------------|-----------------|---------------|------------------|---------------|--------------------------|
| Modulation                 | RB Size | RB Offset | Low Channel     | Low-Mid Channel | Mid Channel   | Mid-High Channel | High Channel  | MPR Allowed Per 3GPP[dB] |
|                            |         |           | 39750           | 40185           | 40620         | 41055            | 41490         |                          |
|                            |         |           | (2 506.0 MHz)   | (2 549.5 MHz)   | (2 593.0 MHz) | (2 636.5 MHz)    | (2 680.0 MHz) |                          |
|                            |         |           | Conducted Power |                 |               |                  |               |                          |
|                            |         |           | [dBm]           | [dBm]           | [dBm]         | [dBm]            | [dBm]         |                          |
| QPSK                       | 1       | 0         | 22.79           | 22.89           | 22.90         | 22.91            | 22.92         | 0                        |
|                            | 1       | 50        | 22.62           | 22.82           | 22.65         | 22.72            | 22.64         |                          |
|                            | 1       | 99        | 22.49           | 22.69           | 22.56         | 22.53            | 22.91         |                          |
|                            | 50      | 0         | 21.72           | 21.83           | 21.78         | 21.79            | 21.86         | 0-1                      |
|                            | 50      | 25        | 21.60           | 21.81           | 21.77         | 21.78            | 21.76         |                          |
|                            | 50      | 13        | 21.66           | 21.80           | 21.75         | 21.83            | 21.71         |                          |
|                            | 100     | 0         | 21.72           | 21.91           | 21.75         | 21.81            | 21.87         |                          |
| 16QAM                      | 1       | 0         | 21.88           | 22.05           | 22.01         | 22.10            | 22.01         | 0-1                      |
|                            | 1       | 50        | 21.58           | 21.93           | 21.70         | 21.79            | 21.70         |                          |
|                            | 1       | 99        | 21.52           | 21.67           | 21.63         | 21.58            | 21.65         |                          |
|                            | 50      | 0         | 20.71           | 21.02           | 20.80         | 20.98            | 20.87         | 0-2                      |
|                            | 50      | 25        | 20.60           | 20.93           | 20.78         | 20.84            | 20.76         |                          |
|                            | 50      | 50        | 20.66           | 20.83           | 20.71         | 20.68            | 20.73         |                          |
|                            | 100     | 0         | 20.72           | 20.86           | 20.75         | 20.74            | 20.82         |                          |

**-LTE Band 66**

| LTE Band66 1.4MHz Bandwidth |         |           |                 |               |               |                          |
|-----------------------------|---------|-----------|-----------------|---------------|---------------|--------------------------|
| Modulation                  | RB Size | RB Offset | Low Channel     | Mid Channel   | High Channel  | MPR Allowed Per 3GPP[dB] |
|                             |         |           | 131979          | 132322        | 132665        |                          |
|                             |         |           | (1 710.7 MHz)   | (1 745.0 MHz) | (1 779.3 MHz) |                          |
|                             |         |           | Conducted Power |               |               |                          |
|                             |         |           | [dBm]           | [dBm]         | [dBm]         |                          |
| QPSK                        | 1       | 0         | 22.49           | 22.15         | 22.17         | 0                        |
|                             | 1       | 2         | 22.51           | 22.19         | 22.21         |                          |
|                             | 1       | 5         | 22.47           | 22.20         | 22.18         |                          |
|                             | 3       | 0         | 22.46           | 22.16         | 22.20         | 0-1                      |
|                             | 3       | 2         | 22.51           | 22.24         | 22.19         |                          |
|                             | 3       | 3         | 22.50           | 22.27         | 22.17         |                          |
|                             | 6       | 0         | 21.50           | 22.16         | 22.16         |                          |
| 16QAM                       | 1       | 0         | 21.81           | 21.47         | 21.52         | 0-1                      |
|                             | 1       | 2         | 21.81           | 21.41         | 21.52         |                          |
|                             | 1       | 5         | 21.77           | 21.43         | 21.55         |                          |
|                             | 3       | 0         | 21.57           | 21.47         | 21.53         | 0-2                      |
|                             | 3       | 2         | 21.65           | 21.61         | 21.52         |                          |
|                             | 3       | 3         | 21.57           | 21.57         | 21.50         |                          |
|                             | 6       | 0         | 20.56           | 21.43         | 21.54         |                          |

| LTE Band66 3MHz Bandwidth |         |           |                 |               |               |                          |
|---------------------------|---------|-----------|-----------------|---------------|---------------|--------------------------|
| Modulation                | RB Size | RB Offset | Low Channel     | Mid Channel   | High Channel  | MPR Allowed Per 3GPP[dB] |
|                           |         |           | 131987          | 132322        | 132657        |                          |
|                           |         |           | (1 711.5 MHz)   | (1 745.0 MHz) | (1 778.5 MHz) |                          |
|                           |         |           | Conducted Power |               |               |                          |
|                           |         |           | [dBm]           | [dBm]         | [dBm]         |                          |
| QPSK                      | 1       | 0         | 22.66           | 22.26         | 22.36         | 0                        |
|                           | 1       | 7         | 22.77           | 22.30         | 22.42         |                          |
|                           | 1       | 14        | 22.73           | 22.24         | 22.45         |                          |
|                           | 8       | 0         | 22.65           | 21.27         | 21.33         | 0-1                      |
|                           | 8       | 4         | 22.67           | 21.28         | 21.34         |                          |
|                           | 8       | 7         | 22.70           | 21.25         | 21.34         |                          |
|                           | 15      | 0         | 21.66           | 21.24         | 21.34         |                          |
| 16QAM                     | 1       | 0         | 21.84           | 21.46         | 21.66         | 0-1                      |
|                           | 1       | 7         | 21.99           | 21.66         | 21.76         |                          |
|                           | 1       | 14        | 21.98           | 21.47         | 21.76         |                          |
|                           | 8       | 0         | 21.75           | 20.35         | 20.38         | 0-2                      |
|                           | 8       | 4         | 21.78           | 20.33         | 20.39         |                          |
|                           | 8       | 7         | 21.74           | 20.34         | 20.40         |                          |
|                           | 15      | 0         | 20.71           | 20.32         | 20.39         |                          |

| LTE Band66 5MHz Bandwidth |         |           |                 |               |               |                          |
|---------------------------|---------|-----------|-----------------|---------------|---------------|--------------------------|
| Modulation                | RB Size | RB Offset | Low Channel     | Mid Channel   | High Channel  | MPR Allowed Per 3GPP[dB] |
|                           |         |           | 131997          | 132322        | 132647        |                          |
|                           |         |           | (1 712.5 MHz)   | (1 745.0 MHz) | (1 777.5 MHz) |                          |
|                           |         |           | Conducted Power |               |               |                          |
|                           |         |           | [dBm]           | [dBm]         | [dBm]         |                          |
| QPSK                      | 1       | 0         | 22.68           | 22.30         | 22.61         | 0                        |
|                           | 1       | 12        | 22.71           | 22.29         | 22.34         |                          |
|                           | 1       | 24        | 22.73           | 22.32         | 22.40         |                          |
|                           | 12      | 0         | 22.67           | 22.27         | 21.48         | 0-1                      |
|                           | 12      | 6         | 22.65           | 22.27         | 21.40         |                          |
|                           | 12      | 13        | 22.63           | 22.26         | 21.37         |                          |
|                           | 25      | 0         | 22.65           | 21.25         | 21.38         |                          |
| 16QAM                     | 1       | 0         | 21.97           | 21.55         | 21.77         | 0-1                      |
|                           | 1       | 12        | 22.02           | 21.59         | 21.67         |                          |
|                           | 1       | 24        | 21.97           | 21.57         | 21.64         |                          |
|                           | 12      | 0         | 21.78           | 21.32         | 20.54         | 0-2                      |
|                           | 12      | 6         | 21.78           | 21.34         | 20.44         |                          |
|                           | 12      | 13        | 21.78           | 21.34         | 20.44         |                          |
|                           | 25      | 0         | 21.75           | 20.30         | 20.44         |                          |

| LTE Band66 10MHz Bandwidth |         |           |                 |               |               |                                |
|----------------------------|---------|-----------|-----------------|---------------|---------------|--------------------------------|
| Modulation                 | RB Size | RB Offset | Low Channel     | Mid Channel   | High Channel  | MPR Allowed<br>Per<br>3GPP[dB] |
|                            |         |           | 132022          | 132322        | 132622        |                                |
|                            |         |           | (1 715.0 MHz)   | (1 745.0 MHz) | (1 775.0 MHz) |                                |
|                            |         |           | Conducted Power |               |               |                                |
|                            |         |           | [dBm]           | [dBm]         | [dBm]         |                                |
| QPSK                       | 1       | 0         | 22.75           | 22.31         | 22.56         | 0                              |
|                            | 1       | 25        | 22.68           | 22.27         | 22.61         |                                |
|                            | 1       | 49        | 22.73           | 22.32         | 22.52         |                                |
|                            | 25      | 0         | 22.67           | 22.29         | 22.58         | 0-1                            |
|                            | 25      | 12        | 22.70           | 22.44         | 22.57         |                                |
|                            | 25      | 25        | 22.72           | 22.29         | 22.51         |                                |
|                            | 50      | 0         | 22.68           | 21.29         | 21.53         |                                |
| 16QAM                      | 1       | 0         | 21.92           | 21.51         | 21.84         | 0-1                            |
|                            | 1       | 25        | 21.95           | 21.51         | 21.79         |                                |
|                            | 1       | 49        | 22.06           | 21.54         | 21.70         |                                |
|                            | 25      | 0         | 21.82           | 21.34         | 21.66         | 0-2                            |
|                            | 25      | 12        | 21.78           | 21.42         | 21.66         |                                |
|                            | 25      | 25        | 21.81           | 21.33         | 21.58         |                                |
|                            | 50      | 0         | 21.78           | 20.33         | 20.56         |                                |

| LTE Band66 15MHz Bandwidth |         |           |                 |               |               |                                   |
|----------------------------|---------|-----------|-----------------|---------------|---------------|-----------------------------------|
| Modulation                 | RB Size | RB Offset | Low Channel     | Mid Channel   | High Channel  | MPR<br>Allowed<br>Per<br>3GPP[dB] |
|                            |         |           | 132047          | 132322        | 132597        |                                   |
|                            |         |           | (1 717.5 MHz)   | (1 745.0 MHz) | (1 772.5 MHz) |                                   |
|                            |         |           | Conducted Power |               |               |                                   |
|                            |         |           | [dBm]           | [dBm]         | [dBm]         |                                   |
| QPSK                       | 1       | 0         | 22.78           | 22.38         | 22.54         | 0                                 |
|                            | 1       | 36        | 22.78           | 22.54         | 22.54         |                                   |
|                            | 1       | 74        | 22.75           | 22.45         | 22.65         |                                   |
|                            | 36      | 0         | 22.78           | 22.47         | 22.55         | 0-1                               |
|                            | 36      | 18        | 22.73           | 22.44         | 22.63         |                                   |
|                            | 36      | 37        | 22.73           | 22.43         | 22.60         |                                   |
|                            | 75      | 0         | 22.73           | 22.42         | 21.60         |                                   |
| 16QAM                      | 1       | 0         | 22.08           | 21.70         | 21.81         | 0-1                               |
|                            | 1       | 36        | 22.10           | 21.87         | 21.92         |                                   |
|                            | 1       | 74        | 21.98           | 21.80         | 21.88         |                                   |
|                            | 36      | 0         | 21.89           | 21.54         | 21.56         | 0-2                               |
|                            | 36      | 18        | 21.82           | 21.52         | 21.63         |                                   |
|                            | 36      | 37        | 21.81           | 21.53         | 21.66         |                                   |
|                            | 75      | 0         | 21.82           | 21.51         | 20.62         |                                   |

| LTE Band66 20MHz Bandwidth |         |           |                 |               |               |                                   |
|----------------------------|---------|-----------|-----------------|---------------|---------------|-----------------------------------|
| Modulation                 | RB Size | RB Offset | Low Channel     | Mid Channel   | High Channel  | MPR<br>Allowed<br>Per<br>3GPP[dB] |
|                            |         |           | 132072          | 132322        | 132572        |                                   |
|                            |         |           | (1 720.0 MHz)   | (1 745.0 MHz) | (1 770.0 MHz) |                                   |
|                            |         |           | Conducted Power |               |               |                                   |
|                            |         |           | [dBm]           | [dBm]         | [dBm]         |                                   |
| QPSK                       | 1       | 0         | 22.87           | 22.39         | 22.74         | 0                                 |
|                            | 1       | 50        | 22.76           | 22.72         | 22.53         |                                   |
|                            | 1       | 99        | 22.74           | 22.28         | 22.47         |                                   |
|                            | 50      | 0         | 22.82           | 22.33         | 22.57         | 0-1                               |
|                            | 50      | 25        | 22.81           | 22.36         | 22.54         |                                   |
|                            | 50      | 13        | 22.75           | 22.37         | 22.51         |                                   |
|                            | 100     | 0         | 22.76           | 22.33         | 21.52         |                                   |
| 16QAM                      | 1       | 0         | 22.02           | 21.56         | 21.80         | 0-1                               |
|                            | 1       | 50        | 22.11           | 21.68         | 21.87         |                                   |
|                            | 1       | 99        | 21.99           | 21.58         | 21.86         |                                   |
|                            | 50      | 0         | 21.87           | 21.41         | 21.58         | 0-2                               |
|                            | 50      | 25        | 21.85           | 21.45         | 21.57         |                                   |
|                            | 50      | 50        | 21.88           | 21.46         | 21.61         |                                   |
|                            | 100     | 0         | 21.84           | 21.37         | 20.55         |                                   |

**-LTE Band 71**


| LTE Band71 5MHz Bandwidth |         |           |                 |             |              |                          |
|---------------------------|---------|-----------|-----------------|-------------|--------------|--------------------------|
| Modulation                | RB Size | RB Offset | Low Channel     | Mid Channel | High Channel | MPR Allowed Per 3GPP[dB] |
|                           |         |           | 133147          | 133297      | 133447       |                          |
|                           |         |           | (665.5 MHz)     | (680.5 MHz) | (695.5 MHz)  |                          |
|                           |         |           | Conducted Power |             |              |                          |
|                           |         |           | [dBm]           | [dBm]       | [dBm]        |                          |
| QPSK                      | 1       | 0         | 23.34           | 23.47       | 23.55        | 0                        |
|                           | 1       | 12        | 23.31           | 23.57       | 23.60        |                          |
|                           | 1       | 24        | 23.42           | 23.49       | 23.58        |                          |
|                           | 12      | 0         | 22.31           | 22.45       | 23.59        | 0-1                      |
|                           | 12      | 6         | 22.44           | 22.43       | 23.47        |                          |
|                           | 12      | 13        | 22.36           | 22.44       | 23.43        |                          |
|                           | 25      | 0         | 22.46           | 22.43       | 23.57        |                          |
| 16QAM                     | 1       | 0         | 22.65           | 22.82       | 22.86        | 0-1                      |
|                           | 1       | 12        | 22.67           | 22.81       | 22.87        |                          |
|                           | 1       | 24        | 22.79           | 22.82       | 22.80        |                          |
|                           | 12      | 0         | 21.44           | 21.49       | 22.87        | 0-2                      |
|                           | 12      | 6         | 21.51           | 21.50       | 22.78        |                          |
|                           | 12      | 13        | 21.45           | 21.48       | 22.85        |                          |
|                           | 25      | 0         | 21.44           | 21.47       | 22.88        |                          |

| LTE Band71 10MHz Bandwidth |         |           |                 |             |              |                          |
|----------------------------|---------|-----------|-----------------|-------------|--------------|--------------------------|
| Modulation                 | RB Size | RB Offset | Low Channel     | Mid Channel | High Channel | MPR Allowed Per 3GPP[dB] |
|                            |         |           | 133172          | 133297      | 133422       |                          |
|                            |         |           | (668.0 MHz)     | (680.5 MHz) | (693.0 MHz)  |                          |
|                            |         |           | Conducted Power |             |              |                          |
|                            |         |           | [dBm]           | [dBm]       | [dBm]        |                          |
| QPSK                       | 1       | 0         | 23.51           | 23.61       | 23.67        | 0                        |
|                            | 1       | 25        | 23.46           | 23.53       | 23.51        |                          |
|                            | 1       | 49        | 23.53           | 23.45       | 23.50        |                          |
|                            | 25      | 0         | 23.51           | 22.54       | 22.53        | 0-1                      |
|                            | 25      | 12        | 23.50           | 22.52       | 22.54        |                          |
|                            | 25      | 25        | 23.58           | 22.45       | 22.53        |                          |
|                            | 50      | 0         | 22.49           | 22.48       | 22.53        |                          |
| 16QAM                      | 1       | 0         | 22.75           | 22.86       | 22.93        | 0-1                      |
|                            | 1       | 25        | 22.73           | 22.76       | 22.75        |                          |
|                            | 1       | 49        | 22.78           | 22.75       | 22.81        |                          |
|                            | 25      | 0         | 22.55           | 21.57       | 21.57        | 0-2                      |
|                            | 25      | 12        | 22.56           | 21.55       | 21.56        |                          |
|                            | 25      | 25        | 22.61           | 21.46       | 21.55        |                          |
|                            | 50      | 0         | 21.55           | 21.49       | 21.55        |                          |

| LTE Band71 15MHz Bandwidth |         |           |                 |             |              |                          |
|----------------------------|---------|-----------|-----------------|-------------|--------------|--------------------------|
| Modulation                 | RB Size | RB Offset | Low Channel     | Mid Channel | High Channel | MPR Allowed Per 3GPP[dB] |
|                            |         |           | 133197          | 133297      | 133397       |                          |
|                            |         |           | (670.5 MHz)     | (680.5 MHz) | (690.5 MHz)  |                          |
|                            |         |           | Conducted Power |             |              |                          |
|                            |         |           | [dBm]           | [dBm]       | [dBm]        |                          |
| QPSK                       | 1       | 0         | 23.73           | 23.59       | 23.69        | 0                        |
|                            | 1       | 36        | 23.53           | 23.64       | 23.37        |                          |
|                            | 1       | 74        | 23.52           | 23.52       | 23.35        |                          |
|                            | 36      | 0         | 22.48           | 22.54       | 22.54        | 0-1                      |
|                            | 36      | 18        | 23.55           | 22.57       | 22.43        |                          |
|                            | 36      | 37        | 23.65           | 22.48       | 22.44        |                          |
|                            | 75      | 0         | 22.55           | 22.58       | 22.44        |                          |
| 16QAM                      | 1       | 0         | 22.87           | 22.96       | 23.01        | 0-1                      |
|                            | 1       | 36        | 22.84           | 22.94       | 22.67        |                          |
|                            | 1       | 74        | 22.97           | 22.82       | 22.65        |                          |
|                            | 36      | 0         | 22.63           | 21.55       | 21.56        | 0-2                      |
|                            | 36      | 18        | 22.60           | 21.60       | 21.47        |                          |
|                            | 36      | 37        | 22.68           | 21.53       | 21.50        |                          |
|                            | 75      | 0         | 21.59           | 21.60       | 21.49        |                          |

| LTE Band71 20MHz Bandwidth |         |           |                 |             |              |                                |
|----------------------------|---------|-----------|-----------------|-------------|--------------|--------------------------------|
| Modulation                 | RB Size | RB Offset | Low Channel     | Mid Channel | High Channel | MPR Allowed<br>Per<br>3GPP[dB] |
|                            |         |           | 133222          | 133297      | 133372       |                                |
|                            |         |           | (673.0 MHz)     | (680.5 MHz) | (688.0 MHz)  |                                |
|                            |         |           | Conducted Power |             |              |                                |
|                            |         |           | [dBm]           | [dBm]       | [dBm]        |                                |
| QPSK                       | 1       | 0         | 23.54           | 23.68       | 23.68        | 0                              |
|                            | 1       | 50        | 23.63           | 23.65       | 23.47        |                                |
|                            | 1       | 99        | 23.64           | 23.45       | 23.44        |                                |
|                            | 50      | 0         | 22.59           | 22.56       | 22.58        | 0-1                            |
|                            | 50      | 25        | 22.55           | 22.54       | 22.55        |                                |
|                            | 50      | 13        | 22.65           | 22.59       | 22.48        |                                |
|                            | 100     | 0         | 22.60           | 22.62       | 22.55        |                                |
| 16QAM                      | 1       | 0         | 22.86           | 22.95       | 22.89        | 0-1                            |
|                            | 1       | 50        | 22.92           | 22.94       | 22.74        |                                |
|                            | 1       | 99        | 22.91           | 22.78       | 22.79        |                                |
|                            | 50      | 0         | 22.68           | 21.62       | 21.66        | 0-2                            |
|                            | 50      | 25        | 22.65           | 21.61       | 21.60        |                                |
|                            | 50      | 50        | 22.76           | 21.61       | 21.47        |                                |
|                            | 100     | 0         | 21.63           | 21.68       | 21.60        |                                |

## 20 DUT Antenna Locations



<The Distance information of Antenna to Edges of Car Telematics Modem>

## 21 SAR Test Exclusion Applied

Based on the maximum tune-up tolerance limit of FDD, TDD, and the antenna to use separation distance, Table “EXEMPT” SAR was not required and Table “Measure” SAR was required.

| Frequency (MHz)    | Output power |      | Separation distances (mm) |      |            |           |        |        | SAR Exemption |         |            |           |         |         |
|--------------------|--------------|------|---------------------------|------|------------|-----------|--------|--------|---------------|---------|------------|-----------|---------|---------|
|                    | dBm          | Mw   | Front                     | Rear | Right Edge | Left Edge | Top    | Bottom | Front         | Rear    | Right Edge | Left Edge | Top     | Bottom  |
| <b>GSM Antenna</b> |              |      |                           |      |            |           |        |        |               |         |            |           |         |         |
| 824.2              | 34.00        | 2512 | 5                         | 5    | 44.97      | 5.45      | 116.47 | 5      | Measure       | Measure | Measure    | Measure   | Measure | Measure |
| 1850.2             | 31.00        | 1259 | 5                         | 5    | 44.97      | 5.45      | 116.47 | 5      | Measure       | Measure | Measure    | Measure   | Measure | Measure |
| 826.4              | 25.00        | 316  | 5                         | 5    | 44.97      | 5.45      | 116.47 | 5      | Measure       | Measure | Measure    | Measure   | Exempt  | Measure |
| 1712.4             | 25.00        | 316  | 5                         | 5    | 44.97      | 5.45      | 116.47 | 5      | Measure       | Measure | Measure    | Measure   | Exempt  | Measure |
| 1880.0             | 25.00        | 316  | 5                         | 5    | 44.97      | 5.45      | 116.47 | 5      | Measure       | Measure | Measure    | Measure   | Exempt  | Measure |
| <b>LTE Antenna</b> |              |      |                           |      |            |           |        |        |               |         |            |           |         |         |
| 782.0              | 24.00        | 251  | 5                         | 5    | 44.97      | 5.45      | 116.47 | 5      | Measure       | Measure | Measure    | Measure   | Exempt  | Measure |
| 844.0              | 24.00        | 251  | 5                         | 5    | 44.97      | 5.45      | 116.47 | 5      | Measure       | Measure | Measure    | Measure   | Exempt  | Measure |
| 1720.0             | 24.00        | 251  | 5                         | 5    | 44.97      | 5.45      | 116.47 | 5      | Measure       | Measure | Measure    | Measure   | Exempt  | Measure |
| 1905.0             | 24.00        | 251  | 5                         | 5    | 44.97      | 5.45      | 116.47 | 5      | Measure       | Measure | Measure    | Measure   | Exempt  | Measure |
| 2560.0             | 24.00        | 251  | 5                         | 5    | 44.97      | 5.45      | 116.47 | 5      | Measure       | Measure | Measure    | Measure   | Exempt  | Measure |

### Note

- Maximum power is the source-based time-average power and represents the maximum RF output power among production units.
- For distances < 5mm, a distance of 5mm is used to determine SAR exclusion and estimated SAR value.
- Output power is the maximum rated power (including tune-up or manufacturing tolerances).
- If the antenna separation distance is > 50mm then the value listed is the output power threshold, above which SAR measurement is required. For separation ≤ 50mm the value is the KDB 447498 D01v06 calculated value and must be less than 7.5 for SAR exemption.
- Formulas round separation distance to nearest mm and power to nearest mW before calculating thresholds or exemption values.

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$$

## 22 SAR Data Summary

### 22.1 SAR data

|                  |                          |            |            |            |
|------------------|--------------------------|------------|------------|------------|
| GSM 850 Body SAR | Ambient Temperature (°C) | 22.7       | 23.0       | 23.2       |
|                  | Liquid Temperature (°C)  | 22.3       | 22.0       | 22.5       |
|                  | Date                     | 2022-07-07 | 2022-07-25 | 2022-08-10 |

| EUT Position | Mode     | Traffic Channel |         | Distance (mm) | Measure Power (dBm) | Measure 1 g SAR (W/kg) | Tune-Up Limit (dBm) | Scaling Factor | Scaling SAR (W/kg) |
|--------------|----------|-----------------|---------|---------------|---------------------|------------------------|---------------------|----------------|--------------------|
|              |          | Frequency (MHz) | Channel |               |                     |                        |                     |                |                    |
| GPRS         |          |                 |         |               |                     |                        |                     |                |                    |
| Front        | GPRS 2Tx | 824.20          | 128     | 45            | 33.16               | 0.013                  | 34.00               | 1.213          | 0.016              |
| Rear         |          | 824.20          | 128     | 45            | 33.16               | 0.007                  | 34.00               | 1.213          | 0.008              |
| Left Edge    |          | 824.20          | 128     | 45            | 33.16               | 0.007                  | 34.00               | 1.213          | 0.008              |
| Right Edge   |          | 824.20          | 128     | 45            | 33.16               | 0.006                  | 34.00               | 1.213          | 0.007              |
| Bottom       |          | 824.20          | 128     | 45            | 33.16               | 0.009                  | 34.00               | 1.213          | 0.011              |
| Top          |          | 824.20          | 128     | 45            | 33.16               | 0.006                  | 34.00               | 1.213          | 0.007              |
| GSM          |          |                 |         |               |                     |                        |                     |                |                    |
| Front        | GSM      | 824.20          | 128     | 45            | 33.18               | 0.018                  | 34.00               | 1.208          | 0.022              |
| Rear         |          | 824.20          | 128     | 45            | 33.18               | 0.016                  | 34.00               | 1.208          | 0.019              |
| Left Edge    |          | 824.20          | 128     | 45            | 33.18               | 0.010                  | 34.00               | 1.208          | 0.012              |
| Right Edge   |          | 824.20          | 128     | 45            | 33.18               | 0.002                  | 34.00               | 1.208          | 0.002              |
| Bottom       |          | 824.20          | 128     | 45            | 33.18               | 0.015                  | 34.00               | 1.208          | 0.018              |
| Top          |          | 824.20          | 128     | 45            | 33.18               | 0.003                  | 34.00               | 1.208          | 0.004              |

|                   |                          |            |            |            |
|-------------------|--------------------------|------------|------------|------------|
| GSM 1900 Body SAR | Ambient Temperature (°C) | 22.9       | 23.0       | 22.9       |
|                   | Liquid Temperature (°C)  | 22.1       | 22.1       | 22.0       |
|                   | Date                     | 2022-07-11 | 2022-07-25 | 2022-08-11 |

| EUT<br>Position | Mode     | Traffic Channel    |         | Distance<br>(mm) | Measure<br>Power<br>(dBm) | Measure<br>1 g SAR<br>(W/kg) | Tune-<br>Up<br>Limit<br>(dBm) | Scaling<br>Factor | Scaling SAR<br>(W/kg) |
|-----------------|----------|--------------------|---------|------------------|---------------------------|------------------------------|-------------------------------|-------------------|-----------------------|
|                 |          | Frequency<br>(MHz) | Channel |                  |                           |                              |                               |                   |                       |
| GPRS            |          |                    |         |                  |                           |                              |                               |                   |                       |
| Front           | GPRS 1Tx | 1850.20            | 512     | 45               | 29.81                     | 0.172                        | 30.50                         | 1.172             | 0.202                 |
| Rear            |          | 1850.20            | 512     | 45               | 29.81                     | 0.012                        | 30.50                         | 1.172             | 0.014                 |
| Left Edge       |          | 1850.20            | 512     | 45               | 29.81                     | 0.026                        | 30.50                         | 1.172             | 0.030                 |
| Right Edge      |          | 1850.20            | 512     | 45               | 29.81                     | 0.002                        | 30.50                         | 1.172             | 0.002                 |
| Bottom          |          | 1850.20            | 512     | 45               | 29.81                     | 0.078                        | 30.50                         | 1.172             | 0.091                 |
| Top             |          | 1850.20            | 512     | 45               | 29.81                     | 0.003                        | 30.50                         | 1.172             | 0.004                 |
| GSM             |          |                    |         |                  |                           |                              |                               |                   |                       |
| Front           | GSM      | 1850.20            | 512     | 45               | 29.86                     | 0.182                        | 30.50                         | 1.159             | <b>0.211</b>          |
| Rear            |          | 1850.20            | 512     | 45               | 29.86                     | 0.015                        | 30.50                         | 1.159             | 0.017                 |
| Left Edge       |          | 1850.20            | 512     | 45               | 29.86                     | 0.032                        | 30.50                         | 1.159             | 0.037                 |
| Right Edge      |          | 1850.20            | 512     | 45               | 29.86                     | 0.004                        | 30.50                         | 1.159             | 0.005                 |
| Bottom          |          | 1850.20            | 512     | 45               | 29.86                     | 0.078                        | 30.50                         | 1.159             | 0.090                 |
| Top             |          | 1850.20            | 512     | 45               | 29.86                     | 0.004                        | 30.50                         | 1.159             | 0.005                 |

|                         |                          |            |            |
|-------------------------|--------------------------|------------|------------|
| <b>WCDMA 2 Body SAR</b> | Ambient Temperature (°C) | 22.7       | 22.9       |
|                         | Liquid Temperature (°C)  | 21.9       | 22.0       |
|                         | Date                     | 2022-06-11 | 2022-08-11 |

| EUT Position | Mode | Traffic Channel |         | Distance (mm) | Measure Power (dBm) | Measure 1 g SAR (W/kg) | Tune-Up Limit (dBm) | Scaling Factor | Scaling SAR (W/kg) |
|--------------|------|-----------------|---------|---------------|---------------------|------------------------|---------------------|----------------|--------------------|
|              |      | Frequency (MHz) | Channel |               |                     |                        |                     |                |                    |
| Front        | RMC  | 1880.00         | 9400    | 45            | 23.30               | 0.289                  | 25.00               | 1.479          | <b>0.427</b>       |
| Rear         | RMC  | 1880.00         | 9400    | 45            | 23.30               | 0.032                  | 25.00               | 1.479          | 0.047              |
| Left Edge    | RMC  | 1880.00         | 9400    | 45            | 23.30               | 0.056                  | 25.00               | 1.479          | 0.083              |
| Right Edge   | RMC  | 1880.00         | 9400    | 45            | 23.30               | N/A                    | 25.00               | 1.479          | N/A                |
| Bottom       | RMC  | 1880.00         | 9400    | 45            | 23.30               | 0.134                  | 25.00               | 1.479          | 0.198              |

|                         |                          |            |            |
|-------------------------|--------------------------|------------|------------|
| <b>WCDMA 4 Body SAR</b> | Ambient Temperature (°C) | 23.1       | 22.9       |
|                         | Liquid Temperature (°C)  | 22.3       | 21.9       |
|                         | Date                     | 2022-07-01 | 2022-08-11 |

| EUT Position | Modulation | Traffic Channel |         | Distance (mm) | Measure Power (dBm) | Measure 1 g SAR (W/kg) | Tune-Up Limit (dBm) | Scaling Factor | Scaling SAR (W/kg) |
|--------------|------------|-----------------|---------|---------------|---------------------|------------------------|---------------------|----------------|--------------------|
|              |            | Frequency (MHz) | Channel |               |                     |                        |                     |                |                    |
| Front        | RMC        | 1712.40         | 1312    | 45            | 23.67               | 0.305                  | 25.00               | 1.358          | <b>0.414</b>       |
| Rear         | RMC        | 1712.40         | 1312    | 45            | 23.67               | 0.020                  | 25.00               | 1.358          | 0.027              |
| Left Edge    | RMC        | 1712.40         | 1312    | 45            | 23.67               | 0.048                  | 25.00               | 1.358          | 0.065              |
| Right Edge   | RMC        | 1712.40         | 1312    | 45            | 23.67               | 0.003                  | 25.00               | 1.358          | 0.004              |
| Bottom       | RMC        | 1712.40         | 1312    | 45            | 23.67               | 0.100                  | 25.00               | 1.358          | 0.136              |

|                         |                          |            |            |
|-------------------------|--------------------------|------------|------------|
| <b>WCDMA 5 Body SAR</b> | Ambient Temperature (°C) | 22.7       | 23.2       |
|                         | Liquid Temperature (°C)  | 22.1       | 22.5       |
|                         | Date                     | 2022-06-28 | 2022-08-10 |

| EUT Position | Modulation | Traffic Channel |         | Distance (mm) | Measure Power (dBm) | Measure 1 g SAR (W/kg) | Tune-Up Limit (dBm) | Scaling Factor | Scaling SAR (W/kg) |
|--------------|------------|-----------------|---------|---------------|---------------------|------------------------|---------------------|----------------|--------------------|
|              |            | Frequency (MHz) | Channel |               |                     |                        |                     |                |                    |
| Front        | RMC        | 826.40          | 4132    | 45            | 24.12               | 0.018                  | 25.00               | 1.225          | <b>0.022</b>       |
| Rear         | RMC        | 826.40          | 4132    | 45            | 24.12               | 0.010                  | 25.00               | 1.225          | 0.012              |
| Left Edge    | RMC        | 826.40          | 4132    | 45            | 24.12               | 0.008                  | 25.00               | 1.225          | 0.010              |
| Right Edge   | RMC        | 826.40          | 4132    | 45            | 24.12               | 0.0000354              | 25.00               | 1.225          | 0.0000434          |
| Bottom       | RMC        | 826.40          | 4132    | 45            | 24.12               | 0.011                  | 25.00               | 1.225          | 0.013              |

|                     |                          |            |            |
|---------------------|--------------------------|------------|------------|
| LTE Band 5 Body SAR | Ambient Temperature (°C) | 22.8       | 23.2       |
|                     | Liquid Temperature (°C)  | 22.3       | 22.5       |
|                     | Date                     | 2022-06-27 | 2022-08-10 |

| EUT Position | Modulation | Bandwidth (MHz) | Traffic Channel |         | RB   |        | Distance (mm) | Measure Power (dBm) | Measure 1 g SAR (W/kg) | Tune-Up Limit (dBm) | Scaling Factor | Scaling SAR (W/kg) |
|--------------|------------|-----------------|-----------------|---------|------|--------|---------------|---------------------|------------------------|---------------------|----------------|--------------------|
|              |            |                 | Frequency (MHz) | Channel | Size | Offset |               |                     |                        |                     |                |                    |
| Front        | QPSK       | 10MHz           | 844.00          | 20600   | 1    | 25     | 45            | 22.94               | 0.013                  | 24.00               | 1.276          | 0.017              |
| Front        | QPSK       | 10MHz           | 844.00          | 20600   | 25   | 12     | 45            | 22.95               | 0.010                  | 23.00               | 1.012          | 0.010              |
| Rear         | QPSK       | 10MHz           | 844.00          | 20600   | 1    | 25     | 45            | 22.94               | 0.006                  | 24.00               | 1.276          | 0.008              |
| Rear         | QPSK       | 10MHz           | 844.00          | 20600   | 25   | 12     | 45            | 22.95               | 0.004                  | 23.00               | 1.012          | 0.004              |
| Right Edge   | QPSK       | 10MHz           | 844.00          | 20600   | 1    | 25     | 45            | 22.94               | 0.002                  | 24.00               | 1.276          | 0.003              |
|              | QPSK       | 10MHz           | 844.00          | 20600   | 25   | 12     | 45            | 22.95               | 0.000851               | 23.00               | 1.012          | 0.001              |
| Left Edge    | QPSK       | 10MHz           | 844.00          | 20600   | 1    | 25     | 45            | 22.94               | 0.006                  | 24.00               | 1.276          | 0.008              |
|              | QPSK       | 10MHz           | 844.00          | 20600   | 25   | 12     | 45            | 22.95               | 0.005                  | 23.00               | 1.012          | 0.005              |
| Bottom       | QPSK       | 10MHz           | 844.00          | 20600   | 1    | 25     | 45            | 22.94               | 0.006                  | 24.00               | 1.276          | 0.008              |
| Bottom       | QPSK       | 10MHz           | 844.00          | 20600   | 25   | 12     | 45            | 22.95               | 0.005                  | 23.00               | 1.012          | 0.005              |

|                     |                          |            |            |            |
|---------------------|--------------------------|------------|------------|------------|
| LTE Band 7 Body SAR | Ambient Temperature (°C) | 22.7       | 23.0       | 22.9       |
|                     | Liquid Temperature (°C)  | 21.8       | 21.9       | 21.9       |
|                     | Date                     | 2022-06-21 | 2022-06-22 | 2022-08-11 |

| EUT Position | Modulation | Bandwidth (MHz) | Traffic Channel |         | RB   |        | Distance (mm) | Measure Power (dBm) | Measure 1 g SAR (W/kg) | Tune-Up Limit (dBm) | Scaling Factor | Scaling SAR (W/kg) |
|--------------|------------|-----------------|-----------------|---------|------|--------|---------------|---------------------|------------------------|---------------------|----------------|--------------------|
|              |            |                 | Frequency (MHz) | Channel | Size | Offset |               |                     |                        |                     |                |                    |
| Front        | QPSK       | 20MHz           | 2560.00         | 21350   | 1    | 0      | 45            | 22.75               | 0.193                  | 24.00               | 1.334          | 0.257              |
| Front        | QPSK       | 20MHz           | 2560.00         | 21350   | 50   | 0      | 45            | 21.73               | 0.136                  | 23.00               | 1.340          | 0.182              |
| Rear         | QPSK       | 20MHz           | 2560.00         | 21350   | 1    | 0      | 45            | 22.75               | 0.006                  | 24.00               | 1.334          | 0.008              |
| Rear         | QPSK       | 20MHz           | 2560.00         | 21350   | 50   | 0      | 45            | 21.73               | 0.004                  | 23.00               | 1.340          | 0.005              |
| Right Edge   | QPSK       | 20MHz           | 2560.00         | 21350   | 1    | 0      | 45            | 22.75               | 0.002                  | 24.00               | 1.334          | 0.003              |
|              | QPSK       | 20MHz           | 2560.00         | 21350   | 50   | 0      | 45            | 21.73               | 0.00005                | 23.00               | 1.340          | 0.00007            |
| Left Edge    | QPSK       | 20MHz           | 2560.00         | 21350   | 1    | 0      | 45            | 22.75               | 0.100                  | 24.00               | 1.334          | 0.133              |
|              | QPSK       | 20MHz           | 2560.00         | 21350   | 50   | 0      | 45            | 21.73               | 0.072                  | 23.00               | 1.340          | 0.096              |
| Bottom       | QPSK       | 20MHz           | 2560.00         | 21350   | 1    | 0      | 45            | 22.75               | 0.023                  | 24.00               | 1.334          | 0.031              |
| Bottom       | QPSK       | 20MHz           | 2560.00         | 21350   | 50   | 0      | 45            | 21.73               | 0.015                  | 23.00               | 1.340          | 0.020              |

|                      |                          |            |            |
|----------------------|--------------------------|------------|------------|
| LTE Band 12 Body SAR | Ambient Temperature (°C) | 23.6       | 23.2       |
|                      | Liquid Temperature (°C)  | 22.1       | 22.5       |
|                      | Date                     | 2022-06-15 | 2022-08-10 |

| EUT Position | Modulation | Bandwidth (MHz) | Traffic Channel |         | RB   |        | Distance (mm) | Measure Power (dBm) | Measure 1 g SAR (W/kg) | Tune-Up Limit (dBm) | Scaling Factor | Scaling SAR (W/kg) |
|--------------|------------|-----------------|-----------------|---------|------|--------|---------------|---------------------|------------------------|---------------------|----------------|--------------------|
|              |            |                 | Frequency (MHz) | Channel | Size | Offset |               |                     |                        |                     |                |                    |
| Front        | QPSK       | 10MHz           | 704.00          | 23060   | 1    | 25     | 45            | 23.19               | 0.069                  | 24.00               | 1.205          | <b>0.083</b>       |
| Front        | QPSK       | 10MHz           | 711.00          | 23130   | 25   | 12     | 45            | 22.13               | 0.058                  | 23.00               | 1.222          | 0.071              |
| Rear         | QPSK       | 10MHz           | 704.00          | 23060   | 1    | 25     | 45            | 23.19               | 0.068                  | 24.00               | 1.205          | 0.082              |
| Rear         | QPSK       | 10MHz           | 711.00          | 23130   | 25   | 12     | 45            | 22.13               | 0.056                  | 23.00               | 1.222          | 0.068              |
| Right Edge   | QPSK       | 10MHz           | 704.00          | 23060   | 1    | 25     | 45            | 23.19               | 0.020                  | 24.00               | 1.205          | 0.024              |
|              | QPSK       | 10MHz           | 711.00          | 23130   | 25   | 12     | 45            | 22.13               | 0.016                  | 23.00               | 1.222          | 0.020              |
| Left Edge    | QPSK       | 10MHz           | 704.00          | 23060   | 1    | 25     | 45            | 23.19               | 0.034                  | 24.00               | 1.205          | 0.041              |
|              | QPSK       | 10MHz           | 711.00          | 23130   | 25   | 12     | 45            | 22.13               | 0.027                  | 23.00               | 1.222          | 0.033              |
| Bottom       | QPSK       | 10MHz           | 704.00          | 23060   | 1    | 25     | 45            | 23.19               | 0.021                  | 24.00               | 1.205          | 0.025              |
| Bottom       | QPSK       | 10MHz           | 711.00          | 23130   | 25   | 12     | 45            | 22.13               | 0.019                  | 23.00               | 1.222          | 0.023              |

|                      |                          |            |            |            |
|----------------------|--------------------------|------------|------------|------------|
| LTE Band 13 Body SAR | Ambient Temperature (°C) | 23.6       | 23.5       | 23.2       |
|                      | Liquid Temperature (°C)  | 22.1       | 22.2       | 22.5       |
|                      | Date                     | 2022-06-15 | 2022-06-16 | 2022-08-10 |

| EUT Position | Modulation | Bandwidth (MHz) | Traffic Channel |         | RB   |        | Distance (mm) | Measure Power (dBm) | Measure 1 g SAR (W/kg) | Tune-Up Limit (dBm) | Scaling Factor | Scaling SAR (W/kg) |
|--------------|------------|-----------------|-----------------|---------|------|--------|---------------|---------------------|------------------------|---------------------|----------------|--------------------|
|              |            |                 | Frequency (MHz) | Channel | Size | Offset |               |                     |                        |                     |                |                    |
| Front        | QPSK       | 10MHz           | 782.00          | 23230   | 1    | 0      | 45            | 23.42               | 0.050                  | 24.00               | 1.143          | <b>0.057</b>       |
| Front        | QPSK       | 10MHz           | 782.00          | 23230   | 25   | 0      | 45            | 22.44               | 0.036                  | 23.00               | 1.138          | 0.041              |
| Rear         | QPSK       | 10MHz           | 782.00          | 23230   | 1    | 0      | 45            | 23.42               | 0.045                  | 24.00               | 1.143          | 0.051              |
| Rear         | QPSK       | 10MHz           | 782.00          | 23230   | 25   | 0      | 45            | 22.44               | 0.031                  | 23.00               | 1.138          | 0.035              |
| Right Edge   | QPSK       | 10MHz           | 782.00          | 23230   | 1    | 0      | 45            | 23.42               | 0.014                  | 24.00               | 1.143          | 0.016              |
|              | QPSK       | 10MHz           | 782.00          | 23230   | 25   | 0      | 45            | 22.44               | 0.010                  | 23.00               | 1.138          | 0.011              |
| Left Edge    | QPSK       | 10MHz           | 782.00          | 23230   | 1    | 0      | 45            | 23.42               | 0.025                  | 24.00               | 1.143          | 0.029              |
|              | QPSK       | 10MHz           | 782.00          | 23230   | 25   | 0      | 45            | 22.44               | 0.020                  | 23.00               | 1.138          | 0.023              |
| Bottom       | QPSK       | 10MHz           | 782.00          | 23230   | 1    | 0      | 45            | 23.42               | 0.022                  | 24.00               | 1.143          | 0.025              |
| Bottom       | QPSK       | 10MHz           | 782.00          | 23230   | 25   | 0      | 45            | 22.44               | 0.016                  | 23.00               | 1.138          | 0.018              |

|                      |                          |            |            |
|----------------------|--------------------------|------------|------------|
| LTE Band 25 Body SAR | Ambient Temperature (°C) | 22.7       | 22.9       |
|                      | Liquid Temperature (°C)  | 21.9       | 22.0       |
|                      | Date                     | 2022-06-11 | 2022-08-11 |

| EUT Position | Modulation | Bandwidth (MHz) | Traffic Channel |         | RB   |        | Distance (mm) | Measure Power (dBm) | Measure 1 g SAR (W/kg) | Tune-Up Limit (dBm) | Scaling Factor | Scaling SAR (W/kg) |
|--------------|------------|-----------------|-----------------|---------|------|--------|---------------|---------------------|------------------------|---------------------|----------------|--------------------|
|              |            |                 | Frequency (MHz) | Channel | Size | Offset |               |                     |                        |                     |                |                    |
| Front        | QPSK       | 20MHz           | 1905.00         | 26590   | 1    | 0      | 45            | 23.15               | 0.297                  | 24.00               | 1.216          | <b>0.361</b>       |
| Front        | QPSK       | 20MHz           | 1905.00         | 26590   | 50   | 0      | 45            | 22.98               | 0.232                  | 23.00               | 1.005          | 0.233              |
| Rear         | QPSK       | 20MHz           | 1905.00         | 26590   | 1    | 0      | 45            | 23.15               | 0.030                  | 24.00               | 1.216          | 0.036              |
| Rear         | QPSK       | 20MHz           | 1905.00         | 26590   | 50   | 0      | 45            | 22.98               | 0.022                  | 23.00               | 1.005          | 0.022              |
| Right Edge   | QPSK       | 20MHz           | 1905.00         | 26590   | 1    | 0      | 45            | 23.15               | 0.010                  | 24.00               | 1.216          | 0.012              |
|              | QPSK       | 20MHz           | 1905.00         | 26590   | 50   | 0      | 45            | 22.98               | 0.007                  | 23.00               | 1.005          | 0.007              |
| Left Edge    | QPSK       | 20MHz           | 1905.00         | 26590   | 1    | 0      | 45            | 23.15               | 0.045                  | 24.00               | 1.216          | 0.055              |
|              | QPSK       | 20MHz           | 1905.00         | 26590   | 50   | 0      | 45            | 22.98               | 0.033                  | 23.00               | 1.005          | 0.033              |
| Bottom       | QPSK       | 20MHz           | 1905.00         | 26590   | 1    | 0      | 45            | 23.15               | 0.127                  | 24.00               | 1.216          | 0.154              |
| Bottom       | QPSK       | 20MHz           | 1905.00         | 26590   | 50   | 0      | 45            | 22.98               | 0.100                  | 23.00               | 1.005          | 0.101              |

|                      |                          |            |            |            |
|----------------------|--------------------------|------------|------------|------------|
| LTE Band 41 Body SAR | Ambient Temperature (°C) | 23         | 23.3       | 22.9       |
|                      | Liquid Temperature (°C)  | 21.9       | 22.2       | 21.9       |
|                      | Date                     | 2022-06-22 | 2022-06-24 | 2022-08-11 |

| EUT Position | Modulation | Bandwidth (MHz) | Traffic Channel |         | RB   |        | Distance (mm) | Measure Power (dBm) | Measure 1 g SAR (W/kg) | Tune-Up Limit (dBm) | Scaling Factor | Scaling SAR (W/kg) |
|--------------|------------|-----------------|-----------------|---------|------|--------|---------------|---------------------|------------------------|---------------------|----------------|--------------------|
|              |            |                 | Frequency (MHz) | Channel | Size | Offset |               |                     |                        |                     |                |                    |
| Front        | QPSK       | 20MHz           | 2680.00         | 41490   | 1    | 0      | 45            | 22.92               | 0.049                  | 24.00               | 1.282          | <b>0.063</b>       |
| Front        | QPSK       | 20MHz           | 2680.00         | 41490   | 50   | 0      | 45            | 21.86               | 0.023                  | 23.00               | 1.300          | 0.030              |
| Rear         | QPSK       | 20MHz           | 2680.00         | 41490   | 1    | 0      | 45            | 22.92               | N/A                    | 24.00               | 1.282          | N/A                |
| Rear         | QPSK       | 20MHz           | 2680.00         | 41490   | 50   | 0      | 45            | 21.86               | N/A                    | 23.00               | 1.300          | N/A                |
| Right Edge   | QPSK       | 20MHz           | 2680.00         | 41490   | 1    | 0      | 45            | 22.92               | 0.002                  | 24.00               | 1.282          | 0.003              |
|              | QPSK       | 20MHz           | 2680.00         | 41490   | 50   | 0      | 45            | 21.86               | 0.000002               | 23.00               | 1.300          | 0.000003           |
| Left Edge    | QPSK       | 20MHz           | 2680.00         | 41490   | 1    | 0      | 45            | 22.92               | 0.036                  | 24.00               | 1.282          | 0.046              |
|              | QPSK       | 20MHz           | 2680.00         | 41490   | 50   | 0      | 45            | 21.86               | 0.015                  | 23.00               | 1.300          | 0.020              |
| Bottom       | QPSK       | 20MHz           | 2680.00         | 41490   | 1    | 0      | 45            | 22.92               | 0.002                  | 24.00               | 1.282          | 0.003              |
| Bottom       | QPSK       | 20MHz           | 2680.00         | 41490   | 50   | 0      | 45            | 21.86               | N/A                    | 23.00               | 1.300          | N/A                |

|                      |                          |            |            |
|----------------------|--------------------------|------------|------------|
| LTE Band 66 Body SAR | Ambient Temperature (°C) | 22.9       | 22.9       |
|                      | Liquid Temperature (°C)  | 21.9       | 21.9       |
|                      | Date                     | 2022-07-04 | 2022-08-11 |

| EUT Position | Modulation | Bandwidth (MHz) | Traffic Channel |         | RB   |        | Distance (mm) | Measure Power (dBm) | Measure 1 g SAR (W/kg) | Tune-Up Limit (dBm) | Scaling Factor | Scaling SAR (W/kg) |
|--------------|------------|-----------------|-----------------|---------|------|--------|---------------|---------------------|------------------------|---------------------|----------------|--------------------|
|              |            |                 | Frequency (MHz) | Channel | Size | Offset |               |                     |                        |                     |                |                    |
| Front        | QPSK       | 20MHz           | 1720.00         | 132072  | 1    | 0      | 45            | 22.87               | 0.273                  | 24.00               | 1.297          | <b>0.354</b>       |
| Front        | QPSK       | 20MHz           | 1720.00         | 132072  | 50   | 0      | 45            | 22.82               | 0.210                  | 23.00               | 1.042          | 0.219              |
| Rear         | QPSK       | 20MHz           | 1720.00         | 132072  | 1    | 0      | 45            | 22.87               | 0.018                  | 24.00               | 1.297          | 0.023              |
| Rear         | QPSK       | 20MHz           | 1720.00         | 132072  | 50   | 0      | 45            | 22.82               | 0.013                  | 23.00               | 1.042          | 0.014              |
| Right Edge   | QPSK       | 20MHz           | 1720.00         | 132072  | 1    | 0      | 45            | 22.87               | 0.003                  | 24.00               | 1.297          | 0.004              |
|              | QPSK       | 20MHz           | 1720.00         | 132072  | 50   | 0      | 45            | 22.82               | 0.002                  | 23.00               | 1.042          | 0.002              |
| Left Edge    | QPSK       | 20MHz           | 1720.00         | 132072  | 1    | 0      | 45            | 22.87               | 0.045                  | 24.00               | 1.297          | 0.058              |
|              | QPSK       | 20MHz           | 1720.00         | 132072  | 50   | 0      | 45            | 22.82               | 0.034                  | 23.00               | 1.042          | 0.035              |
| Bottom       | QPSK       | 20MHz           | 1720.00         | 132072  | 1    | 0      | 45            | 22.87               | 0.088                  | 24.00               | 1.297          | 0.114              |
| Bottom       | QPSK       | 20MHz           | 1720.00         | 132072  | 50   | 0      | 45            | 22.82               | 0.068                  | 23.00               | 1.042          | 0.071              |

|                      |                          |            |            |
|----------------------|--------------------------|------------|------------|
| LTE Band 71 Body SAR | Ambient Temperature (°C) | 23.3       | 23.2       |
|                      | Liquid Temperature (°C)  | 22.3       | 22.5       |
|                      | Date                     | 2022-06-17 | 2022-08-10 |

| EUT Position | Modulation | Bandwidth (MHz) | Traffic Channel |         | RB   |        | Distance (mm) | Measure Power (dBm) | Measure 1 g SAR (W/kg) | Tune-Up Limit (dBm) | Scaling Factor | Scaling SAR (W/kg) |
|--------------|------------|-----------------|-----------------|---------|------|--------|---------------|---------------------|------------------------|---------------------|----------------|--------------------|
|              |            |                 | Frequency (MHz) | Channel | Size | Offset |               |                     |                        |                     |                |                    |
| Front        | QPSK       | 20MHz           | 680.50          | 133297  | 1    | 0      | 45            | 23.68               | 0.069                  | 24.00               | 1.076          | <b>0.074</b>       |
| Front        | QPSK       | 20MHz           | 673.00          | 133222  | 50   | 13     | 45            | 22.65               | 0.059                  | 23.00               | 1.084          | 0.064              |
| Rear         | QPSK       | 20MHz           | 680.50          | 133297  | 1    | 0      | 45            | 23.68               | 0.066                  | 24.00               | 1.076          | 0.071              |
| Rear         | QPSK       | 20MHz           | 673.00          | 133222  | 50   | 13     | 45            | 22.65               | 0.053                  | 23.00               | 1.084          | 0.057              |
| Right Edge   | QPSK       | 20MHz           | 680.50          | 133297  | 1    | 0      | 45            | 23.68               | 0.014                  | 24.00               | 1.076          | 0.015              |
|              | QPSK       | 20MHz           | 673.00          | 133222  | 50   | 13     | 45            | 22.65               | 0.010                  | 23.00               | 1.084          | 0.011              |
| Left Edge    | QPSK       | 20MHz           | 680.50          | 133297  | 1    | 0      | 45            | 23.68               | 0.040                  | 24.00               | 1.076          | 0.043              |
|              | QPSK       | 20MHz           | 673.00          | 133222  | 50   | 13     | 45            | 22.65               | 0.027                  | 23.00               | 1.084          | 0.029              |
| Bottom       | QPSK       | 20MHz           | 680.50          | 133297  | 1    | 0      | 45            | 23.68               | 0.016                  | 24.00               | 1.076          | 0.017              |
| Bottom       | QPSK       | 20MHz           | 673.00          | 133222  | 50   | 13     | 45            | 22.65               | 0.013                  | 23.00               | 1.084          | 0.014              |

**General Notes:**

1. The test data reported are the worst-case SAR values according to test procedures specified in FCC KDB Publication 447498 D01v06.
2. Liquid tissue depth was at least 15 cm for all frequencies.
3. All modes of operation were investigated, and worst-case results are reported.
4. The EUT is tested 2<sup>nd</sup> hot-spot peak, if it is less than 2 dB below the highest peak.
5. The manufacturer has confirmed that the device(s) tested have the same physical, mechanical and thermal characteristics and are within operational tolerances expected for production units.
6. SAR results were scaled to the maximum allowed power to demonstrate compliance per FCC KDB Publication 447498 D01v06.
7. Per FCC KDB 865664 D01V01r04, variability SAR tests were performed when the measured SAR results for a frequency band were greater than or equal to 0.8W/kg. Repeated SAR measurements are highlighted in the tables above for clarity. Please see Section 23 for variability analysis.
8. This device is operating by connecting power supply therefore battery is not required

**WCDMA Notes:**

1. WCDMA mode in Body SAR was tested under RMC 12.2 kbps with HSPA inactive per KDB Publication 941225 D01v03r01. HSPA SAR was not required since the average output power of the HSPA subtests was not more than 0.25 dB higher than the RMC level and SAR was less than 1.2 W/kg.
2. Per FCC KDB Publication 447498 D01v06, if the reported (scaled) SAR measured at the middle channel or highest output power channel for each test configuration is  $\leq 0.8$  W/kg then testing at the other channels is not required for such test configuration(s). When the maximum output power variation across the required test channels is  $> 1/2$  dB, instead of the middle channel, the highest output power channel must be used

**LTE Notes:**

1. LTE Considerations: LTE test configurations are determined according to SAR Evaluation Considerations for LTE Devices in FCC KDB Publication 941225 D05v02r05. The general test procedures used for testing can be found in Section 5.
2. MPR is permanently implemented for this device by the manufacturer. The specific manufacturer target MPR is indicated alongside the SAR results. MPR is enabled for this device, according to 3GPP TS36.101 Section 6.2.3-6.2.5 under Table 6.2.3-1.
3. A-MPR was disabled for all SAR tests by setting NS=01 on the base station simulator.
4. This device supports LTE capabilities with overlapping transmission frequency ranges. When the supported frequency range of an LTE Band falls completely within an LTE band with a larger transmission frequency range, both LTE bands have the same target power (or the band with the larger transmission frequency range has a higher target power), and both LTE bands share the same transmission path and signal characteristics, SAR was only assessed for the band with larger transmission frequency range.

## **23 SAR Measurement Variability**

### **23.1 Measurement Variability**

Per FCC KDB Publication 865664 D01v01r04, SAR measurement variability was assessed for each frequency band, which was determined by the SAR probe calibration point and tissue-equivalent medium used for the device measurements. When both head and body tissue-equivalent media were required for SAR measurements in a frequency band, the variability measurement procedures were applied to the tissue medium with the highest measured SAR, using the highest measured SAR configuration for that tissue-equivalent medium. These additional measurements were repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device was returned to ambient conditions (normal room temperature) with the power supply before it was re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results.

SAR Measurement Variability was assessed using the following procedures for each frequency band:

1. When the original highest measured SAR is  $\geq 0.80$  W/kg, the measurement was repeated once.
2. A second repeated measurement was performed only if the ratio of largest to smallest SAR for the original and first repeated measurements was  $> 1.20$  or when the original or repeated measurement was  $\geq 1.45$  W/kg ( $\sim 10\%$  from the 1-g SAR limit).
3. A third repeated measurement was performed only if the original, first or second repeated measurement was  $\geq 1.5$  W/kg and the ratio of largest to smallest SAR for the original, first and second repeated measurements is  $> 1.20$ .
4. Repeated measurements are not required when the original highest measured SAR is  $< 0.80$  W/kg

### **23.2 Measurement Uncertainty**

The measured SAR was  $< 1.5$  W/kg for all frequency bands. Therefore, per KDB Publication 865664 D01v01r04, the extended measurement uncertainty analysis per IEEE 1528-2013 was not required.

## Appendixes List

|                   |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
|-------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Appendix A</b> | A.1 Verification Test Plots for 750MHz<br>A.2 Verification Test Plots for 835MHz<br>A.3 Verification Test Plots for 1800MHz<br>A.4 Verification Test Plots for 1900MHz<br>A.5 Verification Test Plots for 2600MHz<br>A.6 SAR Test Plots for GSM850<br>A.7 SAR Test Plots for GSM1900<br>A.8 SAR Test Plots for WCDMA II<br>A.9 SAR Test Plots for WCDMA IV<br>A.10 SAR Test Plots for WCDMA V<br>A.11 SAR Test Plots for LTE Band 5<br>A.12 SAR Test Plots for LTE Band 7<br>A.13 SAR Test Plots for LTE Band 12<br>A.14 SAR Test Plots for LTE Band 13<br>A.15 SAR Test Plots for LTE Band 25<br>A.16 SAR Test Plots for LTE Band 41<br>A.17 SAR Test Plots for LTE Band 66<br>A.18 SAR Test Plots for LTE Band 71 |
| <b>Appendix B</b> | B.1 Uncertainty Analysis                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| <b>Appendix C</b> | C.1 Calibration certificate for Probe (S/N : 7412)<br>C.2 Calibration certificate for DAE (S/N : 1595)<br>C.3 Calibration certificate for Dipole 750 MHz (S/N : 1085)<br>C.4 Calibration certificate for Dipole 835 MHz (S/N : 490)<br>C.5 Calibration certificate for Dipole 1800 MHz (S/N : 2d193)<br>C.6 Calibration certificate for Dipole 1800 MHz (S/N : 2d074)<br>C.7 Calibration certificate for Dipole 1900 MHz (S/N : 5d158)<br>C.8 Calibration certificate for Dipole 1900 MHz (S/N : 5d033)<br>C.9 Calibration certificate for Dipole 2600 MHz (S/N : 1038)                                                                                                                                             |

## Appendix A.1 Verification Test Plots for 750MHz

Date: 2022-06-15

Test Laboratory : SGS Korea (Gunpo Laboratory)  
File Name: [750MHz Verification 2022\\_06\\_15 da53-0](#)

Input Power : 100 mW

**DUT: Dipole 750 MHz D750V3; Type: D750V3; Serial: D750V3 - SN:1085**

Communication System: UID 0, CW (0); Frequency: 750 MHz; Duty Cycle: 1:1  
Medium parameters used:  $f = 750$  MHz;  $\sigma = 0.888$  S/m;  $\epsilon_r = 42.575$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
Phantom section: Flat Section

DASY52 Configuration:

- Probe: EX3DV4 - SN7412; ConvF(10.36, 10.36, 10.36) @ 750 MHz; Calibrated: 2022-04-29
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1595; Calibrated: 2022-01-24
- Phantom: ELI v5.0 1244; Type: QDOVA002AA; Serial: TP:1244
- DASY52 52.10.4(1527)SEMCAD X 14.6.14(7483)

**Verification/750MHz Verification/Area Scan (61x121x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm  
Maximum value of SAR (interpolated) = 1.11 W/kg

**Verification/750MHz Verification/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 30.67 V/m; Power Drift = 0.11 dB


Peak SAR (extrapolated) = 1.29 W/kg

**SAR(1 g) = 0.843 W/kg; SAR(10 g) = 0.556 W/kg**

Smallest distance from peaks to all points 3 dB below = 17.2 mm

Ratio of SAR at M2 to SAR at M1 = 65.4%

Maximum value of SAR (measured) = 1.13 W/kg



Date: 2022-06-16

Test Laboratory : SGS Korea (Gunpo Laboratory)  
File Name: [750MHz Verification 2022\\_06\\_16.dn53-0](#)

Input Power : 100 mW

**DUT: Dipole 750 MHz D750V3; Type: D750V3; Serial: D750V3 - SN:1085**

Communication System: UID 0, CW (0); Frequency: 750 MHz; Duty Cycle: 1:1  
Medium parameters used:  $f = 750$  MHz;  $\sigma = 0.872$  S/m;  $\epsilon_r = 42.477$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
Phantom section: Flat Section

DASY52 Configuration:

- Probe: EX3DV4 - SN7412; ConvF(10.36, 10.36, 10.36) @ 750 MHz; Calibrated: 2022-04-29
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1595; Calibrated: 2022-01-24
- Phantom: ELI v5.0 1244; Type: QDOVA002AA; Serial: TP:1244
- DASY52 52.10.4(1527)SEMCAD X 14.6.14(7483)

**Verification/750MHz Verification/Area Scan (61x121x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm  
Maximum value of SAR (interpolated) = 1.08 W/kg

**Verification/750MHz Verification/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 31.02 V/m; Power Drift = 0.13 dB


Peak SAR (extrapolated) = 1.24 W/kg

**SAR(1 g) = 0.810 W/kg; SAR(10 g) = 0.534 W/kg**

Smallest distance from peaks to all points 3 dB below = 17.2 mm

Ratio of SAR at M2 to SAR at M1 = 65.5%

Maximum value of SAR (measured) = 1.09 W/kg



Date: 2022-06-17

Test Laboratory : SGS Korea (Gunpo Laboratory)  
File Name: [750MHz Verification 2022\\_06\\_17.dn53-0](#)

Input Power : 100 mW

**DUT: Dipole 750 MHz D750V3; Type: D750V3; Serial: D750V3 - SN:1085**

Communication System: UID 0, CW (0); Frequency: 750 MHz; Duty Cycle: 1:1  
Medium parameters used:  $f = 750$  MHz;  $\sigma = 0.927$  S/m;  $\epsilon_r = 42.294$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
Phantom section: Flat Section

DASY52 Configuration:

- Probe: EX3DV4 - SN7412; ConvF(10.36, 10.36, 10.36) @ 750 MHz; Calibrated: 2022-04-29
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1595; Calibrated: 2022-01-24
- Phantom: ELI v5.0 1244; Type: QDOVA002AA; Serial: TP:1244
- DASY52 52.10.4(1527)SEMCAD X 14.6.14(7483)

**Verification/750MHz Verification/Area Scan (61x121x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm  
Maximum value of SAR (interpolated) = 1.17 W/kg

**Verification/750MHz Verification/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 31.45 V/m; Power Drift = 0.03 dB


Peak SAR (extrapolated) = 1.32 W/kg

**SAR(1 g) = 0.864 W/kg; SAR(10 g) = 0.570 W/kg**

Smallest distance from peaks to all points 3 dB below = 17.2 mm

Ratio of SAR at M2 to SAR at M1 = 65.4%

Maximum value of SAR (measured) = 1.16 W/kg



Date: 2022-08-10

Test Laboratory : SGS Korea (Gunpo Laboratory)  
File Name: [750MHz Verification 2022\\_08\\_10.dn53-0](#)

Input Power : 100 mW

**DUT: Dipole 750 MHz D750V3; Type: D750V3; Serial: D750V3 - SN:1085**

Communication System: UID 0, CW (0); Frequency: 750 MHz; Duty Cycle: 1:1  
Medium parameters used:  $f = 750$  MHz;  $\sigma = 0.921$  S/m;  $\epsilon_r = 41.961$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
Phantom section: Flat Section

DASY52 Configuration:

- Probe: EX3DV4 - SN7412; ConvF(10.36, 10.36, 10.36) @ 750 MHz; Calibrated: 2022-04-29
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1595; Calibrated: 2022-01-24
- Phantom: ELI v4.0 Phantom TP:1244; Type: ELI v4.0 Phantom; Serial: TP:1244
- DASY52 52.10.4(1527)SEMCAD X 14.6.14(7483)

**Verification/750MHz Verification/Area Scan (61x121x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm  
Maximum value of SAR (interpolated) = 1.11 W/kg

**Verification/750MHz Verification/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 30.51 V/m; Power Drift = 0.18 dB


Peak SAR (extrapolated) = 1.34 W/kg

**SAR(1 g) = 0.861 W/kg; SAR(10 g) = 0.563 W/kg**

Smallest distance from peaks to all points 3 dB below = 17.6 mm

Ratio of SAR at M2 to SAR at M1 = 64.4%

Maximum value of SAR (measured) = 1.16 W/kg



## Appendix A.2 Verification Test Plots for 835MHz

Date: 2022-06-27

Test Laboratory : SGS Korea (Gunpo Laboratory)  
File Name: [835MHz Verification 2022\\_06\\_27.dn53.0](#)

Input Power : 100 mW

**DUT: Dipole 835 MHz D835V2; Type: D835V2; Serial: D835V2 - SN:490**

Communication System: UID 0, CW (0); Frequency: 835 MHz; Duty Cycle: 1:1  
Medium parameters used:  $f = 835$  MHz;  $\sigma = 0.902$  S/m;  $\epsilon_r = 41.791$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
Phantom section: Flat Section

DASY52 Configuration:

- Probe: EX3DV4 - SN7412; ConvF(9.86, 9.86, 9.86) @ 835 MHz; Calibrated: 2022-04-29
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1595; Calibrated: 2022-01-24
- Phantom: ELI v5.0 1244; Type: QDOVA002AA; Serial: TP:1244
- DASY52 52.10.4(1527)SEMCAD X 14.6.14(7483)

**Verification/835MHz Verification/Area Scan (61x121x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm  
Maximum value of SAR (interpolated) = 1.27 W/kg

**Verification/835MHz Verification/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 39.30 V/m; Power Drift = -0.08 dB


Peak SAR (extrapolated) = 1.47 W/kg

**SAR(1 g) = 0.944 W/kg; SAR(10 g) = 0.612 W/kg**

Smallest distance from peaks to all points 3 dB below = 16 mm

Ratio of SAR at M2 to SAR at M1 = 64.2%

Maximum value of SAR (measured) = 1.29 W/kg



Date: 2022-06-28

Test Laboratory : SGS Korea (Gunpo Laboratory)  
File Name: [835MHz Verification 2022\\_06\\_28.da53:0](#)

Input Power : 100 mW

**DUT: Dipole 835 MHz D835V2; Type: D835V2; Serial: D835V2 - SN:490**

Communication System: UID 0, CW (0); Frequency: 835 MHz; Duty Cycle: 1:1  
Medium parameters used:  $f = 835$  MHz;  $\sigma = 0.894$  S/m;  $\epsilon_r = 41.471$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
Phantom section: Flat Section

DASY52 Configuration:

- Probe: EX3DV4 - SN7412; ConvF(9.86, 9.86, 9.86) @ 835 MHz; Calibrated: 2022-04-29
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1595; Calibrated: 2022-01-24
- Phantom: ELI v5.0 1244; Type: QDOVA002AA; Serial: TP:1244
- DASY52 52.10.4(1527)SEMCAD X 14.6.14(7483)

**Verification/835MHz Verification/Area Scan (61x121x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm  
Maximum value of SAR (interpolated) = 1.29 W/kg

**Verification/835MHz Verification/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 39.30 V/m; Power Drift = 0.14 dB


Peak SAR (extrapolated) = 1.49 W/kg

**SAR(1 g) = 0.956 W/kg; SAR(10 g) = 0.621 W/kg**

Smallest distance from peaks to all points 3 dB below = 16 mm

Ratio of SAR at M2 to SAR at M1 = 64.1%

Maximum value of SAR (measured) = 1.31 W/kg



Date: 2022-07-07

Test Laboratory : SGS Korea (Gunpo Laboratory)  
File Name: [835MHz Verification 2022\\_07\\_07\\_da53:0](#)

Input Power: 100 mW

**DUT: Dipole 835 MHz D835V2; Type: D835V2; Serial: D835V2 - SN:490**

Communication System: UID 0, CW (0); Frequency: 835 MHz; Duty Cycle: 1:1  
Medium parameters used:  $f = 835$  MHz;  $\sigma = 0.913$  S/m;  $\epsilon_r = 42.167$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
Phantom section: Flat Section

DASY52 Configuration:

- Probe: EX3DV4 - SN7412; ConvF(9.86, 9.86, 9.86) @ 835 MHz; Calibrated: 2022-04-29
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1595; Calibrated: 2022-01-24
- Phantom: ELI v5.0 1244; Type: QDOVA002AA; Serial: TP:1244
- DASY52 52.10.4(1527)SEMCAD X 14.6.14(7483)

**Verification/835MHz Verification/Area Scan (61x121x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm  
Maximum value of SAR (interpolated) = 1.28 W/kg

**Verification/835MHz Verification/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 39.92 V/m; Power Drift = -0.19 dB


Peak SAR (extrapolated) = 1.46 W/kg

**SAR(1 g) = 0.942 W/kg; SAR(10 g) = 0.611 W/kg**

Smallest distance from peaks to all points 3 dB below = 16 mm

Ratio of SAR at M2 to SAR at M1 = 64.2%

Maximum value of SAR (measured) = 1.28 W/kg



Date: 2022-07-25

Test Laboratory : SGS Korea (Gunpo Laboratory)  
File Name: [835MHz Verification 2022\\_07\\_25\\_da53:0](#)

Input Power: 100 mW

**DUT: Dipole 835 MHz D835V2; Type: D835V2; Serial: D835V2 - SN:490**

Communication System: UID 0, CW (0); Frequency: 835 MHz; Duty Cycle: 1:1  
Medium parameters used:  $f = 835 \text{ MHz}$ ;  $\sigma = 0.911 \text{ S/m}$ ;  $\epsilon_r = 41.953$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Flat Section

DASY52 Configuration:

- Probe: EX3DV4 - SN7412; ConvF(9.86, 9.86, 9.86) @ 835 MHz; Calibrated: 2022-04-29
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1595; Calibrated: 2022-01-24
- Phantom: ELI v4.0 Phantom TP:1244; Type: ELI v4.0 Phantom; Serial: TP:1244
- DASY52 52.10.4(1527)SEMCAD X 14.6.14(7483)

**Verification/835MHz Verification/Area Scan (61x121x1):** Interpolated grid:  $dx=1.500 \text{ mm}$ ,  $dy=1.500 \text{ mm}$   
Maximum value of SAR (interpolated) = 1.24 W/kg

**Verification/835MHz Verification/Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$

Reference Value = 39.16 V/m; Power Drift = -0.20 dB


Peak SAR (extrapolated) = 1.39 W/kg

**SAR(1 g) = 0.896 W/kg; SAR(10 g) = 0.581 W/kg**

Smallest distance from peaks to all points 3 dB below = 16 mm

Ratio of SAR at M2 to SAR at M1 = 64.5%

Maximum value of SAR (measured) = 1.22 W/kg



Date: 2022-08-10

Test Laboratory : SGS Korea (Gunpo Laboratory)  
File Name: [835MHz Verification 2022\\_08\\_10.dn53-0](#)

Input Power : 100 mW

**DUT: Dipole 835 MHz D835V2; Type: D835V2; Serial: D835V2 - SN:490**

Communication System: UID 0, CW (0); Frequency: 835 MHz; Duty Cycle: 1:1  
Medium parameters used:  $f = 835$  MHz;  $\sigma = 0.91$  S/m;  $\epsilon_r = 39.904$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
Phantom section: Flat Section

DASY52 Configuration:

- Probe: EX3DV4 - SN7412; ConvF(9.86, 9.86, 9.86) @ 835 MHz; Calibrated: 2022-04-29
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1595; Calibrated: 2022-01-24
- Phantom: ELI v4.0 Phantom TP:1244; Type: ELI v4.0 Phantom; Serial: TP:1244
- DASY52 52.10.4(1527)SEMCAD X 14.6.14(7483)

**Verification/835MHz Verification/Area Scan (61x121x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm  
Maximum value of SAR (interpolated) = 1.23 W/kg

**Verification/835MHz Verification/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 38.31 V/m; Power Drift = 0.09 dB


Peak SAR (extrapolated) = 1.43 W/kg

**SAR(1 g) = 0.918 W/kg; SAR(10 g) = 0.594 W/kg**

Smallest distance from peaks to all points 3 dB below = 16.3 mm

Ratio of SAR at M2 to SAR at M1 = 64.2%

Maximum value of SAR (measured) = 1.25 W/kg



## Appendix A.3 Verification Test Plots for 1800MHz

Date: 2022-07-01

Test Laboratory : SGS Korea (Gunpo Laboratory)

File Name: [1800MHz Verification 2022\\_07\\_01\\_da53-0](#)

Input Power : 100 mW

**DUT: Dipole 1800 MHz D1800V2; Type: D1800V2; Serial: D1800V2 - SN:2d193**

Communication System: UID 0, CW (0); Frequency: 1800 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 1800$  MHz;  $\sigma = 1.462$  S/m;  $\epsilon_r = 39.558$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

DASY52 Configuration:

- Probe: EX3DV4 - SN7412; ConvF(8.6, 8.6, 8.6) @ 1800 MHz; Calibrated: 2022-04-29
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1595; Calibrated: 2022-01-24
- Phantom: ELI v5.0 1244; Type: QDOVA002AA; Serial: TP:1244
- DASY52 52.10.4(1527)SEMCAD X 14.6.14(7483)

**Verification/1800MHz Verification/Area Scan (61x61x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 6.24 W/kg

**Verification/1800MHz Verification/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 66.77 V/m; Power Drift = -0.06 dB


Peak SAR (extrapolated) = 7.54 W/kg

**SAR(1 g) = 3.94 W/kg; SAR(10 g) = 2.04 W/kg**

Smallest distance from peaks to all points 3 dB below = 9.6 mm

Ratio of SAR at M2 to SAR at M1 = 52.1%

Maximum value of SAR (measured) = 6.22 W/kg



Date: 2022-07-04

Test Laboratory : SGS Korea (Gunpo Laboratory)  
File Name: [1800MHz Verification 2022\\_07\\_04\\_da53-0](#)

Input Power : 100 mW

**DUT: Dipole 1800 MHz D1800V2; Type: D1800V2; Serial: D1800V2 - SN:2d193**

Communication System: UID 0, CW (0); Frequency: 1800 MHz; Duty Cycle: 1:1  
Medium parameters used:  $f = 1800$  MHz;  $\sigma = 1.422$  S/m;  $\epsilon_r = 38.761$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
Phantom section: Flat Section

DASY52 Configuration:

- Probe: EX3DV4 - SN7412; ConvF(8.6, 8.6, 8.6) @ 1800 MHz; Calibrated: 2022-04-29
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1595; Calibrated: 2022-01-24
- Phantom: ELI v5.0 1244; Type: QDOVA002AA; Serial: TP:1244
- DASY52 52.10.4(1527)SEMCAD X 14.6.14(7483)

**Verification/1800MHz Verification/Area Scan (61x61x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm  
Maximum value of SAR (interpolated) = 5.72 W/kg

**Verification/1800MHz Verification/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 64.09 V/m; Power Drift = 0.07 dB


Peak SAR (extrapolated) = 7.40 W/kg

**SAR(1 g) = 3.76 W/kg; SAR(10 g) = 1.93 W/kg**

Smallest distance from peaks to all points 3 dB below = 9.6 mm

Ratio of SAR at M2 to SAR at M1 = 50.9%

Maximum value of SAR (measured) = 5.98 W/kg



Date: 2022-08-11

Test Laboratory : SGS Korea (Gunpo Laboratory)

File Name: [1800MHz Verification 2022\\_08\\_11\\_da53-0](#)

Input Power : 100 mW

**DUT: Dipole 1800 MHz D1800V2; Type: D1800V2; Serial: D1800V2 - SN:2d074**

Communication System: UID 0, CW (0); Frequency: 1800 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 1800 \text{ MHz}$ ;  $\sigma = 1.457 \text{ S/m}$ ;  $\epsilon_r = 39.153$ ;  $\rho = 1000 \text{ kg/m}^3$ 

Phantom section: Flat Section

DASY52 Configuration:

- Probe: EX3DV4 - SN7412; ConvF(8.6, 8.6, 8.6) @ 1800 MHz; Calibrated: 2022-04-29

- Sensor-Surface: 1.4mm (Mechanical Surface Detection)

- Electronics: DAE4 Sn1595; Calibrated: 2022-01-24

- Phantom: ELI v4.0 Phantom TP:1244; Type: ELI v4.0 Phantom; Serial: TP:1244

- DASY52 52.10.4(1527)SEMCAD X 14.6.14(7483)

**Verification/1800MHz Verification/Area Scan (61x61x1):** Interpolated grid:  $dx=1.500 \text{ mm}$ ,  $dy=1.500 \text{ mm}$ 

Maximum value of SAR (interpolated) = 6.57 W/kg

**Verification/1800MHz Verification/Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$ 

Reference Value = 68.73 V/m; Power Drift = 0.03 dB


Peak SAR (extrapolated) = 7.81 W/kg

**SAR(1 g) = 4.1 W/kg; SAR(10 g) = 2.14 W/kg**

Smallest distance from peaks to all points 3 dB below = 9.6 mm

Ratio of SAR at M2 to SAR at M1 = 52.5%

Maximum value of SAR (measured) = 6.42 W/kg



## Appendix A.4 Verification Test Plots for 1900MHz

Date: 2022-06-11

Test Laboratory : SGS Korea (Gunpo Laboratory)

File Name: [1900MHz Verification 2022\\_06\\_11.da53:0](#)

Input Power : 100 mW

**DUT: Dipole 1900 MHz D1900V2; Type: D1900V2; Serial: D1900V2 - SN:5d158**

Communication System: UID 0, CW (0); Frequency: 1900 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 1900$  MHz;  $\sigma = 1.388$  S/m;  $\epsilon_r = 39.926$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

DASY52 Configuration:

- Probe: EX3DV4 - SN7412; ConvF(8.22, 8.22, 8.22) @ 1900 MHz; Calibrated: 2022-04-29
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1595; Calibrated: 2022-01-24
- Phantom: SAM with CRP; Type: SAM; Serial: TP:1720
- DASY52 52.10.4(1527)SEMCAD X 14.6.14(7483)

**Verification/1900MHz Verification/Area Scan (61x61x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 6.58 W/kg

**Verification/1900MHz Verification/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 68.31 V/m; Power Drift = -0.06 dB


Peak SAR (extrapolated) = 7.94 W/kg

**SAR(1 g) = 4.16 W/kg; SAR(10 g) = 2.14 W/kg**

Smallest distance from peaks to all points 3 dB below = 9.7 mm

Ratio of SAR at M2 to SAR at M1 = 52.2%

Maximum value of SAR (measured) = 6.62 W/kg



Date: 2022-07-11

Test Laboratory : SGS Korea (Gunpo Laboratory)

File Name: [1900MHz Verification 2022\\_07\\_11.da53:0](#)

Input Power : 100 mW

**DUT: Dipole 1900 MHz D1900V2; Type: D1900V2; Serial: D1900V2 - SN:5d033**

Communication System: UID 0, CW (0); Frequency: 1900 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 1900$  MHz;  $\sigma = 1.398$  S/m;  $\epsilon_r = 39.362$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

DASY52 Configuration:

- Probe: EX3DV4 - SN7412; ConvF(8.22, 8.22, 8.22) @ 1900 MHz; Calibrated: 2022-04-29

- Sensor-Surface: 1.4mm (Mechanical Surface Detection)

- Electronics: DAE4 Sn1595; Calibrated: 2022-01-24

- Phantom: ELI v5.0 1244; Type: QDOVA002AA; Serial: TP:1244

- DASY52 52.10.4(1527)SEMCAD X 14.6.14(7483)

**Verification/1900MHz Verification/Area Scan (61x61x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 6.01 W/kg

**Verification/1900MHz Verification/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 67.22 V/m; Power Drift = -0.02 dB


Peak SAR (extrapolated) = 7.14 W/kg

**SAR(1 g) = 3.8 W/kg; SAR(10 g) = 1.98 W/kg**

Smallest distance from peaks to all points 3 dB below = 9.6 mm

Ratio of SAR at M2 to SAR at M1 = 53.2%

Maximum value of SAR (measured) = 5.97 W/kg



Date: 2022-07-25

Test Laboratory : SGS Korea (Gunpo Laboratory)

File Name: [1900MHz Verification 2022\\_07\\_25 da53:0](#)

Input Power : 100 mW

**DUT: Dipole 1900 MHz D1900V2; Type: D1900V2; Serial: D1900V2 - SN:5d033**

Communication System: UID 0, CW (0); Frequency: 1900 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 1900$  MHz;  $\sigma = 1.397$  S/m;  $\epsilon_r = 41.74$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

DASY52 Configuration:

- Probe: EX3DV4 - SN7412; ConvF(8.22, 8.22, 8.22) @ 1900 MHz; Calibrated: 2022-04-29

- Sensor-Surface: 1.4mm (Mechanical Surface Detection)

- Electronics: DAE4 Sn1595; Calibrated: 2022-01-24

- Phantom: ELI v4.0 Phantom TP:1244; Type: ELI v4.0 Phantom; Serial: TP:1244

- DASY52 52.10.4(1527)SEMCAD X 14.6.14(7483)

**Verification/1900MHz Verification/Area Scan (61x61x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 6.67 W/kg

**Verification/1900MHz Verification/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 69.69 V/m; Power Drift = 0.15 dB


Peak SAR (extrapolated) = 7.97 W/kg

**SAR(1 g) = 4.18 W/kg; SAR(10 g) = 2.17 W/kg**

Smallest distance from peaks to all points 3 dB below = 10.1 mm

Ratio of SAR at M2 to SAR at M1 = 52.5%

Maximum value of SAR (measured) = 6.60 W/kg



Date: 2022-08-11

Test Laboratory : SGS Korea (Gunpo Laboratory)

File Name: [1900MHz Verification 2022\\_08\\_11.da53:0](#)

Input Power : 100 mW

**DUT: Dipole 1900 MHz D1900V2; Type: D1900V2; Serial: D1900V2 - SN:5d033**

Communication System: UID 0, CW (0); Frequency: 1900 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 1900$  MHz;  $\sigma = 1.4$  S/m;  $\epsilon_r = 41.416$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

DASY52 Configuration:

- Probe: EX3DV4 - SN7412; ConvF(8.22, 8.22, 8.22) @ 1900 MHz; Calibrated: 2022-04-29

- Sensor-Surface: 1.4mm (Mechanical Surface Detection)

- Electronics: DAE4 Sn1595; Calibrated: 2022-01-24

- Phantom: ELI v4.0 Phantom TP:1244; Type: ELI v4.0 Phantom; Serial: TP:1244

- DASY52 52.10.4(1527)SEMCAD X 14.6.14(7483)

**Verification/1900MHz Verification/Area Scan (61x61x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 6.90 W/kg

**Verification/1900MHz Verification/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 64.79 V/m; Power Drift = 0.07 dB


Peak SAR (extrapolated) = 7.57 W/kg

**SAR(1 g) = 3.92 W/kg; SAR(10 g) = 2.01 W/kg**

Smallest distance from peaks to all points 3 dB below = 9.6 mm

Ratio of SAR at M2 to SAR at M1 = 51.7%

Maximum value of SAR (measured) = 6.27 W/kg



## Appendix A.5 Verification Test Plots for 2600MHz

Date: 2022-06-21

Test Laboratory : SGS Korea (Gunpo Laboratory)

File Name: [2600MHz Verification 2022\\_06\\_21\\_da53-0](#)

Input Power : 100 mW

**DUT: Dipole 2600 MHz D2600V2; Type: D2600V2; Serial: D2600V2 - SN:1038**

Communication System: UID 0, CW (0); Frequency: 2600 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 2600$  MHz;  $\sigma = 2.017$  S/m;  $\epsilon_r = 37.354$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

DASY52 Configuration:

- Probe: EX3DV4 - SN7412; ConvF(7.59, 7.59, 7.59) @ 2600 MHz; Calibrated: 2022-04-29
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1595; Calibrated: 2022-01-24
- Phantom: ELI v5.0 1244; Type: QDOVA002AA; Serial: TP:1244
- DASY52 52.10.4(1527)SEMCAD X 14.6.14(7483)

**Verification/2600 MHz Verification/Area Scan (91x91x1):** Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 11.6 W/kg

**Verification/2600 MHz Verification/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 74.06 V/m; Power Drift = 0.12 dB


Peak SAR (extrapolated) = 14.0 W/kg

**SAR(1 g) = 5.97 W/kg; SAR(10 g) = 2.58 W/kg**

Smallest distance from peaks to all points 3 dB below = 9 mm

Ratio of SAR at M2 to SAR at M1 = 42.4%

Maximum value of SAR (measured) = 10.8 W/kg



Date: 2022-06-22

Test Laboratory : SGS Korea (Gunpo Laboratory)

File Name: [2600MHz Verification 2022\\_06\\_22.da53:0](#)

Input Power : 100 mW

**DUT: Dipole 2600 MHz D2600V2; Type: D2600V2; Serial: D2600V2 - SN:1038**

Communication System: UID 0, CW (0); Frequency: 2600 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 2600$  MHz;  $\sigma = 1.969$  S/m;  $\epsilon_r = 38.298$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

DASY52 Configuration:

- Probe: EX3DV4 - SN7412; ConvF(7.59, 7.59, 7.59) @ 2600 MHz; Calibrated: 2022-04-29
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1595; Calibrated: 2022-01-24
- Phantom: ELI v5.0 1244; Type: QDOVA002AA; Serial: TP:1244
- DASY52 52.10.4(1527)SEMCAD X 14.6.14(7483)

**Verification/2600 MHz Verification/Area Scan (91x91x1):** Interpolated grid:  $dx=1.000$  mm,  $dy=1.000$  mm

Maximum value of SAR (interpolated) = 10.3 W/kg

**Verification/2600 MHz Verification/Zoom Scan (7x7x7)/Cube 0:** Measurement grid:  $dx=5$ mm,  $dy=5$ mm,  $dz=5$ mm

Reference Value = 73.60 V/m; Power Drift = 0.05 dB


Peak SAR (extrapolated) = 13.2 W/kg

**SAR(1 g) = 5.67 W/kg; SAR(10 g) = 2.44 W/kg**

Smallest distance from peaks to all points 3 dB below = 9 mm

Ratio of SAR at M2 to SAR at M1 = 42.5%

Maximum value of SAR (measured) = 10.2 W/kg



Date: 2022-06-24

Test Laboratory : SGS Korea (Gunpo Laboratory)  
File Name: [2600MHz Verification 2022\\_06\\_24\\_da53-0](#)

Input Power : 100 mW

**DUT: Dipole 2600 MHz D2600V2; Type: D2600V2; Serial: D2600V2 - SN:1038**

Communication System: UID 0, CW (0); Frequency: 2600 MHz; Duty Cycle: 1:1  
Medium parameters used:  $f = 2600$  MHz;  $\sigma = 1.966$  S/m;  $\epsilon_r = 37.338$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
Phantom section: Flat Section

DASY52 Configuration:

- Probe: EX3DV4 - SN7412; ConvF(7.59, 7.59, 7.59) @ 2600 MHz; Calibrated: 2022-04-29
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1595; Calibrated: 2022-01-24
- Phantom: ELI v5.0 1244; Type: QDOVA002AA; Serial: TP:1244
- DASY52 52.10.4(1527)SEMCAD X 14.6.14(7483)

**Verification/2600 MHz Verification/Area Scan (91x91x1):** Interpolated grid: dx=1.000 mm, dy=1.000 mm  
Maximum value of SAR (interpolated) = 10.2 W/kg

**Verification/2600 MHz Verification/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 73.66 V/m; Power Drift = -0.05 dB


Peak SAR (extrapolated) = 13.1 W/kg

**SAR(1 g) = 5.66 W/kg; SAR(10 g) = 2.45 W/kg**

Smallest distance from peaks to all points 3 dB below = 9 mm

Ratio of SAR at M2 to SAR at M1 = 43%

Maximum value of SAR (measured) = 10.1 W/kg



Date: 2022-08-11

Test Laboratory : SGS Korea (Gunpo Laboratory)

File Name: [2600MHz Verification 2022\\_08\\_11\\_da53-0](#)

Input Power : 100 mW

**DUT: Dipole 2600 MHz D2600V2; Type: D2600V2; Serial: D2600V2 - SN:1038**

Communication System: UID 0, CW (0); Frequency: 2600 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 2600$  MHz;  $\sigma = 1.974$  S/m;  $\epsilon_r = 38.098$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

DASY52 Configuration:

- Probe: EX3DV4 - SN7412; ConvF(7.59, 7.59, 7.59) @ 2600 MHz; Calibrated: 2022-04-29

- Sensor-Surface: 1.4mm (Mechanical Surface Detection)

- Electronics: DAE4 Sn1595; Calibrated: 2022-01-24

- Phantom: ELI v4.0 Phantom TP:1244; Type: ELI v4.0 Phantom; Serial: TP:1244

- DASY52 52.10.4(1527)SEMCAD X 14.6.14(7483)

**Verification/2600 MHz Verification/Area Scan (91x91x1):** Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 9.56 W/kg

**Verification/2600 MHz Verification/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 67.95 V/m; Power Drift = -0.07 dB


Peak SAR (extrapolated) = 12.1 W/kg

**SAR(1 g) = 5.42 W/kg; SAR(10 g) = 2.41 W/kg**

Smallest distance from peaks to all points 3 dB below = 9 mm

Ratio of SAR at M2 to SAR at M1 = 45%

Maximum value of SAR (measured) = 9.52 W/kg



## Appendix A.6 SAR Test Plots for GSM850

Date: 2022-07-25

Test Laboratory : SGS Korea (Gunpo Laboratory)

File Name: [GSM 850\\_Front\\_CH128.da53-0](#)

**DUT: TM04ANNABM2; Type: Car Telematics Modem; Serial: N-128**

Communication System: UID 0, GSM850 (0); Frequency: 824.2 MHz; Duty Cycle: 1:8.30042

Medium parameters used (interpolated):  $f = 824.2$  MHz;  $\sigma = 0.899$  S/m;  $\epsilon_r = 42.086$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

DASY52 Configuration:

- Probe: EX3DV4 - SN7412; ConvF(9.86, 9.86, 9.86) @ 824.2 MHz; Calibrated: 2022-04-29

- Sensor-Surface: 1.4mm (Mechanical Surface Detection)

- Electronics: DAE4 Sn1595; Calibrated: 2022-01-24

- Phantom: ELI v4.0 Phantom TP:1244; Type: ELI v4.0 Phantom; Serial: TP:1244

- DASY52 52.10.4(1527)SEMCAD X 14.6.14(7483)

**Body/GSM 850\_Front\_CH128/Area Scan (101x161x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm

Info: Interpolated medium parameters used for SAR evaluation.

Maximum value of SAR (interpolated) = 0.0225 W/kg

**Body/GSM 850\_Front\_CH128/Zoom Scan (6x6x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 4.159 V/m; Power Drift = 0.15 dB

Peak SAR (extrapolated) = 0.0250 W/kg


**SAR(1 g) = 0.018 W/kg; SAR(10 g) = 0.013 W/kg**

Smallest distance from peaks to all points 3 dB below: Larger than measurement grid

Ratio of SAR at M2 to SAR at M1 = 69.2%

Info: Interpolated medium parameters used for SAR evaluation.

Maximum value of SAR (measured) = 0.0224 W/kg



## Appendix A.7 SAR Test Plots for GSM1900

Date: 2022-07-25

Test Laboratory : SGS Korea (Gunpo Laboratory)  
File Name: [GSM 1900\\_Front\\_CH512\\_da53-0](#)

**DUT: TM04ANNABM2; Type: Car Telematics Modem; Serial: N-128**

Communication System: UID 0, GSM1900 (0); Frequency: 1850.2 MHz; Duty Cycle: 1:8.30042  
Medium parameters used (interpolated):  $f = 1850.2$  MHz;  $\sigma = 1.351$  S/m;  $\epsilon_r = 41.991$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
Phantom section: Flat Section

DASY52 Configuration:

- Probe: EX3DV4 - SN7412; ConvF(8.22, 8.22, 8.22) @ 1850.2 MHz; Calibrated: 2022-04-29
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1595; Calibrated: 2022-01-24
- Phantom: ELI v4.0 Phantom TP:1244; Type: ELI v4.0 Phantom; Serial: TP:1244
- DASY52 52.10.4(1527)/SEMCAD X 14.6.14(7483)

**Body/GSM 1900\_Front\_CH512/Area Scan (131x161x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm

Info: Interpolated medium parameters used for SAR evaluation.

Maximum value of SAR (interpolated) = 0.250 W/kg

**Body/GSM 1900\_Front\_CH512/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 6.438 V/m; Power Drift = 0.07 dB

Peak SAR (extrapolated) = 0.288 W/kg


**SAR(1 g) = 0.182 W/kg; SAR(10 g) = 0.117 W/kg**

Smallest distance from peaks to all points 3 dB below: Larger than measurement grid

Ratio of SAR at M2 to SAR at M1 = 62.5%

Info: Interpolated medium parameters used for SAR evaluation.

Maximum value of SAR (measured) = 0.249 W/kg



## Appendix A.8 SAR Test Plots for WCDMA II

Date: 2022-06-11

Test Laboratory : SGS Korea (Gunpo Laboratory)

File Name: [WCDMA FDD II\\_Front\\_CH9400.da53:0](#)

**DUT: TM04ANNABM2; Type: Car Telematics Modem; Serial: N-128**

Communication System: UID 0, WCDMA2 (0); Frequency: 1880 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 1880$  MHz;  $\sigma = 1.371$  S/m;  $\epsilon_r = 40.001$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

DASY52 Configuration:

- Probe: EX3DV4 - SN7412; ConvF(8.22, 8.22, 8.22) @ 1880 MHz; Calibrated: 2022-04-29
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1595; Calibrated: 2022-01-24
- Phantom: ELI v5.0 1244; Type: QDOVA002AA; Serial: TP:1244
- DASY52 52.10.4(1527)SEMCAD X 14.6.14(7483)

**Body/WCDMA FDD II\_Front\_CH9400/Area Scan (101x91x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.399 W/kg

**Body/WCDMA FDD II\_Front\_CH9400/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 7.412 V/m; Power Drift = -0.08 dB


Peak SAR (extrapolated) = 0.468 W/kg

**SAR(1 g) = 0.289 W/kg; SAR(10 g) = 0.184 W/kg**

Smallest distance from peaks to all points 3 dB below: Larger than measurement grid

Ratio of SAR at M2 to SAR at M1 = 60.6%

Maximum value of SAR (measured) = 0.402 W/kg



## Appendix A.9 SAR Test Plots for WCDMA IV

Date: 2022-07-01

Test Laboratory : SGS Korea (Gunpo Laboratory)

File Name: [WCDMA FDD IV\\_Front\\_CH1312.da53:0](#)

**DUT: TM04ANNABM2; Type: Car Telematics Modem; Serial: N-128**

Communication System: UID 0, WCDMA4 (0); Frequency: 1712.4 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated):  $f = 1712.4$  MHz;  $\sigma = 1.376$  S/m;  $\epsilon_r = 39.849$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

DASY52 Configuration:

- Probe: EX3DV4 - SN7412; ConvF(8.6, 8.6, 8.6) @ 1712.4 MHz; Calibrated: 2022-04-29
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1595; Calibrated: 2022-01-24
- Phantom: ELI v5.0 1244; Type: QDOVA002AA; Serial: TP:1244
- DASY52 52.10.4(1527)SEMCAD X 14.6.14(7483)

**Body/WCDMA FDD IV\_Front\_CH1312/Area Scan (101x131x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm

Info: Interpolated medium parameters used for SAR evaluation.

Maximum value of SAR (interpolated) = 0.419 W/kg

**Body/WCDMA FDD IV\_Front\_CH1312/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 9.755 V/m; Power Drift = -0.05 dB

Peak SAR (extrapolated) = 0.491 W/kg


**SAR(1 g) = 0.305 W/kg; SAR(10 g) = 0.195 W/kg**

Smallest distance from peaks to all points 3 dB below: Larger than measurement grid

Ratio of SAR at M2 to SAR at M1 = 61.7%

Info: Interpolated medium parameters used for SAR evaluation.

Maximum value of SAR (measured) = 0.422 W/kg



## Appendix A.10 SAR Test Plots for WCDMA V

Date: 2022-06-28

Test Laboratory : SGS Korea (Gunpo Laboratory)  
File Name: [WCDMA FDD V\\_Front\\_CH4132.da53:0](#)

**DUT: TM04ANNABM2; Type: Car Telematics Modem; Serial: N-128**

Communication System: UID 0, WCDMA5 (0); Frequency: 826.4 MHz; Duty Cycle: 1:1  
Medium parameters used (interpolated):  $f = 826.4$  MHz;  $\sigma = 0.885$  S/m;  $\epsilon_r = 41.555$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
Phantom section: Flat Section

DASY52 Configuration:

- Probe: EX3DV4 - SN7412; ConvF(9.86, 9.86, 9.86) @ 826.4 MHz; Calibrated: 2022-04-29
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1595; Calibrated: 2022-01-24
- Phantom: ELI v5.0 1244; Type: QDOVA002AA; Serial: TP:1244
- DASY52 52.10.4(1527)SEMCAD X 14.6.14(7483)

**Body/WCDMA FDD V\_Front\_CH4132/Area Scan (101x131x1):** Interpolated grid; dx=1.500 mm, dy=1.500 mm

Info: Interpolated medium parameters used for SAR evaluation.  
Maximum value of SAR (interpolated) = 0.0224 W/kg

**Body/WCDMA FDD V\_Front\_CH4132/Zoom Scan (5x5x7)/Cube 0:** Measurement grid; dx=8mm, dy=8mm, dz=5mm

Reference Value = 4.121 V/m; Power Drift = -0.03 dB


Peak SAR (extrapolated) = 0.0270 W/kg

**SAR(1 g) = 0.018 W/kg; SAR(10 g) = 0.013 W/kg**

Smallest distance from peaks to all points 3 dB below: Larger than measurement grid

Ratio of SAR at M2 to SAR at M1 = 67.3%

Info: Interpolated medium parameters used for SAR evaluation.  
Maximum value of SAR (measured) = 0.0237 W/kg



## Appendix A.11 SAR Test Plots for LTE Band 5

Date: 2022-06-27

Test Laboratory : SGS Korea (Gunpo Laboratory)

File Name: [LTE 5\\_10MHz\\_1@25\\_QPSK\\_Front\\_CH20600.da53.0](#)

**DUT: TM04ANNABM2; Type: Car Telematics Modem; Serial: N-128**

Communication System: UID 0, LTE Band 5 (0); Frequency: 844 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 844$  MHz;  $\sigma = 0.911$  S/m;  $\epsilon_r = 41.699$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

DASY52 Configuration:

- Probe: EX3DV4 - SN7412; ConvF(9.86, 9.86, 9.86) @ 844 MHz; Calibrated: 2022-04-29
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1595; Calibrated: 2022-01-24
- Phantom: ELI v5.0 1244; Type: QDOVA002AA; Serial: TP:1244
- DASY52 52.10.4(1527)SEMCAD X 14.6.14(7483)

**Body/LTE 5\_10MHz\_1@25\_QPSK\_Front\_CH20600/Area Scan (101x131x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.0172 W/kg

**Body/LTE 5\_10MHz\_1@25\_QPSK\_Front\_CH20600/Zoom Scan (5x5x7)/Cube 0:** Measurement grid:

dx=8mm, dy=8mm, dz=5mm

Reference Value = 3.556 V/m; Power Drift = 0.20 dB


Peak SAR (extrapolated) = 0.0200 W/kg

**SAR(1 g) = 0.013 W/kg; SAR(10 g) = 0.009 W/kg**

Smallest distance from peaks to all points 3 dB below: Larger than measurement grid

Ratio of SAR at M2 to SAR at M1 = 64.1%

Maximum value of SAR (measured) = 0.0176 W/kg



## Appendix A.12 SAR Test Plots for LTE Band 7

Date: 2022-06-21

Test Laboratory : SGS Korea (Gunpo Laboratory)

File Name: [LTE 7\\_20MHz\\_1@0\\_QPSK\\_Front\\_CH21350.da53.0](#)

**DUT: TM04ANNABM2; Type: Car Telematics Modem; Serial: N-128**

Communication System: UID 0, LTE Band 7 (0); Frequency: 2560 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 2560$  MHz;  $\sigma = 1.977$  S/m;  $\epsilon_r = 37.457$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

DASY52 Configuration:

- Probe: EX3DV4 - SN7412; ConvF(7.59, 7.59, 7.59) @ 2560 MHz; Calibrated: 2022-04-29
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1595; Calibrated: 2022-01-24
- Phantom: ELI v5.0 1244; Type: QDOVA002AA; Serial: TP:1244
- DASY52 52.10.4(1527)SEMCAD X 14.6.14(7483)

**Body/LTE 7\_20MHz\_1@0\_QPSK\_Front\_CH21350/Area Scan (161x201x1):** Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 0.302 W/kg

**Body/LTE 7\_20MHz\_1@0\_QPSK\_Front\_CH21350/Zoom Scan (7x7x7)/Cube 0:** Measurement grid:

dx=5mm, dy=5mm, dz=5mm

Reference Value = 6.500 V/m; Power Drift = -0.19 dB


Peak SAR (extrapolated) = 0.375 W/kg

**SAR(1 g) = 0.193 W/kg; SAR(10 g) = 0.107 W/kg**

Smallest distance from peaks to all points 3 dB below: Larger than measurement grid

Ratio of SAR at M2 to SAR at M1 = 49%

Maximum value of SAR (measured) = 0.301 W/kg



## Appendix A.13 SAR Test Plots for LTE Band 12

Date: 2022-06-15

Test Laboratory : SGS Korea (Gunpo Laboratory)

File Name: [LTE 12\\_10MHz\\_1@25\\_QPSK\\_Front\\_CH23060.da53:0](#)

**DUT: TM04ANNABM2; Type: Car Telematics Modem; Serial: N-128**

Communication System: UID 0, LTE Band 12 (0); Frequency: 704 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 704$  MHz;  $\sigma = 0.861$  S/m;  $\epsilon_r = 43.473$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

DASY52 Configuration:

- Probe: EX3DV4 - SN7412; ConvF(10.36, 10.36, 10.36) @ 704 MHz; Calibrated: 2022-04-29
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1595; Calibrated: 2022-01-24
- Phantom: ELI v5.0 1244; Type: QDOVA002AA; Serial: TP:1244
- DASY52 52.10.4(1527)SEMCAD X 14.6.14(7483)

**Body/LTE 12\_10MHz\_1@25\_QPSK\_Front\_CH23060/Area Scan (101x131x1):** Interpolated grid:

$dx=1.500$  mm,  $dy=1.500$  mm

Maximum value of SAR (interpolated) = 0.0814 W/kg

**Body/LTE 12\_10MHz\_1@25\_QPSK\_Front\_CH23060/Zoom Scan (5x5x7)/Cube 0:** Measurement grid:

$dx=8$ mm,  $dy=8$ mm,  $dz=5$ mm

Reference Value = 9.949 V/m; Power Drift = 0.07 dB


Peak SAR (extrapolated) = 0.0900 W/kg

**SAR(1 g) = 0.069 W/kg; SAR(10 g) = 0.053 W/kg**

Smallest distance from peaks to all points 3 dB below: Larger than measurement grid

Ratio of SAR at M2 to SAR at M1 = 76.7%

Maximum value of SAR (measured) = 0.0822 W/kg



## Appendix A.14 SAR Test Plots for LTE Band 13

Date: 2022-06-15

Test Laboratory : SGS Korea (Gunpo Laboratory)

File Name: [LTE 13\\_10MHz\\_1@0\\_QPSK\\_Front\\_CH23230.da53.0](#)

**DUT: TM04ANNABM2; Type: Car Telematics Modem; Serial: N-128**

Communication System: UID 0, LTE Band 13 (0); Frequency: 782 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 782$  MHz;  $\sigma = 0.928$  S/m;  $\epsilon_r = 42.38$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

DASY52 Configuration:

- Probe: EX3DV4 - SN7412; ConvF(10.36, 10.36, 10.36) @ 782 MHz; Calibrated: 2022-04-29
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1595; Calibrated: 2022-01-24
- Phantom: ELI v5.0 1244; Type: QDOVA002AA; Serial: TP:1244
- DASY52 52.10.4(1527)SEMCAD X 14.6.14(7483)

**Body/LTE 13\_10MHz\_1@0\_QPSK\_Front\_CH23230/Area Scan (101x131x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.0598 W/kg

**Body/LTE 13\_10MHz\_1@0\_QPSK\_Front\_CH23230/Zoom Scan (5x5x7)/Cube 0:** Measurement grid:

dx=8mm, dy=8mm, dz=5mm

Reference Value = 7.762 V/m; Power Drift = -0.04 dB


Peak SAR (extrapolated) = 0.0690 W/kg

**SAR(1 g) = 0.050 W/kg; SAR(10 g) = 0.037 W/kg**

Smallest distance from peaks to all points 3 dB below: Larger than measurement grid

Ratio of SAR at M2 to SAR at M1 = 72.9%

Maximum value of SAR (measured) = 0.0625 W/kg



## Appendix A.15 SAR Test Plots for LTE Band 25

Date: 2022-06-11

Test Laboratory : SGS Korea (Gunpo Laboratory)

File Name: [LTE 25\\_20MHz\\_1@0\\_QPSK\\_Front\\_CH26590.da53.0](#)

**DUT: TM04ANNABM2; Type: Car Telematics Modem; Serial: N-128**

Communication System: UID 0, LTE Band 25 (0); Frequency: 1905 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated):  $f = 1905$  MHz;  $\sigma = 1.393$  S/m;  $\epsilon_r = 39.907$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

DASY52 Configuration:

- Probe: EX3DV4 - SN7412; ConvF(8.22, 8.22, 8.22) @ 1905 MHz; Calibrated: 2022-04-29
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1595; Calibrated: 2022-01-24
- Phantom: ELI v5.0 1244; Type: QDOVA002AA; Serial: TP:1244
- DASY52 52.10.4(1527)SEMCAD X 14.6.14(7483)

**Body/LTE 25\_20MHz\_1@0\_QPSK\_Front\_CH26590/Area Scan (101x91x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm

Info: Interpolated medium parameters used for SAR evaluation.

Maximum value of SAR (interpolated) = 0.413 W/kg

**Body/LTE 25\_20MHz\_1@0\_QPSK\_Front\_CH26590/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 8.016 V/m; Power Drift = -0.19 dB

Peak SAR (extrapolated) = 0.484 W/kg


**SAR(1 g) = 0.297 W/kg; SAR(10 g) = 0.188 W/kg**

Smallest distance from peaks to all points 3 dB below: Larger than measurement grid

Ratio of SAR at M2 to SAR at M1 = 60.3%

Info: Interpolated medium parameters used for SAR evaluation.

Maximum value of SAR (measured) = 0.414 W/kg



## Appendix A.16 SAR Test Plots for LTE Band 41

Date: 2022-06-22

Test Laboratory : SGS Korea (Gunpo Laboratory)

File Name: LTE 41\_20MHz\_1@0\_QPSK\_Front\_CH41490.da53.0

**DUT: TM04ANNABM2; Type: Car Telematics Modem; Serial: N-128**

Communication System: UID 0, LTE Band 41 (0); Frequency: 2680 MHz; Duty Cycle: 1:1.58016

Medium parameters used:  $f = 2680$  MHz;  $\sigma = 2.053$  S/m;  $\epsilon_r = 37.924$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

DASY52 Configuration:

- Probe: EX3DV4 - SN7412; ConvF(7.59, 7.59, 7.59) @ 2680 MHz; Calibrated: 2022-04-29
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1595; Calibrated: 2022-01-24
- Phantom: ELI v5.0 1244; Type: QDOVA002AA; Serial: TP:1244
- DASY52 52.10.4(1527)SEMCAD X 14.6.14(7483)

**Body/LTE 41\_20MHz\_1@0\_QPSK\_Front\_CH41490/Area Scan (161x201x1):** Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 0.0808 W/kg

**Body/LTE 41\_20MHz\_1@0\_QPSK\_Front\_CH41490/Zoom Scan (7x7x7)/Cube 0:** Measurement grid:

dx=5mm, dy=5mm, dz=5mm

Reference Value = 2.074 V/m; Power Drift = 0.17 dB


Peak SAR (extrapolated) = 0.104 W/kg

**SAR(1 g) = 0.049 W/kg; SAR(10 g) = 0.024 W/kg**

Smallest distance from peaks to all points 3 dB below: Larger than measurement grid

Ratio of SAR at M2 to SAR at M1 = 42.8%

Maximum value of SAR (measured) = 0.0812 W/kg



## Appendix A.17 SAR Test Plots for LTE Band 66

Date: 2022-07-04

Test Laboratory : SGS Korea (Gunpo Laboratory)

File Name: [LTE 66 20MHz\\_1@0\\_QPSK\\_Front\\_CH132072.da53:0](#)

**DUT: TM04ANNABM2; Type: Car Telematics Modem; Serial: N-128**

Communication System: UID 0, LTE Band 66 (0); Frequency: 1720 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 1720$  MHz;  $\sigma = 1.371$  S/m;  $\epsilon_r = 38.92$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

DASY52 Configuration:

- Probe: EX3DV4 - SN7412; ConvF(8.6, 8.6, 8.6) @ 1720 MHz; Calibrated: 2022-04-29
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1595; Calibrated: 2022-01-24
- Phantom: ELI v5.0 1244; Type: QDOVA002AA; Serial: TP:1244
- DASY52 52.10.4(1527)SEMCAD X 14.6.14(7483)

**Body/LTE 66 20MHz\_1@0\_QPSK\_Front\_CH132072/Area Scan (101x131x1):** Interpolated grid:

$dx=1.500$  mm,  $dy=1.500$  mm

Maximum value of SAR (interpolated) = 0.376 W/kg

**Body/LTE 66 20MHz\_1@0\_QPSK\_Front\_CH132072/Zoom Scan (5x5x7)/Cube 0:** Measurement grid:

$dx=8$ mm,  $dy=8$ mm,  $dz=5$ mm

Reference Value = 7.684 V/m; Power Drift = -0.12 dB


Peak SAR (extrapolated) = 0.441 W/kg

**SAR(1 g) = 0.273 W/kg; SAR(10 g) = 0.174 W/kg**

Smallest distance from peaks to all points 3 dB below: Larger than measurement grid

Ratio of SAR at M2 to SAR at M1 = 61.6%

Maximum value of SAR (measured) = 0.377 W/kg



## Appendix A.18 SAR Test Plots for LTE Band 71

Date: 2022-06-17

Test Laboratory : SGS Korea (Gunpo Laboratory)

File Name: [LTE 71\\_20MHz\\_1@0\\_QPSK\\_Front\\_CH133297.da53:0](#)

DUT: TM04ANNABM2; Type: Car Telematics Modem; Serial: N-128

Communication System: UID 0, LTE Band 71 (0); Frequency: 680.5 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated):  $f = 680.5$  MHz;  $\sigma = 0.858$  S/m;  $\epsilon_r = 43.293$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

DASY52 Configuration:

- Probe: EX3DV4 - SN7412; ConvF(10.36, 10.36, 10.36) @ 680.5 MHz; Calibrated: 2022-04-29
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1595; Calibrated: 2022-01-24
- Phantom: ELI v5.0 1244; Type: QDOVA002AA; Serial: TP:1244
- DASY52 52.10.4(1527)SEMCAD X 14.6.14(7483)

**Body/LTE 71\_20MHz\_1@0\_QPSK\_Front\_CH133297/Area Scan (101x131x1):** Interpolated grid:  
dx=1.500 mm, dy=1.500 mm

Info: Interpolated medium parameters used for SAR evaluation.

Maximum value of SAR (interpolated) = 0.0806 W/kg

**Body/LTE 71\_20MHz\_1@0\_QPSK\_Front\_CH133297/Zoom Scan (6x6x7)/Cube 0:** Measurement grid:

dx=8mm, dy=8mm, dz=5mm

Reference Value = 9.785 V/m; Power Drift = 0.09 dB

Peak SAR (extrapolated) = 0.0890 W/kg


**SAR(1 g) = 0.069 W/kg; SAR(10 g) = 0.053 W/kg**

Smallest distance from peaks to all points 3 dB below: Larger than measurement grid

Ratio of SAR at M2 to SAR at M1 = 76.6%

Info: Interpolated medium parameters used for SAR evaluation.

Maximum value of SAR (measured) = 0.0822 W/kg



## Appendix B.1 Uncertainty Analysis

| a<br>Uncertainty Component                                                       | c<br>Tol<br>(%) | d<br>Prob .<br>Dist. | e =<br>f(d,k)<br>Div. | f<br>Ci<br>(1g) | g<br>Ci<br>(10g) | h =          | i =           | k<br>Vi<br>(Veff) |
|----------------------------------------------------------------------------------|-----------------|----------------------|-----------------------|-----------------|------------------|--------------|---------------|-------------------|
|                                                                                  |                 |                      |                       |                 |                  | cxg/e        | cxg/e         |                   |
|                                                                                  |                 |                      |                       |                 |                  | lg<br>ui (%) | 10g<br>ui (%) |                   |
| Probe calibration                                                                | 6.55            | N                    | 1.00                  | 1.00            | 1.00             | 6.55         | 6.55          | ∞                 |
| Axial Isotropy                                                                   | 4.70            | R                    | 1.73                  | 0.71            | 0.71             | 1.92         | 1.92          | ∞                 |
| Hemispherical Isotropy                                                           | 9.60            | R                    | 1.73                  | 0.71            | 0.71             | 3.92         | 3.92          | ∞                 |
| Boundary Effects                                                                 | 2.00            | R                    | 1.73                  | 1.00            | 1.00             | 1.15         | 1.15          | ∞                 |
| Linearity                                                                        | 4.70            | R                    | 1.73                  | 1.00            | 1.00             | 2.71         | 2.71          | ∞                 |
| System Detection Limits                                                          | 0.25            | R                    | 1.73                  | 1.00            | 1.00             | 0.14         | 0.14          | ∞                 |
| Modulation Response                                                              | 4.80            | R                    | 1.73                  | 1.00            | 1.00             | 2.77         | 2.77          | ∞                 |
| Readout Electronics                                                              | 0.30            | N                    | 1.00                  | 1.00            | 1.00             | 0.30         | 0.30          | ∞                 |
| Response Time                                                                    | 0.80            | R                    | 1.73                  | 1.00            | 1.00             | 0.46         | 0.46          | ∞                 |
| Integration Time                                                                 | 2.60            | R                    | 1.73                  | 1.00            | 1.00             | 1.50         | 1.50          | ∞                 |
| RF Ambient Noise                                                                 | 3.00            | R                    | 1.73                  | 1.00            | 1.00             | 1.73         | 1.73          | ∞                 |
| RF Ambient Reflections                                                           | 3.00            | R                    | 1.73                  | 1.00            | 1.00             | 1.73         | 1.73          | ∞                 |
| Probe Positioner mechanical tolerance                                            | 0.40            | R                    | 1.73                  | 1.00            | 1.00             | 0.23         | 0.23          | ∞                 |
| Probe Positioning with respect to phantom shell                                  | 6.70            | R                    | 1.73                  | 1.00            | 1.00             | 3.87         | 3.87          | ∞                 |
| Extrapolation, interpolation, and integration algorithms for max. SAR evaluation | 4.00            | R                    | 1.73                  | 1.00            | 1.00             | 2.31         | 2.31          | ∞                 |
| Test sample positioning                                                          | 3.84/3.83       | N                    | 1.00                  | 1.00            | 1.00             | 3.84         | 3.83          | 29                |
| Device holder uncertainty                                                        | 2.79/2.66       | N                    | 1.00                  | 1.00            | 1.00             | 2.79         | 2.66          | 3                 |
| Output power variation - SAR drift measurement                                   | 5.00            | R                    | 1.73                  | 1.00            | 1.00             | 2.89         | 2.89          | ∞                 |
| Phantom uncertainty                                                              | 6.60            | R                    | 1.73                  | 1.00            | 1.00             | 3.81         | 3.81          | ∞                 |
| Liquid conductivity- Target                                                      | 5.00            | N                    | 1.00                  | 0.78            | 0.71             | 3.90         | 3.55          | ∞                 |
| Liquid conductivity- measurement                                                 | 3.55            | N                    | 1.00                  | 0.78            | 0.71             | 2.77         | 2.52          | 5                 |
| Liquid permittivity- Target                                                      | 5.00            | N                    | 1.00                  | 0.23            | 0.26             | 1.15         | 1.30          | ∞                 |
| Liquid permittivity- measurement                                                 | 3.40            | N                    | 1.00                  | 0.23            | 0.26             | 0.78         | 0.88          | 7                 |
| Liquid conductivity-temperature                                                  | 2.74            | R                    | 1.73                  | 0.78            | 0.71             | 1.23         | 1.12          | 21                |
| Liquid permittivity - temperature                                                | 1.94            | R                    | 1.73                  | 0.23            | 0.26             | 0.26         | 0.29          | 21                |
| Combined standard uncertainty                                                    |                 |                      | RSS                   |                 |                  | 13.38        | 13.22         | 438               |
| Expanded uncertainty<br>(95% CONFIDENCE INTERVAL)                                |                 |                      | k=2                   |                 |                  | 26.76        | 26.44         |                   |

**-THE END-**