

TEST REPORT

FCC Sub6 n66 Test for TM15FNEUJL1
Certification

APPLICANT
LG Electronics Inc.

REPORT NO.
CT-RF-2502-FC098-R1

DATE OF ISSUE
April 8, 2025

Tested by
Beom Jin Cho



Technical Manager
Jong Seok Lee



Accredited by KOLAS, Republic of KOREA

HCT CO., LTD.
BongJai Huh
BongJai Huh / CEO

**HCT CO.,LTD.**

2-6, 73, 74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, Republic of Korea
Tel. +82 31 645 6300 Fax. +82 31 645 6401

TEST REPORT

REPORT NO.

HCT-RF-2502-FC098-R1

DATE OF ISSUE

April 08, 2025

Applicant**LG Electronics Inc.**

128, Yeoui-daero, Yeongdeungpo-gu, Seoul, Republic of Korea

Product Name

Telematics

Model Name

TM15FNEUJL1

Date of Test

December 9, 2024 ~ February 24, 2025

Location of Test☒ Permanent Testing Lab ☐ On Site Testing

(Address : 74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, Republic of Korea)

FCC ID

BEJTM15FNEUJL1

FCC Classification:

PCS Licensed Transmitter (PCB)

Test Standard Used

FCC Rule Part: § 27

Test Results

PASS

REVISION HISTORY

The revision history for this test report is shown in table.

Revision No.	Date of Issue	Description
0	February 24, 2025	Initial Release
1	April 08, 2025	Revised the Product Name.

Notice

Content

The measurements shown in this report were made in accordance with the procedures specified in CFR47 section § 2.947. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them.

HCT CO., LTD. Certifies that no party to this application has subject to a denial of Federal benefits that includes FCC benefits pursuant to section 5301 of the Anti-Drug Abuse Act of 1998, 21 U.S. C. 853(a)

The results shown in this test report only apply to the sample(s), as received, provided by the applicant, unless otherwise stated.

The test results have only been applied with the test methods required by the standard(s).

The laboratory is not accredited for the test results marked *.

Information provided by the applicant is marked **.

Test results provided by external providers are marked ***.

When confirmation of authenticity of this test report is required, please contact www.hct.co.kr

This test report provides test result(s) under the scope accredited by the Korea Laboratory Accreditation Scheme (KOLAS), which signed the ILAC-MRA.

(KOLAS (KS Q ISO/IEC 17025) Accreditation No. KT197)

CONTENTS

1. GENERAL INFORMATION	5
1.1. MAXIMUM OUTPUT POWER	6
2. INTRODUCTION	7
2.1. DESCRIPTION OF EUT	7
2.2. MEASURING INSTRUMENT CALIBRATION.....	7
2.3. TEST FACILITY	7
3. DESCRIPTION OF TESTS	8
3.1 TEST PROCEDURE.....	8
3.2 RADIATED POWER	9
3.3 RADIATED SPURIOUS EMISSIONS	10
3.4 PEAK- TO- AVERAGE RATIO.....	11
3.5 OCCUPIED BANDWIDTH.	13
3.6 SPURIOUS AND HARMONIC EMISSIONS AT ANTENNA TERMINAL	14
3.7 BAND EDGE	15
3.8 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE.....	17
3.9 WORST CASE(RADIATED TEST).....	18
3.10 WORST CASE(CONDUCTED TEST)	19
4. LIST OF TEST EQUIPMENT	20
5. MEASUREMENT UNCERTAINTY.....	21
6. SUMMARY OF TEST RESULTS	22
7. SAMPLE CALCULATION	24
8. TEST DATA	26
8.1 EQUIVALENT ISOTROPIC RADIATED POWER	26
8.2 RADIATED SPURIOUS EMISSIONS	31
8.3 PEAK-TO-AVERAGE RATIO	32
8.4 OCCUPIED BANDWIDTH	33
8.5 CONDUCTED SPURIOUS EMISSIONS.....	34
8.6 BAND EDGE	34
8.7 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE.....	35
9. TEST PLOTS	40
10. ANNEX A_ TEST SETUP PHOTO	151

MEASUREMENT REPORT

1. GENERAL INFORMATION

Applicant Name:	LG Electronics Inc.
Address:	128, Yeoui-daero, Yeongdeungpo-gu, Seoul, Republic of Korea
FCC ID:	BEJTM15FNEUJL1
Application Type:	Certification
FCC Classification:	PCS Licensed Transmitter (PCB)
FCC Rule Part(s):	§ 27
EUT Type:	Telematics
Model(s):	TM15FNEUJL1
SCS(kHz):	15
Bandwidth(MHz):	5, 10, 15, 20, 40
Waveform:	CP-OFDM, DFT-S-OFDM
Modulation:	DFT-S-OFDM: PI/2 BPSK, QPSK, 16QAM, 64QAM, 256QAM CP-OFDM: QPSK, 16QAM, 64QAM, 256QAM
Tx Frequency:	1712.5 MHz – 1777.5 MHz (Sub6 n66(5 MHz)) 1715.0 MHz – 1775.0 MHz (Sub6 n66(10 MHz)) 1717.5 MHz – 1772.5 MHz (Sub6 n66(15 MHz)) 1720.0 MHz – 1770.0 MHz (Sub6 n66(20 MHz)) 1730.0 MHz – 1760.0 MHz (Sub6 n66(40 MHz))
Date(s) of Tests:	December 9, 2024 ~ February 24, 2025
Serial number:	Radiated : 410VIXV000304(NAD) Conducted : 410VIXV000305(NAD)
Antenna Information	Please refer to the Antenna Specification document.

1.1. MAXIMUM OUTPUT POWER

Mode (MHz)	Tx Frequency (MHz)	Emission Designator	Modulation	Conducted Output Power	
				Max. Power (W)	Max. Power (dBm)
Sub6 n66 (5)	1712.5 – 1777.5	4M50G7D	PI/2 BPSK	0.235	23.71
		4M50G7D	QPSK	0.237	23.75
		4M50W7D	16QAM	0.191	22.80
		4M50W7D	64QAM	0.131	21.18
		4M51W7D	256QAM	0.081	19.10
Sub6 n66 (10)	1715.0 – 1775.0	8M98G7D	PI/2 BPSK	0.239	23.78
		8M97G7D	QPSK	0.242	23.84
		8M96W7D	16QAM	0.187	22.71
		8M99W7D	64QAM	0.135	21.31
		8M99W7D	256QAM	0.084	19.24
Sub6 n66 (15)	1717.5 – 1772.5	13M5G7D	PI/2 BPSK	0.249	23.96
		13M5G7D	QPSK	0.248	23.95
		13M5W7D	16QAM	0.197	22.95
		13M5W7D	64QAM	0.139	21.43
		13M4W7D	256QAM	0.088	19.43
Sub6 n66 (20)	1720.0 – 1770.0	18M0G7D	PI/2 BPSK	0.245	23.90
		17M9G7D	QPSK	0.249	23.96
		17M9W7D	16QAM	0.196	22.92
		17M9W7D	64QAM	0.137	21.37
		17M9W7D	256QAM	0.086	19.37
Sub6 n66 (40)	1730.0 – 1760.0	38M7G7D	PI/2 BPSK	0.254	24.04
		38M6G7D	QPSK	0.252	24.02
		38M6W7D	16QAM	0.191	22.81
		38M7W7D	64QAM	0.134	21.26
		38M6W7D	256QAM	0.090	19.52

2. INTRODUCTION

2.1. DESCRIPTION OF EUT

Please refer to the [2G3G] Test Report.

2.2. MEASURING INSTRUMENT CALIBRATION

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipment, which is traceable to recognized national standards.

2.3. TEST FACILITY

The Fully-anechoic chamber and conducted measurement facility used to collect the radiated data are located at the 74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, Republic of Korea.

3. DESCRIPTION OF TESTS

3.1 TEST PROCEDURE

Test Description	Test Procedure Used
Occupied Bandwidth	- KDB 971168 D01 v03r01 – Section 4.3 - ANSI C63.26-2015 – Section 5.4.4
Band Edge	- KDB 971168 D01 v03r01 – Section 6.0 - ANSI C63.26-2015 – Section 5.7
Spurious and Harmonic Emissions at Antenna Terminal	- KDB 971168 D01 v03r01 – Section 6.0 - ANSI C63.26-2015 – Section 5.7
Conducted Output Power	- N/A (See SAR Report)
Peak- to- Average Ratio	- KDB 971168 D01 v03r01 – Section 5.7 - ANSI C63.26-2015 – Section 5.2.3.4
Frequency stability	- ANSI C63.26-2015 – Section 5.6
Radiated Power	- ANSI C63.26-2015 – Section 5.2.4.4 - KDB 971168 D01 v03r01 – Section 5.8
Radiated Spurious and Harmonic Emissions	- ANSI C63.26-2015 – Section 5.5.3 - KDB 971168 D01 v03r01 – Section 5.8

3.2 RADIATED POWER

Test Overview

Radiated tests are performed in the Fully-anechoic chamber.

The equipment under test is placed on a non-conductive table 3-meters away from the receive antenna.

Test Settings

1. Radiated power measurements are performed using the signal analyzer's "channel power" measurement capability for signals with continuous operation.
2. RBW = 1 – 5 % of the expected OBW, not to exceed 1 MHz
3. VBW $\geq$ 3 x RBW
4. Span = 1.5 times the OBW
5. No. of sweep points > 2 x span / RBW
6. Detector = RMS
7. Trigger is set to "free run" for signals with continuous operation with the sweep times set to "auto".
8. The integration bandwidth was roughly set equal to the measured OBW of the signal for signals with continuous operation.
9. Trace mode = trace averaging (RMS) over 100 sweeps
10. The trace was allowed to stabilize

Test Note

1. The turntable is rotated through 360 degrees, and the receiving antenna scans in order to determine the level of the maximized emission.
2. A half wave dipole is then substituted in place of the EUT. For emissions above 1 GHz, a horn antenna is substituted in place of the EUT. The substitute antenna is driven by a signal generator and the previously recorded signal was duplicated.

The power is calculated by the following formula;

$$P_d \text{ (dBm)} = P_g \text{ (dBm)} - \text{cable loss (dB)} + \text{antenna gain (dB)}$$

Where: P_d is the dipole equivalent power and P_g is the generator output power into the substitution antenna.

3. The maximum value is calculated by adding the forward power to the calibrated source plus its appropriate gain value.

These steps are repeated with the receiving antenna in both vertical and horizontal polarization. the difference between the gain of the horn and an isotropic antenna are taken into consideration

4. The EUT was tested in three orthogonal planes(X, Y, Z) and in all possible test configurations and positioning.
5. All measurements are performed as RMS average measurements while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies.

3.3 RADIATED SPURIOUS EMISSIONS

Test Overview

Radiated tests are performed in the Fully-anechoic chamber.

Radiated Spurious Emission Measurements at 3 meters by Substitution Method.

Test Settings

1. RBW = 100 kHz for emissions below 1 GHz and 1 MHz for emissions above 1 GHz
2. VBW $\geq$ 3 x RBW
3. Span = 1.5 times the OBW
4. No. of sweep points $>$ 2 x span / RBW
5. Detector = Peak
6. Trace mode = Max Hold
7. The trace was allowed to stabilize
8. Test channel : Low/ Middle/ High
9. Frequency range : We are performed all frequency to 10th harmonics from 9 kHz.

Test Note

1. Measurements value show only up to 3 maximum emissions noted, or would be lesser
if no specific emissions from the EUT are recorded (ie: margin $>$ 20 dB from the applicable limit)
and considered that's already beyond the background noise floor.
2. The EUT was tested in three orthogonal planes(X, Y, Z) and in all possible test configurations and positioning.
The worst case emissions are reported with the EUT positioning, modulations, RB sizes and offsets,
and channel bandwidth configurations shown in the test data
3. For spurious emissions above 1 GHz, a horn antenna is substituted in place of the EUT. The substitute antenna is driven by a signal generator and the previously recorded signal was duplicated.
The spurious emissions is calculated by the following formula;


$$\text{Result}_{(\text{dBm})} = P_{g(\text{dBm})} - \text{cable loss}_{(\text{dB})} + \text{antenna gain}_{(\text{dBi})}$$

Where: P_g is the generator output power into the substitution antenna.

If the fundamental frequency is below 1 GHz, RF output power has been converted to EIRP.

$$\text{EIRP}_{(\text{dBm})} = \text{ERP}_{(\text{dBm})} + 2.15$$

3.4 PEAK- TO- AVERAGE RATIO



Test setup

① CCDF Procedure for PAPR

Test Settings

1. Set resolution/measurement bandwidth $\geq$ signal's occupied bandwidth;
2. Set the number of counts to a value that stabilizes the measured CCDF curve;
3. Set the measurement interval as follows:
 - .- for continuous transmissions, set to 1 ms,
 - .- or burst transmissions, employ an external trigger that is synchronized with the EUT burst timing sequence, or use the internal burst trigger with a trigger level that allows the burst to stabilize and set the measurement interval to a time that is less than or equal to the burst duration.
4. Record the maximum PAPR level associated with a probability of 0.1 %.

② Alternate Procedure for PAPR

Use one of the procedures presented in 5.2(ANSI C63.26-2015) to measure the total peak power and record as P_{Pk} .
 Use one of the applicable procedures presented 5.2(ANSI C63.26-2015) to measure the total average power and record as P_{Avg} . Determine the P.A.R. from:

$$P.A.R. (dB) = P_{Pk} (dBm) - P_{Avg} (dBm) \quad (P_{Avg} = \text{Average Power} + \text{Duty cycle Factor})$$

Test Settings(Peak Power)


The measurement instrument must have a RBW that is greater than or equal to the OBW of the signal to be measured and a VBW $\geq 3 \times$ RBW.

1. Set the RBW $\geq$ OBW.
2. Set VBW $\geq 3 \times$ RBW.
3. Set span $\geq 2 \times$ OBW.
4. Sweep time $\geq 10 \times$ (number of points in sweep) $\times$ (transmission symbol period).
5. Detector = peak.
6. Trace mode = max hold.
7. Allow trace to fully stabilize.
8. Use the peak marker function to determine the peak amplitude level.

Test Settings(Average Power)

1. Set span to $2 \times$ to $3 \times$ the OBW.
2. Set RBW $\geq$ OBW.
3. Set VBW $\geq 3 \times$ RBW.
4. Set number of measurement points in sweep $\geq 2 \times$ span / RBW.
5. Sweep time:
Set $\geq [10 \times (\text{number of points in sweep}) \times (\text{transmission period})]$ for single sweep (automation-compatible) measurement. The transmission period is the (on + off) time.
6. Detector = power averaging (rms).
7. Set sweep trigger to "free run."
8. Trace average at least 100 traces in power averaging (rms) mode if sweep is set to auto-couple. (To accurately determine the average power over the on and off period of the transmitter, it can be necessary to increase the number of traces to be averaged above 100 or, if using a manually configured sweep time, increase the sweep time.)
9. Use the peak marker function to determine the maximum amplitude level.
10. Add $[10 \log (1/\text{duty cycle})]$ to the measured maximum power level to compute the average power during continuous transmission. For example, add $[10 \log (1/0.25)] = 6$ dB if the duty cycle is a constant 25 %.

3.5 OCCUPIED BANDWIDTH.



Test setup

The width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5 % of the total mean power of a given emission.

The EUT makes a call to the communication simulator.


The conducted occupied bandwidth used the power splitter via EUT RF power connector between simulation base station and spectrum analyzer.

The communication simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency. Use OBW measurement function of Spectrum analyzer to measure 99 % occupied bandwidth

Test Settings

1. The signal analyzer's automatic bandwidth measurement capability was used to perform the 99 % occupied bandwidth and the 26 dB bandwidth. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. RBW = 1 – 5 % of the expected OBW
3. VBW $\geq$ 3 x RBW
4. Detector = Peak
5. Trace mode = max hold
6. Sweep = auto couple
7. The trace was allowed to stabilize
8. If necessary, steps 2 – 7 were repeated after changing the RBW such that it would be within 1 – 5 % of the 99 % occupied bandwidth observed in Step 7

3.6 SPURIOUS AND HARMONIC EMISSIONS AT ANTENNA TERMINAL



Test setup


Test Overview

The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer. The spectrum is scanned from the lowest frequency generated in the equipment up to a frequency including its 10th harmonic. All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

Test Settings

1. RBW = 1 MHz
2. VBW $\geq$ 3 MHz
3. Detector = Peak
4. Trace Mode = Max Hold
5. Sweep time = auto
6. Number of points in sweep $\geq$ 2 x Span / RBW

3.7 BAND EDGE



Test setup

Test Overview

All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at its maximum power and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

Test Settings

1. Start and stop frequency were set such that the band edge would be placed in the center of the plot
2. Span was set large enough so as to capture all out of band emissions near the band edge
3. Within 1MHz of the channel edge the RBW should be 2 % of EBW, then 1 MHz after that.
4. VBW > 3 x RBW
5. Detector = RMS
6. Number of sweep points $\geq 2 \times \text{Span/RBW}$
7. Trace mode = trace average
8. Sweep time = auto couple
9. The trace was allowed to stabilize

Test Notes


According to FCC 22.917, 24.238, 27.53 specified that power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB. In the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed.

All measurements were done at 2 channels (low and high operational frequency range.)

The band edge measurement used the power splitter via EUT RF power connector between simulation base station and spectrum analyzer.

Where $\text{Margin} < 1$ dB the emission level is either corrected by $10 \log(1 \text{ MHz} / \text{RB})$ or the emission is integrated over a 1 MHz bandwidth to determine the final result. When using the integration method the integration window is either centered on the emission or, for emissions at the band edge, centered by an offset of 500 kHz from the block edge so that the integration window is the 1 MHz adjacent to the block edge.

3.8 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE



Test setup

Test Overview

Frequency stability testing is performed in accordance with the guidelines of ANSI C63.26-2015.

The frequency stability of the transmitter is measured by:

1. Temperature:

The temperature is varied from -30 °C to +50 °C in 10 °C increments using an environmental chamber.

2. Primary Supply Voltage:

- . - Unless otherwise specified, vary primary supply voltage from 85 % to 115 % of the nominal value for other than hand carried battery equipment.
- . - For hand carried, battery powered equipment, reduce the primary ac or dc supply voltage to the battery operating end point, which shall be specified by the manufacturer.

Test Settings

1. The carrier frequency of the transmitter is measured at room temperature (20 °C to provide a reference).
2. The equipment is turned on in a “standby” condition for fifteen minutes before applying power to the transmitter.
Measurement of the carrier frequency of the transmitter is made within one minute after applying power to the transmitter.
3. Frequency measurements are made at 10 °C intervals ranging from -30 °C to +50 °C. A period of at least one half-hour is provided to allow stabilization of the equipment at each temperature level.

3.9 WORST CASE(RADIATED TEST)

- The EUT was tested in three orthogonal planes(X, Y, Z) and in all possible test configurations and positioning.
- The worst case is reported with the EUT positioning, modulations, and paging service configurations shown in the test data.
- All modes of operation were investigated and the worst case configuration results are reported.
Mode: SA, NSA
Worst case: SA
- JIG was used to test the EUT. (EUT + JIG)
- All simultaneous transmission scenarios of operation were investigated, and the test results showed no additional significant emissions relative to the least restrictive limit were observed.
Therefore, only the worst case(stand-alone) results were reported.
- Radiated Spurious emissions are measured while operating in EN-DC mode with Sub 6 NR carrier as well as an LTE carrier (anchor).
All EN-DC mode of operation (=anchor) were investigated and the test results were measured No Peak Found.
The test results which are attenuated more than 20 dB below the permissible value, so it was not reported.
- All RB sizes, offsets of operation were investigated and the worst case configuration results are reported.
Please refer to the table below.
- In the case of radiated spurious emissions, all bandwidth of operation was investigated and the worst case bandwidth results are reported. (Worst case : 5 MHz)

[Worst case]

Test Description	Modulation	RB size	RB offset	Axis
Equivalent Isotropic Radiated Power	PI/2 BPSK, QPSK, 16QAM, 64QAM, 256QAM	See Section 8.1		Y
Radiated Spurious Emissions	PI/2 BPSK	See Section 8.2		Y

3.10 WORST CASE(CONDUCTED TEST)

- Waveform : All Waveform of operation were investigated and the worst case configuration results are reported.
(Worst case: DFT-S-OFDM)
- Modulation : All Modulation of operation were investigated and the worst case configuration results are reported.
(Worst case: PI/2 BPSK)
- All modes of operation were investigated and the worst case configuration results are reported.
Mode: SA, NSA
Worst case: SA
- JIG was used to test the EUT. (EUT + JIG)
- All RB sizes, offsets of operation were investigated and the worst case configuration results are reported.
Please refer to the table below.

[Worst case]

Test Description	Modulation	Bandwidth (MHz)	Frequency	RB size	RB offset
Occupied Bandwidth, Peak-To-Average Ratio	PI/2 BPSK, QPSK, 16QAM, 64QAM, 256QAM	5, 10, 15, 20,40	Mid	Full RB	0
Band Edge	PI/2 BPSK	5	Low	1	0
			High	1	24
		10	Low	1	0
			High	1	51
		15	Low	1	0
			High	1	78
		20	Low	1	0
			High	1	105
		40	Low	1	0
			High	1	215
		5, 10, 15, 20,40	Low, High	Full RB	0
Spurious and Harmonic Emissions at Antenna Terminal	PI/2 BPSK	5, 10, 15, 20,40	Low, Mid, High	1	1

4. LIST OF TEST EQUIPMENT

Equipment	Model	Manufacture	Serial No.	Due to Calibration	Calibration Interval
RF Switching System	Switch box(1 G HPF+LNA)	HCT CO., LTD.,	F2L2	12/12/2025	Annual
RF Switching System	Switch box(3 G HPF+LNA)	HCT CO., LTD.,	F2L3	12/12/2025	Annual
RF Switching System	Switch box(LNA)	HCT CO., LTD.,	F2L5	12/12/2025	Annual
RF Switching System	Switch box(6 G HPF+LNA)	HCT CO., LTD.,	F2L14	12/12/2025	Annual
Power Amplifier	CBL18265035	CERNEX	22966	11/07/2025	Annual
Power Amplifier	CBL26405040	CERNEX	25956	02/26/2025	Annual
Power Splitter(DC ~ 26.5 GHz)	11667B	Hewlett Packard	5001	04/17/2025	Annual
DC Power Supply	E3632A	Agilent	MY40010147	08/06/2025	Annual
Dipole Antenna	UHAP	Schwarzbeck	01274	03/10/2026	Biennial
Dipole Antenna	UHAP	Schwarzbeck	01288	08/07/2026	Biennial
Chamber	SU-642	ESPEC	93022487	06/27/2025	Annual
Horn Antenna(1 ~ 18 GHz)	BBHA 9120D	Schwarzbeck	03197	11/28/2025	Biennial
Horn Antenna(1 ~ 18 GHz)	BBHA 9120D	Schwarzbeck	03201	11/28/2025	Biennial
Horn Antenna(15 ~ 40 GHz)	BBHA 9170	Schwarzbeck	BBHA9170342	09/20/2026	Biennial
Horn Antenna(15 ~ 40 GHz)	BBHA 9170	Schwarzbeck	BBHA9170124	03/28/2025	Biennial
Signal Analyzer(10 Hz ~ 26.5 GHz)	N9020A	Agilent	MY52090906	04/19/2025	Annual
ATTENUATOR(20 dB)	8493C	Hewlett Packard	17280	04/17/2025	Annual
Spectrum Analyzer(10 Hz ~ 40 GHz)	FSV40	ROHDE & SCHWARZ	101733	09/19/2025	Annual
Base Station	8960 (E5515C)	Agilent	MY48360800	08/05/2025	Annual
Loop Antenna(9 kHz ~ 30 MHz)	FMZB1513	Schwarzbeck	1513-333	03/07/2026	Biennial
Trilog Broadband Antenna	VULB9168	Schwarzbeck	895	08/28/2026	Biennial
Trilog Broadband Antenna	VULB9168	Schwarzbeck	1135	08/19/2026	Biennial
Radio Communication Test Station	MT8000A	Anritsu Corp.	6272613402	08/28/2025	Annual
SIGNAL GENERATOR (100 kHz ~ 40 GHz)	SMB100A	REOHDE & SCHWARZ	177633	07/26/2025	Annual
Signal Analyzer(5 Hz ~ 40.0 GHz)	N9030B	KEYSIGHT	MY55480167	05/17/2025	Annual
Signal & Spectrum Analyzer (2 Hz~67 GHz)	FSW67	REOHDE & SCHWARZ	101736	05/23/2025	Annual
FCC LTE Mobile Conducted RF Automation Test Software	-	HCT CO., LTD.,	-	-	-

Note:

- Equipment listed above that has a calibration due date during the testing period, the testing is completed before equipment expiration date.
- Especially, all antenna for measurement is calibrated in accordance with the requirements of C63.5 (Version : 2017).

5. MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.4:2014.

All measurement uncertainty values are shown with a coverage factor of $k=2$ to indicate a 95 % level of confidence. The measurement data shown herein meets or exceeds the U_{CISPR} measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Parameter	Expanded Uncertainty ($\pm$ kHz)
Occupied Bandwidth	95 (Confidence level about 95 %, $k=2$)
Frequency stability	28 (Confidence level about 95 %, $k=2$)

Parameter	Expanded Uncertainty ($\pm$ dB)
Block Edge	0.70 (Confidence level about 95 %, $k=2$)
Conducted Spurious Emissions	1.18 (Confidence level about 95 %, $k=2$)
Peak- to- Average Ratio	0.68 (Confidence level about 95 %, $k=2$)
Radiated Power	4.74 (Confidence level about 95 %, $k=2$)
Radiated Disturbance (9 kHz ~ 30 MHz)	4.36 (Confidence level about 95 %, $k=2$)
Radiated Disturbance (30 MHz ~ 1 GHz)	5.70 (Confidence level about 95 %, $k=2$)
Radiated Disturbance (1 GHz ~ 18 GHz)	5.52 (Confidence level about 95 %, $k=2$)
Radiated Disturbance (18 GHz ~ 40 GHz)	5.66 (Confidence level about 95 %, $k=2$)
Radiated Disturbance (Above 40 GHz)	5.58 (Confidence level about 95 %, $k=2$)

6. SUMMARY OF TEST RESULTS

Note. The decision rule applies 'simple acceptance'

6.1 Test Condition : Conducted Test

Test Description	FCC Part Section(s)	Test Limit	Test Result
Occupied Bandwidth	§ 2.1049	N/A	PASS
Band Edge / Spurious and Harmonic Emissions at Antenna Terminal.	§ 2.1051, § 27.53(h)	< 43 + 10log10 (P[Watts]) at Band Edge and for all out-of-band emissions	PASS
Conducted Output Power	§ 2.1046	N/A	<u>See Note1</u>
Peak- to- Average Ratio	§ 27.50(d)(5)	< 13 dB	PASS
Frequency stability / variation of ambient temperature	§ 2.1055, § 27.54	Emission must remain in band	PASS

Note:

1. See SAR Report
2. All conducted tests were tested using 5G Wireless Tester.

6.2 Test Condition: Radiated Test

Test Description	FCC Part Section(s)	Test Limit	Test Result
Equivalent Isotropic Radiated Power	§ 27.50(d)(4)	< 1 Watts max. EIRP	PASS
Radiated Spurious and Harmonic Emissions	§ 2.1053, § 27.53(h)	< 43 + 10log10 (P[Watts]) for all out-of band emissions	PASS

Note:

1. Radiated tests were tested using 5G Wireless Tester.

6.3. Data Referencing

Rule Part	Test item	Data Referencing	Comments
§2.1049	Occupied Bandwidth	Y	-
§2.1051, §27.53(m)(4)	Block Edge / Spurious and Harmonic Emissions at Antenna Terminal..	Y	-
§2.1051, §27.53(h)	Band Edge / Spurious and Harmonic Emissions at Antenna Terminal.	Y	-
§27.50(d)(5)	Peak- to- Average Ratio	Y	-
§2.1055, §27.54	Frequency stability / variation of ambient temperature	Y	-
§27.50(h)(2)	Effective Radiated Power Equivalent Isotropic Radiated Power	Y	Spot-check
§2.1053, §27.53(m)(4)	Radiated Spurious and Harmonic Emissions	Y	Spot-check
§2.1046	Conducted Output Power	Y	-

Spot-Check Result

1. Data was leveraged from model TM15FNEUJL0 for the certification of TM15FNEUJL1.
2. Please refer to the [FCC Evaluation] Report.

7. SAMPLE CALCULATION

7.1 ERP Sample Calculation

Ch./ Freq.		Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain (dBd)	C.L	Pol.	ERP	
channel	Freq.(MHz)						W	dBm
128	824.20	-21.37	38.40	-10.61	0.95	H	0.483	26.84

$$\text{ERP} = \text{Substitute LEVEL(dBm)} + \text{Ant. Gain} - \text{CL(Cable Loss)}$$

- 1) The EUT mounted on a non-conductive turntable is 2.5 meter above test site ground level.
- 2) During the test, the turn table is rotated until the maximum signal is found.
- 3) Record the field strength meter's level.
- 4) Replace the EUT with dipole/Horn antenna that is connected to a calibrated signal generator.
- 5) Increase the signal generator output till the field strength meter's level is equal to the item (3).
- 6) The signal generator output level with Ant. Gain and cable loss are the rating of effective radiated power.

7.2 EIRP Sample Calculation

Ch./ Freq.		Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain (dBi)	C.L	Pol.	EIRP	
channel	Freq.(MHz)						W	dBm
20175	1,732.50	-15.75	18.45	9.90	1.76	H	0.456	26.59

$$\text{EIRP} = \text{Substitute LEVEL(dBm)} + \text{Ant. Gain} - \text{CL(Cable Loss)}$$

- 1) The EUT mounted on a non-conductive turntable is 2.5 meter above test site ground level.
- 2) During the test, the turn table is rotated until the maximum signal is found.
- 3) Record the field strength meter's level.
- 4) Replace the EUT with dipole/Horn antenna that is connected to a calibrated signal generator.
- 5) Increase the signal generator output till the field strength meter's level is equal to the item (3).
- 6) The signal generator output level with Ant. Gain and cable loss are the rating of equivalent isotropic radiated power.

7.3. Emission Designator

GSM Emission Designator

Emission Designator = 249KGXW
GSM BW = 249 kHz
G = Phase Modulation
X = Cases not otherwise covered
W = Combination (Audio/Data)

EDGE Emission Designator

Emission Designator = 249KG7W
GSM BW = 249 kHz
G = Phase Modulation
7 = Quantized/Digital Info
W = Combination (Audio/Data)

WCDMA Emission Designator

Emission Designator = 4M17F9W
WCDMA BW = 4.17 MHz
F = Frequency Modulation
9 = Composite Digital Info
W = Combination (Audio/Data)

QPSK Modulation

Emission Designator = 4M48G7D
LTE BW = 4.48 MHz
G = Phase Modulation
7 = Quantized/Digital Info
D = Data transmission; telemetry; telecommand

QAM Modulation

Emission Designator = 4M48W7D
LTE BW = 4.48 MHz
W = Amplitude/Angle Modulated
7 = Quantized/Digital Info
D = Data transmission; telemetry; telecommand

8. TEST DATA

8.1 EQUIVALENT ISOTROPIC RADIATED POWER

Freq (MHz)	Mod/ Bandwidth [SCS (kHz)]	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain (dBi)	C.L	Pol	Limit	EIRP		RB	
								W	W	dBm	Size	Offset
1712.5		PI/2 BPSK	-18.10	16.31	9.83	2.06	H	< 1.00	0.256	24.08	1	23
		QPSK	-18.12	16.29	9.83	2.06	H		0.255	24.06		
		16-QAM	-19.13	15.28	9.83	2.06	H		0.202	23.05		
		64-QAM	-20.65	13.76	9.83	2.06	H		0.142	21.53		
		256-QAM	-22.69	11.72	9.83	2.06	H		0.089	19.49		
1745.0	Sub6 n66/ 5 MHz [15 kHz]	PI/2 BPSK	-16.23	17.99	9.98	2.07	H	< 1.00	0.389	25.90	1	12
		QPSK	-16.37	17.85	9.98	2.07	H		0.377	25.76		
		16-QAM	-17.26	16.96	9.98	2.07	H		0.307	24.87		
		64-QAM	-18.79	15.43	9.98	2.07	H		0.216	23.34		
		256-QAM	-20.91	13.31	9.98	2.07	H		0.132	21.22		
1777.5		PI/2 BPSK	-15.58	19.07	10.07	2.09	H	< 1.00	0.506	27.05	1	23
		QPSK	-15.59	19.06	10.07	2.09	H		0.506	27.04		
		16-QAM	-16.56	18.09	10.07	2.09	H		0.405	26.07		
		64-QAM	-18.06	16.59	10.07	2.09	H		0.286	24.57		
		256-QAM	-19.99	14.66	10.07	2.09	H		0.183	22.64		

Freq (MHz)	Mod/ Bandwidth [SCS (kHz)]	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain (dBi)	C.L	Pol	Limit	EIRP		RB	
								W	W	dBm	Size	Offset
1715.0		PI/2 BPSK	-17.43	16.98	9.83	2.06	H	< 1.00	0.299	24.75	1	50
		QPSK	-17.53	16.88	9.83	2.06	H		0.292	24.65		
		16-QAM	-18.52	15.89	9.83	2.06	H		0.232	23.66		
		64-QAM	-19.98	14.43	9.83	2.06	H		0.166	22.20		
		256-QAM	-22.05	12.36	9.83	2.06	H		0.103	20.13		
1745.0	Sub6 n66/ 10 MHz [15 kHz]	PI/2 BPSK	-16.02	18.20	9.98	2.07	H	< 1.00	0.408	26.11	1	50
		QPSK	-16.15	18.07	9.98	2.07	H		0.397	25.98		
		16-QAM	-17.14	17.08	9.98	2.07	H		0.315	24.99		
		64-QAM	-18.62	15.60	9.98	2.07	H		0.224	23.51		
		256-QAM	-20.69	13.53	9.98	2.07	H		0.139	21.44		
1775.0		PI/2 BPSK	-15.51	19.08	10.06	2.09	H	< 1.00	0.506	27.05	1	50
		QPSK	-15.57	19.02	10.06	2.09	H		0.500	26.99		
		16-QAM	-16.57	18.02	10.06	2.09	H		0.397	25.99		
		64-QAM	-18.08	16.51	10.06	2.09	H		0.281	24.48		
		256-QAM	-20.02	14.57	10.06	2.09	H		0.180	22.54		

Freq (MHz)	Mod/ Bandwidth [SCS (kHz)]	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain (dBi)	C.L	Pol	Limit	EIRP		RB	
								W	W	dBm	Size	Offset
1717.5	Sub6 n66/ 15 MHz [15 kHz]	PI/2 BPSK	-17.22	17.08	9.86	2.06	H	< 1.00	0.307	24.88	1	77
		QPSK	-17.30	17.00	9.86	2.06	H		0.302	24.80		
		16-QAM	-18.33	15.97	9.86	2.06	H		0.238	23.77		
		64-QAM	-19.81	14.49	9.86	2.06	H		0.169	22.29		
		256-QAM	-21.87	12.43	9.86	2.06	H		0.105	20.23		
1745.0		PI/2 BPSK	-16.04	18.18	9.98	2.07	H		0.406	26.09	1	77
		QPSK	-16.05	18.17	9.98	2.07	H		0.405	26.08		
		16-QAM	-17.09	17.13	9.98	2.07	H		0.319	25.04		
		64-QAM	-18.47	15.75	9.98	2.07	H		0.232	23.66		
		256-QAM	-20.63	13.59	9.98	2.07	H		0.141	21.50		
1772.5		PI/2 BPSK	-15.57	19.02	10.06	2.09	H	0.500	26.99	1	77	
		QPSK	-15.59	19.00	10.06	2.09	H	0.497	26.97			
		16-QAM	-16.57	18.02	10.06	2.09	H	0.397	25.99			
		64-QAM	-18.11	16.48	10.06	2.09	H	0.278	24.45			
		256-QAM	-20.11	14.48	10.06	2.09	H	0.176	22.45			

Freq (MHz)	Mod/ Bandwidth [SCS (kHz)]	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain (dBi)	C.L	Pol	Limit	EIRP		RB	
								W	W	dBm	Size	Offset
1720.0		PI/2 BPSK	-16.96	17.34	9.86	2.06	H	< 1.00	0.327	25.14	1	104
		QPSK	-17.01	17.29	9.86	2.06	H		0.323	25.09		
		16-QAM	-18.03	16.27	9.86	2.06	H		0.255	24.07		
		64-QAM	-19.59	14.71	9.86	2.06	H		0.178	22.51		
		256-QAM	-21.51	12.79	9.86	2.06	H		0.115	20.59		
1745.0	Sub6 n66/ 20 MHz [15 kHz]	PI/2 BPSK	-15.87	18.35	9.98	2.07	H		0.423	26.26	1	104
		QPSK	-15.93	18.29	9.98	2.07	H		0.417	26.20		
		16-QAM	-17.00	17.22	9.98	2.07	H		0.326	25.13		
		64-QAM	-18.46	15.76	9.98	2.07	H		0.233	23.67		
		256-QAM	-20.49	13.73	9.98	2.07	H		0.146	21.64		
1770.0		PI/2 BPSK	-15.59	18.94	10.05	2.09	H		0.489	26.90	1	53
		QPSK	-15.62	18.91	10.05	2.09	H		0.487	26.87		
		16-QAM	-16.62	17.91	10.05	2.09	H		0.387	25.87		
		64-QAM	-18.04	16.49	10.05	2.09	H		0.279	24.45		
		256-QAM	-20.10	14.43	10.05	2.09	H		0.174	22.39		

Freq (MHz)	Mod/ Bandwidth [SCS (kHz)]	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain (dBi)	C.L	Pol	Limit	EIRP		RB	
								W	W	dBm	Size	Offset
1730.0	Sub6 n66/ 40 MHz [15 kHz]	PI/2 BPSK	-16.00	18.27	9.91	2.08	H	< 1.00	0.408	26.10	1	214
		QPSK	-16.08	18.19	9.91	2.08	H		0.400	26.02		
		16-QAM	-17.10	17.17	9.91	2.08	H		0.316	25.00		
		64-QAM	-18.67	15.60	9.91	2.08	H		0.221	23.43		
		256-QAM	-20.44	13.83	9.91	2.08	H		0.146	21.66		
1745.0		PI/2 BPSK	-15.71	18.51	9.98	2.07	H		0.438	26.42	1	214
		QPSK	-15.72	18.50	9.98	2.07	H		0.438	26.41		
		16-QAM	-16.71	17.51	9.98	2.07	H		0.349	25.42		
		64-QAM	-18.11	16.11	9.98	2.07	H		0.252	24.02		
		256-QAM	-19.80	14.42	9.98	2.07	H		0.171	22.33		
1760.0		PI/2 BPSK	-15.98	18.30	10.03	2.09	H	0.421	26.24	1	108	
		QPSK	-16.04	18.24	10.03	2.09	H	0.415	26.18			
		16-QAM	-17.07	17.21	10.03	2.09	H	0.328	25.15			
		64-QAM	-18.55	15.73	10.03	2.09	H	0.233	23.67			
		256-QAM	-20.25	14.03	10.03	2.09	H	0.158	21.97			

8.2 RADIATED SPURIOUS EMISSIONS

NR Band:	<u>N66</u>
Bandwidth:	<u>5 MHz</u>
Modulation:	<u>PI/2 BPSK</u>
Distance:	<u>3 meters</u>
SCS:	<u>15 kHz</u>

Ch	Freq (MHz)	Measured Level (dBm)	Ant. Gain (dBi)	Substitute Level (dBm)	C.L	Pol	Result (dBm)	Limit (dBm)	RB	
									Size	Offset
342500 (1712.5)	3 425.00	-51.51	11.33	-59.09	2.99	H	-50.75	-13.00	1	23
	5 137.50	-52.42	11.27	-54.15	3.80	H	-46.68	-13.00		
	6 850.00	-51.66	11.07	-47.81	4.36	H	-41.10	-13.00		
	8 562.50	-53.25	11.13	-44.76	4.92	H	-38.55	-13.00		
	10 275.00	-52.28	11.66	-44.38	5.58	H	-38.30	-13.00		
349000 (1745.0)	3 490.00	-52.54	11.56	-60.77	3.04	H	-52.25	-13.00	1	12
	5 235.00	-53.77	11.53	-55.08	3.78	H	-47.33	-13.00		
	6 980.00	-51.26	11.12	-48.08	4.48	H	-41.44	-13.00		
	8 725.00	-53.58	11.18	-43.62	5.03	H	-37.47	-13.00		
	10 470.00	-52.72	11.89	-46.00	5.59	H	-39.70	-13.00		
355500 (1777.5)	3 555.00	-52.01	11.67	-60.17	3.09	H	-51.59	-13.00	1	23
	5 332.50	-52.65	11.72	-54.20	3.79	H	-46.27	-13.00		
	7 110.00	-51.25	10.74	-47.06	4.48	H	-40.80	-13.00		
	8 887.50	-53.82	11.34	-44.08	5.08	H	-37.82	-13.00		
	10 665.00	-52.80	11.71	-45.70	5.68	H	-39.67	-13.00		

8.3 PEAK-TO-AVERAGE RATIO

Band	Band Width	Frequency (MHz)	Modulation	Resource Block Size	Resource Block Offset	Data (dB)
Sub6 n66	5 MHz	1745.0	BPSK	25	0	4.09
			QPSK			4.66
			16-QAM			5.87
			64-QAM			6.24
			256-QAM			6.94
	10 MHz		BPSK	50		4.02
			QPSK			4.59
			16-QAM			5.57
			64-QAM			6.06
			256-QAM			6.66
	15 MHz		BPSK	75		4.22
			QPSK			4.60
			16-QAM			5.49
			64-QAM			5.99
			256-QAM			6.66
	20 MHz		BPSK	100		4.18
			QPSK			4.61
			16-QAM			5.56
			64-QAM			6.01
			256-QAM			6.63
	40 MHz		BPSK	216		3.97
			QPSK			4.62
			16-QAM			5.60
			64-QAM			6.04
			256-QAM			6.64

Note:

1. Plots of the EUT's Peak- to- Average Ratio are shown Page 41 ~ 65.

8.4 OCCUPIED BANDWIDTH

Band	Band Width	Frequency (MHz)	Modulation	Resource Block Size	Resource Block Offset	Data (MHz)
Sub6 n66	5 MHz	1745.0	BPSK	25	0	4.4977
			QPSK			4.4964
			16-QAM			4.4986
			64-QAM			4.4994
			256-QAM			4.5092
	10 MHz		BPSK	50		8.9781
			QPSK			8.9717
			16-QAM			8.9621
			64-QAM			8.9859
			256-QAM			8.9894
	15 MHz		BPSK	75		13.468
			QPSK			13.456
			16-QAM			13.457
			64-QAM			13.475
			256-QAM			13.438
	20 MHz		BPSK	100		17.953
			QPSK			17.927
			16-QAM			17.936
			64-QAM			17.930
			256-QAM			17.944
	40 MHz		BPSK	216		38.665
			QPSK			38.602
			16-QAM			38.630
			64-QAM			38.686
			256-QAM			38.565

Note:

1. Plots of the EUT's Occupied Bandwidth are shown Page 66 ~ 90.

8.5 CONDUCTED SPURIOUS EMISSIONS

Band	Band Width (MHz)	Frequency (MHz)	Frequency of Maximum Harmonic (GHz)	Factor (dB)	Measurement Maximum Data (dBm)	Result (dBm)	Limit (dBm)
Sub6 n66	5	1712.5	4.9552	26.600	-61.981	-35.381	-13.00
		1745.0	5.4736	27.520	-62.006	-34.486	
		1777.5	4.5564	26.600	-61.835	-35.235	
	10	1715.0	4.9153	26.600	-60.979	-34.379	
		1745.0	3.7787	26.600	-61.297	-34.697	
		1775.0	3.7488	26.600	-60.741	-34.141	
	15	1717.5	8.3649	27.520	-61.486	-33.966	
		1745.0	5.1147	27.520	-61.343	-33.823	
		1772.5	3.8086	26.600	-60.838	-34.238	
	20	1720.0	3.7887	26.600	-61.380	-34.780	
		1745.0	5.0050	27.520	-61.137	-33.617	
		1770.0	8.1057	27.520	-61.715	-34.195	
	40	1730.0	3.8186	26.600	-61.817	-35.217	
		1745.0	7.5075	27.520	-62.306	-34.786	
		1760.0	3.8086	26.600	-61.634	-35.034	

Note:

1. Plots of the EUT's Conducted Spurious Emissions are shown Page 91 ~ 120.
2. Result (dBm) = Measurement Maximum Data (dBm) + Factor (dB)
3. Factor(dB) = Cable Loss + Ext. Attenuator + Power Splitter

Frequency Range (GHz)	Factor [dB]
0.03 – 1	26.080
1 – 5	26.600
5 – 10	27.520
10 – 15	29.120
15 – 20	31.710
Above 20	32.350

8.6 BAND EDGE

- Plots of the EUT's Band Edge are shown Page 121 ~ 150.

8.7 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE

- ☐ BandWidth: 5 MHz
☐ Voltage(100 %): 12.000 VDC
☐ LIMIT: Emission must remain in band

Test. Frequency	Voltage	Temp.	Frequency	Frequency	Deviation	ppm
(MHz)	(%)	(°C)	(Hz)	Error (Hz)	(%)	
1712.5	100 %	+20(Ref)	1712 499 998	0.0	0.000 000	0.000
	100 %	-30	1712 500 014	16.4	0.000 001	0.010
	100 %	-20	1712 500 011	13.2	0.000 001	0.008
	100 %	-10	1712 500 008	10.8	0.000 001	0.006
	100 %	0	1712 500 006	8.7	0.000 001	0.005
	100 %	+10	1712 500 003	5.9	0.000 000	0.003
	100 %	+30	1712 500 001	3.2	0.000 000	0.002
	100 %	+40	1712 499 998	0.0	0.000 000	0.000
	100 %	+50	1712 499 995	-3.0	0.000 000	-0.002
	85 %	+20	1712 500 003	5.9	0.000 000	0.003
	115 %	+20	1712 500 006	8.7	0.000 001	0.005
1777.5	100 %	+20(Ref)	1777 500 001	0.0	0.000 000	0.000
	100 %	-30	1777 500 001	-0.6	0.000 000	0.000
	100 %	-20	1777 500 018	16.2	0.000 001	0.009
	100 %	-10	1777 500 012	10.4	0.000 001	0.006
	100 %	0	1777 500 014	12.8	0.000 001	0.007
	100 %	+10	1777 500 012	10.4	0.000 001	0.006
	100 %	+30	1777 500 011	9.1	0.000 001	0.005
	100 %	+40	1777 500 009	7.5	0.000 000	0.004
	100 %	+50	1777 500 007	5.4	0.000 000	0.003
	85 %	+20	1777 500 014	12.5	0.000 001	0.007
	115 %	+20	1777 500 018	16.3	0.000 001	0.009

☐ BandWidth: 10 MHz
☐ Voltage(100 %): 12.000 VDC
☐ LIMIT: Emission must remain in band

Test. Frequency	Voltage	Temp.	Frequency	Frequency	Deviation	ppm
(MHz)	(%)	(°C)	(Hz)	Error (Hz)	(%)	
1715.0	100 %	+20(Ref)	1714 999 997	0.0	0.000 000	0.000
	100 %	-30	1714 999 993	-3.8	0.000 000	-0.002
	100 %	-20	1714 999 992	-4.8	0.000 000	-0.003
	100 %	-10	1714 999 991	-5.9	0.000 000	-0.003
	100 %	0	1714 999 990	-7.3	0.000 000	-0.004
	100 %	+10	1714 999 988	-8.5	0.000 000	-0.005
	100 %	+30	1714 999 988	-9.4	-0.000 001	-0.005
	100 %	+40	1714 999 986	-11.1	-0.000 001	-0.006
	100 %	+50	1715 000 007	9.9	0.000 001	0.006
	85 %	+20	1715 000 000	2.9	0.000 000	0.002
	115 %	+20	1714 999 992	-4.8	0.000 000	-0.003
1775.0	100 %	+20(Ref)	1774 999 997	0.0	0.000 000	0.000
	100 %	-30	1774 999 993	-3.6	0.000 000	-0.002
	100 %	-20	1774 999 992	-4.8	0.000 000	-0.003
	100 %	-10	1774 999 992	-4.8	0.000 000	-0.003
	100 %	0	1774 999 990	-6.5	0.000 000	-0.004
	100 %	+10	1774 999 990	-7.2	0.000 000	-0.004
	100 %	+30	1774 999 988	-8.7	0.000 000	-0.005
	100 %	+40	1774 999 986	-10.4	-0.000 001	-0.006
	100 %	+50	1775 000 004	6.7	0.000 000	0.004
	85 %	+20	1774 999 991	-5.5	0.000 000	-0.003
	115 %	+20	1774 999 991	-5.8	0.000 000	-0.003

- ☐ BandWidth: 15 MHz
☐ Voltage(100 %): 12.000 VDC
☐ LIMIT: Emission must remain in band

Test. Frequency	Voltage	Temp.	Frequency	Frequency	Deviation	ppm
(MHz)	(%)	(°C)	(Hz)	Error (Hz)	(%)	
1717.5	100 %	+20(Ref)	1717 500 001	0.0	0.000 000	0.000
	100 %	-30	1717 500 002	0.4	0.000 000	0.000
	100 %	-20	1717 500 000	-0.9	0.000 000	-0.001
	100 %	-10	1717 500 000	-1.2	0.000 000	-0.001
	100 %	0	1717 499 999	-1.9	0.000 000	-0.001
	100 %	+10	1717 499 998	-2.8	0.000 000	-0.002
	100 %	+30	1717 499 998	-3.2	0.000 000	-0.002
	100 %	+40	1717 500 001	0.1	0.000 000	0.000
	100 %	+50	1717 500 018	16.9	0.000 001	0.010
	85 %	+20	1717 500 001	-0.2	0.000 000	0.000
	115 %	+20	1717 500 014	12.5	0.000 001	0.007
1772.5	100 %	+20(Ref)	1772 499 992	0.0	0.000 000	0.000
	100 %	-30	1772 499 985	-7.3	0.000 000	-0.004
	100 %	-20	1772 499 985	-7.6	0.000 000	-0.004
	100 %	-10	1772 499 985	-7.2	0.000 000	-0.004
	100 %	0	1772 499 985	-6.9	0.000 000	-0.004
	100 %	+10	1772 499 985	-7.6	0.000 000	-0.004
	100 %	+30	1772 499 986	-6.8	0.000 000	-0.004
	100 %	+40	1772 499 985	-7.0	0.000 000	-0.004
	100 %	+50	1772 499 986	-5.8	0.000 000	-0.003
	85 %	+20	1772 499 993	0.9	0.000 000	0.001
	115 %	+20	1772 499 983	-8.8	0.000 000	-0.005

☐ BandWidth: 20 MHz
☐ Voltage(100 %): 12.000 VDC
☐ LIMIT: Emission must remain in band


Test. Frequency	Voltage	Temp.	Frequency	Frequency	Deviation	ppm
(MHz)	(%)	(°C)	(Hz)	Error (Hz)	(%)	
1720.0	100 %	+20(Ref)	1719 999 996	0.0	0.000 000	0.000
	100 %	-30	1719 999 991	-4.9	0.000 000	-0.003
	100 %	-20	1719 999 990	-5.9	0.000 000	-0.003
	100 %	-10	1719 999 989	-7.7	0.000 000	-0.004
	100 %	0	1719 999 988	-7.9	0.000 000	-0.005
	100 %	+10	1719 999 987	-9.1	-0.000 001	-0.005
	100 %	+30	1719 999 987	-9.7	-0.000 001	-0.006
	100 %	+40	1719 999 986	-10.7	-0.000 001	-0.006
	100 %	+50	1719 999 985	-11.7	-0.000 001	-0.007
	85 %	+20	1719 999 990	-5.9	0.000 000	-0.003
	115 %	+20	1719 999 988	-8.7	-0.000 001	-0.005
1770.0	100 %	+20(Ref)	1770 000 010	0.0	0.000 000	0.000
	100 %	-30	1770 000 020	10.1	0.000 001	0.006
	100 %	-20	1770 000 020	9.9	0.000 001	0.006
	100 %	-10	1770 000 020	10.3	0.000 001	0.006
	100 %	0	1770 000 020	10.8	0.000 001	0.006
	100 %	+10	1770 000 021	11.0	0.000 001	0.006
	100 %	+30	1770 000 021	11.1	0.000 001	0.006
	100 %	+40	1770 000 021	11.1	0.000 001	0.006
	100 %	+50	1770 000 003	-6.3	0.000 000	-0.004
	85 %	+20	1770 000 019	9.9	0.000 001	0.006
	115 %	+20	1770 000 020	10.2	0.000 001	0.006

- ▣ BandWidth: 40 MHz
- ▣ Voltage(100 %): 12.000 VDC
- ▣ LIMIT: Emission must remain in band


Test. Frequency	Voltage	Temp.	Frequency	Frequency	Deviation	ppm
(MHz)	(%)	(°C)	(Hz)	Error (Hz)	(%)	
1730.0	100 %	+20(Ref)	1729 999 999	0.0	0.000 000	0.000
	100 %	-30	1729 999 992	-6.6	0.000 000	-0.004
	100 %	-20	1729 999 989	-9.5	-0.000 001	-0.006
	100 %	-10	1730 000 005	6.3	0.000 000	0.004
	100 %	0	1730 000 001	2.7	0.000 000	0.002
	100 %	+10	1729 999 999	0.5	0.000 000	0.000
	100 %	+30	1729 999 995	-3.4	0.000 000	-0.002
	100 %	+40	1729 999 993	-5.7	0.000 000	-0.003
	100 %	+50	1730 000 011	12.3	0.000 001	0.007
	85 %	+20	1729 999 997	-1.9	0.000 000	-0.001
	115 %	+20	1730 000 004	5.4	0.000 000	0.003
1760.0	100 %	+20(Ref)	1760 000 010	0.0	0.000 000	0.000
	100 %	-30	1760 000 019	9.0	0.000 001	0.005
	100 %	-20	1759 999 998	-11.8	-0.000 001	-0.007
	100 %	-10	1760 000 016	5.6	0.000 000	0.003
	100 %	0	1760 000 015	4.8	0.000 000	0.003
	100 %	+10	1760 000 013	2.9	0.000 000	0.002
	100 %	+30	1760 000 012	2.2	0.000 000	0.001
	100 %	+40	1760 000 011	0.7	0.000 000	0.000
	100 %	+50	1760 000 010	-0.7	0.000 000	0.000
	85 %	+20	1760 000 019	8.8	0.000 000	0.005
	115 %	+20	1760 000 013	2.7	0.000 000	0.002

9. TEST PLOTS


NR66_5 M_PAR_Mid_BPSK_FullRB




NR66_5 M_PAR_Mid_QPSK_FullRB




NR66_5 M_PAR_Mid_16QAM_FullRB




NR66_5 M_PAR_Mid_64QAM_FullRB




NR66_5 M_PAR_Mid_256QAM_FullRB




NR66_10 M_PAR_Mid_BPSK_FullRB




NR66_10 M_PAR_Mid_QPSK_FullRB




NR66_10 M_PAR_Mid_16QAM_FullRB




NR66_10 M_PAR_Mid_64QAM_FullRB




NR66_10 M_PAR_Mid_256QAM_FullRB




NR66_15 M_PAR_Mid_BPSK_FullRB




NR66_15 M_PAR_Mid_QPSK_FullRB




NR66_15 M_PAR_Mid_16QAM_FullRB




NR66_15 M_PAR_Mid_64QAM_FullRB




NR66_15 M_PAR_Mid_256QAM_FullRB




NR66_20 M_PAR_Mid_BPSK_FullRB




NR66_20 M_PAR_Mid_QPSK_FullRB




NR66_20 M_PAR_Mid_16QAM_FullRB




NR66_20 M_PAR_Mid_64QAM_FullRB




NR66_20 M_PAR_Mid_256QAM_FullRB




NR66_40 M_PAR_Mid_BPSK_FullRB




NR66_40 M_PAR_Mid_QPSK_FullRB




NR66_40 M_PAR_Mid_16QAM_FullRB




NR66_40 M_PAR_Mid_64QAM_FullRB




NR66_40 M_PAR_Mid_256QAM_FullRB




NR66_5 M_OBW_Mid_BPSK_FullRB




NR66_5 M_OBW_Mid_QPSK_FullRB




NR66_5 M_OBW_Mid_16QAM_FullRB




NR66_5 M_OBW_Mid_64QAM_FullRB




NR66_5 M_OBW_Mid_256QAM_FullRB




NR66_10 M_OBW_Mid_BPSK_FullRB




NR66_10 M_OBW_Mid_QPSK_FullRB




NR66_10 M_OBW_Mid_16QAM_FullRB




NR66_10 M_OBW_Mid_64QAM_FullRB




NR66_10 M_OBW_Mid_256QAM_FullRB




NR66_15 M_OBW_Mid_BPSK_FullRB




NR66_15 M_OBW_Mid_QPSK_FullRB




NR66_15 M_OBW_Mid_16QAM_FullRB




NR66_15 M_OBW_Mid_64QAM_FullRB




NR66_15 M_OBW_Mid_256QAM_FullRB




NR66_20 M_OBW_Mid_BPSK_FullRB




NR66_20 M_OBW_Mid_QPSK_FullRB




NR66_20 M_OBW_Mid_16QAM_FullRB




NR66_20 M_OBW_Mid_64QAM_FullRB




NR66_20 M_OBW_Mid_256QAM_FullRB




NR66_40 M_OBW_Mid_BPSK_FullRB




NR66_40 M_OBW_Mid_QPSK_FullRB




NR66_40 M_OBW_Mid_16QAM_FullRB




NR66_40 M_OBW_Mid_64QAM_FullRB




NR66_40 M_OBW_Mid_256QAM_FullRB




NR66_5 M_Conducted Spurious(30 M-10 G)_Low_BPSK_1RB




NR66_5 M_Conducted Spurious(30 M-10 G)_Mid_BPSK_1RB




NR66_5 M_Conducted Spurious(30 M-10 G)_High_BPSK_1RB




NR66_10 M_Conducted Spurious(30 M-10 G)_Low_BPSK_1RB




NR66_10 M_Conducted Spurious(30 M-10 G)_Mid_BPSK_1RB




NR66_10 M_Conducted Spurious(30 M-10 G)_High_BPSK_1RB




NR66_15 M_Conducted Spurious(30 M-10 G)_Low_BPSK_1RB




NR66_15 M_Conducted Spurious(30 M-10 G)_Mid_BPSK_1RB




NR66_15 M_Conducted Spurious(30 M-10 G)_High_BPSK_1RB




NR66_20 M_Conducted Spurious(30 M-10 G)_Low_BPSK_1RB




NR66_20 M_Conducted Spurious(30 M-10 G)_Mid_BPSK_1RB




NR66_20 M_Conducted Spurious(30 M-10 G)_High_BPSK_1RB




NR66_40 M_Conducted Spurious(30 M-10 G)_Low_BPSK_1RB




NR66_40 M_Conducted Spurious(30 M-10 G)_Mid_BPSK_1RB



NR66_40 M_Conducted Spurious(30 M-10 G)_High_BPSK_1RB



NR66_5 M_Conducted Spurious(Above10 G)_Low_BPSK_1RB



NR66_5 M_Conducted Spurious(Above10 G)_Mid_BPSK_1RB

