

TEST REPORT

FCC Sub6 n12 Test for TM19FNNABD2
Certification

APPLICANT
LG Electronics Inc.

REPORT NO.
HCT-RF-2412-FC032

DATE OF ISSUE
December 13, 2024

Tested by
Jung Ki Lim



Technical Manager
Jong Seok Lee



HCT CO., LTD.
Bongjai Huh
BongJai Huh / CEO

**HCT CO.,LTD.**

2-6, 73, 74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, Republic of Korea
Tel. +82 31 645 6300 Fax. +82 31 645 6401

TEST REPORT

REPORT NO.

HCT-RF-2412-FC032

DATE OF ISSUE

December 13, 2024

Applicant

LG Electronics Inc.

128, Yeoui-daero, Yeongdeungpo-gu, Seoul, Republic of Korea

Product Name

Telematics

Model Name

TM19FNN AHD2

Date of Test

September 30, 2024 ~ December 10, 2024

Location of Test

☒ Permanent Testing Lab ☐ On Site Testing

(Address: 74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, Republic of Korea)

FCC ID

BEJTM19FNN AHD2

FCC Classification

PCS Licensed Transmitter (PCB)

Test Standard Used

FCC Rule Part(s) : § 27

Test Results

PASS

REVISION HISTORY

The revision history for this test report is shown in table.

Revision No.	Date of Issue	Description
0	December 13, 2024	Initial Release

Notice

Content

The measurements shown in this report were made in accordance with the procedures specified in CFR47 section § 2.947. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them.

HCT CO., LTD. Certifies that no party to this application has subject to a denial of Federal benefits that includes FCC benefits pursuant to section 5301 of the Anti-Drug Abuse Act of 1998, 21 U.S.C. 853(a)

The results shown in this test report only apply to the sample(s), as received, provided by the applicant, unless otherwise stated.

The test results have only been applied with the test methods required by the standard(s).

The laboratory is not accredited for the test results marked *.

Information provided by the applicant is marked **.

Test results provided by external providers are marked ***.

When confirmation of authenticity of this test report is required, please contact www.hct.co.kr

The test results in this test report are not associated with the ((KS Q) ISO/IEC 17025) accreditation by KOLAS (Korea Laboratory Accreditation Scheme) / A2LA (American Association for Laboratory Accreditation) that are under the ILAC (International Laboratory Accreditation Cooperation) Mutual Recognition Agreement (MRA).

CONTENTS

1. GENERAL INFORMATION.....	5
1.1. MAXIMUM OUTPUT POWER	6
2. INTRODUCTION	7
2.1. DESCRIPTION OF EUT	7
2.2. MEASURING INSTRUMENT CALIBRATION	7
2.3. TEST FACILITY.....	7
3. DESCRIPTION OF TESTS	8
3.1 TEST PROCEDURE	8
3.2 CONDUCTED OUTPUT POWER.....	9
3.3 RADIATED POWER.....	10
3.4 RADIATED SPURIOUS EMISSIONS	11
3.5 PEAK- TO- AVERAGE RATIO	12
3.6 OCCUPIED BANDWIDTH.....	14
3.7 SPURIOUS AND HARMONIC EMISSIONS AT ANTENNA TERMINAL	15
3.8 BAND EDGE.....	16
3.9 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE	18
3.10 WORST CASE(RADIATED TEST)	19
3.11 WORST CASE(CONDUCTED TEST)	20
4. LIST OF TEST EQUIPMENT	21
5. MEASUREMENT UNCERTAINTY	22
6. SUMMARY OF TEST RESULTS	23
7. SAMPLE CALCULATION	24
8. TEST DATA	26
8.1 Conducted Output Power.....	26
8.2 EFFECTIVE RADIATED POWER	29
8.3 RADIATED SPURIOUS EMISSIONS	32
8.4 PEAK-TO-AVERAGE RATIO	33
8.5 OCCUPIED BANDWIDTH	34
8.6 CONDUCTED SPURIOUS EMISSIONS.....	35
8.7 BAND EDGE.....	35
8.8 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE	36
9. TEST PLOTS.....	39
10. ANNEX A_ TEST SETUP PHOTO.....	100

MEASUREMENT REPORT

1. GENERAL INFORMATION

Applicant Name:	LG Electronics Inc.
Address:	128, Yeoui-daero, Yeongdeungpo-gu, Seoul, Republic of Korea
FCC ID:	BEJTM19FNNAHD2
Application Type:	Certification
FCC Classification:	PCS Licensed Transmitter (PCB)
FCC Rule Part(s):	§ 27
EUT Type:	Telematics
Model(s):	TM19FNNAHD2
SCS(kHz):	15
Bandwidth(MHz):	5, 10, 15
Waveform:	CP-OFDM, DFT-S-OFDM
Modulation:	DFT-S-OFDM: PI/2 BPSK, QPSK, 16 QAM, 64 QAM, 256 QAM CP-OFDM: QPSK, 16 QAM, 64 QAM, 256 QAM
Tx Frequency:	701.5 MHz – 713.5 MHz (Sub6 n12 (5 MHz)) 704.0 MHz – 711.0 MHz (Sub6 n12 (10 MHz)) 706.5 MHz – 708.5 MHz (Sub6 n12 (15 MHz))
Date(s) of Tests:	September 30, 2024 ~ December 10, 2024
Serial number:	Radiated : Honda MY26 #02 Conducted : Honda MY26 #01
Antenna Information	Please refer to the Antenna Approval Specification document.

1.1. MAXIMUM OUTPUT POWER

Mode (MHz)	Tx Frequency (MHz)	Emission Designator	Modulation	Conducted Output Power	
				Max. Power (W)	Max. Power (dBm)
Sub6 n12 (5)	701.5 – 713.5	4M50G7D	PI/2 BPSK	0.230	23.62
		4M50G7D	QPSK	0.228	23.57
		4M51W7D	16 QAM	0.178	22.51
		4M51W7D	64 QAM	0.126	21.01
		4M51W7D	256 QAM	0.080	19.04
Sub6 n12 (10)	704.0 – 711.0	8M99G7D	PI/2 BPSK	0.224	23.51
		8M97G7D	QPSK	0.221	23.44
		8M96W7D	16 QAM	0.181	22.57
		8M95W7D	64 QAM	0.127	21.03
		8M99W7D	256 QAM	0.079	19.00
Sub6 n12 (15)	706.5 – 708.5	13M5G7D	PI/2 BPSK	0.231	23.64
		13M4G7D	QPSK	0.229	23.60
		13M5W7D	16 QAM	0.185	22.68
		13M4W7D	64 QAM	0.129	21.11
		13M4W7D	256 QAM	0.081	19.11

2. INTRODUCTION

2.1. DESCRIPTION OF EUT

The EUT was a Telematics with LTE, Sub 6.

2.2. MEASURING INSTRUMENT CALIBRATION

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipment, which is traceable to recognized national standards.

2.3. TEST FACILITY


The Fully-anechoic chamber and conducted measurement facility used to collect the radiated data are located at the **74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, Republic of Korea**

3. DESCRIPTION OF TESTS

3.1 TEST PROCEDURE

Test Description	Test Procedure Used
Occupied Bandwidth	- KDB 971168 D01 v03r01 – Section 4.3 - ANSI C63.26-2015 – Section 5.4.4
Band Edge	- KDB 971168 D01 v03r01 – Section 6.0 - ANSI C63.26-2015 – Section 5.7
Spurious and Harmonic Emissions at Antenna Terminal	- KDB 971168 D01 v03r01 – Section 6.0 - ANSI C63.26-2015 – Section 5.7
Conducted Output Power	- KDB 971168 D01 v03r01 – Section 5.2
Peak- to- Average Ratio	- KDB 971168 D01 v03r01 – Section 5.7 - ANSI C63.26-2015 – Section 5.2.3.4
Frequency stability	- ANSI C63.26-2015 – Section 5.6
Radiated Power	- ANSI C63.26-2015 – Section 5.2.4.4 - KDB 971168 D01 v03r01 – Section 5.8
Radiated Spurious and Harmonic Emissions	- ANSI C63.26-2015 – Section 5.5.3 - KDB 971168 D01 v03r01 – Section 5.8

3.2 CONDUCTED OUTPUT POWER



Test setup

Test Overview

When an average power meter is used to perform RF output power measurements, the fundamental condition that measurements be performed only over durations of active transmissions at maximum output power level applies.

Conducted Output Power was tested in accordance with KDB971168 D01 Power Meas License Digital Systems v03r01, Section 5.2.

3.3 RADIATED POWER

Test Overview

Radiated tests are performed in the Fully-anechoic chamber.

The equipment under test is placed on a non-conductive table 3-meters away from the receive antenna.

Test Settings

1. Radiated power measurements are performed using the signal analyzer's "channel power" measurement capability for signals with continuous operation.
2. RBW = 1 – 5 % of the expected OBW, not to exceed 1 MHz
3. VBW $\geq$ 3 x RBW
4. Span = 1.5 times the OBW
5. No. of sweep points $>$ 2 x span / RBW
6. Detector = RMS
7. Trigger is set to "free run" for signals with continuous operation with the sweep times set to "auto".
8. The integration bandwidth was roughly set equal to the measured OBW of the signal for signals with continuous operation.
9. Trace mode = trace averaging (RMS) over 100 sweeps
10. The trace was allowed to stabilize

Test Note

1. The turntable is rotated through 360 degrees, and the receiving antenna scans in order to determine the level of the maximized emission.
2. A half wave dipole is then substituted in place of the EUT. For emissions above 1 GHz, a horn antenna is substituted in place of the EUT. The substitute antenna is driven by a signal generator and the previously recorded signal was duplicated.

The power is calculated by the following formula;

$$P_d \text{ (dBm)} = P_g \text{ (dBm)} - \text{cable loss (dB)} + \text{antenna gain (dB)}$$

Where: P_d is the dipole equivalent power and P_g is the generator output power into the substitution antenna.

3. The maximum value is calculated by adding the forward power to the calibrated source plus its appropriate gain value.
These steps are repeated with the receiving antenna in both vertical and horizontal polarization. the difference between the gain of the horn and an isotropic antenna are taken into consideration
4. The EUT was tested in three orthogonal planes(X, Y, Z) and in all possible test configurations and positioning.
5. All measurements are performed as RMS average measurements while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies.

3.4 RADIATED SPURIOUS EMISSIONS

Test Overview

Radiated tests are performed in the Fully-anechoic chamber.

Radiated Spurious Emission Measurements at 3 meters by Substitution Method.

Test Settings

1. RBW = 100 kHz for emissions below 1 GHz and 1 MHz for emissions above 1 GHz
2. VBW $\geq 3 \times$ RBW
3. Span = 1.5 times the OBW
4. No. of sweep points $> 2 \times$ span / RBW
5. Detector = Peak
6. Trace mode = Max Hold
7. The trace was allowed to stabilize
8. Test channel : Low/ Middle/ High
9. Frequency range : We are performed all frequency to 10th harmonics from 9 kHz.

Test Note

1. Measurements value show only up to 3 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.
2. The EUT was tested in three orthogonal planes(X, Y, Z) and in all possible test configurations and positioning.
The worst case emissions are reported with the EUT positioning, modulations, RB sizes and offsets, and channel bandwidth configurations shown in the test data
3. For spurious emissions above 1 GHz, a horn antenna is substituted in place of the EUT. The substitute antenna is driven by a signal generator and the previously recorded signal was duplicated.

The spurious emissions is calculated by the following formula;


$$\text{Result}_{(\text{dBm})} = P_g_{(\text{dBm})} - \text{cable loss}_{(\text{dB})} + \text{antenna gain}_{(\text{dBi})}$$

Where: P_g is the generator output power into the substitution antenna.

If the fundamental frequency is below 1 GHz, RF output power has been converted to EIRP.

$$\text{EIRP}_{(\text{dBm})} = \text{ERP}_{(\text{dBm})} + 2.15$$

3.5 PEAK- TO- AVERAGE RATIO



Test setup

① CCDF Procedure for PAPR

Test Settings

1. Set resolution/measurement bandwidth $\geq$ signal's occupied bandwidth;
2. Set the number of counts to a value that stabilizes the measured CCDF curve;
3. Set the measurement interval as follows:
 - for continuous transmissions, set to 1 ms,
 - or burst transmissions, employ an external trigger that is synchronized with the EUT burst timing sequence, or use the internal burst trigger with a trigger level that allows the burst to stabilize and set the measurement interval to a time that is less than or equal to the burst duration.
4. Record the maximum PAPR level associated with a probability of 0.1 %.

② Alternate Procedure for PAPR

Use one of the procedures presented in 5.2(ANSI C63.26-2015) to measure the total peak power and record as P_{Pk} .

Use one of the applicable procedures presented 5.2(ANSI C63.26-2015) to measure the total average power and record as P_{Avg} . Determine the P.A.R. from:

$$P.A.R. (dB) = P_{Pk} (dBm) - P_{Avg} (dBm) \quad (P_{Avg} = \text{Average Power} + \text{Duty cycle Factor})$$

Test Settings(Peak Power)


The measurement instrument must have a RBW that is greater than or equal to the OBW of the signal to be measured and a VBW $\geq 3 \times$ RBW.

1. Set the RBW $\geq$ OBW.
2. Set VBW $\geq 3 \times$ RBW.
3. Set span $\geq 2 \times$ OBW.
4. Sweep time $\geq 10 \times$ (number of points in sweep) $\times$ (transmission symbol period).
5. Detector = peak.
6. Trace mode = max hold.
7. Allow trace to fully stabilize.
8. Use the peak marker function to determine the peak amplitude level.

Test Settings(Average Power)

1. Set span to $2 \times$ to $3 \times$ the OBW.
2. Set RBW $\geq$ OBW.
3. Set VBW $\geq 3 \times$ RBW.
4. Set number of measurement points in sweep $\geq 2 \times$ span / RBW.
5. Sweep time:
Set $\geq [10 \times (\text{number of points in sweep}) \times (\text{transmission period})]$ for single sweep (automation-compatible) measurement. The transmission period is the (on + off) time.
6. Detector = power averaging (rms).
7. Set sweep trigger to "free run."
8. Trace average at least 100 traces in power averaging (rms) mode if sweep is set to auto-couple. (To accurately determine the average power over the on and off period of the transmitter, it can be necessary to increase the number of traces to be averaged above 100 or, if using a manually configured sweep time, increase the sweep time.)
9. Use the peak marker function to determine the maximum amplitude level.
10. Add $[10 \log (1/\text{duty cycle})]$ to the measured maximum power level to compute the average power during continuous transmission. For example, add $[10 \log (1/0.25)] = 6$ dB if the duty cycle is a constant 25 %.

3.6 OCCUPIED BANDWIDTH.



Test setup

The width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5 % of the total mean power of a given emission.

The EUT makes a call to the communication simulator.


The conducted occupied bandwidth used the power splitter via EUT RF power connector between simulation base station and spectrum analyzer.

The communication simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency. Use OBW measurement function of Spectrum analyzer to measure 99 % occupied bandwidth

Test Settings

1. The signal analyzer's automatic bandwidth measurement capability was used to perform the 99 % occupied bandwidth and the 26 dB bandwidth. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. $RBW = 1 - 5\%$ of the expected OBW
3. $VBW \geq 3 \times RBW$
4. Detector = Peak
5. Trace mode = max hold
6. Sweep = auto couple
7. The trace was allowed to stabilize
8. If necessary, steps 2 – 7 were repeated after changing the RBW such that it would be within $1 - 5\%$ of the 99 % occupied bandwidth observed in Step 7

3.7 SPURIOUS AND HARMONIC EMISSIONS AT ANTENNA TERMINAL



Test setup


Test Overview

The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer. The spectrum is scanned from the lowest frequency generated in the equipment up to a frequency including its 10th harmonic. All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

Test Settings

1. RBW = 1 MHz
2. VBW $\geq$ 3 MHz
3. Detector = Peak
4. Trace Mode = Max Hold
5. Sweep time = auto
6. Number of points in sweep $\geq$ 2 x Span / RBW

3.8 BAND EDGE



Test setup

Test Overview

All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

Test Settings

1. Start and stop frequency were set such that the band edge would be placed in the center of the plot
2. Span was set large enough so as to capture all out of band emissions near the band edge
3. RBW > 1 % of the emission bandwidth
4. VBW > 3 x RBW
5. Detector = RMS
6. Number of sweep points $\geq 2 \times \text{Span/RBW}$
7. Trace mode = trace average
8. Sweep time = auto couple
9. The trace was allowed to stabilize

Test Notes


According to FCC 22.917, 24.238, 27.53 specified that power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB. In the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed.

All measurements were done at 2 channels (low and high operational frequency range.)

The band edge measurement used the power splitter via EUT RF power connector between simulation base station and spectrum analyzer.

Where $\text{Margin} < 1$ dB the emission level is either corrected by $10 \log(1 \text{ MHz} / \text{RB})$ or the emission is integrated over a 1 MHz bandwidth to determine the final result. When using the integration method the integration window is either centered on the emission or, for emissions at the band edge, centered by an offset of 500 kHz from the block edge so that the integration window is the 1 MHz adjacent to the block edge.

3.9 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE



Test setup

Test Overview

Frequency stability testing is performed in accordance with the guidelines of ANSI C63.26-2015.

The frequency stability of the transmitter is measured by:

1. Temperature:

The temperature is varied from -30 °C to +50 °C in 10 °C increments using an environmental chamber.

2. Primary Supply Voltage:

- Unless otherwise specified, vary primary supply voltage from 85 % to 115 % of the nominal value for other than hand carried battery equipment.
- For hand carried, battery powered equipment, reduce the primary ac or dc supply voltage to the battery operating end point, which shall be specified by the manufacturer.

Test Settings

1. The carrier frequency of the transmitter is measured at room temperature (20 °C to provide a reference).
2. The equipment is turned on in a “standby” condition for fifteen minutes before applying power to the transmitter.
Measurement of the carrier frequency of the transmitter is made within one minute after applying power to the transmitter.
3. Frequency measurements are made at 10 °C intervals ranging from -30 °C to +50 °C. A period of at least one half-hour is provided to allow stabilization of the equipment at each temperature level.

3.10 WORST CASE(RADIATED TEST)

- The EUT was tested in three orthogonal planes(X, Y, Z) and in all possible test configurations and positioning.
- All modes of operation were investigated and the worst case configuration results are reported.
Mode : SA, NSA
Worst case : SA
- All simultaneous transmission scenarios of operation were investigated, and the test results showed no additional significant emissions relative to the least restrictive limit were observed.
Therefore, only the worst case(stand-alone) results were reported.
- Radiated Spurious emissions are measured while operating in EN-DC mode with Sub 6 NR carrier as well as an LTE carrier (anchor).
All EN-DC mode of operation (=anchor) were investigated and the test results were measured No Peak Found.
The test results which are attenuated more than 20 dB below the permissible value, so it was not reported.
- The worst case is reported with the EUT positioning, modulations, and paging service configurations shown in the test data.
- All RB sizes, offsets of operation were investigated and the worst case configuration results are reported.
Please refer to the table below.
- In the case of radiated spurious emissions, all bandwidth of operation were investigated and the worst case bandwidth results are reported. (Worst case : 5 MHz)

[Worst case]

Test Description	Modulation	RB size	RB offset	Axis
Effective Radiated Power	PI/2 BPSK, QPSK, 16 QAM, 64 QAM, 256 QAM	See Section 8.2		X
Radiated Spurious and Harmonic Emissions	PI/2 BPSK	See Section 8.3		X

3.11 WORST CASE(CONDUCTED TEST)

- Waveform : All Waveform of operation were investigated and the worst case configuration results are reported.
(Worst case: DFT-S-OFDM)
- Modulation : All Modulation of operation were investigated and the worst case configuration results are reported.
(Worst case: PI/2 BPSK)
- All modes of operation were investigated and the worst case configuration results are reported.
Mode: NSA, SA
Worst case: SA
- All RB sizes, offsets of operation were investigated and the worst case configuration results are reported.
Please refer to the table below.

[Worst case]

Test Description	Modulation	Bandwidth (MHz)	Frequency	RB size	RB offset
Occupied Bandwidth Peak- to- Average Ratio	PI/2 BPSK, QPSK, 16 QAM, 64 QAM, 256 QAM	5, 10, 15	Mid	Full RB	0
Band Edge	PI/2 BPSK	5	Low	1	0
			High	1	24
		10	Low	1	0
			High	1	51
		15	Low	1	0
			High	1	78
Spurious and Harmonic Emissions at Antenna Terminal	PI/2 BPSK	5, 10, 15	Low, High	Full RB	0
			Low, Mid, High	1	1

4. LIST OF TEST EQUIPMENT

Equipment	Model	Manufacturer	Serial No.	Due to Calibration	Calibration Interval
Precision Dipole Antenna	UHAP	Schwarzbeck	01273	03/10/2026	Biennial
Precision Dipole Antenna	UHAP	Schwarzbeck	01274	03/10/2026	Biennial
Horn Antenna(1~18 GHz)	BBHA 9120D	Schwarzbeck	02289	02/14/2026	Biennial
Horn Antenna(1~18 GHz)	BBHA 9120D	Schwarzbeck	9120D-1299	04/27/2025	Biennial
Horn Antenna(15~40 GHz)	BBHA 9170	Schwarzbeck	BBHA9170342	09/20/2026	Biennial
Horn Antenna(15~40 GHz)	BBHA 9170	Schwarzbeck	BBHA9170124	03/28/2025	Biennial
Loop Antenna(9 kHz~30 MHz)	FMZB1513	Rohde & Schwarz	1513-175	01/16/2025	Biennial
Bilog Antenna	VULB9160	Schwarzbeck	3150	03/09/2025	Biennial
Hybrid Antenna	VULB9160	Schwarzbeck	760	02/24/2025	Biennial
RF Switching System	FBSR-06B (1G HPF + LNA)	T&M SYSTEM	F3L1	05/14/2025	Annual
RF Switching System	FBSR-06B (3G HPF + LNA)	T&M SYSTEM	F3L2	05/14/2025	Annual
RF Switching System	FBSR-06B (6G HPF + LNA)	T&M SYSTEM	F3L3	05/14/2025	Annual
RF Switching System	FBSR-06B (LNA)	T&M SYSTEM	F3L4	05/14/2025	Annual
Power Amplifier	CBL18265035	CERNEX	22966	11/07/2025	Annual
Power Amplifier	CBL26405040	CERNEX	25956	02/26/2025	Annual
DC Power Supply	E3632A	Hewlett Packard	MY40004427	08/22/2025	Annual
Power Splitter(DC~26.5 GHz)	11667B	Hewlett Packard	11275	02/29/2025	Annual
Chamber	SU-642	ESPEC	93008124	02/19/2025	Annual
Signal Analyzer(10 Hz~26.5 GHz)	N9020A	Agilent	MY51110063	04/04/2025	Annual
ATTENUATOR(20 dB)	8493C	Hewlett Packard	17280	04/17/2025	Annual
Spectrum Analyzer (10 Hz~40 GHz)	FSV40	REOHDE & SCHWARZ	101436	02/13/2025	Annual
Signal & Spectrum Analyzer (2 Hz~67 GHz)	FSW67	REOHDE & SCHWARZ	101736	23/05/2025	Annual
Base Station	8960 (E5515C)	Agilent	MY48360800	08/05/2025	Annual
Wideband Radio Communication Tester	MT8821C	Anritsu Corp.	6262287701	05/16/2025	Annual
Wideband Radio Communication Tester	MT8000A	Anritsu Corp.	6262302511	05/14/2025	Annual
Signal Analyzer(5 Hz~40.0 GHz)	N9030B	KEYSIGHT	MY55480167	05/17/2025	Annual
4-Way Divider	ZC4PD-K1844+	Mini-Circuits	942907	09/10/2025	Annual
FCC LTE Mobile Conducted RF Automation Test Software	-	HCT CO., LTD.,	-	-	-

Note:

- Equipment listed above that has a calibration due date during the testing period, the testing is completed before equipment expiration date.
- Especially, all antenna for measurement is calibrated in accordance with the requirements of C63.5 (Version : 2017).

5. MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.4:2014.

All measurement uncertainty values are shown with a coverage factor of $k=2$ to indicate a 95 % level of confidence. The measurement data shown herein meets or exceeds the U_{CISPR} measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Parameter	Expanded Uncertainty ($\pm$ dB)
Conducted Disturbance (150 kHz ~ 30 MHz)	1.98 (Confidence level about 95 %, $k=2$)
Radiated Disturbance (9 kHz ~ 30 MHz)	4.36 (Confidence level about 95 %, $k=2$)
Radiated Disturbance (30 MHz ~ 1 GHz)	5.70 (Confidence level about 95 %, $k=2$)
Radiated Disturbance (1 GHz ~ 18 GHz)	5.52 (Confidence level about 95 %, $k=2$)
Radiated Disturbance (18 GHz ~ 40 GHz)	5.66 (Confidence level about 95 %, $k=2$)
Radiated Disturbance (Above 40 GHz)	5.58 (Confidence level about 95 %, $k=2$)

6. SUMMARY OF TEST RESULTS

6.1 Test Condition : Conducted Test

Test Description	FCC Part Section(s)	Test Limit	Test Result
Occupied Bandwidth	§2.1049	N/A	PASS
Band Edge / Spurious and Harmonic Emissions at Antenna Terminal.	§2.1051, §27.53(g)	< 43 + 10log10 (P[Watts]) at Band Edge and for all out-of-band emissions	PASS
Conducted Output Power	§2.1046	N/A	PASS
Frequency stability / variation of ambient temperature	§2.1055, §27.54	Emission must remain in band	PASS

Note:

1. Conducted test were tested using 5G Wireless Tester.

6.2 Test Condition : Radiated Test

Test Description	FCC Part Section(s)	Test Limit	Test Result
Effective Radiated Power	§27.50(c)(10)	< 3 Watts max. ERP	PASS
Radiated Spurious and Harmonic Emissions	§2.1053, §27.53(g)	< 43 + 10log10 (P[Watts]) for all out-of band emissions	PASS

Note:

1. Radiated tests were tested using 5G Wireless Tester.

7. SAMPLE CALCULATION

7.1 ERP Sample Calculation

Ch./ Freq.		Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain (dBd)	C.L	Pol.	ERP	
channel	Freq.(MHz)						W	dBm
128	824.20	-21.37	38.40	-10.61	0.95	H	0.483	26.84

$$\text{ERP} = \text{Substitute LEVEL(dBm)} + \text{Ant. Gain} - \text{CL(Cable Loss)}$$

- 1) The EUT mounted on a non-conductive turntable is 2.5 meter above test site ground level.
- 2) During the test, the turn table is rotated until the maximum signal is found.
- 3) Record the field strength meter's level.
- 4) Replace the EUT with dipole/Horn antenna that is connected to a calibrated signal generator.
- 5) Increase the signal generator output till the field strength meter's level is equal to the item (3).
- 6) The signal generator output level with Ant. Gain and cable loss are the rating of effective radiated power.

7.2 EIRP Sample Calculation

Ch./ Freq.		Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain (dBi)	C.L	Pol.	EIRP	
channel	Freq.(MHz)						W	dBm
20175	1,732.50	-15.75	18.45	9.90	1.76	H	0.456	26.59

$$\text{EIRP} = \text{Substitute LEVEL(dBm)} + \text{Ant. Gain} - \text{CL(Cable Loss)}$$

- 1) The EUT mounted on a non-conductive turntable is 2.5 meter above test site ground level.
- 2) During the test, the turn table is rotated until the maximum signal is found.
- 3) Record the field strength meter's level.
- 4) Replace the EUT with dipole/Horn antenna that is connected to a calibrated signal generator.
- 5) Increase the signal generator output till the field strength meter's level is equal to the item (3).
- 6) The signal generator output level with Ant. Gain and cable loss are the rating of equivalent isotropic radiated power.

7.3. Emission Designator

GSM Emission Designator

Emission Designator = 249KGXW

GSM BW = 249 kHz

G = Phase Modulation

X = Cases not otherwise covered

W = Combination (Audio/Data)

EDGE Emission Designator

Emission Designator = 249KG7W

GSM BW = 249 kHz

G = Phase Modulation

7 = Quantized/Digital Info

W = Combination (Audio/Data)

WCDMA Emission Designator

Emission Designator = 4M17F9W

WCDMA BW = 4.17 MHz

F = Frequency Modulation

9 = Composite Digital Info

W = Combination (Audio/Data)

QPSK Modulation

Emission Designator = 4M48G7D

LTE BW = 4.48 MHz

G = Phase Modulation

7 = Quantized/Digital Info

D = Data transmission; telemetry; telecommand

QAM Modulation

Emission Designator = 4M48W7D

LTE BW = 4.48 MHz

W = Amplitude/Angle Modulated

7 = Quantized/Digital Info

D = Data transmission; telemetry; telecommand

8. TEST DATA

8.1 Conducted Output Power

Bandwidth	SCS(kHz)	OFDM	Modulation	RB Size	RB Offset	Max.Average Power (dBm)		
						140300	141500	142700
						701.5 MHz	707.5 MHz	713.5 MHz
5 MHz	15	DFT-s	pi/2 BPSK	1	1	23.62	23.47	23.41
				1	13	23.39	23.37	23.38
				1	23	23.37	23.37	23.31
				12	0	22.99	22.98	22.96
				12	7	23.41	23.44	23.40
				12	13	22.95	22.85	22.88
				25	0	22.91	22.88	22.89
			QPSK	1	1	23.57	23.49	23.30
			16 QAM	1	1	22.50	22.51	22.31
			64 QAM	1	1	21.01	20.97	20.84
			256 QAM	1	1	19.03	19.04	18.93
		CP	QPSK	1	1	22.15	21.95	21.97

Bandwidth	SCS(kHz)	OFDM	Modulation	RB Size	RB Offset	Max.Average Power (dBm)		
						140800	141500	142200
						704.0 MHz	707.5 MHz	711.0 MHz
10 MHz	15	DFT-s	pi/2 BPSK	1	1	23.50	23.51	23.37
				1	26	23.43	23.37	23.31
				1	50	23.37	23.27	23.34
				25	0	22.99	22.95	22.95
				25	14	23.45	23.43	23.41
				25	27	22.93	22.89	22.88
				50	0	22.92	22.99	22.92
			QPSK	1	1	23.44	23.40	23.41
			16 QAM	1	1	22.57	22.43	22.46
			64 QAM	1	1	21.03	20.95	20.89
			256 QAM	1	1	18.95	19.00	18.98
		CP	QPSK	1	1	22.01	21.93	22.10

Bandwidth	SCS(kHz)	OFDM	Modulation	RB Size	RB Offset	Max.Average Power (dBm)		
						141300	141500	141700
						706.5 MHz	707.5 MHz	708.5 MHz
15 MHz	15	DFT-s	pi/2 BPSK	1	1	23.52	23.64	23.55
				1	40	23.45	23.50	23.50
				1	77	23.43	23.47	23.40
				36	0	23.01	23.02	23.08
				36	22	23.54	23.56	23.47
				36	43	22.96	22.92	22.92
				75	0	23.05	23.01	23.00
			QPSK	1	1	23.59	23.60	23.55
			16 QAM	1	1	22.55	22.56	22.68
			64 QAM	1	1	21.03	21.10	21.11
			256 QAM	1	1	19.04	19.11	19.08
		CP	QPSK	1	1	22.06	22.15	22.17

8.2 EFFECTIVE RADIATED POWER

Freq (MHz)	Mod/ Bandwidth [SCS (kHz)]	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain(dBi)	C.L	Pol	Limit	ERP		RB	
								W	W	dBm	Size	Offset
701.5	Sub6 n12/ 5 MHz [15 kHz]	PI/2 BPSK	-28.75	30.63	-9.60	1.29	H	< 3.00	0.094	19.74	1	12
		QPSK	-28.89	30.49	-9.60	1.29	H		0.091	19.60		
		16-QAM	-29.92	29.46	-9.60	1.29	H		0.072	18.57		
		64-QAM	-31.40	27.98	-9.60	1.29	H		0.051	17.09		
		256-QAM	-33.33	26.05	-9.60	1.29	H		0.033	15.16		
707.5		PI/2 BPSK	-28.40	30.66	-9.60	1.29	H		0.095	19.77	1	12
		QPSK	-28.44	30.62	-9.60	1.29	H		0.094	19.73		
		16-QAM	-29.60	29.46	-9.60	1.29	H		0.072	18.57		
		64-QAM	-31.08	27.98	-9.60	1.29	H		0.051	17.09		
		256-QAM	-33.10	25.96	-9.60	1.29	H		0.032	15.07		
713.5		PI/2 BPSK	-28.56	30.59	-9.60	1.30	H		0.093	19.69	1	1
		QPSK	-28.65	30.50	-9.60	1.30	H		0.091	19.60		
		16-QAM	-29.65	29.50	-9.60	1.30	H		0.072	18.60		
		64-QAM	-31.12	28.03	-9.60	1.30	H		0.052	17.13		
		256-QAM	-33.11	26.04	-9.60	1.30	H		0.033	15.14		

Freq (MHz)	Mod/ Bandwidth [SCS (kHz)]	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain(dBi)	C.L	Pol	Limit	ERP		RB	
								W	W	dBm	Size	Offset
704.0		PI/2 BPSK	-28.73	30.47	-9.60	1.29	H	< 3.00	0.091	19.58	1	26
		QPSK	-28.79	30.41	-9.60	1.29	H		0.090	19.52		
		16-QAM	-29.77	29.43	-9.60	1.29	H		0.071	18.54		
		64-QAM	-31.26	27.94	-9.60	1.29	H		0.051	17.05		
		256-QAM	-33.22	25.98	-9.60	1.29	H		0.032	15.09		
707.5	Sub6 n12/ 10 MHz [15 kHz]	PI/2 BPSK	-28.58	30.48	-9.60	1.29	H	< 3.00	0.091	19.59	1	26
		QPSK	-28.65	30.41	-9.60	1.29	H		0.090	19.52		
		16-QAM	-29.64	29.42	-9.60	1.29	H		0.071	18.53		
		64-QAM	-31.12	27.94	-9.60	1.29	H		0.051	17.05		
		256-QAM	-33.11	25.95	-9.60	1.29	H		0.032	15.06		
711.0		PI/2 BPSK	-28.59	30.52	-9.60	1.30	H	< 3.00	0.092	19.62	1	1
		QPSK	-28.64	30.47	-9.60	1.30	H		0.091	19.57		
		16-QAM	-29.62	29.49	-9.60	1.30	H		0.072	18.59		
		64-QAM	-31.10	28.01	-9.60	1.30	H		0.051	17.11		
		256-QAM	-33.10	26.01	-9.60	1.30	H		0.032	15.11		

Freq (MHz)	Mod/ Bandwidth [SCS (kHz)]	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain(dBi)	C.L	Pol	Limit	ERP		RB	
								W	W	dBm	Size	Offset
706.5	Sub6 n12/ 15 MHz [15 kHz]	PI/2 BPSK	-28.48	30.64	-9.60	1.29	H	< 3.00	0.094	19.75	1	39
		QPSK	-28.56	30.56	-9.60	1.29	H		0.093	19.67		
		16-QAM	-29.54	29.58	-9.60	1.29	H		0.074	18.69		
		64-QAM	-31.01	28.11	-9.60	1.29	H		0.053	17.22		
		256-QAM	-33.02	26.10	-9.60	1.29	H		0.033	15.21		
707.5		PI/2 BPSK	-28.53	30.53	-9.60	1.29	H		0.092	19.64	1	39
		QPSK	-28.61	30.45	-9.60	1.29	H		0.090	19.56		
		16-QAM	-29.57	29.49	-9.60	1.29	H		0.072	18.60		
		64-QAM	-31.04	28.02	-9.60	1.29	H		0.052	17.13		
		256-QAM	-33.03	26.03	-9.60	1.29	H		0.033	15.14		
708.5		PI/2 BPSK	-28.53	30.51	-9.60	1.29	H		0.092	19.62	1	39
		QPSK	-28.59	30.45	-9.60	1.29	H		0.090	19.56		
		16-QAM	-29.57	29.47	-9.60	1.29	H		0.072	18.58		
		64-QAM	-31.06	27.98	-9.60	1.29	H		0.051	17.09		
		256-QAM	-33.05	25.99	-9.60	1.29	H		0.032	15.10		

8.3 RADIATED SPURIOUS EMISSIONS

■ NR Band:	<u>N12</u>
■ Bandwidth:	<u>5 MHz</u>
■ Modulation:	<u>PI/2 BPSK</u>
■ Distance:	<u>3 meters</u>
■ SCS:	<u>15 kHz</u>

Ch	Freq (MHz)	Measured Level (dBm)	Ant. Gain (dBi)	Substitute Level (dBm)	C.L	Pol	Result (dBm)	Limit (dBm)	RB	
									Size	Offset
140300 (701.5)	1 403.00	-58.04	7.60	-63.67	1.86	V	-57.93	-13.00	1	12
	2 104.50	-58.90	9.26	-64.38	2.34	V	-57.46	-13.00		
	2 806.00	-60.07	11.20	-63.90	2.68	V	-55.38	-13.00		
141500 (707.5)	1 415.00	-58.93	7.71	-65.36	1.87	V	-59.52	-13.00	1	12
	2 122.50	-59.97	9.55	-65.14	2.28	V	-57.87	-13.00		
	2 830.00	-59.55	11.25	-63.19	2.70	V	-54.64	-13.00		
142700 (713.5)	1 427.00	-57.08	7.82	-63.91	1.87	V	-57.96	-13.00	1	1
	2 140.50	-58.21	9.77	-62.80	2.24	V	-55.27	-13.00		
	2 854.00	-60.67	11.31	-64.38	2.74	V	-55.81	-13.00		

8.4 PEAK-TO-AVERAGE RATIO

Band	Band Width	Frequency (MHz)	Modulation	Resource Block Size	Resource Block Offset	Data (dB)
Sub6 n12	5 MHz	707.5	BPSK	25	0	3.86
			QPSK			4.42
			16-QAM			5.61
			64-QAM			5.99
			256-QAM			6.65
	10 MHz		BPSK	50		4.00
			QPSK			4.56
			16-QAM			5.56
			64-QAM			6.04
			256-QAM			6.61
	15 MHz		BPSK	75		4.01
			QPSK			4.57
			16-QAM			5.46
			64-QAM			5.96
			256-QAM			6.62

Note:

1. Plots of the EUT's Peak- to- Average Ratio are shown Page 40 ~ 54.

8.5 OCCUPIED BANDWIDTH

Band	Band Width	Frequency (MHz)	Modulation	Resource Block Size	Resource Block Offset	Data (MHz)
Sub6 n12	5 MHz	707.5	BPSK	25	0	4.5040
			QPSK			4.5034
			16-QAM			4.5121
			64-QAM			4.5055
			256-QAM			4.5056
	10 MHz		BPSK	50		8.9848
			QPSK			8.9701
			16-QAM			8.9561
			64-QAM			8.9480
			256-QAM			8.9863
	15 MHz		BPSK	75		13.462
			QPSK			13.439
			16-QAM			13.472
			64-QAM			13.423
			256-QAM			13.403

Note:

1. Plots of the EUT's Occupied Bandwidth are shown Page 55 ~ 69.

8.6 CONDUCTED SPURIOUS EMISSIONS

Band	Band Width (MHz)	Frequency (MHz)	Frequency of Maximum Harmonic (GHz)	Factor (dB)	Measurement Maximum Data (dBm)	Result (dBm)	Limit (dBm)
Sub6 n12	5	701.5	3.7688	30.200	-62.686	-32.486	-13.00
		707.5	3.6092	30.200	-61.863	-31.663	
		713.5	4.0080	30.200	-62.646	-32.446	
	10	704.0	9.6511	30.815	-63.130	-32.315	
		707.5	8.2852	30.815	-63.146	-32.331	
		711.0	3.8186	30.200	-62.710	-32.510	
	15	706.5	9.6211	30.815	-63.365	-32.550	
		707.5	3.8385	30.200	-62.733	-32.533	
		708.5	4.0679	30.200	-63.035	-32.835	

Note:

1. Plots of the EUT's Conducted Spurious Emissions are shown Page 70 ~ 78.
2. Result (dBm) = Measurement Maximum Data (dBm) + Factor (dB)
3. Factor(dB) = Cable Loss + Attenuator + Splitter

Frequency Range (GHz)	Factor [dB]
0.03 – 1	27.494
1 – 5	30.200
5 – 10	30.815
10 – 15	31.340
15 – 20	31.713
Above 20	32.355

8.7 BAND EDGE

- Plots of the EUT's Band Edge are shown Page 79 ~ 99.

8.8 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE

- ☐ BandWidth: 5 MHz
☐ Voltage(100 %): 13.200 VDC
☐ Deviation Limit: Emission must remain in band

Test. Frequency (MHz)	Voltage (%)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
707.5	100 %	+20(Ref)	707 500 003	0.0	0.000 000	0.000
	100 %	-30	707 500 006	2.5	0.000 000	0.004
	100 %	-20	707 500 005	2.3	0.000 000	0.003
	100 %	-10	707 500 005	1.5	0.000 000	0.002
	100 %	0	707 500 004	0.6	0.000 000	0.001
	100 %	+10	707 500 003	0.2	0.000 000	0.000
	100 %	+30	707 500 003	-0.2	0.000 000	0.000
	100 %	+40	707 500 003	-0.7	0.000 000	-0.001
	100 %	+50	707 500 002	-1.1	0.000 000	-0.002
	85 %	+20	707 500 001	-1.9	0.000 000	-0.003
	115 %	+20	707 500 000	-3.5	0.000 000	-0.005

☐ BandWidth: 10 MHz
☐ Voltage(100 %): 13.200 VDC
☐ Deviation Limit: Emission must remain in band


Test. Frequency (MHz)	Voltage (%)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
707.5	100 %	+20(Ref)	707 500 000	0.0	0.000 000	0.000
	100 %	-30	707 500 000	-0.2	0.000 000	0.000
	100 %	-20	707 500 000	-0.8	0.000 000	-0.001
	100 %	-10	707 500 008	7.8	0.000 001	0.011
	100 %	0	707 499 999	-1.8	0.000 000	-0.003
	100 %	+10	707 500 007	7.0	0.000 001	0.010
	100 %	+30	707 499 998	-2.8	0.000 000	-0.004
	100 %	+40	707 500 006	5.9	0.000 001	0.008
	100 %	+50	707 500 006	5.4	0.000 001	0.008
	85 %	+20	707 500 003	2.2	0.000 000	0.003
	115 %	+20	707 500 002	1.2	0.000 000	0.002

☐ BandWidth: 15 MHz
☐ Voltage(100 %): 13.200 VDC
☐ Deviation Limit: Emission must remain in band


Test. Frequency (MHz)	Voltage (%)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
707.5	100 %	+20(Ref)	707 499 997	0.0	0.000 000	0.000
	100 %	-30	707 499 993	-3.9	-0.000 001	-0.005
	100 %	-20	707 499 993	-4.0	-0.000 001	-0.006
	100 %	-10	707 499 992	-4.3	-0.000 001	-0.006
	100 %	0	707 500 001	4.5	0.000 001	0.006
	100 %	+10	707 499 992	-4.8	-0.000 001	-0.007
	100 %	+30	707 499 991	-5.3	-0.000 001	-0.008
	100 %	+40	707 500 000	3.8	0.000 001	0.005
	100 %	+50	707 500 000	3.3	0.000 000	0.005
	85 %	+20	707 500 002	4.9	0.000 001	0.007
	115 %	+20	707 500 002	5.5	0.000 001	0.008

9. TEST PLOTS


NR12_5 M_PAR_Mid_BPSK_FullIRB



NR12_5 M_PAR_Mid_QPSK_FullRB



NR12_5 M_PAR_Mid_16QAM_FullRB




NR12_5 M_PAR_Mid_64QAM_FullRB




NR12_5 M_PAR_Mid_256QAM_FullRB



NR12_10 M_PAR_Mid_BPSK_FullIRB



NR12_10 M_PAR_Mid_QPSK_FullRB



NR12_10 M_PAR_Mid_16QAM_FullRB




NR12_10 M_PAR_Mid_64QAM_FullRB




NR12_10 M_PAR_Mid_256QAM_FullRB



NR12_15 M_PAR_Mid_BPSK_FullIRB



NR12_15 M_PAR_Mid_QPSK_FullRB



NR12_15 M_PAR_Mid_16QAM_FullRB




NR12_15 M_PAR_Mid_64QAM_FullRB




NR12_15 M_PAR_Mid_256QAM_FullRB




NR12_5 M_OBW_Mid_BPSK_FullRB




NR12_5 M_OBW_Mid_QPSK_FullRB




NR12_5 M_OBW_Mid_16QAM_FullRB



NR12_5 M_OBW_Mid_64QAM_FullRB




NR12_5 M_OBW_Mid_256QAM_FullRB




NR12_10 M_OBW_Mid_BPSK_FullRB




NR12_10 M_OBW_Mid_QPSK_FullIRB




NR12_10 M_OBW_Mid_16QAM_FullRB




NR12_10 M_OBW_Mid_64QAM_FullRB



NR12_10 M_OBW_Mid_256QAM_FullRB




NR12_15 M_OBW_Mid_BPSK_FullRB




NR12_15 M_OBW_Mid_QPSK_FullIRB



NR12_15 M_OBW_Mid_16QAM_FullRB



NR12_15 M_OBW_Mid_64QAM_FullRB



Spectrum Analyzer 1
Occupied BW

RL → Coupling: DC, Align: Auto
Input Z: 50 Ω, Corr: Corr, Freq Ref: Int (S), NFE: Adaptive
Atten: 14 dB, Preamp: Off
Trig: Free Run, Gate: Off, #IF Gain: Low
Center Freq: 707.500000 MHz, Avg/Hold: 500/500, Radio Std: None

Center Frequency: 707.500000 MHz
Span: 30.000 MHz
CF Step: 3.000000 MHz
Auto Man
Freq Offset: 0 Hz

1 Graph
Scale/Div 10.0 dB
Log
Ref Lvl Offset 27.39 dB
Ref Value 40.00 dBm


Center 707.50 MHz
#Res BW 300.0 kHz
#Video BW 1.2000 MHz
Span 30 MHz
Sweep 1.00 ms (1001 pts)

2 Metrics

Metric	Value
Occupied Bandwidth	13.403 MHz
Transmit Freq Error	-372.17 kHz
x dB Bandwidth	14.30 MHz
Total Power	27.3 dBm
% of OBW Power	99.00 %
x dB	-26.00 dB

Nov 05, 2024 4:51:42 PM


NR12_5 M_Conducted Spurious(30 M-10 G)_Low_BPSK_1RB




NR12_5 M_Conducted Spurious(30 M-10 G)_Mid_BPSK_1RB




NR12_5 M_Conducted Spurious(30 M-10 G)_High_BPSK_1RB




NR12_10 M_Conducted Spurious(30 M-10 G)_Low_BPSK_1RB




NR12_10 M_Conducted Spurious(30 M-10 G)_Mid_BPSK_1RB




NR12_10 M_Conducted Spurious(30 M-10 G)_High_BPSK_1RB




NR12_15 M_Conducted Spurious(30 M-10 G)_Low_BPSK_1RB




NR12_15 M_Conducted Spurious(30 M-10 G)_Mid_BPSK_1RB



NR12_15 M_Conducted Spurious(30 M-10 G)_High_BPSK_1RB



NR12_5 M_Band Edge_Low_BPSK_1RB



NR12_5 M_Band Edge_Low_BPSK_FullIRB




NR12_5 M_Extended Band Edge_Low_BPSK_FullRB



NR12_5 M_Band Edge_High_BPSK_1RB(1)



NR12_5 M_Band Edge_High_BPSK_1RB(2)




NR12_5 M_Band Edge_High_BPSK_FullRB



NR12_5 M_Extended Band Edge_High_BPSK_FullRB



NR12_10 M_Band Edge_Low_BPSK_1RB




NR12_10 M_Band Edge_Low_BPSK_FullRB



NR12_10 M_Extended Band Edge_Low_BPSK_FullRB



NR12_10 M_Band Edge_High_BPSK_1RB(1)



Keysight Spectrum Analyzer 1
Swept SA

Input RF
Coupling DC
Align Auto

Input Z: 50 Ω
Corr C Corr
Freq Ref: Int (S)
NFE: Adaptive

#Atten: 14 dB
Preamp: Off

PNO: Best Wide
Gate: Off
IF Gain: Low
Sig Track: Off

#Avg Type: Power (RMS)
Tng: Free Run

1 2 3 4 5 6
A W W W W W W
A A A A A A A

1 Spectrum
Scale/Div 10 dB
Log

Ref Lvl Offset 27.39 dB
Ref Level 27.39 dBm

Mkr1 716.100 0 MHz
-20.660 dBm

17.4
7.39
-2.81
-12.6
-22.6
-32.6
-42.6
-52.6
-62.6

DL1 -13.80 dBm

Start 716.1000 MHz
#Res BW 100 kHz

#Video BW 300 kHz

Stop 718.0000 MHz
#Sweep 1.00 s (1001 pts)

Meas Setup

Avg/Hold Number 10

Avg Type Power (RMS)

Auto Man

Meas Setup Summary Table

Auto Couple

Meas Preset

Settings

Limits

Meas Standard

Legacy Compat

Advanced

Global

Local


NR12_10 M_Band Edge_High_BPSK_FullRB




NR12_10 M_Extended Band Edge_High_BPSK_FullIRB



NR12_15 M_Band Edge_Low_BPSK_1RB




NR12_15 M_Band Edge_Low_BPSK_FullRB



NR12_15 M_Extended Band Edge_Low_BPSK_FullRB




NR12_15 M_Band Edge_High_BPSK_1RB(1)




NR12_15 M_Band Edge_High_BPSK_1RB(2)



NR12_15 M_Band Edge_High_BPSK_FullRB



NR12_15 M_Extended Band Edge_High_BPSK_FullRB



10. ANNEX A_ TEST SETUP PHOTO

Please refer to test setup photo file no. as follows;

No.	Description
1	HCT-RF-2412-FC032-P