



# PCTEST ENGINEERING LABORATORY, INC.

6660-B Dobbin Road, Columbia, MD 21045 USA  
Tel. 410.290.6652 / Fax 410.290.6554  
<http://www.pctestlab.com>



## CERTIFICATE OF COMPLIANCE (SAR EVALUATION)

**Applicant Name:**  
LG Electronics USA  
1000 Sylvan Avenue  
Englewood Cliffs, NJ 07632  
United States

**Date of Testing:**  
08/06/07 - 08/07/07  
**Test Site/Location:**  
PCTEST Lab, Columbia, MD, USA  
**Test Report Serial No.:**  
0707230752.BEJ

**FCC ID:** BEJVBX10000

**APPLICANT:** LG ELECTRONICS USA

**EUT Type:** Cellular/PCS CDMA Phone with Bluetooth and EvDO  
**Application Type:** Certification  
**FCC Rule Part(s):** §2.1093; FCC/OET Bulletin 65 Supplement C [July 2001]  
**FCC Classification:** Licensed Transmitter Held to Ear (PCE)  
**Model(s):** VX10000 (LSC antenna)  
**Tx Frequency:** 824.70 - 848.31 MHz (Cellular CDMA)  
1851.25 - 1908.75 MHz (PCS CDMA)  
**Conducted Power:** 24.5 dBm CDMA  
24.5 dBm PCS  
**Max. SAR Measurement:** 0.427 W/kg CDMA850 Head SAR  
0.893 W/kg CDMA850 Body SAR  
0.765 W/kg CDMA1900 Head SAR  
0.606 W/kg CDMA1900 Body SAR  
**EUT Serial No.:** Pre-Production [S/N: A00000038A8F1E]

This wireless portable device has been shown to be capable of compliance for localized specific absorption rate (SAR) for uncontrolled environment/general population exposure limits specified in ANSI/IEEE Std. C95.1-2005 and has been tested in accordance with the measurement procedures specified in FCC/OET Bulletin 65 Supplement C (2001) and IEEE Std. 1528-2003.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

**Grant Conditions:** Power output listed is ERP for Part 22 and EIRP for Part 24. SAR compliance for body-worn operating configuration is based on a separation distance of 2.0 cm between the back of the unit and the body of the user. End-users must be informed of the body-worn operating requirements for satisfying RF exposure compliance. Belt clips or holsters not specified in this filing may not contain metallic components.

PCTEST certifies that no party to this application has been denied the FCC benefits pursuant to Section 5301 of the Anti-Drug Abuse Act of 1988, 21 U.S.C. 862.

  
Randy Ortanez  
President



|                                        |                                                                                     |                                                                     |                                                                                       |                                        |
|----------------------------------------|-------------------------------------------------------------------------------------|---------------------------------------------------------------------|---------------------------------------------------------------------------------------|----------------------------------------|
| <b>FCC ID:</b> BEJVBX10000             |  | <b>CERTIFICATION REPORT</b>                                         |  | <b>Reviewed by:</b><br>Quality Manager |
| <b>SAR Filename:</b><br>0707230752.BEJ | <b>Test Dates:</b><br>08/06/07 - 08/07/07                                           | <b>EUT Type:</b><br>Cellular/PCS CDMA Phone with Bluetooth and EvDO |                                                                                       | Page 1 of 25                           |

# TABLE OF CONTENTS

---

|    |                                                 |    |
|----|-------------------------------------------------|----|
| 1  | INTRODUCTION .....                              | 3  |
| 2  | TEST SITE LOCATION.....                         | 4  |
| 3  | SAR MEASUREMENT SETUP .....                     | 5  |
| 4  | DASY E-FIELD PROBE SYSTEM.....                  | 7  |
| 5  | PROBE CALIBRATION PROCESS.....                  | 8  |
| 6  | PHANTOM AND EQUIVALENT TISSUES .....            | 9  |
| 7  | DOSIMETRIC ASSESSMENT & PHANTOM SPECS .....     | 10 |
| 8  | DEFINITION OF REFERENCE POINTS .....            | 11 |
| 9  | TEST CONFIGURATION POSITIONS .....              | 12 |
| 10 | ANSI/IEEE C95.1-2005 RF EXPOSURE LIMITS.....    | 14 |
| 11 | MEASUREMENT UNCERTAINTIES .....                 | 15 |
| 12 | SYSTEM VERIFICATION .....                       | 16 |
| 13 | FCC 3G MEASUREMENT PROCEDURES – JUNE 2006 ..... | 17 |
| 14 | SAR DATA SUMMARY .....                          | 19 |
| 15 | EQUIPMENT LIST .....                            | 22 |
| 16 | CONCLUSION.....                                 | 23 |
| 17 | REFERENCES .....                                | 24 |

|                                        |                                                                                     |                                                                     |                                                                                       |                                        |
|----------------------------------------|-------------------------------------------------------------------------------------|---------------------------------------------------------------------|---------------------------------------------------------------------------------------|----------------------------------------|
| <b>FCC ID:</b> BEJVB10000              |  | <b>CERTIFICATION REPORT</b>                                         |  | <b>Reviewed by:</b><br>Quality Manager |
| <b>SAR Filename:</b><br>0707230752.BEJ | <b>Test Dates:</b><br>08/06/07 - 08/07/07                                           | <b>EUT Type:</b><br>Cellular/PCS CDMA Phone with Bluetooth and EvDO |                                                                                       | Page 2 of 25                           |

# 1 INTRODUCTION

The FCC has adopted the guidelines for evaluating the environmental effects of radio frequency (RF) radiation in ET Docket 93-62 on Aug. 6, 1996 to protect the public and workers from the potential hazards of RF emissions due to FCC-regulated portable devices.[1]

The safety limits used for the environmental evaluation measurements are based on the criteria published by the American National Standards Institute (ANSI) for localized specific absorption rate (SAR) in IEEE/ANSI C95.1-2005 Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz. (c) 2005 by the Institute of Electrical and Electronics Engineers, Inc., New York, New York 10017.[2] The measurement procedure described in IEEE/ANSI C95.3-2002 Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields - RF and Microwave[3] is used for guidance in measuring the Specific Absorption Rate (SAR) due to the RF radiation exposure from the Equipment Under Test (EUT). These criteria for SAR evaluation are similar to those recommended by the International Committee for Non-Ionizing Radiation Protection (ICNIRP) in Biological Effects and Exposure Criteria for Radiofrequency Electromagnetic Fields," Report No. Vol 74. SAR is a measure of the rate of energy absorption due to exposure to an RF transmitting source. SAR values have been related to threshold levels for potential biological hazards.

## 1.1 SAR Definition

Specific Absorption Rate is defined as the time derivative (rate) of the incremental energy (dU) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dV) of a given density ( $\rho$ ). It is also defined as the rate of RF energy absorption per unit mass at a point in an absorbing body (see Fig. 1-1).

$$SAR = \frac{d}{dt} \left( \frac{dU}{dm} \right) = \frac{d}{dt} \left( \frac{dU}{\rho dV} \right)$$

**Figure 1-1**  
**SAR Mathematical Equation**

**SAR is expressed in units of Watts per Kilogram (W/kg).**

$$SAR = \frac{\sigma \cdot E^2}{\rho}$$

where:

- $\sigma$  = conductivity of the tissue-simulating material (S/m)
- $\rho$  = mass density of the tissue-simulating material ( $\text{kg/m}^3$ )
- E = Total RMS electric field strength (V/m)

NOTE: The primary factors that control rate of energy absorption were found to be the wavelength of the incident field in relation to the dimensions and geometry of the irradiated organism, the orientation of the organism in relation to the polarity of field vectors, the presence of reflecting surfaces, and whether conductive contact is made by the organism with a ground plane.[6]

|                                 |                                                                                     |                                                              |                                                                                       |                                 |
|---------------------------------|-------------------------------------------------------------------------------------|--------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: BEJVB10000              |  | CERTIFICATION REPORT                                         |  | Reviewed by:<br>Quality Manager |
| SAR Filename:<br>0707230752.BEJ | Test Dates:<br>08/06/07 - 08/07/07                                                  | EUT Type:<br>Cellular/PCS CDMA Phone with Bluetooth and EvDO |                                                                                       | Page 3 of 25                    |

## 2 TEST SITE LOCATION

### 2.1 INTRODUCTION

The map at the right shows the location of the PCTEST LABORATORY in Columbia, Maryland. It is in proximity to the FCC Laboratory, the Baltimore-Washington International (BWI) airport, the city of Baltimore and Washington, DC (See Figure 2).

These measurement tests were conducted at the PCTEST Engineering Laboratory, Inc. facility in New Concept Business Park, Guilford Industrial Park, Columbia, Maryland. The site address is 6660-B Dobbin Road, Columbia, MD 21045. The test site is one of the highest points in the Columbia area with an elevation of 390 feet above mean sea level. The site coordinates are 39° 11'15" N latitude and 76° 49' 38" W longitude. The facility is 1.5 miles north of the FCC laboratory, and the ambient signal and ambient signal strength are approximately equal to those of the FCC laboratory. There are no FM or TV transmitters within 15 miles of the site. The detailed description of the measurement facility was found to be in compliance with the requirements of § 2.948 according to ANSI C63.4 on January 27, 2006 and Industry Canada.



**Figure 2-1**  
Map of the Greater Baltimore and Metropolitan Washington, D.C. area

### 2.2 Test Facility / Accreditations:

Measurements were performed at an independent accredited PCTEST Engineering Lab located in Columbia, MD 21045, U.S.A.



- PCTEST Lab is accredited to ISO 17025-2005 by the American Association for Laboratory Accreditation (A2LA) in Specific Absorption Rate (SAR) testing, Hearing-Aid Compatibility (HAC), CTIA Test Plans, and wireless testing for FCC and Industry Canada Rules.
- PCTEST Lab is accredited to ISO 17025 by U.S. National Institute of Standards and Technology (NIST) under the National Voluntary Laboratory Accreditation Program (NVLAP Lab code: 100431-0) in EMC, FCC and Telecommunications.
- PCTEST facility is an FCC registered (PCTEST Reg. No. 90864) test facility with the site description report on file and has met all the requirements specified in Section 2.948 of the FCC Rules and Industry Canada (IC-2451).
- PCTEST Lab is a recognized U.S. Conformity Assessment Body (CAB) in EMC and R&TTE (n.b. 0982) under the U.S.-EU Mutual Recognition Agreement (MRA).
- PCTEST TCB is a Telecommunication Certification Body (TCB) accredited to ISO/IEC Guide 65 by the American National Standards Institute (ANSI) in all scopes of FCC Rules and all Industry Canada Standards (RSS).
- PCTEST facility is an IC registered (IC-2451) test laboratory with the site description on file at Industry Canada.
- PCTEST is a CTIA Authorized Test Laboratory (CATL) for AMPS and CDMA, and EvDO mobile phones.
- PCTEST is a CTIA Authorized Test Laboratory (CATL) for Over-the-Air (OTA) Antenna Performance testing for AMPS, CDMA, GSM, GPRS, EGPRS, UMTS (W-CDMA), CDMA 1xEVDO Data, CDMA 1xRTT Data.

|                                        |                                                                                     |                                                                     |                                                                                       |                                        |
|----------------------------------------|-------------------------------------------------------------------------------------|---------------------------------------------------------------------|---------------------------------------------------------------------------------------|----------------------------------------|
| <b>FCC ID:</b> BEJVB10000              |  | <b>CERTIFICATION REPORT</b>                                         |  | <b>Reviewed by:</b><br>Quality Manager |
| <b>SAR Filename:</b><br>0707230752.BEJ | <b>Test Dates:</b><br>08/06/07 - 08/07/07                                           | <b>EUT Type:</b><br>Cellular/PCS CDMA Phone with Bluetooth and EvDO |                                                                                       | Page 4 of 25                           |

## 3 SAR MEASUREMENT SETUP


### 3.1 Robotic System

Measurements are performed using the DASY4 automated dosimetric assessment system. The DASY4 is made by Schmid & Partner Engineering AG (SPEAG) in Zurich, Switzerland and consists of high precision robotics system (Staubli), robot controller, Pentium 4 computer, near-field probe, probe alignment sensor, and the generic twin phantom containing the brain equivalent material. The robot is a six-axis industrial robot performing precise movements to position the probe to the location (points) of maximum electromagnetic field (EMF) (see Figure 3-1).

### 3.2 System Hardware

A cell controller system contains the power supply, robot controller, teach pendant (Joystick), and a remote control used to drive the robot motors. The PC consists of the Gateway Pentium 4 2.53 GHz computer with Windows XP system and SAR Measurement Software DASY4, A/D interface card, monitor, mouse, and keyboard. The Staubli Robot is connected to the cell controller to allow software manipulation of the robot. A data acquisition electronic (DAE) circuit that performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. is connected to the Electro-optical coupler (EOC). The EOC performs the conversion from the optical into digital electric signal of the DAE and transfers data to the PC plug-in card.

### 3.3 System Electronics



**Figure 3-1**  
**SAR Measurement System Setup**

The DAE4 consists of a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD-converter and a command decoder and control logic unit. Transmission to the PC-card is accomplished through an optical downlink for data and status information and an optical uplink for commands and clock lines. The mechanical probe mounting device includes two different sensor systems for frontal and sidewise probe contacts. They are also used for mechanical surface detection and probe collision detection. The robot uses its own controller with a built in VME-bus computer. The system is described in detail in [7].

|                                 |                                                                                     |                                                              |                                                                                       |                                 |
|---------------------------------|-------------------------------------------------------------------------------------|--------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: BEJVB10000              |  | CERTIFICATION REPORT                                         |  | Reviewed by:<br>Quality Manager |
| SAR Filename:<br>0707230752.BEJ | Test Dates:<br>08/06/07 - 08/07/07                                                  | EUT Type:<br>Cellular/PCS CDMA Phone with Bluetooth and EvDO |                                                                                       | Page 5 of 25                    |

### 3.4 Automated Test System Specifications

#### Positioner

Robot: Stäubli Unimation Corp. Robot RX60L  
Repeatability: 0.02 mm  
No. of Axes: 6

#### Data Acquisition Electronic System (DAE)

##### Cell Controller

Processor: Pentium 4  
Clock Speed: 2.53 GHz  
Operating System: Windows XP Professional

##### Data Converter

Features: Signal Amplifier, multiplexer, A/D converter & control logic  
Software: DASY4, SEMCAD software  
Connecting Lines: Optical Downlink for data and status info  
Optical upload for commands and clock

#### PC Interface Card

Function: 166MHz low power Pentium MMX 32MB chipdisk  
Link to DAE  
16-bit A/D converter for surface detection system  
Two Serial & Ethernet link to robotics  
Direct emergency stop output for robot

#### Phantom

Type: SAM Twin Phantom (V4.0)  
Shell Material: Composite  
Thickness:  $2.0 \pm 0.2$  mm



**Figure 3-2**  
**DASY4 SAR Measurement System**

|                                 |                                                                                     |                                                              |                                                                                       |                                 |
|---------------------------------|-------------------------------------------------------------------------------------|--------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: BEJVB10000              |  | CERTIFICATION REPORT                                         |  | Reviewed by:<br>Quality Manager |
| SAR Filename:<br>0707230752.BEJ | Test Dates:<br>08/06/07 - 08/07/07                                                  | EUT Type:<br>Cellular/PCS CDMA Phone with Bluetooth and EvDO |                                                                                       | Page 6 of 25                    |

### 4.1 Probe Measurement System



Figure 4-1  
SAR System

The SAR measurements were conducted with the dosimetric probe EX3DV4, designed in the classical triangular configuration [7] (see Figure 4-3) and optimized for dosimetric evaluation. The probe is constructed using the thick film technique; with printed resistive lines on ceramic substrates. The probe is equipped with an optical multi-fiber line ending at the front of the probe tip. It is connected to the EOC box on the robot arm and provides an automatic detection of the phantom surface. Half of the fibers are connected to a pulsed infrared transmitter, the other half to a synchronized receiver. As the probe approaches the surface, the reflection from the surface produces a coupling from the transmitting to the receiving fibers. This reflection increases first during the approach, reaches maximum and then decreases. If the probe is flatly touching the surface, the coupling is zero. The distance of the coupling maximum to the surface is independent of the surface reflectivity and largely independent of the surface to probe angle. The DASY4 software reads the reflection during a software approach

and looks for the maximum using a 2nd order fitting (see Figure 5-1). The approach is stopped at reaching the maximum.

### 4.2 Probe Specifications

|                          |                                                                                                   |
|--------------------------|---------------------------------------------------------------------------------------------------|
| <b>Model:</b>            | ES3DV3, EX3DV4                                                                                    |
| <b>Frequency Range:</b>  | 10 MHz – 6.0 GHz (EX3DV4)<br>10 MHz – 4 GHz (ES3DV3)                                              |
| <b>Calibration:</b>      | In brain and muscle simulating tissue at<br>Frequencies from 835 up to 5800MHz                    |
| <b>Linearity:</b>        | $\pm 0.2$ dB (30 MHz to 6 GHz) for EX3DV4<br>$\pm 0.2$ dB (30 MHz to 4 GHz) for ES3DV3            |
| <b>Dynamic Range:</b>    | 10 mW/kg – 100 W/kg                                                                               |
| <b>Probe Length:</b>     | 330 mm                                                                                            |
| <b>Probe Tip Length:</b> | 20 mm                                                                                             |
| <b>Body Diameter:</b>    | 12 mm                                                                                             |
| <b>Tip Diameter:</b>     | 2.5 mm (3.9mm for ES3DV3)                                                                         |
| <b>Tip-Center:</b>       | 1 mm (2.0 mm for ES3DV3)                                                                          |
| <b>Application:</b>      | SAR Dosimetry Testing<br>Compliance tests of mobile phones<br>Dosimetry in strong gradient fields |



Figure 4-2  
Near-Field Probe



Figure 4-3  
Triangular Probe Configuration

|                                 |                                                                                     |                                                              |                                                                                       |                                 |
|---------------------------------|-------------------------------------------------------------------------------------|--------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: BEJVB10000              |  | CERTIFICATION REPORT                                         |  | Reviewed by:<br>Quality Manager |
| SAR Filename:<br>0707230752.BEJ | Test Dates:<br>08/06/07 - 08/07/07                                                  | EUT Type:<br>Cellular/PCS CDMA Phone with Bluetooth and EvDO |                                                                                       | Page 7 of 25                    |

## 5 PROBE CALIBRATION PROCESS

### 5.1 Dosimetric Assessment Procedure

Each E-Probe/Probe amplifier combination has unique calibration parameters. A TEM cell calibration procedure is conducted to determine the proper amplifier settings to enter in the probe parameters. The amplifier settings are determined for a given frequency by subjecting the probe to a known E-field density (1 mW/cm<sup>2</sup>) using an RF Signal generator, TEM cell, and RF Power Meter.

### 5.2 Free Space Assessment

The free space E-field from amplified probe outputs is determined in a test chamber. This calibration can be performed in a TEM cell if the frequency is below 1 GHz and in a waveguide or other methodologies above 1 GHz for free space. For the free space calibration, the probe is placed in the volumetric center of the cavity and at the proper orientation with the field. The probe is rotated 360 degrees until the three channels show the maximum reading. The power density readings equates to 1 mW/cm<sup>2</sup>.

### 5.3 Temperature Assessment

E-field temperature correlation calibration is performed in a flat phantom filled with the appropriate simulated brain tissue. The E-field in the medium correlates with the temperature rise in the dielectric medium. For temperature correlation calibration a RF transparent thermistor-based temperature probe is used in conjunction with the E-field probe.

$$SAR = C \frac{\Delta T}{\Delta t}$$

where:

$\Delta t$  = exposure time (30 seconds),

$C$  = heat capacity of tissue (brain or muscle),

$\Delta T$  = temperature increase due to RF exposure.

$$SAR = \frac{|E|^2 \cdot \sigma}{\rho}$$

where:

$\sigma$  = simulated tissue conductivity,

$\rho$  = Tissue density (1.25 g/cm<sup>3</sup> for brain tissue)

SAR is proportional to  $\Delta T/\Delta t$ , the initial rate of tissue heating, before thermal diffusion takes place. Now it's possible to quantify the electric field in the simulated tissue by equating the thermally derived SAR to the E-field;




Figure 5-1 E-Field and Temperature measurements at 900MHz [7]




Figure 5-2 E-Field and temperature measurements at 1.9GHz [7]

|                                 |                                                                                     |                                                              |                                                                                       |                                 |
|---------------------------------|-------------------------------------------------------------------------------------|--------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: BEJVX10000              |  | CERTIFICATION REPORT                                         |  | Reviewed by:<br>Quality Manager |
| SAR Filename:<br>0707230752.BEJ | Test Dates:<br>08/06/07 - 08/07/07                                                  | EUT Type:<br>Cellular/PCS CDMA Phone with Bluetooth and EvDO |                                                                                       | Page 8 of 25                    |

## 6 PHANTOM AND EQUIVALENT TISSUES

### 6.1 SAM Phantoms



**Figure 6-1**  
**SAM Phantoms**

The SAM Twin Phantom V4.0 is constructed of a fiberglass shell integrated in a wooden table. The shape of the shell is based on data from an anatomical study designed to determine the maximum exposure in at least 90% of all users [11][12]. It enables the dosimetric evaluation of left and right hand phone usage as well as body mounted usage at the flat phantom region. A cover prevents the evaporation of the liquid. Reference markings on the Phantom allow the complete setup of all predefined phantom positions and measurement grids by manually teaching three points in the robot. (see Fig. 5.1)

### 6.2 Brain & Muscle Simulating Mixture Characterization



**Figure 6-2**  
**Head Simulated**

The brain and muscle mixtures consist of a viscous gel using hydroxethylcellulose (HEC) gelling agent and saline solution (see Table 6-1). Preservation with a bactericide is added and visual inspection is made to make sure air bubbles are not trapped during the mixing process. The mixture is calibrated to obtain proper dielectric constant (permittivity) and conductivity of the desired tissue. The head tissue dielectric parameters recommended by the IEEE SCC-34/SC-2 have been incorporated in the following table. Other head and body tissue parameters that have not been specified in IEEE-1528 are derived from the tissue dielectric parameters computed from the 4-Cole-Cole equations. The mixture characterizations used for the brain and muscle tissue simulating liquids are according to the data by C. Gabriel and G. Hartsgrrove [13]. (See Table 6-1)

**Table 6-1**  
**Composition of the Brain & Muscle Tissue Equivalent Matter**

| Frequency (MHz)                        | 300   | 450   | 835   | 900   |       |       | 1450  | 1800  |       |       |       | 1900  |       | 1950  | 2000  | 2100  |       |       | 2450  |       | 3000  |
|----------------------------------------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| Recipe #                               | 1     | 1     | 3     | 1     | 1     | 2     | 3     | 1     | 1     | 2     | 2     | 3     | 1     | 2     | 4     | 1     | 1     | 2     | 2     | 3     | 2     |
| Ingredient (% by weight)               |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |
| 1,2-Propanediol                        |       |       |       |       |       |       | 64.81 |       |       |       |       |       |       |       |       |       |       |       |       |       |       |
| Bactericide                            | 0.19  | 0.19  | 0.50  | 0.10  | 0.10  |       | 0.50  |       |       |       |       | 0.50  |       |       |       |       |       |       |       | 0.50  |       |
| Diacetin                               |       |       | 48.90 |       |       |       | 49.20 |       |       |       |       | 49.43 |       |       |       |       |       |       |       | 49.75 |       |
| DGBE                                   |       |       |       |       |       |       |       | 45.41 | 47.00 | 13.84 | 44.92 |       | 44.94 | 13.84 | 45.00 | 50.00 | 50.00 | 7.99  | 7.99  |       | 7.99  |
| HEC                                    | 0.98  | 0.98  |       | 1.00  | 1.00  |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |
| NaCl                                   | 5.95  | 3.95  | 1.70  | 1.45  | 1.48  | 0.79  | 1.10  | 0.67  | 0.36  | 0.35  | 0.18  | 0.64  | 0.18  | 0.35  |       |       |       | 0.16  | 0.16  |       | 0.16  |
| Sucrose                                | 55.32 | 56.32 |       | 57.00 | 56.50 |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |
| Triton X-100                           |       |       |       |       |       |       |       |       |       | 30.45 |       |       | 30.45 |       |       |       |       | 19.97 | 19.97 |       | 19.97 |
| Water                                  | 37.56 | 38.56 | 48.90 | 40.45 | 40.92 | 34.40 | 49.20 | 53.80 | 52.64 | 55.36 | 54.90 | 49.43 | 54.90 | 55.36 | 55.00 | 50.00 | 50.00 | 71.88 | 71.88 | 49.75 | 71.81 |
| Measured dielectric parameters         |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |
| $\epsilon'_p$                          | 46.00 | 43.4  | 44.3  | 41.6  | 41.2  | 41.8  | 42.7  | 40.9  | 39.3  | 41    | 40.4  | 39.2  | 39.9  | 41    | 40.1  | 37    | 36.8  | 41.1  | 40.3  | 39.2  | 37.9  |
| $\sigma$ (S/m)                         | 0.86  | 0.85  | 0.9   | 0.9   | 0.98  | 0.97  | 0.99  | 1.21  | 1.39  | 1.38  | 1.4   | 1.4   | 1.42  | 1.38  | 1.41  | 1.4   | 1.51  | 1.55  | 1.88  | 1.82  | 2.46  |
| Temp. (°C)                             | 22    | 22    | 20    | 22    | 22    | 22    | 20    | 22    | 22    | 21    | 22    | 20    | 21    | 21    | 20    | 22    | 22    | 20    | 20    | 20    | 20    |
| Target dielectric parameters (Table 2) |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |
| $\epsilon'_p$                          | 45.30 | 43.50 | 41.5  |       | 41.50 |       | 40.5  |       |       |       | 40.0  |       |       |       |       |       | 39.80 |       | 39.2  |       | 38.5  |
| $\sigma$ (S/m)                         | 0.87  | 0.87  | 0.9   |       | 0.97  |       | 1.2   |       |       |       | 1.4   |       |       |       |       |       | 1.49  |       | 1.8   |       | 2.4   |

NOTE: Multiple columns for any single frequency are optional recipes. Recipe # reference: 1 (Kashi et al. TB85), 2 (Vargasa TB143), 3 (Fornan and Chelap TB159), 4 (Folman et al. TB59).

NOTE—Multiple columns for any single frequency are optional recipes. Recipe 6, reference: 1 (Kanda et al. [B85]), 2 (Vignone [B143]), 3 (Peyman and Chelvet [B119]), 4 (Folgaraga et al. [B50]).


\*The formulas containing Triton X-100 and corresponding measured parameters are under review and verification.

|                                 |                                                                                     |                                                              |                                                                                       |                                 |
|---------------------------------|-------------------------------------------------------------------------------------|--------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: BEJVV10000              |  | CERTIFICATION REPORT                                         |  | Reviewed by:<br>Quality Manager |
| SAR Filename:<br>0707230752.BEJ | Test Dates:<br>08/06/07 - 08/07/07                                                  | EUT Type:<br>Cellular/PCS CDMA Phone with Bluetooth and EvDO |                                                                                       | Page 9 of 25                    |

### 7.1 Measurement Procedure

The evaluation was performed using the following procedure:

1. The SAR measurement was taken at a selected spatial reference point to monitor power variations during testing. This fixed point was measured and used as a reference value.
2. The SAR distribution at the exposed side of the head was measured at a distance of 3.0mm from the inner surface of the shell. The area covered the entire dimension of the head and the horizontal grid spacing was 15mm x 15mm.
3. Based on the area scan data, the area of the maximum absorption was determined by spline interpolation. Around this point, a volume of 32mm x 32mm x 30mm (fine resolution volume scan, zoom scan) was assessed by measuring 5 x 5 x 7 points. On this basis of this data set, the spatial peak SAR value was evaluated with the following procedure (see Figure 7-1):
  - a. The data at the surface was extrapolated, since the center of the dipoles is 2.7mm away from the tip of the probe and the distance between the surface and the lowest measuring point is 1.2mm. The extrapolation was based on a least square algorithm [15]. A polynomial of the fourth order was calculated through the points in z-axes. This polynomial was then used to evaluate the points between the surface and the probe tip.
  - b. The maximum interpolated value was searched with a straight-forward algorithm. Around this maximum the SAR values averaged over the spatial volumes (1g or 10g) were computed using the 3D-Spline interpolation algorithm. The 3D-spline is composed of three one-dimensional splines with the "Not a knot" condition (in x, y, and z directions) [15][16]. The volume was integrated with the trapezoidal algorithm. One thousand points (10 x 10 x 10) were interpolated to calculate the average.
  - c. All neighboring volumes were evaluated until no neighboring volume with a higher average value was found.
4. The SAR reference value, at the same location as step 1, was re-measured. If the value changed by more than 5%, the evaluation is repeated.



**Figure 7-1**  
**Sample SAR Area Scan**

### 7.2 Specific Anthropomorphic Mannequin (SAM) Specifications

The phantom for handset SAR assessment testing is a low-loss dielectric shell, with shape and dimensions derived from the anthropometric data of the 90th percentile adult male head dimensions as tabulated by the US Army. The SAM Twin Phantom shell is bisected along the mid-sagittal plane into right and left halves (see Figure 7-2). The perimeter sidewalls of each phantom halves are extended to allow filling with liquid to a depth that is sufficient to minimized reflections from the upper surface. The liquid depth is maintained at a minimum depth of 15cm to minimize reflections from the upper surface.




**Figure 7-2**  
**SAM Twin Phantom Shell**

|                                 |                                                                                     |                                                              |                                                                                       |                                 |
|---------------------------------|-------------------------------------------------------------------------------------|--------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: BEJVB10000              |  | CERTIFICATION REPORT                                         |  | Reviewed by:<br>Quality Manager |
| SAR Filename:<br>0707230752.BEJ | Test Dates:<br>08/06/07 - 08/07/07                                                  | EUT Type:<br>Cellular/PCS CDMA Phone with Bluetooth and EvDO |                                                                                       | Page 10 of 25                   |

### 8.1 EAR REFERENCE POINT

Figure 8-1 shows the front, back and side views of the SAM Twin Phantom. The point "M" is the reference point for the center of the mouth, "LE" is the left ear reference point (ERP), and "RE" is the right ERP. The ERP is 15mm posterior to the entrance to the ear canal (EEC) along the B-M line (Back-Mouth), as shown in Figure 8-1. The plane passing through the two ear canals and M is defined as the Reference Plane. The line N-F (Neck-Front) is perpendicular to the reference plane and passing through the RE (or LE) is called the Reference Pivoting Line (see Figure 8-2). Line B-M is perpendicular to the N-F line. Both N-F and B-M lines are marked on the external phantom shell to facilitate handset positioning [5].




**Figure 8-1**  
Close-Up Side view  
of ERP

### 8.2 HANDSET REFERENCE POINTS

Two imaginary lines on the handset were established: the vertical centerline and the horizontal line. The test device was placed in a normal operating position with the "test device reference point" located along the "vertical centerline" on the front of the device aligned to the "ear reference point" (See Figure 8-3). The "test device reference point" was then located at the same level as the center of the ear reference point. The test device was positioned so that the "vertical centerline" was bisecting the front surface of the handset at its top and bottom edges, positioning the "ear reference point" on the outer surface of the both the left and right head phantoms on the ear reference point.



**Figure 8-2**  
Front, back and side view of SAM Twin Phantom



**Figure 8-3**  
Handset Vertical Center & Horizontal Line Reference Points

|                                 |                                                                                     |                                                              |                                                                                       |                                 |
|---------------------------------|-------------------------------------------------------------------------------------|--------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: BEJVB10000              |  | CERTIFICATION REPORT                                         |  | Reviewed by:<br>Quality Manager |
| SAR Filename:<br>0707230752.BEJ | Test Dates:<br>08/06/07 - 08/07/07                                                  | EUT Type:<br>Cellular/PCS CDMA Phone with Bluetooth and EvDO |                                                                                       | Page 11 of 25                   |

## 9

## TEST CONFIGURATION POSITIONS


### 9.1 Positioning for Cheek/Touch

1. The test device was positioned with the handset close to the surface of the phantom such that point A is on the (virtual) extension of the line passing through points RE and LE on the phantom (see Figure 9-1), such that the plane defined by the vertical center line and the horizontal line of the phone is approximately parallel to the sagittal plane of the phantom.



**Figure 9-1 Front, Side and Top View of Cheek/Touch Position**

2. The handset was translated towards the phantom along the line passing through RE & LE until the handset touches the ear.
3. While maintaining the handset in this plane, the handset was rotated around the LE-RE line until the vertical centerline was in the plane normal to MB-NF including the line MB (reference plane).
4. The phone was then rotated around the vertical centerline until the phone (horizontal line) was symmetrical with respect to the line NF.
5. While maintaining the vertical centerline in the reference plane, keeping point A on the line passing through RE and LE, and maintaining the phone contact with the ear, the handset was rotated about the line NF until any point on the handset made contact with a phantom point below the ear (cheek). See Figure 9-2)



**Figure 9-2 Side view w/ relevant markings**

### 9.2 Positioning for Ear / 15° Tilt

With the test device aligned in the “Cheek/Touch Position”:


1. While maintaining the orientation of the phone, the phone was retracted parallel to the reference plane far enough to enable a rotation of the phone by 15degree.
2. The phone was then rotated around the horizontal line by 15 degree.
3. While maintaining the orientation of the phone, the phone was moved parallel to the reference plane until any part of the phone touches the head. (In this position, point A was located on the line RE-LE). The tilted position is obtained when the contact is on the pinna. If the contact was at any location other than the pinna, the angle of the phone would then be reduced. The tilted

|                                 |                                                                                     |                                                              |                                                                                       |                                 |
|---------------------------------|-------------------------------------------------------------------------------------|--------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: BEJYX10000              |  | CERTIFICATION REPORT                                         |  | Reviewed by:<br>Quality Manager |
| SAR Filename:<br>0707230752.BEJ | Test Dates:<br>08/06/07 - 08/07/07                                                  | EUT Type:<br>Cellular/PCS CDMA Phone with Bluetooth and EvDO |                                                                                       | Page 12 of 25                   |

position was obtained when any part of the phone was in contact of the ear as well as a second part of the phone was in contact with the head (see Figure 9-3).



**Figure 9-3 Front, Side and Top View of Ear/15° Tilt Position**



**Figure 9-4**  
**Side view w/ relevant markings**



**Figure 9-5 Body SAR Sample Photo**  
**(Not Actual EUT)**

### 9.3 Body Holster /Belt Clip Configurations

Body-worn operating configurations are tested with the belt-clips and holsters attached to the device and positioned against a flat phantom in a normal use configuration (see Figure 9-5). A device with a headset output is tested with a headset connected to the device.

Accessories for Body-worn operation configurations are divided into two categories: those that do not contain metallic components and those that do contain metallic components. When multiple accessories that do not contain metallic components are supplied with the device, the device is tested with only the accessory that dictates the closest spacing to the body. Then multiple accessories that contain metallic components are tested with the device with each accessory. If multiple accessories share an identical metallic component (i.e. the same metallic belt-clip used with different holsters with no other metallic components) only the accessory that dictates the closest spacing to the body is tested.

Body-worn accessories may not always be supplied or available as options for some devices intended to be authorized for body-worn use. In this case, a test configuration with a separation distance between the back of the device and the flat phantom is used. Test position spacing was documented. Transmitters that are designed to operate in front of a person's face, as in push-to-talk configurations, are tested for SAR compliance with the front of the device positioned to face the flat phantom in brain fluid. For devices that are carried next to the body such as a shoulder, waist or chest-worn transmitters, SAR compliance is tested with the accessories, including headsets and microphones, attached to the device and positioned against a flat phantom in a normal use configuration.

In all cases SAR measurements are performed to investigate the worst-case positioning. Worst-case positioning is then documented and used to perform Body SAR testing.

|                                        |                                                                                     |                                                                     |                                                                                       |                                        |
|----------------------------------------|-------------------------------------------------------------------------------------|---------------------------------------------------------------------|---------------------------------------------------------------------------------------|----------------------------------------|
| <b>FCC ID:</b> BEJVB10000              |  | <b>CERTIFICATION REPORT</b>                                         |  | <b>Reviewed by:</b><br>Quality Manager |
| <b>SAR Filename:</b><br>0707230752.BEJ | <b>Test Dates:</b><br>08/06/07 - 08/07/07                                           | <b>EUT Type:</b><br>Cellular/PCS CDMA Phone with Bluetooth and EvDO |                                                                                       | Page 13 of 25                          |

## 10 ANSI/IEEE C95.1-2005 RF EXPOSURE LIMITS

### 10.1 Uncontrolled Environment

UNCONTROLLED ENVIRONMENTS are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure. The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity.

### 10.2 Controlled Environment

CONTROLLED ENVIRONMENTS are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e. as a result of employment or occupation). In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. This exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

**Table 10-1**  
**SAR Human Exposure Specified in ANSI/IEEE C95.1-2005**

| HUMAN EXPOSURE LIMITS                           |                                                                           |                                                                   |
|-------------------------------------------------|---------------------------------------------------------------------------|-------------------------------------------------------------------|
|                                                 | UNCONTROLLED ENVIRONMENT<br><i>General Population</i><br>(W/kg) or (mW/g) | CONTROLLED ENVIRONMENT<br><i>Occupational</i><br>(W/kg) or (mW/g) |
| SPATIAL PEAK SAR<br>Brain                       | 1.6                                                                       | 8.0                                                               |
| SPATIAL AVERAGE SAR<br>Whole Body               | 0.08                                                                      | 0.4                                                               |
| SPATIAL PEAK SAR<br>Hands, Feet, Ankles, Wrists | 4.0                                                                       | 20                                                                |

1 The Spatial Peak value of the SAR averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.

2 The Spatial Average value of the SAR averaged over the whole body.

3 The Spatial Peak value of the SAR averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.

|                                 |                                                                                     |                                                              |                                                                                       |                                 |
|---------------------------------|-------------------------------------------------------------------------------------|--------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: BEJVV10000              |  | CERTIFICATION REPORT                                         |  | Reviewed by:<br>Quality Manager |
| SAR Filename:<br>0707230752.BEJ | Test Dates:<br>08/06/07 - 08/07/07                                                  | EUT Type:<br>Cellular/PCS CDMA Phone with Bluetooth and EvDO |                                                                                       | Page 14 of 25                   |

# 11 MEASUREMENT UNCERTAINTIES

| a                                                                             | b                    | c             | d              | e=<br>f(d,k) | f                     | g                        | h =<br>c x f/e                 | i =<br>c x g/e                   | k              |
|-------------------------------------------------------------------------------|----------------------|---------------|----------------|--------------|-----------------------|--------------------------|--------------------------------|----------------------------------|----------------|
| Uncertainty<br>Component                                                      | IEEE<br>1528<br>Sec. | Tol.<br>(± %) | Prob.<br>Dist. | Div.         | c <sub>i</sub><br>1gm | c <sub>i</sub><br>10 gms | 1gm<br>u <sub>i</sub><br>(± %) | 10gms<br>u <sub>i</sub><br>(± %) | v <sub>i</sub> |
| <b>Measurement System</b>                                                     |                      |               |                |              |                       |                          |                                |                                  |                |
| Probe Calibration                                                             | E.2.1                | 6.6           | N              | 1            | 1.0                   | 1.0                      | 6.6                            | 6.6                              | ∞              |
| Axial Isotropy                                                                | E.2.2                | 0.25          | N              | 1            | 0.7                   | 0.7                      | 0.2                            | 0.2                              | ∞              |
| Hemishperical Isotropy                                                        | E.2.2                | 1.3           | N              | 1            | 1.0                   | 1.0                      | 1.3                            | 1.3                              | ∞              |
| Boundary Effect                                                               | E.2.3                | 0.4           | N              | 1            | 1.0                   | 1.0                      | 0.4                            | 0.4                              | ∞              |
| Linearity                                                                     | E.2.4                | 0.3           | N              | 1            | 1.0                   | 1.0                      | 0.3                            | 0.3                              | ∞              |
| System Detection Limits                                                       | E.2.5                | 5.1           | N              | 1            | 1.0                   | 1.0                      | 5.1                            | 5.1                              | ∞              |
| Readout Electronics                                                           | E.2.6                | 1.0           | N              | 1            | 1.0                   | 1.0                      | 1.0                            | 1.0                              | ∞              |
| Response Time                                                                 | E.2.7                | 0.8           | R              | 1.73         | 1.0                   | 1.0                      | 0.5                            | 0.5                              | ∞              |
| Integration Time                                                              | E.2.8                | 2.6           | R              | 1.73         | 1.0                   | 1.0                      | 1.5                            | 1.5                              | ∞              |
| RF Ambient Conditions                                                         | E.6.1                | 3.0           | R              | 1.73         | 1.0                   | 1.0                      | 1.7                            | 1.7                              | ∞              |
| Probe Positioner Mechanical Tolerance                                         | E.6.2                | 0.4           | R              | 1.73         | 1.0                   | 1.0                      | 0.2                            | 0.2                              | ∞              |
| Probe Positioning w/ respect to Phantom                                       | E.6.3                | 2.9           | R              | 1.73         | 1.0                   | 1.0                      | 1.7                            | 1.7                              | ∞              |
| Extrapolation, Interpolation & Integration algorithms for Max. SAR Evaluation | E.5                  | 1.0           | R              | 1.73         | 1.0                   | 1.0                      | 0.6                            | 0.6                              | ∞              |
| <b>Test Sample Related</b>                                                    |                      |               |                |              |                       |                          |                                |                                  |                |
| Test Sample Positioning                                                       | E.4.2                | 6.0           | N              | 1            | 1.0                   | 1.0                      | 6.0                            | 6.0                              | 287            |
| Device Holder Uncertainty                                                     | E.4.1                | 3.32          | R              | 1.73         | 1.0                   | 1.0                      | 1.9                            | 1.9                              | ∞              |
| Output Power Variation - SAR drift measurement                                | 6.6.2                | 5.0           | R              | 1.73         | 1.0                   | 1.0                      | 2.9                            | 2.9                              | ∞              |
| <b>Phantom &amp; Tissue Parameters</b>                                        |                      |               |                |              |                       |                          |                                |                                  |                |
| Phantom Uncertainty (Shape & Thickness tolerances)                            | E.3.1                | 4.0           | R              | 1.73         | 1.0                   | 1.0                      | 2.3                            | 2.3                              | ∞              |
| Liquid Conductivity - deviation from target values                            | E.3.2                | 5.0           | R              | 1.73         | 0.64                  | 0.43                     | 1.8                            | 1.2                              | ∞              |
| Liquid Conductivity - measurement uncertainty                                 | E.3.3                | 3.8           | N              | 1            | 0.64                  | 0.43                     | 2.4                            | 1.6                              | 6              |
| Liquid Permittivity - deviation from target values                            | E.3.2                | 5.0           | R              | 1.73         | 0.60                  | 0.49                     | 1.7                            | 1.4                              | ∞              |
| Liquid Permittivity - measurement uncertainty                                 | E.3.3                | 4.5           | N              | 1            | 0.60                  | 0.49                     | 2.7                            | 2.2                              | 6              |
| <b>Combined Standard Uncertainty (k=1)</b>                                    |                      |               |                |              |                       |                          | RSS                            | 12.4                             | 12.0           |
| <b>Expanded Uncertainty</b><br>(95% CONFIDENCE LEVEL)                         |                      |               |                |              |                       |                          | k=2                            | 24.7                             | 24.0           |

The above measurement uncertainties are according to IEEE Std. 1528-2003

|                                 |                                                                                     |                                                              |                                                                                       |                                 |
|---------------------------------|-------------------------------------------------------------------------------------|--------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: BEJXV10000              |  | CERTIFICATION REPORT                                         |  | Reviewed by:<br>Quality Manager |
| SAR Filename:<br>0707230752.BEJ | Test Dates:<br>08/06/07 - 08/07/07                                                  | EUT Type:<br>Cellular/PCS CDMA Phone with Bluetooth and EvDO |                                                                                       | Page 15 of 25                   |

## 12 SYSTEM VERIFICATION

### 12.1 Tissue Verification

**Table 12-1**  
**Measured Tissue Properties**


| Tissue Type    | Relative Permittivity: $\epsilon$ |          |           | Conductivity: $\sigma$ (S/m) |          |           | Calibration Date |
|----------------|-----------------------------------|----------|-----------|------------------------------|----------|-----------|------------------|
|                | Target                            | Measured | Deviation | Target                       | Measured | Deviation |                  |
| 835MHz Brain   | 41.50                             | 42.43    | +2.24%    | 0.90                         | 0.91     | +1.11%    | 08/06/2007       |
| 835MHz Muscle  | 55.20                             | 54.03    | -2.12%    | 0.97                         | 0.98     | +1.03%    | 08/06/2007       |
| 1900MHz Brain  | 40.00                             | 41.53    | +3.83%    | 1.40                         | 1.39     | -0.71%    | 08/06/2007       |
| 1900MHz Muscle | 53.30                             | 53.64    | +0.64%    | 1.52                         | 1.57     | +3.29%    | 08/06/2007       |

### 12.2 Test System Verification

Prior to assessment, the system is verified to  $\pm 10\%$  of the specifications at 835 MHz and 1900 MHz by using the system validation kit(s). (Graphic Plots Attached)

**Table 12-2**  
**System Verification Results**

| Date       | Frequency | Ambient Temp | Liquid Temp | Input Power | Target SAR | Measured SAR | Deviation |
|------------|-----------|--------------|-------------|-------------|------------|--------------|-----------|
|            | MHz       | °C           | °C          | mW          | W/kg       | W/kg         | %         |
| 08/06/2007 | 835       | 23.7         | 21.6        | 250         | 2.290      | 2.310        | +0.87     |
| 08/07/2007 | 835       | 23.8         | 21.5        | 250         | 2.290      | 2.430        | +6.11     |
| 08/06/2007 | 1900      | 23.8         | 21.8        | 100         | 3.770      | 3.730        | -1.06     |
| 08/07/2007 | 1900      | 23.7         | 21.4        | 100         | 3.770      | 3.630        | -3.71     |



**Figure 12-1**  
**System Verification Setup Diagram**



**Figure 12-2**  
**System Verification Setup Photo**

|                                 |                                                                                     |                                                              |                                                                                       |                                 |
|---------------------------------|-------------------------------------------------------------------------------------|--------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: BEJVB10000              |  | CERTIFICATION REPORT                                         |  | Reviewed by:<br>Quality Manager |
| SAR Filename:<br>0707230752.BEJ | Test Dates:<br>08/06/07 - 08/07/07                                                  | EUT Type:<br>Cellular/PCS CDMA Phone with Bluetooth and EvDO |                                                                                       | Page 16 of 25                   |

## 13 FCC 3G MEASUREMENT PROCEDURES – JUNE 2006

Power measurements were performed using a base station simulator under digital average power.

### 13.1 Procedures Used to Establish RF Signal for SAR

The device was placed into a simulated call using a base station simulator in a shielded chamber. Such test signals offer a consistent means for testing SAR and are recommended for evaluating SAR [4]. SAR measurements were taken with a fully charged battery. In order to verify that the device was tested and maintained at full power, it was configured with the base station simulator. The SAR measurement software calculates a reference point at the start and end of the test to check for power drifts. If conducted power deviations of more than 5% occurred, the tests were repeated.

### 13.2 SAR Measurement Conditions for CDMA2000

The following procedures were followed according to FCC “SAR Measurement Procedures for 3G Devices”, June 2006.

#### 13.2.1 Output Power Verification

See 3GPP2 C.S0011/TIA-98-E as recommended by “SAR Measurement Procedures for 3G Devices”, June 2006. Maximum output power is verified on the High, Middle and Low channels according to procedures in section 4.4.5.2 of 3GPP2 C.S0011/TIA-98-E. SO55 tests were measured with power control bits in “All Up” condition. .

1. If the mobile station (MS) supports Reverse TCH RC 1 and Forward TCH RC 1, set up a call using Fundamental Channel Test Mode 1 (RC=1/1) with 9600 bps data rate only.
2. Under RC1, C.S0011 Table 4.4.5.2-1, Table 13-1 parameters were applied.
3. If the MS supports the RC 3 Reverse FCH, RC3 Reverse SCH0 and demodulation of RC 3,4, or 5, set up a call using Supplemental Channel Test Mode 3 (RC 3/3) with 9600 bps Fundamental Channel and 9600 bps SCH0 data rate.
4. Under RC3, C.S0011 Table 4.4.5.2-2, Table 13-2 was applied.
5. FCHs were configured at full rate for maximum SAR with “All Up” power control bits.

**Table 13-1**  
**Parameters for Max. Power for RC1**

| Parameter                    | Units        | Value |
|------------------------------|--------------|-------|
| $I_{or}$                     | dBm/1.23 MHz | -104  |
| $\frac{Pilot E_c}{I_{or}}$   | dB           | -7    |
| $\frac{Traffic E_c}{I_{or}}$ | dB           | -7.4  |

**Table 13-2**  
**Parameters for Max. Power for RC3**

| Parameter                    | Units        | Value |
|------------------------------|--------------|-------|
| $I_{or}$                     | dBm/1.23 MHz | -86   |
| $\frac{Pilot E_c}{I_{or}}$   | dB           | -7    |
| $\frac{Traffic E_c}{I_{or}}$ | dB           | -7.4  |

#### 13.2.2 Head SAR Measurements

SAR for head exposure configurations is measured in RC3 with the DUT configured to transmit at full rate using Loopback Service Option SO55. SAR for RC1 is not required when the maximum average output of each channel is less than ¼ dB higher than that measured in RC3. Otherwise, SAR is measured on the maximum output channel in RC1 using the exposure configuration that results in the highest SAR for that channel in RC3.

|                                 |                                                                                     |                                                              |                                                                                       |                                 |
|---------------------------------|-------------------------------------------------------------------------------------|--------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: BEJVX10000              |  | CERTIFICATION REPORT                                         |  | Reviewed by:<br>Quality Manager |
| SAR Filename:<br>0707230752.BEJ | Test Dates:<br>08/06/07 - 08/07/07                                                  | EUT Type:<br>Cellular/PCS CDMA Phone with Bluetooth and EvDO |                                                                                       | Page 17 of 25                   |

### 13.2.3 Body SAR Measurements

SAR for body exposure configurations is measured in RC3 with the DUT configured to transmit at full rate on FCH with all other code channels disabled using TDSO / SO32. SAR for multiple code channels (FCH + SCHn) is not required when the maximum average output of each RF channel is less than ¼ dB higher than that measured with FCH only. Otherwise, SAR is measured on the maximum output channel (FCH + SCHn) with FCH at full rate and SCH0 enabled at 9600 bps using the exposure configuration that results in the highest SAR for that channel with FCH only. When multiple code channels are enabled, the DUT output may shift by more than 0.5 dB and lead to higher SAR drifts and SCH dropouts. Body SAR was measured using TDSO / SO32 with power control bits in the “All Up”


Body SAR in RC1 is not required when the maximum average output of each channel is less than ¼ dB higher than that measured in RC3. Otherwise, SAR is measured on the maximum output channel in RC1; with Loopback Service Option SO55, at full rate, using the body exposure configuration that results in the highest SAR for that channel in RC3.

### 13.2.4 Handsets with EVDO

For handsets with Ev-Do capabilities, when the maximum average output of each channel in Rev. 0 is less than ¼ dB higher than that measured in RC3 (1x RTT), body SAR for EV-DO is not required.<sup>7</sup> Otherwise, SAR for Rev. 0 is measured on the maximum output channel at 153.6 kbps using the body exposure configuration that results in the highest SAR for that channel in RC3.<sup>7</sup> SAR for Rev. A is not required when the maximum average output of each channel is less than that measured in Rev. 0 or less than ¼ dB higher than that measured in RC3. Otherwise, SAR is measured on the maximum output channel for Rev. A using a Reverse Data Channel payload size of 4096 bits and a Termination Target of 16 slots defined for Subtype 2 Physical Layer configurations. A Forward Traffic Channel data rate corresponding to the 2-slot version of 307.2 kbps with the ACK Channel transmitting in all slots should be configured in the downlink for both Rev. 0 and Rev. A.

## 13.3 Handset Capabilities\*:

\*See Device Capabilities attachment for applicable device modes and powers.



**Figure 13-1**  
**Power Measurement Setup**

|                                 |                                                                                     |                                                              |                                                                                       |                                 |
|---------------------------------|-------------------------------------------------------------------------------------|--------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: BEJVB10000              |  | CERTIFICATION REPORT                                         |  | Reviewed by:<br>Quality Manager |
| SAR Filename:<br>0707230752.BEJ | Test Dates:<br>08/06/07 - 08/07/07                                                  | EUT Type:<br>Cellular/PCS CDMA Phone with Bluetooth and EvDO |                                                                                       | Page 18 of 25                   |

## 14 SAR DATA SUMMARY

### 14.1 Cellular Band Head SAR Results

| MEASUREMENT RESULTS                                                                               |     |      |              |       |       |                                                  |              |          |           |        |        |
|---------------------------------------------------------------------------------------------------|-----|------|--------------|-------|-------|--------------------------------------------------|--------------|----------|-----------|--------|--------|
| FREQUENCY                                                                                         |     | Mode | C_Power[dBm] |       | Side  | Test Position                                    | Antenna Type | Battery  | Bluetooth | Memory | SAR    |
| MHz                                                                                               | Ch. |      | Start        | End   |       |                                                  |              |          |           |        | (W/kg) |
| 836.52                                                                                            | 384 | CDMA | 24.48        | 24.57 | Right | Touch                                            | Fixed        | Standard | off       | no     | 0.427  |
| 836.52                                                                                            | 384 | CDMA | 24.48        | 24.36 | Right | Touch                                            | Fixed        | Standard | on        | no     | 0.417  |
| 836.52                                                                                            | 384 | CDMA | 24.48        | 24.58 | Right | Touch                                            | Fixed        | Standard | off       | yes    | 0.422  |
| 836.52                                                                                            | 384 | CDMA | 24.48        | 24.53 | Right | Tilt                                             | Fixed        | Standard | off       | no     | 0.357  |
| 836.52                                                                                            | 384 | CDMA | 24.48        | 24.57 | Left  | Touch                                            | Fixed        | Standard | off       | no     | 0.414  |
| 836.52                                                                                            | 384 | CDMA | 24.48        | 24.55 | Left  | Touch                                            | Fixed        | Standard | on        | no     | 0.405  |
| 836.52                                                                                            | 384 | CDMA | 24.48        | 24.52 | Left  | Touch                                            | Fixed        | Standard | off       | yes    | 0.413  |
| 836.52                                                                                            | 384 | CDMA | 24.48        | 24.52 | Left  | Tilt                                             | Fixed        | Standard | off       | no     | 0.345  |
| ANSI / IEEE C95.1 2005 - SAFETY LIMIT<br>Spatial Peak<br>Uncontrolled Exposure/General Population |     |      |              |       |       | Brain<br>1.6 W/kg (mW/g)<br>averaged over 1 gram |              |          |           |        |        |

Notes:

1. The test data reported are the worst-case SAR value with the position set in a typical configuration. Test procedures used are according to FCC/OET Bulletin 65, Supplement C [July 2001].
2. All modes of operation were investigated, and worst-case results are reported.
3. Batteries are fully charged for all readings. Standard batteries were investigated.
4. Tissue parameters and temperatures are listed on the SAR plots.
5. Liquid tissue depth is 15.1 cm.  $\pm$  0.1.
6. Justification for reduced test configurations: Per FCC/OET Bulletin 65 Supplement C (July, 2001) and Public Notice DA-02-1438, if the SAR measured at the middle channel for each test configuration (left, right, cheek/touch, tilt/ear, extended and retracted) is at least 3.0 dB lower than the SAR limit, testing at the high and low channels is optional for such test configuration(s).
7. Head SAR was tested under RC3/SO55

|                                 |                                                                                     |                                                              |                                                                                       |                                 |
|---------------------------------|-------------------------------------------------------------------------------------|--------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: BEJVB10000              |  | CERTIFICATION REPORT                                         |  | Reviewed by:<br>Quality Manager |
| SAR Filename:<br>0707230752.BEJ | Test Dates:<br>08/06/07 - 08/07/07                                                  | EUT Type:<br>Cellular/PCS CDMA Phone with Bluetooth and EvDO |                                                                                       | Page 19 of 25                   |

## 14.2 PCS Band Head SAR Results

| MEASUREMENT RESULTS                      |     |      |              |       |       |                      |              |          |           |        |        |
|------------------------------------------|-----|------|--------------|-------|-------|----------------------|--------------|----------|-----------|--------|--------|
| FREQUENCY                                |     | Mode | C_Power[dBm] |       | Side  | Test Position        | Antenna Type | Battery  | Bluetooth | Memory | SAR    |
| MHz                                      | Ch. |      | Start        | End   |       |                      |              |          |           |        | (W/kg) |
| 1880.00                                  | 600 | PCS  | 24.80        | 24.62 | Right | Touch                | Fixed        | Standard | off       | no     | 0.526  |
| 1880.00                                  | 600 | PCS  | 24.80        | 24.70 | Right | Tilt                 | Fixed        | Standard | off       | no     | 0.753  |
| 1880.00                                  | 600 | PCS  | 24.80        | 24.84 | Right | Tilt                 | Fixed        | Standard | on        | no     | 0.742  |
| 1880.00                                  | 600 | PCS  | 24.80        | 24.76 | Right | Tilt                 | Fixed        | Standard | off       | yes    | 0.731  |
| 1880.00                                  | 600 | PCS  | 24.80        | 24.95 | Left  | Touch                | Fixed        | Standard | off       | no     | 0.503  |
| 1880.00                                  | 600 | PCS  | 24.80        | 24.92 | Left  | Tilt                 | Fixed        | Standard | off       | no     | 0.765  |
| 1880.00                                  | 600 | PCS  | 24.80        | 24.82 | Left  | Tilt                 | Fixed        | Standard | on        | no     | 0.763  |
| 1880.00                                  | 600 | PCS  | 24.80        | 24.93 | Left  | Tilt                 | Fixed        | Standard | off       | yes    | 0.743  |
| ANSI / IEEE C95.1 2005 - SAFETY LIMIT    |     |      |              |       |       | Brain                |              |          |           |        |        |
| Spatial Peak                             |     |      |              |       |       | 1.6 W/kg (mW/g)      |              |          |           |        |        |
| Uncontrolled Exposure/General Population |     |      |              |       |       | averaged over 1 gram |              |          |           |        |        |

### Notes:

1. The test data reported are the worst-case SAR value with the position set in a typical configuration. Test procedures used are according to FCC/OET Bulletin 65, Supplement C [July 2001].
2. All modes of operation were investigated, and worst-case results are reported.
3. Batteries are fully charged for all readings. Standard batteries were investigated.
4. Tissue parameters and temperatures are listed on the SAR plots.
5. Liquid tissue depth is 15.1 cm.  $\pm$  0.1.
6. Justification for reduced test configurations: Per FCC/OET Bulletin 65 Supplement C (July, 2001) and Public Notice DA-02-1438, if the SAR measured at the middle channel for each test configuration (left, right, cheek/touch, tilt/ear, extended and retracted) is at least 3.0 dB lower than the SAR limit, testing at the high and low channels is optional for such test configuration(s).
7. Head SAR was tested under RC3/SO55

|                                 |                                                                                     |                                                              |                                                                                       |                                 |
|---------------------------------|-------------------------------------------------------------------------------------|--------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: BEJVV10000              |  | CERTIFICATION REPORT                                         |  | Reviewed by:<br>Quality Manager |
| SAR Filename:<br>0707230752.BEJ | Test Dates:<br>08/06/07 - 08/07/07                                                  | EUT Type:<br>Cellular/PCS CDMA Phone with Bluetooth and EvDO |                                                                                       | Page 20 of 25                   |

### 14.3 Body SAR Results

| MEASUREMENT RESULTS                                                                               |      |      |              |       |          |         |                                                   |          |           |        |       |        |
|---------------------------------------------------------------------------------------------------|------|------|--------------|-------|----------|---------|---------------------------------------------------|----------|-----------|--------|-------|--------|
| FREQUENCY                                                                                         |      | Mode | C_Power[dBm] |       | Position | Service | Spacing                                           | Battery  | Bluetooth | Memory | Side  | SAR    |
| MHz                                                                                               | Ch.  |      | Start        | End   |          |         |                                                   |          |           |        |       | (W/kg) |
| 824.70                                                                                            | 1013 | CDMA | 24.65        | 24.74 | Body     | TDSO32  | 2.0 cm                                            | Standard | off       | no     | back  | 0.893  |
| 836.52                                                                                            | 384  | CDMA | 24.64        | 24.72 | Body     | TDSO32  | 2.0 cm                                            | Standard | off       | no     | back  | 0.813  |
| 848.31                                                                                            | 777  | CDMA | 24.67        | 24.85 | Body     | TDSO32  | 2.0 cm                                            | Standard | off       | no     | back  | 0.772  |
| 824.70                                                                                            | 1013 | CDMA | 24.65        | 24.75 | Body     | TDSO32  | 2.0 cm                                            | Standard | on        | no     | back  | 0.877  |
| 824.70                                                                                            | 1013 | CDMA | 24.65        | 24.65 | Body     | TDSO32  | 2.0 cm                                            | Standard | off       | yes    | back  | 0.888  |
| 824.70                                                                                            | 1013 | CDMA | 24.65        | 24.68 | Body     | TDSO32  | 2.0 cm                                            | Standard | off       | no     | front | 0.295  |
| 1880.00                                                                                           | 600  | PCS  | 24.94        | 24.91 | Body     | TDSO32  | 2.0 cm                                            | Standard | off       | no     | back  | 0.606  |
| 1880.00                                                                                           | 600  | PCS  | 24.94        | 24.86 | Body     | TDSO32  | 2.0 cm                                            | Extended | off       | no     | back  | 0.605  |
| 1880.00                                                                                           | 600  | PCS  | 24.94        | 24.92 | Body     | TDSO32  | 2.0 cm                                            | Standard | on        | no     | back  | 0.598  |
| 1880.00                                                                                           | 600  | PCS  | 24.94        | 24.80 | Body     | TDSO32  | 2.0 cm                                            | Standard | off       | no     | front | 0.167  |
| ANSI / IEEE C95.1 2005 - SAFETY LIMIT<br>Spatial Peak<br>Uncontrolled Exposure/General Population |      |      |              |       |          |         | Muscle<br>1.6 W/kg (mW/g)<br>averaged over 1 gram |          |           |        |       |        |

#### Notes:

1. The test data reported are the worst-case SAR value with the position set in a typical configuration. Test procedures used are according to FCC/OET Bulletin 65, Supplement C [July 2001].
2. All modes of operation were investigated, and worst-case results are reported.
3. Batteries are fully charged for all readings. Standard batteries were investigated.
4. Tissue parameters and temperatures are listed on the SAR plots.
5. Both sides of the phone were tested, and the worst-case is reported.
6. Liquid tissue depth is 15.1 cm.  $\pm$  0.1.
7. Device was tested using a fixed spacing.
8. Body SAR was tested under RC3/SO32. EVDO is evaluated when the conducted powers are 0.25 dB or greater than the RC3/SO32 conducted power.
9. Justification for reduced test configurations: This device supports Ev-DO. Because the maximum average output of each channel in this mode is less than ¼ dB higher than that measured in RC3 (1x RTT), body SAR is not required for Ev-DO mode.

|                                 |                                                                                     |                                                              |                                                                                       |                                 |
|---------------------------------|-------------------------------------------------------------------------------------|--------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: BEJXV10000              |  | CERTIFICATION REPORT                                         |  | Reviewed by:<br>Quality Manager |
| SAR Filename:<br>0707230752.BEJ | Test Dates:<br>08/06/07 - 08/07/07                                                  | EUT Type:<br>Cellular/PCS CDMA Phone with Bluetooth and EvDO |                                                                                       | Page 21 of 25                   |

## 15 EQUIPMENT LIST

| Manufacturer    | Model / Equipment                       | Calibration Date | Cal Interval | Calibration Due | Serial No. |
|-----------------|-----------------------------------------|------------------|--------------|-----------------|------------|
| Agilent         | N4010A Wireless Connectivity Test Set   | 6/11/2007        | Annual       | 6/10/2008       | GB46170464 |
| Agilent         | E5515C Wireless Communications Test Set | 7/27/2006        | Biennial     | 7/26/2008       | GB41450275 |
| Agilent         | E5515C Wireless Communications Test Set | 10/6/2006        | Biennial     | 10/5/2008       | GB43193972 |
| Agilent         | 8648D (9kHz-4GHz) Signal Generator      | 10/1/2006        | Annual       | 10/1/2007       | 3613A00315 |
| Agilent         | E5515C Wireless Communications Test Set | 10/26/2006       | Biennial     | 10/25/2008      | GB46310798 |
| Rohde & Schwarz | NRVS Power Meter                        | 7/3/2007         | Biennial     | 7/2/2009        | 835360/079 |
| Rohde & Schwarz | NRV-Z53 Power Sensor                    | 7/3/2007         | Biennial     | 7/2/2009        | 846076/007 |
| Rohde & Schwarz | CMU200 Base Station Simulator           | 11/8/2006        | Annual       | 11/8/2007       | 107826     |
| Rohde & Schwarz | CMU200 Base Station Simulator           | 5/24/2007        | Annual       | 5/23/2008       | 836371/079 |
| SPEAG           | D1900V2 1900 MHz SAR Dipole             | 1/23/2007        | Biennial     | 1/22/2009       | 502        |
| SPEAG           | D835V2 835MHz SAR Dipole                | 8/24/2005        | Biennial     | 8/24/2007       | 4d026      |
| SPEAG           | D5GHzV2 5 GHz SAR Dipole                | 10/5/2005        | Biennial     | 10/5/2007       | 1007       |
| SPEAG           | EX3DV4 SAR Probe                        | 1/22/2007        | Annual       | 1/22/2008       | 3550       |
| SPEAG           | DAE4                                    | 5/24/2007        | Annual       | 5/23/2008       | 704        |
| SPEAG           | EX3DV4 SAR Probe                        | 5/28/2007        | Annual       | 5/27/2008       | 3589       |
| SPEAG           | DAE4                                    | 9/4/2006         | Annual       | 9/4/2007        | 665        |
| SPEAG           | EX3DV4 SAR Probe                        | 11/23/2006       | Annual       | 11/23/2007      | 3561       |
| SPEAG           | ES3DV2 SAR Probe                        | 9/20/2006        | Annual       | 9/20/2007       | 3022       |
| SPEAG           | DAE3                                    | 10/16/2006       | Annual       | 10/16/2007      | 455        |
| SPEAG           | DAE4                                    | 1/23/2007        | Annual       | 1/23/2008       | 649        |
| SPEAG           | D2600V2 2600MHz SAR Dipole              | 1/5/2007         | Annual       | 1/5/2008        | 1004       |
| Agilent         | E8257D (250kHz-20GHz) Signal Generator  | 3/8/2007         | Annual       | 3/7/2008        | MY45470194 |
| VWR             | 61161-274 Alarm Digital Thermometer     | 8/19/2006        | Annual       | 8/19/2007       | 51280556   |
| Rohde & Schwarz | NRVD Dual Channel Power Meter           | 12/11/2006       | Biennial     | 12/10/2008      | 101695     |
| Rohde & Schwarz | NRV-Z33 Peak Power Sensor (1mW-20W)     | 11/28/2006       | Biennial     | 11/27/2008      | 100155     |
| Rohde & Schwarz | NRV-Z32 Peak Power Sensor (100uW-2W)    | 12/21/2006       | Biennial     | 12/20/2008      | 100004     |
| SPEAG           | D835V2 835MHz SAR Dipole                | 1/8/2007         | Biennial     | 1/7/2009        | 4d047      |
| SPEAG           | D1900V2 1900MHz SAR Dipole              | 1/23/2007        | Biennial     | 1/22/2009       | 5d080      |
| SPEAG           | D2450V2 2450MHz SAR Dipole              | 1/17/2007        | Biennial     | 1/16/2009       | 797        |
| SPEAG           | D5GHzV2 5GHz SAR Dipole                 | 1/24/2007        | Biennial     | 1/23/2009       | 1057       |
| SPEAG           | D1450V2 1450 MHz SAR Dipole             | 6/11/2007        | Biennial     | 6/10/2009       | 1025       |
| SPEAG           | D1765V2 1765 MHz SAR Dipole             | 6/11/2007        | Biennial     | 6/10/2009       | 1008       |

### Notes:

The E-field probe was calibrated by SPEAG, by the waveguide technique procedure. Dipole Validation measurement is performed by PCTEST prior to SAR evaluation. The brain simulating material is calibrated by PCTEST using the dielectric probe system and network analyzer to determine the conductivity and permittivity (dielectric constant) of the brain-equivalent material.

|                                 |                                                                                     |                                                              |                                                                                       |                                 |
|---------------------------------|-------------------------------------------------------------------------------------|--------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: BEJXX10000              |  | CERTIFICATION REPORT                                         |  | Reviewed by:<br>Quality Manager |
| SAR Filename:<br>0707230752.BEJ | Test Dates:<br>08/06/07 - 08/07/07                                                  | EUT Type:<br>Cellular/PCS CDMA Phone with Bluetooth and EvDO |                                                                                       | Page 22 of 25                   |

## 16 CONCLUSION

### 16.1 Measurement Conclusion

The SAR evaluation indicates that the EUT complies with the RF radiation exposure limits of the FCC, with respect to all parameters subject to this test. These measurements were taken to simulate the RF effects of RF exposure under worst-case conditions. Precise laboratory measures were taken to assure repeatability of the tests. The results and statements relate only to the item(s) tested.

Please note that the absorption and distribution of electromagnetic energy in the body are very complex phenomena that depend on the mass, shape, and size of the body, the orientation of the body with respect to the field vectors, and the electrical properties of both the body and the environment. Other variables that may play a substantial role in possible biological effects are those that characterize the environment (e.g. ambient temperature, air velocity, relative humidity, and body insulation) and those that characterize the individual (e.g. age, gender, activity level, debilitation, or disease). Because various factors may interact with one another to vary the specific biological outcome of an exposure to electromagnetic fields, any protection guide should consider maximal amplification of biological effects as a result of field-body interactions, environmental conditions, and physiological variables. [3]

|                                        |                                                                                     |                                                                     |                                                                                       |                                        |
|----------------------------------------|-------------------------------------------------------------------------------------|---------------------------------------------------------------------|---------------------------------------------------------------------------------------|----------------------------------------|
| <b>FCC ID:</b> BEJVX10000              |  | <b>CERTIFICATION REPORT</b>                                         |  | <b>Reviewed by:</b><br>Quality Manager |
| <b>SAR Filename:</b><br>0707230752.BEJ | <b>Test Dates:</b><br>08/06/07 - 08/07/07                                           | <b>EUT Type:</b><br>Cellular/PCS CDMA Phone with Bluetooth and EvDO |                                                                                       | Page 23 of 25                          |

## 17 REFERENCES

- [1] Federal Communications Commission, ET Docket 93-62, Guidelines for Evaluating the Environmental Effects of Radiofrequency Radiation, Aug. 1996.
- [2] ANSI/IEEE C95.1-2005, American National Standard safety levels with respect to human exposure to radio frequency electromagnetic fields, 300kHz to 100GHz, New York: IEEE, April 2006.
- [3] ANSI/IEEE C95.3-2002, IEEE Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields - RF and Microwave, New York: IEEE, December 2002.
- [4] Federal Communications Commission, OET Bulletin 65 (Edition 97-01), Supplement C (Edition 01-01), Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields, July 2001.
- [5] IEEE Standards Coordinating Committee 34 – IEEE Std. 1528-2003, Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Body Due to Wireless Communications Devices.
- [6] NCRP, National Council on Radiation Protection and Measurements, Biological Effects and Exposure Criteria for RadioFrequency Electromagnetic Fields, NCRP Report No. 86, 1986. Reprinted Feb. 1995.
- [7] T. Schmid, O. Egger, N. Kuster, Automated E-field scanning system for dosimetric assessments, IEEE Transaction on Microwave Theory and Techniques, vol. 44, Jan. 1996, pp. 105-113.
- [8] K. Pokovic, T. Schmid, N. Kuster, Robust setup for precise calibration of E-field probes in tissue simulating liquids at mobile communications frequencies, ICECOM97, Oct. 1997, pp. 120-124.
- [9] K. Pokovic, T. Schmid, and N. Kuster, E-field Probe with improved isotropy in brain simulating liquids, Proceedings of the ELMAR, Zadar, Croatia, June 23-25, 1996, pp. 172-175.
- [10] Schmid & Partner Engineering AG, Application Note: Data Storage and Evaluation, June 1998, p2.
- [11] V. Hombach, K. Meier, M. Burkhardt, E. Kuhn, N. Kuster, The Dependence of EM Energy Absorption upon Human Head Modeling at 900 MHz, IEEE Transaction on Microwave Theory and Techniques, vol. 44 no. 10, Oct. 1996, pp. 1865-1873.
- [12] N. Kuster and Q. Balzano, Energy absorption mechanism by biological bodies in the near field of dipole antennas above 300MHz, IEEE Transaction on Vehicular Technology, vol. 41, no. 1, Feb. 1992, pp. 17-23.
- [13] G. Hartsgrrove, A. Kraszewski, A. Surowiec, Simulated Biological Materials for Electromagnetic Radiation Absorption Studies, University of Ottawa, Bioelectromagnetics, Canada: 1987, pp. 29-36.
- [14] Q. Balzano, O. Garay, T. Manning Jr., Electromagnetic Energy Exposure of Simulated Users of Portable Cellular Telephones, IEEE Transactions on Vehicular Technology, vol. 44, no.3, Aug. 1995.
- [15] W. Gander, Computermathematick, Birkhaeuser, Basel, 1992.
- [16] W.H. Press, S.A. Teukolsky, W.T. Vetterling, and B.P. Flannery, Numerical Recepies in C, The Art of Scientific Computing, Second edition, Cambridge University Press, 1992.

|                                        |                                                                                     |                                                                     |                                                                                       |                                        |
|----------------------------------------|-------------------------------------------------------------------------------------|---------------------------------------------------------------------|---------------------------------------------------------------------------------------|----------------------------------------|
| <b>FCC ID:</b> BEJVB10000              |  | <b>CERTIFICATION REPORT</b>                                         |  | <b>Reviewed by:</b><br>Quality Manager |
| <b>SAR Filename:</b><br>0707230752.BEJ | <b>Test Dates:</b><br>08/06/07 - 08/07/07                                           | <b>EUT Type:</b><br>Cellular/PCS CDMA Phone with Bluetooth and EvDO |                                                                                       | Page 24 of 25                          |

- [17] Federal Communications Commission, OET Bulletin 65, Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields. Supplement C, Dec. 1997.
- [18] N. Kuster, R. Kastle, T. Schmid, Dosimetric evaluation of mobile communications equipment with known precision, IEEE Transaction on Communications, vol. E80-B, no. 5, May 1997, pp. 645-652.
- [19] CENELEC CLC/SC111B, European Prestandard (prENV 50166-2), Human Exposure to Electromagnetic Fields High-frequency: 10kHz-300GHz, Jan. 1995.
- [20] Prof. Dr. Niels Kuster, ETH, Eidgenössische Technische Hochschule Zürich, Dosimetric Evaluation of the Cellular Phone.
- [21] FCC SAR Measurement Procedures for 3G Devices, June 2006
- [22] SAR Measurement procedures for IEEE 802.11a/b/g rev 1.1, Oct 2006
- [23] IEC 62209-1, Human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices - Human models, instrumentation, and procedures - Part 1: Procedure to determine the specific absorption rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz), Feb. 2005.
- [24] FCC Public Notice DA-02-1438. Office of Engineering and Technology Announces a Transition Period for the Phantom Requirements of Supplement C to OET Bulletin 65, June 19, 2002

|                                        |                                                                                     |                                                                     |                                                                                       |                                        |
|----------------------------------------|-------------------------------------------------------------------------------------|---------------------------------------------------------------------|---------------------------------------------------------------------------------------|----------------------------------------|
| <b>FCC ID:</b> BEJVX10000              |  | <b>CERTIFICATION REPORT</b>                                         |  | <b>Reviewed by:</b><br>Quality Manager |
| <b>SAR Filename:</b><br>0707230752.BEJ | <b>Test Dates:</b><br>08/06/07 - 08/07/07                                           | <b>EUT Type:</b><br>Cellular/PCS CDMA Phone with Bluetooth and EvDO |                                                                                       | Page 25 of 25                          |

## **APPENDIX A: SAR TEST DATA**

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: VX10000; Type: Cellular/PCS CDMA Phone with Bluetooth and EvDO; Serial: A00000038A8F1E**  
**Conducted Power: 24.5 dBm**

Communication System: Cellular CDMA; Frequency: 836.52 MHz; Duty Cycle: 1:1

Medium: 835 Brain ( $\sigma = 0.91$  mho/m,  $\epsilon_r = 42.43$ ,  $\rho = 1000$  kg/m<sup>3</sup>)

Phantom section: Right Section

Test Date: 08-07-2007; Ambient Temp: 23.8°C; Tissue Temp: 21.5°C

Probe: EX3DV4 - SN3561; ConvF(7.94, 7.94, 7.94); Calibrated: 11/23/2006

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn649; Calibrated: 1/23/2007

Phantom: SAM Main; Type: SAM 4.0; Serial: TP-1114

Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

**Mode: Cellular CDMA, Right Head, Touch, Mid.ch, Standard Battery**


**Area Scan (7x11x1):** Measurement grid: dx=15mm, dy=15mm

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 21.6 V/m

Peak SAR (extrapolated) = 0.559 W/kg

**SAR(1 g) = 0.427 mW/g; SAR(10 g) = 0.320 mW/g**



0 dB = 0.500mW/g

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: VX10000; Type: Cellular/PCS CDMA Phone with Bluetooth and EvDO; Serial: A00000038A8F1E**  
**Conducted Power: 24.5 dBm**

Communication System: Cellular CDMA; Frequency: 836.52 MHz; Duty Cycle: 1:1

Medium: 835 Brain ( $\sigma = 0.91$  mho/m,  $\epsilon_r = 42.43$ ,  $\rho = 1000$  kg/m<sup>3</sup>)

Phantom section: Right Section

Test Date: 08-07-2007; Ambient Temp: 23.8°C; Tissue Temp: 21.5°C

Probe: EX3DV4 - SN3561; ConvF(7.94, 7.94, 7.94); Calibrated: 11/23/2006

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn649; Calibrated: 1/23/2007

Phantom: SAM Main; Type: SAM 4.0; Serial: TP-1114

Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

**Mode: Cellular CDMA, Right Head, Tilt, Mid.ch, Standard Battery**


**Area Scan (7x11x1):** Measurement grid: dx=15mm, dy=15mm

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 20.8 V/m

Peak SAR (extrapolated) = 0.519 W/kg

**SAR(1 g) = 0.357 mW/g; SAR(10 g) = 0.244 mW/g**



0 dB = 0.400mW/g

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: VX10000; Type: Cellular/PCS CDMA Phone with Bluetooth and EvDO; Serial: A00000038A8F1E**  
**Conducted Power: 24.5 dBm**

Communication System: Cellular CDMA; Frequency: 836.52 MHz; Duty Cycle: 1:1

Medium: 835 Brain ( $\sigma = 0.91$  mho/m,  $\epsilon_r = 42.43$ ,  $\rho = 1000$  kg/m<sup>3</sup>)

Phantom section: Left Section

Test Date: 08-07-2007; Ambient Temp: 23.8°C; Tissue Temp: 21.5°C

Probe: EX3DV4 - SN3561; ConvF(7.94, 7.94, 7.94); Calibrated: 11/23/2006

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn649; Calibrated: 1/23/2007

Phantom: SAM Main; Type: SAM 4.0; Serial: TP-1114

Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

**Mode: Cellular CDMA, Left Head, Touch, Mid.ch, Standard Battery**


**Area Scan (7x11x1):** Measurement grid: dx=15mm, dy=15mm

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 21.5 V/m

Peak SAR (extrapolated) = 0.584 W/kg

**SAR(1 g) = 0.414 mW/g; SAR(10 g) = 0.292 mW/g**



0 dB = 0.500mW/g

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: VX10000; Type: Cellular/PCS CDMA Phone with Bluetooth and EvDO; Serial: A00000038A8F1E**  
**Conducted Power: 24.5 dBm**

Communication System: Cellular CDMA; Frequency: 836.52 MHz; Duty Cycle: 1:1

Medium: 835 Brain ( $\sigma = 0.91$  mho/m,  $\epsilon_r = 42.43$ ,  $\rho = 1000$  kg/m<sup>3</sup>)

Phantom section: Left Section

Date: 08-07-2007; Ambient Temp: 23.8°C; Tissue Temp: 21.5°C

Probe: EX3DV4 - SN3561; ConvF(7.94, 7.94, 7.94); Calibrated: 11/23/2006

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn649; Calibrated: 1/23/2007

Phantom: SAM Main; Type: SAM 4.0; Serial: TP-1114

Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

**Mode: Cellular CDMA, Left Head, Tilt, Mid.ch, Standard Battery**


**Area Scan (7x11x1):** Measurement grid: dx=15mm, dy=15mm

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 20.0 V/m

Peak SAR (extrapolated) = 0.528 W/kg

**SAR(1 g) = 0.345 mW/g; SAR(10 g) = 0.229 mW/g**



0 dB = 0.400mW/g

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: VX10000; Type: Cellular/PCS CDMA Phone with Bluetooth and EvDO; Serial: A00000038A8F1E**  
**Conducted Power: 24.5 dBm**

Communication System: PCS CDMA; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: 1900 Brain ( $\sigma = 1.39$  mho/m,  $\epsilon_r = 41.53$ ,  $\rho = 1000$  kg/m<sup>3</sup>)

Phantom section: Right Section

Test Date: 08-06-2007; Ambient Temp: 23.8°C; Tissue Temp: 21.8°C

Probe: EX3DV4 - SN3561; ConvF(6.99, 6.99, 6.99); Calibrated: 11/23/2006

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn649; Calibrated: 1/23/2007

Phantom: SAM Sub; Type: SAM 4.0; Serial: TP-1357

Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

**Mode: PCS CDMA, Right Head, Touch, Mid.ch, Standard Battery**


**Area Scan (7x11x1):** Measurement grid: dx=15mm, dy=15mm

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 18.7 V/m

Peak SAR (extrapolated) = 0.812 W/kg

**SAR(1 g) = 0.526 mW/g; SAR(10 g) = 0.328 mW/g**



0 dB = 0.600mW/g

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: VX10000; Type: Cellular/PCS CDMA Phone with Bluetooth and EvDO; Serial: A00000038A8F1E**  
**Conducted Power: 24.5 dBm**

Communication System: PCS CDMA; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: 1900 Brain ( $\sigma = 1.39$  mho/m,  $\epsilon_r = 41.53$ ,  $\rho = 1000$  kg/m<sup>3</sup>)

Phantom section: Right Section

Test Date: 08-06-2007; Ambient Temp: 23.8°C; Tissue Temp: 21.8°C

Probe: EX3DV4 - SN3561; ConvF(6.99, 6.99, 6.99); Calibrated: 11/23/2006

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn649; Calibrated: 1/23/2007

Phantom: SAM Sub; Type: SAM 4.0; Serial: TP-1357

Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

**Mode: PCS CDMA, Right Head, Tilt, Mid.ch, Standard Battery**


**Area Scan (7x11x1):** Measurement grid: dx=15mm, dy=15mm

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 24.3 V/m

Peak SAR (extrapolated) = 1.29 W/kg

**SAR(1 g) = 0.753 mW/g; SAR(10 g) = 0.428 mW/g**



0 dB = 0.800mW/g

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: VX10000; Type: Cellular/PCS CDMA Phone with Bluetooth and EvDO; Serial: A00000038A8F1E**  
**Conducted Power: 24.5 dBm**

Communication System: PCS CDMA; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: 1900 Brain ( $\sigma = 1.39$  mho/m,  $\epsilon_r = 41.53$ ,  $\rho = 1000$  kg/m<sup>3</sup>)

Phantom section: Left Section

Test Date: 08-07-2007; Ambient Temp: 23.7°C; Tissue Temp: 21.4°C

Probe: EX3DV4 - SN3561; ConvF(6.99, 6.99, 6.99); Calibrated: 11/23/2006

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn649; Calibrated: 1/23/2007

Phantom: SAM Sub; Type: SAM 4.0; Serial: TP-1357

Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

**Mode: PCS CDMA, Left Head, Touch, Mid.ch, Standard Battery**


**Area Scan (7x11x1):** Measurement grid: dx=15mm, dy=15mm

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 15.9 V/m

Peak SAR (extrapolated) = 0.888 W/kg

**SAR(1 g) = 0.503 mW/g; SAR(10 g) = 0.280 mW/g**



0 dB = 0.600mW/g

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: VX10000; Type: Cellular/PCS CDMA Phone with Bluetooth and EvDO; Serial: A00000038A8F1E**  
**Conducted Power: 24.5 dBm**

Communication System: PCS CDMA; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: 1900 Brain ( $\sigma = 1.39$  mho/m,  $\epsilon_r = 41.53$ ,  $\rho = 1000$  kg/m<sup>3</sup>)

Phantom section: Left Section

Test Date: 08-07-2007; Ambient Temp: 23.7°C; Tissue Temp: 21.4°C

Probe: EX3DV4 - SN3561; ConvF(6.99, 6.99, 6.99); Calibrated: 11/23/2006

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn649; Calibrated: 1/23/2007

Phantom: SAM Sub; Type: SAM 4.0; Serial: TP-1357

Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

**Mode: PCS CDMA, Left Head, Tilt, Mid.ch, Standard Battery**


**Area Scan (7x11x1):** Measurement grid: dx=15mm, dy=15mm

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 23.2 V/m

Peak SAR (extrapolated) = 1.38 W/kg

**SAR(1 g) = 0.765 mW/g; SAR(10 g) = 0.414 mW/g**



0 dB = 0.800mW/g

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: VX10000; Type: Cellular/PCS CDMA Phone with Bluetooth and EvDO; Serial: A00000038A8F1E**  
**Conducted Power: 24.5 dBm**

Communication System: Cellular CDMA; Frequency: 824.7 MHz; Duty Cycle: 1:1

Medium: 835 Muscle ( $\sigma = 0.98$  mho/m,  $\epsilon_r = 54.03$ ,  $\rho = 1000$  kg/m<sup>3</sup>)

Phantom section: Flat Section; Space: 2.0 cm

Test Date: 08-06-2007; Ambient Temp: 23.4°C; Tissue Temp: 21.7°C

Probe: EX3DV4 - SN3561; ConvF(7.92, 7.92, 7.92); Calibrated: 11/23/2006

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn649; Calibrated: 1/23/2007

Phantom: SAM Main; Type: SAM 4.0; Serial: TP-1114

Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

**Mode: Cellular CDMA, Body SAR, Back side, Low.ch, Standard Battery**


**Area Scan (7x11x1):** Measurement grid: dx=15mm, dy=15mm

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 30.7 V/m

Peak SAR (extrapolated) = 1.15 W/kg

**SAR(1 g) = 0.893 mW/g; SAR(10 g) = 0.662 mW/g**



0 dB = 0.900mW/g

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: VX10000; Type: Cellular/PCS CDMA Phone with Bluetooth and EvDO; Serial: A00000038A8F1E**  
**Conducted Power: 24.5 dBm**

Communication System: Cellular CDMA; Frequency: 836.52 MHz; Duty Cycle: 1:1

Medium: 835 Muscle ( $\sigma = 0.98$  mho/m,  $\epsilon_r = 54.03$ ,  $\rho = 1000$  kg/m<sup>3</sup>)

Phantom section: Flat Section; Space: 2.0 cm

Test Date: 08-06-2007; Ambient Temp: 23.4°C; Tissue Temp: 21.7°C

Probe: EX3DV4 - SN3561; ConvF(7.92, 7.92, 7.92); Calibrated: 11/23/2006

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn649; Calibrated: 1/23/2007

Phantom: SAM Main; Type: SAM 4.0; Serial: TP-1114

Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

**Mode: Cellular CDMA, Body SAR, Front side, Mid.ch, Standard Battery**


**Area Scan (7x11x1):** Measurement grid: dx=15mm, dy=15mm

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 18.3 V/m

Peak SAR (extrapolated) = 0.363 W/kg

**SAR(1 g) = 0.295 mW/g; SAR(10 g) = 0.226 mW/g**



0 dB = 0.300mW/g

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: VX10000; Type: Cellular/PCS CDMA Phone with Bluetooth and EvDO; Serial: A00000038A8F1E**  
**Conducted Power: 24.5 dBm**

Communication System: PCS CDMA; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: 1900 Muscle ( $\sigma = 1.57$  mho/m,  $\epsilon_r = 53.64$ ,  $\rho = 1000$  kg/m<sup>3</sup>)

Phantom section: Flat Section; Space: 2.0 cm

Test Date: 08-06-2007; Ambient Temp: 23.6°C; Tissue Temp: 21.5°C

Probe: EX3DV4 - SN3561; ConvF(6.47, 6.47, 6.47); Calibrated: 11/23/2006

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn649; Calibrated: 1/23/2007

Phantom: SAM Sub; Type: SAM 4.0; Serial: TP-1357

Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

**Mode: PCS CDMA, Body SAR, Back side, Mid.ch, Standard Battery**


**Area Scan (7x11x1):** Measurement grid: dx=15mm, dy=15mm

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 8.94 V/m

Peak SAR (extrapolated) = 0.999 W/kg

**SAR(1 g) = 0.606 mW/g; SAR(10 g) = 0.355 mW/g**



0 dB = 0.700mW/g

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: VX10000; Type: Cellular/PCS CDMA Phone with Bluetooth and EvDO; Serial: A00000038A8F1E**  
**Conducted Power: 24.5 dBm**

Communication System: PCS CDMA; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: 1900 Muscle ( $\sigma = 1.57$  mho/m,  $\epsilon_r = 53.64$ ,  $\rho = 1000$  kg/m<sup>3</sup>)

Phantom section: Flat Section; Space: 2.0 cm

Test Date: 08-06-2007; Ambient Temp: 23.6°C; Tissue Temp: 21.5°C

Probe: EX3DV4 - SN3561; ConvF(6.47, 6.47, 6.47); Calibrated: 11/23/2006

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn649; Calibrated: 1/23/2007

Phantom: SAM Sub; Type: SAM 4.0; Serial: TP-1357

Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

**Mode: PCS CDMA, Body SAR, Front side, Mid.ch, Standard Battery**


**Area Scan (7x11x1):** Measurement grid: dx=15mm, dy=15mm

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 6.35 V/m

Peak SAR (extrapolated) = 0.272 W/kg

**SAR(1 g) = 0.167 mW/g; SAR(10 g) = 0.104 mW/g**



0 dB = 0.200mW/g

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: VX10000; Type: Cellular/PCS CDMA Phone with Bluetooth and EvDO; Serial: A00000038A8F1E**  
**Conducted Power: 24.5 dBm**

Communication System: Cellular CDMA; Frequency: 836.52 MHz; Duty Cycle: 1:1

Medium: 835 Brain ( $\sigma = 0.91$  mho/m,  $\epsilon_r = 42.43$ ,  $\rho = 1000$  kg/m<sup>3</sup>)

Phantom section: Right Section

Test Date: 08-07-2007; Ambient Temp: 23.8°C; Tissue Temp: 21.5°C

Probe: EX3DV4 - SN3561; ConvF(7.94, 7.94, 7.94); Calibrated: 11/23/2006

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn649; Calibrated: 1/23/2007

Phantom: SAM Main; Type: SAM 4.0; Serial: TP-1114

Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

**Mode: Cellular CDMA, Right Head, Touch, Mid.ch, Standard Battery**


**Area Scan (7x11x1):** Measurement grid: dx=15mm, dy=15mm

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 21.6 V/m

Peak SAR (extrapolated) = 0.559 W/kg

**SAR(1 g) = 0.427 mW/g; SAR(10 g) = 0.320 mW/g**



# PCTEST ENGINEERING LABORATORY, INC.

**DUT: VX10000; Type: Cellular/PCS CDMA Phone with Bluetooth and EvDO; Serial: A00000038A8F1E**  
**Conducted Power: 24.5 dBm**

Communication System: PCS CDMA; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: 1900 Brain ( $\sigma = 1.39$  mho/m,  $\epsilon_r = 41.53$ ,  $\rho = 1000$  kg/m<sup>3</sup>)

Phantom section: Left Section

Test Date: 08-07-2007; Ambient Temp: 23.7°C; Tissue Temp: 21.4°C

Probe: EX3DV4 - SN3561; ConvF(6.99, 6.99, 6.99); Calibrated: 11/23/2006

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn649; Calibrated: 1/23/2007

Phantom: SAM Sub; Type: SAM 4.0; Serial: TP-1357

Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

**Mode: PCS CDMA, Left Head, Tilt, Mid.ch, Standard Battery**


**Area Scan (7x11x1):** Measurement grid: dx=15mm, dy=15mm

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 23.2 V/m

Peak SAR (extrapolated) = 1.38 W/kg

**SAR(1 g) = 0.765 mW/g; SAR(10 g) = 0.414 mW/g**



# PCTEST ENGINEERING LABORATORY, INC.

**DUT: VX10000; Type: Cellular/PCS CDMA Phone with Bluetooth and EvDO; Serial: A00000038A8F1E**  
**Conducted Power: 24.5 dBm**

Communication System: Cellular CDMA; Frequency: 824.7 MHz; Duty Cycle: 1:1

Medium: 835 Muscle ( $\sigma = 0.98$  mho/m,  $\epsilon_r = 54.03$ ,  $\rho = 1000$  kg/m<sup>3</sup>)

Phantom section: Flat Section; Space: 2.0 cm

Test Date: 08-06-2007; Ambient Temp: 23.4°C; Tissue Temp: 21.7°C

Probe: EX3DV4 - SN3561; ConvF(7.92, 7.92, 7.92); Calibrated: 11/23/2006

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn649; Calibrated: 1/23/2007

Phantom: SAM Main; Type: SAM 4.0; Serial: TP-1114

Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

**Mode: Cellular CDMA, Body SAR, Back side, Low.ch, Standard Battery**


**Area Scan (7x11x1):** Measurement grid: dx=15mm, dy=15mm

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 30.7 V/m

Peak SAR (extrapolated) = 1.15 W/kg

**SAR(1 g) = 0.893 mW/g; SAR(10 g) = 0.662 mW/g**



# PCTEST ENGINEERING LABORATORY, INC.

**DUT: VX10000; Type: Cellular/PCS CDMA Phone with Bluetooth and EvDO; Serial: A00000038A8F1E**  
**Conducted Power: 24.5 dBm**

Communication System: PCS CDMA; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: 1900 Muscle ( $\sigma = 1.57$  mho/m,  $\epsilon_r = 53.64$ ,  $\rho = 1000$  kg/m<sup>3</sup>)

Phantom section: Flat Section; Space: 2.0 cm

Test Date: 08-06-2007; Ambient Temp: 23.6°C; Tissue Temp: 21.5°C

Probe: EX3DV4 - SN3561; ConvF(6.47, 6.47, 6.47); Calibrated: 11/23/2006

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn649; Calibrated: 1/23/2007

Phantom: SAM Sub; Type: SAM 4.0; Serial: TP-1357

Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

**Mode: PCS CDMA, Body SAR, Back side, Mid.ch, Standard Battery**


**Area Scan (7x11x1):** Measurement grid: dx=15mm, dy=15mm

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 8.94 V/m

Peak SAR (extrapolated) = 0.999 W/kg

**SAR(1 g) = 0.606 mW/g; SAR(10 g) = 0.355 mW/g**



## **APPENDIX B: DIPOLE VALIDATION**

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: D835V2 - SN4d047; Type: 835MHz SAR Validation Dipole ; Serial: 4d047**

Communication System: CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium: 835 Brain ( $\sigma = 0.91$  mho/m,  $\epsilon_r = 42.43$ ,  $\rho = 1000$  kg/m<sup>3</sup>)

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 08-06-2007; Ambient Temp: 23.7°C; Tissue Temp: 21.6°C

Probe: EX3DV4 - SN3561; ConvF(7.94, 7.94, 7.94); Calibrated: 11/23/2006

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn649; Calibrated: 1/23/2007

Phantom: SAM Main; Type: SAM 4.0; Serial: TP-1114

Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

## 835MHz Dipole Validation


**Area Scan (7x13x1):** Measurement grid: dx=15mm, dy=15mm

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Input Power = 24.0 dBm (250 mW)

**SAR(1 g) = 2.31 mW/g; SAR(10 g) = 1.53 mW/g**

Target SAR(1g) = 2.29 mW/g; Deviation = +0.87 %



0 dB = 2.40mW/g

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: D835V2 - SN4d047; Type: 835MHz SAR Validation Dipole ; Serial: 4d047**

Communication System: CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium: 835 Brain ( $\sigma = 0.91$  mho/m,  $\epsilon_r = 42.43$ ,  $\rho = 1000$  kg/m<sup>3</sup>)

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 08-07-2007; Ambient Temp: 23.8°C; Tissue Temp: 21.5°C

Probe: EX3DV4 - SN3561; ConvF(7.94, 7.94, 7.94); Calibrated: 11/23/2006

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn649; Calibrated: 1/23/2007

Phantom: SAM Main; Type: SAM 4.0; Serial: TP-1114

Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

## 835MHz Dipole Validation


**Area Scan (7x13x1):** Measurement grid: dx=15mm, dy=15mm

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Input Power = 24.0 dBm (250 mW)

**SAR(1 g) = 2.43 mW/g; SAR(10 g) = 1.6 mW/g**

Target SAR(1g) = 2.29 mW/g; Deviation = +6.11 %



0 dB = 2.50mW/g

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: D1900V2 - SN5d080; Type: 1900MHz SAR Validation Dipole; Serial: 5d080**

Communication System: CW; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: 1900 Brain ( $\sigma = 1.39$  mho/m,  $\epsilon_r = 41.53$ ,  $\rho = 1000$  kg/m<sup>3</sup>)

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 08-06-2007; Ambient Temp: 23.8°C; Tissue Temp: 21.8°C

Probe: EX3DV4 - SN3561; ConvF(6.99, 6.99, 6.99); Calibrated: 11/23/2006

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn649; Calibrated: 1/23/2007

Phantom: SAM Sub; Type: SAM 4.0; Serial: TP-1357

Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

## 1900MHz Dipole Validation


**Area Scan (5x7x1):** Measurement grid: dx=15mm, dy=15mm

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Input Power = 20.0 dBm (100 mW)

**SAR(1 g) = 3.73 mW/g; SAR(10 g) = 1.92 mW/g**

Target SAR(1g) = 3.77 mW/g; Deviation = -1.06 %



0 dB = 3.80mW/g

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: D1900V2 - SN5d080; Type: 1900MHz SAR Validation Dipole; Serial: 5d080**

Communication System: CW; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: 1900 Brain ( $\sigma = 1.39$  mho/m,  $\epsilon_r = 41.53$ ,  $\rho = 1000$  kg/m<sup>3</sup>)

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 08-07-2007; Ambient Temp: 23.7°C; Tissue Temp: 21.4°C

Probe: EX3DV4 - SN3561; ConvF(6.99, 6.99, 6.99); Calibrated: 11/23/2006

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn649; Calibrated: 1/23/2007

Phantom: SAM Sub; Type: SAM 4.0; Serial: TP-1357

Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

## 1900MHz Dipole Validation


**Area Scan (5x7x1):** Measurement grid: dx=15mm, dy=15mm

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Input Power = 20.0 dBm (100 mW)

**SAR(1 g) = 3.63 mW/g; SAR(10 g) = 1.86 mW/g**

Target SAR(1g) = 3.77 mW/g; Deviation = -3.71 %



0 dB = 3.70mW/g

## **APPENDIX C: PROBE CALIBRATION**



Accredited by the Swiss Federal Office of Metrology and Accreditation  
 The Swiss Accreditation Service is one of the signatories to the EA  
 Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 108**

Client **PC Test**

Certificate No: **EX3-3561\_Nov06**

## CALIBRATION CERTIFICATE

Object **EX3DV4 - SN:3561**

Calibration procedure(s) **QA CAL-01.v5 and QA CAL-14.v3  
 Calibration procedure for dosimetric E-field probes**

Calibration date: **November 23, 2006**

Condition of the calibrated item **In Tolerance**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).  
 The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature  $(22 \pm 3)^{\circ}\text{C}$  and humidity  $< 70\%$ .

Calibration Equipment used (M&TE critical for calibration)

| Primary Standards          | ID #            | Cal Date (Calibrated by, Certificate No.) | Scheduled Calibration |
|----------------------------|-----------------|-------------------------------------------|-----------------------|
| Power meter E4419B         | GB41293874      | 5-Apr-06 (METAS, No. 251-00557)           | Apr-07                |
| Power sensor E4412A        | MY41495277      | 5-Apr-06 (METAS, No. 251-00557)           | Apr-07                |
| Power sensor E4412A        | MY41498087      | 5-Apr-06 (METAS, No. 251-00557)           | Apr-07                |
| Reference 3 dB Attenuator  | SN: S5054 (3c)  | 10-Aug-06 (METAS, No. 217-00592)          | Aug-07                |
| Reference 20 dB Attenuator | SN: S5086 (20b) | 4-Apr-06 (METAS, No. 251-00558)           | Apr-07                |
| Reference 30 dB Attenuator | SN: S5129 (30b) | 10-Aug-06 (METAS, No. 217-00593)          | Aug-07                |
| Reference Probe ES3DV2     | SN: 3013        | 2-Jan-06 (SPEAG, No. ES3-3013_Jan06)      | Jan-07                |
| DAE4                       | SN: 654         | 21-Jun-06 (SPEAG, No. DAE4-654_Jun06)     | Jun-07                |

| Secondary Standards       | ID #         | Check Date (in house)                    | Scheduled Check        |
|---------------------------|--------------|------------------------------------------|------------------------|
| RF generator HP 8648C     | US3642U01700 | 4-Aug-99 (SPEAG, in house check Nov-05)  | In house check: Nov-07 |
| Network Analyzer HP 8753E | US37390585   | 18-Oct-01 (SPEAG, in house check Oct-06) | In house check: Oct-07 |

|                |               |                   |           |
|----------------|---------------|-------------------|-----------|
|                | Name          | Function          | Signature |
| Calibrated by: | Katja Pokovic | Technical Manager |           |
| Approved by:   | Niels Kuster  | Quality Manager   |           |

Issued: November 23, 2006

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.



Accredited by the Swiss Federal Office of Metrology and Accreditation  
 The Swiss Accreditation Service is one of the signatories to the EA  
 Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 108**

### Glossary:

|                          |                                                                                                                                                      |
|--------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------|
| TSL                      | tissue simulating liquid                                                                                                                             |
| NORM <sub>x,y,z</sub>    | sensitivity in free space                                                                                                                            |
| ConF                     | sensitivity in TSL / NORM <sub>x,y,z</sub>                                                                                                           |
| DCP                      | diode compression point                                                                                                                              |
| Polarization $\phi$      | $\phi$ rotation around probe axis                                                                                                                    |
| Polarization $\vartheta$ | $\vartheta$ rotation around an axis that is in the plane normal to probe axis (at measurement center), i.e., $\vartheta = 0$ is normal to probe axis |

### Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2003, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", December 2003
- CENELEC EN 50361, "Basic standard for the measurement of Specific Absorption Rate related to human exposure to electromagnetic fields from mobile phones (300 MHz - 3 GHz), July 2001

### Methods Applied and Interpretation of Parameters:

- NORM<sub>x,y,z</sub>**: Assessed for E-field polarization  $\vartheta = 0$  ( $f \leq 900$  MHz in TEM-cell;  $f > 1800$  MHz: R22 waveguide). NORM<sub>x,y,z</sub> are only intermediate values, i.e., the uncertainties of NORM<sub>x,y,z</sub> does not effect the E<sup>2</sup>-field uncertainty inside TSL (see below *ConvF*).
- NORM(f)<sub>x,y,z</sub>** = NORM<sub>x,y,z</sub> \* *frequency\_response* (see Frequency Response Chart). This linearization is implemented in DASY4 software versions later than 4.2. The uncertainty of the frequency response is included in the stated uncertainty of *ConvF*.
- DCP<sub>x,y,z</sub>**: DCP are numerical linearization parameters assessed based on the data of power sweep (no uncertainty required). DCP does not depend on frequency nor media.
- ConvF and Boundary Effect Parameters**: Assessed in flat phantom using E-field (or Temperature Transfer Standard for  $f \leq 800$  MHz) and inside waveguide using analytical field distributions based on power measurements for  $f > 800$  MHz. The same setups are used for assessment of the parameters applied for boundary compensation (alpha, depth) of which typical uncertainty values are given. These parameters are used in DASY4 software to improve probe accuracy close to the boundary. The sensitivity in TSL corresponds to NORM<sub>x,y,z</sub> \* *ConvF* whereby the uncertainty corresponds to that given for *ConvF*. A frequency dependent *ConvF* is used in DASY version 4.4 and higher which allows extending the validity from  $\pm 50$  MHz to  $\pm 100$  MHz.
- Spherical isotropy (3D deviation from isotropy)**: in a field of low gradients realized using a flat phantom exposed by a patch antenna.
- Sensor Offset**: The sensor offset corresponds to the offset of virtual measurement center from the probe tip (on probe axis). No tolerance required.

# Probe EX3DV4

## SN:3561

|                  |                   |
|------------------|-------------------|
| Manufactured:    | February 14, 2005 |
| Last calibrated: | August 24, 2005   |
| Recalibrated:    | November 23, 2006 |

Calibrated for DASY Systems

(Note: non-compatible with DASY2 system!)

## DASY - Parameters of Probe: EX3DV4 SN:3561

### Sensitivity in Free Space<sup>A</sup>

|       |                      |                                     |
|-------|----------------------|-------------------------------------|
| NormX | <b>0.450</b> ± 10.1% | $\mu\text{V}/(\text{V}/\text{m})^2$ |
| NormY | <b>0.490</b> ± 10.1% | $\mu\text{V}/(\text{V}/\text{m})^2$ |
| NormZ | <b>0.420</b> ± 10.1% | $\mu\text{V}/(\text{V}/\text{m})^2$ |

### Diode Compression<sup>B</sup>

|       |              |
|-------|--------------|
| DCP X | <b>87</b> mV |
| DCP Y | <b>91</b> mV |
| DCP Z | <b>89</b> mV |

### Sensitivity in Tissue Simulating Liquid (Conversion Factors)

Please see Page 8.

### Boundary Effect

**TSL                      900 MHz      Typical SAR gradient: 5 % per mm**

|                                           |                              |               |               |
|-------------------------------------------|------------------------------|---------------|---------------|
| Sensor Center to Phantom Surface Distance |                              | <b>2.0 mm</b> | <b>3.0 mm</b> |
| SAR <sub>be</sub> [%]                     | Without Correction Algorithm | 3.8           | 1.5           |
| SAR <sub>be</sub> [%]                     | With Correction Algorithm    | 0.0           | 0.0           |

**TSL                      1810 MHz      Typical SAR gradient: 10 % per mm**

|                                           |                              |               |               |
|-------------------------------------------|------------------------------|---------------|---------------|
| Sensor Center to Phantom Surface Distance |                              | <b>2.0 mm</b> | <b>3.0 mm</b> |
| SAR <sub>be</sub> [%]                     | Without Correction Algorithm | 4.7           | 2.8           |
| SAR <sub>be</sub> [%]                     | With Correction Algorithm    | 1.1           | 0.8           |

### Sensor Offset

Probe Tip to Sensor Center                      **1.0 mm**


**The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor k=2, which for a normal distribution corresponds to a coverage probability of approximately 95%.**

<sup>A</sup> The uncertainties of NormX,Y,Z do not affect the E<sup>2</sup>-field uncertainty inside TSL (see Page 8).




<sup>B</sup> Numerical linearization parameter: uncertainty not required.

## Frequency Response of E-Field


(TEM-Cell:ifi110 EXX, Waveguide: R22)



Uncertainty of Frequency Response of E-field:  $\pm 6.3\%$  ( $k=2$ )



Receiving Pattern ( $\phi$ ),  $\vartheta = 0^\circ$ Uncertainty of Axial Isotropy Assessment:  $\pm 0.5\%$  ( $k=2$ )

# Dynamic Range $f(\text{SAR}_{\text{head}})$ (Waveguide R22, $f = 1800 \text{ MHz}$ )



Uncertainty of Linearity Assessment:  $\pm 0.6\%$  ( $k=2$ )

## Conversion Factor Assessment




| f [MHz] | Validity [MHz] <sup>c</sup> | TSL  | Permittivity | Conductivity | Alpha | Depth | ConvF Uncertainty  |
|---------|-----------------------------|------|--------------|--------------|-------|-------|--------------------|
| 900     | ± 50 / ± 100                | Head | 41.5 ± 5%    | 0.97 ± 5%    | 0.35  | 1.30  | 7.94 ± 11.0% (k=2) |
| 1810    | ± 50 / ± 100                | Head | 40.0 ± 5%    | 1.40 ± 5%    | 0.19  | 1.20  | 6.99 ± 11.0% (k=2) |
| 2450    | ± 50 / ± 100                | Head | 39.2 ± 5%    | 1.80 ± 5%    | 0.44  | 1.00  | 6.32 ± 11.8% (k=2) |
| 5200    | ± 50 / ± 100                | Head | 36.0 ± 5%    | 4.66 ± 5%    | 0.45  | 1.36  | 4.34 ± 13.1% (k=2) |
| 5300    | ± 50 / ± 100                | Head | 35.9 ± 5%    | 4.76 ± 5%    | 0.45  | 1.40  | 4.23 ± 13.1% (k=2) |
| 5800    | ± 50 / ± 100                | Head | 35.3 ± 5%    | 5.27 ± 5%    | 0.45  | 1.42  | 4.01 ± 13.1% (k=2) |
| 900     | ± 50 / ± 100                | Body | 55.0 ± 5%    | 1.05 ± 5%    | 0.40  | 1.25  | 7.92 ± 11.0% (k=2) |
| 1810    | ± 50 / ± 100                | Body | 53.3 ± 5%    | 1.52 ± 5%    | 0.21  | 1.20  | 6.47 ± 11.0% (k=2) |
| 2450    | ± 50 / ± 100                | Body | 52.7 ± 5%    | 1.95 ± 5%    | 0.47  | 1.00  | 6.33 ± 11.8% (k=2) |
| 5200    | ± 50 / ± 100                | Body | 49.0 ± 5%    | 5.30 ± 5%    | 0.40  | 1.50  | 3.89 ± 13.1% (k=2) |
| 5300    | ± 50 / ± 100                | Body | 48.5 ± 5%    | 5.42 ± 5%    | 0.45  | 1.50  | 3.63 ± 13.1% (k=2) |
| 5800    | ± 50 / ± 100                | Body | 48.2 ± 5%    | 6.00 ± 5%    | 0.45  | 1.70  | 3.59 ± 13.1% (k=2) |

<sup>c</sup> The validity of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2). The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band.

## Deviation from Isotropy in HSL

Error ( $\phi$ ,  $\theta$ ),  $f = 900$  MHz



Uncertainty of Spherical Isotropy Assessment:  $\pm 2.6\%$  ( $k=2$ )