



FCC TEST REPORT

According to

47 CFR, Part 2, Part 15 and CISPR PUB. 22

Applicant	: LG Electronics USA
Address	: 1000 Sylvan Avenue Englewood Cliffs New Jersey United States
Manufacturer	: LG Electronics Nanjing Display Co., Ltd.
Address	: No.346,Yaoxin Road Economic & Technical Development Zone Nanjing China
Equipment	: LCD Monitor
Model No.	: W2243SEV
FCC ID	: BEJW2243SEV
Trade Name	: LG

- The test result refers exclusively to the test presented test model / sample.
- Without written approval of **Cerpass Technology Corp.** the test report shall not be reproduced except in full.
- The test report must not be used by the clients to claim product certification approval by **NVLAP** or any agency of the Government.



Table of Contents

1. Summary of Test Procedure and Test Result	5
2. Test Configuration of Equipment under Test.....	6
2.1. Feature of Equipment under Test	6
2.2. Test Manner.....	6
2.3. Description of Test System	7
2.4. Connection Diagram of Test System	7
2.5. General Information of Test	8
2.6. Measurement Uncertainty	9
3. Test of Conducted Emission	10
3.1. Test Limit	10
3.2. Test Procedures.....	10
3.3. Typical test Setup	11
3.4. Measurement equipment.....	11
3.5. Test Result and Data	12
4. Test of Radiated Emission	14
4.1. Test Limit	14
4.2. Test Procedures.....	15
4.3. Typical test Setup	16
4.4. Measurement equipment.....	17
4.5. Test Result and Data	18

[illegible]



FCC TEST REPORT

According to

47 CFR, Part 2, Part 15 and CISPR PUB. 22

Applicant	: LG Electronics USA
Address	: 1000 Sylvan Avenue Englewood Cliffs New Jersey United States
Manufacturer	: LG Electronics Nanjing Display Co., Ltd.
Address	: No.346,Yaoxin Road Economic & Technical Development Zone Nanjing China
Equipment	: LCD Monitor
Model No.	: W2243SEV
FCC ID	: BEJW2243SEV
Trade Name	: LG

I HEREBY CERTIFY THAT :

The measurements shown in this test report were made in accordance with the procedures given in **ANSI C63.4 – 2003** and the energy emitted by this equipment was **passed** **CISPR PUB. 22 and FCC Part 15** in both radiated and conducted emission class B limits. Testing was carried out on *May. 20, 2009* at **Cerpass Technology Corp.**

Documented By:

Approved By:

Released By:

Cathy Chen/ Administration

John Wang/ Technical director

Alex Chiu/ Supervisor



1. Summary of Test Procedure and Test Result

Test Item	Normative References	Test Result
Conducted Emission	ANSI C63.4-2003 FCC Part 15 Subpart B	Pass
Radiated Emission	ANSI C63.4-2003 FCC Part 15 Subpart B	Pass



2. Test Configuration of Equipment under Test

2.1. Feature of Equipment under Test

LCD Monitor	Model No :	W2243SEV
	Serial No :	N/A
VGA Cable	Shielded, 1.8m, with two ferrite cores bonded	
VGA Cable	Shielded, 1.8m	
Power Supply	Non-Shielded, 1.8m	
Note : The VGA cable is alternative on selling.		

2.2. Test Manner


Test Software	
a	During testing, the interface cables and equipment positions were varied according to ANSI C63.4.
b	The complete test system included the PC, Printer, USB Keyboard, USB Mouse and EUT for EMI test.
c	During the test, Setup up the EUT and all system, turn on the power of all Equipment, run the test software "H", make the EUT at the test mode and it is normal operation, and then test.
The pre-test modes	
	Test Mode 1: Full system by VGA mode(1920*1080@60Hz)
	Test Mode 2: Full system by VGA mode(1024*768@60Hz)
	Test Mode 3: Full system by VGA mode(640*480@60Hz)
Select the worst case of the pre-test modes as the final test mode	
	Test Mode 1: Full system by VGA mode(1920*1080@60Hz)



2.3. Description of Test System

Device	Manufacturer	Model No.	Description
PC	DELL	DCTA	N/A
Printer	Epson	EX3	N/A
USB Keyboard	DELL	SK-8115	shielded, with one ferrite core bonded, 2.1m
USB Mouse	Logitech	831912-0000	shielded, 1.8m

2.4. Connection Diagram of Test System



No	Cable	Quantity	Description
A	VGA Cable	1	Shielded, 1.8m
B	Parallel Cable	1	Shielded, 1.8m
C	USB Cable	1	Shielded, 2.1m with one ferrite core bonded
D	USB Cable	1	Shielded, 1.8m



2.5. General Information of Test

Test Site :	Cerpass Technology Corp.	
Performed Location	No.66, Tangzhuang Road, Suzhou Industrial Park, Jiangsu, China	
NVLAP LAB Code :	200814-0	
FCC Registration Number :	632249 (Taipei)	916572 (SuZhou)
IC Registration Number :	6597A-1 (Taipei)	7290A-1 (SuZhou)
VCCI Registration Number :	T-338 for Telecommunication Test (Taipei) C-2188 for Conducted emission test (Taipei) R-1902 for Radiated emission test (Taipei)	
	T-343 for Telecommunication Test (Suzhou) C-2919 for Conducted emission test (Suzhou) R-2670 for Radiated emission test (Suzhou)	
Test Voltage:	AC 120V/ 60Hz	
Test in Compliance with:	ANSI C63.4-2003 FCC Part 15 Subpart B	
Frequency Range Investigated :	Conducted: from 150kHz to 30 MHz Radiation: from 30 MHz to 1,000 MHz Radiation: from 1GHz to 18GHz	
Test Distance :	The test distance of radiated emission below 1GHz from antenna to EUT is 3 M. The test distance of radiated emission above 1GHz from antenna to EUT is 3 M.	

Laboratory accreditation





2.6. Measurement Uncertainty

Conducted Emission	
The measurement uncertainty is evaluated as ± 2.24 dB.	
Radiated Emission	
(30MHz -1000MHz) The measurement uncertainty is evaluated as ± 2.98 dB.	
(1G-18GHz)	The measurement uncertainty is evaluated as ± 2.15 dB.



3. Test of Conducted Emission

3.1. Test Limit

Conducted Emissions were measured from 150 kHz to 30 MHz with a bandwidth of 9 KHz on the 120 VAC power and return leads of the EUT according to the methods defined in ANSI C63.4-2003 Section 3.1. The EUT was placed on a nonmetallic stand in a shielded room 0.8 meters above the ground plane as shown in section 2.2. The interface cables and equipment positioning were varied within limits of reasonable applications to determine the position produced maximum conducted emissions.


Frequency (MHz)	Quasi Peak (dB μ V)	Average (dB μ V)
0.15 – 0.5	66-56*	56-46*
0.5 – 5.0	56	46
5.0 – 30.0	60	50

3.2. Test Procedures

- The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
- Connect EUT to the power mains through a line impedance stabilization network (LISN).
- All the support units are connecting to the other LISN.
- The LISN provides 50 ohm coupling impedance for the measuring instrument.
- The FCC states that a 50 ohm, 50 micro-Henry LISN should be used.
- Both sides of AC line were checked for maximum conducted interference.
- The frequency range from 150 kHz to 30 MHz was searched.
- Set the test-receiver system to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.



3.3. Typical test Setup




3.4. Measurement equipment

Instrument	Manufacturer	Model No.	Serial No.	Calibration Data
EMC Emission Tester	EMCPARTNER	Harmonics-1000	159	2008.06.30
Test Receiver	R&S	ESCI	100565	2008.06.30
AMN	R&S	ESH2-Z5	100182	2008.06.30
Two-Line V-Network	R&S	ENV216	100325	2008.06.30
ISN	FCC	FCC-TLISN-T2-02	20379	2008.06.30
ISN	FCC	FCC-TLISN-T4-02	20380	2008.06.30
ISN	FCC	FCC-TLISN-T8-02	20381	2008.06.30
Current Probe	R&S	EZ-17	100303	2008.06.30
Passive Voltage Probe	R&S	ESH2-Z3	100026	2008.06.30
Decoupling Clamp	LUTHI	FTC 40 X 15 E	5685	2008.11.01
Absorbing Clamp	Schwarzbeck	MDS21	3753	2008.11.01
Minimum Loss Pad	Agilent	11852B	61650	2008.06.30
Temperature/ Humidity Meter	Zhicheng	ZC1-11	CEP-TH-004	2008.09.24



3.5. Test Result and Data

Standard	:	FCC_Part 15B_Class B_2007	Date/Time	:	2009/05/18
Model	:	W2243SEV	Serial	:	N/A
Operator	:	DAFEI	AC Power	:	AC120V/60Hz
Temp	:	20'	Humidity	:	50%
Remark	:	Mode 1: Full system by VGA mode(1920*1080@60Hz)			





Final Data List

Frequency MHz	Line Phase	Reading dB(uV) QP	Reading dB(uV) AV	Factor dB	Level dB(uV) QP	Level dB(uV) AV	Limit dB(uV) QP	Limit dB(uV) AV	Margin dB QP	Margin dB AV	Pass/Fail
0.19336	N	34.4	28.3	10.1	44.5	38.4	63.9	53.9	19.4	15.5	Pass
0.26126	N	27.3	21.3	10.1	37.4	31.4	61.4	51.4	24.0	20.0	Pass
0.55294	N	16.4	10.2	10.1	26.5	20.3	56.0	46.0	29.5	25.7	Pass
2.80324	N	15.3	12.5	10.2	25.5	22.7	56.0	46.0	30.5	23.3	Pass
6.9669	N	23.0	15.8	10.5	33.5	26.3	60.0	50.0	26.5	23.7	Pass
23.9994	N	36.7	35.4	11.0	47.7	46.4	60.0	50.0	12.3	3.6	Pass
0.19394	L1	34.3	26.7	10.1	44.4	36.8	63.9	53.9	19.5	17.1	Pass
0.3668	L1	18.8	16.9	10.1	28.9	27.0	58.6	48.6	29.7	21.6	Pass
0.59659	L1	17.8	17.3	10.0	27.8	27.3	56.0	46.0	28.2	18.7	Pass
1.19304	L1	19.0	19.2	10.0	29.0	29.2	56.0	46.0	27.0	16.8	Pass
18.2954	L1	27.0	14.7	11.1	38.1	25.8	60.0	50.0	21.9	24.2	Pass
24.0002	L1	36.1	35.3	11.2	47.3	46.5	60.0	50.0	12.7	3.5	Pass

Note: Measurement Level = Reading Level + Correct Factor

Test engineer: dafer



4. Test of Radiated Emission

4.1. Test Limit

Radiated emissions from 30 MHz to 1,000 MHz were measured with a bandwidth of 120 kHz according to the methods defines in ANSI C63.4-2003. The EUT was placed on a nonmetallic stand in the open-field site, 0.8 meter above the ground plane, as shown in section 3.2. The interface cables and equipment positions were varied within limits of reasonable applications to determine the positions producing maximum radiated emissions.

For unintentional device, according to § 15.109(a), except for Class A digital devices, the field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values:

Frequency (MHz)	Distance (m)	Level (dBuV/m)	Level (dBuV/m)
30 - 88	3	40(QP)	N/A
88 - 216	3	43(QP)	N/A
216-960	3	46(QP)	N/A
960-1000	3	54(QP)	N/A
1000-18000	3	74(PK)	54(AV)
18000-40000	1	84(PK)	64(AV)

For unintentional device, according to CISPR PUB.22, for Class B digital devices, the general requirement of field strength of radiated emissions from intentional radiators at a distance of 10 meters shall not exceed the below table.

Frequency (MHz)	Distance Meters	Radiated (dB μ V/ M)
30-230	10	30
230-1000	10	37




4.2. Test Procedures

- a. The EUT was placed on a Rota table top 0.8 meter above ground.
- b. The EUT and its simulators are placed on the ground. The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT was positioned such that the distance from antenna to the EUT was 3 meters or 1 meter.
- c. The antenna can move up and down between 1 meter and 4 meters to find out the maximum emission level.
- d. Both horizontal and vertical polarization of the antenna are set on measurement. In order to find the maximum emission, all of the interface cables must be manipulated on radiated measurement.
- e. Radiated emissions were investigated over the frequency range from 30MHz to 1GHz using a receiver bandwidth of 120KHz and the frequency range from 1GHz to 18GHz using a receiver bandwidth of 1MHz. Radiated was performed at an antenna to EUT distance of 3 meters .




4.3. Typical test Setup

Below 1GHz Test Setup



Above 1GHz Test Setup



**4.4. Measurement equipment**


Instrument	Model No.	Manufacturer	Serial No.	Calibration Date
EMI Test Receiver	R&S	ESCI	100564	2008.06.30
Preamplifier	Agilent	87405B	My39500554	2008.11.04
Preamplifier	R&S	PR-AMP26	1248791	2008.06.30
Ultra Broadband Antenna	R&S	HL562	100362	2008.11.04
Broad-Band Horn Antenna	Schwarzbeck	BBHA9120D	9120D-619	2008.09.26
Spectrum Analyzer	R&S	FSP40	100324	2008.09.28
Temperature/ Humidity Meter	Zhicheng	ZC1-11	CEP-TH-001	2008.09.24



4.5. Test Result and Data

Under 1G:

Site : EMC Lab AC 102	Time : 2009/05/20 - 10:36
Limit : FCC_CLASS_B_03M_QP	Margin : 6
EUT : LCD Monitor	Probe : HL562(30-1000MHz) - HORIZONTAL
Power : AV120V/60HZ	Note : Mode 1: Full system by VGA mode(1920*1080@60Hz)




		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBuV)	Measure Level (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Detector Type	Ant Pos (cm)	Table Pos (deg)
1		69.850	-17.476	51.600	33.124	-6.876	40.000	QUASIPeAK	200.000	152.000
2		110.900	-14.000	46.700	32.700	-10.800	43.500	QUASIPeAK	100.000	24.000
3		164.500	-15.402	55.400	39.998	-3.502	43.500	QUASIPeAK	152.000	96.000
4		216.800	-14.440	53.100	38.660	-7.340	46.000	QUASIPeAK	200.000	125.000
5		486.970	-5.115	45.690	40.575	-5.425	46.000	QUASIPeAK	200.000	325.000
6		733.200	0.000	41.550	41.550	-4.450	46.000	QUASIPeAK	200.000	310.000

Note:

1. All Readings below 1GHz are Quasi-Peak, above are performed with peak and/or average measurements as necessary.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor



Site : EMC Lab AC 102	Time : 2009/05/20 - 10:37
Limit : FCC_CLASS_B_03M_QP	Margin : 6
EUT : LCD Monitor	Probe : HL562(30-1000MHz) - VERTICAL
Power : AV120V/60HZ	Note : Mode 1: Full system by VGA mode(1920*1080@60Hz)



		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBuV)	Measure Level (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Detector Type	Ant Pos (cm)	Table Pos (deg)
1		32.450	-6.468	44.300	37.832	-2.168	40.000	QUASIPeAK	100.000	54.000
2		45.140	-13.381	51.917	37.536	-2.464	40.000	QUASIPeAK	100.000	42.000
3		83.400	-15.293	51.700	37.406	-2.594	40.000	QUASIPeAK	100.000	64.000
4		108.450	-14.128	53.000	38.872	-4.628	43.500	QUASIPeAK	100.000	210.000
5		216.440	-14.462	54.900	40.438	-5.562	46.000	QUASIPeAK	120.000	62.000
6	*	433.600	-6.728	50.100	43.371	-2.629	46.000	QUASIPeAK	100.000	122.000
7		32.450	-6.468	44.300	37.832	-2.168	40.000	QUASIPeAK	100.000	54.000


Note:

1. All Readings below 1GHz are Quasi-Peak, above are performed with peak and/or average measurements as necessary.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor



Above 1G:

Site : EMC Lab AC 102	Time : 2009/05/20 - 12:38
Limit : FCC 15_03M_PK	Margin : 6
EUT : LCD Monitor	Probe : BBHA9120D(1-18GHz) - HORIZONTAL
Power : AC120V/60Hz	Note : Mode 1: Full system by VGA mode(1920*1080@60Hz)




		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBuV)	Measure Level (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Detector Type	Ant Pos (cm)	Table Pos (deg)
1		1220.000	-11.999	56.800	44.801	-29.199	74.000	PEAK	100.00	220.00
2		1534.000	-11.390	56.800	45.410	-28.590	74.000	PEAK	150.00	120.00
3	*	2680.000	-5.862	51.300	45.438	-28.562	74.000	PEAK	100.00	0.00

Note:

1. All Readings below 1GHz are Quasi-Peak, above are performed with peak and/or average measurements as necessary.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor



Site : EMC Lab AC 102	Time : 2009/05/20 - 12:38
Limit : FCC_15_03M_AV	Margin : 6
EUT : LCD Monitor	Probe : BBHA9120D(1-18GHz) - HORIZONTAL
Power : AC120V/60Hz	Note : Mode 1: Full system by VGA mode(1920*1080@60Hz)




		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBuV)	Measure Level (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Detector Type	Ant Pos (cm)	Table Pos (deg)
1		1220.000	-11.999	53.600	41.601	-12.399	54.000	AVERAGE	100.00	220.00
2		1534.000	-11.390	50.600	39.210	-14.790	54.000	AVERAGE	150.00	120.00
3	*	2680.000	-5.862	47.490	41.628	-12.372	54.000	AVERAGE	100.00	0.00

Note:

1. All Readings below 1GHz are Quasi-Peak, above are performed with peak and/or average measurements as necessary.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor



Site : EMC Lab AC 102	Time : 2009/05/20 - 12:42
Limit : FCC_15_03M_PK	Margin : 6
EUT : LCD Monitor	Probe : BBHA9120D(1-18GHz) - VERTICAL
Power : AC120V/60Hz	Note : Mode 1: Full system by VGA mode(1920*1080@60Hz)




		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBuV)	Measure Level (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Detector Type	Ant Pos (cm)	Table Pos (deg)
1		1305.300	-11.184	55.400	44.216	-29.784	74.000	PEAK	100.00	220.00
2		1453.000	-11.606	55.900	44.294	-29.706	74.000	PEAK	150.00	120.00
3	*	2687.000	-5.850	55.700	49.850	-24.150	74.000	PEAK	100.00	0.00

Note:

1. All Readings below 1GHz are Quasi-Peak, above are performed with peak and/or average measurements as necessary.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor



Site : EMC Lab AC 102	Time : 2009/05/20 - 12:42
Limit : FCC_15_03M_AV	Margin : 6
EUT : LCD Monitor	Probe : BBHA9120D(1-18GHz) - VERTICAL
Power : AC120V/60Hz	Note : Mode 1: Full system by VGA mode(1920*1080@60Hz)



		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBuV)	Measure Level (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Detector Type	Ant Pos (cm)	Table Pos (deg)
1		1305.300	-11.184	51.200	40.016	-13.984	54.000	AVERAGE	100.00	220.00
2		1453.000	-11.606	50.400	38.794	-15.206	54.000	AVERAGE	150.00	120.00
3	*	2687.000	-5.850	49.800	43.950	-10.050	54.000	AVERAGE	100.00	0.00

Note:

1. All Readings below 1GHz are Quasi-Peak, above are performed with peak and/or average measurements as necessary.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor

Fred Guo

Test engineer:_____