



PCTEST ENGINEERING LABORATORY, INC.

6660-B Dobbin Road, Columbia, MD 21045 USA
Tel. 410.290.6652 / Fax 410.290.6554
<http://www.pctestlab.com>



RF EXPOSURE EVALUATION Maximum Permissible Exposure (MPE)

Applicant Name:

LG Electronics Inc.
222 LG-ro
Jinwi-myeon, Pyeongtaek-si
Gyeonggi-do, 17709, Korea

Date of Testing:

6/29-7/7/2017

Test Site/Location:

PCTEST Lab, Columbia, MD, USA

Test Report Serial No.:

1M1706220210-02-R1.BEJ

FCC ID: BEJWC910FC

APPLICANT: LG Electronics Inc.

EUT Type: Vehicle Installed Wireless Charging System

FCC Rule Part(s): FCC Part 1 (§1.1310) and Part 2 (§2.1091)

FCC Classifications: Part 15 Low Power Transmitter Below 1705 kHz (DCD)

Test Procedure: KDB 680106 D01 v02

The device bearing the FCC Identifier specified above has been shown to comply with the applicable technical standards as indicated in the measurement report and has been tested in accordance with the measurement procedures specified in KDB 680106 D01 v02. These measurements were performed with no deviation from the standards. Test results reported herein relate only to the item(s) tested.

This revised Test Report (S/N: 1M1706220210-02-R1.BEJ) supersedes and replaces the previously issued test report (S/N: 1M1706220210-02.BEJ) on the same subject device for the same type of testing as indicated. Please discard or destroy the previously issued test report(s) and dispose of it accordingly.

I authorize and attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.


Randy Ortanez
President



FCC ID: BEJWC910FC		 MAXIMUM PERMISSIBLE EXPOSURE (MPE) DATA REPORT			Reviewed by: Quality Manager
Test Report S/N: 1M1706220210-02-R1.BEJ	Test Dates: 6/29-7/7/2017	EUT Type: Vehicle Installed Wireless Charging System		Page 1 of 8	

T A B L E O F C O N T E N T S

1.0	RF EXPOSURE EVALUATION – MAXIMUM PERMISSIBLE EXPOSURE (MPE).....	3
1.1	Introduction.....	3
1.2	EUT Description.....	3
1.3	MPE Requirements Overview.....	4
1.4	Test Equipment	5
1.5	Test Setup	5
1.6	Mobile Condition MPE	6
2.0	CONCLUSION.....	8

FCC ID: BEJWC910FC		MAXIMUM PERMISSIBLE EXPOSURE (MPE) DATA REPORT		Reviewed by: Quality Manager
Test Report S/N: 1M1706220210-02-R1.BEJ	Test Dates: 6/29-7/7/2017	EUT Type: Vehicle Installed Wireless Charging System		Page 2 of 8

1.0 RF EXPOSURE EVALUATION – MAXIMUM PERMISSIBLE EXPOSURE (MPE)

1.1 Introduction

This document is prepared on behalf of LG Electronics Inc. to show compliance with the RF Exposure requirements as required in §1.1310 of the FCC Rules and Regulations in the mobile two operating condition of the EUT. MPE testing was performed to demonstrate compliance with the MPE limits for the mobile use condition.

The limit for Maximum Permissible Exposure (MPE), specified in FCC §1.1310, is listed in Table 1-1. According to FCC §1.1310: the criteria listed in the following table shall be used to evaluate the environmental impact of human exposure to radio-frequency (RF) radiation as specified in §1.1307(b).

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (Minutes)
(A) Limits For Occupational / Control Exposures (f = frequency)				
0.3-3.0	614	1.63	*(100)	6
3.0-30	1842/f	4.89/f	*(900/f ²)	6
30-300	61.4	0.163	1.0	6
300-1500	...	...	f/300	6
1500-100,000	...	...	5.0	6
(B) Limits For General Population / Uncontrolled Exposure (f = frequency)				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	...	...	f/1500	30
1500-100,000	...	...	1.0	30

Table 1-1. Limits for Maximum Permissible Exposure (MPE)

Per the guidance of KDB 680106, the E-field and H-field limits shown in the table above are extended down to 100kHz.

1.2 EUT Description

The EUT consists of the LGE Vehicle Installed Wireless Charger System used with three dummy loads that are representative of the PMA and WPC wireless charging protocols. Wireless power transfer is initiated when one of the loads is placed on the charger system. Output power of the charging pad is 5W and 15W in WPC mode and 5W in PMA mode.

FCC ID: BEJWC910FC		MAXIMUM PERMISSIBLE EXPOSURE (MPE) DATA REPORT		Reviewed by: Quality Manager
Test Report S/N: 1M1706220210-02-R1.BEJ	Test Dates: 6/29-7/7/2017	EUT Type: Vehicle Installed Wireless Charging System	Page 3 of 8	

1.3 MPE Requirements Overview

Three different categories of transmitters are defined by the FCC in KDB 680106 D01 v02. These categories are fixed installation, mobile, and portable and are defined as follows:

- o **Fixed Installations:** fixed location means that the device, including its antenna, is physically secured at a permanent location and is not able to be easily moved to another location. Additionally, distance to humans from the antenna is maintained to at least 2 meters.
- o **Mobile Devices:** a mobile device is defined as a transmitting device designed to be used in other than fixed locations and to be generally used in such a way that a separation distance of at least 20 centimeters is normally maintained between the transmitter's radiating structures and the body of the user or nearby persons. Transmitters designed to be used by consumers or workers that can be easily re-located, such as a wireless modem operating in a laptop computer, are considered mobile devices if they meet the 20 centimeter separation requirement. The FCC rules for evaluating mobile devices for RF compliance are found in 47 CFR §2.1091.
- o **Portable Devices:** a portable device is defined as a transmitting device designed to be used so that the radiating structure(s) of the device is/are within 20 centimeters of the body of the user. Portable device requirements are found in Section 2.1093 of the FCC's Rules (47 CFR §2.1093).

The FCC also categorizes the use of the device as based upon the user's awareness and ability to exercise control over his or her exposure. The two categories defined are Occupational/ Controlled Exposure and General Population/Uncontrolled Exposure. These two categories are defined as follows:

- o **Occupational/Controlled Exposure:** In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. This exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means. Awareness of the potential for RF exposure in a workplace or similar environment can be provided through specific training as part of a RF safety program. If appropriate, warning signs and labels can also be used to establish such awareness by providing prominent information on the risk of potential exposure and instructions on methods to minimize such exposure risks.
- o **General Population/Uncontrolled Exposure:** The general population / uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity. Warning labels placed on low-power consumer devices such as cellular telephones are not considered sufficient to allow the device to be considered under the occupational/controlled category, and the general population/uncontrolled exposure limits apply to these devices.

The **LGE Vehicle Installed Wireless Charging System FCC ID: BEJWC910FC** is evaluated to the "General Population/Uncontrolled Exposure" limits for Mobile exposure condition as described in Section 1.1 above.

FCC ID: BEJWC910FC		MAXIMUM PERMISSIBLE EXPOSURE (MPE) DATA REPORT		Reviewed by: Quality Manager
Test Report S/N: 1M1706220210-02-R1.BEJ	Test Dates: 6/29-7/7/2017	EUT Type: Vehicle Installed Wireless Charging System		Page 4 of 8

1.4 Test Equipment

Test equipment calibration is traceable to the National Institute of Standards and Technology (NIST).

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
Narda	EHP-200AC	Electronic & Magnetic Field Probe	5/31/2016	Annual	7/31/2017	170WX60209

Table 1-2. Test Equipment List

1.5 Test Setup

Maximum E-field and H-field measurements were made on each of five sides of the EUT that could come in contact with a user. The five sides are defined as follows: Top (A), Left (B), Bottom (C), Right (D), and Front (E). Refer to the test position diagram below.

Mobile Condition

Probe	Condition	Test Distance (cm)
E-field	Mobile	Variable
H-field	Mobile	Variable




Figure 1. Test Positions and Probe Distance

FCC ID: BEJWC910FC	PCTEST ENGINEERING LABORATORY, INC.	MAXIMUM PERMISSIBLE EXPOSURE (MPE) DATA REPORT	LG	Reviewed by: Quality Manager
Test Report S/N: 1M1706220210-02-R1.BEJ	Test Dates: 6/29-7/7/2017	EUT Type: Vehicle Installed Wireless Charging System		Page 5 of 8

1.6 Mobile Condition MPE

The procedure used to determine the RF power density for the mobile condition was based upon E-field and H-field measurements recorded using a calibrated probe. All measurements were recorded with the EUT (the charging system) transferring power to the Rx dummy loads that support the PMA and WPC charging protocols. The pad itself was running off of a 12VDC power supply.

The field strength of the E field and H-field was measured at an EUT-to-probe-measurement-axis distance as shown in Section 1.5 using the equipment listed in Section 1.4.

Care was exercised to ensure that the charging system was transferring power to the dummy loads throughout the duration of the field strength measurements. The field strength data in the tables below are shown for each of the dummy loads (PMA and WPC).

During testing, the charging system with the PMA and WPC dummy loads was placed on a non-conductive (composite plastic) table top. The probe was positioned at the location where there is maximum field strength on each side of the EUT. The maximum E-field and H-field is reported below for each configuration.

E Measurements (V/m)	Distance from probe (cm)						Limit (V/m)
	0	2	4	6	8	10	
A (Bottom)	24.980	10.765	5.067	2.605	1.954	1.554	614.00
B (Right)	60.776	17.201	7.522	4.633	3.224	2.416	614.00
C (Top)	21.047	9.208	5.859	3.792	2.494	1.696	614.00
D (Left)	49.378	11.858	5.081	3.467	2.325	1.703	614.00
E (Front)	57.127	24.093	12.829	7.625	5.055	3.119	614.00

Table 1-3. E-field Measurements for Decremental Test Distances (5W WPC)

E Measurements (V/m)	Distance from probe (cm)						Limit (V/m)
	0	2	4	6	8	10	
A (Bottom)	3.927	2.306	1.546	1.022	0.806	0.548	614.00
B (Right)	38.042	10.840	4.753	2.441	1.463	1.019	614.00
C (Top)	5.458	2.790	1.715	0.919	0.671	0.513	614.00
D (Left)	45.085	11.067	4.510	2.081	1.258	0.743	614.00
E (Front)	5.187	2.148	1.474	1.225	0.910	0.675	614.00

Table 1-4. E-field Measurements for Decremental Test Distances (5W PMA)

E Measurements (V/m)	Distance from probe (cm)						Limit (V/m)
	0	2	4	6	8	10	
A (Bottom)	4.987	2.294	1.901	1.581	1.292	1.076	614.00
B (Right)	51.450	12.587	5.054	3.051	2.097	1.563	614.00
C (Top)	4.311	2.940	2.345	1.823	1.380	1.013	614.00
D (Left)	45.487	11.541	5.356	2.826	1.950	1.250	614.00
E (Front)	41.950	16.942	8.998	5.062	3.434	2.270	614.00

Table 1-5. E-field Measurements for Decremental Test Distances (15W WPC)

FCC ID: BEJWC910FC		MAXIMUM PERMISSIBLE EXPOSURE (MPE) DATA REPORT		Reviewed by: Quality Manager
Test Report S/N: 1M1706220210-02-R1.BEJ	Test Dates: 6/29-7/7/2017	EUT Type: Vehicle Installed Wireless Charging System		Page 6 of 8

H Measurements (A/m)	Distance from probe (cm)						Limit (A/m)
	0	2	4	6	8	10	
A (Bottom)	5.235	3.228	2.350	1.422	1.065	0.930	1.63
B (Right)	6.863	4.179	2.929	2.240	1.724	1.453	1.63
C (Top)	4.087	2.690	2.009	1.604	1.293	1.021	1.63
D (Left)	5.989	3.425	2.306	1.504	1.159	0.808	1.63
E (Front)	6.814	5.085	2.963	2.229	1.419	1.074	1.63

Table 1-6. H-field Measurements for Decremental Test Distances (5W WPC)

H Measurements (A/m)	Distance from probe (cm)						Limit (A/m)
	0	2	4	6	8	10	
A (Bottom)	1.737	1.056	0.755	0.565	0.440	0.377	1.63
B (Right)	3.558	1.723	1.072	0.662	0.709	0.520	1.63
C (Top)	1.647	0.777	0.588	0.514	0.409	0.394	1.63
D (Left)	3.816	1.581	0.931	0.730	0.417	0.402	1.63
E (Front)	1.051	0.596	0.513	0.480	0.411	0.393	1.63

Table 1-7. H-field Measurements for Decremental Test Distances (5W PMA)

H Measurements (A/m)	Distance from probe (cm)						Limit (A/m)
	0	2	4	6	8	10	
A (Bottom)	3.067	2.363	1.641	1.230	1.080	0.880	1.63
B (Right)	5.523	3.763	2.626	1.986	1.648	1.252	1.63
C (Top)	3.962	3.046	2.131	1.605	1.354	1.011	1.63
D (Left)	4.533	3.020	1.962	1.358	1.186	0.794	1.63
E (Front)	5.920	3.705	2.546	1.738	1.218	0.954	1.63

Table 1-8. H-field Measurements for Decremental Test Distances (15W WPC)

FCC ID: BEJWC910FC		MAXIMUM PERMISSIBLE EXPOSURE (MPE) DATA REPORT		Reviewed by: Quality Manager
Test Report S/N: 1M1706220210-02-R1.BEJ	Test Dates: 6/29-7/7/2017	EUT Type: Vehicle Installed Wireless Charging System	Page 7 of 8	

2.0 CONCLUSION

The E-field and H-field data shown in this report show that the Vehicle Installed Wireless Charger System is compliant with the MPE limits for both the PMA and WPC charging dummy loads at variable distances from 0cm up to and including 10cm.

FCC ID: BEJWC910FC		MAXIMUM PERMISSIBLE EXPOSURE (MPE) DATA REPORT		Reviewed by: Quality Manager
Test Report S/N: 1M1706220210-02-R1.BEJ	Test Dates: 6/29-7/7/2017	EUT Type: Vehicle Installed Wireless Charging System		Page 8 of 8