

9.7		APPROVED MEDIA (TBD)
A4	:	TOSHIBA Copier Paper (European paper) XL Paper 3R91720 XL Recycle Paper (3R91165, 3R94565: TBC) XEROX Transparency (3R96023, 3R96002, 3R96000, 3R91334)
Letter	:	XEROX 4024, 20lb. (3R721) Hammer Mill TIDAL DP, 20 lb. XEROX Recycle Paper 3R5130 Transparency, (TBD)
Legal	:	XEROX 4024, 20lb. (3R727) Hammer Mill TIDAL DP, 20 lb. XEROX Recycle Paper 3R5132

9.8 RECORDING DENSITY
Solid image density should meet the following in all recording areas.

Density Variation :	not greater than 0.3 OD
Minimum Density :	not less than 1.0 OD

Note:
Test Method
Measure darkness of each black solid block (20mm x 20mm , 0.787inches x 0.787 inches) using Macbeth Density Meter.

Test Condition:
The recording paper must be wrapped well just before testing. Recording shall be done at 15 to 25°C, 40 to 70% RH. environment.

9.9 RECORDED PAPER STACK
Recorded paper stack shall stack 150 sheets of A4 / Letter / Legal paper, face-up with collated (by memory). Letter and Legal size of Hammer Mill TIDAL DP,20lb or XEROX 4024,20lb at the standard condition (15 to 25°C, 40 to 70% RH).

9.10 RECORDED PAPER REMOVAL
It shall be possible to remove papers from the printer in the event of power failure or ASF malfunction.