

## Display Information

|                                |                                                                       |
|--------------------------------|-----------------------------------------------------------------------|
| LCD Module                     | 15-in, active matrix TFT, anti-glare coating, 0.297 mm pixel pitch    |
| Display Size                   | 304.1 mm x 228.1 mm                                                   |
| Viewing Angle                  |                                                                       |
| Left/Right                     | -60° / 60°                                                            |
| Up/Down                        | -55° / 45°                                                            |
| Display Colors                 | 262144                                                                |
| Power Input                    | 100 ~ 240 V <sub>AC</sub> Full Range, 50/60 Hz (External AC adapter)  |
| Power consumption              | Operation Mode : 30W max<br>Off Mode : 2W max                         |
| Signal Input                   |                                                                       |
| Video Signal                   | RGB positive 0.7V <sub>pp</sub> , 75ohm                               |
| Sync signals                   | Separate & Composite, TTL Level                                       |
| Line (horizontal)<br>frequency | 31.5 kHz ~ 60 kHz                                                     |
| Raster (vertical)<br>frequency | 56 Hz ~ 75 Hz                                                         |
| Pixel dot clock                | 80 MHz (maximum)                                                      |
| Recommended mode               | 1024 x 768 @ 60 Hz                                                    |
| Pedestal tilt                  | 20° forward, -5°backward                                              |
| Dimensions<br>(W x H x D)      | 341mm x 317mm x 140mm<br>341mm x 338mm x 68mm (pedestal fold)         |
| Net Weight                     | 3.0 kg                                                                |
| Gross Weight                   | 4.5 kg                                                                |
| Operating Conditions           |                                                                       |
| Temperature                    | 5° ~ 40°C at altitude 0 ~ 2000m<br>5° ~ 30°C at altitude 2000 ~ 3000m |
| Humidity                       | 20% ~ 85% RH, non-condensing                                          |
| Altitude                       | 3000m Max.                                                            |
| Storage Conditions             |                                                                       |
| Temperature                    | -20° ~ 60°C                                                           |
| Humidity                       | 5% ~ 95% RH                                                           |
| Altitude                       | 10000m Max.                                                           |

## Video Modes

Your LCD monitor supports the following industry-standard combinations of screen resolution and refresh rates. Other combinations are possible, but may require adjustments to the image.