

MPE Calculation : Bluetooth

Mode	Frequency range (MHz)			Max Target Power (dBm)	ANT Gain (dBi)	Maximum EIRP (dBm)	Maximum EIRP (mW)	Maximum power density (mW/cm ²)	Requirement (mW/cm ²)
Bluetooth(1Mbps)	2402.00	~	2480.00	1.00	3.25	4.25	2.661	0.0006	1.000
Bluetooth(2,3Mbps)	2402.00	~	2480.00	-4.00	3.25	-0.75	0.842	0.0002	1.000
		~							
		~							
		~							
		~							
		~							
		~							

Note: Please refer to the operation description for Max tune-up power.

The EUT will only be used with a separation of 20 centimeters or greater between the antenna and the body of the user.

The MPE sample calculation for this exposure is shown below.

$$\begin{aligned}
 S &= \text{EIRP} / (4 R^2 \pi) \\
 &= 2.661 / (4 \times 20^2 \times \pi) \\
 &= 0.0006 \text{ mW/cm}^2
 \end{aligned}$$

- Note

S= Maximum power density(mW/cm²)

EIRP= Equivalent Isotropic Radiated Power(mW)

R= Distance to the center of the radiation of the antenna

▪ Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)			Electric Field strength (V/m)	Magnetic field strength (A/m)	Power Density (mW/cm ²)	Averageing time (minutes)
0.3	~	1.34	614	1.63	*100	30
1.34	~	30	824/f	2.19 / f	*180 / f ²	30
30	~	300	27.5	0.073	0.2	30
300	~	1,500			f / 1500	30
1,500	~	100,000			1.0	30

Conclusion : The exposure condition of this device is compliant with FCC

MPE Calculation : WLAN

Mode(Worst case)	Frequency range (MHz)			Max Target Power (dBm)	ANT Gain (dBi)	Maximum EIRP (dBm)	Maximum EIRP (mW)	Maximum power density (mW/cm ²)	Requirment (mW/cm ²)
802.11g	2412.00	~	2462.00	8.50	3.23	11.73	14.894	0.0030	1.000
802.11a	5180.00	~	5240.00	9.00	5.49	14.49	28.120	0.0056	1.000
802.11a	5745.00	~	5825.00	9.00	5.49	14.49	28.120	0.0056	1.000
		~							
		~							
		~							
		~							

Note: Please refer to the operation description for Max tune-up power.

The EUT will only be used with a separation of 20 centimeters or greater between the antenna and the body of the user.

The MPE sample calculation for this exposure is shown below.

$$\begin{aligned}
 S &= \text{EIRP} / (4 R^2 \pi) \\
 &= 28.120 / (4 \times 20^2 \times \pi) \\
 &= 0.0056 \text{ mW/cm}^2
 \end{aligned}$$

- Note

S= Maximum power density(mW/cm²)

EIRP= Equivalent Isotropic Radiated Power(mW)

R= Distance to the center of the radiation of the antenn

▪ Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)			Electric Field strength (V/m)	Magnetic field strength (A/m)	Power Density (mW/cm ²)	Averageing time (minutes)
0.3	~	1.34	614	1.63	*100	30
1.34	~	30	824/f	2.19 / f	*180 / f ²	30
30	~	300	27.5	0.073	0.2	30
300	~	1,500			f / 1500	30
1,500	~	100,000			1.0	30

Conclusion : The exposure condition of this device is compliant with FCC

RF Exposure Compliance for simultaneous operations

- Worst case for simultaneous operations
- BT + WLAN(5GHz)

RF function or mode(Worst case)	BT	WLAN 5GHz	-	-	-	-	-	Σ of MPE ratios
Band(Worst case)	2.4GHz	NII-3	-	-	-	-	-	
Power Density (mW/cm2)	0.0006	0.0056					-	
Requirement (mW/cm2)	1.0000	1.0000					-	
MPE ratio (Power Density/Requirement)	0.0006	0.0056					-	
Worst case(MPE ratio)	0.0006	0.0056						0.0062

- Requirement = Σ of MPE ratios ≤ 1

Conclusion : The exposure condition of this device is compliant with FCC rules.