

MPE Calculation

Regulation(s): Part 1.1310, Part 2.1091

Method: KDB447498 D01v06

RF feature(Mode)	Frequency range (MHz)			Max Target Power (dBm)	ANT Gain (dBi)	Maximum EIRP (dBm)	Maximum EIRP (mW)	Maximum power density (mW/cm ²)	Requirement (mW/cm ²)
Bluetooth(1 Mbps)	2 402.00	~	2 480.00	-2.00	4.49	2.49	1.775	0.000 4	1.000 0
Bluetooth(2, 3 Mbps)	2 402.00	~	2 480.00	-1.50	4.49	2.99	1.991	0.000 4	1.000 0
		~							
		~							
		~							
		~							
		~							
		~							

Note: Please refer to the operation description for Max tune-up power.

The EUT will only be used with a separation of 20 centimeters or greater between the antenna and the body of the user.

The MPE sample calculation for this exposure is shown below.

$$\begin{aligned}
 S &= \text{EIRP} / (4 R^2 \pi) \\
 &= 1.775 / (4 \times 20^2 \times \pi) \\
 &= 0.000 \text{ mW/cm}^2
 \end{aligned}$$

- Note

S= Maximum power density(mW/cm²)

EIRP= Equivalent Isotropic Radiated Power(mW)

R= Distance to the center of the radiation of the antenna(20cm)

Part 1.1310

▪ Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)			Electric Field strength (V/m)	Magnetic field strength (A/m)	Power Density (mW/cm ²)	Averaging time (minutes)
0.3	~	1.34	614	1.63	*100	30
1.34	~	30	824/f	2.19 / f	*180 / f ²	30
30	~	300	27.5	0.073	0.2	30
300	~	1,500			f / 1500	30
1,500	~	100,000			1.0	30

Conclusion : **The exposure condition of this device is compliant with FCC**

MPE Calculation

Regulation(s): Part 1.1310, Part 2.1091

Method: KDB447498 D01v06

RF feature(Mode)	Frequency range (MHz)			Max Target Power (dBm)	ANT Gain (dBi)	Maximum EIRP (dBm)	Maximum EIRP (mW)	Maximum power density (mW/cm ²)	Requirement (mW/cm ²)
WLAN 802.11g (SISO)	2 412.00	~	2 462.00	6.00	4.84	10.84	12.134	0.002 5	1.000 0
WLAN 802.11a (2TX)	5 180.00	~	5 240.00	11.50	5.22	16.72	46.990	0.009 4	1.000 0
WLAN 802.11a (2TX)	5 745.00	~	5 825.00	12.50	7.02	19.52	89.537	0.017 9	1.000 0
		~							
		~							
		~							
		~							
		~							

Note: Please refer to the operation description for Max tune-up power.

The EUT will only be used with a separation of 20 centimeters or greater between the antenna and the body of the user.

The MPE sample calculation for this exposure is shown below.

$$\begin{aligned}
 S &= \text{EIRP} / (4 R^2 \pi) \\
 &= 12.134 / (4 \times 20^2 \times \pi) \\
 &= 0.003 \text{ mW/cm}^2
 \end{aligned}$$

- Note

S= Maximum power density(mW/cm²)

EIRP= Equivalent Isotropic Radiated Power(mW)

R= Distance to the center of the radiation of the antenna(20cm)

Part 1.1310

▪ Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)			Electric Field strength (V/m)	Magnetic field strength (A/m)	Power Density (mW/cm ²)	Averaging time (minutes)
0.3	~	1.34	614	1.63	*100	30
1.34	~	30	824/f	2.19 / f	*180 / f ²	30
30	~	300	27.5	0.073	0.2	30
300	~	1,500			f / 1500	30
1,500	~	100,000			1.0	30

Conclusion : The exposure condition of this device is compliant with FCC

RF Exposure Compliance for simultaneous operations

- Worst case for simultaneous operations
- BT + 5GHz WLAN

RF feature	BT	WLAN	-	-	-	-	-	Σ of MPE ratios
Worst case(MPE ratio)	2.4GHz	5GHz	-	-	-	-	-	
Power Density (mW/cm2)	0.000 4	0.017 9	-	-	-	-	-	
Requirement (mW/cm2)	1.000 0	1.000 0	-	-	-	-	-	
MPE ratio (Power Density/Requirement)	0.000 4	0.017 9	-	-	-	-	-	
Worst case(MPE ratio)	0.000 4	0.017 9	-	-	-	-	-	0.018 3

- Requirement = $\Sigma \text{ of MPE ratios} \leq 1$

Conclusion : The exposure condition of this device is compliant with FCC rules.