

FCC RF EXPOSURE REPORT

DONGGUAN ALLLIKE ELECTRONIC CO.,LTD

OUTDOOR BLUETOOTH ROCK SPEAKERS

Model Number: ITSBO-358P10

FCC ID: BUQBR90P10

Prepared for : DONGGUAN ALLLIKE ELECTRONIC CO.,LTD
CHUANCHANG DEVELOPMENT DISTRICT MAYONG TOWN
DONGGUAN GUANGDONG China

Prepared By : EST Technology Co., Ltd.
Santun(guantai Road), Houjie Town, DongGuan City,
GuangDong, China.

Tel: 86-769-83081888-808

Report Number: ESTE-R1612002
Date of Test : November 02,2016~ December 01, 2016
Date of Report : December 02, 2016



Maximum Permissible Exposure

1、Applicable Standard

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2m normally can be maintained between the user and the device.

(a)、Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength E (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-10000			5	6

(b)、Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength E (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-10000			1.0	30

Note: f=frequency in MHz; *Plane-wave equivalent power density

2、MPE Calculation Method

$$E \text{ (V/m)} = (30 \cdot P \cdot G)^{0.5} / d \quad \text{Power Density: } P_d \text{ (W/m}^2\text{)} = E^2 / 377$$

E = Electric Field (V/m)

P = Peak RF output Power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$P_d = (30 \cdot P \cdot G) / (377 \cdot d^2)$$

From the peak EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained

3、Calculated Result and Limit

Model	Frequency (MHz)	Peak output power (dBm)	Peak output power (mW)	Antenna gain		Target power (dBm)	Power Density (S) (mW/cm2)	Limited of Power Density (S) (mW/cm2)	Test Result
				(dBi)	(Linear)				
GFSK	2402	-3.099	0.490	0	1	-3±1	0.000125525	1	Compiles
	2441	-4.115	0.388	0	1	-4±1	9.97078E-05	1	Compiles
	2480	-5.248	0.299	0	1	-5±1	7.92007E-05	1	Compiles
8-DPSK	2402	-3.241	0.474	0	1	-3±1	0.000125525	1	Compiles
	2441	-4.289	0.372	0	1	-4±1	9.97078E-05	1	Compiles
	2480	-5.341	0.292	0	1	-5±1	7.92007E-05	1	Compiles