



# Test Report - FCC Part 1.1310/ MPE

## Applicant: Enterprise Electronics Corporation

Approved for Release By:

Signature: Bruno Clavier

Name & Title: Bruno Clavier, General Manager

Date of Signature 12/15/2022

This test report shall not be reproduced except in full without the written and signed permission of Timco Engineering Inc. (IIA). This test report relates only to the items tested as identified and is not valid for any subsequent changes or modifications made to the equipment under test.



## Table of Contents

---

|       |                                                                |   |
|-------|----------------------------------------------------------------|---|
| 1.    | CUSTOMER INFORMATION.....                                      | 3 |
| 2.    | LOCATION OF TESTING .....                                      | 3 |
| 2.1   | TEST LABORATORY .....                                          | 3 |
| 2.2   | TESTING WAS PERFORMED, REVIEWED BY .....                       | 4 |
| 3.    | TEST SAMPLE(S) (EUT/DUT) .....                                 | 5 |
| 3.1   | DESCRIPTION OF THE EUT.....                                    | 5 |
| 4.    | TEST METHODS & APPLICABLE REGULATORY LIMITS.....               | 6 |
| 4.1   | TEST METHODS/STANDARDS/GUIDANCE: .....                         | 6 |
| 4.1.1 | <i>FCC Limits for Maximum Permissible Exposure (MPE)</i> ..... | 6 |
| 4.2   | EQUATIONS.....                                                 | 7 |
| 5.    | RF EXPOSURE RESULTS .....                                      | 8 |
| 6.    | HISTORY OF TEST REPORT CHANGES .....                           | 9 |



Timco Engineering, Inc., an IIA Company  
849 NW State Road 45, Newberry, Florida 32669  
(352) 472-5500 / [testing@timcoengr.com](mailto:testing@timcoengr.com)

## 1. Customer Information

Applicant: Enterprise Electronics Corporation.  
Address: 128 South Industrial Blvd.  
Enterprise Alabama 36330 USA

## 2. Location of Testing

### 2.1 Test Laboratory

Timco Engineering Inc. is a subsidiary of Industrial Inspection & Analysis, Inc. ("IIA"). Testing was performed at Timco's permanent laboratory located at 849 NW State Road 45, Newberry, Florida 32669

FCC test firm # 578780  
FCC Designation # US1070  
FCC site registration is under A2LA certificate # 0955.01  
ISED Canada test site registration # 2056A  
EU Notified Body # 1177  
For all designations see A2LA scope # 0955.01



Timco Engineering, Inc., an IIA Company  
849 NW State Road 45, Newberry, Florida 32669  
(352) 472-5500 / [testing@timcoengr.com](mailto:testing@timcoengr.com)

## 2.2 Testing was performed, reviewed by

Dates of Testing: 9/27/2022

Signature:

Sr. EMC Engineer  
EMC-003838-NE



Name & Title:

Tim Royer, EMC Engineer

Date of Signature

12/15/2022

Signature:

Name & Title:

Terri Allen, Lab Assistant

Date of Signature

12/15/2022



### 3. Test Sample(s) (EUT/DUT)

The test sample was received: 09/26/2022

#### 3.1 Description of the EUT

A description as well as unambiguous identification of the EUT(s) tested. Where more than one sample is required for technical reasons (such as the use of connected units for the purpose of conducted output power testing where the product units will have integral antennas), each specific test shall identify which unit was tested.

| Identification    |                   |
|-------------------|-------------------|
| FCC ID:           | BUV-DEFENDERSK850 |
| Brief Description | WEATHER RADAR     |
| Model(s) #        | DEFENDER SK850    |
| Firmware version  | 2.1.15            |
| Software version  | 2.1.15            |
| Serial Number     | #001              |

| Technical Characteristics    |                         |
|------------------------------|-------------------------|
| Technology                   | Unmodulated Pulse       |
| Frequency Range              | 2967MHz                 |
| Modulation                   | Pulse                   |
| Bandwidth & Emission Class   | PON                     |
| Antenna Connector            | WR-284 S-Band Waveguide |
| Voltage Rating (AC or Batt.) | 110V AC 3 Phase         |

| Antenna Characteristics |                 |                                 |              |
|-------------------------|-----------------|---------------------------------|--------------|
| Antenna                 | Frequency Range | Mode / BW                       | Antenna Gain |
| 1                       | 2967 MHz        | 20' prime fed parabolic antenna | 44 dBi       |



#### 4. Test methods & Applicable Regulatory Limits

##### 4.1 Test methods/Standards/Guidance:

The following guidance FCC KDB 447498 D01 General RF Exposure Guidance v06 was used for RF exposure evaluation as per FCC Part 1.1310 and FCC Part 2.1091 and part 2.1093. Full test results are available in this report.

##### 4.1.1 FCC Limits for Maximum Permissible Exposure (MPE)

| Frequency Range (MHz)                                 | Electric field strength (V/m) | Magnetic field strength (A/m) | Power density (mW/cm <sup>2</sup> ) | Averaging Time (minutes) |
|-------------------------------------------------------|-------------------------------|-------------------------------|-------------------------------------|--------------------------|
| A Limits for Occupational/Controlled Exposure         |                               |                               |                                     |                          |
| 0.3-3.0                                               | 614                           | 1.63                          | *(100)                              | ≤6                       |
| 3.0-30                                                | 1842/f                        | 4.89/f                        | *(900/f <sup>2</sup> )              | <6                       |
| 30-300                                                | 61.4                          | 0.163                         | 1.0                                 | <6                       |
| 300-1,500                                             |                               |                               | f/300                               | <6                       |
| 1,500-100,000                                         |                               |                               | 5                                   | <6                       |
| B Limits for General Population/Uncontrolled Exposure |                               |                               |                                     |                          |
| 0.3-1.34                                              | 614                           | 1.63                          | *(100)                              | <30                      |
| 1.34-30                                               | 824/f                         | 2.19/f                        | *(180/f <sup>2</sup> )              | <30                      |
| 30-300                                                | 27.5                          | 0.073                         | 0.2                                 | <30                      |
| 300-1,500                                             |                               |                               | f/1500                              | <30                      |
| 1,500-100,000                                         |                               |                               | 1.0                                 | <30                      |



## 4.2 Equations

### POWER DENSITY

$$E(V/m) = \text{SQRT} ( 30 * P * G ) / d$$

$$Pd(W/m^2) = E^2 / 377$$

$$S = \text{EIRP} / ( 4 * \text{Pi} * D^2v )$$

Where:

S = Power density, in mW/cm<sup>2</sup>

EIRP = Equivalent Isotropic Radiated Power, in mW

D = Separation distance in cm

Power density is converted from units of mW/cm<sup>2</sup> to units of W/m<sup>2</sup> by multiplying by 10.

### DISTANCE

$$D = \text{SQRT} ( \text{EIRP} / ( 4 * \text{Pi} * S ) )$$

Where:

D = Separation distance in cm

EIRP = Equivalent Isotropic Radiated Power, in mW

S = Power density in mW/cm<sup>2</sup>

**SOURCE-BASED DUTY CYCLE** (When applicable (for example, multi-slot mobile phone applications) A duty cycle factor may be applied.)

$$\text{Source-based time-average EIRP} = ( \text{DC} / 100 ) * \text{EIRP}$$

Where:

DC = Duty Cycle in % as applicable.

EIRP = Equivalent Isotropic radiated Power, in mW



Timco Engineering, Inc., an IIA Company  
849 NW State Road 45, Newberry, Florida 32669  
(352) 472-5500 / [testing@timcoengr.com](mailto:testing@timcoengr.com)

## 5. RF Exposure Results

Separation Distance: 41247.26 cm

### MPE

| Frequency Band | Evaluation Distance (cm) | Max Power + Tolerance (dBm) | Antenna Gain (dBi) | Duty Cycle (%) | EIRP (W)    | Power Density                  | Limit for Uncontrolled Exposure | Limit for Controlled Exposure | Distance Required to meet Uncontrolled Exposure Limit (cm) |
|----------------|--------------------------|-----------------------------|--------------------|----------------|-------------|--------------------------------|---------------------------------|-------------------------------|------------------------------------------------------------|
| 2967-2967 MHz  | 20                       | 103.30                      | 44.00              | 0%             | 21379620.90 | 4253340.434 mW/cm <sup>2</sup> | 1 mW/cm <sup>2</sup>            | 5 mW/cm <sup>2</sup>          | 41247.26                                                   |

RESULT: Pass at DISTANCE 41247.26 cm



Timco Engineering, Inc., an IIA Company  
849 NW State Road 45, Newberry, Florida 32669  
(352) 472-5500 / [testing@timcoengr.com](mailto:testing@timcoengr.com)

## 6. History of Test Report Changes

| Test Report #               | Revision # | Description                   | Date of Issue |
|-----------------------------|------------|-------------------------------|---------------|
| TR_4363-22_FCC 1.1310/ MPE_ | 1          | Initial release               | 10/06/2022    |
|                             | 2          | Updated Description, Page 5,8 | 12/15/2022    |
|                             |            |                               |               |



Timco Engineering, Inc., an IIA Company  
849 NW State Road 45, Newberry, Florida 32669  
(352) 472-5500 / [testing@timcoengr.com](mailto:testing@timcoengr.com)

---

END OF TEST REPORT

---