RF EXPOSURE EVALUATION

1. PRODUCT INFORMATION

Product Description	Bluetooth Headphone
Model Name	AH-GC25W
FCC ID	BV2-AH-GC25W

2. EVALUATION METHOD

According to 447498 D01 General RF Exposure Guidance v05
The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:
[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] ·[√f(GHz)] ≤ 3.0 for 1-g SAR and ≤ 7.5 for 10-g extremity SAR.
Where f(GHz) is the RF channel transmit frequency in GHz
Power and distance are rounded to the nearest mW and mm before calculation

3. CALCULATION

BLE:

P_t=4.315dBm=2.70mW

The value of the Maximum output power P_t is referred to the test report of the CFR47 §15.247.

The result for RF exposure evaluation SAR=(2.70mW /5mm) .[√2.48(GHz)]= 0.85<3.0 for 1-g SAR and ≤ 7.5 for 10-g extremity SAR.

BR&EDR:

P_t=1.123dBm=1.30mW

The value of the Maximum output power P_t is referred to the test report of the CFR47 §15.247.

The result for RF exposure evaluation SAR=(1.30mW /5mm) .[√2.44(GHz)]= 0.41<3.0 for 1-g SAR and ≤ 7.5 for 10-g extremity SAR.

4. CONCLUSION

The SAR evaluation is not required.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at http://www.agc-cert.com.