



Engineering and Testing for EMC and Safety Compliance

Certification Report

M/A-Com, Inc.
221 Jefferson Ridge Parkway
Lynchburg, VA 24501
Daryl Popowitch
Phone: (434) 455-9527
E-Mail: popowitda@tycoelectronics.com

Model: VIDA Broadband Client
4940–4990 MHz

FCC ID: BV8VMXCL
IC: 3670A-VMXCL

August 24, 2006

Standards Referenced for this Report	
Part 2: 2005	Frequency Allocations and Radio Treaty Matters; General Rules and Regulations
Part 90: 2005	Private Land Mobile Radio Services
ANSI/TIA-603-C-2004	Land Mobile FM or PM Communications Equipment Measurement and Performance Standards
ANSI/TIA/EIA – 102.CAAA; 2002	Digital C4FM/CQPSK Transceiver Measurement Methods
RSS-111 Issue 1 2006	Broadband Public Safety Equipment Operating in the Band 4940-4990 MHz

Frequency Range	Rated Peak Transmit Power (W)	Measured Frequency Tolerance (ppm)	Emission Designator
4940-4990 MHz	0.10	5.9	5M0X7D

Report Prepared by Test Engineer: Daniel Biggs

Document Number: 2006124

*This report may not be reproduced, except in full, without the written approval of Rhein Tech Laboratories, Inc.
Test results relate only to the product tested.*

360 Herndon Parkway
Suite 1400
Herndon, VA 20170
Ph: 703-689-0368 Fax: 703-689-2056

Table of Contents

1	General Information	5
1.1	Test Facility	5
1.2	Related Submittal(s)/Grant(s)	5
2	Tested System Details	6
3	FCC Rules and Regulations Part 2 §2.1033(c)(8) Voltages and Currents Through The Final Amplifying Stage	7
4	FCC Rules and Regulations Part 90 §90.1215(a) and Part 2 §2.1046(a): Peak Output Power; RSS-111 Section 4.3: Transmitter Output Power and Channel Bandwidth	8
4.1	Test Procedure	8
4.2	Test Data	9
5	FCC Rules and Regulations Part 90 §90.1215(a): Peak Power Spectral Density; RSS-111 Section 4.3: Transmitter Output Power and Channel Bandwidth	21
5.1	Test Procedure	21
5.2	Test Data	22
6	FCC Rules and Regulations Part 90 §90.210(m) and Part 2 §2.1049: Occupied Bandwidth (Emissions Masks) and Conducted Spurious Emissions; RSS-111 Section 4.4: Transmitter Unwanted Emissions	34
6.1	Test Procedure	34
6.2	Reference Level Measurements	35
6.3	In Band Spurious Test Data	35
6.4	Out of Band Spurious Test Data	39
7	FCC Rules and Regulations Part 90 §90.210(l) and Part 2 §2.1053(a): Field Strength of Spurious Radiation; RSS-111 Section 3.3: Transmitter Unwanted Emissions	42
7.1	Test Procedure	42
7.2	Test Data	43
7.2.1	CFR 47 Part 90.210 Requirements	43
8	FCC Rules and Regulation Part 90 §90.213(a) and Part 2 §2.1055: Frequency Stability; RSS-111 Section 4.2: Transmitter Frequency Stability	45
8.1	Test Procedure	45
8.2	Frequency Stability Test Data	46
8.2.1	Frequency Stability/Temperature Variation	46
8.2.2	Frequency Stability/Voltage Variation	46
9	Conclusion	47

Table of Tables

Table 2-1: Equipment Under Test (EUT).....	6
Table 2-2: Ports and Cabling (EUT)	6
Table 2-3: Support Equipment	7
Table 4-1: RF Power Output: Carrier Output Power.....	9
Table 4-2: RF Power Output (Rated Power)	9
Table 4-3: Test Equipment for Testing RF Power Output - Conducted.....	20
Table 5-1: RF Power Output: Peak Power Spectral Density	22
Table 5-2: Test Equipment for Testing Peak Power Spectral Density - Conducted	33
Table 6-1: Test Equipment for Testing Occupied Bandwidth/Conducted Spurious Emissions.....	41
Table 7-1: Field Strength of Spurious Radiation: Channel 9 – 4962.5 MHz (High Power)	43
Table 7-2: Test Equipment for Testing Field Strength of Spurious Radiation.....	44
Table 8-1: Frequency Stability/Temperature Variation – Channel 9 - 4962.5 MHz	46
Table 8-2: Frequency Stability/Voltage Variation – Channel 9 - 4962.5 MHz.....	46
Table 8-3: Test Equipment for Testing Frequency Stability.....	47

Table of Plots

Plot 4-1: Channel Power Output; Channel 3 - 4942.5 MHz	10
Plot 4-2: Channel Power Output; Channel 6 - 4947.5 MHz	11
Plot 4-3: Channel Power Output; Channel 7 - 4952.5 MHz	12
Plot 4-4: Channel Power Output; Channel 8 - 4957.5 MHz	13
Plot 4-5: Channel Power Output; Channel 9 - 4962.5 MHz	14
Plot 4-6: Channel Power Output; Channel 10 - 4967.5 MHz	15
Plot 4-7: Channel Power Output; Channel 11 - 4972.5 MHz	16
Plot 4-8: Channel Power Output; Channel 12 - 4977.5 MHz	17
Plot 4-9: Channel Power Output; Channel 13 - 4982.5 MHz	18
Plot 4-10: Channel Power Output; Channel 16 - 4987.5 MHz	19
Plot 5-1: Peak Power Spectral Density; Channel 3 - 4942.5 MHz	23
Plot 5-2: Peak Power Spectral Density; Channel 6 - 4947.5 MHz	24
Plot 5-3: Peak Power Spectral Density; Channel 7 - 4952.5 MHz	25
Plot 5-4: Peak Power Spectral Density; Channel 8 - 4957.5 MHz	26
Plot 5-5: Peak Power Spectral Density; Channel 9 - 4962.5 MHz	27
Plot 5-6: Peak Power Spectral Density; Channel 10 - 4967.5 MHz	28
Plot 5-7: Peak Power Spectral Density; Channel 11 - 4972.5 MHz	29
Plot 5-8: Peak Power Spectral Density; Channel 12 - 4977.5 MHz	30
Plot 5-9: Peak Power Spectral Density; Channel 13 - 4982.5 MHz	31
Plot 5-10: Peak Power Spectral Density; Channel 16 - 4987.5 MHz	32
Plot 6-1: Occupied Bandwidth; Channel 3 - 4942.5 MHz	35
Plot 6-2: Emissions Mask M; Channel 3 - 4942.5 MHz	36
Plot 6-3: Occupied Bandwidth; Channel 16 - 4987.5 MHz	37
Plot 6-4: Emissions Mask M; Channel 16 - 4987.5 MHz	38
Plot 6-5: Conducted Spurious Emissions; Channel 9 – 4962.5 MHz; 30 MHz – 13 GHz	39
Plot 6-6: Conducted Spurious Emissions; Channel 9 – 4962.5 MHz; 13 GHz – 50 GHz.....	40

Table of Figures

Figure 2-1: Configuration of Tested System	7
--	---

Table of Appendixes

Appendix A:	RF Exposure Compliance	48
Appendix B:	Agency Authorization Letter	49
Appendix C:	Confidentiality Request Letter	50
Appendix D:	IC Letters.....	51
Appendix E:	Label Information.....	52
Appendix F:	Operational Description.....	53
Appendix G:	Parts List	54
Appendix H:	Tune Up/Alignment Procedure	55
Appendix I:	Schematics	56
Appendix J:	Block Diagram	57
Appendix K:	Manual	58
Appendix L:	Test Configuration Photographs.....	59
Appendix M:	External Photographs.....	63
Appendix N:	Internal Photographs	70

Table of Photographs

Photograph 1:	ID Label Sample	52
Photograph 2:	ID Label Location.....	52
Photograph 3:	AC Conducted Emissions – Front View	59
Photograph 4:	AC Conducted Emissions – Rear View	60
Photograph 5:	Radiated Emissions Front View	61
Photograph 6:	Radiated Emissions Rear View	62
Photograph 7:	Top	63
Photograph 8:	Bottom	64
Photograph 9:	Sides.....	65
Photograph 10:	RF Connector	66
Photograph 11:	RF Connector	67
Photograph 12:	Hardened Version.....	68
Photograph 13:	Power and Data Connectors.....	69
Photograph 14:	Open Chassis - Hardened Version	70
Photograph 15:	Open Chassis – AC Version	71
Photograph 16:	PCB XCVR Top View	72
Photograph 17:	PCB XCVR Bottom View	73
Photograph 18:	PCB PWR&COM Top View	74
Photograph 19:	PCB PWR&COM Bottom View	75
Photograph 20:	PCB Fiber Top View	76
Photograph 21:	PCB Fiber Bottom View	77

1 General Information

The following Certification Report is prepared on behalf of **M/A-COM, Inc.** in accordance with the Federal Communications Commission. The Equipment Under Test (EUT) was the **VIDA Broadband Client; FCC ID: BV8VMXCL and IC: 3670A-VMXCL**. The test results reported in this document relate only to the item that was tested.

All measurements contained in this application were conducted in accordance with the applicable FCC Rules and Regulations in CFR 47. Calibration checks are performed regularly on the instruments, and all accessories including high pass filter, coaxial attenuator, preamplifier and cables.

1.1 Test Facility

The open area test site and conducted measurement facility used to collect the radiated data is located on the parking lot of Rhein Tech Laboratories, Inc., 360 Herndon Parkway, Suite 1400, Herndon, Virginia, 20170. This site has been fully described in a report submitted to and approved by the Federal Communications Commission to perform AC line conducted and radiated emissions testing.

1.2 Related Submittal(s)/Grant(s)

This is an original application report.

2 Tested System Details

The test sample was received on August 14, 2006. Listed below are the identifiers and descriptions of all equipment, cables, and internal devices used with the EUT for this test, as applicable. The VIDA Broadband Client implements the 802.16-2004 protocol in a 5 MHz channel, delivering an over-the-air throughput of 2–19 Mbps. The system was tested at a data rate of 6 Mb/s at a 5 MHz channel bandwidth.

The client used for testing was AC powered; there is also a version that is powered by DC voltage, to be included in this certification also. The RF portions of both versions are identical. The DC powered version, a hardened version of the AC powered version, has a fiber optic interface, and uses transient protection. The AC powered client with the Ethernet interface was used for testing to Part 90 requirements. The DC version was tested for Part 15 unintentional emissions; this data is contained in a separate DoC report and is available upon request.

Model Tested	VIDA Broadband Client
Frequency Band	4940–4990 MHz
Modulation Type	OFDM, QPSK, BPSK, 16 QAM, 64 QAM
Channel Step Size	2.5 MHz
Channel Bandwidth	5 MHz
Primary Power	9 to 30 VDC/VAC
Rated Transmitter Output Power	1uW to 0.1W (-30 dBm to +20 dBm programmable with 1 dB step)
Duty Cycle	50% maximum

Table 2-1: Equipment Under Test (EUT)

Part	Manufacturer	Model	PN/SN	FCC ID	RTL Bar Code
Client (AC powered)	M/A-Com, Inc.	VIDA Broadband Client	MAVM-VMCLL	BV8VMXCL	17503
Client (DC powered)	M/A-Com, Inc.	VIDA Broadband Client	MAVM-VMCLH	BV8VMXCL	17504
Antenna (26 dBi gain)	MTI	Linear Vertical	MT-466003	N/A	17334


Table 2-2: Ports and Cabling (EUT)

Port	Cable Type	Quantity	Length (feet)	Shield
AC/DC Power Port	3-pin industrial Conxall	1	6	No
RJ-45 Ethernet Port	RJ-45	1	6	No
Remote Antenna Mount Port	N type female	1	N/A	Yes
Service Port	RJ-45	1	N/A	No

Table 2-3: Support Equipment

Part	Manufacturer	Model	PN/SN	FCC ID	RTL Bar Code
Notebook Computer	IBM	Thinkpad	N/A	N/A	N/A
RJ-45 Cable	N/A	N/A	N/A	N/A	N/A

Figure 2-1: Configuration of Tested System



3 FCC Rules and Regulations Part 2 §2.1033(c)(8) Voltages and Currents Through The Final Amplifying Stage

Nominal DC Voltage: 6.5 VDC
Current: 0.8 AMPS

4 FCC Rules and Regulations Part 90 §90.1215(a) and Part 2 §2.1046(a): Peak Output Power; RSS-111 Section 4.3: Transmitter Output Power and Channel Bandwidth

§90.1215: The transmitting power of stations operating in the 4940-4990 MHz band must not exceed the maximum limits in this section.

(a) The peak transmit power should not exceed:

Channel Bandwidth (MHz)	Low Power Device Peak Transmitter Power (dBm)	High Power Device Peak Transmitter Power (dBm)
1.....	7.0	20.0
5.....	14.0	27.0
10.....	17.0	30.0
15.....	18.8	31.8
20.....	20.0	33.0

High power devices are also limited to a peak power spectral density of 21 dBm per 1 MHz. High power devices using channel bandwidths other than those listed above permitted; however, they are limited to a peak power spectral density of 21 dBm MHz. If the transmitting antennas of directional gain greater than 9dBi are used, both the peak transmit power and the peak power spectral density should be reduced by the amount in decibels that the directional gain of the antenna exceeds 9 dBi. However, high power point-to-point or point-to-multipoint operation (both fixed and temporary-fixed rapid deployment) may employ transmitting antennas with a directional gain up to 26 dBi without any corresponding reduction in the transmitter power or the spectral density. Corresponding reduction in the peak transmit power and peak power spectral density should be the amount in decibels that the directional gain of the antenna exceeds 26 dBi.

4.1 Test Procedure

TIA-603-C Section 2.2.1

The EUT transmitter output was connected through an appropriate 50 ohm attenuator to a spectrum analyzer. The resolution bandwidth was set to a value greater than the signal bandwidth. The video bandwidth was set to a value greater than the resolution bandwidth (preferred value is video bandwidth at least three times greater than the resolution bandwidth). The peak transmit power was measured as a conducted emission over the interval of continuous transmission in terms of an RMS equivalent voltage. Peak power was taken with trace in max hold and no averaging.

Combined 10dB and 20 dB attenuators were used between the EUT and the spectrum analyzer for all power measurements. No cable was used between EUT and analyzer.

The system loss was measured by using a signal generator and reference cable. The attenuation was first measured with a reference cable, then measured in combination with the attenuators.

Loss (reference cable/attenuators) – Loss (reference cable) = Attenuator loss

31.3 dB – 0.8 dB = 30.5 dB total system loss (relative offset entered into analyzer)

4.2 Test Data

The EUT complies with 47CFR 2.1046 and 90.1215(a). The EUT does not exceed 27 dBm at carrier frequency.

Table 4-1: RF Power Output: Carrier Output Power


Channel	Frequency (MHz)	Peak Power (dBm)	Limit (dBm)
3	4942.5	19.66	27
6	4947.5	19.99	27
7	4952.5	19.92	27
8	4957.5	19.87	27
9	4962.5	19.80	27
10	4967.5	19.82	27
11	4972.5	19.69	27
12	4977.5	19.68	27
13	4982.5	19.58	27
16	4987.5	19.54	27

*Measurement accuracy: +/- .3 dB


Table 4-2: RF Power Output (Rated Power)

Rated Power
0.1 W


Plot 4-1: Channel Power Output; Channel 3 - 4942.5 MHz




Plot 4-2: Channel Power Output; Channel 6 - 4947.5 MHz




Plot 4-3: Channel Power Output; Channel 7 - 4952.5 MHz




Plot 4-4: Channel Power Output; Channel 8 - 4957.5 MHz




Plot 4-5: Channel Power Output; Channel 9 - 4962.5 MHz




Plot 4-6: Channel Power Output; Channel 10 - 4967.5 MHz




Plot 4-7: Channel Power Output; Channel 11 - 4972.5 MHz



Plot 4-8: Channel Power Output; Channel 12 - 4977.5 MHz



Plot 4-9: Channel Power Output; Channel 13 - 4982.5 MHz



Plot 4-10: Channel Power Output; Channel 16 - 4987.5 MHz





Table 4-3: Test Equipment for Testing RF Power Output - Conducted

RTL Asset #	Manufacturer	Model	Part Type	Serial Number	Calibration Due
901413	Agilent	E4448	Spectrum Analyzer	US44020346	11/2/07
901138	MCE Weinschel	48-20-34	Attenuator, 20 dB, DC-18 GHz, 100 W	BK5859	12/9/08
900948	MCE Weinschel	47-10-43	Attenuator, 10 dB, DC-18 GHz, 50 W	BH1487	12/2/08

Test Personnel:

Daniel Biggs		August 14, 2006
Test Engineer	Signature	Date Of Tests

5 FCC Rules and Regulations Part 90 §90.1215(a): Peak Power Spectral Density; RSS-111 Section 4.3: Transmitter Output Power and Channel Bandwidth

(a) High power devices are also limited to a peak power spectral density of 21 dBm per 1 MHz. High power devices using channel bandwidths other than those listed above permitted; however, they are limited to a peak power spectral density of 21 dBm MHz. If the transmitting antennas of directional gain greater than 9 dBi are used, both the peak transmit power and the peak power spectral density should be reduced by the amount in decibels that the directional gain of the antenna exceeds 9 dBi. However, high power point-to-point or point-to-multipoint operation (both fixed and temporary-fixed rapid deployment) may employ transmitting antennas with a directional gain up to 26 dBi without any corresponding reduction in the transmitter power or the spectral density. Corresponding reduction in the peak transmit power and peak power spectral density should be the amount in decibels that the directional gain of the antenna exceeds 26 dBi.

(b) The peak power spectral density is measured as a conducted emission by direct connection of a calibrated test instrument to the equipment under test. If the device cannot be connected directly, alternative techniques acceptable to the Commission may be used. Measurements are made over a bandwidth of 1 MHz or the 26 dB emission bandwidth of the device, whichever is less. A resolution bandwidth less than the measurement bandwidth can be used, provided that the measured power is integrated to show total power over the measurement bandwidth. If the resolution bandwidth is approximately equal to the measurement bandwidth, and much less than the emission bandwidth of the equipment under test, the measured results shall be corrected for any difference between the resolution bandwidth of the test instrument and its actual noise bandwidth.

Limit determined by antenna gain:

<u>Antenna Gain (dBi)</u>	<u>Limit (dBm)</u>
----------------------------------	---------------------------

Up to 26 dBi	21
--------------	----

5.1 Test Procedure

The EUT transmitter output was connected through the appropriate 50 ohm attenuator to a spectrum analyzer. Resolution bandwidth was set to 1 MHz and video bandwidth was set to a value greater than the resolution bandwidth (8 MHz). Peak search was used to find peak spectral density within 5 MHz signal bandwidth.

Combined 10dB and 20 dB attenuators were used between the EUT and the spectrum analyzer for all PSD measurements. No cable was used between the EUT and the analyzer.

Path loss was calculated as follows below (checked across the frequency band of interest).

The system loss was measured by using a signal generator and reference cable. The attenuation was first measured with a reference cable, then measured in combination with the attenuators.

Loss (reference cable/attenuators) – Loss (reference cable) = Attenuator loss

31.9 dB – 0.9 dB = 31.0 dB total system loss (relative offset entered into analyzer)

5.2 Test Data


EUT complies with 47CFR 2.1046 and 90.1215(a). EUT does not exceed 21 dBm at carrier frequency.

Table 5-1: RF Power Output: Peak Power Spectral Density

Channel	Frequency (MHz)	Channel BW (MHz)	Measured Peak Power Spectral Density (dBm per one MHz)	Limit (dBm per one MHz)
3	4942.5	5	13.14	21
6	4947.5	5	12.19	21
7	4952.5	5	11.92	21
8	4957.5	5	14.73	21
9	4962.5	5	14.82	21
10	4967.5	5	12.35	21
11	4972.5	5	12.36	21
12	4977.5	5	12.26	21
13	4982.5	5	11.76	21
16	4987.5	5	11.77	21

* Measurement accuracy: +/- .3 dB


Plot 5-1: Peak Power Spectral Density; Channel 3 - 4942.5 MHz



Result: Peak power spectral density = 13.14 dBm per one MHz


Note: PPSD is circled red in plot and is indicated by peak marker.

Plot 5-2: Peak Power Spectral Density; Channel 6 - 4947.5 MHz




Result: Peak power spectral density = 12.19 dBm per one MHz

Plot 5-3: Peak Power Spectral Density; Channel 7 - 4952.5 MHz




Result: Peak power spectral density = 11.92 dBm per one MHz

Plot 5-4: Peak Power Spectral Density; Channel 8 - 4957.5 MHz




Result: Peak power spectral density = 14.73 dBm per one MHz

Plot 5-5: Peak Power Spectral Density; Channel 9 - 4962.5 MHz




Result: Peak power spectral density = 14.82 dBm per one MHz

Plot 5-6: Peak Power Spectral Density; Channel 10 - 4967.5 MHz




Result: Peak power spectral density = 12.35 dBm per one MHz

Plot 5-7: Peak Power Spectral Density; Channel 11 - 4972.5 MHz




Result: Peak power spectral density = 12.36 dBm per one MHz

Plot 5-8: Peak Power Spectral Density; Channel 12 - 4977.5 MHz




Result: Peak power spectral density = 12.26 dBm per one MHz

Plot 5-9: Peak Power Spectral Density; Channel 13 - 4982.5 MHz



Result: Peak power spectral density = 11.76 dBm per one MHz

Plot 5-10: Peak Power Spectral Density; Channel 16 - 4987.5 MHz



Result: Peak power spectral density = 11.77 dBm per one MHz

Table 5-2: Test Equipment for Testing Peak Power Spectral Density - Conducted

RTL Asset #	Manufacturer	Model	Part Type	Serial Number	Calibration Due
901413	Agilent	E4448	Spectrum Analyzer	US44020346	11/2/07
901138	MCE Weinschel	48-20-34	Attenuator, 20 dB, DC-18 GHz, 100 W	BK5859	12/9/08
900948	MCE Weinschel	47-10-43	Attenuator, 10 dB, DC-18 GHz, 50 W	BH1487	12/2/08

Test Personnel:

Daniel Biggs		August 14, 2006
Test Engineer	Signature	Date Of Tests

6 FCC Rules and Regulations Part 90 §90.210(m) and Part 2 §2.1049: Occupied Bandwidth (Emissions Masks) and Conducted Spurious Emissions; RSS-111 Section 4.4: Transmitter Unwanted Emissions

§90.210(m) Emission Mask M: For high power transmitters (greater than 20 dBm) operating in the 4940-4990 MHz frequency band, the power spectral density of the emissions must be attenuated below the output power of the transmitter as follows:

- (1) On any frequency removed from the assigned frequency between 0–45% of the authorized bandwidth (BW): 0 dB
- (2) On any frequency removed from the assigned frequency between 45–500% of the authorized bandwidth: $56.8 \log (\% \text{ of (BW)/45})$ dB.
- (3) On any frequency removed from the assigned frequency between 50–55% of the authorized bandwidth: $26 + 14.5 \log (\% \text{ of (BW)/50})$ dB.
- (4) On any frequency removed from the assigned frequency between 55–100% of the authorized bandwidth: $32 + 3.1 \log (\% \text{ of (BW)/55})$ dB attenuation.
- (5) On any frequency removed from the assigned frequency between 100–150% of the authorized bandwidth: $40 + 5.7 \log (\% \text{ of (BW)/100})$ dB attenuation.
- (6) On any frequency removed from the assigned frequency between 100–150% of the authorized bandwidth: 50 or $55 + 10 \log (P)$ dB, whichever is the lesser attenuation.
- (7) The zero dB reference is measured relative to the highest average power of the fundamental emission measured across the designated channel bandwidth using a resolution bandwidth of at least 1% of the occupied bandwidth of the fundamental emission and a video bandwidth of 30 kHz. The power spectral density is the power measured within the resolution bandwidth of the measurement device divided by the resolution bandwidth of the measurement device. Emissions levels are also based on the use of measurement instrumentation employing a resolution bandwidth of at least 1% of the occupied bandwidth.

Additionally, the latest FCC interpretation was followed:

With regard to the L and M masks in Part 90.210, the rule indicates using a minimum RBW of 1% of the fundamental emission to determine the reference level, and a minimum RBW of 1% of the fundamental to determine the mask skirts. The mask should be developed using the same resolution bandwidth throughout, for the reference level and the mask skirts. This interpretation was coordinated with the Wireless Bureau; the inquirer was asked whether the same RBW should be used or if different RBW's could be used, provided each was greater than 1% of the fundamental.

6.1 Test Procedure

TIA-603-C Section 2.2.11, 2.2.13 (with FCC deviations)

The EUT transmitter was connected to a spectrum analyzer through an appropriate 50 ohm attenuator. The reference level for the mask was set using the highest average power of the fundamental emission measured across the channel bandwidth using a RBW of at least 1% of the occupied bandwidth of the fundamental emission (240 kHz for this test) and a VBW of 30 kHz. The mask was then taken using the same RBW of 240 kHz per the latest FCC interpretation.

Combined 10dB and 20 dB attenuators were used between the EUT and the spectrum analyzer for all PSD measurements. No cable was used between EUT and analyzer.

Path loss was calculated as follows (checked across the frequency band of interest).

The system loss was measured by using a signal generator and reference cable. The attenuation was first measured with a reference cable, then measured in combination with the attenuators.

Loss (reference cable/attenuators) – Loss (reference cable) = Attenuator loss

31.9 dB – 0.9 dB = 31.0 dB total system loss (relative offset entered into analyzer)


6.2 Reference Level Measurements

The following measurements were taken in order to determine the reference level for the mask measurements.


Channel	RBW (kHz)	VBW (kHz)	Level (dBm)
3	240	30	24.6
16	240	30	24.6

6.3 In Band Spurious Test Data


Plot 6-1: Occupied Bandwidth; Channel 3 - 4942.5 MHz




Plot 6-2: Emissions Mask M; Channel 3 - 4942.5 MHz



Plot 6-3: Occupied Bandwidth; Channel 16 - 4987.5 MHz




Plot 6-4: Emissions Mask M; Channel 16 - 4987.5 MHz



6.4 Out of Band Spurious Test Data

Plot 6-5: Conducted Spurious Emissions; Channel 9 – 4962.5 MHz; 30 MHz – 13 GHz



Plot 6-6: Conducted Spurious Emissions; Channel 9 – 4962.5 MHz; 13 GHz – 50 GHz



Table 6-1: Test Equipment for Testing Occupied Bandwidth/Conducted Spurious Emissions

RTL Asset #	Manufacturer	Model	Part Type	Serial Number	Calibration Due
901413	Agilent	E4448	Spectrum Analyzer	US44020346	11/2/06
901138	MCE Weinschel	48-20-34	Attenuator, 20 dB, DC-18 GHz, 100 W	BK5859	12/9/08
900948	MCE Weinschel	47-10-43	Attenuator, 10 dB, DC-18 GHz, 50 W	BH1487	12/2/08

Test Personnel:

Daniel Biggs		August 14, 2006
Test Engineer	Signature	Date Of Tests

7 FCC Rules and Regulations Part 90 §90.210(l) and Part 2 §2.1053(a): Field Strength of Spurious Radiation; RSS-111 Section 3.3: Transmitter Unwanted Emissions

§90.210(l): Emission Mask M: For high power transmitters (20 dBm or greater) operating in the 4940-4990 MHz frequency band, the power spectral density of the emissions must be attenuated below the output power of the transmitter as follows:

On any frequency removed from the assigned frequency above 150% of the authorized bandwidth: 40 dB

The zero dB reference is measured relative to the highest average power of the fundamental emission measured across the designated channel bandwidth using a resolution bandwidth of at least 1% of the occupied bandwidth of the fundamental emission and a video bandwidth of 30 kHz. The power spectral density is the power measured within the resolution bandwidth of the measurement device divided by the resolution bandwidth of the measurement device. Emissions levels are also based on the use of measurement instrumentation employing a resolution bandwidth of at least 1% of the occupied bandwidth.

7.1 Test Procedure

TIA-603-C-2004, section 2.2.12.

The EUT was set to center channel and output power was set to maximum.

The EUT was placed on a non conducting table 80 cm above the ground plane. The antenna-to-EUT distance is 3 m. The EUT is rotated through 360 degrees to maximize emissions. The antenna is scanned in both vertical and horizontal polarizations. The spurious emissions levels were measured and the device under test was replaced by a substitution antenna connected to a signal generator. This signal generator level was then corrected by subtracting the cable loss from the substitution antenna to the signal generator, and the gain of the antenna was further corrected to a half-wave dipole.

The EUT was scanned from 30 GHz to the 10th harmonic of the fundamental. The spectrum analyzer resolution bandwidth was set to 1 MHz, and the video bandwidth was set to 1 MHz.

The spurious radiated emission limit is calculated as follows:

Average output power: 19.6 dBm

Spurious limit = 19.6 dBm – 50 db = -30.4 dBm

7.2 Test Data

7.2.1 CFR 47 Part 90.210 Requirements

The worst-case emissions test data are shown. The magnitude of emissions attenuated more than 20 dB below the FCC limit need not be recorded.

Table 7-1: Field Strength of Spurious Radiation: Channel 9 – 4962.5 MHz (High Power)

Limit = 50 dBc or -30.4 dBm
 Conducted Power (Avg) = 19.6 dBm = 0.09 W

Frequency (MHz)	Polarization (H/V)	Spectrum Analyzer Level (dBuV)	Signal Generator Level (dBm)	Cable Loss* (dB)	Antenna Gain (dBd)	EIRP (dBm)	Limit	Margin (dB)
9925.0	H	41.8	-43.0	7.5	8.4	-42.1	-30.4	-11.7
9925.0	V	41.8	-43.5	7.5	8.6	-42.4	-30.4	-12.0
14887.5	H	44.8	-54.3	8.7	10.9	-52.2	-30.4	-21.8
19850.0	V	44.5	-54.3	8.7	9.8	-53.2	-30.4	-22.8
24812.5	-	SNF	-	-	-			-
29775.0	-	SNF	-	-	-			-
34737.5	-	SNF	-	-	-			-
39700.0	-	SNF	-	-	-			-
44662.5	-	SNF	-	-	-			-
49625.0	-	SNF	-	-	-			-

*This insertion loss corresponds to the cable connecting the RF Signal Generator to the ½ wave dipole antenna.

Note: SNF = Spectrum analyzer noise floor

Table 7-2: Test Equipment for Testing Field Strength of Spurious Radiation

RTL Asset #	Manufacturer	Model	Part Type	Serial Number	Calibration Due
901053	Schaffner-Chase	CBL6112	Antenna (25 MHz – 2 GHz)	2648	11/1/06
901413	Agilent	E4448	Spectrum Analyzer	US44020346	11/2/06
901138	MCE Weinschel	48-20-34	Attenuator, 20 dB, DC-18 GHz, 100 W	BK5859	12/9/08
900948	MCE Weinschel	47-10-43	Attenuator, 10 dB, DC-18 GHz, 50 W	BH1487	12/2/08
900928	Hewlett Packard	HP 83752A	Synthesized Sweeper (.01 – 20 GHz)	3610A00866	11/10/06
900321	EMCO	3161-03	Horn Antennas (4 – 8 GHz)	9508-1020	5/20/07
900323	EMCO	3160-07	Horn Antennas (8.2 – 12 GHz)	9605-1054	7/31/09
900356	EMCO	3160-08	Horn Antennas (12.4 – 18 GHz)	9607-1044	5/20/07
900392	Hewlett Packard	1197OK	Harmonic mixer (18 – 26.5 GHz)	3525A00159	11/27/07
900126	Hewlett Packard	11970A	Horn Antennas (26.5 – 40 GHz)	2332A01199	10/29/09
901262	ETS	3115	Double ridge horn (1 – 26 GHz)	6748	4/19/08
901422	Insulated Wire, Inc.	KPS-1503-2400-KPS	RF cable, 20'	NA	12/12/06
901424	Insulated Wire Inc.	KPS-1503-360-KPS	RF cable 36"	NA	12/12/06

Test Personnel:

Daniel Biggs		August 14, 2006
Test Engineer	Signature	Date Of Tests

8 FCC Rules and Regulation Part 90 §90.213(a) and Part 2 §2.1055: Frequency Stability; RSS-111 Section 4.2: Transmitter Frequency Stability

§90.213(a): Unless noted elsewhere, transmitters used in the services governed by this part must have minimum frequency stability as specified in table (see 90.213 for table).

Above 2450 MHz, the frequency stability is to be specified in the station authorization.

For equipment authorization purposes, this is a reporting requirement only.

8.1 Test Procedure

TIA-603-C-2004, section 2.3.1 and 2.3.2.

The carrier frequency stability is the ability of the transmitter to maintain an assigned carrier frequency.

The EUT was evaluated over the temperature range -30°C to +60°C.

The temperature was initially set to -30°C and a 2-hour period was observed for stabilization of the EUT. The frequency stability was measured within one minute after application of primary power to the transmitter. The temperature was raised at intervals of 10°C through the range. A ½ hour period was observed to stabilize the EUT at each measurement step, and the frequency stability was measured within one minute after application of primary power to the transmitter. Additionally, the power supply voltage of the EUT was varied +/-15% nominal input voltage.

The worst-case test data are shown below in Table 8-1 and Table 8-2.

8.2 Frequency Stability Test Data

8.2.1 Frequency Stability/Temperature Variation

Table 8-1: Frequency Stability/Temperature Variation – Channel 9 - 4962.5 MHz

Temperature (°C)	Channel Frequency (MHz)	Measured Frequency (MHz)	Delta Freq (MHz)	ppm
-30	4962.5	4962.485000	-0.015000	3.02
-20	4962.5	4962.484600	-0.015400	3.10
-10	4962.5	4962.485500	-0.014500	2.92
0	4962.5	4962.483300	-0.016700	3.37
10	4962.5	4962.483500	-0.016500	3.32
20	4962.5	4962.484500	-0.015500	3.12
30	4962.5	4962.476600	-0.023400	4.72
40	4962.5	4962.475400	-0.024600	4.96
50	4962.5	4962.470700	-0.029300	5.90
60	4962.5	4962.473500	-0.026500	5.34

8.2.2 Frequency Stability/Voltage Variation

Table 8-2: Frequency Stability/Voltage Variation – Channel 9 - 4962.5 MHz

Voltage (VAC)	Channel Frequency (MHz)	Measured Frequency (MHz)	Delta Freq (MHz)	ppm
8.5	4962.5	4962.4782000	-0.021800	4.39
24	4962.5	4962.4781000	-0.021900	4.41
36.8	4962.5	4962.4719000	-0.028100	5.66

Table 8-3: Test Equipment for Testing Frequency Stability

RTL Asset #	Manufacturer	Model	Part Type	Serial Number	Calibration Due
900946	Tenney Engineering, Inc.	TH65	Temperature Chamber with Humidity	11380	02/04/07
901413	Agilent	E4448	Spectrum Analyzer	US44020346	11/2/06
900948	MCE Weinschel	47-10-43	Attenuator, 10 dB, DC-18 GHz, 50 W	BH1487	12/2/08
901424	Insulated Wire Inc.	KPS-1503-360-KPS	RF cable 36"	NA	12/12/06
901354	Meterman	37XR	Digital Multimeter	N/A	8/31/06

Test Personnel:

Daniel Biggs		August 18, 2006
Test Engineer	Signature	Date Of Tests

9 Conclusion

The data in this measurement report shows that the **M/A-COM, Inc. Model VIDA Broadband Client, FCC ID: BV8VMXCL, IC: 3670A-VMXCL**, complies with all the applicable requirements of FCC Parts 90, 15 and 2 and Industry Canada RSS-111.