



RADIO FREQUENCY EXPOSURE

LIMIT

According to §15.247(i), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines. See § 1.1307(b)(1) of this chapter.

EUT Specification

EUT	HD IP Camera
Model	IP-2100
Frequency band (Operating)	☒ 802.11b/g/gn HT20: 2.412GHz ~ 2.462GHz 802.11gn HT40: 2.422GHz ~ 2.452GHz ☐ Others
Device category	☐ Portable (<20cm separation) ☒ Mobile (>20cm separation) ☐ Others
Exposure classification	☐ Occupational/Controlled exposure ($S = 5\text{mW/cm}^2$) ☒ General Population/Uncontrolled exposure ($S=1\text{mW/cm}^2$)
Antenna Specification	2.4GHz: Antenna Gain : 2.00 dBi (Numeric gain 1.58)
Maximum output power	IEEE 802.11b Mode: 18.38 dBm (68.865 mW) IEEE 802.11g Mode: 19.23 dBm (83.753 mW) IEEE 802.11gn HT 20 Mode: 19.14 dBm (82.035 mW) IEEE 802.11gn HT 40 Mode: 19.11 dBm (81.470 mW)
Evaluation applied	☒ MPE Evaluation* ☐ SAR Evaluation ☐ N/A



Revision History

Rev.	Issue Date	Revisions	Effect Page	Revised By
00	2014/07/25	Initial Issue	ALL	Gloria Chang



TEST RESULTS

No non-compliance noted.

Calculation

Given $E = \frac{\sqrt{30 \times P \times G}}{d}$ & $S = \frac{E^2}{3770}$

Where E = Field strength in Volts / meter

P = Power in Watts

G = Numeric antenna gain

d = Distance in meters

S = Power density in milliwatts / square centimeter

Combining equations and re-arranging the terms to express the distance as a function of the remaining variables yields:

$$S = \frac{30 \times P \times G}{3770 d^2}$$

Changing to units of mW and cm, using:

$$P \text{ (mW)} = P \text{ (W)} / 1000 \text{ and}$$

$$d \text{ (cm)} = d \text{ (m)} / 100$$

Yields

$$S = \frac{30 \times (P / 1000) \times G}{3770 \times (d / 100)^2} = 0.0796 \times \frac{P \times G}{d^2} \quad \textbf{Equation 1}$$

Where d = Distance in cm

P = Power in mW

G = Numeric antenna gain

S = Power density in mW / cm²

**Maximum Permissible Exposure**

Substituting the MPE safe distance using $d = 20$ cm into Equation 1:

$$S = 0.000199 \times P \times G$$

Where P = Power in mW

G = Numeric antenna gain

S = Power density in mW / cm²

IEEE 802.11b mode:

Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm2)
2412~2462	68.865	1.58	20	0.0217	1

IEEE 802.11g mode:

Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm2)
2412~2462	83.753	1.58	20	0.0263	1

IEEE 802.11gn HT20 mode:

Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm2)
2412~2462	82.035	1.58	20	0.0258	1

IEEE 802.11gn HT40 mode:

Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm2)
2412~2462	81.47	1.58	20	0.0256	1