

FCC Part 15 EMI TEST REPORT

Part I – Bluetooth (BR/EDR)

of

E.U.T. : FM/AM radio with Bluetooth

Model : XRM04

FCC ID : BYG026

for

APPLICANT : SANGEAN ELECTRONICS INC.

ADDRESS : NO.18, LANE 7, LI-DE STREET, CHUNG HO
DISTRICT, NEW TAIPEI CITY, 23584,
TAIWAN, R.O.C.

Test Performed by

ELECTRONICS TESTING CENTER, TAIWAN

NO. 34. LIN 5, DINGFU VIL., LINKOU DIST.,
NEW TAIPEI CITY, TAIWAN, 24442, R.O.C.

Tel:(02)26023052 Fax:(02)26010910

<http://www.etc.org.tw> ; e-mail : emc@etc.org.tw

Report Number : 14-07-RBF-045-01

TEST REPORT CERTIFICATION

Applicant : SANGEAN ELECTRONICS INC.
NO.18, LANE 7, LI-DE STREET, CHUNG HO DISTRICT, NEW
TAIPEI CITY, 23584, TAIWAN, R.O.C.

Manufacture : SANGEAN ELECTRONICS INC.
NO.18, LANE 7, LI-DE STREET, CHUNG HO DISTRICT, NEW
TAIPEI CITY, 23584, TAIWAN, R.O.C.

Description of Device :

- a) Type of EUT : FM/AM radio with Bluetooth
- b) Trade Name : MAKITA
- c) Model No. : XRM04
- d) Power Supply : Adaptor Model: SE00000104(HKP12~1201200dU)
Input: 120V~60Hz 0.4A Max
Output: 12V, 1.2A

Regulation Applied : FCC Rules and Regulations Part 15 Subpart C

I HEREBY CERTIFY THAT: The data shown in this report were made in accordance with the procedures given in ANSI C63.4, and the energy emitted by the device was founded to be within the limits applicable. I assume full responsibility for accuracy and completeness of these data.

Note: 1. The result of the testing report relate only to the item tested.

2. The testing report shall not be reproduced expect in full, without the written approval of ETC.

Summary of Tests

Test	Results
Radiated Emission	Pass
Conducted Emission	Pass
Hopping Channel Separation	Pass
Number of Hopping frequencies used	Pass
Hopping Channel Bandwidth	Pass
Dwell Time of each frequency	Pass
Output Power Requirement	Pass
100 kHz Bandwidth of Frequency Band Edges Requirement	Pass
Out-of-Band Conducted Emission Requirement	Pass

Date Test Item Received : Jul. 30, 2014
Date Test Campaign Completed : Aug. 14, 2014
Date of Issue : Sep. 19, 2014

Test Engineer : Tien Lu Liao
(Tien Lu Liao , Engineer)

Approve & Authorized : S. S. Liou
S. S. Liou, Section Manager
EMC Dept. II of ELECTRONICS
TESTING CENTER, TAIWAN



Table of Contents	Page
1 GENERAL INFORMATION.....	1
1.1 Product Description.....	1
1.2 Test Methodology	1
1.3 Test Facility.....	1
2 PROVISIONS APPLICABLE.....	2
2.1 Definition	2
2.2 Requirement for Compliance	3
2.3 Restricted Bands of Operation	5
2.4 Labeling Requirement.....	6
2.5 User Information	6
3 SYSTEM TEST CONFIGURATION	7
3.1 Justification	7
3.2 Devices for Tested System.....	7
4 RADIATED EMISSION MEASUREMENT	8
4.1 Applicable Standard	8
4.2 Measurement Procedure.....	8
4.3 Measuring Instrument	10
4.4 Radiated Emission Data	11
4.5 Field Strength Calculation.....	21
4.6 Photos of Radiation Measuring Setup.....	22
5 CONDUCTED EMISSION MEASUREMENT.....	23
5.1 Standard Applicable	23
5.2 Measurement Procedure.....	23
5.3 Conducted Emission Data	24
5.4 Result Data Calculation.....	26
5.5 Conducted Measurement Equipment	26
5.6 Photos of Conduction Measuring Setup.....	27
6 ANTENNA REQUIREMENT.....	28
6.1 Standard Applicable	28
6.2 Antenna Construction.....	28
7 HOPPING CHANNEL SEPARATION.....	29
7.1 Standard Applicable	29
7.2 Measurement Procedure.....	29
7.3 Measurement Equipment	30
7.4 Measurement Data	30

8 NUMBER OF HOPPING FREQUENCY USED	37
8.1 Standard Applicable	37
8.2 Measurement Procedure	37
8.3 Measurement Equipment	37
8.4 Measurement Data	38
9 CHANNEL BANDWIDTH	45
9.1 Standard Applicable	45
9.2 Measurement Procedure	45
9.3 Measurement Equipment	46
9.4 Measurement Data	46
10 DWELL TIME ON EACH CHANNEL	53
10.1 Standard Applicable	53
10.2 Measurement Procedure	53
10.3 Measurement Equipment	53
10.4 Measurement Data	54
11 OUTPUT POWER MEASUREMENT	74
11.1 Standard Applicable	74
11.2 Measurement Procedure	74
11.3 Measurement Equipment	74
11.4 Measurement Data	75
12 100 kHz BANDWIDTH OF BAND EDGES MEASUREMENT	82
12.1 Standard Applicable	82
12.2 Measurement Procedure	82
12.3 Measurement Equipment	83
12.4 Measurement Data	83
13 CONDUCTED SPURIOUS EMISSION MEASUREMENT	92
13.1 Standard Applicable	92
13.2 Measurement Procedure	92
13.3 Measurement Equipment	93
13.4 Measurement Data	93

1 GENERAL INFORMATION

1.1 Product Description

- a) Type of EUT : FM/AM radio with Bluetooth
- b) Trade Name : MAKITA
- c) Model No. : XRM04
- d) Power Supply : Adaptor Model: SE00000104(HKP12~1201200dU)
Input: 120V~60Hz 0.4A Max
Output: 12V, 1.2A

1.2 Test Methodology

Both conducted and radiated emissions were performed according to the procedures illustrated in ANSI C63.4 (2003). Other required measurements were illustrated in separate sections of this test report for details.

1.3 Test Facility

The open area test site and conducted measurement facility used to collect the radiated data is located on the roof top of Building at No.34, Lin 5, Dingfu Vil., Linkou Dist., New Taipei City, Taiwan 24442, R.O.C.

This site is FCC 2.948 listed and accepted in a letter dated Jan. 29, 2014.

Registration Number: 90589

2 PROVISIONS APPLICABLE

2.1 Definition

Unintentional radiator:

A device that intentionally generates and radio frequency energy for use within the device, or that sends radio frequency signals by conduction to associated equipment via connecting wiring, but which is not intended to emit RF energy by radiation or induction.

Class A Digital Device:

A digital device which is marketed for use in commercial or business environment; exclusive of a device which is market for use by the general public, or which is intended to be used in the home.

Class B Digital Device :

A digital device which is marketed for use in a residential environment notwithstanding use in a commercial, business of industrial environment. Example of such devices that are marketed for the general public.

Note : A manufacturer may also qualify a device intended to be marketed in a commercial, business, or industrial environment as a Class B digital device, and in fact is encouraged to do so, provided the device complies with the technical specifications for a Class B Digital Device. In the event that a particular type of device has been found to repeatedly cause harmful interference to radio communications, the Commission may classify such a digital device as a Class B Digital Device, Regardless of its intended use.

Intentional radiator:

A device that intentionally generates and emits radio frequency energy by radiation or induction.

2.2 Requirement for Compliance

(1) Conducted Emission Requirement

Except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.

Frequency MHz	Quasi Peak dB μ V	Average dB μ V
0.15 - 0.5	66-56*	56-46*
0.5 - 5.0	56	46
5.0 - 30.0	60	50

* Decreases with the logarithm of the frequency

For intentional device, according to §15.207(a) Line Conducted Emission Limits is same as above table.

(2) Radiated Emission Requirement

For unintentional device, according to §15.109(a), except for Class A digital devices, the field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values:

Frequency MHz	Distance Meters	Radiated dB μ V/m	Radiated μ V/m
30 - 88	3	40.0	100
88 - 216	3	43.5	150
216 - 960	3	46.0	200
Above 960	3	54.0	500

For intentional device, according to §15.209(a), the general requirement of field strength of radiated emissions from intentional radiators at a distance of 3 meters shall not exceed the above table.

(3) Antenna Requirement

For intentional device, according to §15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

(4) Hopping Channel Separation

According to 15.247(a)(1), frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

(5) Number of Hopping frequencies used

According to 15.247(a)(1)(iii), frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels.

(6) Hopping Channel Bandwidth

For frequency hopping system operating in the 2400–2483.5 MHz band, there is no requirement for the maximum 20dB bandwidth of the hopping channel. The measurement of the hopping channel bandwidth is for the reference of the hopping channel separation requirement.

(7) Dwell Time of each frequency

According to 15.247(a)(1)(iii), for frequency hopping system operating in the 2400-2483.5 band, the average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

(8) Output Power Requirement

According to 15.247(b)(1), for frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725–5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400–2483.5 MHz band: 0.125 watts.

(9) 100 kHz Bandwidth of Frequency Band Edges Requirement

According to 15.247(d), in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the

transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required.

(10) Out-of-Band Conducted Emission Requirement

According to 15.247(d), in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required.

2.3 Restricted Bands of Operation

Only spurious emissions are permitted in any of the frequency bands listed below :

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42-16.423	399.9-410	4.5-5.15
0.495 - 0.505 **	16.69475 - 16.69525	608-614	5.35-5.46
2.1735 - 2.1905	16.80425 - 16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475 - 156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2655-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3360-4400	Above 38.6
13.36-13.41			

** : Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz

2.4 Labeling Requirement

The device shall bear the following statement in a conspicuous location on the device :

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions : (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

2.5 User Information

The users manual or instruction manual for an intentional or unintentional radiator shall caution the user that changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

For a Class B digital device or peripheral, the instructions furnished the user shall include the following or similar statement, placed in a prominent location in the text of the manual.

The Federal Communications Commission Radio Frequency Interference Statement includes the following paragraph.

This equipment has been tested and found to comply with the limits for a Class B Digital Device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation.

This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instruction may cause harmful interference to radio communication. However, there is no guarantee that interference will not occur in a particular installation.

If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio / TV technician for help.

3 SYSTEM TEST CONFIGURATION

3.1 Justification

For both radiated and conducted emissions below 1 GHz, the system was configured for testing in a typical fashion as a customer would normally use it. The peripherals other than EUT were connected in normally standing by situation. Measurement was performed under the condition that a computer program was exercised to simulate data communication of EUT, and the transmission rate was set to maximum allowed by EUT. Three highest emissions were verified with varying placement of the transmitting antenna connected to EUT (if applicable) to maximize the emission from EUT.

For conducted and radiated emissions, whichever RF channel is operated, the digital circuits' function identically. As the reason, measurement of emissions from digital circuits is performed with the highest, middle and the lowest channel by transmitting mode.

The following modes were investigated and the worst cases (mode 1 and 3) were chosen for final test.

1. Basic Rate (BR) 1 Mbps uses GFSK modulation
2. Enhanced Data Rate (EDR) 2Mbps uses $\pi/4$ -DQPSK modulation
3. Enhanced Data Rate (EDR) 3Mbps uses 8DPSK modulation

3.2 Devices for Tested System

Device	Manufacture	Model / FCC ID.	Description
FM/AM radio with Bluetooth *	SANGEAN ELECTRONICS INC.	XRM04/ BYG026	1.5m Unshielded AC Adaptor Power Line 1.6m Unshielded Audio Line*2 1.2m Shielded USB Line
iPod	SONY	NEW-E443F	---
Cell phone	Nokia	N73	---

Remark “*” means equipment under test.

4 RADIATED EMISSION MEASUREMENT

4.1 Applicable Standard

For unintentional radiator, the radiated emission shall comply with §15.109(a).

For intentional radiators, according to §15.247 (a), operation under this provision is limited to frequency hopping and direct sequence spread spectrum, and the out band emission shall be comply with §15.247 (c)

4.2 Measurement Procedure

1. Setup the configuration per figure 1 and 2 for frequencies measured below and above 1 GHz respectively.
2. For emission frequencies measured below 1 GHz, a pre-scan is performed in a shielded chamber to determine the accurate frequencies of higher emissions will be checked on a open test site. As the same purpose, for emission frequencies measured above 1 GHz, a pre-scan also be performed with a 1 meter measuring distance before final test.
3. For emission frequencies measured below and above 1 GHz, set the spectrum analyzer on a 100 kHz and 1 MHz resolution bandwidth respectively for each frequency measured in step 2.
4. The search antenna is to be raised and lowered over a range from 1 to 4 meters in horizontally polarized orientation. Position the highness when the highest value is indicated on spectrum analyzer, then change the orientation of EUT on test table over a range from 0 ° to 360 ° with a speed as slow as possible, and keep the azimuth that highest emission is indicated on the spectrum analyzer. Vary the antenna position again and record the highest value as a final reading. A RF test receiver is also used to confirm emissions measured.
5. Repeat step 4 until all frequencies need to be measured were complete.
6. Repeat step 5 with search antenna in vertical polarized orientations.
7. Check the three frequencies of highest emission with varying the placement of cables associated with EUT to obtain the worse case and record the result.

Figure 1 : Frequencies measured below 1 GHz configuration





Figure 2 : Frequencies measured above 1 GHz configuration



4.3 Measuring Instrument

The following instrument are used for radiated emissions measurement:

Equipment	Manufacturer	Model No.	Calibration Date	Next Cal. Date
Test Receiver	Rohde & Schwarz	ESVS30	2014/05/29	2015/05/28
Bi-Log Antenna	ETC	MCTD 2756	2014/01/03	2015/01/02
Log-periodic Antenna	EMCO	3146	2013/10/25	2014/10/24
Biconical Antenna	EMCO	3110	2013/10/25	2014/10/24
Horn Antenna	EMCO	3115	2014/08/02	2015/08/01
Horn Antenna	EMCO	3116	2014/01/15	2015/01/14
Horn Antenna	ETS	3117	2013/09/17	2014/09/16
Spectrum	R&S	FSP3	2014/08/08	2015/08/07
Amplifier	HP	8447D	2014/05/29	2015/05/28
EMI Test Receiver	Rohde & Schwarz	ESU 40	2013/09/24	2014/09/23
Double Ridged Antenna	EMCO	3115	2014/08/02	2015/08/01
Attenuator	WEINSCHL ENGINEERING	AY8986	2013/09/16	2014/09/15
Amplifier	HP	83051A	2014/05/05	2015/05/04


Measuring instrument setup in measured frequency band when specified detector function is used :

Frequency Band (MHz)	Instrument	Function	Resolution bandwidth	Video Bandwidth
30 to 1000	RF Test Receiver	Quasi-Peak	120 kHz	N/A
	Spectrum Analyzer	Peak	100 kHz	100 kHz
Above 1000	Spectrum Analyzer	Peak	1 MHz	1 MHz
	Spectrum Analyzer	Average	1 MHz	10 Hz

4.4 Radiated Emission Data

4.4.1 Tx Portion


A. Bluetooth BR

Test Date : Aug. 05, 2014 Temperature : 27 °C Humidity : 56 %

Site	:Open Site #2	Date	:2014-08-05
EUT	:FM/AM radio with Bluetooth	Ant. Pol.	:HORIZONTAL
Model	:XRM04	Detector	:
Power Rating	:120Vac/60Hz	Engineer	:Tien-Lu Liao
Limit	:FCC 1G TO 40G PEAK	Temp.	:27° C
Memo	:Bluetooth BR	Humi.	:56 %
Memo	:TX/RX:2402MHz, 2441MHz, 2480MHz		
Memo	:Duty cycle > 98%		

Freq MHz	Reading dBuV	Correction Factor dB	Result dBuV/m	Limits dBuV/m	Over limit dB	Detector
4804.3600	6.5	37.8	44.3	54.0	-9.7	Average
4804.3600	11.1	37.8	48.9	74.0	-25.1	Peak
4881.6000	8.6	37.9	46.5	54.0	-7.5	Average
4881.6000	12.8	37.9	50.7	74.0	-23.3	Peak
4959.5800	10.8	38.1	48.9	54.0	-5.1	Average
4959.5800	14.8	38.1	52.9	74.0	-21.1	Peak

1. Result = Reading + Corrected Factor
2. Corrected Factor = Antenna Factor + Cable Loss - Amplifier Gain (if any)
3. The margin value=Limit - Result




Site	:Open Site #2	Date	:2014-08-05
EUT	:FM/AM radio with Bluetooth	Ant. Pol.	:VERTICAL
Model	:XRM04	Detector	:
Power Rating	:110Vac/60Hz	Engineer	:Tien-Lu Liao
Limit	:FCC 1G TO 40G PEAK	Temp.	:27°C
Memo	:Bluetooth BR	Humi.	:56 %
Memo	:TX/RX:2402MHz, 2441MHz, 2480MHz		
Memo	:Duty cycle > 98%		

Freq MHz	Reading dBuV	Correction Factor dB	Result dBuV/m	Limits dBuV/m	Over limit dB	Detector
4804.3600	8.4	37.8	46.2	54.0	-7.8	Average
4804.3600	13.0	37.8	50.8	74.0	-23.2	Peak
4881.6000	10.6	37.9	48.5	54.0	-5.5	Average
4881.6000	14.0	37.9	51.9	74.0	-22.1	Peak
4959.5800	11.2	38.1	49.3	54.0	-4.7	Average
4959.5800	14.6	38.1	52.7	74.0	-21.3	Peak

Note :

1. Result = Reading + Corrected Factor
2. Corrected Factor = Antenna Factor + Cable Loss - Amplifier Gain (if any)
3. The margin value=Limit - Result

B. Bluetooth EDR


Test Date : Aug. 07, 2014 Temperature : 27 °C Humidity : 56 %

Site	:Open Site #2	Date	:2014-08-07
EUT	:FM/AM radio with Bluetooth	Ant. Pol.	:HORIZONTAL
Model	:XRM04	Detector	:
Power Rating	:110Vac/60Hz	Engineer	:Tien-Lu Liao
Limit	:FCC 1G TO 40G PEAK	Temp.	:27 °C
Memo	:Bluetooth EDR	Humi.	:56 %
Memo	:TX/RX:2402MHz, 2441MHz, 2480MHz		
Memo	:Duty cycle > 98%		

Freq MHz	Reading dBuV	Correction Factor dB	Result dBuV/m	Limits dBuV/m	Over limit dB	Detector
4804.1200	5.7	37.8	43.5	54.0	-10.5	Average
4804.1200	10.1	37.8	47.9	74.0	-26.1	Peak
4881.1600	7.9	37.9	45.8	54.0	-8.2	Average
4881.1600	11.7	37.9	49.6	74.0	-24.4	Peak
4959.2800	9.5	38.1	47.6	54.0	-6.4	Average
4959.2800	13.5	38.1	51.6	74.0	-22.4	Peak

Note :

1. Result = Reading + Corrected Factor
2. Corrected Factor = Antenna Factor + Cable Loss - Amplifier Gain (if any)
3. The margin value=Limit - Result



Site	:Open Site #2	Date	:2014-08-07
EUT	:FM/AM radio with Bluetooth	Ant. Pol.	:VERTICAL
Model	:XRM04	Detector	:
Power Rating	:120Vac/60Hz	Engineer	:Tien-Lu Liao
Limit	:FCC 1G TO 40G PEAK	Temp.	:27°C
Memo	:Bluetooth EDR	Humi.	:56 %
Memo	:TX/RX:2402MHz, 2441MHz, 2480MHz		
Memo	:Duty cycle > 98%		


Freq MHz	Reading dBuV	Correction Factor dB	Result dBuV/m	Limits dBuV/m	Over limit dB	Detector
4804.1200	7.8	37.8	45.6	54.0	-8.4	Average
4804.1200	12.1	37.8	49.9	74.0	-24.1	Peak
4879.4400	9.4	37.9	47.3	54.0	-6.7	Average
4879.4400	13.7	37.9	51.6	74.0	-22.4	Peak
4959.2800	10.5	38.1	48.6	54.0	-5.4	Average
4959.2800	14.2	38.1	52.3	74.0	-21.7	Peak

Note :

1. Result = Reading + Corrected Factor
2. Corrected Factor = Antenna Factor + Cable Loss - Amplifier Gain (if any)
3. The margin value=Limit - Result

4.4.2 Radiated Emissions in Restricted BandsOperation Mode : Bluetooth TX/RX

A. Bluetooth BR


Test Date : Aug. 05, 2014 Temperature : 27 °C Humidity : 56 %

Site	: Open Site #2	Date	: 2014-08-05
EUT	: FM/AM radio with Bluetooth	Ant. Pol.	: HORIZONTAL
Model	: XRM04	Detector	:
Power Rating	: 120Vac/60Hz	Engineer	: Tien-Lu Liao
Limit	: FCC 1G TO 40G PEAK	Temp.	: 27 °C
Memo	: Restricted bands	Humi.	: 56 %
Memo	: TX/RX: 2402MHz, 2441MHz, 2480MHz		
Memo	: Bluetooth BR	Memo	: Duty cycle > 98%

Freq MHz	Reading dBuV	Correction Factor dB	Result dBuV/m	Limits (AVG) dBuV/m	Over limit dB	Detector
2315.5600	15.5	31.3	46.8	54.0	-7.2	Peak
2360.5400	16.4	31.5	47.9	54.0	-6.1	Peak
2484.5000	17.0	31.9	48.9	54.0	-5.1	Peak
2495.6400	18.0	31.9	49.9	54.0	-4.1	Peak

Note :

1. Result = Reading + Corrected Factor
2. Corrected Factor = Antenna Factor + Cable Loss - Amplifier Gain (if any)
3. The margin value = Limit - Result
4. Peak measurements are compared to the average limit - as peak measurements are below the average limit, they also comply with the peak limit.




Site	:Open Site #2	Date	:2014-08-05
EUT	:FM/AM radio with Bluetooth	Ant. Pol.	:VERTICAL
Model	:XRM04	Detector	:
Power Rating	:120Vac/60Hz	Engineer	:Tien-Lu Liao
Limit	:FCC 1G TO 40G PEAK	Temp.	:27°C
Memo	:Restricted bands	Humi.	:56 %
Memo	:TX/RX:2402MHz, 2441MHz, 2480MHz		
Memo	: Bluetooth BR	Memo	:Duty cycle > 98%

Freq MHz	Reading dBuV	Correction Factor dB	Result dBuV/m	Limits (AVG) dBuV/m	Over limit dB	Detector
2315.5600	16.9	31.3	48.2	54.0	-5.8	Peak
2360.5400	17.4	31.5	48.9	54.0	-5.1	Peak
2484.5600	18.0	31.9	49.9	54.0	-4.1	Peak
2495.6400	19.0	31.9	50.9	54.0	-3.1	Peak

Note :

1. Result = Reading + Corrected Factor
2. Corrected Factor = Antenna Factor + Cable Loss - Amplifier Gain (if any)
3. The margin value=Limit - Result
4. Peak measurements are compared to the average limit - as peak measurements are below the average limit, they also comply with the peak limit.

B. Bluetooth EDR


Test Date : Aug. 07, 2014 Temperature : 27 °C Humidity : 56 %

Site	:Open Site #2	Date	:2014-08-07
EUT	:FM/AM radio with Bluetooth	Ant. Pol.	:HORIZONTAL
Model	:XRM04	Detector	:
Power Rating	:120Vac/60Hz	Engineer	:Tien-Lu Liao
Limit	:FCC 1G TO 40G PEAK	Temp.	:27° C
Memo	:Restricted bands	Humi.	:56 %
Memo	:TX/RX:2402MHz, 2441MHz, 2480MHz		
Memo	: Bluetooth EDR	Memo	:Duty cycle > 98%

Freq MHz	Reading dBuV	Correction Factor dB	Result dBuV/m	Limits (AVG) dBuV/m	Over limit dB	Detector
2330.8300	16.1	31.4	47.5	54.0	-6.5	Peak
2375.2500	17.3	31.6	48.9	54.0	-5.1	Peak
2484.1500	17.7	31.9	49.6	54.0	-4.4	Peak
2495.6700	18.7	31.9	50.6	54.0	-3.4	Peak

Note :

1. Result = Reading + Corrected Factor
2. Corrected Factor = Antenna Factor + Cable Loss - Amplifier Gain (if any)
3. The margin value=Limit - Result
4. Peak measurements are compared to the average limit - as peak measurements are below the average limit, they also comply with the peak limit.



Site	:Open Site #2	Date	:2014-08-07
EUT	:FM/AM radio with Bluetooth	Ant. Pol.	:VERTICAL
Model	:XRM04	Detector	:
Power Rating	:120Vac/60Hz	Engineer	:Tien-Lu Liao
Limit	:FCC 1G TO 40G PEAK	Temp.	:27°C
Memo	:Restricted bands	Humi.	:56 %
Memo	:TX/RX:2402MHz, 2441MHz, 2480MHz		
Memo	: Bluetooth EDR	Memo	:Duty cycle > 98%


Freq MHz	Reading dBuV	Correction Factor dB	Result dBuV/m	Limits (AVG) dBuV/m	Over limit dB	Detector
2375.2500	18.6	31.6	50.2	54.0	-3.8	Peak
2380.8300	17.2	31.6	48.8	54.0	-5.2	Peak
2484.1500	19.0	31.9	50.9	54.0	-3.1	Peak
2495.6700	20.0	31.9	51.9	54.0	-2.1	Peak

Note :

1. Result = Reading + Corrected Factor
2. Corrected Factor = Antenna Factor + Cable Loss - Amplifier Gain (if any)
3. The margin value=Limit - Result
4. Peak measurements are compared to the average limit - as peak measurements are below the average limit, they also comply with the peak limit.

4.4.3 Other Emissions

a) Emission frequencies below 1 GHz




Site	:Open site	Date	:2014-08-14
EUT	:FM/AM radio with Bluetooth	Ant. Pol.	:HORIZONTAL
Model	:XRM04	Detector	:QP
Power Rating	:120Vac/60Hz	Engineer	:Tien-Lu Liao
Limit	:FCC CLASS-B	Temp.	:34 °C
Memo	:Bluetooth	Humi.	:56 %

Freq MHz	Reading dBuV	Correction Factor dB	Result dBuV/m	Limits dBuV/m	Over limit dB
31.9400	13.6	15.3	28.9	40.0	-11.1
134.7600	10.2	13.2	23.4	43.5	-20.1
398.6000	7.4	19.1	26.5	46.0	-19.5
559.6200	4.1	22.4	26.5	46.0	-19.5
650.8000	7.2	24.0	31.2	46.0	-14.8
672.1400	9.4	24.5	33.9	46.0	-12.1

Note :

1. Result = Reading + Corrected Factor
2. Corrected Factor = Antenna Factor + Cable Loss
3. The margin value=Limit - Result



Site	:Open site	Date	:2014-08-14
EUT	:FM/AM radio with Bluetooth	Ant. Pol.	:VERTICAL
Model	:XRM04	Detector	:QP
Power Rating	:120Vac/60Hz	Engineer	:Tien-Lu Liao
Limit	:FCC CLASS-B	Temp.	:34 °C
Memo	:Bluetooth	Humi.	:56 %

Freq	Reading	Correction	Result	Limits	Over limit
MHz	dBuV	Factor	dBuV/m	dBuV/m	dB
31.9400	11.3	15.3	26.6	40.0	-13.4
120.2100	17.9	12.4	30.3	43.5	-13.2
134.7600	15.6	13.2	28.8	43.5	-14.7
388.9000	4.7	18.9	23.6	46.0	-22.4
485.9000	5.7	21.2	26.9	46.0	-19.1
658.5600	6.8	24.2	31.0	46.0	-15.0

Note :

1. Result = Reading + Corrected Factor
2. Corrected Factor = Antenna Factor + Cable Loss
3. The margin value=Limit - Result

b) Emission frequencies above 1 GHz

Radiated emission frequencies above 1 GHz to 25 GHz were too low to be measured with a pre-amplifier of 35 dB.

4.5 Field Strength Calculation

The field strength is calculated by adding the Antenna Factor, High Pass Filter Loss (if used) and Cable Loss, and subtracting the Amplifier Gain (if any) from the measured reading. The basic equation calculation is as follows:

$$\textbf{Result} = \textbf{Reading} + \textbf{Corrected Factor}$$

where Corrected Factor

$$= \text{Antenna FACTOR} + \text{Cable Loss} + \text{High Pass Filter Loss} - \text{Amplifier Gain}$$

4.6 Photos of Radiation Measuring Setup



5 CONDUCTED EMISSION MEASUREMENT


5.1 Standard Applicable

For unintentional and intentional device, Line Conducted Emission Limits are in accordance to § 15.107(a) and § 15.207(a) respectively. Both Limits are identical specification.


5.2 Measurement Procedure

1. Setup the configuration per figure 3.
2. A preliminary scan with a spectrum monitor is performed to identify the frequency of emission that has the highest amplitude relative to the limit by operating the EUT in selected modes of operation, typical cable positions, and with a typical system configuration.
3. Record the 6 or 8 highest emissions relative to the limit.
4. Measure each frequency obtained from step 3 by a test receiver set on quasi peak detector function, and then record the accuracy frequency and emission level. If all emissions measured in the specified band are attenuated more than 20 dB from the limit, this step would be ignored, and the peak detector function would be used.
5. Confirm the highest three emissions with variation of the EUT cable configuration and record the final data.
6. Repeat all above procedures on measuring each operation mode of EUT.

Figure 3 : Conducted emissions measurement configuration



5.3 Conducted Emission Data




Site	: conducted #1	Date	: 08-13-2014
Condition	: CLASS-B QP	LISN	: NEUTRAL
Tem / Hum	: 27 °C / 56%	Test Mode	: Bluetooth Play
EUT	: FM/AM radio with Bluetooth	Power Rating	: 120Vac/60Hz
Memo	:	Memo	:

Freq (MHz)	Reading (dBuV)	Factor (dB)	Emission Level (dBuV)	Limit Line (dBuV)	Over Limit (dB)	Remark
0.1607	28.3	10.2	38.5	65.4	-26.9	QP
0.1864	29.8	10.2	40.0	64.2	-24.2	QP
0.2442	24.5	10.2	34.7	62.0	-27.3	QP
0.2971	25.5	10.2	35.7	60.3	-24.6	QP
0.3634	24.6	10.2	34.8	58.7	-23.9	QP
0.4812	20.6	10.2	30.8	56.3	-25.5	QP

Note :

1. Result = Reading + Factor
2. Factor = LISN Factor + Cable Loss



Site	: conducted #1	Date	: 08-13-2014
Condition	: CLASS-B QP	LISN	: LINE
Tem / Hum	: 27 °C / 56%	Test Mode	: Bluetooth Play
EUT	: FM/AM radio with Bluetooth	Power Rating	: 120Vac/60Hz
Memo	:	Memo	:

Freq (MHz)	Reading (dBuV)	Factor (dB)	Emission Level (dBuV)	Limit Line (dBuV)	Over Limit (dB)	Remark
0.1624	29.9	10.1	40.0	65.3	-25.3	QP
0.1864	30.3	10.1	40.4	64.2	-23.8	QP
0.2417	25.7	10.1	35.8	62.0	-26.2	QP
0.2924	24.6	10.1	34.7	60.5	-25.8	QP
0.4127	21.1	10.2	31.3	57.6	-26.3	QP
0.5238	19.0	10.2	29.2	56.0	-26.8	QP

Note :

1. Result = Reading + Factor
2. Factor = LISN Factor + Cable Loss

5.4 Result Data Calculation

The result data is calculated by adding the LISN Factor to the measured reading. The basic equation with a sample calculation is as follows:

$$\text{RESULT} = \text{READING} + \text{LISN FACTOR}$$

Assume a receiver reading of 22.5 dB μ V is obtained, and LISN Factor is 0.1 dB, then the total of disturbance voltage is 22.6 dB μ V.

$$\text{RESULT} = 22.5 + 0.1 = 22.6 \text{ dB } \mu \text{ V}$$


$$\begin{aligned} \text{Level in } \mu \text{ V} &= \text{Common Antilogarithm}[(22.6 \text{ dB } \mu \text{ V})/20] \\ &= 13.48 \mu \text{ V} \end{aligned}$$

5.5 Conducted Measurement Equipment

The following test equipment are used during the conducted test .

Equipment	Manufacturer	Model No.	Calibration Date	Next Cal. Date
EMI Test Receiver	Rohde & Schwarz	ESCI	2014/08/01	2015/07/31
LISN	Shibasoku	563	2014/01/21	2015/01/20
LISN	Rohde & Schwarz	ESH2-Z5	2014/04/08	2015/04/07

5.6 Photos of Conduction Measuring Setup



6 ANTENNA REQUIREMENT

6.1 Standard Applicable

For intentional device, according to 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

6.2 Antenna Construction

The antenna is permanently mounted on main PCB, no consideration of replacement. The antenna gain is 0dBi.

Please see internal photos and the antenna specifications.

7 HOPPING CHANNEL SEPARATION


7.1 Standard Applicable

According to 15.247(a)(1), frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

7.2 Measurement Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT as shown in figure 4 without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. The EUT must have its hopping function enabled. Then set it to any one convenient frequency within its operating range.
3. Use the following spectrum analyzer settings:
Span = wide enough to capture the peaks of two adjacent channels
Resolution (or IF) Bandwidth (RBW) $\geq 1\%$ of the span
Video (or Average) Bandwidth (VBW) $\geq$ RBW
Sweep = auto
Detector function = peak
Trace = max hold
4. Allow the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels. Plot the result on the screen of spectrum analyzer.
5. Repeat above procedures until all frequencies measured were complete.

Figure 4 : Measurement configuration.



7.3 Measurement Equipment

Equipment	Manufacturer	Model No.	Calibration Date	Next Cal. Date
Spectrum	Rohde & Schwarz	FSP40	2014/01/21	2015/01/20
Attenuator	Weinschel Engineering	AY7602	2013/09/16	2014/09/15

7.4 Measurement Data

Test Date : Aug. 05, 2014 Temperature : 27 °C Humidity : 56 %

Mode: Bluetooth BR

- a) Channel Low : Adjacent Hopping Channel Separation is 1.004 MHz
- b) Channel Middle : Adjacent Hopping Channel Separation is 1.004 MHz
- c) Channel High : Adjacent Hopping Channel Separation is 1.004 MHz

Test Date : Aug. 07, 2014 Temperature : 27 °C Humidity : 56 %


Mode: Bluetooth EDR

- a) Channel Low : Adjacent Hopping Channel Separation is 1.002 MHz
- b) Channel Middle : Adjacent Hopping Channel Separation is 1.002 MHz
- c) Channel High : Adjacent Hopping Channel Separation is 1.002 MHz


Note : The expanded uncertainty: $\text{frequency} \times 1.65 \times 10^{-6}$ ($1 \text{ GHz} < f \leq 18 \text{ GHz}$).

Mode: Bluetooth BR


Channel Low



Channel Middle




Channel High





Mode: Bluetooth EDR

Channel Low



Channel Middle



Channel High

8 NUMBER OF HOPPING FREQUENCY USED

8.1 Standard Applicable

According to 15.247(a)(1)(iii), frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels.

8.2 Measurement Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT as shown in figure 4 without connection to measurement instrument.
Turn on the EUT and connect it to measurement instrument. The EUT must have its hopping function enabled.
3. Use the following spectrum analyzer settings:
Span = the frequency band of operation
RBW $\geq$ 1% of the span
VBW $\geq$ RBW
Sweep = auto
Detector function = peak
Trace = max hold
4. Allow the trace to stabilize. Plot the result on the screen of spectrum analyzer.
5. Repeat above procedures until all frequencies measured were complete.

8.3 Measurement Equipment

Equipment	Manufacturer	Model No.	Calibration Date	Next Cal. Date
Spectrum	Rohde & Schwarz	FSP40	2014/01/21	2015/01/20
Attenuator	Weinschel Engineering	AY7602	2013/09/16	2014/09/15

8.4 Measurement Data

A. Bluetooth BR

Test Date : Aug. 05, 2014 Temperature : 27 °C Humidity : 56 %

There are 79 hopping frequencies used.

B. Bluetooth EDR

Test Date : Aug. 07, 2014 Temperature : 27 °C Humidity : 56 %


There are 79 hopping frequencies used.


Justification on AFH mode:


Adaptive Frequency Hopping (AFH) means that a device can hop over a reduced set of frequencies. The frequencies hopped may reduced in AFH mode but at least 15 channels will be used, normally AFH mode has 20 channels.

Note : The expanded uncertainty: $\text{frequency} \times 1.65 \times 10^{-6}$ ($1 \text{ GHz} < f \leq 18 \text{ GHz}$).


Mode: Bluetooth BR









Mode: Bluetooth EDR







9 CHANNEL BANDWIDTH

9.1 Standard Applicable

For frequency hopping system operating in the 2400–2483.5 MHz band, there is no requirement for the maximum 20dB bandwidth of the hopping channel. The measurement of the hopping channel bandwidth is for the reference of the hopping channel separation requirement.

9.2 Measurement Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT as shown in figure 4 without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range.
3. Use the following spectrum analyzer settings:
Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hopping channel
RBW $\geq$ 1% of the 20 dB bandwidth
VBW $\geq$ RBW
Sweep = auto
Detector function = peak
Trace = max hold
4. Allow the trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission. Use the marker-delta function to measure 20 dB down one side of the emission. Reset the marker-delta function, and move the marker to the other side of the emission, until it is (as close as possible to) even with the reference marker level. The marker-delta reading at this point is the 20 dB bandwidth of the emission. Plot the result on the screen of spectrum analyzer.
5. Repeat above procedures until all frequencies measured were complete.

9.3 Measurement Equipment

Equipment	Manufacturer	Model No.	Calibration Date	Next Cal. Date
Spectrum	Rohde & Schwarz	FSP40	2014/01/21	2015/01/20
Attenuator	Weinschel Engineering	AY7602	2013/09/16	2014/09/15

9.4 Measurement Data

Test Date : Aug. 05, 2014 Temperature : 27 °C Humidity : 56 %

Mode: Bluetooth BR

- a) Channel Low : Channel Bandwidth is 0.880 MHz
- b) Channel Middle : Channel Bandwidth is 0.852 MHz
- c) Channel High : Channel Bandwidth is 0.852 MHz

Test Date : Aug. 07, 2014 Temperature : 27 °C Humidity : 56 %


Mode: Bluetooth EDR

- a) Channel Low : Channel Bandwidth is 1.208 MHz
- b) Channel Middle : Channel Bandwidth is 1.212 MHz
- c) Channel High : Channel Bandwidth is 1.216 MHz

Note : The expanded uncertainty: $frequency \times 1.65 \times 10^{-6}$ ($1\text{ GHz} < f \leq 18\text{ GHz}$).

Mode:Bluetooth BR


Channel Low



Channel Middle




1 PK
VIEW



Channel High




1 PK
VIEW



Mode: Bluetooth EDR


Channel Low



Channel Middle




1 PK
MAXH



Channel High



1 PK
VIEW



10 DWELL TIME ON EACH CHANNEL

10.1 Standard Applicable

According to 15.247(a)(1)(iii), for frequency hopping system operating in the 2400-2483.5 band, the average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

10.2 Measurement Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT as shown in figure 4 without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. The EUT must have its hopping function enabled.
3. Use the following spectrum analyzer settings:
Span = zero span, centered on a hopping channel
RBW = 1 MHz
VBW $\geq$ RBW
Sweep = as necessary to capture the entire dwell time per hopping channel
Detector function = peak
Trace = max hold
4. Use the marker-delta function to determine the dwell time. Plot the result on the screen of spectrum analyzer.
5. Repeat above procedures until all frequencies measured were complete.

Justification on AFH mode:

Adaptive Frequency Hopping (AFH) means that a device can hop over a reduced set of frequencies. The frequencies hopped may reduced in AFH mode but at least 15 channels will be used, normally AFH mode has 20 channels.

10.3 Measurement Equipment

Equipment	Manufacturer	Model No.	Calibration Date	Next Cal. Date
Spectrum	Rohde & Schwarz	FSP40	2014/01/21	2015/01/20
Attenuator	Weinschel Engineering	AY7602	2013/09/16	2014/09/15

10.4 Measurement Data

Test Mode: Bluetooth BR

Test Date : Aug. 05, 2014 Temperature : 27 °C Humidity : 56 %

$$\text{Period} = 0.4(\text{seconds}) \times 79(\text{channels}) = 31.6 \text{ seconds}$$

A. DH1 Mode

The Bluetooth system hops at a rate of 1600 times per second. This means there are 1600 timeslots in one second. The DH1 data rate operates on a one-slot transmission and one-slot receiving basis. Thus there are $1600/(1+1) = 800$ transmissions per second. In one period for each particular channel there are $10.13 \times 31.6 = 320.1$ times of transmissions.

- a) Channel Low : the dwell time is 0.46 ms x 320.1 = 147.246 ms
- b) Channel Middle : the dwell time is 0.46 ms x 320.1 = 147.246 ms
- c) Channel High : the dwell time is 0.46 ms x 320.1 = 147.246 ms

The maximum time of occupancy for a particular channel is 147.246ms in any 31.6 second period, which is less than the 400ms allowed by the rules; therefore, it meets the requirements of this section.

B. DH3 Mode

The Bluetooth system hops at a rate of 1600 times per second. This means there are 1600 timeslots in one second. The DH3 data rate operates on a three-slot transmission and one-slot receiving basis. Thus there are $1600/(3+1) = 400$ transmissions per second. In one period for each particular channel there are $5.06 \times 31.6 = 159.9$ times of transmissions.

- a) Channel Low : the dwell time is 1.76 ms x 159.9 = 281.424 ms
- b) Channel Middle : the dwell time is 1.76 ms x 159.9 = 281.424 ms
- c) Channel High : the dwell time is 1.76 ms x 159.9 = 281.424 ms

The maximum time of occupancy for a particular channel is 281.424ms in any 31.6 second period, which is less than the 400 ms allowed by the rules; therefore, it meets the requirements of this section.

C. DH5 Mode

The Bluetooth system hops at a rate of 1600 times per second. This means there are 1600 timeslots in one second. The DH5 data rate operates on a five-slot transmission and one-slot receiving basis. Thus there are $1600/(5+1) = 266.7$ transmissions per second. In one period for each particular channel there are $3.38 \times 31.6 = 106.81$ times of transmissions.

- a) Channel Low : the dwell time is 3.06 ms x 106.81 = 326.838 ms
- b) Channel Middle : the dwell time is 3.06 ms x 106.81 = 326.838 ms
- c) Channel High : the dwell time is 3.06 ms x 106.81 = 326.838 ms

The maximum time of occupancy for a particular channel is 326.838ms in any 31.6 second period, which is less than the 400 ms allowed by the rules; therefore, it meets the requirements of this section.

Note : The expanded uncertainty of dwell time on each channel tests is 2dB.

Test Mode:Bluetooth EDRTest Date : Aug. 07, 2014 Temperature : 27 °C Humidity : 56 %

$$\text{Period} = 0.4(\text{seconds}) \times 20(\text{channels}) = 8 \text{ seconds}$$

A. DH1 Mode

The Bluetooth system hops at a rate of 800 times per second. This means there are 800 timeslots in one second. The DH1 data rate operates on a one-slot transmission and one-slot receiving basis. Thus there are $800/(1+1) = 400$ transmissions per second. In one period for each particular channel there are $20 \times 8 = 160$ times of transmissions.

- a) Channel Low : the dwell time is $0.47\text{ms} \times 160 = 75.2$ ms
- b) Channel Middle : the dwell time is $0.47\text{ms} \times 160 = 75.2$ ms
- c) Channel Hi : the dwell time is $0.47\text{ms} \times 160 = 75.2$ ms

The maximum time of occupancy for a particular channel is 75.2ms in any 8 second period, which is less than the 400ms allowed by the rules; therefore, it meets the requirements of this section.

B. DH3 Mode

The Bluetooth system hops at a rate of 800 times per second. This means there are 800 timeslots in one second. The DH3 data rate operates on a three-slot transmission and one-slot receiving basis. Thus there are $800/(3+1) = 200$ transmissions per second. In one period for each particular channel there are $10 \times 8 = 80$ times of transmissions.

- a) Channel Low : the dwell time is $1.74\text{ms} \times 80 = 139.200$ ms
- b) Channel Middle : the dwell time is $1.74\text{ms} \times 80 = 139.200$ ms
- c) Channel Hi : the dwell time is $1.74\text{ms} \times 80 = 139.200$ ms

The maximum time of occupancy for a particular channel is 139.200ms in any 8 second period, which is less than the 400 ms allowed by the rules; therefore, it meets the requirements of this section.

C. DH5 Mode

The Bluetooth system hops at a rate of 800 times per second. This means there are 800 timeslots in one second. The DH5 data rate operates on a five-slot transmission and one-slot receiving basis. Thus there are $800/(5+1) = 133.3$ transmissions per second. In one period for each particular channel there are $6.665 \times 8 = 53.32$ times of transmissions.


- a) Channel Low : the dwell time is $3.04\text{ms} \times 53.32 = 162.092$ ms
- b) Channel Middle : the dwell time is $3.04\text{ms} \times 53.32 = 162.092$ ms
- c) Channel Hi : the dwell time is $3.04\text{ms} \times 53.32 = 162.092$ ms


The maximum time of occupancy for a particular channel is 162.092ms in any 8 second period, which is less than the 400 ms allowed by the rules; therefore, it meets the requirements of this section.


Note : The expanded uncertainty of dwell time on each channel tests is 2dB.


Mode: Bluetooth BR

Channel Low; DH1













Channel Middle; DH3









Channel Middle; DH5






Mode: Bluetooth EDR


Channel Low; DH1





1 PK
CLRWR




















11 OUTPUT POWER MEASUREMENT

11.1 Standard Applicable

According to 15.247(b)(1), for frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725–5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400–2483.5 MHz band: 0.125 watts.

11.2 Measurement Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT as shown in figure 4 without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
3. Use the following spectrum analyzer settings:
Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel
RBW > the 20 dB bandwidth of the emission being measured
VBW $\geq$ RBW
Sweep = auto
Detector function = peak
Trace = max hold
4. Allow the trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission. The indicated level is the peak output power. Plot the result on the screen of spectrum analyzer.
5. Repeat above procedures until all frequencies measured were complete.

11.3 Measurement Equipment

Equipment	Manufacturer	Model No.	Calibration Date	Next Cal. Date
Spectrum	Rohde & Schwarz	FSP40	2014/01/21	2015/01/20
Attenuator	Weinschel Engineering	AY7602	2013/09/16	2014/09/15

11.4 Measurement Data

Test Date : Aug. 05, 2014 Temperature : 27 °C Humidity : 56 %

Mode: Bluetooth BR

- | | | | | |
|-------------------|---|----------------------|-------------|------------|
| a) Channel Low | : | Output Peak Power is | 1.06 dBm or | 1.276 mW ° |
| b) Channel Middle | : | Output Peak Power is | 2.30 dBm or | 1.698 mW ° |
| c) Channel High | : | Output Peak Power is | 2.43 dBm or | 1.750 mW ° |

Test Date : Aug. 07, 2014 Temperature : 27 °C Humidity : 56 %

Mode: Bluetooth EDR

- | | | | | |
|-------------------|---|----------------------|-------------|------------|
| a) Channel Low | : | Output Peak Power is | 0.62 dBm or | 1.153 mW ° |
| b) Channel Middle | : | Output Peak Power is | 1.94 dBm or | 1.563 mW ° |
| c) Channel High | : | Output Peak Power is | 2.09 dBm or | 1.618 mW ° |

Justification on AFH mode:

Adaptive Frequency Hopping (AFH) means that a device can hop over a reduced set of frequencies. The frequencies hopped may reduced in AFH mode but at least 15 channels will be used. Hence the output power limit is 125mW.


Note : The expanded uncertainty: 2dB.

Mode: Bluetooth BR

Channel Low



1 PK
VIEW



Channel Middle




```
* RBW 1 MHz      Marker 1 [T1 ]
VBW 3 MHz      2.30 dBm
SWT 2.5 ms     2.440800000 GHz
```

Ref 15 dBm

* Att 20 dB

SWT 2.5 ms


2.440800000 GHz



Channel High



1 PK
VIEW




Mode: Bluetooth EDR

Channel Low



1 PK
VIEW



Channel Middle




```
* RBW 3 MHz      Marker 1 [T1 ]
VBW 10 MHz      1.94 dBm
SWT 2.5 ms      2.440580000 GHz
```

Ref 15 dBm

* Att 20 dB

SWT 2.5 ms

2.440580000 GHz



12 100 kHz BANDWIDTH OF BAND EDGES MEASUREMENT

12.1 Standard Applicable

According to 15.247(d), in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required.

12.2 Measurement Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT as shown in figure 4 without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
3. Use the following spectrum analyzer settings:
 - Span = wide enough to capture the peak level of the emission operating on the channel closest to the bandedge, as well as any modulation products which fall outside of the authorized band of operation
 - $RBW \geq 1\%$ of the span
 - $VBW \geq RBW$
 - Sweep = auto
 - Detector function = peak
 - Trace = max hold
4. Allow the trace to stabilize. Set the marker on the emission at the bandedge, or on the highest modulation product outside of the band, if this level is greater than that at the bandedge. Enable the marker-delta function, then use the marker-to-peak function to move the marker to the peak of the in-band emission. Plot the result on the screen of spectrum analyzer.
5. Repeat above procedures until all measured frequencies were complete.

12.3 Measurement Equipment

Equipment	Manufacturer	Model No.	Calibration Date	Next Cal. Date
Spectrum	Rohde & Schwarz	FSP40	2014/01/21	2015/01/20
Attenuator	Weinschel Engineering	AY7602	2013/09/16	2014/09/15

12.4 Measurement Data

Test Date : Aug. 05, 2014 Temperature : 27 °C Humidity : 56 %

Mode: Bluetooth BR

- a) Lower Band Edge : All emissions in this 100kHz bandwidth are attenuated more than 20dB from the carrier.
- b) Upper Band Edge : All emissions in this 100kHz bandwidth are attenuated more than 20dB from the carrier.

Test Date : Aug. 07, 2014 Temperature : 27 °C Humidity : 56 %

Mode: Bluetooth EDR

- a) Lower Band Edge : All emissions in this 100kHz bandwidth are attenuated more than 20dB from the carrier.
- b) Upper Band Edge : All emissions in this 100kHz bandwidth are attenuated more than 20dB from the carrier.


Note : The expanded uncertainty: 2dB.

Mode: Bluetooth BR


Lower Band Edge (Hoppin off)



1 PK
VIEW




Upper Band Edge (Hoppin off)



Lower Band Edge (Hoppin on)



1 PK
VIEW



Upper Band Edge (Hoppin on)




Mode: Bluetooth EDR


Lower Band Edge (Hoppin off)




1 PK
VIEW




Upper Band Edge (Hoppin off)





Upper Band Edge (Hoppin on)



13 CONDUCTED SPURIOUS EMISSION MEASUREMENT

13.1 Standard Applicable

According to 15.247(d), in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required.

13.2 Measurement Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT as shown in figure 4 without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
3. Use the following spectrum analyzer settings:
 - Span = wide enough to capture the peak level of the in-band emission and all spurious emissions (e.g., harmonics) from the lowest frequency generated in the EUT up through the 10th harmonic. Typically, several plots are required to cover this entire span.
 - RBW = 100 kHz
 - VBW $\geq$ RBW
 - Sweep = auto
 - Detector function = peak
 - Trace = max hold.
4. Allow the trace to stabilize. Set the marker on the peak of any spurious emission recorded. Plot the result on the screen of spectrum analyzer.
5. Repeat above procedures until all measured frequencies were complete.

13.3 Measurement Equipment

Equipment	Manufacturer	Model No.	Calibration Date	Next Cal. Date
Spectrum	Rohde & Schwarz	FSP40	2014/01/21	2015/01/20
Attenuator	Weinschel Engineering	AY7602	2013/09/16	2014/09/15

13.4 Measurement Data

Test Date : Aug. 05, 2014 Temperature : 27 °C Humidity : 56 %

Mode: Bluetooth BR**Mode : Low Channel/ Mid Channel/ Hi Channel**

- a) 1 GHz to 26.5 GHz frequency band: All emissions are attenuated more than 20dB from the carrier.


Test Date : Aug. 07, 2014 Temperature : 27 °C Humidity : 56 %

Mode: Bluetooth EDR**Mode : Low Channel/ Mid Channel/ Hi Channel**


- a) 1 GHz to 26.5 GHz frequency band: All emissions are attenuated more than 20dB from the carrier.

Note : The expanded uncertainty: 2dB.


Mode : Low Channel




Mode : Mid Channel




Mode : Hi Channel



Mode : Low Channel



Mode : Mid Channel



Mode : Hi Channel

