



M. Flom Associates, Inc. - Global Compliance Center

3356 North San Marcos Place, Suite 107, Chandler, Arizona 85225-7176

www.mflom.com general@mflom.com (480) 926-3100, FAX: 926-3598

Transmitter Certification

of

FCC ID: BYMBP850

Model: BP850

to

Federal Communications Commission

Rule Part(s) 74H, Confidentiality

Date of report: August 18, 2003

On the Behalf of the Applicant:

HM Electronics, Inc.

At the Request of:

P.O. Part of 20213

HM Electronics, Inc.
14110 Stowe Drive
Poway, CA 92064

Attention of:

(858) 535-6000 Corporate
Tom Riches, Engineering Services manager
(858) 535-6098; FAX: -9019
email: triches@hme.com

Supervised by:

A handwritten signature in black ink, reading "M. Flom P. Eng.", is positioned above the printed name.

Morton Flom, P. Eng.

List of Exhibits

(FCC **Certification** (Transmitters) - Revised 9/28/98)

Applicant: HM Electronics, Inc.

FCC ID: BYMBP850

By Applicant:

- | | |
|---|---|
| 1. Letter of Authorization | x |
| 2. Identification Drawings, 2.1033(c)(11) | |
| <u>x</u> Label | |
| <u>x</u> Location of Label | |
| <u>x</u> Compliance Statement | |
| <u>x</u> Location of Compliance Statement | |
| 3. Photographs, 2.1033(c)(12) | x |
| 4. Documentation: 2.1033(c) | |
| (3) User Manual | x |
| (9) Tune Up Info | x |
| (10) Schematic Diagram | x |
| (10) Circuit Description | x |
| Block Diagram | x |
| Parts List | x |
| Active Devices | x |

By M.F.A. Inc.:

- A. Testimonial & Statement of Certification
- B. Statement of Qualifications

The Applicant has been cautioned as to the following:**15.21 Information to the User.**

The users manual or instruction manual for an intentional radiator shall caution the user that changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

15.27(a) Special Accessories.

Equipment marketed to a consumer must be capable of complying with the necessary regulations in the configuration in which the equipment is marketed. Where special accessories, such as shielded cables and/or special connectors are required to enable an unintentional or intentional radiator to comply with the emission limits in this part, the equipment must be marketed with, i.e. shipped and sold with, those special accessories. However, in lieu of shipping or packaging the special accessories with the unintentional or intentional radiator, the responsible party may employ other methods of ensuring that the special accessories are provided to the consumer, without additional charge.

Information detailing any alternative method used to supply the special accessories for a grant of equipment authorization or retained in the verification records, as appropriate. The party responsible for the equipment, as detailed in § 2.909 of this chapter, shall ensure that these special accessories are provided with the equipment. The instruction manual for such devices shall include appropriate instructions on the first page of text concerned with the installation of the device that these special accessories must be used with the device. It is the responsibility of the user to use the needed special accessories supplied with the equipment.

Table of Contents

<u>Rule</u>	<u>Description</u>	<u>Page</u>
	Test Report	1
2.1033(c)	General Information Required	2
2.1033(c)(14)	Rule Summary	5
	Standard Test Conditions and Engineering Practices	6
2.1046(a)	Carrier Output Power (Conducted)	7
2.1046(a)	ERP Carrier Power (Radiated)	9
2.1053(a)	Field Strength of Spurious Radiation	10
2.1049(c)(1)	Emission Masks (Occupied Bandwidth)	14
2.1055(a)(1)	Frequency Stability (Temperature Variation)	18
2.202(g)	Necessary Bandwidth and Emission Bandwidth	22

Page Number

1 of 22.

Required information per ISO/IEC Guide 25-1990, paragraph 13.2:

a)

Test Report

b) Laboratory:

(FCC: 31040/SIT)

(Canada: IC 2044)

M. Flom Associates, Inc.

3356 N. San Marcos Place, Suite 107

Chandler, AZ 85225

c) Report Number:

d0380033

d) Client:

HM Electronics, Inc.

14110 Stowe Drive

Poway, CA 92064

e) Identification:

BP850

FCC ID: BYMBP850

EUT Description:

f) EUT Condition:

Not required unless specified in individual tests.

g) Report Date:

August 18, 2003

EUT Received:

July 14, 2003

h, j, k):

As indicated in individual tests.

i) Sampling method:

No sampling procedure used.

l) Uncertainty:

In accordance with MFA internal quality manual.

m) Supervised by:



Morton Flom, P. Eng.

n) Results:

The results presented in this report relate only to the item tested.

o) Reproduction:

This report must not be reproduced, except in full, without written permission from this laboratory.

Page Number

2 of 22.

List of General Information Required for Certification

In Accordance with FCC Rules and Regulations,
Volume II, Part 2 and to

74H, Confidentiality

Sub-part 2.1033**(c)(1): Name and Address of Applicant:**

HM Electronics, Inc.
14110 Stowe Drive
Poway, CA 92064

Manufacturer:

Applicant

(c)(2): FCC ID:

BYMBP850

Model Number:

BP850

(c)(3): Instruction Manual(s):

Please see attached exhibits

(c)(4): Type of Emission:

190KF9W

(c)(5): Frequency Range, MHz:

470 to 608
614 to 740

(c)(6): Power Rating, Watts:

____ Switchable

____ Variable

0.100

____ N/A

(c)(7): Maximum Power Rating, Watts:

0.250

DUT Results:

Passes ____ x ____

Fails ____

Page Number

4 of 22.

Subpart 2.1033 (continued)(c)(8): Voltages & currents in all elements in final RF stage, including final transistor or solid-state device:

Collector Current, A	=	per manual
Collector Voltage, Vdc	=	per manual
Supply Voltage, Vdc	=	6

(c)(9): **Tune-Up Procedure :**

Please see attached exhibits

(c)(10): **Circuit Diagram / Circuit Description:**

Including description of circuitry & devices provided for determining and stabilizing frequency, for suppression of spurious radiation, for limiting modulation and limiting power.

Please see attached exhibits

(c)(11): **Label Information:**

Please see attached exhibits

(c)(12): **Photographs:**

Please see attached exhibits

(c)(13): **Digital Modulation Description:**

☐ Attached Exhibits
☒ N/A

(c)(14): **Test and Measurement Data:**

Follows

Page Number

5 of 22.

Sub-part

2.1033(c)(14):**Test and Measurement Data**

All tests and measurement data shown were performed in accordance with FCC Rules and Regulations, Volume II; Part 2, Sub-part J, Sections 2.947, 2.1033(c), 2.1041, 2.1046, 2.1047, 2.1079, 2.1051, 2.1053, 2.1055, 2.1057 and the following individual Parts:

- ☐ 21 – Domestic Public Fixed Radio Services
- ☐ 22 – Public Mobile Services
- ☐ 22 Subpart H - Cellular Radiotelephone Service
- ☐ 22.901(d) - Alternative technologies and auxiliary services
- ☐ 23 – International Fixed Public Radiocommunication services
- ☐ 24 – Personal Communications Services
- ☒ 74 Subpart H - Low Power Auxiliary Stations
- ☐ 80 – Stations in the Maritime Services
- ☐ 80 Subpart E - General Technical Standards
- ☐ 80 Subpart F - Equipment Authorization for Compulsory Ships
- ☐ 80 Subpart K - Private Coast Stations and Marine Utility Stations
- ☐ 80 Subpart S - Compulsory Radiotelephone Installations for Small Passenger Boats
- ☐ 80 Subpart T - Radiotelephone Installation Required for Vessels on the Great Lakes
- ☐ 80 Subpart U - Radiotelephone Installations Required by the Bridge-to-Bridge Act
- ☐ 80 Subpart V - Emergency Position Indicating Radio Beacons (EPIRB'S)
- ☐ 80 Subpart W - Global Maritime Distress and Safety System (GMDSS)
- ☐ 80 Subpart X - Voluntary Radio Installations
- ☐ 87 – Aviation Services
- ☐ 90 – Private Land Mobile Radio Services
- ☐ 94 – Private Operational-Fixed Microwave Service
- ☐ 95 Subpart A - General Mobile Radio Service (GMRS)
- ☐ 95 Subpart C - Radio Control (R/C) Radio Service
- ☐ 95 Subpart D - Citizens Band (CB) Radio Service
- ☐ 95 Subpart E - Family Radio Service
- ☐ 95 Subpart F - Interactive Video and Data Service (IVDS)
- ☐ 97 - Amateur Radio Service
- ☐ 101 – Fixed Microwave Services

**Standard Test Conditions
and
Engineering Practices**

Except as noted herein, the following conditions and procedures were observed during the testing:

In accordance with ANSI C63.4-1992/2000 Draft, section 6.1.9, and unless otherwise indicated in the specific measurement results, the ambient temperature of the actual EUT was maintained within the range of 10° to 40°C (50° to 104 °F) unless the particular equipment requirements specify testing over a different temperature range. Also, unless otherwise indicated, the humidity levels were in the range of 10% to 90% relative humidity.

Prior to testing, the EUT was tuned up in accordance with the manufacturer's alignment procedures. All external gain controls were maintained at the position of maximum and/or optimum gain throughout the testing.

Measurement results, unless otherwise noted, are worst-case measurements.

Page Number 7 of 22.

Name of Test: Carrier Output Power (Conducted)

Specification: 47 CFR 2.1046(a)

Guide: ANSI/TIA/EIA-603-1992, Paragraph 2.2.1

Test Equipment: As per attached page

Measurement Procedure

1. The EUT was connected to a resistive coaxial attenuator of normal load impedance, and the unmodulated output power was measured by means of an RF Power Meter.
2. Measurement accuracy is $\pm 3\%$.

Measurement Results (Worst case)

Frequency of Carrier, MHz = 659 MHz
Ambient Temperature, F = $23^{\circ}\text{C} \pm 3$

Power Setting	RF Power, Watts
High	0.100




Performed By:

David Lee

Transmitter Power Conducted Measurements

Test A. RF Power Output
 Test B. Frequency Stability



Asset (as applicable)	Description	s/n
(1) Coaxial Attenuator		
i00122	Narda 766-10	7802
i00123	Narda 766-10	7802A
i00069	Bird 8329 (30 dB)	1006
i00113	Sierra 661A-3D	1059
(2) Power Meters		
i00014	HP 435A	1733A05836
i00039	HP 436A	2709A26776
i00020	HP 8901A Power Mode	2105A01087
(3) Frequency Counter		
i00042	HP 5383A	1628A00959
i00019	HP 5334B	2704A00347
i00020	HP 8901A Frequency Mode	2105A01087

Page Number


9 of 22.

Name of Test: ERP Carrier Power (Radiated)**Specification:** TIA/EIA 603A (Substitution Method)

2.2.17.1 Definition: The average radiated power of a licensed device is the equivalent power required, when delivered to a half-wave dipole or horn antenna, to produce at a distant point the same average received power as produced by the licensed device.

2.2.17.2 Method of Measurement:

a) Connect the equipment as illustrated. Place the transmitter to be tested on the turntable in the standard test site.



b) Raise and lower the test antenna from 1m to 6 m with the transmitter facing the antenna and record the highest received signal in dB as LVL.

c) Repeat step b) for seven additional readings at 45° interval positions of the turntable.

d) Replace the transmitter under test with a half-wave or horn vertically polarized antenna. The center of the antenna should be at the same location as the transmitter under test. Connect the antenna to a signal generator with a known output power and record the path loss in dB or LOSS.

e) Calculate the average radiated output power from the readings in step c) and d) by the following:

$$\text{average radiated power} = 10 \log_{10} S 10(\text{LVL} - \text{LOSS})/10 \text{ (dBm)}$$

Results

	650.000 MHz		659.000 MHz		666.475 MHz	
	LVL, dbm	Path Loss, db	LVL, dbm	Path Loss, db	LVL, dbm	Path Loss, db
0°	17.5	-1.2	20.6	-0.6	19.8	-0.8
45°	19.0	-1.2	18.8	-0.6	17.8	-0.8
90°	17.5	-1.2	19.8	-0.6	14.7	-0.8
135°	16.7	-1.2	16.6	-0.6	16.0	-0.8
180°	20.7	-1.2	16.8	-0.6	15.2	-0.8
225°	19.5	-1.2	20.3	-0.6	18.5	-0.8
270°	20.0	-1.2	16.4	-0.6	20.2	-0.8
315°	17.2	-1.2	16.9	-0.6	15.3	-0.8
	650.000 MHz		659.000 MHz		666.475 MHz	
Av. Radiated Power:	17.3 dbm		17.68 dbm		16.39 dbm	

Page Number 10 of 22.

Name of Test: Field Strength of Spurious Radiation

Specification: 47 CFR 2.1053(a)


Guide: ANSI/TIA/EIA-603-1992/2001, Paragraph 1.2.12 and Table 16, 47 CFR 22.917

Measurement Procedure

1.2.12.1 Definition: Radiated spurious emissions are emissions from the equipment when transmitting into a non-radiating load on a frequency or frequencies which are outside an occupied band sufficient to ensure transmission of information of required quality for the class of communications desired.


1.2.12.2 Method of Measurement

- A) Connect the equipment as illustrated
- B) Adjust the spectrum analyzer for the following settings:
 - 1) Resolution Bandwidth 100 kHz (<1 GHz), 1 MHz (> 1GHz).
 - 2) Video Bandwidth = 3 times Resolution Bandwidth, or 30 kHz (22.917)
 - 3) Sweep Speed ≤ 2000 Hz/second
 - 4) Detector Mode = Mean or Average Power
- C) Place the transmitter to be tested on the turntable in the standard test site. The transmitter is transmitting into a non-radiating load which is placed on the turntable. The RF cable to this load should be of minimum length.



Name of Test: Field Strength of Spurious Radiation (Cont.)

- D) For each spurious measurement the test antenna should be adjusted to the correct length for the frequency involved. This length may be determined from a calibration ruler supplied with the equipment. Measurements shall be made from the lowest radio frequency generated in the equipment to the tenth harmonic of the carrier, except for the region close to the carrier equal to $\pm$ the test bandwidth (see section 1.3.4.4).
- E) For each spurious frequency, raise and lower the test antenna from 1 m to 4 m to obtain a maximum reading on the spectrum analyzer with the test antenna at horizontal polarity. Repeat this procedure to obtain the highest possible reading. Record this maximum reading.
- F) Repeat step E) for each spurious frequency with the test antenna polarized vertically.



- G) Reconnect the equipment as illustrated.
- H) Keep the spectrum analyzer adjusted as in step B).
- I) Remove the transmitter and replace it with a substitution antenna (the antenna should be half-wavelength for each frequency involved). The center of the substitution antenna should be approximately at the same location as the center of the transmitter. At lower frequencies, where the substitution antenna is very long, this will be impossible to achieve when the antenna is polarized vertically. In such case the lower end of the antenna should be 0.3 m above the ground.

Page Number 12 of 22.

Name of Test: Field Strength of Spurious Radiation (Cont.)

- J) Feed the substitution antenna at the transmitter end with a signal generator connected to the antenna by means of a non-radiating cable. With the antennas at both ends horizontally polarized and with the signal generator tuned to a particular spurious frequency, raise and lower the test antenna to obtain a maximum reading at the spectrum analyzer. Adjust the level of the signal generator output until the previously recorded maximum reading for this set of conditions is obtained. This should be done carefully repeating the adjustment of the test antenna and generator output.
- K) Repeat step J) with both antennas vertically polarized for each spurious frequency.
- L) Calculate power in dBm into a reference ideal half-wave dipole antenna by reducing the readings obtained in steps J) and K) by the power loss in the cable between the generator and the antenna and further corrected for the gain of the substitution antenna used relative to an ideal half-wave dipole antenna.
- M) The levels recorded in step L) are absolute levels of radiated spurious emissions in dBm. The radiated spurious emissions in dB can be calculated by the following:

$$\text{Radiated spurious emissions dB} = 10\log_{10}(\text{TX power in watts}/0.001) - \text{the levels in step l)}$$

NOTE: It is permissible that other antennas provided can be referenced to a dipole.

Test Equipment:

Asset (as applicable)	Description	s/n	Cycle	Last Cal
Transducer				
i00088	EMCO 3109-B 25MHz-300MHz	2336	12 mo.	Sep-02
i00065	EMCO 3301-B Active Monopole	2635	12 mo.	Sep-02
i00089	Apriel 2001 200MHz-1GHz	001500	12 mo.	Sep-02
i00103	EMCO 3115 1GHz-18GHz	9208-3925	12 mo.	Sep-02
Amplifier				
i00028	HP 8449A	2749A00121	12 mo.	Mar-03
Spectrum Analyzer				
i00029	HP 8563E	3213A00104	12 mo.	Jan-03
i00033	HP 85462A	3625A00357	12 mo.	Jan-03
i00048	HP 8566B	2511AD1467	6 mo.	Jul-03
Microphone, Antenna Port, and Cabling				
Microphone	Yes/No	<u>N</u>	Cable Length	<u>0.5</u> Meters
Antenna Port Terminated	Yes/No	<u>Y</u>	Load	<u>N/A</u> Antenna Gain <u>0 dBd</u>
All Ports Terminated by	Load	<u>Y</u>	Peripheral	<u>N</u>

Page Number 13 of 22.

Name of Test: Field Strength of Spurious Radiation

g0380249: 2003-Aug-11 Mon 08:42:00

STATE: 2:High Power

Ambient Temperature 23°C ± 3

Frequency Tuned, MHz	Frequency Emission, MHz	ERP, dBm	ERP, dbc
659.000000	1317.968333	-63.1	≤ -66.3
659.000000	1976.960833	-46.3	≤ -66.3
659.000000	2635.902500	-57.8	≤ -66.3
659.000000	3294.906667	-54.4	≤ -66.3
659.000000	3953.983333	-59.2	≤ -66.3
659.000000	4612.990833	-55.6	≤ -66.3
659.000000	5271.990833	-57.9	≤ -66.3
659.000000	5931.015833	-55.7	≤ -66.3
659.000000	6590.015833	-55.1	≤ -66.3



Performed By:

David Lee

Page Number 14 of 22.

Name of Test: Emission Masks (Occupied Bandwidth)

Specification: 47 CFR 2.1049(c)(1)

Guide: ANSI/TIA/EIA-603-1992, Paragraph 2.2.11

Test Equipment: As per previous page

Measurement Procedure

1. The EUT and test equipment were set up as shown on the following page, with the Spectrum Analyzer connected.
2. For EUTs supporting audio modulation, the audio signal generator was adjusted to the frequency of maximum response and with output level set for $\pm 2.5/\pm 1.25$ kHz deviation (or 50% modulation). With level constant, the signal level was increased 16 dB.
3. For EUTs supporting digital modulation, the digital modulation mode was operated to its maximum extent.
4. The Occupied Bandwidth was measured with the Spectrum Analyzer controls set as shown on the test results.
5. Measurement Results: Attached


Page Number 15 of 22.

Name of Test: Emission Masks (Occupied Bandwidth)

g0370040: 2003-Jul-22 Tue 15:27:00

State: 2:High Power

Ambient Temperature 23°C ± 3



Power:

HIGH

Modulation:

NONE

Performed By:

David Lee


Page Number 16 of 22.

Name of Test: Emission Masks (Occupied Bandwidth)

g0370041: 2003-Jul-22 Tue 15:31:00

State: 2:High Power

Ambient Temperature $23^{\circ}\text{C} \pm 3$



Power:

HIGH

Modulation:

NONE

Performed By:

David Lee


Page Number 17 of 22.

Name of Test: Emission Masks (Occupied Bandwidth)

g0370042: 2003-Jul-22 Tue 15:32:00

State: 2:High Power

Ambient Temperature 23°C ± 3



Power:

HIGH

Modulation:

NONE

MASK: Wireless Mic, 74.861

Performed By:

David Lee

Page Number 18 of 22.

Name of Test: Frequency Stability (Temperature Variation)

Specification: 47 CFR 2.1055(a)(1)

Guide: ANSI/TIA/EIA-603-1992, Paragraph 2.2.2

Test Conditions: As Indicated


Test Equipment: As per previous page

Measurement Procedure

1. The EUT and test equipment were set up as shown on the following page.
2. With all power removed, the temperature was decreased to -30°C and permitted to stabilize for three hours. Power was applied and the maximum change in frequency was noted within one minute.
3. With power OFF, the temperature was raised in 10°C steps. The sample was permitted to stabilize at each step for at least one-half hour. Power was applied and the maximum frequency change was noted within one minute.
4. The temperature tests were performed for the worst case.
5. Measurement Results: Attached

Transmitter Test Set-Up

Test A. Operational Stability
 Test B. Carrier Frequency Stability
 Test C. Operational Performance Stability
 Test D. Humidity
 Test E. Vibration
 Test F. Environmental Temperature
 Test G. Frequency Stability: Temperature Variation
 Test H. Frequency Stability: Voltage Variation




Asset (as applicable)	Description	s/n
(1)	Temperature, Humidity, Vibration	
i00027	Tenney Temp. Chamber	9083-765-234
i00	Weber Humidity Chamber	
i00	L.A.B. RVH 18-100	
(2)	Coaxial Attenuator	
i00122	NARDA 766-10	7802
i00123	NARDA 766-10	7802A
i00113	SIERRA 661A-3D	1059
i00069	BIRD 8329 (30 dB)	10066
(3)	RF Power	
i00014	HP 435A Power Meter	1733A05839
i00039	HP 436A Power Meter	2709A26776
i00020	HP 8901A Power Mode	2105A01087
(4)	Frequency Counter	
i00042	HP 5383A	1628A00959
i00019	HP 5334B	2704A00347
i00020	HP 8901A	2105A01087

Page Number 20 of 22.

Name of Test: Frequency Stability (Temperature Variation)

Ambient Temperature: 23



Performed By:

David Lee

Page Number

21 of 22.

Page Left Intentionally Blank

Page Number 22 of 22.

Name of Test: Necessary Bandwidth and Emission Bandwidth

Specification: 47 CFR 2.202(g)

Modulation = 190KF3E

Measured 190 KHz

A handwritten signature in black ink, appearing to read 'David Lee', with a stylized flourish at the end.

Performed By:

David Lee

END OF TEST REPORT

**Testimonial
and
Statement of Certification**

This is to Certify:

1. **That** the application was prepared either by, or under the direct supervision of, the undersigned.
2. **That** the technical data supplied with the application was taken under my direction and supervision.
3. **That** the data was obtained on representative units, randomly selected.
4. **That**, to the best of my knowledge and belief, the facts set forth in the application and accompanying technical data are true and correct.

Certifying Engineer:

A handwritten signature in black ink, appearing to read "M. Flom P. Eng.", with a horizontal line drawn underneath the signature.

Morton Flom, P. Eng.