



Test Mode: 04; Polarity: Vertical; Modulation:802.11n; Bandwidth:40MHz; Channel:Low




		ReadAntenna		Cable	Preamp		Limit	Over		
	Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	5646.426	62.92	31.95	6.35	36.89	64.33	68.20	-3.87	VERTICAL	Peak
2	5715.000	62.18	32.04	6.33	36.89	63.66	109.40	-45.74	VERTICAL	Peak
3	5725.000	65.01	32.07	6.25	36.89	66.44	122.20	-55.76	VERTICAL	Peak
4	5755.000	107.60	32.10	6.20	36.89	109.01	125.20	-16.19	VERTICAL	Peak

Test Mode: 04; Polarity: Horizontal; Modulation:802.11n; Bandwidth:40MHz; Channel:High




		ReadAntenna		Cable	Preamp		Limit	Over		
	Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	5795.000	97.69	32.19	6.10	36.89	99.09	125.20	-26.11	HORIZONTAL	Peak
2	5850.000	62.42	32.25	6.00	36.90	63.77	122.20	-58.43	HORIZONTAL	Peak
3	5860.000	62.44	32.27	5.96	36.90	63.77	109.40	-45.63	HORIZONTAL	Peak
4	5942.559	63.42	32.36	6.05	36.90	64.93	68.20	-3.27	HORIZONTAL	Peak

Test Mode: 04; Polarity: Vertical; Modulation:802.11n; Bandwidth:40MHz; Channel:High



		ReadAntenna		Cable	Preamp		Limit	Over		
	Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	5795.000	107.25	32.19	6.10	36.89	108.65	125.20	-16.55	VERTICAL	Peak
2	5850.000	61.75	32.25	6.00	36.90	63.10	122.20	-59.10	VERTICAL	Peak
3	5860.000	63.33	32.27	5.96	36.90	64.66	109.40	-44.74	VERTICAL	Peak
4	5930.167	63.50	32.34	6.00	36.90	64.94	68.20	-3.26	VERTICAL	Peak

Test Mode: 04; Polarity: Horizontal; Modulation:802.11ac; Bandwidth:20MHz; Channel:Low




		ReadAntenna		Cable	Preamp		Limit	Over		
	Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	5646.088	61.86	31.95	6.35	36.89	63.27	68.20	-4.93	HORIZONTAL	Peak
2	5715.000	60.35	32.04	6.33	36.89	61.83	109.40	-47.57	HORIZONTAL	Peak
3	5725.000	61.49	32.07	6.25	36.89	62.92	122.20	-59.28	HORIZONTAL	Peak
4	5745.000	102.84	32.10	6.20	36.89	104.25	125.20	-20.95	HORIZONTAL	Peak



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.


Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

Test Mode: 04; Polarity: Vertical; Modulation:802.11ac; Bandwidth:20MHz; Channel:Low



		ReadAntenna		Cable	Preamp		Limit	Over		
	Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	5645.257	62.26	31.95	6.35	36.89	63.67	68.20	-4.53	VERTICAL	Peak
2	5715.000	61.26	32.04	6.33	36.89	62.74	109.40	-46.66	VERTICAL	Peak
3	5725.000	63.59	32.07	6.25	36.89	65.02	122.20	-57.18	VERTICAL	Peak
4	5745.000	111.37	32.10	6.20	36.89	112.78	125.20	-12.42	VERTICAL	Peak


Test Mode: 04; Polarity: Horizontal; Modulation: 802.11ac; Bandwidth: 20MHz; Channel: High



Trace: (Discrete)


	Read	Antenna	Cable	Preamp		Limit	Over		
Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	5825.000	100.69	32.23	6.04	36.90	102.06	125.20	-23.14	HORIZONTAL Peak
2	5850.000	62.19	32.25	6.00	36.90	63.54	122.20	-58.66	HORIZONTAL Peak
3	5860.000	63.09	32.27	5.96	36.90	64.42	109.40	-44.98	HORIZONTAL Peak
4	5941.546	63.50	32.36	6.05	36.90	65.01	68.20	-3.19	HORIZONTAL Peak

Test Mode: 04; Polarity: Vertical; Modulation:802.11ac; Bandwidth:20MHz; Channel:High




		Read	Antenna	Cable	Preamp		Limit	Over		
	Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	5825.000	110.83	32.23	6.04	36.90	112.20	125.20	-13.00	VERTICAL	Peak
2	5850.000	62.68	32.25	6.00	36.90	64.03	122.20	-58.17	VERTICAL	Peak
3	5860.000	62.80	32.27	5.96	36.90	64.13	109.40	-45.27	VERTICAL	Peak
4	5926.496	64.61	32.34	6.00	36.90	66.05	68.20	-2.15	VERTICAL	Peak

Test Mode: 04; Polarity: Horizontal; Modulation:802.11ac; Bandwidth:40MHz; Channel:Low




		ReadAntenna		Cable	Preamp		Limit	Over		
	Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	5646.885	61.72	31.95	6.35	36.89	63.13	68.20	-5.07	HORIZONTAL	Peak
2	5715.000	60.89	32.04	6.33	36.89	62.37	109.40	-47.03	HORIZONTAL	Peak
3	5725.000	61.50	32.07	6.25	36.89	62.93	122.20	-59.27	HORIZONTAL	Peak
4	5755.000	98.25	32.10	6.20	36.89	99.66	125.20	-25.54	HORIZONTAL	Peak

Test Mode: 04; Polarity: Vertical; Modulation:802.11ac; Bandwidth:40MHz; Channel:Low




		ReadAntenna		Cable	Preamp		Limit	Over		
	Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	5645.354	62.47	31.95	6.35	36.89	63.88	68.20	-4.32	VERTICAL	Peak
2	5715.000	62.66	32.04	6.33	36.89	64.14	109.40	-45.26	VERTICAL	Peak
3	5725.000	67.16	32.07	6.25	36.89	68.59	122.20	-53.61	VERTICAL	Peak
4	5755.000	107.53	32.10	6.20	36.89	108.94	125.20	-16.26	VERTICAL	Peak

Test Mode: 04; Polarity: Horizontal; Modulation: 802.11ac; Bandwidth: 40MHz; Channel: High




		ReadAntenna	Cable	Preamp		Limit	Over			
	Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	5795.000	97.03	32.19	6.10	36.89	98.43	125.20	-26.77	HORIZONTAL	Peak
2	5850.000	62.43	32.25	6.00	36.90	63.78	122.20	-58.42	HORIZONTAL	Peak
3	5860.000	61.64	32.27	5.96	36.90	62.97	109.40	-46.43	HORIZONTAL	Peak
4	5942.559	63.36	32.36	6.05	36.90	64.87	68.20	-3.33	HORIZONTAL	Peak

Test Mode: 04; Polarity: Vertical; Modulation: 802.11ac; Bandwidth: 40MHz; Channel: High




		ReadAntenna		Cable	Preamp		Limit	Over		
	Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	5795.000	107.12	32.19	6.10	36.89	108.52	125.20	-16.68	VERTICAL	Peak
2	5850.000	62.36	32.25	6.00	36.90	63.71	122.20	-58.49	VERTICAL	Peak
3	5860.000	63.27	32.27	5.96	36.90	64.60	109.40	-44.80	VERTICAL	Peak
4	5928.747	63.22	32.34	6.00	36.90	64.66	68.20	-3.54	VERTICAL	Peak

Test Mode: 04; Polarity: Horizontal; Modulation:802.11ac; Bandwidth:80MHz; Channel:middle



		ReadAntenna		Cable	Preamp		Limit	Over		
	Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	5724.088	61.52	32.07	6.25	36.89	62.95	120.12	-57.17	HORIZONTAL	Peak
2	5775.000	94.22	32.16	6.10	36.89	95.59	125.20	-29.61	HORIZONTAL	Peak
3	5855.199	62.17	32.25	6.00	36.90	63.52	110.74	-47.22	HORIZONTAL	Peak
4	5937.803	62.24	32.34	6.00	36.90	63.68	68.20	-4.52	HORIZONTAL	Peak


Test Mode: 04; Polarity: Vertical; Modulation: 802.11ac; Bandwidth: 80MHz; Channel: middle



		ReadAntenna		Cable	Preamp		Limit	Over		
	Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	5722.280	64.07	32.07	6.25	36.89	65.50	116.00	-50.50	VERTICAL	Peak
2	5775.000	103.92	32.16	6.10	36.89	105.29	125.20	-19.91	VERTICAL	Peak
3	5856.741	62.86	32.27	5.96	36.90	64.19	110.31	-46.12	VERTICAL	Peak
4	5932.802	63.32	32.34	6.00	36.90	64.76	68.20	-3.44	VERTICAL	Peak

Test data for GW-5G01


Test Mode: 01; Polarity: Horizontal; Modulation:802.11a; Bandwidth:20MHz; Channel:Low



Trace: (Discrete)


		ReadAntenna		Cable	Preamp		Limit	Over		
	Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	5101.783	48.91	31.72	5.65	36.86	49.42	54.00	-4.58	HORIZONTAL	Average
2	5101.783	61.96	31.72	5.65	36.86	62.47	74.00	-11.53	HORIZONTAL	Peak
3	5149.980	48.66	31.72	5.62	36.86	49.14	54.00	-4.86	HORIZONTAL	Average
4	5149.980	60.76	31.72	5.62	36.86	61.24	74.00	-12.76	HORIZONTAL	Peak
5	5180.000	94.10	31.73	5.61	36.87	94.57	-----	-----	HORIZONTAL	Average
6 *	5180.000	102.99	31.73	5.61	36.87	103.46	68.20	35.26	HORIZONTAL	Peak

Test Mode: 01; Polarity: Vertical; Modulation:802.11a; Bandwidth:20MHz; Channel:Low




race: (Discrete)		Frequency (MHz)								
	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark	
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	5123.425	49.36	31.72	5.64	36.86	49.86	54.00	-4.14	VERTICAL	Average
2	5123.425	61.72	31.72	5.64	36.86	62.22	74.00	-11.78	VERTICAL	Peak
3	5149.980	49.19	31.72	5.62	36.86	49.67	54.00	-4.33	VERTICAL	Average
4	5149.980	61.19	31.72	5.62	36.86	61.67	74.00	-12.33	VERTICAL	Peak
5	5180.000	97.03	31.73	5.61	36.87	97.50	-----	-----	VERTICAL	Average
6 *	5180.000	106.34	31.73	5.61	36.87	106.81	68.20	38.61	VERTICAL	Peak

Test Mode: 01; Polarity: Horizontal; Modulation:802.11a; Bandwidth:20MHz; Channel:High




		ReadAntenna		Cable	Preamp		Limit	Over		
	Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	5240.000	92.67	31.75	5.74	36.87	93.29	-----	-----	HORIZONTAL	Average
2 *	5240.000	101.42	31.75	5.74	36.87	102.04	68.20	33.84	HORIZONTAL	Peak
3	5350.020	48.66	31.77	6.05	36.88	49.60	54.00	-4.40	HORIZONTAL	Average
4	5350.020	60.41	31.77	6.05	36.88	61.35	74.00	-12.65	HORIZONTAL	Peak
5	5352.487	61.02	31.77	6.05	36.88	61.96	74.00	-12.04	HORIZONTAL	Peak
6	5356.029	48.73	31.78	6.03	36.88	49.66	54.00	-4.34	HORIZONTAL	Average

Test Mode: 01; Polarity: Vertical; Modulation:802.11a; Bandwidth:20MHz; Channel:High



		ReadAntenna		Cable	Preamp		Limit	Over		
	Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	5240.000	96.91	31.75	5.74	36.87	97.53	-----	-----	VERTICAL	Average
2 *	5240.000	105.89	31.75	5.74	36.87	106.51	68.20	38.31	VERTICAL	Peak
3	5350.020	48.72	31.77	6.05	36.88	49.66	54.00	-4.34	VERTICAL	Average
4	5350.020	60.79	31.77	6.05	36.88	61.73	74.00	-12.27	VERTICAL	Peak
5	5351.070	49.04	31.77	6.05	36.88	49.98	54.00	-4.02	VERTICAL	Average
6	5351.920	61.09	31.77	6.05	36.88	62.03	74.00	-11.97	VERTICAL	Peak


Test Mode: 01; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:Low



Trace: (Discrete)


	Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	5101.089	48.87	31.72	5.65	36.86	49.38	54.00	-4.62	HORIZONTAL	Average
2	5101.089	61.44	31.72	5.65	36.86	61.95	74.00	-12.05	HORIZONTAL	Peak
3	5149.980	48.67	31.72	5.62	36.86	49.15	54.00	-4.85	HORIZONTAL	Average
4	5149.980	61.08	31.72	5.62	36.86	61.56	74.00	-12.44	HORIZONTAL	Peak
5	5180.000	87.41	31.73	5.61	36.87	87.88	68.20	19.68	HORIZONTAL	Average
6 *	5180.000	100.25	31.73	5.61	36.87	100.72	68.20	32.52	HORIZONTAL	Peak

Test Mode: 01; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:Low




race: (Discrete)	Frequency (MHz)									
		Read	Antenna	Cable	Preamp		Limit	Over		
	Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	5131.689	49.20	31.72	5.63	36.86	49.69	54.00	-4.31	VERTICAL	Average
2	5131.689	62.11	31.72	5.63	36.86	62.60	74.00	-11.40	VERTICAL	Peak
3	5149.980	49.19	31.72	5.62	36.86	49.67	54.00	-4.33	VERTICAL	Average
4	5149.980	61.07	31.72	5.62	36.86	61.55	74.00	-12.45	VERTICAL	Peak
5	5180.000	91.94	31.73	5.61	36.87	92.41	-----	-----	VERTICAL	Average
6 *	5180.000	105.01	31.73	5.61	36.87	105.48	68.20	37.28	VERTICAL	Peak

Test Mode: 01; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:High



		ReadAntenna		Cable	Preamp		Limit	Over		
	Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	5240.000	86.80	31.75	5.74	36.87	87.42	-----	-----	HORIZONTAL	Average
2 *	5240.000	100.05	31.75	5.74	36.87	100.67	68.20	32.47	HORIZONTAL	Peak
3	5350.020	48.39	31.77	6.05	36.88	49.33	54.00	-4.67	HORIZONTAL	Average
4	5350.020	60.23	31.77	6.05	36.88	61.17	74.00	-12.83	HORIZONTAL	Peak
5	5358.582	48.65	31.78	6.03	36.88	49.58	54.00	-4.42	HORIZONTAL	Average
6	5358.582	60.79	31.78	6.03	36.88	61.72	74.00	-12.28	HORIZONTAL	Peak


Test Mode: 01; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:High



Trace: (Discrete)

	Freq	ReadAntenna	Cable	Preamp		Limit	Over		
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	5240.000	91.74	31.75	5.74	36.87	92.36	-----	-----	VERTICAL
2 *	5240.000	104.52	31.75	5.74	36.87	105.14	68.20	36.94	VERTICAL
3	5350.020	48.73	31.77	6.05	36.88	49.67	54.00	-4.33	VERTICAL
4	5350.020	60.39	31.77	6.05	36.88	61.33	74.00	-12.67	VERTICAL
5	5351.778	48.80	31.77	6.05	36.88	49.74	54.00	-4.26	VERTICAL
6	5359.858	61.60	31.78	6.03	36.88	62.53	74.00	-11.47	VERTICAL


Test Mode: 01; Polarity: Horizontal; Modulation:802.11n; Bandwidth:40MHz; Channel:Low



Trace: (Discrete)


		ReadAntenna		Cable	Preamp		Limit	Over		
	Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	5101.423	49.04	31.72	5.65	36.86	49.55	54.00	-4.45	HORIZONTAL	Average
2	5101.423	61.91	31.72	5.65	36.86	62.42	74.00	-11.58	HORIZONTAL	Peak
3	5149.980	48.49	31.72	5.62	36.86	48.97	54.00	-5.03	HORIZONTAL	Average
4	5149.980	60.86	31.72	5.62	36.86	61.34	74.00	-12.66	HORIZONTAL	Peak
5	5190.000	79.83	31.73	5.60	36.87	80.29	-----	-----	HORIZONTAL	Average
6 *	5190.000	98.60	31.73	5.60	36.87	99.06	68.20	30.86	HORIZONTAL	Peak

Test Mode: 01; Polarity: Vertical; Modulation:802.11n; Bandwidth:40MHz; Channel:Low



Race: (Discrete)	Frequency (MHz)									
	Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	5147.067	61.48	31.72	5.62	36.86	61.96	74.00	-12.04	VERTICAL	Peak
2	5149.461	49.41	31.72	5.62	36.86	49.89	54.00	-4.11	VERTICAL	Average
3	5149.980	48.87	31.72	5.62	36.86	49.35	54.00	-4.65	VERTICAL	Average
4	5149.980	60.72	31.72	5.62	36.86	61.20	74.00	-12.80	VERTICAL	Peak
5	5190.000	82.97	31.73	5.60	36.87	83.43	-----	-----	VERTICAL	Average
6 *	5190.000	102.15	31.73	5.60	36.87	102.61	68.20	34.41	VERTICAL	Peak


Test Mode: 01; Polarity: Horizontal; Modulation:802.11n; Bandwidth:40MHz; Channel:High



Trace: (Discrete)


		ReadAntenna		Cable	Preamp		Limit	Over		
	Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	5230.000	78.50	31.74	5.70	36.87	79.07	-----	-----	HORIZONTAL	Average
2 *	5230.000	97.14	31.74	5.70	36.87	97.71	68.20	29.51	HORIZONTAL	Peak
3	5350.020	48.41	31.77	6.05	36.88	49.35	54.00	-4.65	HORIZONTAL	Average
4	5350.020	59.97	31.77	6.05	36.88	60.91	74.00	-13.09	HORIZONTAL	Peak
5	5352.857	61.09	31.77	6.05	36.88	62.03	74.00	-11.97	HORIZONTAL	Peak
6	5358.051	48.65	31.78	6.03	36.88	49.58	54.00	-4.42	HORIZONTAL	Average

Test Mode: 01; Polarity: Vertical; Modulation:802.11n; Bandwidth:40MHz; Channel:High



race: (Discrete)	Frequency (MHz)									
	Freq	ReadAntenna	Cable	Preamp		Limit	Over	Pol/Phase	Remark	
		Level	Factor	Loss	Factor	Level	Line			Limit
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	5230.000	83.01	31.74	5.70	36.87	83.58	-----	-----	VERTICAL	Average
2 *	5230.000	102.36	31.74	5.70	36.87	102.93	68.20	34.73	VERTICAL	Peak
3	5350.020	48.65	31.77	6.05	36.88	49.59	54.00	-4.41	VERTICAL	Average
4	5350.020	60.39	31.77	6.05	36.88	61.33	74.00	-12.67	VERTICAL	Peak
5	5354.155	61.25	31.78	6.03	36.88	62.18	74.00	-11.82	VERTICAL	Peak
6	5360.000	48.73	31.78	6.03	36.88	49.66	54.00	-4.34	VERTICAL	Average


Test Mode: 01; Polarity: Horizontal; Modulation:802.11ac; Bandwidth:20MHz; Channel:Low



Trace: (Discrete)

	Read	Antenna	Cable	Preamp		Limit	Over		
Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	5129.896	48.99	31.72	5.63	36.86	49.48	54.00	-4.52	HORIZONTAL Average
2	5129.896	61.98	31.72	5.63	36.86	62.47	74.00	-11.53	HORIZONTAL Peak
3	5149.980	48.56	31.72	5.62	36.86	49.04	54.00	-4.96	HORIZONTAL Average
4	5149.980	60.58	31.72	5.62	36.86	61.06	74.00	-12.94	HORIZONTAL Peak
5	5180.000	77.96	31.73	5.61	36.87	78.43	-----	-----	HORIZONTAL Average
6 *	5180.000	101.01	31.73	5.61	36.87	101.48	68.20	33.28	HORIZONTAL Peak


Test Mode: 01; Polarity: Vertical; Modulation: 802.11ac; Bandwidth: 20MHz; Channel: Low



Trace: (Discrete)


	Freq	ReadAntenna Level Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Pol/Phase	Remark	
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	5105.351	62.27	31.72	5.65	36.86	62.78	74.00	-11.22	VERTICAL	Peak
2	5105.450	49.12	31.72	5.65	36.86	49.63	54.00	-4.37	VERTICAL	Average
3	5149.980	48.65	31.72	5.62	36.86	49.13	54.00	-4.87	VERTICAL	Average
4	5149.980	60.19	31.72	5.62	36.86	60.67	74.00	-13.33	VERTICAL	Peak
5	5180.000	80.94	31.73	5.61	36.87	81.41	-----	-----	VERTICAL	Average
6 *	5180.000	104.12	31.73	5.61	36.87	104.59	68.20	36.39	VERTICAL	Peak

Test Mode: 01; Polarity: Horizontal; Modulation: 802.11ac; Bandwidth: 20MHz; Channel: High



	Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Limit Level	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dB		
1	5240.000	77.12	31.75	5.74	36.87	77.74	-----	HORIZONTAL	Average
2 *	5240.000	99.27	31.75	5.74	36.87	99.89	68.20	31.69	HORIZONTAL Peak
3	5350.020	48.39	31.77	6.05	36.88	49.33	54.00	-4.67	HORIZONTAL Average
4	5350.020	60.52	31.77	6.05	36.88	61.46	74.00	-12.54	HORIZONTAL Peak
5	5355.179	61.36	31.78	6.03	36.88	62.29	74.00	-11.71	HORIZONTAL Peak
6	5359.716	48.69	31.78	6.03	36.88	49.62	54.00	-4.38	HORIZONTAL Average

Test Mode: 01; Polarity: Vertical; Modulation:802.11ac; Bandwidth:20MHz; Channel:High



Trace: (Discrete)

	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	5240.000	81.37	31.75	5.74	36.87	81.99	-----	-----	VERTICAL	Average
2 *	5240.000	104.05	31.75	5.74	36.87	104.67	68.20	36.47	VERTICAL	Peak
3	5350.020	48.61	31.77	6.05	36.88	49.55	54.00	-4.45	VERTICAL	Average
4	5350.020	60.34	31.77	6.05	36.88	61.28	74.00	-12.72	VERTICAL	Peak
5	5353.762	61.35	31.77	6.05	36.88	62.29	74.00	-11.71	VERTICAL	Peak
6	5359.007	48.72	31.78	6.03	36.88	49.65	54.00	-4.35	VERTICAL	Average