

## APPENDIX D: SAR TISSUE SPECIFICATIONS

### Measurement Procedure for Tissue verification:

- 1) The network analyzer and probe system was configured and calibrated.
- 2) The probe was immersed in the tissue. The tissue was placed in a nonmetallic container. Trapped air bubbles beneath the flange were minimized by placing the probe at a slight angle.
- 3) The complex admittance with respect to the probe aperture was measured
- 4) The complex relative permittivity  $\epsilon'$  can be calculated from the below equation (Pournaropoulos and Misra):

$$Y = \frac{j2\omega\epsilon_r\epsilon_0}{[\ln(b/a)]^2} \int_a^b \int_a^b \int_0^\pi \cos\phi' \frac{\exp[-j\omega r(\mu_0\epsilon_r'\epsilon_0)^{1/2}]}{r} d\phi' d\rho' d\rho$$

where  $Y$  is the admittance of the probe in contact with the sample, the primed and unprimed coordinates refer to source and observation points, respectively,  $r^2 = \rho^2 + \rho'^2 - 2\rho\rho'\cos\phi'$ ,  $\omega$  is the angular frequency, and  $j = \sqrt{-1}$ .

### 3 Composition / Information on ingredients

#### 3.2 Mixtures

**Description:** Aqueous solution with surfactants and inhibitors

**Declarable, or hazardous components:**

|                                                                        |                                                                                                                       |           |
|------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------|-----------|
| CAS: 107-21-1<br>EINECS: 203-473-3<br>Reg.nr.: 01-2119456816-28-0000   | <b>Ethanediol</b><br>STOT RE 2, H373;<br>Acute Tox. 4, H302                                                           | >1.0-4.9% |
| CAS: 68608-26-4<br>EINECS: 271-781-5<br>Reg.nr.: 01-2119527859-22-0000 | <b>Sodium petroleum sulfonate</b><br>Eye Irrit. 2, H319                                                               | < 2.9%    |
| CAS: 107-41-5<br>EINECS: 203-489-0<br>Reg.nr.: 01-2119539582-35-0000   | <b>Hexylene Glycol / 2-Methyl-pentane-2,4-diol</b><br>Skin Irrit. 2, H315; Eye Irrit. 2, H319                         | < 2.9%    |
| CAS: 68920-66-1<br>NLP: 500-236-9<br>Reg.nr.: 01-2119489407-26-0000    | <b>Alkoxyated alcohol, &gt; C<sub>16</sub></b><br>Aquatic Chronic 2, H411;<br>Skin Irrit. 2, H315; Eye Irrit. 2, H319 | < 2.0%    |

**Additional information:**

For the wording of the listed risk phrases refer to section 16.

Not mentioned CAS-, EINECS- or registration numbers are to be regarded as Proprietary/Confidential.

The specific chemical identity and/or exact percentage concentration of proprietary components is withheld as a trade secret.

**Figure D-1**

Note: Liquid recipes are proprietary SPEAG. Since the composition is approximate to the actual liquids utilized, the manufacturer tissue-equivalent liquid data sheets are provided below.

|                                     |                                                                                                                                                                                                                                                                                                        |                                          |
|-------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------|
| <b>FCC ID</b> C3K00002101           | <b>RF EXPOSURE PART 1 TEST REPORT</b>                                                                                                                                                                                                                                                                  | <b>Approved by:</b><br>Technical Manager |
| <b>DUT Type:</b><br>Wireless Module | This report is Blockchain Verified. To verify the report authenticity, please visit <a href="https://www.blockchain-verified.com">HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM</a> or by clicking on the Blockchain logo.  | <b>APPENDIX D:</b><br>Page 1 of 2        |

Schmid & Partner Engineering AG

s p e a g

Zeughausstrasse 43, 8004 Zurich, Switzerland  
Phone +41 44 245 9700, Fax +41 44 245 9779  
www.speag.swiss, info@speag.swiss

### Measurement Certificate / Material Test

|              |                                                |
|--------------|------------------------------------------------|
| Item Name    | Head Tissue Simulating Liquid (HBL600-10000V6) |
| Product No.  | SL AAH U16 CB (Batch: 260423-3)                |
| Manufacturer | SPEAG                                          |

### Measurement Method

TSL dielectric parameters measured using calibrated DAK probe.

### Target Parameters

Target parameters as defined in the IEEE 1528 and IEC 62209 compliance standards.

### Test Condition

Ambient Condition 22°C ; 30% humidity

TSL Temperature 22°C

Test Date 29-Apr-26

Operator CL



### Additional Information

TSL Density

TSL Heat-capacity

### Results

| f [MHz] | Measured |      |       | Target |       | Diff.to Target [%] |         |
|---------|----------|------|-------|--------|-------|--------------------|---------|
|         | e'       | e''  | sigma | eps    | sigma | Δ-eps              | Δ-sigma |
| 600     | 44.9     | 24.7 | 0.82  | 42.7   | 0.88  | 5.1                | -7.0    |
| 750     | 44.4     | 20.9 | 0.87  | 41.9   | 0.89  | 5.9                | -2.6    |
| 800     | 44.2     | 20.0 | 0.89  | 41.7   | 0.90  | 6.0                | -0.8    |
| 825     | 44.2     | 19.6 | 0.90  | 41.6   | 0.91  | 6.3                | -0.7    |
| 835     | 44.2     | 19.4 | 0.91  | 41.5   | 0.91  | 6.4                | -0.2    |
| 850     | 44.1     | 19.2 | 0.91  | 41.5   | 0.92  | 6.3                | -0.7    |
| 900     | 44.0     | 18.5 | 0.93  | 41.5   | 0.97  | 6.0                | -4.1    |
| 1400    | 43.0     | 14.7 | 1.14  | 40.6   | 1.18  | 5.9                | -3.3    |
| 1450    | 43.0     | 14.5 | 1.17  | 40.5   | 1.20  | 6.2                | -2.5    |
| 1600    | 42.7     | 14.0 | 1.24  | 40.3   | 1.28  | 5.9                | -3.5    |
| 1625    | 42.7     | 13.9 | 1.26  | 40.3   | 1.30  | 6.0                | -3.0    |
| 1640    | 42.7     | 13.9 | 1.27  | 40.3   | 1.31  | 6.1                | -2.8    |
| 1650    | 42.7     | 13.9 | 1.27  | 40.2   | 1.31  | 6.1                | -3.3    |
| 1700    | 42.6     | 13.7 | 1.30  | 40.2   | 1.34  | 6.1                | -3.1    |
| 1750    | 42.5     | 13.6 | 1.33  | 40.1   | 1.37  | 6.0                | -3.0    |
| 1800    | 42.4     | 13.6 | 1.36  | 40.0   | 1.40  | 6.0                | -2.9    |
| 1810    | 42.4     | 13.5 | 1.37  | 40.0   | 1.40  | 6.0                | -2.1    |
| 1825    | 42.4     | 13.5 | 1.38  | 40.0   | 1.40  | 6.0                | -1.4    |
| 1850    | 42.4     | 13.5 | 1.39  | 40.0   | 1.40  | 6.0                | -0.7    |
| 1900    | 42.3     | 13.4 | 1.42  | 40.0   | 1.40  | 5.7                | 1.4     |
| 1950    | 42.2     | 13.4 | 1.45  | 40.0   | 1.40  | 5.5                | 3.6     |
| 2000    | 42.2     | 13.3 | 1.48  | 40.0   | 1.40  | 5.5                | 5.7     |
| 2050    | 42.1     | 13.3 | 1.51  | 39.9   | 1.44  | 5.5                | 4.5     |
| 2100    | 42.0     | 13.3 | 1.55  | 39.8   | 1.49  | 5.5                | 4.1     |
| 2150    | 42.0     | 13.2 | 1.58  | 39.7   | 1.53  | 5.7                | 3.0     |
| 2200    | 41.9     | 13.2 | 1.62  | 39.6   | 1.58  | 5.7                | 2.7     |
| 2250    | 41.8     | 13.2 | 1.65  | 39.6   | 1.62  | 5.7                | 1.7     |
| 2300    | 41.8     | 13.2 | 1.69  | 39.5   | 1.67  | 5.9                | 1.4     |
| 2350    | 41.7     | 13.2 | 1.73  | 39.4   | 1.71  | 5.9                | 1.1     |
| 2400    | 41.6     | 13.2 | 1.77  | 39.3   | 1.76  | 5.9                | 0.8     |
| 2450    | 41.6     | 13.3 | 1.81  | 39.2   | 1.80  | 6.1                | 0.6     |
| 2500    | 41.5     | 13.3 | 1.85  | 39.1   | 1.85  | 6.0                | -0.2    |
| 2550    | 41.4     | 13.3 | 1.89  | 39.1   | 1.91  | 6.0                | -1.0    |
| 2600    | 41.3     | 13.3 | 1.93  | 39.0   | 1.96  | 5.9                | -1.7    |



|       |      |      |       |      |       |      |      |
|-------|------|------|-------|------|-------|------|------|
| 3500  | 39.8 | 13.9 | 2.71  | 37.9 | 2.91  | 4.9  | -7.1 |
| 3700  | 39.5 | 14.0 | 2.89  | 37.7 | 3.12  | 4.7  | -7.3 |
| 5200  | 37.0 | 15.7 | 4.54  | 36.0 | 4.66  | 2.7  | -2.4 |
| 5250  | 36.8 | 15.7 | 4.80  | 35.9 | 4.71  | 2.6  | -2.4 |
| 5300  | 36.7 | 15.8 | 4.65  | 35.9 | 4.76  | 2.4  | -2.3 |
| 5500  | 36.3 | 16.0 | 4.88  | 35.6 | 4.96  | 1.8  | -1.6 |
| 5600  | 36.1 | 16.1 | 5.01  | 35.5 | 5.07  | 1.6  | -1.1 |
| 5700  | 35.9 | 16.2 | 5.14  | 35.4 | 5.17  | 1.4  | -0.6 |
| 5800  | 35.8 | 16.3 | 5.25  | 35.3 | 5.27  | 1.3  | -0.3 |
| 6000  | 35.6 | 16.4 | 5.47  | 35.1 | 5.48  | 1.4  | -0.2 |
| 6500  | 34.6 | 17.0 | 6.14  | 34.5 | 6.07  | 0.4  | 1.1  |
| 7000  | 33.8 | 17.3 | 6.75  | 33.9 | 6.65  | -0.3 | 1.6  |
| 7500  | 32.9 | 17.7 | 7.37  | 33.3 | 7.24  | -1.2 | 1.7  |
| 8000  | 32.0 | 17.9 | 7.98  | 32.7 | 7.84  | -2.1 | 1.8  |
| 8500  | 31.2 | 18.2 | 8.61  | 32.1 | 8.45  | -3.0 | 1.8  |
| 9000  | 30.3 | 18.5 | 9.24  | 31.5 | 9.08  | -3.9 | 1.8  |
| 9500  | 29.5 | 18.6 | 9.85  | 31.0 | 9.71  | -4.8 | 1.5  |
| 10000 | 28.7 | 18.8 | 10.46 | 30.4 | 10.38 | -5.7 | 1.0  |

Figure D-2  
600– 10000 MHz Head Tissue Equivalent Matter

|                              |                                                                                                                                                                                                                                                                                                        |                                   |
|------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------|
| FCC ID C3K00002101           | RF EXPOSURE PART 1 TEST REPORT                                                                                                                                                                                                                                                                         | Approved by:<br>Technical Manager |
| DUT Type:<br>Wireless Module | This report is Blockchain Verified. To verify the report authenticity, please visit <a href="https://www.blockchain-verified.com">https://www.blockchain-verified.com</a> or by clicking on the Blockchain logo.  | APPENDIX D:<br>Page 2 of 2        |