

**ELEMENT WASHINGTON DC LLC**

7185 Oakland Mills Road, Columbia, MD 21046 USA

Tel. 410.290.6652 / Fax 410.290.6654

<http://www.element.com>**RF EXPOSURE EVALUATION**
Maximum Permissible Exposure (MPE)**Applicant Name:**Microsoft Corporation
One Microsoft Way
Redmond, WA 98052
United States**Date of Testing:**

12/16/2025 - 02/02/2026

Test Report Issue Date:

02/27/2025

Test Site/Location:

Element Lab. Columbia, MD, USA

Test Report Serial No.:

1M2511240098-15-R1.C3K

FCC ID:**C3K2076****APPLICANT:****Microsoft Corporation****EUT Type:**

Portable Computing Device

FCC Classification:Digital Transmission System (DTS)
Part 15 Spread Spectrum Transmitter (DSS)
Unlicensed National Information Infrastructure TX (NII)
15E 6 GHz Low Power Dual Client (6CD)**FCC Rule Part:**

FCC Part 1 (§1.1310) and Part 2 (§2.1091)

Test Procedure(s):

KDB 447498 D01 v06

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in FCC KDB 447498 D01. Test results reported herein relate only to the item(s) tested.

This revised Test Report (S/N: 1M2511240098-15-R1.C3K) supersedes and replaces the previously issued test report (S/N: 1M2511240098-15.C3K) on the same subject device for the same type of testing as indicated. Please discard or destroy the previously issued test report(s) and dispose of it accordingly.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

RJ Ortanez
Executive Vice President

FCC ID: C3K2076	MAXIMUM PERMISSIBLE EXPOSURE REPORT		Approved by: Technical Manager
Test Report S/N: 1M2511240098-15-R1.C3K	Test Dates: 12/16/2025 - 02/02/2026	EUT Type: Portable Computing Device	Page 1 of 7

© 2026 ELEMENT

V 11.3 5/14/2025

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without written permission from Element. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.



TABLE OF CONTENTS

1.0 RF EXPOSURE EVALUATION – MAXIMUM PERMISSIBLE EXPOSURE (MPE) 4

1.1 Introduction 4

1.2 EUT Description.....4

1.3 Procedure 5

2.0 CONCLUSION 7

FCC ID: C3K2076	MAXIMUM PERMISSIBLE EXPOSURE REPORT		Approved by: Technical Manager
Test Report S/N: 1M2511240098-15-R1.C3K	Test Dates: 12/16/2025 - 02/02/2026	EUT Type: Portable Computing Device	Page 2 of 7

TEST REPORT REVISION HISTORY

Rev. No.	Description	Issue Date	Revised By
-	Initial Release	3/11/2026	WKR0000005826
1	Addressed TCB reviewer comments	3/24/2026	WKR0000005874

FCC ID: C3K2076	MAXIMUM PERMISSIBLE EXPOSURE REPORT		Approved by: Technical Manager
Test Report S/N: 1M2511240098-15-R1.C3K	Test Dates: 12/16/2025 - 02/02/2026	EUT Type: Portable Computing Device	Page 3 of 7

1.0 RF EXPOSURE EVALUATION – MAXIMUM PERMISSIBLE EXPOSURE (MPE)

1.1 Introduction

This document is prepared to show compliance with the RF Exposure requirements as required in §1.1310 of the FCC Rules and Regulations.

The limit for Maximum Permissible Exposure (MPE), specified in FCC §1.1310, is listed in Table 1-1. According to FCC §1.1310: the criteria listed in the following table shall be used to evaluate the environmental impact of human exposure to radio-frequency (RF) radiation as specified in §1.1307(b).

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (Minutes)
(A) Limits For Occupational / Control Exposures (f = frequency)				
30-300	61.4	0.163	1.0	6
300-1500	...	...	f/300	6
1500-100,000	...	...	5.0	6
(B) Limits For General Population / Uncontrolled Exposure (f = frequency)				
30-300	27.5	0.073	0.2	30
300-1500	...	...	f/1500	30
1500-100,000	...	...	1.0	30

Table 1-1. Limits for Maximum Permissible Exposure (MPE)

1.2 EUT Description

The **Microsoft Corporation FCC ID: C3K2076** is a Portable Computing Device containing 2.4GHz transmit output ports, 5GHz, and 6GHz transmit output ports capable for transmitting 802.11a/b/g/n/ac/ax/be modes operation. This MPE evaluation will cover RF Exposure for simultaneous transmission modes of transmitters operating at maximum power.

EUT:

Company Name: Microsoft Corporation

FCC ID: C3K2076

Antenna(s): Please see technical description for list of available antenna options

FCC ID: C3K2076	MAXIMUM PERMISSIBLE EXPOSURE REPORT		Approved by: Technical Manager
Test Report S/N: 1M2511240098-15-R1.C3K	Test Dates: 12/16/2025 - 02/02/2026	EUT Type: Portable Computing Device	Page 4 of 7

1.3 Procedure

The procedure used to determine the RF power density was based upon a calculation for determining compliance with the MPE requirements.

The power generated by each transmitter used in this product was initially measured by a power meter or spectrum analyzer and the powers were recorded. Through use of the Friis transmission formula and knowledge of the maximum antenna gain to be used, the power density level is calculated at a distance of 20cm.

Friis Transmission Formula

Friis transmission formula: $P_d = (P_{out} * G) / (4\pi r^2)$

Where,

P_d = Power Density (mW/cm²)

π = 3.1416

P_{out} = output power to antenna (mW)

r = distance between observation point and center of the radiator (cm)

G = gain of antenna in linear scale

Calculated MPE

The power density limit for General Population/Uncontrolled Exposure at each frequency is determined based on the information in Table 1-1.

There is no co-location between the electric fields of any two transmitters therefore following power densities are calculated for each individual transmitter by frequency at 20cm spacing:

Frequency	2412 MHz		
FCC Limit	1.000 mW/cm ²		
Distance (cm), R =	20 cm		
Power (dBm), P =	19 dBm	79.43 mW	
TX Ant Gain (dBi), G =	5.63 dBi		
Power Density (S) =	0.058 mW/cm ²	(at 20cm)	
Minimum Distance =	4.8 cm		

Table 1-2. Calculated MPE Data for WIFI 2.4GHz (MIMO)

Frequency	5180 MHz		
Limit	1.000 mW/cm ²		
Distance (cm), R =	20 cm		
Power (dBm), P =	18 dBm	63.10 mW	
TX Ant Gain (dBi), G =	7.72 dBi		
Power Density (S) =	0.074 mW/cm ²	(at 20cm)	
Minimum Distance =	5.4 cm		

Table 1-3. Calculated MPE Data for WIFI 5GHz (MIMO)

FCC ID: C3K2076	MAXIMUM PERMISSIBLE EXPOSURE REPORT		Approved by: Technical Manager
Test Report S/N: 1M2511240098-15-R1.C3K	Test Dates: 12/16/2025 - 02/02/2026	EUT Type: Portable Computing Device	Page 5 of 7

Frequency	5935 MHz		
Limit	1.000 mW/cm ²		
Distance (cm), R =	20 cm		
Power (dBm), P =	7 dBm	5.01 mW	
TX Ant Gain (dBi), G =	8.41 dBi		
Power Density (S) =	0.007 mW/cm ²	(at 20cm)	
Minimum Distance =	1.7 cm		

Table 1-4. Calculated MPE Data for WIFI 6GHz (MIMO)

	Power Density (mW/cm ²)	Limit (mW/cm ²)	Percent MPE Used (%)
2.4GHz MIMO	0.058	1.000	5.78
5G MIMO	0.074	1.000	7.43
Total			13.20

Table 1-5. Co-location MPE Data for Simultaneous Transmission

FCC ID: C3K2076	MAXIMUM PERMISSIBLE EXPOSURE REPORT		Approved by: Technical Manager
Test Report S/N: 1M2511240098-15-R1.C3K	Test Dates: 12/16/2025 - 02/02/2026	EUT Type: Portable Computing Device	Page 6 of 7

2.0 CONCLUSION

The device meets the mobile RF exposure limit at a 20cm separation distance as specified in §2.1091 of the FCC Rules and Regulations. An appropriate RF exposure compliance statement will be placed in the user's manual.

FCC ID: C3K2076	MAXIMUM PERMISSIBLE EXPOSURE REPORT		Approved by: Technical Manager
Test Report S/N: 1M2511240098-15-R1.C3K	Test Dates: 12/16/2025 - 02/02/2026	EUT Type: Portable Computing Device	Page 7 of 7