






Plot 7-105. Average Conducted Power (2Mbps – Ch. 78) – DUAL ANT2




Plot 7-106. Average Conducted Power (3Mbps – Ch. 0) – DUAL ANT2

FCC ID: C3K2076 IC: 3048A-2076	MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Technical Manager
Test Report S/N: 1M2511240098-05-R3.C3K	Test Dates: 12/16/2025 - 02/02/2026	EUT Type: Portable Computing Device	Page 73 of 139



Plot 7-107. Average Conducted Power (3Mbps – Ch. 39) – DUAL ANT2



Plot 7-108. Average Conducted Power (3Mbps – Ch. 78) – DUAL ANT2

FCC ID: C3K2076 IC: 3048A-2076	MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Technical Manager
Test Report S/N: 1M2511240098-05-R3.C3K	Test Dates: 12/16/2025 - 02/02/2026	EUT Type: Portable Computing Device	Page 74 of 139

7.4 Band Edge Compliance

Test Overview and Limits

EUT operates in hopping and non-hopping transmission mode. Measurement is taken at the highest point located outside of the emission bandwidth. **The maximum permissible out-of-band emission level is 20 dBc.**

Test Procedure Used

ANSI C63.10-2020 – Section 6.10.4

Test Settings

1. Start and stop frequency were set such that the band edge would be placed in the center of the plot
2. Span was set large enough so as to capture all out of band emissions near the band edge
3. RBW = 100kHz
4. VBW = 300kHz
5. Detector = Peak
6. Number of sweep points $\geq 2 \times \text{Span/RBW}$
7. Trace mode = max hold
8. Sweep time = auto couple
9. The trace was allowed to stabilize

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-3. Test Instrument & Measurement Setup

Test Notes

Out of band conducted spurious emissions at the band edge were investigated for all data rates in hopping and non-hopping modes. The worst case emissions were found with the EUT transmitting at 3 Mbps. Band edge emissions were also investigated with the EUT transmitting in all data rates. Plots of the worst case emissions are shown below.

FCC ID: C3K2076 IC: 3048A-2076	MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Technical Manager
Test Report S/N: 1M2511240098-05-R3.C3K	Test Dates: 12/16/2025 - 02/02/2026	EUT Type: Portable Computing Device	Page 75 of 139

SISO ANT 1




Plot 7-109. Band Edge Plot (Bluetooth with Hopping Disabled, 3 Mbps – Ch. 0) – SISO ANT1



Plot 7-110. Band Edge Plot (Bluetooth with Hopping Disabled, 3 Mbps – Ch. 78) – SISO ANT1

FCC ID: C3K2076 IC: 3048A-2076	MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Technical Manager
Test Report S/N: 1M2511240098-05-R3.C3K	Test Dates: 12/16/2025 - 02/02/2026	EUT Type: Portable Computing Device	Page 76 of 139



Plot 7-111. Band Edge Plot (Bluetooth with Hopping Enabled, 3 Mbps) – SISO ANT1



Plot 7-112. Band Edge Plot (Bluetooth with Hopping Enabled, 3 Mbps) – SISO ANT1

FCC ID: C3K2076 IC: 3048A-2076	MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Technical Manager
Test Report S/N: 1M2511240098-05-R3.C3K	Test Dates: 12/16/2025 - 02/02/2026	EUT Type: Portable Computing Device	Page 77 of 139

SISO ANT 2



Plot 7-113. Band Edge Plot (Bluetooth with Hopping Disabled, 3 Mbps – Ch. 0) – SISO ANT2



Plot 7-114. Band Edge Plot (Bluetooth with Hopping Disabled, 3 Mbps – Ch. 78) – SISO ANT2

FCC ID: C3K2076 IC: 3048A-2076	MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Technical Manager
Test Report S/N: 1M2511240098-05-R3.C3K	Test Dates: 12/16/2025 - 02/02/2026	EUT Type: Portable Computing Device	Page 78 of 139



Plot 7-115. Band Edge Plot (Bluetooth with Hopping Enabled, 3 Mbps) – SISO ANT2




Plot 7-116. Band Edge Plot (Bluetooth with Hopping Enabled, 3 Mbps) – SISO ANT2

FCC ID: C3K2076 IC: 3048A-2076	MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Technical Manager
Test Report S/N: 1M2511240098-05-R3.C3K	Test Dates: 12/16/2025 - 02/02/2026	EUT Type: Portable Computing Device	Page 79 of 139

DUAL ANT 1



Plot 7-117. Band Edge Plot (Bluetooth with Hopping Disabled, 3 Mbps – Ch. 0) – DUAL ANT1




Plot 7-118. Band Edge Plot (Bluetooth with Hopping Disabled, 3 Mbps – Ch. 78) – DUAL ANT1

FCC ID: C3K2076 IC: 3048A-2076	MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Technical Manager
Test Report S/N: 1M2511240098-05-R3.C3K	Test Dates: 12/16/2025 - 02/02/2026	EUT Type: Portable Computing Device	Page 80 of 139




Plot 7-119. Band Edge Plot (Bluetooth with Hopping Enabled, 3 Mbps) – DUAL ANT1




Plot 7-120. Band Edge Plot (Bluetooth with Hopping Enabled, 3 Mbps) – DUAL ANT1

FCC ID: C3K2076 IC: 3048A-2076	MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Technical Manager
Test Report S/N: 1M2511240098-05-R3.C3K	Test Dates: 12/16/2025 - 02/02/2026	EUT Type: Portable Computing Device	Page 81 of 139

DUAL ANT 2




Plot 7-121. Band Edge Plot (Bluetooth with Hopping Disabled, 3 Mbps – Ch. 0) – DUAL ANT2



Plot 7-122. Band Edge Plot (Bluetooth with Hopping Disabled, 3 Mbps – Ch. 78) – DUAL ANT2

FCC ID: C3K2076 IC: 3048A-2076	MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Technical Manager
Test Report S/N: 1M2511240098-05-R3.C3K	Test Dates: 12/16/2025 - 02/02/2026	EUT Type: Portable Computing Device	Page 82 of 139



FCC ID: C3K2076 IC: 3048A-2076	MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Technical Manager
Test Report S/N: 1M2511240098-05-R3.C3K	Test Dates: 12/16/2025 - 02/02/2026	EUT Type: Portable Computing Device	Page 83 of 139

7.5 Carrier Frequency Separation

Test Overview and Limit

Measurement is made with EUT operating in hopping mode. ***The minimum permissible channel separation for this system is 2/3 the value of the 20dB BW.***

Test Procedure Used

ANSI C63.10-2020 – Section 7.8.2

Test Settings

1. Span = Wide enough to capture peaks of two adjacent channels
2. RBW = 30% of channel spacing. Adjust as necessary to best identify center of each individual channel
3. VBW $\geq$ RBW
4. Sweep = Auto
5. Detector = Peak
6. Trace mode = max hold
7. The trace was allowed to stabilize.
8. Marker-delta function used to determine separation between peaks of the adjacent channels

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



Figure 7-4. Test Instrument & Measurement Setup


Test Notes

The EUT complies with the minimum channel separation requirement when it is operating in 1x/EDR mode using 79 channels and when operating in AFH mode using 20 channels.

FCC ID: C3K2076 IC: 3048A-2076	MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Technical Manager
Test Report S/N: 1M2511240098-05-R3.C3K	Test Dates: 12/16/2025 - 02/02/2026	EUT Type: Portable Computing Device	Page 84 of 139

Frequency [MHz]	Data Rate [Mbps]	Mod.	Channel No.	Min. Channel Separation [MHz]
2402	1.0	GFSK	0	0.629
2441	1.0	GFSK	39	0.630
2480	1.0	GFSK	78	0.630
2402	2.0	$\pi/4$ -DQPSK	0	0.895
2441	2.0	$\pi/4$ -DQPSK	39	0.881
2480	2.0	$\pi/4$ -DQPSK	78	0.880
2402	3.0	8DPSK	0	0.865
2441	3.0	8DPSK	39	0.861
2480	3.0	8DPSK	78	0.878

Table 7-9. Minimum Channel Separation – SISO ANT1



Plot 7-125. Channel Spacing Plot (Bluetooth) – SISO ANT1

FCC ID: C3K2076 IC: 3048A-2076	MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Technical Manager
Test Report S/N: 1M2511240098-05-R3.C3K	Test Dates: 12/16/2025 - 02/02/2026	EUT Type: Portable Computing Device	Page 85 of 139

Frequency [MHz]	Data Rate [Mbps]	Mod.	Channel No.	Min. Channel Separation [MHz]
2402	1.0	GFSK	0	0.630
2441	1.0	GFSK	39	0.630
2480	1.0	GFSK	78	0.630
2402	2.0	$\pi/4$ -DQPSK	0	0.880
2441	2.0	$\pi/4$ -DQPSK	39	0.879
2480	2.0	$\pi/4$ -DQPSK	78	0.879
2402	3.0	8DPSK	0	0.869
2441	3.0	8DPSK	39	0.883
2480	3.0	8DPSK	78	0.865

Table 7-10. Minimum Channel Separation – SISO ANT2




Plot 7-126. Channel Spacing Plot (Bluetooth) – SISO ANT2

FCC ID: C3K2076 IC: 3048A-2076	MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Technical Manager
Test Report S/N: 1M2511240098-05-R3.C3K	Test Dates: 12/16/2025 - 02/02/2026	EUT Type: Portable Computing Device	Page 86 of 139

Frequency [MHz]	Data Rate [Mbps]	Mod.	Channel No.	Min. Channel Separation [MHz]
2402	1.0	GFSK	0	0.632
2441	1.0	GFSK	39	0.631
2480	1.0	GFSK	78	0.631
2402	2.0	$\pi/4$ -DQPSK	0	0.905
2441	2.0	$\pi/4$ -DQPSK	39	0.905
2480	2.0	$\pi/4$ -DQPSK	78	0.902
2402	3.0	8DPSK	0	0.906
2441	3.0	8DPSK	39	0.905
2480	3.0	8DPSK	78	0.905

Table 7-11. Minimum Channel Separation – DUAL ANT1




Plot 7-127. Channel Spacing Plot (Bluetooth) – DUAL ANT1

FCC ID: C3K2076 IC: 3048A-2076	MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Technical Manager
Test Report S/N: 1M2511240098-05-R3.C3K	Test Dates: 12/16/2025 - 02/02/2026	EUT Type: Portable Computing Device	Page 87 of 139

Frequency [MHz]	Data Rate [Mbps]	Mod.	Channel No.	Min. Channel Separation [MHz]
2402	1.0	GFSK	0	0.635
2441	1.0	GFSK	39	0.630
2480	1.0	GFSK	78	0.631
2402	2.0	$\pi/4$ -DQPSK	0	0.907
2441	2.0	$\pi/4$ -DQPSK	39	0.907
2480	2.0	$\pi/4$ -DQPSK	78	0.907
2402	3.0	8DPSK	0	0.903
2441	3.0	8DPSK	39	0.906
2480	3.0	8DPSK	78	0.907

Table 7-12. Minimum Channel Separation – DUAL ANT2



Plot 7-128. Channel Spacing Plot (Bluetooth) – DUAL ANT2

FCC ID: C3K2076 IC: 3048A-2076	MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Technical Manager
Test Report S/N: 1M2511240098-05-R3.C3K	Test Dates: 12/16/2025 - 02/02/2026	EUT Type: Portable Computing Device	Page 88 of 139

7.6 Time of Occupancy

Test Overview and Limit

Measurement is made while EUT is operating in hopping mode with the spectrum analyzer set to zero span. ***The maximum permissible time of occupancy is 400 ms within a period of 400ms multiplied by the number of hopping channels employed.***

Test Procedure Used

ANSI C63.10-2020 – Section 7.8.4

Test Settings

1. Span = zero span, centered on a hopping channel
2. RBW $\leq$ channel spacing and $\gg 1/T$, where T is expected dwell time per channel
3. Sweep = as necessary to capture entire dwell time. Second plot may be required to demonstrate two successive hops on a channel
4. Trigger is set with appropriate trigger delay to place pulse near the center of the plot
5. Detector = peak
6. Trace mode = max hold
7. Marker-delta function used to determine transmit time per hop


Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



Figure 7-5. Test Instrument & Measurement Setup

FCC ID: C3K2076 IC: 3048A-2076	MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Technical Manager
Test Report S/N: 1M2511240098-05-R3.C3K	Test Dates: 12/16/2025 - 02/02/2026	EUT Type: Portable Computing Device	Page 89 of 139



Plot 7-129. Time of Occupancy Plot (Bluetooth) – SISO ANT1

Bluetooth Time of Occupancy Calculation


Typically, Bluetooth 1x/EDR mode has a channel hopping rate of 1600 hops/s. Since 1x/EDR modes use 5 transmit and 1 receive slot, for a total of 6 slots, the Bluetooth transmitter is actually hopping at a rate of $1600 / 6 = 266.67$ hops/s/slot

- $400\text{ms} \times 79$ hopping channels = 31.6 sec (Time of Occupancy Limit)
- Worst case BT has 266.67 hops/second (for 1x/EDR modes with DH5 operation)
- $266.67 \text{ hops/second} / 79 \text{ channels} = 3.38 \text{ hops/second}$ (# of hops/second on one channel)
- $3.38 \text{ hops/second/channel} \times 31.6 \text{ seconds} = 106.67 \text{ hops}$ (# hops over a 31.6 second period)
- $106.67 \text{ hops} \times 2.875 \text{ ms/channel} = 306.68 \text{ ms}$ (worst case dwell time for one channel in 1x/EDR modes)

With AFH, the number of channels is reduced to a minimum of 20 channels and the channel hopping rate is reduced by 50% to 800 hops/s. AFH mode also uses 6 total slots so the Bluetooth transmitter hops at a rate of $800 / 6 = 133.3$ hops/s/slot

- $400\text{ms} \times 20$ hopping channels = 8 sec (Time of Occupancy Limit)
- Worst case BT has 133.3 hops/second/slot (for AFH mode with DH5 operation)
- $133.3 \text{ hops/s} / 20 \text{ channels} = 6.67 \text{ hops/second}$ (# of hops/second on one channel)
- $6.67 \text{ hops/s} / \text{channel} \times 8 \text{ seconds} = 53.34 \text{ hops}$ (# hops over a 8 second period)
- $53.34 \text{ hops} \times 2.875 \text{ ms/channel} = 153.35 \text{ ms}$ (worst case dwell time for one channel in AFH mode)

FCC ID: C3K2076 IC: 3048A-2076	MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Technical Manager
Test Report S/N: 1M2511240098-05-R3.C3K	Test Dates: 12/16/2025 - 02/02/2026	EUT Type: Portable Computing Device	Page 90 of 139



Plot 7-130. Time of Occupancy Plot (Bluetooth) – SISO ANT2

Bluetooth Time of Occupancy Calculation

Typically, Bluetooth 1x/EDR mode has a channel hopping rate of 1600 hops/s. Since 1x/EDR modes use 5 transmit and 1 receive slot, for a total of 6 slots, the Bluetooth transmitter is actually hopping at a rate of $1600 / 6 = 266.67$ hops/s/slot

- $400\text{ms} \times 79$ hopping channels = 31.6 sec (Time of Occupancy Limit)
- Worst case BT has 266.67 hops/second (for 1x/EDR modes with DH5 operation)
- $266.67 \text{ hops/second} / 79 \text{ channels} = 3.38 \text{ hops/second}$ (# of hops/second on one channel)
- $3.38 \text{ hops/second/channel} \times 31.6 \text{ seconds} = 106.67 \text{ hops}$ (# hops over a 31.6 second period)
- $106.67 \text{ hops} \times 2.870 \text{ ms/channel} = 306.14 \text{ ms}$ (worst case dwell time for one channel in 1x/EDR modes)

With AFH, the number of channels is reduced to a minimum of 20 channels and the channel hopping rate is reduced by 50% to 800 hops/s. AFH mode also uses 6 total slots so the Bluetooth transmitter hops at a rate of $800 / 6 = 133.3$ hops/s/slot

- $400\text{ms} \times 20$ hopping channels = 8 sec (Time of Occupancy Limit)
- Worst case BT has 133.3 hops/second/slot (for AFH mode with DH5 operation)
- $133.3 \text{ hops/s} / 20 \text{ channels} = 6.67 \text{ hops/second}$ (# of hops/second on one channel)
- $6.67 \text{ hops/s} / \text{channel} \times 8 \text{ seconds} = 53.34 \text{ hops}$ (# hops over a 8 second period)
- $53.34 \text{ hops} \times 2.870 \text{ ms/channel} = 153.09 \text{ ms}$ (worst case dwell time for one channel in AFH mode)

FCC ID: C3K2076 IC: 3048A-2076	MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Technical Manager
Test Report S/N: 1M2511240098-05-R3.C3K	Test Dates: 12/16/2025 - 02/02/2026	EUT Type: Portable Computing Device	Page 91 of 139

7.7 Number of Hopping Channels

Test Overview and Limit

Measurement is made while EUT is operating in hopping mode. ***This frequency hopping system must employ a minimum of 15 hopping channels.***

Test Procedure Used

ANSI C63.10-2020 – Section 7.8.3

Test Settings

1. Span = frequency of band of operation (divided into two plots)
2. RBW < 30% of channel spacing or 20dB bandwidth, whichever is smaller
3. VBW ≥ RBW
4. Sweep = auto
5. Detector = peak
6. Trace mode = max hold
7. Trace was allowed to stabilize

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-6. Test Instrument & Measurement Setup

Test Notes


The frequency spectrum was broken up into two sub-ranges to clearly show all the hopping frequencies. In AFH mode, this device operates using 20 channels so the requirement for minimum number of hopping channels is satisfied.

FCC ID: C3K2076 IC: 3048A-2076	MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Technical Manager
Test Report S/N: 1M2511240098-05-R3.C3K	Test Dates: 12/16/2025 - 02/02/2026	EUT Type: Portable Computing Device	Page 92 of 139

SISO ANT1




Plot 7-131. Low End Spectrum Channel Hopping Plot (Bluetooth) – SISO ANT1




Plot 7-132. High End Spectrum Channel Hopping Plot (Bluetooth) – SISO ANT1

FCC ID: C3K2076 IC: 3048A-2076	MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Technical Manager
Test Report S/N: 1M2511240098-05-R3.C3K	Test Dates: 12/16/2025 - 02/02/2026	EUT Type: Portable Computing Device	Page 93 of 139

SISO ANT2




Plot 7-133. Low End Spectrum Channel Hopping Plot (Bluetooth) – SISO ANT2




Plot 7-134. High End Spectrum Channel Hopping Plot (Bluetooth) – SISO ANT2

FCC ID: C3K2076 IC: 3048A-2076	MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Technical Manager
Test Report S/N: 1M2511240098-05-R3.C3K	Test Dates: 12/16/2025 - 02/02/2026	EUT Type: Portable Computing Device	Page 94 of 139

DUAL ANT1




Plot 7-135. Low End Spectrum Channel Hopping Plot (Bluetooth) – DUAL ANT1




Plot 7-136. High End Spectrum Channel Hopping Plot (Bluetooth) – DUAL ANT1

FCC ID: C3K2076 IC: 3048A-2076	MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Technical Manager
Test Report S/N: 1M2511240098-05-R3.C3K	Test Dates: 12/16/2025 - 02/02/2026	EUT Type: Portable Computing Device	Page 95 of 139

DUAL ANT2



Plot 7-137. Low End Spectrum Channel Hopping Plot (Bluetooth) – DUAL ANT2



Plot 7-138. High End Spectrum Channel Hopping Plot (Bluetooth) – DUAL ANT2

FCC ID: C3K2076 IC: 3048A-2076	MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Technical Manager
Test Report S/N: 1M2511240098-05-R3.C3K	Test Dates: 12/16/2025 - 02/02/2026	EUT Type: Portable Computing Device	Page 96 of 139

7.8 Conducted Spurious Emissions

Test Overview and Limit

Conducted out-of-band spurious emissions were investigated from 30MHz up to 25GHz to include the 10th harmonic of the fundamental transmit frequency. **The maximum permissible out-of-band emission level is 20 dBc.**

Test Procedure Used

ANSI C63.10-2020 – Section 7.8.8

Test Settings

1. Start frequency was set to 30MHz and stop frequency was set to 25GHz (separated into two plots per channel)
2. RBW = 1MHz* (See note below)
3. VBW = 3MHz
4. Detector = Peak
5. Trace mode = max hold
6. Sweep time = auto couple
7. The trace was allowed to stabilize

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-7. Test Instrument & Measurement Setup

Test Notes


Out-of-band conducted spurious emissions were investigated for all data rates and the worst-case emissions were found with the EUT transmitting at 1Mbps. The display line shown in the following plots is the limit at 20dB below the fundamental emission level measured in a 100kHz bandwidth. However, the traces in the following plots are measured with a 1MHz RBW to reduce test time, so the display line may not necessarily appear to be 20dB below the level of the fundamental in a 1MHz bandwidth.

FCC ID: C3K2076 IC: 3048A-2076	MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Technical Manager
Test Report S/N: 1M2511240098-05-R3.C3K	Test Dates: 12/16/2025 - 02/02/2026	EUT Type: Portable Computing Device	Page 97 of 139

SISO ANT1




Plot 7-139. Conducted Spurious Plot (Bluetooth, 1Mbps – Ch. 0) - SISO ANT1




Plot 7-140. Conducted Spurious Plot (Bluetooth, 1Mbps – Ch. 0) - SISO ANT1

FCC ID: C3K2076 IC: 3048A-2076	MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Technical Manager
Test Report S/N: 1M2511240098-05-R3.C3K	Test Dates: 12/16/2025 - 02/02/2026	EUT Type: Portable Computing Device	Page 98 of 139





Plot 7-141. Conducted Spurious Plot (Bluetooth, 1Mbps – Ch. 39) - SISO ANT1




Plot 7-142. Conducted Spurious Plot (Bluetooth, 1Mbps – Ch. 39) - SISO ANT1

FCC ID: C3K2076 IC: 3048A-2076	MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Technical Manager
Test Report S/N: 1M2511240098-05-R3.C3K	Test Dates: 12/16/2025 - 02/02/2026	EUT Type: Portable Computing Device	Page 99 of 139




FCC ID: C3K2076 IC: 3048A-2076	MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Technical Manager
Test Report S/N: 1M2511240098-05-R3.C3K	Test Dates: 12/16/2025 - 02/02/2026	EUT Type: Portable Computing Device	Page 100 of 139

SISO ANT2





Plot 7-145. Conducted Spurious Plot (Bluetooth, 1Mbps – Ch. 0) - SISO ANT2





Plot 7-146. Conducted Spurious Plot (Bluetooth, 1Mbps – Ch. 0) - SISO ANT2

FCC ID: C3K2076 IC: 3048A-2076	MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Technical Manager
Test Report S/N: 1M2511240098-05-R3.C3K	Test Dates: 12/16/2025 - 02/02/2026	EUT Type: Portable Computing Device	Page 101 of 139




FCC ID: C3K2076 IC: 3048A-2076	MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Technical Manager
Test Report S/N: 1M2511240098-05-R3.C3K	Test Dates: 12/16/2025 - 02/02/2026	EUT Type: Portable Computing Device	Page 102 of 139




FCC ID: C3K2076 IC: 3048A-2076	MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Technical Manager
Test Report S/N: 1M2511240098-05-R3.C3K	Test Dates: 12/16/2025 - 02/02/2026	EUT Type: Portable Computing Device	Page 103 of 139

DUAL ANT1





Plot 7-151. Conducted Spurious Plot (Bluetooth, 1Mbps – Ch. 0) – DUAL ANT1




Plot 7-152. Conducted Spurious Plot (Bluetooth, 1Mbps – Ch. 0) – DUAL ANT1

FCC ID: C3K2076 IC: 3048A-2076	MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Technical Manager
Test Report S/N: 1M2511240098-05-R3.C3K	Test Dates: 12/16/2025 - 02/02/2026	EUT Type: Portable Computing Device	Page 104 of 139




FCC ID: C3K2076 IC: 3048A-2076	MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Technical Manager
Test Report S/N: 1M2511240098-05-R3.C3K	Test Dates: 12/16/2025 - 02/02/2026	EUT Type: Portable Computing Device	Page 106 of 139

DUAL ANT2




Plot 7-157. Conducted Spurious Plot (Bluetooth, 1Mbps – Ch. 0) – DUAL ANT2




Plot 7-158. Conducted Spurious Plot (Bluetooth, 1Mbps – Ch. 0) – DUAL ANT2

FCC ID: C3K2076 IC: 3048A-2076	MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Technical Manager
Test Report S/N: 1M2511240098-05-R3.C3K	Test Dates: 12/16/2025 - 02/02/2026	EUT Type: Portable Computing Device	Page 107 of 139




Plot 7-159. Conducted Spurious Plot (Bluetooth, 1Mbps – Ch. 39) – DUAL ANT2




Plot 7-160. Conducted Spurious Plot (Bluetooth, 1Mbps – Ch. 39) – DUAL ANT2

FCC ID: C3K2076 IC: 3048A-2076	MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Technical Manager
Test Report S/N: 1M2511240098-05-R3.C3K	Test Dates: 12/16/2025 - 02/02/2026	EUT Type: Portable Computing Device	Page 108 of 139



Plot 7-161. Conducted Spurious Plot (Bluetooth, 1Mbps – Ch. 78) – DUAL ANT2



Plot 7-162. Conducted Spurious Plot (Bluetooth, 1Mbps – Ch. 78) – DUAL ANT2

FCC ID: C3K2076 IC: 3048A-2076	MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Technical Manager
Test Report S/N: 1M2511240098-05-R3.C3K	Test Dates: 12/16/2025 - 02/02/2026	EUT Type: Portable Computing Device	Page 109 of 139

7.9 Radiated Spurious Emission Measurements – Above 1GHz

Test Overview and Limit

All out of band radiated spurious emissions are measured with a spectrum analyzer connected to a receive antenna while the EUT is operating at maximum power and at the appropriate frequencies. Only the radiated emissions of the configuration that produced the worst-case emissions are reported in this section.

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR and Table 6 of RSS-Gen (8.10) must not exceed the limits shown below per Section 15.209 and RSS-Gen (8.9).

Frequency	Field Strength [μV/m]	Measured Distance [Meters]
Above 960.0 MHz	500	3

Table 7-13. Radiated Limits

Test Procedure Used

ANSI C63.10-2020 – Section 6.6.4.3

Test Settings

Average Field Strength Measurements per Section 4.1.5.2.3 of ANSI C63.10-2020

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW = 1kHz $\geq 1/\tau$ Hz, where τ = pulse width in seconds
4. Averaging type was set to RMS to ensure that video filtering was applied in the power domain
5. Detector = peak
6. Sweep time = auto
7. Trace mode = max hold
8. Trace was allowed to stabilize

Peak Field Strength Measurements per Section 4.1.5.2.2 of ANSI C63.10-2020

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW is set depending on measurement frequency, as specified in Table 7-14 below
3. VBW = 3MHz
4. Detector = peak
5. Sweep time = auto couple
6. Trace mode = max hold
7. Trace was allowed to stabilize

FCC ID: C3K2076 IC: 3048A-2076	MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Technical Manager
Test Report S/N: 1M2511240098-05-R3.C3K	Test Dates: 12/16/2025 - 02/02/2026	EUT Type: Portable Computing Device	Page 110 of 139

Frequency	RBW
9 – 150kHz	200 – 300Hz
0.15 – 30MHz	9 – 10kHz
30 – 1000MHz	100 – 120kHz
> 1000MHz	1MHz

Table 7-14. RBW as a Function of Frequency

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-8. Radiated Test Setup >1GHz

Test Notes

- All emissions lying in restricted bands specified in §15.205 and Section 8.10 of RSS-Gen are below the limit shown in §15.209.
- No significant radiated emissions were found in the 2310 - 2390MHz restricted band.
- The antenna is manipulated through typical positions, polarity, and length during the tests. The EUT is manipulated through three orthogonal planes.
- This unit was tested with its standard battery.
- The spectrum is measured from 9kHz to the 10th harmonic and the worst-case emissions are reported.
- The duty cycle correction factor was not applied to noise floor measurements.
- The wide spectrum spurious emissions plots shown on the following pages are used only for the purpose of emission identification. Any emissions found to be within 20dB of the limit are fully investigated and the results are shown in this section.
- The "-" shown in the following RSE tables is used to denote a noise floor measurement.

FCC ID: C3K2076 IC: 3048A-2076	MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Technical Manager
Test Report S/N: 1M2511240098-05-R3.C3K	Test Dates: 12/16/2025 - 02/02/2026	EUT Type: Portable Computing Device	Page 111 of 139

Sample Calculation


- Field Strength Level $_{[dB_{\mu V/m}]} = \text{Analyzer Level }_{[dBm]} + 107 + \text{AFCL }_{[dB/m]} + \text{Duty Cycle Correction }_{[dB]}$
- $\text{AFCL }_{[dB/m]} = \text{Antenna Factor }_{[dB/m]} + \text{Cable Loss }_{[dB]}$
- $\text{Margin }_{[dB]} = \text{Field Strength Level }_{[dB_{\mu V/m}]} - \text{Limit }_{[dB_{\mu V/m}]}$

Duty Cycle Correction Factor Calculation


- Channel hop rate = 800hops/second (AFH Mode)
- Adjusted channel hop rate for DH5 mode = 133.33 hops/second
- Time per channel hop = $1 / 133.33 \text{ hops/second} = 7.50 \text{ ms}$
- Time to cycle through all channels = $7.50 \times 20 \text{ channels} = 150\text{ms}$
- Number of times transmitter hits on one channel = $100 \text{ ms} / 150 \text{ ms} = 1 \text{ time(s)}$
- Worst case dwell time = 7.5 ms
- Duty cycle correction factor = $20\log_{10}(7.5\text{ms}/100\text{ms}) = -22.5 \text{ dB}$

FCC ID: C3K2076 IC: 3048A-2076	MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Technical Manager
Test Report S/N: 1M2511240098-05-R3.C3K	Test Dates: 12/16/2025 - 02/02/2026	EUT Type: Portable Computing Device	Page 112 of 139


SISO ANT1



Plot 7-163. Radiated Spurious Plot above 1GHz (BT – Ch. 0)




Plot 7-164. Radiated Spurious Plot above 1GHz (BT – Ch. 39)




Plot 7-165. Radiated Spurious Plot above 1GHz (BT – Ch. 78)

FCC ID: C3K2076 IC: 3048A-2076	MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Technical Manager
Test Report S/N: 1M2511240098-05-R3.C3K	Test Dates: 12/16/2025 - 02/02/2026	EUT Type: Portable Computing Device	Page 113 of 139


SISO ANT2



Plot 7-166. Radiated Spurious Plot above 1GHz (BT – Ch. 0)




Plot 7-167. Radiated Spurious Plot above 1GHz (BT – Ch. 39)




Plot 7-168. Radiated Spurious Plot above 1GHz (BT – Ch. 78)

FCC ID: C3K2076 IC: 3048A-2076	MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Technical Manager
Test Report S/N: 1M2511240098-05-R3.C3K	Test Dates: 12/16/2025 - 02/02/2026	EUT Type: Portable Computing Device	Page 114 of 139


DUAL



Plot 7-169. Radiated Spurious Plot above 1GHz (BT – Ch. 0)



Plot 7-170. Radiated Spurious Plot above 1GHz (BT – Ch. 39)



Plot 7-171. Radiated Spurious Plot above 1GHz (BT – Ch. 78)


FCC ID: C3K2076 IC: 3048A-2076	MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Technical Manager
Test Report S/N: 1M2511240098-05-R3.C3K	Test Dates: 12/16/2025 - 02/02/2026	EUT Type: Portable Computing Device	Page 115 of 139



Radiated Spurious Emissions Measurements (Above 18GHz)


§15.209; RSS-Gen [8.9]

SISO ANT1




Plot 7-172. Radiated Spurious Plot above 18GHz

SISO ANT2



Plot 7-173. Radiated Spurious Plot above 18GHz

DUAL



Plot 7-174. Radiated Spurious Plot above 18GHz

FCC ID: C3K2076 IC: 3048A-2076		MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Technical Manager
Test Report S/N: 1M2511240098-05-R3.C3K	Test Dates: 12/16/2025 - 02/02/2026	EUT Type: Portable Computing Device		Page 116 of 139

© 2026 ELEMENT

V 11.3 5/14/2025

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without written permission from Element. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.



Radiated Spurious Emission Measurements

§15.205 §15.209 §15.247 (d); RSS-Gen [8.9]

SISO ANT1

Worst Case Mode: Bluetooth
Worst Case Data Rate: 1 Mbps
Measurement Distance: 3 Meters
Operating Frequency: 2402MHz
Channel: 0

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Duty Cycle Correction [dB]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
4804.00	Avg	H	-	-	-78.31	2.72	0.00	31.41	53.98	-22.57
4804.00	Peak	H	-	-	-74.62	2.72	0.00	35.10	73.98	-38.88
12010.00	Avg	H	-	-	-80.12	13.32	0.00	40.20	53.98	-13.78
12010.00	Peak	H	-	-	-75.25	13.32	0.00	45.07	73.98	-28.91

Table 7-15. Radiated Measurements

Worst Case Mode: Bluetooth
Worst Case Data Rate: 1 Mbps
Measurement Distance: 3 Meters
Operating Frequency: 2441MHz
Channel: 39

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Duty Cycle Correction [dB]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
4882.00	Avg	H	152	223	-80.07	3.10	-22.50	7.53	53.98	-46.45
4882.00	Peak	H	152	223	-72.00	3.10	0.00	38.10	73.98	-35.88
7323.00	Avg	H	-	-	-74.68	9.53	0.00	41.85	53.98	-12.13
7323.00	Peak	H	-	-	-77.82	9.53	0.00	38.71	73.98	-35.27
12205.00	Avg	H	-	-	-75.40	13.21	0.00	44.81	53.98	-9.17
12205.00	Peak	H	-	-	-78.59	13.21	0.00	41.62	73.98	-32.36

Table 7-16. Radiated Measurements

FCC ID: C3K2076 IC: 3048A-2076	MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Technical Manager
Test Report S/N: 1M2511240098-05-R3.C3K	Test Dates: 12/16/2025 - 02/02/2026	EUT Type: Portable Computing Device	Page 117 of 139



Radiated Spurious Emission Measurements

§15.205 §15.209 §15.247 (d); RSS-Gen [8.9]

Worst Case Mode:	Bluetooth
Worst Case Data Rate:	1 Mbps
Measurement Distance:	3 Meters
Operating Frequency:	2480MHz
Channel:	78

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Duty Cycle Correction [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
4960.00	Avg	H	-	-	-74.96	3.05	0.00	35.09	53.98	-18.89
4960.00	Peak	H	-	-	-71.54	3.05	0.00	38.51	73.98	-35.47
7440.00	Avg	H	-	-	-75.38	9.19	0.00	40.81	53.98	-13.17
7440.00	Peak	H	-	-	-74.70	9.19	0.00	41.49	73.98	-32.49
12400.00	Avg	H	-	-	-75.31	13.27	0.00	44.96	53.98	-9.02
12400.00	Peak	H	-	-	-74.76	13.27	0.00	45.51	73.98	-28.47

Table 7-17. Radiated Measurements

FCC ID: C3K2076 IC: 3048A-2076	MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Technical Manager
Test Report S/N: 1M2511240098-05-R3.C3K	Test Dates: 12/16/2025 - 02/02/2026	EUT Type: Portable Computing Device	Page 118 of 139



SISO ANT2

Worst Case Mode: Bluetooth
Worst Case Data Rate: 1 Mbps
Measurement Distance: 3 Meters
Operating Frequency: 2402MHz
Channel: 0

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Duty Cycle Correction [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
4804.00	Avg	H	-	-	-74.81	2.72	0.00	34.91	53.98	-19.07
4804.00	Peak	H	-	-	-74.03	2.72	0.00	35.69	73.98	-38.29
12010.00	Avg	H	-	-	-75.39	13.32	0.00	44.93	53.98	-9.05
12010.00	Peak	H	-	-	-74.69	13.32	0.00	45.63	73.98	-28.35

Table 7-18. Radiated Measurements

Worst Case Mode: Bluetooth
Worst Case Data Rate: 1 Mbps
Measurement Distance: 3 Meters
Operating Frequency: 2441MHz
Channel: 39

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Duty Cycle Correction [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
4882.00	Avg	H	-	-	-78.39	3.10	0.00	31.71	53.98	-22.27
4882.00	Peak	H	-	-	-75.79	3.10	0.00	34.31	73.98	-39.67
7323.00	Avg	H	257	105	-78.46	9.53	-22.50	15.57	53.98	-38.41
7323.00	Peak	H	257	105	-75.45	9.53	0.00	41.08	73.98	-32.90
12205.00	Avg	H	-	-	-79.61	13.21	0.00	40.60	53.98	-13.38
12205.00	Peak	H	-	-	-76.77	13.21	0.00	43.44	73.98	-30.54

Table 7-19. Radiated Measurements

FCC ID: C3K2076 IC: 3048A-2076	MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Technical Manager
Test Report S/N: 1M2511240098-05-R3.C3K	Test Dates: 12/16/2025 - 02/02/2026	EUT Type: Portable Computing Device	Page 119 of 139

Worst Case Mode: Bluetooth
 Worst Case Data Rate: 1 Mbps
 Measurement Distance: 3 Meters
 Operating Frequency: 2480MHz
 Channel: 78

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Duty Cycle Correction [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
4960.00	Avg	H	-	-	-74.50	3.05	0.00	35.55	53.98	-18.43
4960.00	Peak	H	-	-	-72.02	3.05	0.00	38.03	73.98	-35.95
7440.00	Avg	H	-	-	-75.25	9.19	0.00	40.94	53.98	-13.04
7440.00	Peak	H	-	-	-71.50	9.19	0.00	44.69	73.98	-29.29
12400.00	Avg	H	-	-	-75.37	13.27	0.00	44.90	53.98	-9.08
12400.00	Peak	H	-	-	-72.00	13.27	0.00	48.27	73.98	-25.71

Table 7-20. Radiated Measurements

FCC ID: C3K2076 IC: 3048A-2076	MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Technical Manager
Test Report S/N: 1M2511240098-05-R3.C3K	Test Dates: 12/16/2025 - 02/02/2026	EUT Type: Portable Computing Device	Page 120 of 139



DUAL

Worst Case Mode: Bluetooth
Worst Case Data Rate: 1 Mbps
Measurement Distance: 3 Meters
Operating Frequency: 2402MHz
Channel: 0

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Duty Cycle Correction [dB]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
4804.00	Avg	H	-	-	-74.86	2.72	0.00	34.86	53.98	-19.12
4804.00	Peak	H	-	-	-74.38	2.72	0.00	35.34	73.98	-38.64
12010.00	Avg	H	-	-	-75.42	13.32	0.00	44.90	53.98	-9.08
12010.00	Peak	H	-	-	-74.59	13.32	0.00	45.73	73.98	-28.25

Table 7-21. Radiated Measurements

Worst Case Mode: Bluetooth
Worst Case Data Rate: 1 Mbps
Measurement Distance: 3 Meters
Operating Frequency: 2441MHz
Channel: 39

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Duty Cycle Correction [dB]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
4882.00	Avg	H	-	-	-74.54	3.10	0.00	35.56	53.98	-18.42
4882.00	Peak	H	-	-	-73.84	3.10	0.00	36.26	73.98	-37.72
7323.00	Avg	H	184	201	-73.94	9.53	-22.50	20.09	53.98	-33.89
7323.00	Peak	H	184	201	-72.46	9.53	0.00	44.07	73.98	-29.91
12205.00	Avg	H	-	-	-75.43	13.21	0.00	44.78	53.98	-9.20
12205.00	Peak	H	-	-	-74.77	13.21	0.00	45.44	73.98	-28.54

Table 7-22. Radiated Measurements

FCC ID: C3K2076 IC: 3048A-2076	MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Technical Manager
Test Report S/N: 1M2511240098-05-R3.C3K	Test Dates: 12/16/2025 - 02/02/2026	EUT Type: Portable Computing Device	Page 121 of 139

Worst Case Mode: Bluetooth
 Worst Case Data Rate: 1 Mbps
 Measurement Distance: 3 Meters
 Operating Frequency: 2480MHz
 Channel: 78

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Duty Cycle Correction [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
4960.00	Avg	H	387	247	-75.36	3.05	-22.50	12.19	53.98	-41.79
4960.00	Peak	H	387	247	-73.68	3.05	0.00	36.37	73.98	-37.61
7440.00	Avg	H	-	-	-75.62	9.19	0.00	40.57	53.98	-13.41
7440.00	Peak	H	-	-	-74.48	9.19	0.00	41.71	73.98	-32.27
12400.00	Avg	H	-	-	-75.04	13.27	0.00	45.23	53.98	-8.75
12400.00	Peak	H	-	-	-74.72	13.27	0.00	45.55	73.98	-28.43

Table 7-23. Radiated Measurements

FCC ID: C3K2076 IC: 3048A-2076	MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Technical Manager
Test Report S/N: 1M2511240098-05-R3.C3K	Test Dates: 12/16/2025 - 02/02/2026	EUT Type: Portable Computing Device	Page 122 of 139

7.10 Radiated Restricted Band Edge Measurements

Test Overview and Limit

All out of band radiated emissions at the band edge are measured with a spectrum analyzer connected to a receive antenna while the EUT is operating at maximum power, at the appropriate frequencies, and with hopping disabled. Only the radiated emissions of the configuration that produced the worst-case emissions are reported in this section.

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR and Table 6 of RSS-Gen (8.10) must not exceed the limits shown below per Section 15.209 and RSS-Gen (8.9).

Frequency	Field Strength [$\mu\text{V/m}$]	Measured Distance [Meters]
Above 960.0 MHz	500	3

Table 7-24. Radiated Limits

Test Procedure Used

ANSI C63.10-2020 – Section 6.10.5.2

Test Settings

1. Span is set large enough to capture the peak level of the emission operating on the channel closest to the band edge
2. Reference level offset is set with the appropriate corrections for the frequencies shown in the plots
3. Reference level is set to provide the appropriate amount of “head room” above the signal as specified in ANSI C63.10-2020 Section 4.1.5.2
4. Attenuation is set to a low enough level to maintain enough dynamic range between the noise floor and the radiated limit
5. Sweep time = Auto coupled
6. RBW = 1MHz
7. VBW = 3 x RBW for peak measurements and 1kHz for RMS measurements
8. Detector = RMS and peak
9. Trace = Max Hold
10. Trace was allowed to stabilize

FCC ID: C3K2076 IC: 3048A-2076	MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Technical Manager
Test Report S/N: 1M2511240098-05-R3.C3K	Test Dates: 12/16/2025 - 02/02/2026	EUT Type: Portable Computing Device	Page 123 of 139

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-9. Radiated Test Setup >1GHz

Test Notes

1. All emissions lying in restricted bands specified in §15.205 and Section 8.10 of RSS-Gen are below the limits shown in §15.209.
2. No significant radiated emissions were found in the 2310 - 2390MHz restricted band.
3. The antenna is manipulated through typical positions, polarity, and length during the tests. The EUT is manipulated through three orthogonal planes.
4. This unit was tested with its standard battery.
5. The spectrum is measured from 9kHz to the 10th harmonic and the worst-case emissions are reported.
6. Two different amplitude offsets were used depending on whether peak or average measurements were measured. The average measurements use a duty cycle correction factor (DCCF).


The amplitude offset shown in the following plots for average measurements was calculated using the formula:

$$\text{Offset (dB)} = (\text{Antenna Factor} + \text{Cable Loss} + \text{Attenuator}) - \text{Preamplifier Gain} + \text{DCCF}$$


7. The "-" shown in the following RSE tables is used to denote a noise floor measurement.

FCC ID: C3K2076 IC: 3048A-2076	MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Technical Manager
Test Report S/N: 1M2511240098-05-R3.C3K	Test Dates: 12/16/2025 - 02/02/2026	EUT Type: Portable Computing Device	Page 124 of 139

Worst Case Mode:	Bluetooth
Worst Case Data Rate:	3 Mbps
Measurement Distance:	3 Meters
Operating Frequency:	2480MHz
Channel:	78




Plot 7-175. Radiated Restricted Upper Band Edge Measurement (Average) – SISO ANT1




Plot 7-176. Radiated Restricted Upper Band Edge Measurement (Peak) – SISO ANT1

Worst Case Mode:	Bluetooth
Worst Case Data Rate:	1 Mbps
Measurement Distance:	3 Meters
Operating Frequency:	2480MHz
Channel:	78




Plot 7-177. Radiated Restricted Upper Band Edge Measurement (Average) – SISO ANT2




Plot 7-178. Radiated Restricted Upper Band Edge Measurement (Peak) – SISO ANT2

FCC ID: C3K2076 IC: 3048A-2076	MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Technical Manager
Test Report S/N: 1M2511240098-05-R3.C3K	Test Dates: 12/16/2025 - 02/02/2026	EUT Type: Portable Computing Device	Page 125 of 139

Worst Case Mode:	Bluetooth
Worst Case Data Rate:	3 Mbps
Measurement Distance:	3 Meters
Operating Frequency:	2480MHz
Channel:	78



Plot 7-179. Radiated Restricted Upper Band Edge Measurement (Average) – DUAL



Plot 7-180. Radiated Restricted Upper Band Edge Measurement (Peak) – DUAL

FCC ID: C3K2076 IC: 3048A-2076	MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Technical Manager
Test Report S/N: 1M2511240098-05-R3.C3K	Test Dates: 12/16/2025 - 02/02/2026	EUT Type: Portable Computing Device	Page 126 of 139

7.11 Radiated Spurious Emissions Measurements – Below 1GHz

Test Overview and Limit

All out of band radiated spurious emissions are measured with a spectrum analyzer connected to a receive antenna while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates and modes were investigated for radiated spurious emissions. Only the radiated emissions of the configuration that produced the worst case emissions are reported in this section.

All out of band emissions must not exceed the limits shown below per Section 15.209 and RSS-Gen (8.9).

Frequency	Field Strength [$\mu\text{V/m}$]	Measured Distance [Meters]
0.009 – 0.490 MHz	2400/F (kHz)	300
0.490 – 1.705 MHz	24000/F (kHz)	30
1.705 – 30.00 MHz	30	30
30.00 – 88.00 MHz	100	3
88.00 – 216.0 MHz	150	3
216.0 – 960.0 MHz	200	3
Above 960.0 MHz	500	3

Table 7-25. Radiated Limits

Test Procedures Used

ANSI C63.10-2020

Test Settings

Quasi-Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 120kHz (for emissions from 30MHz – 1GHz)
3. Detector = quasi-peak
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize

FCC ID: C3K2076 IC: 3048A-2076	MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Technical Manager
Test Report S/N: 1M2511240098-05-R3.C3K	Test Dates: 12/16/2025 - 02/02/2026	EUT Type: Portable Computing Device	Page 127 of 139

Test Setup

The EUT and measurement equipment were set up as shown in the diagrams below.




Figure 7-10. Radiated Test Setup < 1GHz




Figure 7-11. Radiated Test Setup <30M

FCC ID: C3K2076 IC: 3048A-2076		MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Technical Manager
Test Report S/N: 1M2511240098-05-R3.C3K	Test Dates: 12/16/2025 - 02/02/2026	EUT Type: Portable Computing Device		Page 128 of 139


Test Notes

1. All emissions lying in restricted bands specified in §15.205 and RSS-Gen (8.10) are below the limits shown in §15.209.
2. The broadband receive antenna is manipulated through vertical and horizontal polarizations during the tests. The EUT is manipulated through three orthogonal planes.
3. This unit was tested with its standard battery.
4. The spectrum is investigated using a peak detector and final measurements are recorded using CISPR quasi peak detector. The worst-case emissions are reported however emissions whose levels were not within 20dB of the respective limits were not reported.
5. Emissions were measured at a 3 meter test distance.
6. Emissions are investigated while operating on the center channel of the mode, band, and modulation that produced the worst case results during the transmitter spurious emissions testing.
7. No spurious emissions were detected within 20dB of the limit below 30MHz.
8. The results recorded using the broadband antenna is known to correlate with the results obtained by using a tuned dipole with an acceptable degree of accuracy. The VSWR for the measurement antenna was found to be less than 2:1.
9. The wide spectrum spurious emissions plots shown on the following pages are used only for the purpose of emission identification. There were no emissions detected in the 30MHz – 1GHz frequency range, as shown in the subsequent plots.

FCC ID: C3K2076 IC: 3048A-2076	MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Technical Manager
Test Report S/N: 1M2511240098-05-R3.C3K	Test Dates: 12/16/2025 - 02/02/2026	EUT Type: Portable Computing Device	Page 129 of 139

Radiated Spurious Emissions Measurements (Below 1GHz)

§15.209; RSS-Gen [8.9]




Plot 7-181. Radiated Spurious Plot below 1GHz – SISO ANT1

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
57.60	Quasi-Peak	H	116	184	-93.96	14.09	27.13	40.00	-12.87
77.05	Quasi-Peak	H	108	206	-91.00	14.39	30.39	40.00	-9.61
223.25	Quasi-Peak	H	-	-	-96.49	18.12	28.63	46.02	-17.39
558.15	Quasi-Peak	H	-	-	-96.77	26.62	36.85	46.02	-9.17
616.85	Quasi-Peak	H	-	-	-95.75	27.25	38.50	46.02	-7.52
819.60	Quasi-Peak	H	-	-	-95.74	30.45	41.71	46.02	-4.31

Table 7-26. Radiated Spurious Emissions Below 1GHz – SISO ANT1

FCC ID: C3K2076 IC: 3048A-2076	MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Technical Manager
Test Report S/N: 1M2511240098-05-R3.C3K	Test Dates: 12/16/2025 - 02/02/2026	EUT Type: Portable Computing Device	Page 130 of 139




Plot 7-182. Radiated Spurious Plot below 1GHz – SISO ANT2

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
51.05	Quasi-Peak	V	-	-	-94.88	14.55	26.67	40.00	-13.33
55.80	Quasi-Peak	V	-	-	-92.59	14.08	28.49	40.00	-11.51
59.15	Quasi-Peak	V	-	-	-92.10	14.12	29.02	40.00	-10.98
74.80	Quasi-Peak	V	113	38	-90.40	14.50	31.10	40.00	-8.90
367.60	Quasi-Peak	V	-	-	-97.14	22.52	32.38	46.02	-13.64

Table 7-27. Radiated Spurious Emissions Below 1GHz – SISO ANT2

FCC ID: C3K2076 IC: 3048A-2076	MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Technical Manager
Test Report S/N: 1M2511240098-05-R3.C3K	Test Dates: 12/16/2025 - 02/02/2026	EUT Type: Portable Computing Device	Page 131 of 139



Plot 7-183. Radiated Spurious Plot below 1GHz – DUAL

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
55.70	Quasi-Peak	V	272	241	-90.44	13.96	30.52	40.00	-9.48
59.00	Quasi-Peak	H	108	84	-98.10	14.02	22.92	40.00	-17.08
73.50	Quasi-Peak	H	112	262	-99.68	14.60	21.92	40.00	-18.08
392.80	Quasi-Peak	V	261	194	-96.82	23.11	33.29	46.02	-12.73
712.10	Quasi-Peak	V	250	136	-95.99	28.81	39.82	46.02	-6.20

Table 7-28. Radiated Spurious Emissions Below 1GHz – DUAL

FCC ID: C3K2076 IC: 3048A-2076	MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Technical Manager
Test Report S/N: 1M2511240098-05-R3.C3K	Test Dates: 12/16/2025 - 02/02/2026	EUT Type: Portable Computing Device	Page 132 of 139

7.12 Line Conducted Measurement Data

Test Overview and Limit

All AC line conducted spurious emissions are measured with a receiver connected to a grounded LISN while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates and modes were investigated for conducted spurious emissions. Only the conducted emissions of the configuration that produced the worst case emissions are reported in this section.

All conducted emissions must not exceed the limits shown in the table below per Section 15.207 and RSS-Gen (8.8).

Frequency of emission (MHz)	Conducted Limit (dBμV)	
	Quasi-peak	Average
0.15 – 0.5	66 to 56*	56 to 46*
0.5 – 5	56	46
5 – 30	60	50

Table 7-29. Conducted Limits

*Decreases with the logarithm of the frequency.

Test Procedures Used

ANSI C63.10-2020, Section 6.2

Test Settings

Quasi-Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the spurious emission of interest
2. RBW = 9kHz (for emissions from 150kHz – 30MHz)
3. Detector = quasi-peak
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize

Average Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the spurious emission of interest
2. RBW = 9kHz (for emissions from 150kHz – 30MHz)
3. Detector = RMS
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize

FCC ID: C3K2076 IC: 3048A-2076	MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Technical Manager
Test Report S/N: 1M2511240098-05-R3.C3K	Test Dates: 12/16/2025 - 02/02/2026	EUT Type: Portable Computing Device	Page 133 of 139

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.





Figure 7-12. Test Instrument & Measurement Setup


Test Notes

1. All modes of operation were investigated, and the worst-case emissions are reported using mid channel. The emissions found were not affected by the choice of channel used during testing.
2. The limit for an intentional radiator from 150kHz to 30MHz are specified in 15.207 and RSS-Gen (8.8).
3. $\text{Corr. (dB)} = \text{Cable loss (dB)} + \text{LISN insertion factor (dB)}$
4. $\text{QP/AV Level (dB}\mu\text{V)} = \text{QP/AV Analyzer/Receiver Level (dB}\mu\text{V)} + \text{Corr. (dB)}$
5. $\text{Margin (dB)} = \text{QP/AV Limit (dB}\mu\text{V)} - \text{QP/AV Level (dB}\mu\text{V)}$
6. Traces shown in plot are made using a peak detector.
7. Deviations to the Specifications: None.

FCC ID: C3K2076 IC: 3048A-2076	MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Technical Manager
Test Report S/N: 1M2511240098-05-R3.C3K	Test Dates: 12/16/2025 - 02/02/2026	EUT Type: Portable Computing Device	Page 134 of 139



Plot 7-184. Line-Conducted Test Plot (L1)



Plot 7-185. Line-Conducted Test Plot (N)

FCC ID: C3K2076 IC: 3048A-2076	MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Technical Manager
Test Report S/N: 1M2511240098-05-R3-C3K	Test Dates: 12/16/2025 - 02/02/2026	EUT Type: Portable Computing Device	Page 135 of 139

8.0 CONCLUSION

The data collected relate only to the item(s) tested and show that the **Microsoft Corporation Portable Computing Device FCC ID: C3K2076 / IC: 3048A-2076** is in compliance with Part 15 Subpart C (15.247) of the FCC Rules and RSS-247 of the ISED rules. After additional testing it is concluded that the component change detailed in the FCC Change Document does not meaningfully affect compliance.

FCC ID: C3K2076 IC: 3048A-2076	MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Technical Manager
Test Report S/N: 1M2511240098-05-R3.C3K	Test Dates: 12/16/2025 - 02/02/2026	EUT Type: Portable Computing Device	Page 136 of 139

9.0 APPENDIX A – DATA REFERENCING SPOT-CHECKS


The spot-check data presented in this section was measured on the variant model following the guidance of the FCC's Data Referencing guidance in KDB 484596 D01 v03. Each spot-check test on the EUT was performed using the same procedure and setting that were used to perform the test on the corresponding reference device. For the worst-case RSE data, the measurement is determined by an actual emission and not by noise floor.

All test cases were performed to verify the variant EUT is still in compliance with the spot-checked results to the reference device and was performed using the guidance of ANSI C63.10-2020.

Notes


- Each spot check test on the EUT was performed using the same procedure and setting that were used to perform the test on the corresponding reference device.

Conducted Spot-Checks – C3K2076



Plot 9-1. Conducted Output Power Measurements SISO ANT 1 (Spot-check)

FCC ID: C3K2076 IC: 3048A-2076	MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Technical Manager
Test Report S/N: 1M2511240098-05-R3.C3K	Test Dates: 12/16/2025 - 02/02/2026	EUT Type: Portable Computing Device	Page 137 of 139



Plot 9-2. Conducted Output Power Measurements SISO ANT 2 (Spot-check)


FCC ID: C3K2076 IC: 3048A-2076	MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)		Approved by: Technical Manager
Test Report S/N: 1M2511240098-05-R3.C3K	Test Dates: 12/16/2025 - 02/02/2026	EUT Type: Portable Computing Device	Page 138 of 139

Radiated Spot-Checks – C3K2076

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Duty Cycle Correction [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
7323.00	Avg	H	176	202	-75.86	9.08	-22.50	17.72	53.98	-36.26

Table 9-1. RSE Measurements (Spot-check)

Worst Case Mode:	Bluetooth
Worst Case Data Rate:	3 Mbps
Measurement Distance:	3 Meters
Operating Frequency:	2480MHz
Channel:	78



Plot 9-3. Radiated Restricted Upper Band Edge Measurement (Average) - Ant 2 – Spot-check

Results

FCC Rules	Test Item	Test Case	Units	Limit	Reference Model: 2085 C2PC	Variant Model: 2076 C2PC	Deviation (dB)	Max Deviation (dB)	Pass/Fail
15.247(b)(1)	Conducted Output Power	SISO ANT1 - 1M - CH39 - AVG	dBm	N/A	18.44	18.48	0.04	1	PASS
		SISO ANT2 - 1M - CH39 - AVG	dBm	N/A	18.43	18.96	0.53	1	PASS
15.209	Radiated Spurious Emissions	DUAL - Ch.39 - Average - 7323MHz	dBμV/m	53.98	20.09	17.72	-2.37	3	PASS
15.209	Radiated Band Edge Emissions	ANT2 Ch.78: 3Mbps - Average	dBμV/m	53.98	20.93	22.92	1.99	3	PASS

Table 9-2. Summary of Spot-checks

- END OF TEST REPORT -

FCC ID: C3K2076 IC: 3048A-2076	MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE)			Approved by: Technical Manager
Test Report S/N: 1M2511240098-05-R3.C3K	Test Dates: 12/16/2025 - 02/02/2026	EUT Type: Portable Computing Device		Page 139 of 139