



RF EXPOSURE TEST REPORT

Applicant Name:
Microsoft Corporation
One Microsoft Way
Redmond, WA 98052 USA

Date of Testing:
12/08/2025-01/27/2026
Test Site/Location:
Element, Columbia, MD, USA
Document Serial No.:
1M2511200095-01.C3K

FCC ID: C3K2085

APPLICANT: MICROSOFT CORPORATION

DUT Type: Portable Computing Device
Application Type: Class II Permissive Change
FCC Rule Part(s): CFR §2.1093
Model(s): 2085
Permissive Change(s): Please see change document

Equipment Class	Band & Mode	Tx Frequency	SAR	
			1g Body (W/kg)	
DTS	2.4 GHz WIFI	2412 - 2472 MHz	0.71	
NII	5 GHz WIFI	U-NII-1: 5180 - 5240 MHz U-NII-2A: 5260 - 5320 MHz U-NII-2C: 5500 - 5720 MHz U-NII-3: 5745 - 5825 MHz U-NII-4: 5845 - 5885 MHz	0.67	
6CD	6 GHz WIFI	U-NII-5: 5935 - 6415 MHz U-NII-6: 6435 - 6515 MHz U-NII-7: 6535 - 6875 MHz U-NII-8: 6895 - 7115 MHz	0.62	
DSS	2.4 GHz Bluetooth	2402 - 2480 MHz	0.79	
Simultaneous SAR per KDB 690783 D01v01r03:			1.59	
Equipment Class	Band & Mode	Tx Frequency	APD (W/m ²) Body	Reported PD (W/m ²)
6CD	6 GHz WIFI	U-NII-5: 5935 - 6415 MHz U-NII-6: 6435 - 6515 MHz U-NII-7: 6535 - 6875 MHz U-NII-8: 6895 - 7115 MHz	4.83	7.01

Only operations relevant to this permissive change were evaluated for compliance. Please see the original compliance evaluation in RF Exposure Technical Report S/N: 1M2311170118-01.C3K(R1) for complete evaluation of all other operating modes. The operational description includes a description of all changed items.

This wireless portable device has been shown to be capable of compliance for localized specific absorption rate (SAR) for uncontrolled environment/general population exposure limits specified in ANSI/IEEE C95.1-1992 and has been tested in accordance with the measurement procedures specified in Section 1.9 of this report; for North American frequency bands only.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them. Test results reported herein relate only to the item(s) tested.



RJ Ortanez
Executive Vice President



The SAR Tick is an initiative of the Mobile & Wireless Forum (MWF). While a product may be considered eligible, use of the SAR Tick logo requires an agreement with the MWF. Further details can be obtained by emailing: sartick@mwfai.info.

FCC ID: C3K2085	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
Document S/N: 1M2511200095-01.C3K	DUT Type: Portable Computing Device	Page 1 of 53

REV 22.0
03/30/2022

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element. If you have any questions or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact CT.INFO@ELEMENT.COM.

Revision	Description	Issue Date	Revised By
-	Initial Release	03/24/2026	WKR017811

FCC ID: C3K2085	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
Document S/N: 1M2511200095-01.C3K	DUT Type: Portable Computing Device	Page 2 of 53

REV 22.0
03/30/2022

TABLE OF CONTENTS

1	TEST LABORATORY INFORMATION.....	4
2	DEVICE UNDER TEST	5
3	INTRODUCTION	16
4	DOSIMETRIC ASSESSMENT	17
5	TEST CONFIGURATION POSITIONS.....	18
6	RF EXPOSURE LIMITS	19
7	FCC MEASUREMENT PROCEDURES.....	21
8	RF CONDUCTED POWERS.....	24
9	SYSTEM VERIFICATION.....	36
10	SAR DATA SUMMARY	39
11	POWER DENSITY DATA SUMMARY	46
12	SAR MEASUREMENT VARIABILITY	47
13	EQUIPMENT LIST.....	48
14	MEASUREMENT UNCERTAINTIES.....	49
15	CONCLUSION.....	51
16	REFERENCES	52
APPENDIX A: SAR TEST PLOTS		
APPENDIX B: SAR DIPOLE VERIFICATION PLOTS		
APPENDIX C: PROBE AND DIPOLE CALIBRATION CERTIFICATES		
APPENDIX D: SAR TISSUE SPECIFICATIONS		
APPENDIX E: MULTI-TX AND ANTENNA SAR CONSIDERATIONS		
APPENDIX F: SAR SYSTEM VALIDATION		
APPENDIX G: IEEE 802.11ax/be RU SAR EXCLUSION		
APPENDIX H: DUT ANTENNA DIAGRAM AND SAR TEST SETUP PHOTOGRAPHS		

FCC ID: C3K2085	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
Document S/N: 1M2511200095-01.C3K	DUT Type: Portable Computing Device	Page 3 of 53

REV 22.0
03/30/2022

1 TEST LABORATORY INFORMATION

1.1 Introduction

This test report for device subject to testing at an accredited testing laboratory has been generated by the testing laboratory that tested the device. Measurements were performed at various locations within Element Materials Technology. Detailed location and accredited information regarding the testing laboratories are provided below.

1.2 Test Laboratory Information

1.2.1 Testing Laboratory 1

Test Firm Name	ELEMENT MATERIALS TECHNOLOGY WASHINGTON DC LLC
Test Lab Location	7185 Oakland Mills Road, Columbia, MD 21046, United States Tel. +1.410.290.6652 / Fax +1.410.290.6654
Accreditation Info.	Lab Code. (ISED): 2451B
	CAB Identifier (NIST): US0110
	ISO/IEC 17025 (A2LA): CERT #2041.01
	
Measurement system No.	G, R, S

FCC ID: C3K2085	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
Document S/N: 1M2511200095-01.C3K	DUT Type: Portable Computing Device	Page 4 of 53

REV 22.0
03/30/2022

2 DEVICE UNDER TEST

2.1 Device Overview

Band & Mode	Operating Modes	Tx Frequency
2.4 GHz WIFI	Voice/Data	2412 - 2472 MHz
5 GHz WIFI	Voice/Data	U-NII-1: 5180 - 5240 MHz U-NII-2A: 5260 - 5320 MHz U-NII-2C: 5500 - 5720 MHz U-NII-3: 5745 - 5825 MHz U-NII-4: 5845 - 5885 MHz
6 GHz WIFI	Voice/Data	U-NII-5: 5935 - 6415 MHz U-NII-6: 6435 - 6515 MHz U-NII-7: 6535 - 6875 MHz U-NII-8: 6895 - 7115 MHz
2.4 GHz Bluetooth	Data	2402 - 2480 MHz
NFC	Data	13.56 MHz

FCC ID: C3K2085	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
Document S/N: 1M2511200095-01.C3K	DUT Type: Portable Computing Device	Page 5 of 53

REV 22.0
03/30/2022

2.2 Time-Averaging Algorithm for RF Exposure Compliance

This Device is enabled with the Qualcomm® FastConnect TAS feature for WLAN technologies. This feature performs time averaging algorithm in real time to control and manage transmitting power and ensure the time-averaged RF exposure is in compliance with FCC requirements all the time. Refer to Compliance Summary document for detailed description of Qualcomm® FastConnect TAS feature (report SN could be found in Section 2.11 – Bibliography).

Note that Bluetooth and NFC operations are not enabled with TAS.

The FastConnect TAS algorithm maintains the time-averaged transmit power, in turn, time-averaged RF exposure of SAR_design_target, below the predefined time-averaged power limit (i.e., P_{limit} for WLAN), for each characterized technology and band (see RF Exposure Part 0 Test Report, report SN can be found in Section 2.11 - Bibliography).

FastConnect TAS allows the device to transmit at higher power instantaneously, as high as P_{max} , when needed, but enforces power limiting to maintain time-averaged transmit power to P_{limit} . Below table shows Final P_{limit} settings and maximum tune up output power P_{max} configured for this EUT for various transmit conditions (Device State Index DSI for FastConnect.)

Exposure Scenario			Maximum Tune-Up Output Power*	Body
Averaging Volume				1g
Spacing				0mm
DSI				1
Technology/Band	Antenna	Antenna Group	P _{max}	P _{limit}
2.4 GHz WIFI	R	AG0	20.0	17.25
2.4 GHz WIFI	L	AG1	20.0	17.25
5 GHz WIFI UNII-1	R	AG0	16.5	15.75
5 GHz WIFI UNII-1	L	AG1	16.5	16.25
5 GHz WIFI UNII-2A	R	AG0	16.5	15.25
5 GHz WIFI UNII-2A	L	AG1	16.5	16.25
5 GHz WIFI UNII-2C	R	AG0	17.0	14.50
5 GHz WIFI UNII-2C	L	AG1	17.0	14.00
5 GHz WIFI UNII-3	R	AG0	19.5	14.00
5 GHz WIFI UNII-3	L	AG1	19.5	14.00
5 GHz WIFI UNII-4	R	AG0	16.5	14.00
5 GHz WIFI UNII-4	L	AG1	16.5	13.75
6 GHz WIFI UNII-5	R	AG0	16.5	12.75
6 GHz WIFI UNII-5	L	AG1	16.5	13.25
6 GHz WIFI UNII-6	R	AG0	7.5	7.50
6 GHz WIFI UNII-6	L	AG1	7.5	7.50
6 GHz WIFI UNII-7	R	AG0	17.0	12.75
6 GHz WIFI UNII-7	L	AG1	17.0	13.75
6 GHz WIFI UNII-8	R	AG0	7.5	7.50
6 GHz WIFI UNII-8	L	AG1	7.5	7.50

Notes:

1. MIMO is not included in SAR CHAR due to the two antennas being in separate Antenna Groups.
2. Maximum tune up output power P_{max} is used to configure EUT during RF tune up procedure. The maximum allowed output power is equal to maximum Tune up output power + 1dB device design uncertainty. SAR values in this report were scaled to this maximum time-averaged output power to determine compliance per KDB Publication 447498 D04v01.
3. The purpose of this report (Part 1 test) is to demonstrate that the EUT meets FCC SAR limits when transmitting in static transmission scenario at maximum allowable time-averaged power levels.

FCC ID: C3K2085	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
Document S/N: 1M2511200095-01.C3K	DUT Type: Portable Computing Device	Page 6 of 53

REV 22.0
03/30/2022

2.3 Power Reduction for SAR

This device used an independent fixed level power reduction mechanism for BT when the device is used in portable configuration and motion is sensed. Detailed descriptions of the power reduction mechanism are included in the operational description.

2.4 Nominal and Maximum Output Power Specifications

This device operates using the following maximum and nominal output power specifications. SAR values were scaled to the maximum allowed power to determine compliance per KDB Publication 447498 D04v01.

Note: Targets for 802.11ax/be RU operations can be found in 802.11ax/be RU SAR Exclusion Appendix.

2.4.1 2.4 GHz SISO/MIMO WLAN Output Powers

The below table is applicable in the following conditions:

- Pmax, DSI=0 (No Motion)

Band	IEEE 802.11 Modulated/Frame Output Power (in dBm)																							
	SISO / SISO in MIMO												SISO / SISO in MIMO											
	Antenna R						Antenna L						Antenna R						Antenna L					
	b	g	n	ac	ax (SU)	be (SU)	b	g	n	ac	ax (SU)	be (SU)	b	g	n	ac	ax (SU)	be (SU)	b	g	n	ac	ax (SU)	be (SU)
Maximum / Nominal Power	Max	Nom.	Max	Nom.	Max	Nom.	Max	Nom.	Max	Nom.	Max	Nom.	Max	Nom.	Max	Nom.	Max	Nom.	Max	Nom.	Max	Nom.	Max	Nom.
2.4 GHz WLAN 20MHz	ch. 1: 17.00	18.00	ch. 1: 14.00	15.00	ch. 1: 12.00	13.00	ch. 1: 12.00	13.00	ch. 1: 12.00	13.00	ch. 1: 12.00	13.00	ch. 1: 12.00	13.00	ch. 1: 12.00	13.00	ch. 1: 12.00	13.00	ch. 1: 12.00	13.00	ch. 1: 12.00	13.00	ch. 1: 12.00	13.00
	ch. 2: 18.00	19.00	ch. 2: 15.00	16.00	ch. 2: 14.00	15.00	ch. 2: 14.00	15.00	ch. 2: 14.00	15.00	ch. 2: 14.00	15.00	ch. 2: 14.00	15.00	ch. 2: 14.00	15.00	ch. 2: 14.00	15.00	ch. 2: 14.00	15.00	ch. 2: 14.00	15.00	ch. 2: 14.00	15.00
	ch. 3: 17.00	18.00	ch. 3: 14.00	15.00	ch. 3: 12.00	13.00	ch. 3: 12.00	13.00	ch. 3: 12.00	13.00	ch. 3: 12.00	13.00	ch. 3: 12.00	13.00	ch. 3: 12.00	13.00	ch. 3: 12.00	13.00	ch. 3: 12.00	13.00	ch. 3: 12.00	13.00	ch. 3: 12.00	13.00
	ch. 11: 18.00	19.00	ch. 11: 15.00	16.00	ch. 11: 14.00	15.00	ch. 11: 14.00	15.00	ch. 11: 14.00	15.00	ch. 11: 14.00	15.00	ch. 11: 14.00	15.00	ch. 11: 14.00	15.00	ch. 11: 14.00	15.00	ch. 11: 14.00	15.00	ch. 11: 14.00	15.00	ch. 11: 14.00	15.00
	ch. 12: 17.00	18.00	ch. 12: 12.00	13.00	ch. 12: 12.00	13.00	ch. 12: 12.00	13.00	ch. 12: 12.00	13.00	ch. 12: 12.00	13.00	ch. 12: 12.00	13.00	ch. 12: 12.00	13.00	ch. 12: 12.00	13.00	ch. 12: 12.00	13.00	ch. 12: 12.00	13.00	ch. 12: 12.00	13.00
	ch. 13: 15.00	16.00	ch. 13: -4.50	-5.50	ch. 13: -5.00	-6.00	ch. 13: -5.00	-6.00	ch. 13: -5.00	-6.00	ch. 13: -5.00	-6.00	ch. 13: -5.00	-6.00	ch. 13: -5.00	-6.00	ch. 13: -5.00	-6.00	ch. 13: -5.00	-6.00	ch. 13: -5.00	-6.00	ch. 13: -5.00	-6.00
	ch. 1: 17.00	18.00	ch. 1: 14.00	15.00	ch. 1: 12.00	13.00	ch. 1: 12.00	13.00	ch. 1: 12.00	13.00	ch. 1: 12.00	13.00	ch. 1: 12.00	13.00	ch. 1: 12.00	13.00	ch. 1: 12.00	13.00	ch. 1: 12.00	13.00	ch. 1: 12.00	13.00	ch. 1: 12.00	13.00
	ch. 2: 18.00	19.00	ch. 2: 15.00	16.00	ch. 2: 14.00	15.00	ch. 2: 14.00	15.00	ch. 2: 14.00	15.00	ch. 2: 14.00	15.00	ch. 2: 14.00	15.00	ch. 2: 14.00	15.00	ch. 2: 14.00	15.00	ch. 2: 14.00	15.00	ch. 2: 14.00	15.00	ch. 2: 14.00	15.00
	ch. 3: 17.00	18.00	ch. 3: 14.00	15.00	ch. 3: 12.00	13.00	ch. 3: 12.00	13.00	ch. 3: 12.00	13.00	ch. 3: 12.00	13.00	ch. 3: 12.00	13.00	ch. 3: 12.00	13.00	ch. 3: 12.00	13.00	ch. 3: 12.00	13.00	ch. 3: 12.00	13.00	ch. 3: 12.00	13.00
	ch. 11: 18.00	19.00	ch. 11: 15.00	16.00	ch. 11: 14.00	15.00	ch. 11: 14.00	15.00	ch. 11: 14.00	15.00	ch. 11: 14.00	15.00	ch. 11: 14.00	15.00	ch. 11: 14.00	15.00	ch. 11: 14.00	15.00	ch. 11: 14.00	15.00	ch. 11: 14.00	15.00	ch. 11: 14.00	15.00
	ch. 12: 17.00	18.00	ch. 12: 12.00	13.00	ch. 12: 12.00	13.00	ch. 12: 12.00	13.00	ch. 12: 12.00	13.00	ch. 12: 12.00	13.00	ch. 12: 12.00	13.00	ch. 12: 12.00	13.00	ch. 12: 12.00	13.00	ch. 12: 12.00	13.00	ch. 12: 12.00	13.00	ch. 12: 12.00	13.00
	ch. 13: 15.00	16.00	ch. 13: -4.50	-5.50	ch. 13: -5.00	-6.00	ch. 13: -5.00	-6.00	ch. 13: -5.00	-6.00	ch. 13: -5.00	-6.00	ch. 13: -5.00	-6.00	ch. 13: -5.00	-6.00	ch. 13: -5.00	-6.00	ch. 13: -5.00	-6.00	ch. 13: -5.00	-6.00	ch. 13: -5.00	-6.00

- DSI=1 (Motion)

Band	IEEE 802.11 Modulated/Frame Output Power (in dBm)																							
	SISO / SISO in MIMO												SISO / SISO in MIMO											
	Antenna R						Antenna L						Antenna R						Antenna L					
	b	g	n	ac	ax (SU)	be (SU)	b	g	n	ac	ax (SU)	be (SU)	b	g	n	ac	ax (SU)	be (SU)	b	g	n	ac	ax (SU)	be (SU)
Maximum / Nominal Power	Max	Nom.	Max	Nom.	Max	Nom.	Max	Nom.	Max	Nom.	Max	Nom.	Max	Nom.	Max	Nom.	Max	Nom.	Max	Nom.	Max	Nom.	Max	Nom.
2.4 GHz WLAN 20MHz	ch. 1: 17.00	18.00	ch. 1: 14.00	15.00	ch. 1: 12.00	13.00	ch. 1: 12.00	13.00	ch. 1: 12.00	13.00	ch. 1: 12.00	13.00	ch. 1: 12.00	13.00	ch. 1: 12.00	13.00	ch. 1: 12.00	13.00	ch. 1: 12.00	13.00	ch. 1: 12.00	13.00	ch. 1: 12.00	13.00
	ch. 2: 18.00	19.00	ch. 2: 15.00	16.00	ch. 2: 14.00	15.00	ch. 2: 14.00	15.00	ch. 2: 14.00	15.00	ch. 2: 14.00	15.00	ch. 2: 14.00	15.00	ch. 2: 14.00	15.00	ch. 2: 14.00	15.00	ch. 2: 14.00	15.00	ch. 2: 14.00	15.00	ch. 2: 14.00	15.00
	ch. 3: 17.00	18.00	ch. 3: 14.00	15.00	ch. 3: 12.00	13.00	ch. 3: 12.00	13.00	ch. 3: 12.00	13.00	ch. 3: 12.00	13.00	ch. 3: 12.00	13.00	ch. 3: 12.00	13.00	ch. 3: 12.00	13.00	ch. 3: 12.00	13.00	ch. 3: 12.00	13.00	ch. 3: 12.00	13.00
	ch. 11: 18.00	19.00	ch. 11: 15.00	16.00	ch. 11: 14.00	15.00	ch. 11: 14.00	15.00	ch. 11: 14.00	15.00	ch. 11: 14.00	15.00	ch. 11: 14.00	15.00	ch. 11: 14.00	15.00	ch. 11: 14.00	15.00	ch. 11: 14.00	15.00	ch. 11: 14.00	15.00	ch. 11: 14.00	15.00
	ch. 12: 17.00	18.00	ch. 12: 12.00	13.00	ch. 12: 12.00	13.00	ch. 12: 12.00	13.00	ch. 12: 12.00	13.00	ch. 12: 12.00	13.00	ch. 12: 12.00	13.00	ch. 12: 12.00	13.00	ch. 12: 12.00	13.00	ch. 12: 12.00	13.00	ch. 12: 12.00	13.00	ch. 12: 12.00	13.00
	ch. 13: 15.00	16.00	ch. 13: -4.50	-5.50	ch. 13: -5.00	-6.00	ch. 13: -5.00	-6.00	ch. 13: -5.00	-6.00	ch. 13: -5.00	-6.00	ch. 13: -5.00	-6.00	ch. 13: -5.00	-6.00	ch. 13: -5.00	-6.00	ch. 13: -5.00	-6.00	ch. 13: -5.00	-6.00	ch. 13: -5.00	-6.00
	ch. 1: 17.00	18.00	ch. 1: 14.00	15.00	ch. 1: 12.00	13.00	ch. 1: 12.00	13.00	ch. 1: 12.00	13.00	ch. 1: 12.00	13.00	ch. 1: 12.00	13.00	ch. 1: 12.00	13.00	ch. 1: 12.00	13.00	ch. 1: 12.00	13.00	ch. 1: 12.00	13.00	ch. 1: 12.00	13.00
	ch. 2: 18.00	19.00	ch. 2: 15.00	16.00	ch. 2: 14.00	15.00	ch. 2: 14.00	15.00	ch. 2: 14.00	15.00	ch. 2: 14.00	15.00	ch. 2: 14.00	15.00	ch. 2: 14.00	15.00	ch. 2: 14.00	15.00	ch. 2: 14.00	15.00	ch. 2: 14.00	15.00	ch. 2: 14.00	15.00
	ch. 3: 17.00	18.00	ch. 3: 14.00	15.00	ch. 3: 12.00	13.00	ch. 3: 12.00	13.00	ch. 3: 12.00	13.00	ch. 3: 12.00	13.00	ch. 3: 12.00	13.00	ch. 3: 12.00	13.00	ch. 3: 12.00	13.00	ch. 3: 12.00	13.00	ch. 3: 12.00	13.00	ch. 3: 12.00	13.00
	ch. 11: 18.00	19.00	ch. 11: 15.00	16.00	ch. 11: 14.00	15.00	ch. 11: 14.00	15.00	ch. 11: 14.00	15.00	ch. 11: 14.00	15.00	ch. 11: 14.00	15.00	ch. 11: 14.00	15.00	ch. 11: 14.00	15.00	ch. 11: 14.00	15.00	ch. 11: 14.00	15.00	ch. 11: 14.00	15.00
	ch. 12: 17.00	18.00	ch. 12: 12.00	13.00	ch. 12: 12.00	13.00	ch. 12: 12.00	13.00	ch. 12: 12.00	13.00	ch. 12: 12.00	13.00	ch. 12: 12.00	13.00	ch. 12: 12.00	13.00	ch. 12: 12.00	13.00	ch. 12: 12.00	13.00	ch. 12: 12.00	13.00	ch. 12: 12.00	13.00
	ch. 13: 15.00	16.00	ch. 13: -4.50	-5.50	ch. 13: -5.00	-6.00	ch. 13: -5.00	-6.00	ch. 13: -5.00	-6.00	ch. 13: -5.00	-6.00	ch. 13: -5.00	-6.00	ch. 13: -5.00	-6.00	ch. 13: -5.00	-6.00	ch. 13: -5.00	-6.00	ch. 13: -5.00	-6.00	ch. 13: -5.00	-6.00

FCC ID: C3K2085	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
Document S/N: 1M2511200095-01.C3K	DUT Type: Portable Computing Device	Page 7 of 53

2.4.2 5 GHz SISO/MIMO WLAN Output Power

The below table is applicable in the following conditions:

- Pmax, DSI=0 (No Motion)

Mode	Band	IEEE 802.11 Modulated Output Power (in dBm)																			
		SISO / SISO in MIMO										SISO / SISO in MIMO									
		Antenna R										Antenna L									
		a		n		ac (SU)		be (SU)		a		n		ac (SU)		be (SU)					
Maximum / Nominal Power	Max	Nom.	Max	Nom.	Max	Nom.	Max	Nom.	Max	Nom.	Max	Nom.	Max	Nom.	Max	Nom.	Max	Nom.			
5 GHz WiFi (20MHz BW)	UNII-1	17.00	16.00	17.50	16.50	17.50	16.50	17.50	16.50	17.50	16.50	17.00	16.00	17.50	16.50	17.50	16.50	17.50	16.50		
	UNII-2A	17.50	16.50	17.50	16.50	17.50	16.50	17.50	16.50	17.50	16.50	17.50	16.50	17.50	16.50	17.50	16.50	17.50	16.50		
	ch. 64: 18.00	17.00	16.00	ch. 64: 15.00	14.00	ch. 64: 15.00	14.00	ch. 64: 15.00	14.00	ch. 64: 15.00	14.00	ch. 64: 15.00	14.00	ch. 64: 15.00	14.00	ch. 64: 15.00	14.00	ch. 64: 15.00	14.00		
	UNII-2C	18.00	17.00	18.00	17.00	18.00	17.00	18.00	17.00	18.00	17.00	18.00	17.00	18.00	17.00	18.00	17.00	18.00	17.00		
5 GHz WiFi (40MHz BW)	ch. 144: 17.00	16.00	15.00	ch. 144: 17.00	16.50	ch. 144: 17.00	16.00	ch. 144: 17.00	16.50	ch. 144: 17.00	16.00	ch. 144: 17.00	16.50	ch. 144: 17.00	16.00	ch. 144: 17.00	16.50	ch. 144: 17.00	16.00		
	20.50	19.50	20.50	19.50	20.50	19.50	20.50	19.50	20.50	19.50	20.50	19.50	20.50	19.50	20.50	19.50	20.50	19.50			
	ch. 149: 15.00	14.00	ch. 149: 15.00	14.50	ch. 149: 15.00	14.00	ch. 149: 15.00	14.50	ch. 149: 15.00	14.00	ch. 149: 15.00	14.50	ch. 149: 15.00	14.00	ch. 149: 15.00	14.50	ch. 149: 15.00	14.00			
	UNII-4	14.50	13.50	14.50	13.50	14.50	13.50	14.50	13.50	14.50	13.50	14.50	13.50	14.50	13.50	14.50	13.50	14.50			
5 GHz WiFi (80MHz BW)	UNII-1	18.00	17.00	18.00	17.00	18.00	17.00	18.00	17.00	18.00	17.00	18.00	17.00	18.00	17.00	18.00	17.00	18.00	17.00		
	UNII-2A	18.00	17.00	18.00	17.00	18.00	17.00	18.00	17.00	18.00	17.00	18.00	17.00	18.00	17.00	18.00	17.00	18.00	17.00		
	UNII-2C	15.00	14.00	15.00	14.00	15.00	14.00	15.00	14.00	15.00	14.00	15.00	14.00	15.00	14.00	15.00	14.00	15.00	14.00		
	UNII-4	17.50	16.50	17.50	16.50	17.50	16.50	17.50	16.50	17.50	16.50	17.50	16.50	17.50	16.50	17.50	16.50	17.50	16.50		
5 GHz WiFi (160MHz BW)	UNII-1	14.50	13.50	14.50	13.50	14.50	13.50	14.50	13.50	14.50	13.50	14.50	13.50	14.50	13.50	14.50	13.50	14.50	13.50		
	UNII-2A	14.50	13.50	14.50	13.50	14.50	13.50	14.50	13.50	14.50	13.50	14.50	13.50	14.50	13.50	14.50	13.50	14.50	13.50		
	UNII-2C	18.00	17.00	18.00	17.00	18.00	17.00	18.00	17.00	18.00	17.00	18.00	17.00	18.00	17.00	18.00	17.00	18.00	17.00		
	UNII-4	106: 13.50	12.50	106: 13.50	12.50	106: 13.50	12.50	106: 13.50	12.50	106: 13.50	12.50	106: 13.50	12.50	106: 13.50	12.50	106: 13.50	12.50	106: 13.50	12.50		
5 GHz WiFi (160MHz BW)	UNII-1	13.50	12.50	13.50	12.50	13.50	12.50	13.50	12.50	13.50	12.50	13.50	12.50	13.50	12.50	13.50	12.50	13.50	12.50		
	UNII-12A	14.50	13.50	14.50	13.50	14.50	13.50	14.50	13.50	14.50	13.50	14.50	13.50	14.50	13.50	14.50	13.50	14.50	13.50		
	UNII-2C	13.50	12.50	13.50	12.50	13.50	12.50	13.50	12.50	13.50	12.50	13.50	12.50	13.50	12.50	13.50	12.50	13.50	12.50		
	UNII-3/4	12.50	11.50	12.50	11.50	12.50	11.50	12.50	11.50	12.50	11.50	12.50	11.50	12.50	11.50	12.50	11.50	12.50	11.50		

- DSI=1 (Motion)

Mode	Band	IEEE 802.11 Modulated Output Power (in dBm)																			
		SISO / SISO in MIMO										SISO / SISO in MIMO									
		Antenna R										Antenna L									
		a		n		ac		ae (SU)		be (SU)		a		n		ac		ae (SU)		be (SU)	
Maximum / Nominal Power		Max	Nom.	Max	Nom.	Max	Nom.	Max	Nom.	Max	Nom.	Max	Nom.	Max	Nom.	Max	Nom.	Max	Nom.	Max	Nom.
5 GHz WiFi (20MHz BW)	UNII-1	16.75	15.75	16.75	15.75	16.75	15.75	16.75	15.75	16.75	15.75	17.00	16.00	17.25	16.25	17.25	16.25	17.25	16.25	17.25	16.25
	UNII-2A	ch. 64: 15.00	16.25	16.25	16.25	15.25	16.25	16.25	16.25	15.25	16.25	17.25	16.25	17.25	16.25	17.25	16.25	17.25	16.25	17.25	16.25
	UNII-2C	15.50	14.50	15.50	14.50	14.00	15.50	14.00	15.50	14.00	15.50	14.00	14.00	15.50	14.00	15.50	14.00	15.50	14.00	15.50	14.00
	UNII-4	14.50	14.00	15.00	14.00	15.00	14.00	15.00	14.00	15.00	14.00	15.00	14.00	15.00	14.00	15.00	14.00	15.00	14.00	15.00	14.00
5 GHz WiFi (40MHz BW)	UNII-1	14.50	13.50	14.50	13.50	14.50	13.50	14.50	13.50	14.50	13.50	14.50	13.50	14.50	13.50	14.50	13.50	14.50	13.50	14.50	13.50
	UNII-2A	15.00	14.00	15.00	14.00	14.00	15.00	14.00	15.00	14.00	15.00	14.00	15.00	14.00	15.00	14.00	15.00	14.00	15.00	14.00	15.00
	UNII-2C	15.00	14.00	15.00	14.00	15.00	14.00	15.00	14.00	15.00	14.00	15.00	14.00	15.00	14.00	15.00	14.00	15.00	14.00	15.00	14.00
	UNII-3	15.00	14.00	15.00	14.00	15.00	14.00	15.00	14.00	15.00	14.00	15.00	14.00	15.00	14.00	15.00	14.00	15.00	14.00	15.00	14.00
5 GHz WiFi (80MHz BW)	UNII-1	14.50	13.50	14.50	13.50	14.50	13.50	14.50	13.50	14.50	13.50	14.75	13.75	14.75	13.75	14.75	13.75	14.75	13.75	14.75	13.75
	UNII-2A	14.50	13.50	14.50	13.50	14.50	13.50	14.50	13.50	14.50	13.50	14.50	13.50	14.50	13.50	14.50	13.50	14.50	13.50	14.50	13.50
	UNII-2C	ch. 106: 13.50	12.50	ch. 106: 13.50	12.50	ch. 106: 13.50	12.50	ch. 106: 13.50	12.50	ch. 106: 13.50	12.50	ch. 106: 13.50	12.50	ch. 106: 13.50	12.50	ch. 106: 13.50	12.50	ch. 106: 13.50	12.50	ch. 106: 13.50	12.50
	UNII-3	13.50	12.50	13.50	12.50	13.50	12.50	13.50	12.50	13.50	12.50	13.50	12.50	13.50	12.50	13.50	12.50	13.50	12.50	13.50	12.50
5 GHz WiFi (160MHz BW)	UNII-1	13.00	12.00	13.00	12.00	13.00	12.00	13.00	12.00	13.00	12.00	13.00	12.00	13.00	12.00	13.00	12.00	13.00	12.00	13.00	12.00
	UNII-1/2A	14.50	13.50	14.50	13.50	14.50	13.50	14.50	13.50	14.50	13.50	14.50	13.50	14.50	13.50	14.50	13.50	14.50	13.50	14.50	13.50
	UNII-2C	13.50	12.50	13.50	12.50	13.50	12.50	13.50	12.50	13.50	12.50	13.50	12.50	13.50	12.50	13.50	12.50	13.50	12.50	13.50	12.50
	UNII-3/4	12.50	11.50	12.50	11.50	12.50	11.50	12.50	11.50	12.50	11.50	12.50	11.50	12.50	11.50	12.50	11.50	12.50	11.50	12.50	11.50

FCC ID: C3K2085	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
Document S/N: 1M2511200095-01.C3K	DUT Type: Portable Computing Device	Page 8 of 53

REV 22.0
03/30/2022

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element. If you have any questions or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact CT.INFO@ELEMENT.COM.

2.4.3 6 GHz SISO/MIMO WLAN SP Output Power

The below table is applicable in the following conditions:

- P_{max}, DSI=0 (No Motion)

Mode	Band	IEEE 802.11 Modulated/Frame Output Power (in dBm)												
		SISO / SISO in MIMO						SISO / SISO in MIMO						
		Antenna R						Antenna L						
a		ax (SU)		be (SU)		a		ax (SU)		be (SU)				
Maximum / Nominal Power		Max	Nom.	Max	Nom.	Max	Nom.	Max	Nom.	Max	Nom.	Max	Nom.	
6 GHz WIFI (20MHz BW) - SP	UNII-5	15.50 ch. 2: 7.00	14.50 6.00	16.50 ch. 2: 7.00	15.50 6.00	16.50 ch. 2: 7.00	15.50 6.00	15.50 ch. 2: 7.00	14.50 6.00	16.50 ch. 2: 7.00	15.50 6.00	16.50 ch. 2: 7.00	15.50 6.00	
	UNII-7	16.50	15.50	17.00	16.00	17.00	16.00	16.50	15.50	17.00	16.00	17.00	16.00	
6 GHz WIFI (40MHz BW) - SP	UNII-5			17.50	16.50	17.50	16.50			17.50	16.50	17.50	16.50	
	UNII-7					18.00	17.00			18.00	17.00	18.00	17.00	18.00
6 GHz WIFI (80MHz BW) - SP	UNII-5			ch. 179: 15.00	14.00	ch. 179: 15.00	14.00			ch. 179: 15.00	14.00	ch. 179: 15.00	14.00	
	UNII-7													16.00
6 GHz WIFI (160MHz BW) - SP	UNII-5				16.00	15.00	16.00	15.00			16.00	15.00	16.00	15.00
	UNII-7													
6 GHz WIFI (320MHz BW) - SP	UNII-5				16.00	15.00	16.00	15.00			16.00	15.00	16.00	15.00
	UNII-7													
6 GHz WIFI (320MHz BW) - SP	UNII-5					15.50	14.50					15.50	14.50	

- DSI=1 (Motion)

Mode	Band	IEEE 802.11 Modulated/Frame Output Power (in dBm)														
		SISO / SISO in MIMO						SISO / SISO in MIMO								
		Antenna R						Antenna L								
a		ax (SU)		be (SU)		a		ax (SU)		be (SU)						
Maximum / Nominal Power		Max	Nom.	Max	Nom.	Max	Nom.	Max	Nom.	Max	Nom.	Max	Nom.			
6 GHz WIFI (20MHz BW) - SP	UNII-5	13.75 ch. 2: 7.00	12.75 6.00	13.75 ch. 2: 7.00	12.75 6.00	13.75 ch. 2: 7.00	12.75 6.00	14.25 ch. 2: 7.00	13.25 6.00	14.25 ch. 2: 7.00	13.25 6.00	14.25 ch. 2: 7.00	13.25 6.00			
	UNII-7	13.75	12.75	13.75	12.75	13.75	12.75	14.75	13.75	14.75	13.75	14.75	13.75			
6 GHz WIFI (40MHz BW) - SP	UNII-5			13.75	12.75	13.75	12.75			14.25	13.25	14.25	13.25			
	UNII-7			13.75	12.75	13.75	12.75			14.75	13.75	14.75	13.75			
6 GHz WIFI (80MHz BW) - SP	UNII-5			13.75	12.75	13.75	12.75			14.25	13.25	14.25	13.25			
	UNII-7			13.75	12.75	13.75	12.75			14.75	13.75	14.75	13.75			
6 GHz WIFI (160MHz BW) - SP	UNII-5			13.75	12.75	13.75	12.75			14.25	13.25	14.25	13.25			
	UNII-7			13.75	12.75	13.75	12.75			14.75	13.75	14.75	13.75			
6 GHz WIFI (320MHz BW) - SP	UNII-5						13.75			12.75					14.25	13.25
	UNII-7															

2.4.4 6 GHz SISO/MIMO WLAN LPI Output Power

The below table is applicable in the following conditions:

- P_{max}, DSI=0 (No Motion), DSI=1 (Motion)

Mode	Band	IEEE 802.11 Modulated/Frame Output Power (in dBm)											
		SISO / SISO in MIMO						SISO / SISO in MIMO					
		Antenna R						Antenna L					
		a		ax (SU)		be (SU)		a		ax (SU)		be (SU)	
Maximum / Nominal Power		Max	Nom.	Max	Nom.	Max	Nom.	Max	Nom.	Max	Nom.	Max	Nom.
6 GHz WIFI (20MHz BW) - LPI	UNII-5	-1.00	-2.00	-1.00	-2.00	-1.00	-2.00	-1.00	-2.00	-1.00	-2.00	-1.00	-2.00
	UNII-6	-1.50	-2.50	-1.50	-2.50	-1.50	-2.50	-1.50	-2.50	-1.50	-2.50	-1.50	-2.50
	UNII-7	-1.50	-2.50	-1.50	-2.50	-1.50	-2.50	-1.50	-2.50	-1.50	-2.50	-1.50	-2.50
	UNII-8	0.00	-1.00	0.00	-1.00	0.00	-1.00	0.00	-1.00	0.00	-1.00	0.00	-1.00
6 GHz WIFI (40MHz BW) - LPI	UNII-5			2.50	1.50	2.50	1.50			2.50	1.50	2.50	1.50
	UNII-6			1.50	0.50	1.50	0.50			1.50	0.50	1.50	0.50
	UNII-7			3.00	2.00	3.00	2.00			3.00	2.00	3.00	2.00
	UNII-8			3.00	2.00	3.00	2.00			3.00	2.00	3.00	2.00
6 GHz WIFI (80MHz BW) - LPI	UNII-5			4.00	3.00	4.00	3.00			4.00	3.00	4.00	3.00
	UNII-6			4.50	3.50	4.50	3.50			4.50	3.50	4.50	3.50
	UNII-7			5.50	4.50	5.50	4.50			5.50	4.50	5.50	4.50
	UNII-8			ch. 119: 4.50	3.50	ch. 119: 4.50	3.50			ch. 119: 4.50	3.50	ch. 119: 4.50	3.50
6 GHz WIFI (160MHz BW) - LPI	UNII-5			5.50	4.50	5.50	4.50			5.50	4.50	5.50	4.50
	UNII-6			6.50	5.50	6.50	5.50			6.50	5.50	6.50	5.50
	UNII-7			8.00	7.00	8.00	7.00			8.00	7.00	8.00	7.00
	UNII-8			8.00	7.00	8.00	7.00			8.00	7.00	8.00	7.00
6 GHz WIFI (320MHz BW) - LPI	UNII-5					9.00	8.00					9.00	8.00
	UNII-6					8.50	7.50					8.50	7.50
	UNII-7					8.50	7.50					8.50	7.50
	UNII-8					8.50	7.50					8.50	7.50

FCC ID: C3K2085	RF EXPOSURE PART 1 TEST REPORT		Approved by: Technical Manager
Document S/N: 1M2511200095-01.C3K	DUT Type: Portable Computing Device		Page 9 of 53

REV 22.0
03/30/2022

2.4.5 2.4 GHz Maximum Bluetooth Output Power

The below table is applicable in the following conditions:

- No Motion

Mode	Data Rate	Modulated Output Power (in dBm)					
		Single Antenna				Each Chain in Beam Forming Mode	
		Antenna R		Antenna L		Beam Forming	
Maximum / Nominal Power		Max	Nom.	Max	Nom.	Max	Nom.
Bluetooth	1Mbps	19.50	17.50	19.50	17.50	17.00	15.00
Bluetooth EDR	2Mbps	17.50	15.50	17.50	15.50	13.00	11.00
Bluetooth EDR	3Mbps	17.50	15.50	17.50	15.50	13.00	11.00
Bluetooth LE	1Mbps	20.50	18.50	20.50	18.50	15.50	13.50
Bluetooth LE	2Mbps	20.50	18.50	20.50	18.50	15.50	13.50
Bluetooth LE	125kbps	12.00	10.00	12.00	10.00	N/A	N/A
Bluetooth LE	500kbps	12.00	10.00	12.00	10.00	N/A	N/A

2.4.6 2.4 GHz Reduced Bluetooth Output Power

The below table is applicable in the following conditions:

- Motion sensor active

Mode	Data Rate	Modulated Output Power (in dBm)					
		Single Antenna				Each Chain in Beam Forming Mode	
		Antenna R		Antenna L		Beam Forming	
Maximum / Nominal Power		Max	Nom.	Max	Nom.	Max	Nom.
Bluetooth	1Mbps	19.25	17.25	19.25	17.25	17.00	15.00
Bluetooth EDR	2Mbps	17.50	15.50	17.50	15.50	13.00	11.00
Bluetooth EDR	3Mbps	17.50	15.50	17.50	15.50	13.00	11.00
Bluetooth LE	1Mbps	19.25	17.25	19.25	17.25	15.50	13.50
Bluetooth LE	2Mbps	19.25	17.25	19.25	17.25	15.50	13.50
Bluetooth LE	125kbps	12.00	10.00	12.00	10.00	N/A	N/A
Bluetooth LE	500kbps	12.00	10.00	12.00	10.00	N/A	N/A

FCC ID: C3K2085	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
Document S/N: 1M2511200095-01.C3K	DUT Type: Portable Computing Device	Page 10 of 53

REV 22.0
03/30/2022

The below table is applicable in the following conditions:

- Motion sensor active and WLAN active

Mode	Data Rate	Modulated Output Power (in dBm)					
		Single Antenna				Each Chain in Beam Forming Mode	
		Antenna R		Antenna L		Beam Forming	
Maximum / Nominal Power		Max	Nom.	Max	Nom.	Max	Nom.
Bluetooth	1Mbps	14.00	12.00	14.00	12.00	14.00	12.00
Bluetooth EDR	2Mbps	14.00	12.00	14.00	12.00	13.00	11.00
Bluetooth EDR	3Mbps	14.00	12.00	14.00	12.00	13.00	11.00
Bluetooth LE	1Mbps	14.00	12.00	14.00	12.00	14.00	12.00
Bluetooth LE	2Mbps	14.00	12.00	14.00	12.00	14.00	12.00
Bluetooth LE	125kbps	12.00	10.00	12.00	10.00	N/A	N/A
Bluetooth LE	500kbps	12.00	10.00	12.00	10.00	N/A	N/A

FCC ID: C3K2085	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
Document S/N: 1M2511200095-01.C3K	DUT Type: Portable Computing Device	Page 11 of 53

REV 22.0
03/30/2022

2.5 DUT Antenna Locations

The overall dimensions of this device is > 200 mm. A diagram showing the location of the device antennas can be found in the DUT Antenna Diagram and SAR Test Setup Photographs Appendix. Exact dimensions and separation distances are shown in the Technical Descriptions in the FCC filings.

Table 2-1
Device Edges/Sides for SAR Testing Tablet Mode

Antenna	Back	Front	Top	Bottom	Right	Left
R	Yes	No	Yes	No	Yes	No
L	Yes	No	Yes	No	No	Yes
NFC	Yes	No	Yes	Yes	Yes	Yes

Note: Per FCC KDB Publication 616217 D04v01r01, particular edges were not required to be evaluated for SAR based on the SAR exclusion threshold in KDB 447498 D04v01. Additional edges may have been evaluated for simultaneous transmission analysis.

2.6 Near Field Communications (NFC) Antenna

This DUT has NFC operations. The NFC antenna is integrated into the device for this model. Therefore, all SAR tests were performed with the device which already incorporates the NFC antenna. A diagram showing the location of the NFC antenna can be found in the DUT Antenna Diagram and SAR Test Setup Photographs Appendix.

FCC ID: C3K2085	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
Document S/N: 1M2511200095-01.C3K	DUT Type: Portable Computing Device	Page 12 of 53

REV 22.0
03/30/2022

2.7 Simultaneous Transmission Capabilities

According to FCC KDB Publication 447498 D04v01, transmitters are considered to be operating simultaneously when there is overlapping transmission, with the exception of transmissions during network hand-offs with maximum hand-off duration less than 30 seconds.

This device contains multiple transmitters that may operate simultaneously, and therefore requires a simultaneous transmission analysis according to FCC KDB Publication 447498 D04v01 4.3.2 procedures.

**Table 2-2
Simultaneous Transmission Scenarios**

No.	Capable Transmit Configuration	Laptop	Tablet
1	2.4 GHz WLAN MIMO	Yes	Yes
2	5 GHz WLAN MIMO	Yes	Yes
3	6 GHz WLAN MIMO	Yes	Yes
4	2.4 GHz Bluetooth Beam Forming	Yes	Yes
5	2.4 GHz WLAN Ant R + 2.4 GHz Bluetooth Ant L	Yes	Yes
6	2.4 GHz Bluetooth Ant R + 2.4 GHz WLAN Ant L	Yes	Yes
7	5 GHz WLAN Ant R + 2.4 GHz Bluetooth Ant L	Yes	Yes
8	6 GHz WLAN Ant R + 2.4 GHz Bluetooth Ant L	Yes	Yes
9	2.4 GHz Bluetooth Ant R + 5 GHz WLAN Ant L	Yes	Yes
10	2.4 GHz Bluetooth Ant R + 6 GHz WLAN Ant L	Yes	Yes
11	5 GHz WLAN MIMO + 2.4 GHz Bluetooth Ant R	Yes	Yes
12	6 GHz WLAN MIMO + 2.4 GHz Bluetooth Ant R	Yes	Yes
13	5 GHz WLAN MIMO + 2.4 GHz Bluetooth Ant L	Yes	Yes
14	6 GHz WLAN MIMO + 2.4 GHz Bluetooth Ant L	Yes	Yes
15	2.4 GHz WLAN MIMO + 5 GHz WLAN MIMO	Yes	Yes
16	2.4 GHz WLAN MIMO + 6 GHz WLAN MIMO	Yes	Yes
17	5 GHz WLAN MIMO + 2.4 GHz WLAN Ant R	Yes	Yes
18	6 GHz WLAN MIMO + 2.4 GHz WLAN Ant R	Yes	Yes
19	5 GHz WLAN MIMO + 2.4 GHz WLAN Ant L	Yes	Yes
20	6 GHz WLAN MIMO + 2.4 GHz WLAN Ant L	Yes	Yes
21	2.4 GHz Bluetooth Ant R + 2.4 GHz WLAN Ant L + 5 GHz WLAN Ant L	Yes	Yes
22	2.4 GHz Bluetooth Ant R + 2.4 GHz WLAN Ant L + 6 GHz WLAN Ant L	Yes	Yes
23	2.4 GHz WLAN Ant R + 5 GHz WLAN Ant R + 2.4 GHz Bluetooth Ant L	Yes	Yes
24	2.4 GHz WLAN Ant R + 6 GHz WLAN Ant R + 2.4 GHz Bluetooth Ant L	Yes	Yes
25	5 GHz WLAN MIMO + 2.4 GHz Bluetooth Ant R + 2.4 GHz WLAN Ant L	Yes	Yes
26	6 GHz WLAN MIMO + 2.4 GHz Bluetooth Ant R + 2.4 GHz WLAN Ant L	Yes	Yes
27	5 GHz WLAN MIMO + 2.4 GHz WLAN Ant R + 2.4 GHz Bluetooth Ant L	Yes	Yes
28	6 GHz WLAN MIMO + 2.4 GHz WLAN Ant R + 2.4 GHz Bluetooth Ant L	Yes	Yes
29	2.4 GHz WLAN Ant R + 5 GHz WLAN Ant L	Yes	Yes
30	2.4 GHz WLAN Ant R + 6 GHz WLAN Ant L	Yes	Yes
31	5 GHz WLAN Ant R + 2.4 GHz WLAN Ant L	Yes	Yes
32	6 GHz WLAN Ant R + 2.4 GHz WLAN Ant L	Yes	Yes
33	5 GHz WLAN Ant L + 2.4 GHz Bluetooth Ant L	Yes	Yes
34	6 GHz WLAN Ant L + 2.4 GHz Bluetooth Ant L	Yes	Yes
35	5 GHz WLAN Ant R + 2.4 GHz Bluetooth Ant R	Yes	Yes
36	6 GHz WLAN Ant R + 2.4 GHz Bluetooth Ant R	Yes	Yes
37	2.4 GHz WLAN MIMO + 5 GHz WLAN Ant R	Yes	Yes
38	2.4 GHz WLAN MIMO + 6 GHz WLAN Ant R	Yes	Yes
39	2.4 GHz WLAN MIMO + 5 GHz WLAN Ant L	Yes	Yes
40	2.4 GHz WLAN MIMO + 6 GHz WLAN Ant L	Yes	Yes
41	2.4 GHz WLAN Ant L + 5 GHz WLAN Ant L	Yes	Yes
42	2.4 GHz WLAN Ant L + 6 GHz WLAN Ant L	Yes	Yes
43	2.4 GHz WLAN Ant R + 5 GHz WLAN Ant R	Yes	Yes
44	2.4 GHz WLAN Ant R + 6 GHz WLAN Ant R	Yes	Yes
45	5 GHz WLAN MIMO + 2.4 GHz Bluetooth Beam Forming	Yes	Yes
46	6 GHz WLAN MIMO + 2.4 GHz Bluetooth Beam Forming	Yes	Yes
47	2.4 GHz WLAN Ant R + NFC	Yes	Yes
48	2.4 GHz WLAN Ant L + NFC	Yes	Yes
49	2.4 GHz Bluetooth Ant R + NFC	Yes	Yes
50	2.4 GHz Bluetooth Ant L + NFC	Yes	Yes
51	5 GHz WLAN Ant R + NFC	Yes	Yes
52	5 GHz WLAN Ant L + NFC	Yes	Yes
53	6 GHz WLAN Ant R + NFC	Yes	Yes
54	6 GHz WLAN Ant L + NFC	Yes	Yes

- 2.4 GHz WLAN Antenna R and 2.4 GHz Bluetooth Ant R share the same antenna path and cannot transmit simultaneously.
- 2.4 GHz WLAN Antenna L and 2.4 GHz Bluetooth Ant L share the same antenna path and cannot transmit simultaneously.
- 5 GHz WLAN and 6 GHz WLAN share the same antenna path and cannot transmit simultaneously.
- This device supports 2x2 MIMO Tx for WLAN 802.11a/g/n/ac/ax/be. 802.11a/g/n/ac/ax/be supports CDD and STBC and 802.11n/ac/ax/be additionally supports SDM.
- This device supports Bluetooth Tethering.
- For scenarios #1-46, WLAN simultaneous TX modes can also transmit simultaneously with the NFC (13.56 MHz) transmitter.

FCC ID: C3K2085	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
Document S/N: 1M2511200095-01.C3K	DUT Type: Portable Computing Device	Page 13 of 53

REV 22.0
03/30/2022

2.8 Miscellaneous SAR Test Considerations

This device supports IEEE 802.11ac with the following features:

- a) Up to 160 MHz Bandwidth only
- b) No aggregate channel configurations
- c) 2 Tx antenna output
- d) 256 QAM is supported
- e) TDWR and Band gap channels are supported

This device supports IEEE 802.11ax/be with the following features:

- a) Up to 320 MHz Bandwidth only for 6 GHz
- b) Up to 160 MHz Bandwidth only for 5 GHz
- c) Up to 40 MHz Bandwidth only for 2.4 GHz
- d) 2 Tx antenna output
- e) Up to 1024 QAM is supported
- f) TDWR and Band gap channels are supported for 5/6 GHz
- g) MU-MIMO UL Operations are not supported

This device supports channel 1-13 for 2.4 GHz WLAN. However, because channel 12/13 targets are not higher than that of channels 1-11, channels 1, 6, and 11 were considered for SAR testing per FCC KDB 248227 D01V02r02.

Per FCC guidance, SAR was performed using 6.5 GHz SAR probe calibration factors. FCC KDB 648474 and FCC KDB 248227 were followed for test positions, distances, and modes. Per TCB workshop October 2020 notes, 5 channels were tested. Absorbed power density (APD) using a 4cm² averaging area is reported based on SAR measurements. Incident power density is evaluated at 0mm and measured at 2mm ensuring that the resolution is sufficient such that integrated power density (iPD) between d=2mm and d= λ /5mm is $\geq$ -1dB per equipment manufacturer guidance. Power density results are scaled up for uncertainty above 30%.

Per FCC Guidance, 802.11ax/be RU was considered a higher order 802.11 mode when compared to a/b/g/n/ac/be to apply KDB Publication 248227 D01v02r02 for OFDM mode selection. Therefore, SAR tests were not required for 802.11ax/be RU based on the maximum allowed output powers of OFDM modes and the reported SAR values. Per FCC Guidance, maximum conducted powers were performed for each RU size to demonstrate that the output powers would not be higher than the other OFDM 802.11 modes.

When U-NII-1 and U-NII-2A bands have the same maximum output power and the highest reported SAR for U-NII-2A is less than 1.2 W/kg, SAR is not required for U-NII-1 band according to FCC KDB Publication 248227 D01v02r02.

FCC ID: C3K2085	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
Document S/N: 1M2511200095-01.C3K	DUT Type: Portable Computing Device	Page 14 of 53

REV 22.0
03/30/2022

2.9 Guidance Applied

- IEEE 1528-2013
- FCC KDB Publication 248227 D01v02r02 (SAR Considerations for 802.11 Devices)
- FCC KDB Publication 447498 D04v01 (Interim General SAR Guidance)
- FCC KDB Publication 865664 D01v01r04, D02v01r02 (SAR Measurements up to 6 GHz)
- FCC KDB Publication 616217 D04v01r02 (Tablet/Laptop)
- FCC KDB 648474 D04 (Accessories)
- April 2019 TCB Workshop Notes (IEEE 802.11ax)
- IEC/IEEE 63195-1:2022
- IEC 62479:2010
- November 2017, October 2018, April 2019, November 2019, October 2020 TCB Workshop Notes (IEEE 802.11ax)
- SPEAG DASY6 System Handbook
- SPEAG DASY6 Application Note (Interim Procedures for Devices Operating at 6-10 GHz) (Nov 2021)

2.10 Device Serial Numbers

Several samples with identical hardware were used to support SAR and PD testing. The manufacturer has confirmed that the device(s) tested have the same physical, mechanical and thermal characteristics and are within operational tolerances expected for production units. The serial numbers used for each test are indicated alongside the results in Section 10 and Section 11.

2.11 Bibliography

Report Type	Report Serial Number
RF Exposure Part 0 Test Report	1M2511200095-13.C3K
RF Exposure Part 2 Test Report	1M2511200095-16.C3K
RF Exposure Compliance Summary Report	1M2511200095-14.C3K
RF Exposure Part 0 Test Report (Original filing)	1M2311170118-21.C3K
RF Exposure Part 1 Test Report (Original filing)	1M2311170118-01.C3K
RF Exposure Part 2 Test Report (Original filing)	1M2311170118-22.C3K
RF Exposure Compliance Summary Report (Original filing)	1M2311170118-02.C3K

FCC ID: C3K2085	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
Document S/N: 1M2511200095-01.C3K	DUT Type: Portable Computing Device	Page 15 of 53

REV 22.0
03/30/2022

3 INTRODUCTION

The FCC and Innovation, Science, and Economic Development Canada have adopted the guidelines for evaluating the environmental effects of radio frequency (RF) radiation in ET Docket 93-62 on Aug. 6, 1996 and Health Canada Safety Code 6 to protect the public and workers from the potential hazards of RF emissions due to FCC-regulated portable devices. [1]

The safety limits used for the environmental evaluation measurements are based on the criteria published by the American National Standards Institute (ANSI) for localized specific absorption rate (SAR) in IEEE/ANSI C95.1-1992 Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz [3] and Health Canada RF Exposure Guidelines Safety Code 6 [22]. The measurement procedure described in IEEE/ANSI C95.3-2002 Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields - RF and Microwave [4] is used for guidance in measuring the Specific Absorption Rate (SAR) due to the RF radiation exposure from the Equipment Under Test (EUT). These criteria for SAR evaluation are similar to those recommended by the International Committee for Non-Ionizing Radiation Protection (ICNIRP) in Biological Effects and Exposure Criteria for Radiofrequency Electromagnetic Fields,” Report No. Vol 74. SAR is a measure of the rate of energy absorption due to exposure to an RF transmitting source. SAR values have been related to threshold levels for potential biological hazards.

3.1 SAR Definition

Specific Absorption Rate is defined as the time derivative (rate) of the incremental energy (dU) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dV) of a given density (ρ). It is also defined as the rate of RF energy absorption per unit mass at a point in an absorbing body (see Equation 3-1).

Equation 3-1
SAR Mathematical Equation

$$SAR = \frac{d}{dt} \left(\frac{dU}{dm} \right) = \frac{d}{dt} \left(\frac{dU}{\rho dv} \right)$$

SAR is expressed in units of Watts per Kilogram (W/kg).

$$SAR = \frac{\sigma \cdot E^2}{\rho}$$

where:

- σ = conductivity of the tissue-simulating material (S/m)
- ρ = mass density of the tissue-simulating material (kg/m³)
- E = Total RMS electric field strength (V/m)

NOTE: The primary factors that control rate of energy absorption were found to be the wavelength of the incident field in relation to the dimensions and geometry of the irradiated organism, the orientation of the organism in relation to the polarity of field vectors, the presence of reflecting surfaces, and whether conductive contact is made by the organism with a ground plane.[6]

FCC ID: C3K2085	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
Document S/N: 1M2511200095-01.C3K	DUT Type: Portable Computing Device	Page 16 of 53

REV 22.0
03/30/2022

4 DOSIMETRIC ASSESSMENT

4.1 Measurement Procedure

The evaluation was performed using the following procedure compliant to FCC KDB Publication 865664 D01v01r04 and IEEE 1528-2013:

1. The SAR distribution at the exposed side of the head or body was measured at a distance no greater than 5.0 mm from the inner surface of the shell. The area covered the entire dimension of the device-head and body interface and the horizontal grid resolution was determined per FCC KDB Publication 865664 D01v01r04 (See Table 4-1) and IEEE 1528-2013.
2. The point SAR measurement was taken at the maximum SAR region determined from Step 1 to enable the monitoring of SAR fluctuations/drifts during the 1g/10g cube evaluation. SAR at this fixed point was measured and used as a reference value.
3. Based on the area scan data, the peak of the region with maximum SAR was determined by spline interpolation. Around this point, a volume was assessed according to the measurement resolution and volume size requirements of FCC KDB Publication 865664 D01v01r04 (See Table 4-1) and IEEE 1528-2013. On the basis of this data set, the spatial peak SAR value was evaluated with the following procedure (see references or the DASY manual online for more details):
 - a. SAR values at the inner surface of the phantom are extrapolated from the measured values along the line away from the surface with spacing no greater than that in Table 4-1. The extrapolation was based on a least-squares algorithm. A polynomial of the fourth order was calculated through the points in the z-axis (normal to the phantom shell).
 - b. After the maximum interpolated values were calculated between the points in the cube, the SAR was averaged over the spatial volume (1g or 10g) using a 3D-Spline interpolation algorithm. The 3D-spline is composed of three one-dimensional splines with the “Not a knot” condition (in x, y, and z directions). The volume was then integrated with the trapezoidal algorithm. One thousand points (10 x 10 x 10) were obtained through interpolation, in order to calculate the averaged SAR.
 - c. All neighboring volumes were evaluated until no neighboring volume with a higher average value was found.
4. The SAR reference value, at the same location as step 2, was re-measured after the zoom scan was complete to calculate the SAR drift. If the drift deviated by more than 5%, the SAR test and drift measurements were repeated.




Figure 4-1
Sample SAR Area
Scan

Table 4-1
Area and Zoom Scan Resolutions per FCC KDB Publication 865664 D01v01r04*

Frequency	Maximum Area Scan Resolution (mm) ($\Delta x_{\text{area}}, \Delta y_{\text{area}}$)	Maximum Zoom Scan Resolution (mm) ($\Delta x_{\text{zoomTV}}, \Delta y_{\text{zoom}}$)	Maximum Zoom Scan Spatial Resolution (mm)			Minimum Zoom Scan Volume (mm) (x,y,z)
			Uniform Grid	Graded Grid		
				$\Delta z_{\text{zoom}}(n)$	$\Delta z_{\text{zoom}}(1)^*$	
≤2 GHz	≤15	≤8	≤5	≤4	≤1.5* $\Delta z_{\text{zoom}}(n-1)$	≥30
2-3 GHz	≤12	≤5	≤5	≤4	≤1.5* $\Delta z_{\text{zoom}}(n-1)$	≥30
3-4 GHz	≤12	≤5	≤4	≤3	≤1.5* $\Delta z_{\text{zoom}}(n-1)$	≥28
4-5 GHz	≤10	≤4	≤3	≤2.5	≤1.5* $\Delta z_{\text{zoom}}(n-1)$	≥25
5-6 GHz	≤10	≤4	≤2	≤2	≤1.5* $\Delta z_{\text{zoom}}(n-1)$	≥22

*Also compliant to IEEE 1528-2013 Table 6

FCC ID: C3K2085	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
Document S/N: 1M2511200095-01.C3K	DUT Type: Portable Computing Device	Page 17 of 53

REV 22.0
03/30/2022

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element. If you have any questions or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact CT.INFO@ELEMENT.COM.

5 TEST CONFIGURATION POSITIONS

5.1 Device Holder

The device holder is made out of low-loss POM material having the following dielectric parameters: relative permittivity $\epsilon = 3$ and loss tangent $\delta = 0.02$.

5.2 SAR Testing per KDB Publication 616217 D04v01r02

Per FCC KDB Publication 616217 D04v01r02, the back surface and edges of the portable computing devices should be tested for SAR compliance with the device touching the phantom. The SAR Exclusion Threshold in KDB 447498 D04v01 can be applied to determine SAR test exclusion for adjacent edge configurations. The closest distance from the antenna to an adjacent device edge is used to determine if SAR testing is required for the adjacent edges, with the adjacent edge positioned against the phantom and the edge containing the antenna positioned perpendicular to the phantom.

FCC ID: C3K2085	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
Document S/N: 1M2511200095-01.C3K	DUT Type: Portable Computing Device	Page 18 of 53

REV 22.0
03/30/2022

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element. If you have any questions or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact CT.INFO@ELEMENT.COM.

6 RF EXPOSURE LIMITS

6.1 Uncontrolled Environment

UNCONTROLLED ENVIRONMENTS are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure. The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity.

6.2 Controlled Environment

CONTROLLED ENVIRONMENTS are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e. as a result of employment or occupation). In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. This exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

6.3 RF Exposure Limits for Frequencies Below 6 GHz

Table 6-1
SAR Human Exposure Specified in ANSI/IEEE C95.1-1992 and Health Canada Safety Code 6

HUMAN EXPOSURE LIMITS		
	UNCONTROLLED ENVIRONMENT <i>General Population</i> (W/kg) or (mW/g)	CONTROLLED ENVIRONMENT <i>Occupational</i> (W/kg) or (mW/g)
Peak Spatial Average SAR Head	1.6	8.0
Whole Body SAR	0.08	0.4
Peak Spatial Average SAR Hands, Feet, Ankle, Wrists, etc.	4.0	20

1. The Spatial Peak value of the SAR averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.
2. The Spatial Average value of the SAR averaged over the whole body.
3. The Spatial Peak value of the SAR averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.

FCC ID: C3K2085	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
Document S/N: 1M2511200095-01.C3K	DUT Type: Portable Computing Device	Page 19 of 53

REV 22.0
03/30/2022

6.4 RF Exposure Limits for Frequencies Above 6 GHz

Per §1.1310 (d)(3), the MPE limits are applied for frequencies above 6 GHz. Power Density is expressed in units of W/m^2 or mW/cm^2 .

Peak Spatially Averaged Power Density was evaluated over a circular area of 4 cm^2 per interim FCC Guidance for near-field power density evaluations per October 2018 TCB Workshop notes.

Table 6-2
Human Exposure Limits Specified in FCC 47 CFR §1.1310

Human Exposure to Radiofrequency (RF) Radiation Limits		
Frequency Range [MHz]	Power Density [mW/cm ²]	Average Time [Minutes]
(A) Limits For Occupational / Controlled Environments		
1,500 – 100,000	5.0	6
(B) Limits For General Population / Uncontrolled Environments		
1,500 – 100,000	1.0	30

Note: 1.0 mW/cm² is 10 W/m²

FCC ID: C3K2085	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
Document S/N: 1M2511200095-01.C3K	DUT Type: Portable Computing Device	Page 20 of 53

REV 22.0
03/30/2022

7 FCC MEASUREMENT PROCEDURES

Power measurements for licensed transmitters are performed using a base station simulator under digital average power.

7.1 Measured and Reported SAR

Per FCC KDB Publication 447498 D04v01, when SAR is not measured at the maximum power level allowed for production units, the results must be scaled to the maximum tune-up tolerance limit according to the power applied to the individual channels tested to determine compliance. For simultaneous transmission, the measured aggregate SAR must be scaled according to the sum of the differences between the maximum tune-up tolerance and actual power used to test each transmitter. When SAR is measured at or scaled to the maximum tune-up tolerance limit, the results are referred to as *reported* SAR. The highest *reported* SAR results are identified on the grant of equipment authorization according to procedures in KDB 690783 D01v01r03.

7.2 SAR Testing with 802.11 Transmitters

The normal network operating configurations of 802.11 transmitters are not suitable for SAR measurements. Unpredictable fluctuations in network traffic and antenna diversity conditions can introduce undesirable variations in SAR results. The SAR for these devices should be measured using chipset based test mode software to ensure the results are consistent and reliable. See KDB Publication 248227 D01v02r02 for more details.

7.2.1 General Device Setup

Chipset based test mode software is hardware dependent and generally varies among manufacturers. The device operating parameters established in test mode for SAR measurements must be identical to those programmed in production units, including output power levels, amplifier gain settings and other RF performance tuning parameters.

A periodic duty factor is required for current generation SAR systems to measure SAR. When 802.11 frame gaps are accounted for in the transmission, a maximum transmission duty factor of 92 - 96% is typically achievable in most test mode configurations. A minimum transmission duty factor of 85% is required to avoid certain hardware and device implementation issues related to wide range SAR scaling. The reported SAR is scaled to 100% transmission duty factor to determine compliance at the maximum tune-up tolerance limit.

7.2.2 U-NII-1 and U-NII-2A

For devices that operate in both U-NII-1 and U-NII-2A bands, when the same maximum output power is specified for both bands, SAR measurement using OFDM SAR test procedures is not required for U-NII-1 unless the highest reported SAR for U-NII-2A is > 1.2 W/kg. When different maximum output powers are specified for the bands, SAR measurement for the U-NII band with the lower maximum output power is not required unless the highest reported SAR for the U-NII band with the higher maximum output power, adjusted by the ratio of lower to higher specified maximum output power for the two bands, is > 1.2 W/kg. When 10g SAR measurement is considered, a factor of 2.5 is applied to the thresholds above.

7.2.3 U-NII-2C and U-NII-3

The frequency range covered by U-NII-2C and U-NII-3 is 380 MHz (5.47 – 5.85 GHz), which requires a minimum of at least two SAR probe calibration frequency points to support SAR measurements. When Terminal Doppler Weather Radar (TDWR) restriction applies, the channels at 5.60 – 5.65 GHz in U-NII-2C band must be disabled with acceptable mechanisms and documented in the equipment certification. Unless band gap channels are permanently disabled, SAR must be considered for these channels. Each band is tested independently according to the normally required OFDM SAR measurement and probe calibration frequency points requirements.

FCC ID: C3K2085	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
Document S/N: 1M2511200095-01.C3K	DUT Type: Portable Computing Device	Page 21 of 53

REV 22.0
03/30/2022

7.2.4 Initial Test Position Procedure

For exposure conditions with multiple test positions, such as handset operating next to the ear, devices with hotspot mode or UMPC mini-tablet, procedures for initial test position can be applied. Using the transmission mode determined by the DSSS procedure or initial test configuration, area scans are measured for all positions in an exposure condition. The test position with the highest extrapolated (peak) SAR is used as the initial test position. When reported SAR for the initial test position is ≤ 0.4 W/kg, no additional testing for the remaining test positions is required. Otherwise, SAR is evaluated at the subsequent highest peak SAR positions until the reported SAR result is ≤ 0.8 W/kg or all test positions are measured. When 10g SAR measurement is considered, a factor of 2.5 is applied to the thresholds above.

7.2.5 2.4 GHz SAR Test Requirements

SAR is measured for 2.4 GHz 802.11b DSSS using either the fixed test position or, when applicable, the initial test position procedure. SAR test reduction is determined according to the following:

- 1) When the reported SAR of the highest measured maximum output power channel for the exposure configuration is ≤ 0.8 W/kg, no further SAR testing is required for 802.11b DSSS in that exposure configuration.
- 2) When the reported SAR is > 0.8 W/kg, SAR is required for that position using the next highest measured output power channel. When any reported SAR is > 1.2 W/kg, SAR is required for the third channel; i.e., all channels require testing.

2.4 GHz 802.11 g/n/ax OFDM are additionally evaluated for SAR if the highest reported SAR for 802.11b, adjusted by the ratio of the OFDM to DSSS specified maximum output power, is > 1.2 W/kg. When SAR is required for OFDM modes in 2.4 GHz band, the Initial Test Configuration Procedures should be followed. When 10g SAR measurement is considered, a factor of 2.5 is applied to the thresholds above.

7.2.6 OFDM Transmission Mode and SAR Test Channel Selection

When the same maximum output power was specified for multiple OFDM transmission mode configurations in a frequency band or aggregated band, SAR is measured using the configuration with the largest channel bandwidth, lowest order modulation and lowest data rate. When the maximum output power of a channel is the same for equivalent OFDM configurations; for example, 802.11a, 802.11n and 802.11ac or 802.11g and 802.11n with the same channel bandwidth, modulation and data rate etc., the lower order 802.11 mode i.e., 802.11a, then 802.11n and 802.11ac or 802.11g then 802.11n, is used for SAR measurement. Per April 2019 TCB Workshop guidance, 802.11ax was considered the highest order 802.11 mode. When the maximum output power are the same for multiple test channels, either according to the default or additional power measurement requirements, SAR is measured using the channel closest to the middle of the frequency band or aggregated band. When there are multiple channels with the same maximum output power, SAR is measured using the higher number channel.

7.2.7 Initial Test Configuration Procedure

For OFDM, an initial test configuration is determined for each frequency band and aggregated band, according to the transmission mode with the highest maximum output power specified for SAR measurements. When the same maximum output power is specified for multiple OFDM transmission mode configurations in a frequency band or aggregated band, SAR is measured using the configuration(s) with the largest channel bandwidth, lowest order modulation, lowest data rate and lowest order IEEE 802.11 mode. The channel of the transmission mode with the highest average RF output conducted power will be the initial test configuration.

FCC ID: C3K2085	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
Document S/N: 1M2511200095-01.C3K	DUT Type: Portable Computing Device	Page 22 of 53

REV 22.0
03/30/2022

When the reported SAR is ≤ 0.8 W/kg, no additional measurements on other test channels are required. Otherwise, SAR is evaluated using the subsequent highest average RF output channel until the reported SAR result is ≤ 1.2 W/kg or all channels are measured. When there are multiple untested channels having the same subsequent highest average RF output power, the channel with higher frequency from the lowest 802.11 mode is considered for SAR measurements (See Section 7.2.6). When 10g SAR measurement is considered, a factor of 2.5 is applied to the thresholds above.

7.2.8 Subsequent Test Configuration Procedures

For OFDM configurations in each frequency band and aggregated band, SAR is evaluated for initial test configuration using the fixed test position or the initial test position procedure. When the highest reported SAR (for the initial test configuration), adjusted by the ratio of the specified maximum output power of the subsequent test configuration to initial test configuration, is ≤ 1.2 W/kg, no additional SAR tests for the subsequent test configurations are required. When 10g SAR measurement is considered, a factor of 2.5 is applied to the thresholds above.

7.2.9 MIMO SAR considerations

Per KDB Publication 248227 D01v02r02, the simultaneous SAR provisions in KDB Publication 447498 D04v01 should be applied to determine simultaneous transmission SAR test exclusion for WIFI MIMO. If the sum of 1g single transmission chain SAR measurements is < 1.6 W/kg, no additional SAR measurements for MIMO are required. Alternatively, SAR for MIMO can be measured with all antennas transmitting simultaneously at the specified maximum output power of MIMO operation. When 10g SAR measurement is considered, a factor of 2.5 is applied to the thresholds above.

FCC ID: C3K2085	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
Document S/N: 1M2511200095-01.C3K	DUT Type: Portable Computing Device	Page 23 of 53

REV 22.0
03/30/2022

8 RF CONDUCTED POWERS

8.1 WLAN Conducted Powers

Table 8-1
2.4 GHz WLAN Measured P_{Limit} Average Power for DSI = 1 (Motion) – Antenna R LCD

2.4GHz WIFI (20MHz 802.11b SISO ANT R)			
Freq. [MHz]	Channel	Detector	Conducted Power [dBm]
2412	1	Average	17.35
2417	2		17.82
2422	3		17.93
2437	6		18.04
2457	10		18.24
2462	11		17.72
2.4GHz WIFI (20MHz 802.11g SISO ANT R)			
Freq. [MHz]	Channel	Detector	Conducted Power [dBm]
2412	1	Average	13.93
2417	2		15.04
2422	3		16.99
2427	4		18.06
2437	6		17.77
2457	10		18.03
2462	11		16.36

Table 8-2
2.4 GHz WLAN Measured P_{Limit} Average Power for DSI = 1 (Motion) – Antenna R OLED

2.4GHz WIFI (20MHz 802.11b SISO ANT R)			
Freq. [MHz]	Channel	Detector	Conducted Power [dBm]
2412	1	Average	16.70
2417	2		16.81
2422	3		18.11
2437	6		18.15
2457	10		18.19
2462	11		16.97
2.4GHz WIFI (20MHz 802.11g SISO ANT R)			
Freq. [MHz]	Channel	Detector	Conducted Power [dBm]
2412	1	Average	13.85
2417	2		15.42
2422	3		16.95
2427	4		18.18
2437	6		17.92
2457	10		17.86
2462	11		16.27

FCC ID: C3K2085	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
Document S/N: 1M2511200095-01.C3K	DUT Type: Portable Computing Device	Page 24 of 53

REV 22.0
03/30/2022

Table 8-3
2.4 GHz WLAN Measured P_{Limit} Average Power for DSI = 1 (Motion) – Antenna L LCD

2.4GHz WIFI (20MHz 802.11b SISO ANT L)			
Freq. [MHz]	Channel	Detector	Conducted Power [dBm]
2412	1	Average	17.25
2417	2		17.85
2422	3		17.96
2437	6		17.88
2457	10		17.87
2462	11		17.96
2.4GHz WIFI (20MHz 802.11g SISO ANT L)			
Freq. [MHz]	Channel	Detector	Conducted Power [dBm]
2412	1	Average	13.75
2417	2		15.35
2422	3		16.56
2427	4		18.16
2437	6		18.01
2457	10		17.91
2462	11		15.43

Table 8-4
2.4 GHz WLAN Measured P_{Limit} Average Power for DSI = 1 (Motion) – Antenna L OLED

2.4GHz WIFI (20MHz 802.11b SISO ANT L)			
Freq. [MHz]	Channel	Detector	Conducted Power [dBm]
2412	1	Average	16.78
2417	2		17.02
2422	3		18.10
2437	6		18.09
2457	10		18.11
2462	11		17.47
2.4GHz WIFI (20MHz 802.11g SISO ANT L)			
Freq. [MHz]	Channel	Detector	Conducted Power [dBm]
2412	1	Average	13.87
2417	2		15.40
2422	3		16.62
2427	4		17.86
2437	6		18.15
2457	10		18.14
2462	11		16.06

FCC ID: C3K2085	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
Document S/N: 1M2511200095-01.C3K	DUT Type: Portable Computing Device	Page 25 of 53

REV 22.0
03/30/2022

Table 8-5

5 GHz WLAN Measured P_{Limit} Average Power for DSI = 1 (Motion) – Antenna R LCD

5GHz WIFI (20MHz 802.11a SISO ANT R)			
Band	Freq. [MHz]	Channel	Avg. Conducted Power [dBm]
UNII-1	5180	36	16.74
	5200	40	16.67
	5220	44	16.72
	5240	48	16.66
UNII-2A	5260	52	16.20
	5280	56	16.24
	5300	60	16.15
	5320	64	14.25
5GHz WIFI (20MHz 802.11n SISO ANT R)			
Band	Freq. [MHz]	Channel	Avg. Conducted Power [dBm]
UNII-1	5180	36	16.68
	5200	40	16.68
	5220	44	16.71
	5240	48	16.67
UNII-2A	5260	52	16.19
	5280	56	16.24
	5300	60	16.22
	5320	64	14.15
5GHz WIFI (20MHz 802.11ac SISO ANT R)			
Band	Freq. [MHz]	Channel	Avg. Conducted Power [dBm]
UNII-1	5180	36	16.65
	5200	40	16.55
	5220	44	16.57
	5240	48	16.65
UNII-2A	5260	52	16.01
	5280	56	16.05
	5300	60	16.04
	5320	64	14.03
5GHz WIFI (20MHz 802.11ax SISO ANT R)			
Band	Freq. [MHz]	Channel	Avg. Conducted Power [dBm]
UNII-1	5180	36	16.67
	5200	40	16.69
	5220	44	16.70
	5240	48	16.65
UNII-2A	5260	52	16.16
	5280	56	16.19
	5300	60	16.14
	5320	64	14.11
5GHz WIFI (20MHz 802.11be SISO ANT R)			
Band	Freq. [MHz]	Channel	Avg. Conducted Power [dBm]
UNII-1	5180	36	16.68
	5200	40	16.66
	5220	44	16.71
	5240	48	16.69
UNII-2A	5260	52	16.17
	5280	56	16.24
	5300	60	16.21
	5320	64	14.17

5GHz WIFI (80MHz 802.11ac SISO ANT R)			
Band	Freq. [MHz]	Channel	Avg. Conducted Power [dBm]
UNII-2C	5530	106	12.77
	5610	122	12.78
	5690	138	15.44
5GHz WIFI (80MHz 802.11ax SISO ANT R)			
Band	Freq. [MHz]	Channel	Avg. Conducted Power [dBm]
UNII-2C	5530	106	12.68
	5610	122	12.71
	5690	138	15.07
5GHz WIFI (80MHz 802.11be SISO ANT R)			
Band	Freq. [MHz]	Channel	Avg. Conducted Power [dBm]
UNII-2C	5530	106	12.67
	5610	122	12.69
	5690	138	15.05

5GHz WIFI (40MHz 802.11n SISO ANT R)			
Band	Freq. [MHz]	Channel	Avg. Conducted Power [dBm]
UNII-3	5755	151	14.94
	5795	159	14.91
UNII-4	5835	167	14.93
	5875	175	14.95
5GHz WIFI (40MHz 802.11ac SISO ANT R)			
Band	Freq. [MHz]	Channel	Avg. Conducted Power [dBm]
UNII-3	5755	151	14.55
	5795	159	14.43
UNII-4	5835	167	14.01
	5875	175	14.16
5GHz WIFI (40MHz 802.11ax SISO ANT R)			
Band	Freq. [MHz]	Channel	Avg. Conducted Power [dBm]
UNII-3	5755	151	14.81
	5795	159	14.72
UNII-4	5835	167	14.29
	5875	175	14.41
5GHz WIFI (40MHz 802.11be SISO ANT R)			
Band	Freq. [MHz]	Channel	Avg. Conducted Power [dBm]
UNII-3	5755	151	14.81
	5795	159	14.71
UNII-4	5835	167	14.28
	5875	175	14.41

FCC ID: C3K2085	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
Document S/N: 1M2511200095-01.C3K	DUT Type: Portable Computing Device	Page 26 of 53

REV 22.0
03/30/2022

Table 8-6

5 GHz WLAN Measured P_{Limit} Average Power for DSI = 1 (Motion) – Antenna R OLED

5GHz WIFI (20MHz 802.11a SISO ANT R)			
Band	Freq. [MHz]	Channel	Avg. Conducted Power [dBm]
UNII-1	5180	36	16.37
	5200	40	16.34
	5220	44	16.39
	5240	48	16.42
UNII-2A	5260	52	15.91
	5280	56	15.96
	5300	60	15.90
	5320	64	14.45
5GHz WIFI (20MHz 802.11n SISO ANT R)			
Band	Freq. [MHz]	Channel	Avg. Conducted Power [dBm]
UNII-1	5180	36	16.32
	5200	40	16.36
	5220	44	16.32
	5240	48	16.44
UNII-2A	5260	52	15.89
	5280	56	16.00
	5300	60	15.93
	5320	64	13.89
5GHz WIFI (20MHz 802.11ac SISO ANT R)			
Band	Freq. [MHz]	Channel	Avg. Conducted Power [dBm]
UNII-1	5180	36	15.33
	5200	40	15.37
	5220	44	15.38
	5240	48	15.46
UNII-2A	5260	52	15.25
	5280	56	14.76
	5300	60	14.78
	5320	64	13.28
5GHz WIFI (20MHz 802.11ax SISO ANT R)			
Band	Freq. [MHz]	Channel	Avg. Conducted Power [dBm]
UNII-1	5180	36	15.69
	5200	40	15.63
	5220	44	15.70
	5240	48	15.67
UNII-2A	5260	52	14.99
	5280	56	15.05
	5300	60	15.01
	5320	64	13.55
5GHz WIFI (20MHz 802.11be SISO ANT R)			
Band	Freq. [MHz]	Channel	Avg. Conducted Power [dBm]
UNII-1	5180	36	15.64
	5200	40	15.56
	5220	44	15.68
	5240	48	15.68
UNII-2A	5260	52	14.99
	5280	56	15.06
	5300	60	15.00
	5320	64	13.55

5GHz WIFI (80MHz 802.11ac SISO ANT R)			
Band	Freq. [MHz]	Channel	Avg. Conducted Power [dBm]
UNII-2C	5530	106	12.05
	5610	122	12.21
	5690	138	14.68
5GHz WIFI (80MHz 802.11ax SISO ANT R)			
Band	Freq. [MHz]	Channel	Avg. Conducted Power [dBm]
UNII-2C	5530	106	12.76
	5610	122	12.78
	5690	138	15.15
5GHz WIFI (80MHz 802.11be SISO ANT R)			
Band	Freq. [MHz]	Channel	Avg. Conducted Power [dBm]
UNII-2C	5530	106	12.77
	5610	122	12.75
	5690	138	15.14

5GHz WIFI (40MHz 802.11n SISO ANT R)			
Band	Freq. [MHz]	Channel	Avg. Conducted Power [dBm]
UNII-3	5755	151	14.51
	5795	159	14.43
UNII-4	5835	167	14.46
	5875	175	14.56
5GHz WIFI (40MHz 802.11ac SISO ANT R)			
Band	Freq. [MHz]	Channel	Avg. Conducted Power [dBm]
UNII-3	5755	151	14.93
	5795	159	14.83
UNII-4	5835	167	14.62
	5875	175	14.63
5GHz WIFI (40MHz 802.11ax SISO ANT R)			
Band	Freq. [MHz]	Channel	Avg. Conducted Power [dBm]
UNII-3	5755	151	14.92
	5795	159	14.97
UNII-4	5835	167	14.59
	5875	175	14.60
5GHz WIFI (40MHz 802.11be SISO ANT R)			
Band	Freq. [MHz]	Channel	Avg. Conducted Power [dBm]
UNII-3	5755	151	14.93
	5795	159	14.95
UNII-4	5835	167	14.56
	5875	175	14.59

FCC ID: C3K2085	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
Document S/N: 1M2511200095-01.C3K	DUT Type: Portable Computing Device	Page 27 of 53

REV 22.0
03/30/2022

Table 8-7

5 GHz WLAN Measured P_{Limit} Average Power for DSI = 1 (Motion) – Antenna L LCD

5GHz WIFI (20MHz 802.11a SISO ANT L)			
Band	Freq. [MHz]	Channel	Avg. Conducted Power [dBm]
UNII-2A	5260	52	16.31
	5280	56	16.37
	5300	60	16.30
	5320	64	14.11
5GHz WIFI (20MHz 802.11n SISO ANT L)			
Band	Freq. [MHz]	Channel	Avg. Conducted Power [dBm]
UNII-1	5180	36	16.75
	5200	40	16.74
	5220	44	16.78
	5240	48	16.87
UNII-2A	5260	52	16.12
	5280	56	16.13
	5300	60	16.16
	5320	64	13.97
5GHz WIFI (20MHz 802.11ac SISO ANT L)			
Band	Freq. [MHz]	Channel	Avg. Conducted Power [dBm]
UNII-1	5180	36	16.19
	5200	40	16.30
	5220	44	16.25
	5240	48	16.31
UNII-2A	5260	52	16.37
	5280	56	16.45
	5300	60	16.42
	5320	64	13.75
5GHz WIFI (20MHz 802.11ax SISO ANT L)			
Band	Freq. [MHz]	Channel	Avg. Conducted Power [dBm]
UNII-1	5180	36	16.22
	5200	40	16.27
	5220	44	16.31
	5240	48	16.32
UNII-2A	5260	52	16.34
	5280	56	16.37
	5300	60	16.38
	5320	64	13.75
5GHz WIFI (20MHz 802.11be SISO ANT L)			
Band	Freq. [MHz]	Channel	Avg. Conducted Power [dBm]
UNII-1	5180	36	16.22
	5200	40	16.26
	5220	44	16.32
	5240	48	16.32
UNII-2A	5260	52	16.37
	5280	56	16.36
	5300	60	16.42
	5320	64	13.75

5GHz WIFI (80MHz 802.11ac SISO ANT L)			
Band	Freq. [MHz]	Channel	Avg. Conducted Power [dBm]
UNII-2C	5530	106	12.90
	5610	122	12.84
	5690	138	14.89
5GHz WIFI (80MHz 802.11ax SISO ANT L)			
Band	Freq. [MHz]	Channel	Avg. Conducted Power [dBm]
UNII-2C	5530	106	12.96
	5610	122	12.89
	5690	138	14.72
5GHz WIFI (80MHz 802.11be SISO ANT L)			
Band	Freq. [MHz]	Channel	Avg. Conducted Power [dBm]
UNII-2C	5530	106	12.94
	5610	122	12.87
	5690	138	14.73

5GHz WIFI (40MHz 802.11n SISO ANT L)			
Band	Freq. [MHz]	Channel	Avg. Conducted Power [dBm]
UNII-3	5755	151	14.64
	5795	159	14.65
UNII-4	5835	167	14.67
	5875	175	14.60
5GHz WIFI (40MHz 802.11ac SISO ANT L)			
Band	Freq. [MHz]	Channel	Avg. Conducted Power [dBm]
UNII-3	5755	151	14.65
	5795	159	14.73
UNII-4	5835	167	14.68
	5875	175	14.66
5GHz WIFI (40MHz 802.11ax SISO ANT L)			
Band	Freq. [MHz]	Channel	Avg. Conducted Power [dBm]
UNII-3	5755	151	14.61
	5795	159	14.66
UNII-4	5835	167	14.69
	5875	175	14.67
5GHz WIFI (40MHz 802.11be SISO ANT L)			
Band	Freq. [MHz]	Channel	Avg. Conducted Power [dBm]
UNII-3	5755	151	14.58
	5795	159	14.67
UNII-4	5835	167	14.68
	5875	175	14.66

FCC ID: C3K2085	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
Document S/N: 1M2511200095-01.C3K	DUT Type: Portable Computing Device	Page 28 of 53

REV 22.0
03/30/2022

Table 8-8

5 GHz WLAN Measured P_{Limit} Average Power for DSI = 1 (Motion) – Antenna L OLED

5GHz WIFI (20MHz 802.11a SISO ANT L)			
Band	Freq. [MHz]	Channel	Avg. Conducted Power [dBm]
UNII-2A	5260	52	15.84
	5280	56	15.82
	5300	60	15.77
	5320	64	13.73
5GHz WIFI (20MHz 802.11n SISO ANT L)			
Band	Freq. [MHz]	Channel	Avg. Conducted Power [dBm]
UNII-1	5180	36	16.46
	5200	40	16.52
	5220	44	16.59
	5240	48	16.64
UNII-2A	5260	52	15.86
	5280	56	15.92
	5300	60	15.88
	5320	64	13.77
5GHz WIFI (20MHz 802.11ac SISO ANT L)			
Band	Freq. [MHz]	Channel	Avg. Conducted Power [dBm]
UNII-1	5180	36	16.06
	5200	40	16.07
	5220	44	16.16
	5240	48	16.22
UNII-2A	5260	52	16.12
	5280	56	16.21
	5300	60	16.19
	5320	64	13.57
5GHz WIFI (20MHz 802.11ax SISO ANT L)			
Band	Freq. [MHz]	Channel	Avg. Conducted Power [dBm]
UNII-1	5180	36	16.08
	5200	40	16.05
	5220	44	16.19
	5240	48	16.23
UNII-2A	5260	52	16.16
	5280	56	16.22
	5300	60	16.19
	5320	64	13.55
5GHz WIFI (20MHz 802.11be SISO ANT L)			
Band	Freq. [MHz]	Channel	Avg. Conducted Power [dBm]
UNII-1	5180	36	16.08
	5200	40	16.09
	5220	44	16.20
	5240	48	16.25
UNII-2A	5260	52	16.19
	5280	56	16.28
	5300	60	16.25
	5320	64	13.58

5GHz WIFI (80MHz 802.11ac SISO ANT L)			
Band	Freq. [MHz]	Channel	Avg. Conducted Power [dBm]
UNII-2C	5530	106	12.45
	5610	122	12.34
	5690	138	14.38
	5GHz WIFI (80MHz 802.11ax SISO ANT L)		
Band	Freq. [MHz]	Channel	Avg. Conducted Power [dBm]
UNII-2C	5530	106	13.13
	5610	122	13.08
	5690	138	14.80
	5GHz WIFI (80MHz 802.11be SISO ANT L)		
Band	Freq. [MHz]	Channel	Avg. Conducted Power [dBm]
UNII-2C	5530	106	13.15
	5610	122	13.08
	5690	138	14.83

5GHz WIFI (40MHz 802.11n SISO ANT L)			
Band	Freq. [MHz]	Channel	Avg. Conducted Power [dBm]
UNII-3	5755	151	14.31
	5795	159	14.26
UNII-4	5835	167	14.26
	5875	175	14.19
5GHz WIFI (40MHz 802.11ac SISO ANT L)			
Band	Freq. [MHz]	Channel	Avg. Conducted Power [dBm]
UNII-3	5755	151	14.79
	5795	159	14.78
UNII-4	5835	167	14.74
	5875	175	14.71
5GHz WIFI (40MHz 802.11ax SISO ANT L)			
Band	Freq. [MHz]	Channel	Avg. Conducted Power [dBm]
UNII-3	5755	151	14.71
	5795	159	14.62
UNII-4	5835	167	14.65
	5875	175	14.64
5GHz WIFI (40MHz 802.11be SISO ANT L)			
Band	Freq. [MHz]	Channel	Avg. Conducted Power [dBm]
UNII-3	5755	151	14.70
	5795	159	14.61
UNII-4	5835	167	14.64
	5875	175	14.63

FCC ID: C3K2085	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
Document S/N: 1M2511200095-01.C3K	DUT Type: Portable Computing Device	Page 29 of 53

REV 22.0
03/30/2022

Table 8-9

6 GHz WLAN Measured P_{Limit} Average Power for DSI = 1 (Motion) – Antenna R LCD

6GHz WIFI (160MHz 802.11ax SISO ANT R)				6GHz WIFI (320MHz 802.11be SISO ANT R)			
Band	Freq. [MHz]	Channel	Avg. Conducted Power [dBm]	Band	Freq. [MHz]	Channel	Avg. Conducted Power [dBm]
UNII-5	6025	15	13.29	UNII-6	6425	95	6.71
	6345	79	13.39	UNII-8	6905	191	6.75
UNII-7	6665	143	13.63				
6GHz WIFI (160MHz 802.11be SISO ANT R)							
Band	Freq. [MHz]	Channel	Avg. Conducted Power [dBm]				
UNII-5	6025	15	13.38				
	6345	79	13.57				
UNII-7	6665	143	13.25				

Table 8-10

6 GHz WLAN Measured P_{Limit} Average Power for DSI = 1 (Motion) – Antenna R OLED

6GHz WIFI (160MHz 802.11ax SISO ANT R)				6GHz WIFI (320MHz 802.11be SISO ANT R)			
Band	Freq. [MHz]	Channel	Avg. Conducted Power [dBm]	Band	Freq. [MHz]	Channel	Avg. Conducted Power [dBm]
UNII-5	6025	15	13.22	UNII-6	6425	95	8.29
	6345	79	13.34	UNII-8	6905	191	7.85
UNII-7	6665	143	13.52				
6GHz WIFI (160MHz 802.11be SISO ANT R)							
Band	Freq. [MHz]	Channel	Avg. Conducted Power [dBm]				
UNII-5	6025	15	13.67				
	6345	79	13.58				
UNII-7	6665	143	13.23				

Table 8-11

6 GHz WLAN Measured P_{Limit} Average Power for DSI = 1 (Motion) – Antenna L LCD

6GHz WIFI (160MHz 802.11ax SISO ANT L)				6GHz WIFI (320MHz 802.11be SISO ANT L)			
Band	Freq. [MHz]	Channel	Avg. Conducted Power [dBm]	Band	Freq. [MHz]	Channel	Avg. Conducted Power [dBm]
UNII-5	6025	15	13.61	UNII-6	6425	95	6.89
	6345	79	14.02	UNII-8	6905	191	6.74
UNII-7	6665	143	14.40				
6GHz WIFI (160MHz 802.11be SISO ANT L)							
Band	Freq. [MHz]	Channel	Avg. Conducted Power [dBm]				
UNII-5	6025	15	12.78				
	6345	79	13.24				
UNII-7	6665	143	13.05				

FCC ID: C3K2085	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
Document S/N: 1M2511200095-01.C3K	DUT Type: Portable Computing Device	Page 30 of 53

REV 22.0
03/30/2022

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element. If you have any questions or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact CT.INFO@ELEMENT.COM.

Table 8-12

6 GHz WLAN Measured P_{Limit} Average Power for DSI = 1 (Motion) – Antenna L OLED

6GHz WIFI (160MHz 802.11ax SISO ANT L)				6GHz WIFI (320MHz 802.11be SISO ANT L)			
Band	Freq. [MHz]	Channel	Avg. Conducted Power [dBm]	Band	Freq. [MHz]	Channel	Avg. Conducted Power [dBm]
UNII-5	6025	15	13.81	UNII-6	6425	95	7.90
	6345	79	13.69	UNII-8	6905	191	7.47
UNII-7	6665	143	14.33				
6GHz WIFI (160MHz 802.11be SISO ANT L)							
Band	Freq. [MHz]	Channel	Avg. Conducted Power [dBm]				
UNII-5	6025	15	13.15				
	6345	79	13.45				
UNII-7	6665	143	13.11				

Justification for test configurations for WLAN per KDB Publication 248227 D01v02r02:

- Power measurements were performed for the transmission mode configuration with the highest maximum output power specified for production units.
- For transmission modes with the same maximum output power specification, powers were measured for the largest channel bandwidth, lowest order modulation and lowest data rate.
- For transmission modes with identical maximum specified output power, channel bandwidth, modulation and data rates, power measurements were required for all identical configurations.
- For each transmission mode configuration, powers were measured for the highest and lowest channels; and at the mid-band channel(s) when there were at least 3 channels supported. For configurations with multiple mid-band channels, due to an even number of channels, both channels were measured.




Figure 8-1
Power Measurement Setup

FCC ID: C3K2085	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
Document S/N: 1M2511200095-01.C3K	DUT Type: Portable Computing Device	Page 31 of 53

REV 22.0
03/30/2022

8.2 Bluetooth Conducted Powers

Table 8-13
Bluetooth Reduced Average RF Power in Motion – Antenna R LCD

Frequency [MHz]	Data Rate [Mbps]	Channel No.	Avg Conducted Power	
			[dBm]	[mW]
2402	1.0	0	18.29	67.453
2441	1.0	39	18.51	70.958
2480	1.0	78	18.18	65.766

Table 8-14
Bluetooth Reduced Average RF Power in Motion – Antenna R OLED

Frequency [MHz]	Data Rate [Mbps]	Channel No.	Avg Conducted Power	
			[dBm]	[mW]
2402	1.0	0	18.52	71.121
2441	1.0	39	18.68	73.790
2480	1.0	78	18.45	69.984

Table 8-15
Bluetooth Reduced Average RF Power during conditions with 2.4/5/6 GHz WLAN – Antenna R LCD

Frequency [MHz]	Data Rate [Mbps]	Channel No.	Avg Conducted Power	
			[dBm]	[mW]
2402	1.0	0	13.21	20.941
2441	1.0	39	13.43	22.029
2480	1.0	78	13.14	20.606

Table 8-16
Bluetooth Reduced Average RF Power during conditions with 2.4/5/6 GHz WLAN – Antenna R OLED

Frequency [MHz]	Data Rate [Mbps]	Channel No.	Avg Conducted Power	
			[dBm]	[mW]
2402	1.0	0	13.22	20.989
2441	1.0	39	13.35	21.627
2480	1.0	78	13.20	20.893

FCC ID: C3K2085	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
Document S/N: 1M2511200095-01.C3K	DUT Type: Portable Computing Device	Page 32 of 53

REV 22.0
03/30/2022

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element. If you have any questions or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact CT.INFO@ELEMENT.COM.

Table 8-17
Bluetooth Reduced Average RF Power in Motion – Antenna L LCD

Frequency [MHz]	Data Rate [Mbps]	Channel No.	Avg Conducted Power	
			[dBm]	[mW]
2402	1.0	0	18.42	69.502
2441	1.0	39	18.69	73.961
2480	1.0	78	18.48	70.469

Table 8-18
Bluetooth Reduced Average RF Power in Motion – Antenna L OLED

Frequency [MHz]	Data Rate [Mbps]	Channel No.	Avg Conducted Power	
			[dBm]	[mW]
2402	1.0	0	18.32	67.920
2441	1.0	39	18.63	72.946
2480	1.0	78	18.47	70.307

Table 8-19
Bluetooth Reduced Average RF Power with 2.4/5/6 GHz WLAN – Antenna L LCD

Frequency [MHz]	Data Rate [Mbps]	Channel No.	Avg Conducted Power	
			[dBm]	[mW]
2402	1.0	0	13.07	20.277
2441	1.0	39	13.42	21.979
2480	1.0	78	13.33	21.528


Table 8-20
Bluetooth Reduced Average RF Power with 2.4/5/6 GHz WLAN – Antenna L OLED

Frequency [MHz]	Data Rate [Mbps]	Channel No.	Avg Conducted Power	
			[dBm]	[mW]
2402	1.0	0	13.15	20.654
2441	1.0	39	13.31	21.429
2480	1.0	78	13.14	20.606

FCC ID: C3K2085	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
Document S/N: 1M2511200095-01.C3K	DUT Type: Portable Computing Device	Page 33 of 53

REV 22.0
03/30/2022

Figure 8-3
Bluetooth Antenna L Transmission Plot



Equation 8-2
Bluetooth Antenna L Duty Cycle Calculation

$$\text{Duty Cycle} = \frac{\text{Pulse Width}}{\text{Period}} * 100\% = \frac{2.888\text{ms}}{3.749\text{ms}} * 100\% = 77.03\%$$




Figure 8-4
Power Measurement Setup

FCC ID: C3K2085	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
Document S/N: 1M2511200095-01.C3K	DUT Type: Portable Computing Device	Page 35 of 53

REV 22.0
03/30/2022

9 SYSTEM VERIFICATION

9.1 Tissue Verification

Table 9-1
Measured Head Tissue Properties

Calibrated for Tests Performed on:	Tissue Type	Tissue Temp During Calibration (°C)	Measured Frequency (MHz)	Measured Conductivity, σ (S/m)	Measured Dielectric Constant, ϵ'	TARGET Conductivity, σ (S/m)	TARGET Dielectric Constant, ϵ'	% dev σ	% dev ϵ'
12/08/2025	2450 Head	24.6	2300	1.647	39.835	1.670	39.500	-1.38%	0.85%
			2310	1.654	39.835	1.679	39.480	-1.49%	0.90%
			2320	1.659	39.831	1.687	39.460	-1.66%	0.94%
			2400	1.744	39.722	1.756	39.289	-2.39%	1.10%
			2450	1.747	39.612	1.800	39.200	-2.94%	1.05%
			2480	1.771	39.595	1.833	39.162	-3.38%	1.11%
			2500	1.781	39.555	1.855	39.136	-3.99%	1.10%
			2510	1.787	39.542	1.866	39.123	-4.23%	1.07%
			2535	1.808	39.491	1.893	39.092	-4.60%	1.02%
			2550	1.819	39.471	1.909	39.073	-4.71%	1.02%
			2560	1.827	39.455	1.920	39.060	-4.84%	1.01%
			2300	1.651	39.803	1.670	39.500	-1.14%	0.26%
12/18/2025	2450 Head	24.5	2310	1.658	39.590	1.679	39.480	-1.25%	0.28%
			2320	1.664	39.581	1.687	39.460	-1.36%	0.31%
			2400	1.717	39.487	1.756	39.289	-2.22%	0.50%
			2450	1.753	39.414	1.800	39.200	-2.61%	0.55%
			2480	1.774	39.377	1.833	39.162	-3.22%	0.55%
			2500	1.786	39.349	1.855	39.136	-3.72%	0.54%
			2510	1.793	39.325	1.866	39.123	-3.91%	0.52%
			2535	1.810	39.272	1.893	39.092	-4.36%	0.46%
			2550	1.820	39.268	1.909	39.073	-4.66%	0.47%
			2560	1.826	39.250	1.920	39.060	-4.90%	0.49%
			5150	4.421	35.558	4.608	36.050	-4.06%	-1.37%
			5160	4.433	35.547	4.618	36.040	-4.01%	-1.37%
01/19/2026	5200-5800 Head	19.0	5170	4.441	35.560	4.629	36.030	-4.06%	-1.36%
			5180	4.451	35.519	4.635	36.009	-3.97%	-1.36%
			5190	4.464	35.485	4.645	35.998	-3.90%	-1.43%
			5200	4.477	35.467	4.655	35.986	-3.82%	-1.44%
			5210	4.489	35.461	4.666	35.975	-3.79%	-1.43%
			5220	4.499	35.443	4.676	35.963	-3.79%	-1.49%
			5240	4.525	35.394	4.696	35.940	-3.64%	-1.52%
			5250	4.539	35.373	4.706	35.929	-3.59%	-1.55%
			5260	4.549	35.363	4.717	35.917	-3.56%	-1.57%
			5270	4.559	35.337	4.727	35.906	-3.55%	-1.58%
			5280	4.566	35.326	4.737	35.894	-3.61%	-1.58%
			5290	4.575	35.311	4.748	35.883	-3.64%	-1.59%
01/12/2026	6000 Head	19.0	5300	4.587	35.293	4.758	35.871	-3.59%	-1.64%
			5310	4.597	35.270	4.768	35.860	-3.58%	-1.63%
			5320	4.609	35.264	4.778	35.849	-3.54%	-1.63%
			5500	4.811	34.931	4.963	35.643	-3.06%	-2.00%
			5510	4.818	34.890	4.973	35.632	-3.12%	-2.08%
			5520	4.835	34.881	4.983	35.620	-3.97%	-2.13%
			5530	4.850	34.844	4.994	35.609	-2.88%	-2.16%
			5540	4.864	34.838	5.004	35.597	-2.80%	-2.14%
			5550	4.875	34.822	5.014	35.586	-2.77%	-2.16%
			5560	4.882	34.802	5.024	35.574	-2.83%	-2.17%
			5580	4.905	34.774	5.045	35.551	-2.78%	-2.19%
			5600	4.927	34.740	5.065	35.529	-2.72%	-2.22%
01/12/2026	6000 Head	19.0	5610	4.933	34.713	5.076	35.518	-2.82%	-2.27%
			5620	4.946	34.685	5.086	35.506	-2.71%	-2.31%
			5640	4.979	34.652	5.106	35.483	-2.49%	-2.94%
			5660	4.997	34.604	5.127	35.460	-2.54%	-2.41%
			5670	5.010	34.591	5.137	35.449	-2.47%	-2.42%
			5680	5.025	34.585	5.147	35.437	-2.41%	-2.40%
			5690	5.035	34.576	5.158	35.426	-2.38%	-2.40%
			5700	5.048	34.560	5.168	35.414	-2.32%	-2.41%
			5710	5.056	34.520	5.178	35.403	-2.36%	-2.49%
			5720	5.069	34.480	5.188	35.391	-2.39%	-2.55%
			5745	5.100	34.459	5.214	35.363	-2.19%	-2.58%
			5750	5.107	34.451	5.219	35.357	-2.15%	-2.58%
			5755	5.114	34.442	5.224	35.351	-2.11%	-2.57%
01/12/2026	6000 Head	19.0	5765	5.124	34.426	5.234	35.340	-2.10%	-2.59%
			5775	5.136	34.413	5.245	35.329	-2.08%	-2.58%
			5785	5.148	34.393	5.255	35.317	-2.04%	-2.62%
			5795	5.158	34.368	5.265	35.305	-2.03%	-2.66%
			5805	5.168	34.343	5.275	35.294	-2.03%	-2.69%
			5820	5.185	34.328	5.296	35.271	-2.02%	-2.67%
			5835	5.200	34.319	5.305	35.230	-1.98%	-2.59%
			5845	5.213	34.296	5.315	35.210	-1.92%	-2.60%
			5850	5.220	34.277	5.320	35.200	-1.88%	-2.62%
			5855	5.226	34.261	5.325	35.197	-1.86%	-2.66%
			5875	5.245	34.232	5.347	35.183	-1.91%	-2.70%
			5885	5.256	34.228	5.357	35.177	-1.89%	-2.70%
01/12/2026	6000 Head	19.0	5905	5.281	34.188	5.379	35.163	-1.82%	-2.77%
			5935	5.231	34.151	5.411	35.143	-3.33%	-1.78%
			5970	5.222	34.525	5.448	35.120	-4.15%	-1.69%
			5985	5.233	34.441	5.464	35.110	-4.23%	-1.91%
			6000	5.221	34.367	5.480	35.100	-4.73%	-2.09%
			6025	5.244	34.283	5.510	35.070	-4.89%	-2.30%
			6065	5.313	34.204	5.557	35.022	-4.38%	-2.34%
			6075	5.320	34.168	5.589	35.010	-4.47%	-2.41%
			6085	5.324	34.142	5.580	34.998	-4.59%	-2.45%
			6185	5.467	33.944	5.698	34.878	-4.05%	-2.69%
			6275	5.586	33.774	5.805	34.770	-3.60%	-2.88%
			6285	5.590	33.795	5.816	34.758	-3.73%	-2.77%
01/12/2026	6000 Head	19.0	6305	5.621	33.789	5.840	34.734	-3.75%	-2.72%
			6345	5.675	33.685	5.887	34.686	-3.60%	-2.89%
			6475	5.834	33.380	6.041	34.530	-3.42%	-3.30%
			6485	5.847	33.359	6.052	34.518	-3.39%	-3.24%
			6500	5.863	33.409	6.070	34.500	-3.41%	-3.16%
			6505	5.864	33.424	6.076	34.494	-3.49%	-3.10%
			6545	5.884	33.328	6.122	34.446	-3.89%	-3.25%
			6665	5.998	33.051	6.265	34.302	-4.29%	-3.65%
			6675	6.015	33.090	6.273	34.280	-4.11%	-3.67%
			6685	6.045	32.979	6.285	34.278	-3.82%	-3.79%
			6715	6.083	32.914	6.319	34.242	-3.73%	-3.70%
			6785	6.142	32.757	6.400	34.158	-4.03%	-3.98%
			6825	6.225	32.727	6.447	34.110	-3.44%	-4.05%
01/12/2026	6000 Head	19.0	6985	6.371	32.547	6.633	33.918	-3.95%	-4.04%
			6995	6.340	32.558	6.644	33.906	-4.50%	-4.07%
			7000	6.341	32.528	6.650	33.900	-4.65%	-4.05%
			7005	6.342	32.506	6.656	33.894	-4.72%	-4.10%
			7025	6.389	32.361	6.680	33.870	-4.36%	-4.46%

The above measured tissue parameters were used in the DASY software. The DASY software was used to perform interpolation to determine the dielectric parameters at the SAR test device frequencies (per KDB Publication 865664 D01v01r04 and IEEE 1528-2013 6.6.1.2. The tissue parameters listed in the SAR test plots may slightly differ from the table above due to significant digit rounding in the software.

FCC ID: C3K2085	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
Document S/N: 1M2511200095-01.C3K	DUT Type: Portable Computing Device	Page 36 of 53

REV 22.0
03/30/2022

9.2 Test System Verification

Prior to SAR assessment, the system is verified to $\pm 10\%$ of the SAR measurement on the reference dipole at the time of calibration by the calibration facility. Full system validation status and result summary can be found in the SAR System Validation Appendix.

Table 9-2
System Verification Results

SAR System	Tissue Frequency (MHz)	Tissue Type	Date	Amb. Temp. (C)	Liquid Temp. (C)	Input Power (W)	Source SN	Probe SN	DAE	Measured SAR 1g (W/kg)	1W Target SAR 1g (W/kg)	1W Normalized SAR 1g (W/kg)	Deviation 1g (%)	Measured SAR 10g (W/kg)	1W Target SAR 10g (W/kg)	1W Normalized SAR 10g (W/kg)	Deviation 10g (%)	Measured 4cm2 APD (W/m2)	1W Target 4cm2 APD (W/m2)	1W Normalized 4cm2 APD (W/m2)	Deviation 4cm2 APD (%)
G	2450	HEAD	12/06/2025	22.0	23.1	0.10	797	7488	1415	4.90	52.60	49.00	-6.84%	2.30	24.80	23.00	-7.26%	N/A	N/A	N/A	N/A
G	2450	HEAD	12/18/2025	21.1	23.0	0.10	797	7488	1415	5.09	52.60	50.90	-3.23%	2.40	24.80	24.00	-3.23%	N/A	N/A	N/A	N/A
S	5250	HEAD	01/19/2026	19.1	19.0	0.05	1057	7661	1558	3.81	79.40	76.20	-4.03%	1.09	22.70	21.80	-3.96%	N/A	N/A	N/A	N/A
S	5600	HEAD	01/19/2026	19.1	19.0	0.05	1057	7661	1558	3.88	82.80	77.60	-6.28%	1.11	23.60	22.20	-5.93%	N/A	N/A	N/A	N/A
S	5750	HEAD	01/19/2026	19.1	19.0	0.05	1057	7661	1558	3.83	79.80	76.60	-4.01%	1.09	22.70	21.80	-3.96%	N/A	N/A	N/A	N/A
S	5850	HEAD	01/19/2026	19.1	19.0	0.05	1057	7661	1558	3.97	81.50	79.40	-2.58%	1.13	23.00	22.60	-1.74%	N/A	N/A	N/A	N/A
R	6500	HEAD	01/12/2026	19.2	19.0	0.025	1018	7570	1638	7.58	298.00	303.20	1.74%	1.39	55.70	55.60	-0.18%	33.60	1350.00	1344.00	-0.44%




Figure 9-1
System Verification Setup Diagram



Figure 9-2
System Verification Setup Photo

FCC ID: C3K2085	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
Document S/N: 1M2511200095-01.C3K	DUT Type: Portable Computing Device	Page 37 of 53

REV 22.0
03/30/2022

9.3 Power Density Test System Verification

The system was verified to be within ± 0.66 dB of the power density targets on the calibration certificate according to the test system specification in the user's manual and calibration facility recommendation. The 0.66 dB deviation threshold represents the expanded uncertainty for system performance checks using SPEAG's mmWave verification sources. The same spatial resolution and measurement region used in the source calibration was applied during the system check.

The measured power density distribution of verification source was also confirmed through visual inspection to have no noticeable differences, both spatially (shape) and numerically (level) from the distribution provided by the manufacturer, per November 2017 TCBC Workshop Notes.




Figure 9-3
System Verification Setup Photo

Table 9-3
10 GHz Verifications

System	Frequency (GHz)	Date	Source S/N	Probe S/N	Prad (mW)	Normal psPD (W/m ² over 4 cm ²)		Deviation (dB)	Total psPD (W/m ² over 4 cm ²)		Deviation (dB)
						Measured	Target		Measured	Target	
Q	10	01/27/2026	1002	9421	93.3	52.60	53.80	-0.10	53.00	54.00	-0.08

Note: A **10 mm distance spacing** was used from the reference horn antenna aperture to the probe element.

FCC ID: C3K2085	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
Document S/N: 1M2511200095-01.C3K	DUT Type: Portable Computing Device	Page 38 of 53

REV 22.0
03/30/2022

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element. If you have any questions or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact CT.INFO@ELEMENT.COM.

10 SAR DATA SUMMARY

10.1 DTS SISO Standalone SAR Data

Table 10-1
DTS SISO Antenna R - Motion LCD

Exposure	Band / Mode	Bandwidth [MHz]	Service / Modulation	Ant.	Screen	Serial Number	Duty Cycle [%]	Power Drift [dB]	Frequency [MHz]	Channel #	Data Rate [Mbps]	Max Allowed Power [dBm]	Conducted Power [dBm]	Test Position	Spacing [mm]	Accessory	Measured 1g SAR [W/kg]	Power Scaling Factor	Duty Cycle Scaling Factor	Reported 1g SAR [W/kg]	Exposure Ratio (1g SAR)	Plot #	Plimit [dBm]	Overall Plimit [dBm]
Body	2.4 GHz WIF/ IEEE 802.11b	22	DSSS	R	LCD	0F3DM3925423TF	98.08	0.00	2457.00	10	1.0	18.25	18.24	Back	0	N/A	0.876	1.002	1.020	0.878	0.049		29.3	
Body	2.4 GHz WIF/ IEEE 802.11b	22	DSSS	R	LCD	0F3DM3925423TF	98.08	-0.01	2457.00	10	1.0	18.25	18.24	Top	0	Keyboard	0.422	1.002	1.020	0.431	0.269		21.9	
Body	2.4 GHz WIF/ IEEE 802.11b	22	DSSS	R	LCD	0F3DM3925423TF	98.08	0.01	2457.00	10	1.0	18.25	18.24	Top	0	N/A	0.483	1.002	1.020	0.494	0.309		21.3	
Body	2.4 GHz WIF/ IEEE 802.11b	22	DSSS	R	LCD	0F3DM3925423TF	98.08	0.01	2457.00	10	1.0	18.25	18.24	Bottom	0	N/A	0.901	1.002	1.020	0.906	0.001		48.1	
Body	2.4 GHz WIF/ IEEE 802.11b	22	DSSS	R	LCD	0F3DM3925423TF	98.08	0.01	2457.00	10	1.0	18.25	18.24	Right	0	N/A	0.000	1.002	1.020	0.000	0.000		58.1	
Body	2.4 GHz WIF/ IEEE 802.11b	22	DSSS	R	LCD	0F3DM3925423TF	98.08	0.04	2457.00	10	1.0	18.25	18.24	Left	0	N/A	0.999	1.002	1.020	0.999	0.000		58.1	
ANS/IEEE C95.1.1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population																	Body 1.6 W/kg (mW/g) averaged over 1 gram							

Table 10-2
DTS SISO Antenna R - Motion OLED

Exposure	Band / Mode	Bandwidth [MHz]	Service / Modulation	Ant.	Screen	Serial Number	Duty Cycle [%]	Power Drift [dB]	Frequency [MHz]	Channel #	Data Rate [Mbps]	Max Allowed Power [dBm]	Conducted Power [dBm]	Test Position	Spacing [mm]	Accessory	Measured 1g SAR [W/kg]	Power Scaling Factor	Duty Cycle Scaling Factor	Reported 1g SAR [W/kg]	Exposure Ratio (1g SAR)	Plot #	Plimit [dBm]	Overall Plimit [dBm]
Body	2.4 GHz WIF/ IEEE 802.11b	22	DSSS	R	OLED	0F343425403TF	98.08	0.03	2457.00	10	1.0	18.25	18.19	Back	0	N/A	0.865	1.014	1.020	0.867	0.042		29.9	
Body	2.4 GHz WIF/ IEEE 802.11b	22	DSSS	R	OLED	0F343425403TF	98.08	0.01	2457.00	10	1.0	18.25	18.19	Top	0	N/A	0.449	1.014	1.020	0.455	0.284		21.6	
Body	2.4 GHz WIF/ IEEE 802.11b	22	DSSS	R	OLED	0F343425403TF	98.08	0.04	2457.00	10	1.0	18.25	18.19	Top	0	Keyboard	0.454	1.014	1.020	0.470	0.294		21.5	
Body	2.4 GHz WIF/ IEEE 802.11b	22	DSSS	R	OLED	0F343425403TF	98.08	0.01	2457.00	10	1.0	18.25	18.19	Bottom	0	N/A	0.901	1.014	1.020	0.902	0.001		45.0	
Body	2.4 GHz WIF/ IEEE 802.11b	22	DSSS	R	OLED	0F343425403TF	98.08	-0.18	2457.00	10	1.0	18.25	18.19	Right	0	N/A	0.001	1.014	1.020	0.001	0.001		43.3	
Body	2.4 GHz WIF/ IEEE 802.11b	22	DSSS	R	OLED	0F343425403TF	98.08	0.01	2457.00	10	1.0	18.25	18.19	Left	0	N/A	0.999	1.014	1.020	0.999	0.000		58.1	
ANS/IEEE C95.1.1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population																	Body 1.6 W/kg (mW/g) averaged over 1 gram							

Table 10-3
DTS SISO Antenna L - Motion LCD

Exposure	Band / Mode	Bandwidth [MHz]	Service / Modulation	Ant.	Screen	Serial Number	Duty Cycle [%]	Power Drift [dB]	Frequency [MHz]	Channel #	Data Rate [Mbps]	Max Allowed Power [dBm]	Conducted Power [dBm]	Test Position	Spacing [mm]	Accessory	Measured 1g SAR [W/kg]	Power Scaling Factor	Duty Cycle Scaling Factor	Reported 1g SAR [W/kg]	Exposure Ratio (1g SAR)	Plot #	Plimit [dBm]	Overall Plimit [dBm]
Body	2.4 GHz WIF/ IEEE 802.11b	22	DSSS	L	LCD	0F3DM3925423TF	98.08	0.09	2422.00	3	1.0	18.25	17.96	Back	0	N/A	0.089	1.069	1.020	0.094	0.009		28.5	
Body	2.4 GHz WIF/ IEEE 802.11b	22	DSSS	L	LCD	0F3DM3925423TF	98.08	-0.01	2422.00	3	1.0	18.25	17.96	Top	0	Keyboard	0.425	1.069	1.020	0.463	0.289		21.5	
Body	2.4 GHz WIF/ IEEE 802.11b	22	DSSS	L	LCD	0F3DM3925423TF	98.08	0.01	2422.00	3	1.0	18.25	17.96	Top	0	N/A	0.464	1.069	1.020	0.508	0.216		21.2	
Body	2.4 GHz WIF/ IEEE 802.11b	22	DSSS	L	LCD	0F3DM3925423TF	98.08	0.06	2422.00	3	1.0	18.25	17.96	Bottom	0	N/A	0.909	1.069	1.020	0.907	0.004		40.0	
Body	2.4 GHz WIF/ IEEE 802.11b	22	DSSS	L	LCD	0F3DM3925423TF	98.08	0.06	2422.00	3	1.0	18.25	17.96	Right	0	N/A	0.000	1.069	1.020	0.000	0.000		57.8	
Body	2.4 GHz WIF/ IEEE 802.11b	22	DSSS	L	LCD	0F3DM3925423TF	98.08	0.01	2422.00	3	1.0	18.25	17.96	Left	0	N/A	0.999	1.069	1.020	0.992	0.001		44.8	
ANS/IEEE C95.1.1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population																	Body 1.6 W/kg (mW/g) averaged over 1 gram							

Table 10-4
DTS SISO Antenna L - Motion OLED| Plot A1

Exposure	Band / Mode	Bandwidth [MHz]	Service / Modulation	Ant.	Screen	Serial Number	Duty Cycle [%]	Power Drift [dB]	Frequency [MHz]	Channel #	Data Rate [Mbps]	Max Allowed Power [dBm]	Conducted Power [dBm]	Test Position	Spacing [mm]	Accessory	Measured 1g SAR [W/kg]	Power Scaling Factor	Duty Cycle Scaling Factor	Reported 1g SAR [W/kg]	Exposure Ratio (1g SAR)	Plot #	Plimit [dBm]	Overall Plimit [dBm]
Body	2.4 GHz WIF/ IEEE 802.11b	22	DSSS	L	OLED	0F343425403TF	98.08	-0.02	2457.00	10	1.0	18.25	18.11	Back	0	N/A	0.997	1.033	1.020	0.102	0.064		28.1	
Body	2.4 GHz WIF/ IEEE 802.11b	22	DSSS	L	OLED	0F343425403TF	98.08	0.02	2457.00	10	1.0	18.25	18.11	Top	0	N/A	0.575	1.033	1.020	0.602	0.376		20.4	
Body	2.4 GHz WIF/ IEEE 802.11b	22	DSSS	L	OLED	0F343425403TF	98.08	0.01	2457.00	10	1.0	18.25	18.11	Top	0	Keyboard	0.610	1.033	1.020	0.648	0.402	Plot	20.1	
Body	2.4 GHz WIF/ IEEE 802.11b	22	DSSS	L	OLED	0F343425403TF	98.08	0.06	2457.00	10	1.0	18.25	18.11	Bottom	0	N/A	0.997	1.033	1.020	0.991	0.001		48.0	
Body	2.4 GHz WIF/ IEEE 802.11b	22	DSSS	L	OLED	0F343425403TF	98.08	0.05	2457.00	10	1.0	18.25	18.11	Right	0	N/A	0.001	1.033	1.020	0.001	0.001		48.0	
Body	2.4 GHz WIF/ IEEE 802.11b	22	DSSS	L	OLED	0F343425403TF	98.08	0.04	2457.00	10	1.0	18.25	18.11	Left	0	N/A	0.997	1.033	1.020	0.997	0.004		39.5	
ANS/IEEE C95.1.1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population																	Body 1.6 W/kg (mW/g) averaged over 1 gram							

FCC ID: C3K2085	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
Document S/N: 1M2511200095-01.C3K	DUT Type: Portable Computing Device	Page 39 of 53

10.2 NII SISO Standalone SAR Data

Table 10-5
NII SISO Antenna R - Motion LCD

Exposure	Band / Mode	Bandwidth [MHz]	Service / Modulation	Ant.	Screen	Serial Number	Duty Cycle [%]	Power Drift [dB]	Frequency [MHz]	Channel #	U-NI band	Data Rate [Mbps]	Max Allowed Power [dBm]	Conducted Power [dBm]	Test Position	Spacing [mm]	Accessory	Measured Ig SAR [W/kg]	Power Scaling Factor	Duty Cycle Scaling Factor	Reported Ig SAR [W/kg]	Exposure Ratio [kg SAR]	Plot #	Plimit [dBm]	Overall Plimit [dBm]
Body	5 GHz WUFI / IEEE 802.11a	20	OFDM	R	LCD	QF10M325423TF	99.10	0.05	5180.00	36	U-NI-1	6.0	16.75	16.74	Back	0	N/A	0.062	1.002	1.009	0.053	0.033		29.5	
Body	5 GHz WUFI / IEEE 802.11a	20	OFDM	R	LCD	QF10M325423TF	99.10	0.08	5180.00	56	U-NI-2A	6.0	16.25	16.24	Back	0	N/A	0.064	1.002	1.009	0.055	0.034		28.8	
Body	5 GHz WUFI / IEEE 802.11a	20	OFDM	R	LCD	QF10M325423TF	99.12	0.04	5690.00	138	U-NI-3	29.3	15.50	15.46	Back	0	N/A	0.043	1.014	1.009	0.044	0.029		29.0	
Body	5 GHz WUFI / IEEE 802.11a	40	OFDM	R	LCD	QF10M325423TF	99.63	0.08	5755.00	151	U-NI-3	13.5	15.00	14.94	Back	0	N/A	0.031	1.014	1.004	0.032	0.020		30.0	
Body	5 GHz WUFI / IEEE 802.11a	40	OFDM	R	LCD	QF10M325423TF	99.63	0.04	5875.00	175	U-NI-4	13.5	15.00	14.95	Back	0	N/A	0.047	1.012	1.004	0.048	0.030		28.2	
Body	5 GHz WUFI / IEEE 802.11a	20	OFDM	R	LCD	QF10M325423TF	99.10	0.04	5180.00	56	U-NI-2A	6.0	16.25	16.24	Top	0	N/A	0.064	1.002	1.009	0.055	0.034		29.0	
Body	5 GHz WUFI / IEEE 802.11a	20	OFDM	R	LCD	QF10M325423TF	99.10	0.08	5180.00	56	U-NI-2A	6.0	16.25	16.24	Top	0	N/A	0.064	1.002	1.009	0.055	0.034		29.0	
Body	5 GHz WUFI / IEEE 802.11a	40	OFDM	R	LCD	QF10M325423TF	99.63	0.08	5755.00	151	U-NI-3	13.5	15.00	14.94	Top	0	N/A	0.031	1.014	1.004	0.032	0.020		30.0	
Body	5 GHz WUFI / IEEE 802.11a	40	OFDM	R	LCD	QF10M325423TF	99.63	0.04	5875.00	175	U-NI-4	13.5	15.00	14.95	Top	0	N/A	0.047	1.012	1.004	0.048	0.030		28.2	
Body	5 GHz WUFI / IEEE 802.11a	20	OFDM	R	LCD	QF10M325423TF	99.10	0.04	5180.00	56	U-NI-2A	6.0	16.25	16.24	Bottom	0	N/A	0.064	1.002	1.009	0.055	0.034		29.0	
Body	5 GHz WUFI / IEEE 802.11a	20	OFDM	R	LCD	QF10M325423TF	99.10	0.08	5180.00	56	U-NI-2A	6.0	16.25	16.24	Bottom	0	N/A	0.064	1.002	1.009	0.055	0.034		29.0	
Body	5 GHz WUFI / IEEE 802.11a	40	OFDM	R	LCD	QF10M325423TF	99.63	0.08	5755.00	151	U-NI-3	13.5	15.00	14.94	Bottom	0	N/A	0.031	1.014	1.004	0.032	0.020		30.0	
Body	5 GHz WUFI / IEEE 802.11a	40	OFDM	R	LCD	QF10M325423TF	99.63	0.04	5875.00	175	U-NI-4	13.5	15.00	14.95	Bottom	0	N/A	0.047	1.012	1.004	0.048	0.030		28.2	
Body	5 GHz WUFI / IEEE 802.11a	20	OFDM	R	LCD	QF10M325423TF	99.10	0.04	5180.00	56	U-NI-2A	6.0	16.25	16.24	Right	0	N/A	0.064	1.002	1.009	0.055	0.034		29.0	
Body	5 GHz WUFI / IEEE 802.11a	20	OFDM	R	LCD	QF10M325423TF	99.10	0.08	5180.00	56	U-NI-2A	6.0	16.25	16.24	Right	0	N/A	0.064	1.002	1.009	0.055	0.034		29.0	
Body	5 GHz WUFI / IEEE 802.11a	40	OFDM	R	LCD	QF10M325423TF	99.63	0.08	5755.00	151	U-NI-3	13.5	15.00	14.94	Right	0	N/A	0.031	1.014	1.004	0.032	0.020		30.0	
Body	5 GHz WUFI / IEEE 802.11a	40	OFDM	R	LCD	QF10M325423TF	99.63	0.04	5875.00	175	U-NI-4	13.5	15.00	14.95	Right	0	N/A	0.047	1.012	1.004	0.048	0.030		28.2	
Body	5 GHz WUFI / IEEE 802.11a	20	OFDM	R	LCD	QF10M325423TF	99.10	0.04	5180.00	56	U-NI-2A	6.0	16.25	16.24	Left	0	N/A	0.064	1.002	1.009	0.055	0.034		29.0	
Body	5 GHz WUFI / IEEE 802.11a	20	OFDM	R	LCD	QF10M325423TF	99.10	0.08	5180.00	56	U-NI-2A	6.0	16.25	16.24	Left	0	N/A	0.064	1.002	1.009	0.055	0.034		29.0	
Body	5 GHz WUFI / IEEE 802.11a	40	OFDM	R	LCD	QF10M325423TF	99.63	0.08	5755.00	151	U-NI-3	13.5	15.00	14.94	Left	0	N/A	0.031	1.014	1.004	0.032	0.020		30.0	
Body	5 GHz WUFI / IEEE 802.11a	40	OFDM	R	LCD	QF10M325423TF	99.63	0.04	5875.00	175	U-NI-4	13.5	15.00	14.95	Left	0	N/A	0.047	1.012	1.004	0.048	0.030		28.2	
Body	5 GHz WUFI / IEEE 802.11a	20	OFDM	R	LCD	QF10M325423TF	99.10	0.04	5180.00	56	U-NI-2A	6.0	16.25	16.24	Right	0	N/A	0.064	1.002	1.009	0.055	0.034		29.0	
Body	5 GHz WUFI / IEEE 802.11a	20	OFDM	R	LCD	QF10M325423TF	99.10	0.08	5180.00	56	U-NI-2A	6.0	16.25	16.24	Right	0	N/A	0.064	1.002	1.009	0.055	0.034		29.0	
Body	5 GHz WUFI / IEEE 802.11a	40	OFDM	R	LCD	QF10M325423TF	99.63	0.08	5755.00	151	U-NI-3	13.5	15.00	14.94	Right	0	N/A	0.031	1.014	1.004	0.032	0.020		30.0	
Body	5 GHz WUFI / IEEE 802.11a	40	OFDM	R	LCD	QF10M325423TF	99.63	0.04	5875.00	175	U-NI-4	13.5	15.00	14.95	Right	0	N/A	0.047	1.012	1.004	0.048	0.030		28.2	
Body	5 GHz WUFI / IEEE 802.11a	20	OFDM	R	LCD	QF10M325423TF	99.10	0.04	5180.00	56	U-NI-2A	6.0	16.25	16.24	Left	0	N/A	0.064	1.002	1.009	0.055	0.034		29.0	
Body	5 GHz WUFI / IEEE 802.11a	20	OFDM	R	LCD	QF10M325423TF	99.10	0.08	5180.00	56	U-NI-2A	6.0	16.25	16.24	Left	0	N/A	0.064	1.002	1.009	0.055	0.034		29.0	
Body	5 GHz WUFI / IEEE 802.11a	40	OFDM	R	LCD	QF10M325423TF	99.63	0.08	5755.00	151	U-NI-3	13.5	15.00	14.94	Left	0	N/A	0.031	1.014	1.004	0.032	0.020		30.0	
Body	5 GHz WUFI / IEEE 802.11a	40	OFDM	R	LCD	QF10M325423TF	99.63	0.04	5875.00	175	U-NI-4	13.5	15.00	14.95	Left	0	N/A	0.047	1.012	1.004	0.048	0.030		28.2	
AND/IEEE C95.1.1992 - SAFETY LIMIT																		Body 1.6 W/kg (mW/g) averaged over 1 gram							
Uncorrelated Exposure/General Population																									

Table 10-6
NII SISO Antenna R - Motion OLED| Plot A2

Exposure	Band / Mode	Bandwidth [MHz]	Service / Modulation	Ant.	Screen	Serial Number	Duty Cycle [%]	Power Drift [dB]	Frequency [MHz]	Channel #	U-NI band	Data Rate [Mbps]	Max Allowed Power [dBm]	Conducted Power [dBm]	Test Position	Spacing [mm]	Accessory	Measured Ig SAR [W/kg]	Power Scaling Factor	Duty Cycle Scaling Factor	Reported Ig SAR [W/kg]	Exposure Ratio [Ig SAR]	Plot #	Plimit [dBm]	Overall Plimit [dBm]
Body	5 GHz WUFI / IEEE 802.11a	20	OFDM	R	OLED	QF10M325423TF	99.10	-0.12	5240.00	48	U-NI-1	6.0	16.75	16.42	Back	0	N/A	0.064	1.079	1.009	0.070	0.044		28.3	
Body	5 GHz WUFI / IEEE 802.11a	20	OFDM	R	OLED	QF10M325423TF	99.10	0.01	5280.00	36	U-NI-2A	6.0	16.25	15.96	Back	0	N/A	0.056	1.069	1.009	0.058	0.024		30.4	
Body	5 GHz WUFI / IEEE 802.11a	40	OFDM	R	OLED	QF10M325423TF	99.12	0.02	5680.00	138	U-NI-2C	29.3	15.50	14.68	Back	0	N/A	0.048	1.208	1.009	0.059	0.037		27.8	
Body	5 GHz WUFI / IEEE 802.11a	40	OFDM	R	OLED	QF10M325423TF	99.63	0.08	5755.00	151	U-NI-3	13.5	15.00	14.53	Back	0	N/A	0.048	1.119	1.004	0.067	0.042		26.7	
Body	5 GHz WUFI / IEEE 802.11a	40	OFDM	R	OLED	QF10M325423TF	99.63	0.08	5755.00	175	U-NI-4	13.5	15.00	14.58	Back	0	N/A	0.048	1.107	1.004	0.063	0.033		27.2	
Body	5 GHz WUFI / IEEE 802.11a	20	OFDM	R	OLED	QF10M325423TF	99.10	0.01	5240.00	48	U-NI-1A	6.0	16.75	16.42	Top	0	N/A	0.069	1.079	1.009	0.080	0.038		18.8	
Body	5 GHz WUFI / IEEE 802.11a	20	OFDM	R	OLED	QF10M325423TF	99.10	-0.05	5280.00	36	U-NI-2A	6.0	16.25	15.96	Top	0	N/A	0.064	1.069	1.009	0.054	0.026		18.8	
Body	5 GHz WUFI / IEEE 802.11a	40	OFDM	R	OLED	QF10M325423TF	99.12	0.08	5680.00	138	U-NI-2C	29.3	15.50	14.68	Top	0	N/A	0.046	1.208	1.009	0.057	0.037		18.4	
Body	5 GHz WUFI / IEEE 802.11a	40	OFDM	R	OLED	QF10M325423TF	99.63	0.08	5755.00	151	U-NI-3	13.5	15.00	14.53	Top	0	N/A	0.056	1.119	1.004	0.079	0.029		18.1	
Body	5 GHz WUFI / IEEE 802.11a	40	OFDM	R	OLED	QF10M325423TF	99.63	0.08	5875.00	175	U-NI-4	13.5	15.00	14.56	Top	0	N/A	0.043	1.107	1.004	0.069	0.036		17.4	
Body	5 GHz WUFI / IEEE 802.11a	20	OFDM	R	OLED	QF10M325423TF	99.10	0.01	5240.00	48	U-NI-1A	6.0	16.75	16.42	Bottom	0	N/A	0.069	1.079	1.009	0.080	0.038		39.1	
Body	5 GHz WUFI / IEEE 802.11a	20	OFDM	R	OLED	QF10M325423TF	99.10	0.08	5280.00	56	U-NI-2A	6.0	16.25	15.96	Bottom	0	N/A	0.064	1.069	1.009	0.054	0.026		37.4	
Body	5 GHz WUFI / IEEE 802.11a	40	OFDM	R	OLED	QF10M325423TF	99.12	0.08	5680.00	138	U-NI-2C	29.3	15.50	14.48	Bottom	0	N/A	0.043	1.208	1.009	0.060	0.030		41.6	
Body	5 GHz WUFI / IEEE 802.11a	40	OFDM	R	OLED	QF10M325423TF	99.63	0.08	5755.00	151	U-NI-3	13.5	15.00	14.53	Bottom	0	N/A	0.056	1.119	1.004	0.079	0.029		41.6	
Body	5 GHz WUFI / IEEE 802.11a	40	OFDM	R	OLED	QF10M325423TF	99.63	0.04	5875.00	175	U-NI-4	13.5	15.00	14.56	Bottom	0	N/A	0.040	1.107	1.004	0.060	0.030		41.6	
Body	5 GHz WUFI / IEEE 802.11a	20	OFDM	R	OLED	QF10M325423TF	99.10	0.02	5240.00	48	U-NI-1A	6.0	16.75	16.42	Right	0	N/A	0.063	1.079	1.009	0.075	0.036		32.7	
Body	5 GHz WUFI / IEEE 802.11a	20	OFDM	R	OLED	QF10M325423TF	99.10	0.08	5280.00	56	U-NI-2A	6.0	16.25	15.96	Right	0	N/A	0.063	1.069	1.009	0.054	0.026		34.1	
Body	5 GHz WUFI / IEEE 802.11a	40	OFDM	R	OLED	QF10M325423TF	99.12	0.08	5680.00	138	U-NI-2C	29.3	15.50	14.48	Right	0	N/A	0.036	1.208	1.009	0.030	0.013		32.7	
Body	5 GHz WUFI / IEEE 802.11a	40	OFDM	R	OLED	QF10M325423TF	99.63	0.08	5755.00	151	U-NI-3	13.5	15.00	14.53	Right	0	N/A	0.059	1.119	1.004	0.071	0.031		31.7	
Body	5 GHz WUFI / IEEE 802.11a	40	OFDM	R	OLED	QF10M325423TF	99.63	0.08	5875.00	175	U-NI-4	13.5	15.00	14.56	Right	0	N/A	0.040	1.107	1.004	0.061	0.031		31.7	
Body	5 GHz WUFI / IEEE 802.11a	20	OFDM	R	OLED	QF10M325423TF	99.10	0.01	5240.00	48	U-NI-1A	6.0	16.75	16.42	Left	0	N/A	0.069	1.079	1.009	0.080	0.038		56.8	
Body	5 GHz WUFI / IEEE 802.11a	20	OFDM	R	OLED	QF10M325423TF	99.10	0.08	5280.00	56	U-NI-2A	6.0	16.25	15.96	Left	0	N/A	0.063	1.069	1.009	0.054	0.026		56.8	
Body	5 GHz WUFI / IEEE 802.11a	40	OFDM	R	OLED	QF10M325423TF	99.12	0.01	5680.00	138	U-NI-2C	29.3	15.50	14.48	Left	0	N/A	0.000	1.208	1.000	0.000	0.000		54.6	
Body	5 GHz WUFI / IEEE 802.11a	40	OFDM	R	OLED	QF10M325423TF	99.63	0.06	5755.00	151	U-NI-3	13.5	15.00	14.53	Left	0	N/A	0.000	1.119	1.004	0.000	0.000		54.6	
Body	5 GHz WUFI / IEEE 802.11a	40	OFDM	R	OLED	QF10M325423TF	99.63	0.06	5875.00	175	U-NI-4	13.5	15.0	14.56	Left	0	N/A	0.000	1.107	1.004	0.000	0.000		54.5	
ANSI/ESD C96.1 1992 - SAFETY LIMIT																			Body						
Spatial Peak																			1.6 W/kg (avg)						
Uncontrolled Exposure/General Population																			averaged over 1 gram						



Table 10-8
NII SISO Antenna L - Motion OLED

Exposure	Band / Mode	Bandwidth [MHz]	Service / Modulation	Ant.	Screen	Serial Number	Duty Cycle [%]	Power Drift [dB]	Frequency [MHz]	Channel #	U-NII band	Data Rate [Mbps]	Max Allowed Power [dBm]	Conducted Power [dBm]	Test Position	Spacing [mm]	Accessory	Measured 1g SAR [W/kg]	Power Scaling Factor	Duty Cycle Scaling Factor	Reported 1g SAR [W/kg]	Exposure Ratio (1g SAR)	Plot #	Plimit [dBm]	Overall Plimit [dBm]
Body	5 GHz WUPF / IEEE 802.11a	20	OFDM	L	OLED	QF396T825413TF	99.05	0.16	5260.00	52	U-NII-2A	6.0	17.25	15.84	Back	0	N/A	0.049	1.384	1.000	0.058	0.043		28.8	
Body	5 GHz WUPF / IEEE 802.11a	80	OFDM	L	OLED	QF396T825413TF	99.19	0.05	5690.00	138	U-NII-2C	29.3	15.00	14.38	Back	0	N/A	0.460	1.153	1.008	0.070	0.044		26.5	
Body	5 GHz WUPF / IEEE 802.11a	40	OFDM	L	OLED	QF396T825413TF	99.05	0.09	5750.00	151	U-NII-3	13.5	15.00	14.31	Back	0	N/A	0.487	1.172	1.004	0.096	0.082		28.4	
Body	5 GHz WUPF / IEEE 802.11a	40	OFDM	L	OLED	QF396T825413TF	99.05	0.06	5835.00	167	U-NII-4	13.5	14.75	14.26	Back	0	N/A	0.488	1.119	1.004	0.043	0.027		28.2	
Body	5 GHz WUPF / IEEE 802.11a	20	OFDM	L	OLED	QF396T825413TF	99.05	-0.07	5260.00	52	U-NII-2A	6.0	17.25	15.84	Top	0	N/A	0.067	1.384	1.000	0.085	0.048		19.1	
Body	5 GHz WUPF / IEEE 802.11a	20	OFDM	L	OLED	QF396T825413TF	99.05	0.04	5260.00	52	U-NII-2A	6.0	17.25	15.84	Top	0	Keyboard	0.461	1.384	1.000	0.444	0.403		19.1	
Body	5 GHz WUPF / IEEE 802.11a	80	OFDM	L	OLED	QF396T825413TF	99.19	0.05	5690.00	138	U-NII-2C	29.3	15.00	14.38	Top	0	N/A	0.426	1.153	1.008	0.472	0.295		18.2	
Body	5 GHz WUPF / IEEE 802.11a	40	OFDM	L	OLED	QF396T825413TF	99.05	-0.17	5750.00	151	U-NII-3	13.5	15.00	14.31	Top	0	N/A	0.456	1.172	1.004	0.477	0.298		18.2	
Body	5 GHz WUPF / IEEE 802.11a	40	OFDM	L	OLED	QF396T825413TF	99.05	0.04	5835.00	167	U-NII-4	13.5	14.75	14.26	Top	0	N/A	0.456	1.119	1.004	0.458	0.286		18.1	
Body	5 GHz WUPF / IEEE 802.11a	20	OFDM	L	OLED	QF396T825413TF	99.05	0.02	5260.00	52	U-NII-2A	6.0	17.25	15.84	Bottom	0	N/A	0.000	1.864	1.000	0.000	0.000		55.7	
Body	5 GHz WUPF / IEEE 802.11a	80	OFDM	L	OLED	QF396T825413TF	99.19	0.06	5690.00	138	U-NII-2C	29.3	15.00	14.38	Bottom	0	N/A	0.000	1.153	1.008	0.000	0.000		54.1	
Body	5 GHz WUPF / IEEE 802.11a	40	OFDM	L	OLED	QF396T825413TF	99.05	0.06	5750.00	151	U-NII-3	13.5	15.00	14.31	Bottom	0	N/A	0.000	1.172	1.004	0.000	0.000		54.2	
Body	5 GHz WUPF / IEEE 802.11a	40	OFDM	L	OLED	QF396T825413TF	99.05	0.00	5835.00	167	U-NII-4	13.5	14.75	14.26	Bottom	0	N/A	0.000	1.119	1.004	0.000	0.000		54.2	
Body	5 GHz WUPF / IEEE 802.11a	20	OFDM	L	OLED	QF396T825413TF	99.05	0.04	5260.00	52	U-NII-2A	6.0	17.25	15.84	Right	0	N/A	0.000	1.864	1.000	0.000	0.000		55.7	
Body	5 GHz WUPF / IEEE 802.11a	80	OFDM	L	OLED	QF396T825413TF	99.19	0.01	5690.00	138	U-NII-2C	29.3	15.00	14.38	Right	0	N/A	0.000	1.172	1.004	0.000	0.000		54.1	
Body	5 GHz WUPF / IEEE 802.11a	40	OFDM	L	OLED	QF396T825413TF	99.05	0.04	5750.00	151	U-NII-3	13.5	15.00	14.31	Right	0	N/A	0.000	1.172	1.004	0.000	0.000		54.2	
Body	5 GHz WUPF / IEEE 802.11a	40	OFDM	L	OLED	QF396T825413TF	99.05	0.01	5835.00	167	U-NII-4	13.5	14.75	14.26	Right	0	N/A	0.000	1.119	1.004	0.000	0.000		54.2	
Body	5 GHz WUPF / IEEE 802.11a	20	OFDM	L	OLED	QF396T825413TF	99.05	0.04	5260.00	52	U-NII-2A	6.0	17.25	15.84	Left	0	N/A	0.004	1.864	1.000	0.009	0.006		27.7	
Body	5 GHz WUPF / IEEE 802.11a	80	OFDM	L	OLED	QF396T825413TF	99.19	0.02	5690.00	138	U-NII-2C	29.3	15.00	14.38	Left	0	N/A	0.003	1.153	1.008	0.008	0.004		29.1	
Body	5 GHz WUPF / IEEE 802.11a	40	OFDM	L	OLED	QF396T825413TF	99.05	0.00	5750.00	151	U-NII-3	13.5	15.00	14.31	Left	0	N/A	0.000	1.172	1.004	0.002	0.008		34.2	
Body	5 GHz WUPF / IEEE 802.11a	40	OFDM	L	OLED	QF396T825413TF	99.05	0.01	5835.00	167	U-NII-4	13.5	14.75	14.26	Left	0	N/A	0.000	1.119	1.004	0.000	0.006		34.2	
ANSI/IEEE C95.1-1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population																									
																			Body 1.6 W/kg (mW/g) averaged over 1 gram						

10.3 6CD SISO Standalone SAR & APD Data

Table 10-9
6CD SISO Antenna R - Motion LCD

Exposure	Band / Mode	Bandwidth [MHz]	Service / Modulation	Ant.	Screen	Serial Number	Duty Cycle [%]	Power Drift [dB]	Frequency [MHz]	Channel #	Data Rate [Mbps]	Max Allowed Power [dBm]	Conducted Power [dBm]	Test Position	Spacing [mm]	Accessory	Measured 1g SAR [W/kg]	Power Scaling Factor	Duty Cycle Scaling Factor	Reported 1g SAR [W/kg]	Exposure Ratio (1g SAR)	Plot #	Plimit [dBm]	Overall Plimit [dBm]
Body	6 GHz WUPF / IEEE 802.11ax	160	OFDM	R	LCD	QF3DM3125433TF	99.44	-0.08	6025.00	15	68.1	13.75	13.20	Back	0	N/A	0.046	1.112	1.006	0.051	0.027		26.6	
Body	6 GHz WUPF / IEEE 802.11ax	160	OFDM	R	LCD	QF3DM3125433TF	99.44	0.09	6065.00	143	68.1	13.75	13.63	Back	0	N/A	0.042	1.028	1.006	0.043	0.027		27.3	
Body	6 GHz WUPF / IEEE 802.11ax	160	OFDM	R	LCD	QF3DM3025423TF	99.44	0.04	6025.00	15	68.1	13.75	13.29	Top	0	N/A	0.389	1.112	1.006	0.435	0.272		17.3	
Body	6 GHz WUPF / IEEE 802.11ax	160	OFDM	R	LCD	QF396TC25413TF	99.48	0.06	6425.00	95	136.1	8.50	8.29	Top	0	N/A	0.162	1.050	1.005	0.246	0.154		14.5	
Body	6 GHz WUPF / IEEE 802.11ax	320	OFDM	R	LCD	QF396TC25413TF	99.48	0.08	6905.00	191	136.1	8.50	8.29	Top	0	N/A	0.129	1.496	1.005	0.154	0.121		15.6	
Body	6 GHz WUPF / IEEE 802.11ax	160	OFDM	R	LCD	QF396TC25413TF	99.44	0.00	6365.00	79	68.1	13.75	13.39	Top	0	N/A	0.442	1.086	1.006	0.483	0.302		16.9	
Body	6 GHz WUPF / IEEE 802.11ax	160	OFDM	R	LCD	QF396TC25413TF	99.44	0.04	6665.00	143	68.1	13.75	13.63	Top	0	N/A	0.151	1.028	1.006	0.158	0.102		16.5	
Body	6 GHz WUPF / IEEE 802.11ax	160	OFDM	R	LCD	QF396TC25413TF	99.44	-0.09	6665.00	143	68.1	13.75	13.63	Top	0	Keyboard	0.466	1.028	1.006	0.482	0.301		16.9	
Body	6 GHz WUPF / IEEE 802.11ax	160	OFDM	R	LCD	QF396TC25413TF	99.44	0.19	6025.00	15	68.1	13.75	13.29	Bottom	0	N/A	0.005	1.112	1.006	0.006	0.004		36.2	
Body	6 GHz WUPF / IEEE 802.11ax	160	OFDM	R	LCD	QF3DM3125433TF	99.44	0.01	6665.00	143	68.1	13.75	13.63	Bottom	0	N/A	0.000	1.028	1.006	0.000	0.000		18.8	
Body	6 GHz WUPF / IEEE 802.11ax	160	OFDM	R	LCD	QF396TC25413TF	99.44	0.06	6025.00	15	68.1	13.75	13.29	Right	0	N/A	0.001	1.112	1.006	0.003	0.004		30.0	
Body	6 GHz WUPF / IEEE 802.11ax	160	OFDM	R	LCD	QF3DM3125433TF	99.44	0.05	6665.00	143	68.1	13.75	13.63	Right	0	N/A	0.003	1.028	1.006	0.004	0.003		29.9	
Body	6 GHz WUPF / IEEE 802.11ax	160	OFDM	R	LCD	QF396TC25413TF	99.44	0.02	6025.00	15	68.1	13.75	13.29	Left	0	N/A	0.000	1.112	1.006	0.000	0.000		53.2	
Body	6 GHz WUPF / IEEE 802.11ax	160	OFDM	R	LCD	QF3DM3125433TF	99.44	0.07	6665.00	143	68.1	13.75	13.63	Left	0	N/A	0.000	1.028	1.006	0.000	0.000		53.6	
ANSI/IEEE C95.1-1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population																								
Body 1.6 W/kg (mW/g) averaged over 1 gram																								

Exposure	Band/ Mode	Bandwidth [MHz]	Service/ Modulation	Ant.	Screen	Serial Number	Duty Cycle [%]	Power Drift [dB]	Frequency [MHz]	Channel #	Data Rate [Mbps]	Max Allowed Power [dBm]	Conducted Power [dBm]	Test Position	Spacing [mm]	Accessory	Measured APD [W/m²/4cm²]	Power Scaling Factor	Duty Cycle Scaling Factor	Reported APD [W/m²/4cm²]	APD Exposure Ratio	Plot #	Plimit [dBm]	Overall Plimit [dBm]
Body	6 GHz WUPF / IEEE 802.11ax	160	OFDM	R	LCD	QF3DM3125433TF	99.44	-0.08	6025.00	15	68.1	13.75	13.20	Back	0	N/A	0.411	1.112	1.006	0.460	0.023		26.1	
Body	6 GHz WUPF / IEEE 802.11ax	160	OFDM	R	LCD	QF3DM3125433TF	99.44	0.09	6065.00	143	68.1	13.75	13.63	Back	0	N/A	0.313	1.028	1.006	0.365	0.018		26.1	
Body	6 GHz WUPF / IEEE 802.11ax	160	OFDM	R	LCD	QF3DM3025423TF	99.44	0.04	6025.00	15	68.1	13.75	13.29	Top	0	N/A	0.880	1.112	1.006	0.922	0.161		19.1	
Body	6 GHz WUPF / IEEE 802.11ax	320	OFDM	R	LCD	QF396TC25413TF	99.48	0.06	6425.00	95	136.1	8.50	8.29	Top	0	N/A	0.129	1.510	1.005	0.160	0.093		16.7	
Body	6 GHz WUPF / IEEE 802.11ax	320	OFDM	R	LCD	QF396TC25413TF	99.48	0.08	6905.00	191	136.1	8.50	8.29	Top	0	N/A	0.100	1.496	1.005	0.103	0.075		17.7	
Body	6 GHz WUPF / IEEE 802.11ax	160	OFDM	R	LCD	QF396TC25413TF	99.44	0.02	6365.00	79	68.1	13.75	13.39	Top	0	N/A	0.430	1.086	1.006	0.747	0.187		19.0	
Body	6 GHz WUPF / IEEE 802.11ax	160	OFDM	R	LCD	QF396TC25413TF	99.44	0.04	6665.00	143	68.1	13.75	13.63	Top	0	N/A	0.000	1.028	1.006	0.000	0.000		18.8	
Body	6 GHz WUPF / IEEE 802.11ax	160	OFDM	R	LCD	QF396TC25413TF	99.44	-0.09	6665.00	143	68.1	13.75	13.63	Top	0	Keyboard	0.460	1.028	1.006	0.816	0.191		18.9	
Body	6 GHz WUPF / IEEE 802.11ax	160	OFDM	R	LCD	QF396TC25413TF	99.44	0.19	6025.00	15	68.1	13.75	13.29	Bottom	0	N/A	0.040	1.112	1.006	0.045	0.002		38.2	
Body	6 GHz WUPF / IEEE 802.11ax	160	OFDM	R	LCD	QF3DM3125433TF	99.44	0.01	6665.00	143	68.1	13.75	13.63	Bottom	0	N/A	0.000	1.028	1.006	0.000	0.000		18.8	
Body	6 GHz WUPF / IEEE 802.11ax	160	OFDM	R	LCD	QF396TC25413TF	99.44	0.06	6025.00	15	68.1	13.75	13.29	Bottom	0	N/A	0.000	1.112	1.006	0.000	0.000		38.2	
Body	6 GHz WUPF / IEEE 802.11ax	160	OFDM	R	LCD	QF3DM3125433TF	99.44	0.08	6665.00	143	68.1	13.75	13.63	Right	0	N/A	0.060	1.028	1.006	0.165	0.008		32.5	
Body	6 GHz WUPF / IEEE 802.11ax	160	OFDM	R	LCD	QF396TC25413TF	99.44	0.06	6025.00	15	68.1	13.75	13.29	Right	0	N/A	0.000	1.112	1.006	0.000	0.000		38.2	
Body	6 GHz WUPF / IEEE 802.11ax	160	OFDM	R	LCD	QF3DM3125433TF	99.44	0.07	6665.00	143	68.1	13.75	13.63	Left	0	N/A	0.000	1.028	1.006	0.000	0.000		46.6	

Table 10-11
6CD SISO Antenna L - Motion LCD

Exposure	Band / Mode	Bandwidth [MHz]	Service / Modulation	Ant.	Screen	Serial Number	Duty Cycle [%]	Power Drift [dB]	Frequency [MHz]	Channel #	Data Rate [Mbps]	Max Allowed Power [dBm]	Conducted Power [dBm]	Test Position	Spacing [mm]	Accessory	Measured 1g SAR [W/kg]	Power Scaling Factor	Duty Cycle Scaling Factor	Reported 1g SAR [W/kg]	Exposure Ratio [1g SAR]	Plot #	Plimit [dBm]	Overall Plimit [dBm]
Body	6 GHz WIFU / IEEE 802.11ax	160	OFDM	L	LCD	0F36TC25413TF	99.46	-0.18	6025.00	15	68.1	14.25	13.61	Back	0	N/A	0.064	1.159	1.005	0.075	0.047		25.5	
Body	6 GHz WIFU / IEEE 802.11ax	160	OFDM	L	LCD	0F36M325423TF	99.46	-0.06	6665.00	143	68.1	14.75	14.40	Back	0	N/A	0.039	1.084	1.005	0.033	0.021		29.6	
Body	6 GHz WIFU / IEEE 802.11ax	160	OFDM	L	LCD	0F36TC25413TF	99.46	-0.14	6025.00	15	68.1	14.25	13.61	Top	0	N/A	0.254	1.159	1.005	0.412	0.258		18.6	
Body	6 GHz WIFU / IEEE 802.11ax	160	OFDM	L	LCD	0F36TC25413TF	99.46	-0.00	6365.00	79	68.1	14.25	14.02	Top	0	N/A	0.405	1.054	1.005	0.429	0.268		17.9	
Body	6 GHz WIFU / IEEE 802.11ax	160	OFDM	L	LCD	0F36TC25413TF	99.46	-0.11	6665.00	143	68.1	14.75	14.40	Top	0	N/A	0.481	1.084	1.005	0.524	0.328		17.5	
Body	6 GHz WIFU / IEEE 802.11ax	160	OFDM	L	LCD	0F36TC25413TF	99.46	-0.11	6665.00	143	68.1	14.75	14.40	Top	0	N/A	0.474	1.084	1.005	0.526	0.313		17.6	
Body	6 GHz WIFU / IEEE 802.11be	320	OFDM	L	LCD	0F36M3125423TF	99.32	-0.02	6425.00	95	136.1	8.50	6.86	Top	0	N/A	0.186	1.449	1.007	0.271	0.169		14.1	
Body	6 GHz WIFU / IEEE 802.11be	320	OFDM	L	LCD	0F36M3125423TF	99.32	-0.02	6905.00	191	136.1	8.50	6.74	Top	0	N/A	0.157	1.500	1.007	0.217	0.148		14.7	
Body	6 GHz WIFU / IEEE 802.11ax	160	OFDM	L	LCD	0F36TC25413TF	99.46	-0.06	6025.00	15	68.1	14.25	13.61	Bottom	0	N/A	0.002	1.159	1.005	0.002	0.001		40.1	
Body	6 GHz WIFU / IEEE 802.11ax	160	OFDM	L	LCD	0F36M3125423TF	99.46	-0.01	6665.00	143	68.1	14.75	14.40	Bottom	0	N/A	0.013	1.084	1.005	0.014	0.009		33.2	
Body	6 GHz WIFU / IEEE 802.11ax	160	OFDM	L	LCD	0F36TC25413TF	99.46	-0.07	6025.00	15	68.1	14.25	13.61	Right	0	N/A	0.003	1.159	1.005	0.003	0.002		38.8	
Body	6 GHz WIFU / IEEE 802.11ax	160	OFDM	L	LCD	0F36M3125423TF	99.46	-0.05	6665.00	143	68.1	14.75	14.40	Right	0	N/A	0.005	1.084	1.005	0.005	0.003		37.1	
Body	6 GHz WIFU / IEEE 802.11ax	160	OFDM	L	LCD	0F36TC25413TF	99.46	-0.08	6025.00	15	68.1	14.25	13.61	Left	0	N/A	0.019	1.159	1.005	0.022	0.014		30.7	
Body	6 GHz WIFU / IEEE 802.11ax	160	OFDM	L	LCD	0F36TC25413TF	99.46	-0.06	6665.00	143	68.1	14.75	14.40	Left	0	N/A	0.003	1.084	1.005	0.003	0.002		39.6	
ANOMIE CMC 192 - SAFETY LIMIT																								
Spatial Peak																								
Uncontrolled Exposure/General Population																								
																	1.6 W/kg (mW/g) averaged over 1 gram							
Exposure	Band/ Mode	Bandwidth [MHz]	Service/ Modulation	Ant.	Screen	Serial Number	Duty Cycle [%]	Power Drift [dB]	Frequency [MHz]	Channel #	Data Rate [Mbps]	Max Allowed Power [dBm]	Conducted Power [dBm]	Test Position	Spacing [mm]	Accessory	Measured APO Exposure Ratio	Power Scaling Factor	Duty Cycle Scaling Factor	Reported APO Exposure Ratio	APO Exposure Ratio	Plot #	Plimit [dBm]	Overall Plimit [dBm]
Body	6 GHz WIFU / IEEE 802.11ax	160	OFDM	L	LCD	0F36TC25413TF	99.46	-0.18	6025.00	15	68.1	14.25	13.61	Back	0	N/A	0.067	1.159	1.005	0.660	0.033		27.0	
Body	6 GHz WIFU / IEEE 802.11ax	160	OFDM	L	LCD	0F36M325423TF	99.46	-0.06	6665.00	143	68.1	14.75	14.40	Back	0	N/A	0.266	1.084	1.005	0.269	0.014		31.1	
Body	6 GHz WIFU / IEEE 802.11ax	160	OFDM	L	LCD	0F36TC25413TF	99.46	-0.14	6025.00	15	68.1	14.25	13.61	Top	0	N/A	0.720	1.159	1.005	0.168	0.158		20.2	
Body	6 GHz WIFU / IEEE 802.11ax	160	OFDM	L	LCD	0F36TC25413TF	99.46	-0.00	6365.00	79	68.1	14.25	14.03	Top	0	N/A	0.220	1.054	1.005	0.411	0.171		19.9	
Body	6 GHz WIFU / IEEE 802.11ax	160	OFDM	L	LCD	0F36TC25413TF	99.46	-0.11	6665.00	143	68.1	14.75	14.40	Top	0	N/A	0.480	1.084	1.005	0.271	0.214		18.4	
Body	6 GHz WIFU / IEEE 802.11be	320	OFDM	L	LCD	0F36TC25413TF	99.46	-0.11	6665.00	143	68.1	14.75	14.40	Top	0	Keyboard	0.820	1.084	1.005	0.162	0.208		19.5	
Body	6 GHz WIFU / IEEE 802.11be	320	OFDM	L	LCD	0F36M3125423TF	99.32	-0.02	6425.00	95	136.1	8.50	6.89	Top	0	N/A	0.340	1.449	1.007	1.955	0.098		16.5	
Body	6 GHz WIFU / IEEE 802.11ax	160	OFDM	L	LCD	0F36TC25413TF	99.46	-0.02	6025.00	15	68.1	14.25	13.61	Bottom	0	N/A	0.002	1.159	1.005	0.002	0.001		40.1	
Body	6 GHz WIFU / IEEE 802.11ax	160	OFDM	L	LCD	0F36M3125423TF	99.46	-0.06	6025.00	15	68.1	14.25	13.61	Bottom	0	N/A	0.010	1.159	1.005	0.012	0.001		44.5	
Body	6 GHz WIFU / IEEE 802.11ax	160	OFDM	L	LCD	0F36TC25413TF	99.46	-0.01	6665.00	143	68.1	14.75	14.40	Bottom	0	N/A	0.113	1.084	1.005	0.123	0.066		34.8	
Body	6 GHz WIFU / IEEE 802.11ax	160	OFDM	L	LCD	0F36TC25413TF	99.46	-0.07	6025.00	15	68.1	14.25	13.61	Right	0	N/A	0.003	1.159	1.005	0.003	0.002		38.8	
Body	6 GHz WIFU / IEEE 802.11ax	160	OFDM	L	LCD	0F36M3125423TF	99.46	-0.05	6665.00	143	68.1	14.75	14.40	Right	0	N/A	0.007	1.084	1.005	0.040	0.002		39.7	
Body	6 GHz WIFU / IEEE 802.11ax	160	OFDM	L	LCD	0F36TC25413TF	99.46	-0.08	6025.00	15	68.1	14.25	13.61	Left	0	N/A	0.046	1.159	1.005	0.170	0.009		32.9	
Body	6 GHz WIFU / IEEE 802.11ax	160	OFDM	L	LCD	0F36M3125423TF	99.46	-0.06	6665.00	143	68.1	14.75	14.40	Left	0	N/A	0.025	1.084	1.005	0.027	0.001		41.4	

Table 10-12 6CD SISO Antenna L - Motion OLED																								
Exposure	Band / Mode	Bandwidth [MHz]	Service / Modulation	Ant.	Screen	Serial Number	Duty Cycle [%]	Power Drift [dB]	Frequency [MHz]	Channel #	Data Rate [Mbps]	Max Allowed Power [dBm]	Conducted Power [dBm]	Test Position	Spacing [mm]	Accessory	Measured Iq SAR [W/kg]	Power Scaling Factor	Duty Cycle Scaling Factor	Reported Iq SAR [W/kg]	Exposure Ratio [W/kg]	Plot #	Plimit [dBm]	Overall Plimit [dBm]
Body	6 GHz WIFU / IEEE 802.11ax	160	OFDM	L	OLED	0F36TC25413TF	99.46	-0.06	6025.00	15	68.1	14.25	13.61	Back	0	N/A	0.058	1.107	1.005	0.055	0.041		36.1	
Body	6 GHz WIFU / IEEE 802.11ax	160	OFDM	L	OLED	0F36TC25413TF	99.46	-0.14	6665.00	143	68.1	14.75	14.33	Back	0	N/A	0.055	1.102	1.005	0.061	0.038		26.9	
Body	6 GHz WIFU / IEEE 802.11ax	160	OFDM	L	OLED	0F36TC25413TF	99.46	-0.14	6025.00	15	68.1	14.25	13.61	Top	0	N/A	0.178	1.107	1.005	0.421	0.263		18.0	
Body	6 GHz WIFU / IEEE 802.11ax	160	OFDM	L	OLED	0F36TC25413TF	99.46	-0.00	6365.00	79	68.1	14.25	13.89	Top	0	N/A	0.339	1.118	1.005	0.494	0.253		18.1	
Body	6 GHz WIFU / IEEE 802.11ax	160	OFDM	L	OLED	0F36TC25413TF	99.46	-0.13	6665.00	143	68.1	14.75	14.33	Top	0	N/A	0.473	1.102	1.005	0.532	0.335		17.5	
Body	6 GHz WIFU / IEEE 802.11ax	160	OFDM	L	OLED	0F36TC25413TF	99.46	-0.06	6665.00	143	68.1	14.75	14.33	Top	0	Keyboard	0.466	1.102	1.005	0.516	0.323		17.6	
Body	6 GHz WIFU / IEEE 802.11be	320	OFDM	L	OLED	0F36TC25413TF	99.32	-0.01	6425.00	95	136.1	8.50	7.80	Top	0	N/A	0.141	1.148	1.007	0.163	0.132		16.3	
Body	6 GHz WIFU / IEEE 802.11be	320	OFDM	L	OLED	0F36TC25413TF	99.32	-0.01	6905.00	191	136.1	8.50	7.47	Top	0	N/A	0.114	1.268	1.007	0.131	0.094		16.7	
Body	6 GHz WIFU / IEEE 802.11ax	160	OFDM	L	OLED	0F36TC25413TF	99.46	-0.08	6025.00	15	68.1	14.25	13.61	Bottom	0	N/A	0.002	1.107	1.005	0.002	0.001		44.7	
Body	6 GHz WIFU / IEEE 802.11ax	160	OFDM	L	OLED	0F36TC25413TF	99.46	-0.06	6665.00	143	68.1	14.75	14.33	Bottom	0	N/A	0.012	1.102	1.005	0.013	0.008		33.5	
Body	6 GHz WIFU / IEEE 802.11ax	160	OFDM	L	OLED	0F36TC25413TF	99.46	-0.07	6025.00	15	68.1	14.25	13.61	Right	0	N/A	0.002	1.107	1.005	0.000	0.000		51.7	
Body	6 GHz WIFU / IEEE 802.11ax	160	OFDM	L	OLED	0F36TC25413TF	99.46	-0.04	6665.00	143	68.1	14.75	14.33	Right	0	N/A	0.000	1.102	1.005	0.000	0.000		54.1	
Body	6 GHz WIFU / IEEE 802.11ax	160	OFDM	L	OLED	0F36TC25413TF	99.46	-0.03	6025.00	15	68.1	14.25	13.61	Left	0	N/A	0.021	1.107	1.005	0.023	0.014		30.5	
Body	6 GHz WIFU / IEEE 802.11ax	160	OFDM	L	OLED	0F36TC25413TF	99.46	-0.09	6665.00	143	68.1	14.75	14.33	Left	0	N/A	0.021	1.102	1.005	0.023	0.014		31.0	
ANSI/IEEE C37.192 - SAFETY LIMIT																Body 1.6 W/kg (mW/g) averaged over 1 gram								
Uncontrolled Exposure/General Population																								
Exposure	Band/ Mode	Bandwidth [MHz]	Service/ Modulation	Ant.	Screen	Serial Number	Duty Cycle [%]	Power Drift [dB]	Frequency [MHz]	Channel #	Data Rate [Mbps]	Max Allowed Power [dBm]	Conducted Power [dBm]	Test Position	Spacing [mm]	Accessory	Measured APD [W/m² (4cm²)]	Power Scaling Factor	Duty Cycle Scaling Factor	Reported APD [W/m² (4cm²)]	APD Exposure Ratio	Plot #	Plimit [dBm]	Overall Plimit [dBm]
Body	6 GHz WIFU / IEEE 802.11ax	160	OFDM	L	OLED	0F36TC25413TF	99.46	-0.06	6025.00	15	68.1	14.25	13.61	Back	0	N/A	0.470	1.107	1.005	0.523	0.026		28.0	
Body	6 GHz WIFU / IEEE 802.11ax	160	OFDM	L	OLED	0F36TC25413TF	99.46	-0.14	6665.00	143	68.1	14.75	14.33	Back	0	N/A	0.499	1.102	1.005	0.553	0.028		28.3	
Body	6 GHz WIFU / IEEE 802.11ax	160	OFDM	L	OLED	0F36TC25413TF	99.46	-0.14	6025.00	15	68.1	14.25	13.61	Top	0	N/A	2.940	1.107	1.005	3.271	0.144		20.1	
Body	6 GHz WIFU / IEEE 802.11ax	160	OFDM	L	OLED	0F36TC25413TF	99.46	-0.20	6365.00	79	68.1	14.25	13.69	Top	0	N/A	2.610	1.118	1.005	2.714	0.161		20.1	
Body	6 GHz WIFU / IEEE 802.11ax	160	OFDM	L	OLED	0F36TC25413TF	99.46	-0.13	6665.00	143	68.1	14.75	14.33	Top	0	N/A	1.970	1.102	1.005	4.397	0.230		19.3	
Body	6 GHz WIFU / IEEE 802.11ax	160	OFDM	L	OLED	0F36TC25413TF	99.46	-0.06	6665.00	143	68.1	14.75	14.33	Top	0	Keyboard	1.860	1.102	1.005	4.275	0.214		19.4	
Body	6 GHz WIFU / IEEE 802.11be	320	OFDM	L	OLED	0F36TC25413TF	99.32	-0.01	6425.00	95	136.1	8.50	7.80	Top	0	N/A	0.140	1.148	1.007	0.163	0.132		16.3	
Body	6 GHz WIFU / IEEE 802.11be	320	OFDM	L	OLED	0F36TC25413TF	99.32	-0.01	6905.00	191	136.1	8.50	7.47	Top	0	N/A	0.111	1.268	1.007	0.125	0.056		18.9	
Body	6 GHz WIFU / IEEE 802.11ax	160	OFDM	L	OLED	0F36TC25413TF	99.46	-0.08	6025.00	15	68.1	14.25	13.61	Bottom	0	N/A	0.016	1.107	1.005	0.018	0.001		42.7	
Body	6 GHz WIFU / IEEE 802.11ax	160	OFDM	L	OLED	0F36TC25413TF	99.46	-0.06	6665.00	143	68.1	14.75	14.33	Bottom	0	N/A	0.007	1.102	1.005	0.007	0.002		45.4	
Body	6 GHz WIFU / IEEE 802.11ax	160	OFDM	L	OLED	0F36TC25413TF	99.46	-0.09	6025.00	15	68.1	14.25	13.61	Right	0	N/A	0.002	1.107	1.005	0.002	0.000		51.7	
Body	6 GHz WIFU / IEEE 802.11ax	160	OFDM	L	OLED	0F36TC25413TF	99.46	-0.04	6665.00	143	68.1	14.75	14.33	Right	0	N/A	0.011	1.102	1.005	0.012	0.001		44.8	
Body	6 GHz WIFU / IEEE 802.11ax	160	OFDM	L	OLED	0F36TC25413TF	99.46	-0.03	6025.00	15	68.1	14.25	13.61	Left	0	N/A	0.178	1.107	1.005	0.199	0.009		32.4	
Body	6 GHz WIFU / IEEE 802.11ax	160	OFDM	L	OLED	0F36TC25413TF	99.46	-0.09	6665.00	143	68.1	14.75	14.33	Left	0	N/A	0.160	1.102	1.005	0.177	0.009		33.2	

Table 10-12
6CD SISO Antenna L - Motion OLED

Exposure	Band / Mode	Bandwidth [MHz]	Service / Modulation	Ant.	Screen	Serial Number	Duty Cycle [%]	Power Drift [dB]	Frequency [MHz]	Channel #	Data Rate [Mbps]	Max Allowed Power [dBm]	Conducted Power [dBm]	Test Position	Spacing [mm]	Accessory	Measured 1g SAR [W/kg]	Power Scaling Factor	Duty Cycle Scaling Factor	Reported 1g SAR [W/kg]	Exposure Ratio [1g SAR]	Plot #	Plimit [dBm]	Overall Plimit [dBm]
Body	6 GHz WIFU / IEEE 802.11ax	160	OFDM	L	OLED	0F36TC25413TF	99.46	-0.06	6025.00	15	68.1	14.25	13.61	Back	0	N/A	0.058	1.107	1.005	0.065	0.041		26.1	
Body	6 GHz WIFU / IEEE 802.11ax	160	OFDM	L	OLED	0F36TC25413TF	99.46	-0.14	6665.00	143	68.1	14.75	14.33	Back	0	N/A	0.005	1.102	1.005	0.061	0.038		26.9	
Body	6 GHz WIFU / IEEE 802.11ax	160	OFDM	L	OLED	0F36TC25413TF	99.46	-0.14	6025.00	15	68.1	14.25	13.61	Top	0	N/A	0.378	1.107	1.005	0.421	0.263		18.0	
Body	6 GHz WIFU / IEEE 802.11ax	160	OFDM	L	OLED	0F36TC25413TF	99.46	-0.00	6365.00	79	68.1	14.25	13.69	Top	0	N/A	0.951	1.138	1.005	1.406	0.253		18.1	
Body	6 GHz WIFU / IEEE 802.11ax	160	OFDM	L	OLED	0F36TC25413TF	99.46	-0.13	6665.00	143	68.1	14.75	14.33	Top	0	N/A	0.471	1.102	1.005	0.522	0.326		17.5	
Body	6 GHz WIFU / IEEE 802.11ax	160	OFDM	L	OLED	0F36TC25413TF	99.46	-0.06	6665.00	143	68.1	14.75	14.33	Top	0	Keyboard	0.466	1.102	1.005	0.516	0.313		17.6	
Body	6 GHz WIFU / IEEE 802.11be	320	OFDM	L	OLED	0F36TC25413TF	99.32	-0.01	6425.00	95	136.1	8.50	7.89	Top	0	N/A	1.141	1.148	1.007	1.163	0.102		16.1	
Body	6 GHz WIFU / IEEE 802.11be	320	OFDM	L	OLED	0F36TC25413TF	99.32	-0.01	6905.00	191	136.1	8.50	7.47	Top	0	N/A	0.118	1.268	1.007	0.131	0.094		16.7	
Body	6 GHz WIFU / IEEE 802.11ax	160	OFDM	L	OLED	0F36TC25413TF	99.46	-0.08	6025.00	15	68.1	14.25	13.61	Bottom	0	N/A	0.002	1.107	1.005	0.002	0.001		40.7	
Body	6 GHz WIFU / IEEE 802.11ax	160	OFDM	L	OLED	0F36TC25413TF	99.46	-0.06	6665.00	143	68.1	14.75	14.33	Bottom	0	N/A	0.012	1.102	1.005	0.013	0.008		33.1	
Body	6 GHz WIFU / IEEE 802.11ax	160	OFDM	L	OLED	0F36TC25413TF	99.46	-0.09	6025.00	15	68.1	14.25	13.61	Right	0	N/A	0.000	1.107	1.005	0.000	0.000		53.7	
Body	6 GHz WIFU / IEEE 802.11ax	160	OFDM	L	OLED	0F36TC25413TF	99.46	-0.04	6665.00	143	68.1	14.75	14.33	Right	0	N/A	0.000	1.102	1.005	0.000	0.000		54.1	
Body	6 GHz WIFU / IEEE 802.11ax	160	OFDM	L	OLED	0F36TC25413TF	99.46	-0.03	6025.00	15	68.1	14.25	13.61	Left	0	N/A	0.021	1.107	1.005	0.023	0.014		30.5	
Body	6 GHz WIFU / IEEE 802.11ax	160	OFDM	L	OLED	0F36TC25413TF	99.46	-0.04	6665.00	143	68.1	14.75	14.33	Left	0	N/A	0.021	1.102	1.005	0.023	0.014		31.0	
ANSI/IEEE C95.1 1992 - SAFETY LIMIT																								
Spatial Peak																								
Uncontrolled Exposure/General Population																								
1.6 W/kg (mW/g) averaged over 1 gram																								
Exposure	Band/ Mode	Bandwidth [MHz]	Service/ Modulation	Ant.	Screen	Serial Number	Duty Cycle [%]	Power Drift [dB]	Frequency [MHz]	Channel #	Data Rate [Mbps]	Max Allowed Power [dBm]	Conducted Power [dBm]	Test Position	Spacing [mm]	Accessory	Measured APD [W/m ² /kg]	Power Scaling Factor	Duty Cycle Scaling Factor	Reported APD [W/m ² /kg]	APD Exposure Ratio	Plot #	Plimit [dBm]	Overall Plimit [dBm]
Body	6 GHz WIFU / IEEE 802.11ax	160	OFDM	L	OLED	0F36TC25413TF	99.46	-0.06	6025.00	15	68.1	14.25	13.61	Back	0	N/A	0.470	1.107	1.005	0.523	0.026		28.0	
Body	6 GHz WIFU / IEEE 802.11ax	160	OFDM	L	OLED	0F36TC25413TF	99.46	-0.14	6665.00	143	68.1	14.75	14.33	Back	0	N/A	0.499	1.102	1.005	0.531	0.028		28.2	
Body	6 GHz WIFU / IEEE 802.11ax	160	OFDM	L	OLED	0F36TC25413TF	99.46	-0.14	6025.00	15	68.1	14.25	13.61	Top	0	N/A	0.951	1.107	1.005	1.271	0.184		20.1	
Body	6 GHz WIFU / IEEE 802.11ax	160	OFDM	L	OLED	0F36TC25413TF	99.46	-0.20	6365.00	79	68.1	14.25	13.69	Top	0	N/A	2.810	1.138	1.005	2.514	0.161		20.3	
Body	6 GHz WIFU / IEEE 802.11ax	160	OFDM	L	OLED	0F36TC25413TF	99.46	-0.13	6665.00	143	68.1	14.75	14.33	Top	0	N/A	0.471	1.102	1.005	0.522	0.189		19.0	
Body	6 GHz WIFU / IEEE 802.11ax	160	OFDM	L	OLED	0F36TC25413TF	99.46	-0.08	6665.00	143	68.1	14.75	14.33	Top	0	Keyboard	1.860	1.102	1.005	2.475	0.214		19.4	
Body	6 GHz WIFU / IEEE 802.11be	320	OFDM	L	OLED	0F36TC25413TF	99.32	-0.01	6425.00	95	136.1	8.50	7.89	Top	0	N/A	1.940	1.148	1.007	1.203	0.060		18.7	
Body	6 GHz WIFU / IEEE 802.11be	320	OFDM	L	OLED	0F36TC25413TF	99.32	-0.01	6905.00	191	136.1	8.50	7.47	Top	0	N/A	0.180	1.268	1.007	0.188	0.020		18.9	
Body	6 GHz WIFU / IEEE 802.11ax	160	OFDM	L	OLED	0F36TC25413TF	99.46	-0.08	6025.00	15	68.1	14.25	13.61	Bottom	0	N/A	0.016	1.107	1.005	0.018	0.001		42.1	
Body	6 GHz WIFU / IEEE 802.11ax	160	OFDM	L	OLED	0F36TC25413TF	99.46	-0.06	6665.00	143	68.1	14.75	14.33	Bottom	0	N/A	0.007	1.102	1.005	0.107	0.005		35.4	
Body	6 GHz WIFU / IEEE 802.11ax	160	OFDM	L	OLED	0F36TC25413TF	99.46	-0.09	6025.00	15	68.1	14.25	13.61	Right	0	N/A	0.000	1.107	1.005	0.000	0.000		53.7	
Body	6 GHz WIFU / IEEE 802.11ax	160	OFDM	L	OLED	0F36TC25413TF	99.46	-0.04	6665.00	143	68.1	14.75	14.33	Right	0	N/A	0.011	1.102	1.005	0.012	0.001		44.8	
Body	6 GHz WIFU / IEEE 802.11ax	160	OFDM	L	OLED	0F36TC25413TF	99.46	-0.03	6025.00	15	68.1	14.25	13.61	Left	0	N/A	0.110	1.107	1.005	0.189	0.009		32.4	
Body	6 GHz WIFU / IEEE 802.11ax	160	OFDM	L	OLED	0F36TC25413TF	99.46	-0.04	6665.00	143	68.1	14.75	14.33	Left	0	N/A	0.110	1.102	1.005	0.189	0.009		32.4	

10.4 DSS SISO Standalone SAR Data

Table 10-13
DSS SISO Antenna R - Motion LCD

Exposure	Band / Mode	Service / Modulation	Ant.	Screen	Serial Number	Duty Cycle [%]	Power Drift [dB]	Frequency [MHz]	Channel #	Data Rate [Mbps]	Max Allowed Power [dBm]	Conducted Power [dBm]	Test Position	Spacing [mm]	Accessory	Measured 1g SAR [W/kg]	Power Scaling Factor	Duty Cycle Scaling Factor	Reported 1g SAR [W/kg]	Exposure Ratio (1g SAR)	Plot #
Body	2.4 GHz Bluetooth	FHSS	R	LCD	0F3DM3925423TF	77.03	0.02	2441.00	39	1	19.25	18.51	Back	0	N/A	0.064	1.186	1.026	0.078	0.049	
Body	2.4 GHz Bluetooth	FHSS	R	LCD	0F3DM3925423TF	77.03	0.06	2441.00	39	1	19.25	18.51	Top	0	N/A	0.280	1.186	1.026	0.462	0.289	
Body	2.4 GHz Bluetooth	FHSS	R	LCD	0F3DM3925423TF	77.03	0.04	2441.00	39	1	19.25	18.51	Top	0	Keyboard	0.376	1.186	1.026	0.458	0.386	
Body	2.4 GHz Bluetooth	FHSS	R	LCD	0F3DM3925423TF	77.03	0.01	2441.00	39	1	19.25	18.51	Bottom	0	N/A	0.003	1.186	1.026	0.004	0.003	
Body	2.4 GHz Bluetooth	FHSS	R	LCD	0F3DM3925423TF	77.03	0.06	2441.00	39	1	19.25	18.51	Right	0	N/A	0.001	1.186	1.026	0.001	0.001	
Body	2.4 GHz Bluetooth	FHSS	R	LCD	0F3DM3925423TF	77.03	0.06	2441.00	39	1	19.25	18.51	Left	0	N/A	0.000	1.186	1.026	0.000	0.000	
ANSI/IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population																Body 1.6 W/kg (mW/g) averaged over 1 gram					

Table 10-14
DSS SISO Antenna R - Motion OLED

Exposure	Band / Mode	Service / Modulation	Ant.	Screen	Serial Number	Duty Cycle [%]	Power Drift [dB]	Frequency [MHz]	Channel #	Data Rate [Mbps]	Max Allowed Power [dBm]	Conducted Power [dBm]	Test Position	Spacing [mm]	Accessory	Measured 1g SAR [W/kg]	Power Scaling Factor	Duty Cycle Scaling Factor	Reported 1g SAR [W/kg]	Exposure Ratio (1g SAR)	Plot #
Body	2.4 GHz Bluetooth	FHSS	R	OLED	0F3343V25403TF	77.03	0.14	2441.00	39	1	19.25	18.68	Back	0	N/A	0.056	1.140	1.026	0.065	0.041	
Body	2.4 GHz Bluetooth	FHSS	R	OLED	0F3343V25403TF	77.03	-0.07	2441.00	39	1	19.25	18.68	Top	0	N/A	0.466	1.140	1.026	0.545	0.341	
Body	2.4 GHz Bluetooth	FHSS	R	OLED	0F3343V25403TF	77.03	-0.15	2441.00	39	1	19.25	18.68	Top	0	Keyboard	0.487	1.140	1.026	0.570	0.356	
Body	2.4 GHz Bluetooth	FHSS	R	OLED	0F3343425403TF	77.03	0.03	2441.00	39	1	19.25	18.68	Bottom	0	N/A	0.000	1.140	1.026	0.000	0.000	
Body	2.4 GHz Bluetooth	FHSS	R	OLED	0F3343V25403TF	77.03	0.02	2441.00	39	1	19.25	18.68	Right	0	N/A	0.003	1.140	1.026	0.004	0.003	
Body	2.4 GHz Bluetooth	FHSS	R	OLED	0F3343425403TF	77.03	-0.04	2441.00	39	1	19.25	18.68	Left	0	N/A	0.000	1.140	1.026	0.000	0.000	
ANSI/IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population																Body 1.6 W/kg (mW/g) averaged over 1 gram					

Table 10-15
DSS SISO Antenna R - Motion during conditions with 2.4/5/6 GHz WLAN LCD

Exposure	Band / Mode	Service / Modulation	Ant.	Screen	Serial Number	Duty Cycle [%]	Power Drift [dB]	Frequency [MHz]	Channel #	Data Rate [Mbps]	Max Allowed Power [dBm]	Conducted Power [dBm]	Test Position	Spacing [mm]	Accessory	Measured 1g SAR [W/kg]	Power Scaling Factor	Duty Cycle Scaling Factor	Reported 1g SAR [W/kg]	Exposure Ratio (1g SAR)	Plot #
Body	2.4 GHz Bluetooth	FHSS	R	LCD	0F3DM3925423TF	77.03	0.03	2441.00	39	1	14.0	13.43	Back	0		0.007	1.140	1.026	0.008	0.005	
Body	2.4 GHz Bluetooth	FHSS	R	LCD	0F3DM3925423TF	77.03	-0.11	2441.00	39	1	14.0	13.43	Top	0		0.047	1.140	1.026	0.055	0.034	
ANSI/IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population																Body 1.6 W/kg (mW/g) averaged over 1 gram					

Table 10-16
DSS SISO Antenna R - Motion during conditions with 2.4/5/6 GHz WLAN OLED

Exposure	Band / Mode	Service / Modulation	Ant.	Screen	Serial Number	Duty Cycle [%]	Power Drift [dB]	Frequency [MHz]	Channel #	Data Rate [Mbps]	Max Allowed Power [dBm]	Conducted Power [dBm]	Test Position	Spacing [mm]	Accessory	Measured 1g SAR [W/kg]	Power Scaling Factor	Duty Cycle Scaling Factor	Reported 1g SAR [W/kg]	Exposure Ratio (1g SAR)	Plot #
Body	2.4 GHz Bluetooth	FHSS	R	OLED	0F3343425403TF	77.03	0.08	2441.00	39	1	14.0	13.35	Back	0		0.008	1.161	1.026	0.010	0.006	
Body	2.4 GHz Bluetooth	FHSS	R	OLED	0F3343425403TF	77.03	0.01	2441.00	39	1	14.0	13.35	Top	0		0.058	1.161	1.026	0.069	0.043	
ANSI/IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population																Body 1.6 W/kg (mW/g) averaged over 1 gram					

Table 10-17
DSS SISO Antenna L - Motion LCD

Exposure	Band / Mode	Service / Modulation	Ant.	Screen	Serial Number	Duty Cycle [%]	Power Drift [dB]	Frequency [MHz]	Channel #	Data Rate [Mbps]	Max Allowed Power [dBm]	Conducted Power [dBm]	Test Position	Spacing [mm]	Accessory	Measured 1g SAR [W/kg]	Power Scaling Factor	Duty Cycle Scaling Factor	Reported 1g SAR [W/kg]	Exposure Ratio (1g SAR)	Plot #
Body	2.4 GHz Bluetooth	FHSS	L	LCD	0F3DM3925423TF	77.03	0.11	2441.00	39	1	19.25	18.69	Back	0	N/A	0.104	1.138	1.026	0.121	0.076	
Body	2.4 GHz Bluetooth	FHSS	L	LCD	0F3DM3925423TF	77.03	0.06	2441.00	39	1	19.25	18.69	Top	0	N/A	0.409	1.138	1.026	0.478	0.299	
Body	2.4 GHz Bluetooth	FHSS	L	LCD	0F3DM3925423TF	77.03	-0.11	2441.00	39	1	19.25	18.69	Top	0	Keyboard	0.397	1.138	1.026	0.464	0.290	
Body	2.4 GHz Bluetooth	FHSS	L	LCD	0F3DM3925423TF	77.03	0.06	2441.00	39	1	19.25	18.69	Bottom	0	N/A	0.012	1.138	1.026	0.014	0.009	
Body	2.4 GHz Bluetooth	FHSS	L	LCD	0F3DM3925423TF	77.03	0.03	2441.00	39	1	19.25	18.69	Right	0	N/A	0.000	1.138	1.026	0.000	0.000	
Body	2.4 GHz Bluetooth	FHSS	L	LCD	0F3DM3925423TF	77.03	0.02	2441.00	39	1	19.25	18.69	Left	0	N/A	0.004	1.138	1.026	0.005	0.003	
ANSI/IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population																Body 1.6 W/kg (mW/g) averaged over 1 gram					

Table 10-18
DSS SISO Antenna L - Motion OLED| Plot A4

Exposure	Band / Mode	Service / Modulation	Ant.	Screen	Serial Number	Duty Cycle [%]	Power Drift [dB]	Frequency [MHz]	Channel #	Data Rate [Mbps]	Max Allowed Power [dBm]	Conducted Power [dBm]	Test Position	Spacing [mm]	Accessory	Measured 1g SAR [W/kg]	Power Scaling Factor	Duty Cycle Scaling Factor	Reported 1g SAR [W/kg]	Exposure Ratio (1g SAR)	Plot #
Body	2.4 GHz Bluetooth	FHSS	L	OLED	0F3343V25403TF	77.03	0.01	2441.00	39	1	19.25	18.63	Back	0	N/A	0.084	1.153	1.026	0.099	0.062	
Body	2.4 GHz Bluetooth	FHSS	L	OLED	0F3343V25403TF	77.03	-0.01	2441.00	39	1	19.25	18.63	Top	0	N/A	0.495	1.153	1.026	0.586	0.366	
Body	2.4 GHz Bluetooth	FHSS	L	OLED	0F3343V25403TF	77.03	0.01	2441.00	39	1	19.25	18.63	Top	0	Keyboard	0.521	1.153	1.026	0.608	0.385	Plot
Body	2.4 GHz Bluetooth	FHSS	L	OLED	0F3343425403TF	77.03	0.04	2441.00	39	1	19.25	18.63	Bottom	0	N/A	0.003	1.153	1.026	0.004	0.003	
Body	2.4 GHz Bluetooth	FHSS	L	OLED	0F3343425403TF	77.03	0.07	2441.00	39	1	19.25	18.63	Right	0	N/A	0.000	1.153	1.026	0.000	0.000	
Body	2.4 GHz Bluetooth	FHSS	L	OLED	0F3343425403TF	77.03	0.01	2441.00	39	1	19.25	18.63	Left	0	N/A	0.000	1.153	1.026	0.000	0.000	
ANSI/IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population																Body 1.6 W/kg (mW/g) averaged over 1 gram					

FCC ID: C3K2085	RF EXPOSURE PART 1 TEST REPORT														Approved by: Technical Manager					
Document S/N: 1M2511200095-01.C3K	DUT Type: Portable Computing Device														Page 43 of 53					

REV 22.0
03/30/2022

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element. If you have any questions or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact CT.INFO@ELEMENT.COM.

Table 10-19
DSS SISO Antenna L - Motion during conditions with 2.4/5/6 GHz WLAN LCD

Exposure	Band / Mode	Service / Modulation	Ant.	Screen	Serial Number	Duty Cycle [%]	Power Drift [dB]	Frequency [MHz]	Channel #	Data Rate [Mbps]	Max Allowed Power [dBm]	Conducted Power [dBm]	Test Position	Spacing [mm]	Measured 1g SAR [W/kg]	Power Scaling Factor	Duty Cycle Scaling Factor	Reported 1g SAR [W/kg]	Exposure Ratio (1g SAR)	Plot #
Body	2.4 GHz Bluetooth	FHSS	L	LCD	0F3D39254231F	77.03	-0.09	2441.00	39	1	14.0	13.42	Back	0	0.013	1.143	1.026	0.015	0.009	
Body	2.4 GHz Bluetooth	FHSS	L	LCD	0F3D39254231F	77.03	-0.07	2441.00	39	1	14.0	13.42	Top	0	0.056	1.143	1.026	0.066	0.041	
ANSI/IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population														Body 1.6 W/kg (mW/g) averaged over 1 gram						

Table 10-20
DSS SISO Antenna L - Motion during conditions with 2.4/5/6 GHz WLAN OLED

Exposure	Band / Mode	Service / Modulation	Ant.	Screen	Serial Number	Duty Cycle [%]	Power Drift [dB]	Frequency [MHz]	Channel #	Data Rate [Mbps]	Max Allowed Power [dBm]	Conducted Power [dBm]	Test Position	Spacing [mm]	Measured 1g SAR [W/kg]	Power Scaling Factor	Duty Cycle Scaling Factor	Reported 1g SAR [W/kg]	Exposure Ratio (1g SAR)	Plot #
Body	2.4 GHz Bluetooth	FHSS	L	OLED	0F33434254031F	77.03	0.09	2441.00	39	1	14.0	13.31	Back	0	0.019	1.172	1.026	0.023	0.014	
Body	2.4 GHz Bluetooth	FHSS	L	OLED	0F33434254031F	77.03	-0.12	2441.00	39	1	14.0	13.31	Top	0	0.105	1.172	1.026	0.126	0.079	
ANSI/IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population														Body 1.6 W/kg (mW/g) averaged over 1 gram						

10.5 SAR Test Notes

General Notes:

- The test data reported are the worst-case SAR values according to test procedures specified in IEEE 1528-2013, FCC KDB Publication 447498 D04v01, and FCC KDB Publication 616217 D04v01r02.
- Batteries are fully charged at the beginning of the SAR measurements.
- Liquid tissue depth was at least 15.0 cm for all frequencies.
- The manufacturer has confirmed that the device(s) tested have the same physical, mechanical and thermal characteristics and are within operational tolerances expected for production units.
- SAR results were scaled to the maximum allowed power to demonstrate compliance per FCC KDB Publication 447498 D04v01.
- Per FCC KDB Publication 865664 D01v01r04, variability SAR tests were not required since measured SAR results for all frequency bands were less than 0.8 W/kg.
- This device uses Qualcomm FastConnect TAS for WLAN operations to control and manage transmitting power in real time to ensure RF Exposure compliance. Per FCC Guidance, compliance for was assessed at the minimum of the time averaged power and the maximum output power for each band/mode/exposure condition (DSI).
- Per October 2020 TCB Workshop notes, absorbed power density (APD) using a 4cm² averaging area is reported based on SAR measurements.
- FCC KDB Publication 616217 D04v01r02 Section 4.3, SAR tests are required for the back surface and edges of the device with the device touching the phantom. The SAR Exclusion Threshold in FCC KDB 447498 D04v01 was applied to determine SAR test exclusion for adjacent edge configurations.
- Per FCC KDB 648474 D04, when the motion sensor is active, the highest reported SAR tablet configuration for a transmission band on an antenna was additionally evaluated with keyboard accessory attached and folded back at 360°.
- The orange highlights throughout the report represent the highest scaled SAR per Equipment Class.
- The device is sold with either an OLED or LCD display type. Testing was performed with both display types.
- Please see the original filing for reference for NFC and No Motion data.

WLAN Notes:

- Justification for test configurations for WLAN per KDB Publication 248227 D01v02r02 for 2.4 GHz WIFI single transmission chain operations, the highest measured maximum output power channel for DSSS was selected for SAR measurement. SAR for OFDM modes (2.4 GHz 802.11g/n/ax) was not required due to the maximum allowed powers and the highest reported DSSS SAR. See Section 7.2.5 for more information.

FCC ID: C3K2085	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
Document S/N: 1M2511200095-01.C3K	DUT Type: Portable Computing Device	Page 44 of 53

REV 22.0
03/30/2022

2. Justification for test configurations for WLAN per KDB Publication 248227 D01v02r02 for 5 GHz WIFI operations, the initial test configuration was selected according to the transmission mode with the highest maximum allowed powers. Other transmission modes were not investigated since the highest reported SAR for initial test configuration adjusted by the ratio of maximum output powers is less than 1.2 W/kg for 1g evaluations. See Section 7.2.6 for more information.
3. Per KDB Publication 248227 D01v02r02, SAR for MIMO was evaluated by following the simultaneous SAR provisions from KDB Publication 447498 D04v01 by either evaluating the sum of the 1g SAR values of each antenna transmitting independently or making a SAR measurement with both antennas transmitting simultaneously. Please see the Multi-Tx and Antenna SAR Considerations Appendix for complete analysis.
4. When the maximum reported 1g averaged SAR is ≤ 0.8 W/kg, SAR testing on additional channels was not required. Otherwise, SAR for the next highest output power channel was required until the reported SAR result was ≤ 1.20 W/kg for 1g evaluations or all test channels were measured.
5. The device was configured to transmit continuously at the required data rate, channel bandwidth and signal modulation, using the highest transmission duty factor supported by the test mode tools. The reported SAR was scaled to the 100% transmission duty factor to determine compliance. Procedures used to measure the duty factor are identical to that in the associated EMC test reports.
6. Per FCC guidance, SAR was performed using 6.5 GHz SAR probe calibration factors. Per October 2020 TCB Workshop notes, 5 channels were tested.

Bluetooth Notes

1. Bluetooth SAR was measured with the device connected to a call box with hopping disabled with DH5 operation and Tx Tests test mode type. Per October 2016 TCB Workshop Notes, the reported SAR was scaled to the 79% transmission duty factor to determine compliance. See Section 8.2 for the time domain plot and calculation for the duty factor of the device.

FCC ID: C3K2085	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
Document S/N: 1M2511200095-01.C3K	DUT Type: Portable Computing Device	Page 45 of 53

REV 22.0
03/30/2022

11 POWER DENSITY DATA SUMMARY

11.1 6 GHz WIFI Power Density Results

Table 10-1
6CD - Motion Power Density – LCD| Plot A5

MEASUREMENT RESULTS																									
Frequency (MHz)	Channel	Mode	Service	Bandwidth (MHz)	Maximum Allowed Power (Ant 1) [dBm]	Conducted Power (Ant 1) [dBm]	Maximum Allowed Power (Ant 2) [dBm]	Conducted Power (Ant 2) [dBm]	Power Df/B [dB]	Spacing (mm)	Antenna Config.	DUT Serial Number	Data Rate (Mbps)	Side	Duty Cycle (%)	Grid Step (A)	iPD (W/m²)	Scaling Factor for Measurement Uncertainty per IEC 62479	Scaling Factor (Power)	Scaling Factor (Duty Cycle)	Normal psPD (W/m²)	Scaled Normal psPD (W/m²)	Total psPD (W/m²)	Scaled Total psPD (W/m²)	Plot #
6665.00	143	802.11ax	OFDM	160	13.75	13.63	N/A	N/A	0.12	2	R	9F3DM325423TF	66.1	Top	99.44	0.05	2.890	1.554	1.028	1.006	3.380	5.432	3.960	6.364	Plot
6665.00	143	802.11ax	OFDM	160	13.75	13.63	N/A	N/A	0.10	9	R	9F3DM325423TF	66.1	Top	99.44	0.05	2.470	1.554	1.028	1.006	1.000	1.607	1.120	1.800	
6665.00	143	802.11ax	OFDM	160	N/A	N/A	14.75	14.40	0.11	2	L	9F3DM325423TF	66.1	Top	99.46	0.05	1.660	1.554	1.084	1.005	1.820	3.081	2.430	4.114	
6665.00	143	802.11ax	OFDM	160	N/A	N/A	14.75	14.40	-0.09	9	L	9F3DM325423TF	66.1	Top	99.46	0.25	1.950	1.554	1.084	1.005	1.300	2.201	1.440	2.438	
47 CFR §1.1310 - SAFETY LIMIT Spatial Average Uncontrolled Exposure / General Population																		Power Density 10 W/m² averaged over 4 cm²							

Table 10-2
6CD - Motion Power Density – OLED

MEASUREMENT RESULTS																									
Frequency (MHz)	Channel	Mode	Service	Bandwidth (MHz)	Maximum Allowed Power (Ant 1) (dBm)	Conducted Power (Ant 1) (dBm)	Maximum Allowed Power (Ant 2) (dBm)	Conducted Power (Ant 2) (dBm)	Power Df/B (dB)	Spacing (mm)	Antenna Config.	DUT Serial Number	Data Rate (Mbps)	Side	Duty Cycle (%)	Grid Step (A)	iPD (W/m²)	Scaling Factor for Measurement Uncertainty per IEC 62479	Scaling Factor (Power)	Scaling Factor (Duty Cycle)	Normal psPD (W/m²)	Scaled Normal psPD (W/m²)	Total psPD (W/m²)	Scaled Total psPD (W/m²)	Plot #
6665.00	143	802.11ax	OFDM	160	13.75	13.52	N/A	N/A	-0.16	2	R	9F36T825413TF	66.1	Top	99.44	0.05	2.060	1.554	1.054	1.006	2.110	3.477	2.140	3.526	
6665.00	143	802.11ax	OFDM	160	13.75	13.52	N/A	N/A	0.14	9	R	9F36T825413TF	66.1	Top	99.44	0.25	0.836	1.554	1.054	1.006	0.162	0.267	0.169	0.278	
6665.00	143	802.11ax	OFDM	160	N/A	N/A	14.75	14.33	-0.15	2	L	9F36T825413TF	66.1	Top	99.46	0.05	2.470	1.554	1.102	1.005	2.370	4.079	2.850	4.905	
6665.00	143	802.11ax	OFDM	160	N/A	N/A	14.75	14.33	-0.19	9	L	9F36T825413TF	66.1	Top	99.46	0.05	1.220	1.554	1.102	1.005	1.150	1.979	1.180	2.031	
47 CFR §1.1310 - SAFETY LIMIT Spatial Average Uncontrolled Exposure / General Population																		Power Density 10 W/m² averaged over 4 cm²							

Power Density General Notes

1. The manufacturer has confirmed that the devices tested have the same physical, mechanical and thermal characteristics and are within operational tolerances expected for production units.
2. Batteries are fully charged at the beginning of the measurements. The DUT was connected to a wall charger for some measurements due to the test duration. It was confirmed that the charger plugged into this DUT did not impact the near-field PD test results.
3. Power density was calculated by repeated E-field measurements on two measurement planes separated by $\lambda/4$.
4. The device was configured to transmit continuously at the required data rate, channel bandwidth and signal modulation, using the highest transmission duty factor supported by the test mode tools.
5. Per FCC guidance and equipment manufacturer guidance, power density results were scaled according to IEC 62479:2010 for the portion of the measurement uncertainty > 30%. Total expanded uncertainty of 2.68 dB (85.4%) was used to determine the psPD measurement scaling factor.
6. Per equipment manufacturer guidance, power density was measured at $d=2\text{mm}$ and $d=\lambda/5\text{mm}$ using the same grid size and grid step size for some frequencies and surfaces. The integrated Power Density (iPD) was calculated based on these measurements. Since iPD ratio between the two distances is $\geq -1\text{dB}$, the grid step was sufficient for determining compliance at $d=2\text{mm}$.
7. PTP-PR algorithm was used during psPD measurement and calculations.
8. PD results were scaled to the maximum allowed power to demonstrate compliance per FCC KDB Publication 447498 D04.

FCC ID: C3K2085	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
Document S/N: 1M2511200095-01.C3K	DUT Type: Portable Computing Device	Page 46 of 53

12 SAR MEASUREMENT VARIABILITY

12.1 Measurement Variability

Per FCC KDB Publication 865664 D01v01r04, all measured 1 g SAR values were <0.8 W/kg. Therefore, no SAR measurement variability analysis was required.

12.2 Measurement Uncertainty

The measured SAR was <1.5 W/kg for 1g for all frequency bands. Therefore, per KDB Publication 865664 D01v01r04, the extended measurement uncertainty analysis per IEEE 1528-2013 was not required.

FCC ID: C3K2085	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
Document S/N: 1M2511200095-01.C3K	DUT Type: Portable Computing Device	Page 47 of 53

REV 22.0
03/30/2022

13 EQUIPMENT LIST

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
Agilent	N5182A	MXG Vector Signal Generator	5/30/2025	Annual	5/30/2026	MY48180366
Agilent	N5182A	MXG Vector Signal Generator	8/1/2025	Annual	8/1/2026	MY47420651
Anritsu	MS2038C	20 GHz Network Analyzer	5/14/2025	Annual	5/14/2026	1214109
Agilent	N4010A	Wireless Connectivity Test Set	N/A	N/A	N/A	GB46170464
Amplifier Research	15S1G6	Amplifier	CBT	N/A	CBT	433974
Anritsu	MN8110B	I/O Adaptor	CBT	N/A	CBT	6261747881
Rohde & Schwarz	NRP2	Power Meter	5/23/2025	Annual	5/23/2026	103084
Anritsu	MA24106A	USB Power Sensor	5/29/2025	Annual	5/29/2026	1344554
Anritsu	MA24106A	USB Power Sensor	6/26/2025	Annual	6/26/2026	1827529
Control Company	4052	Long Stem Thermometer	2/27/2024	Biennial	2/27/2026	240174346
Control Company	4052	Long Stem Thermometer	2/27/2024	Biennial	2/27/2026	240171096
Control Company	4052	Long Stem Thermometer	2/27/2024	Biennial	2/27/2026	240171059
Control Company	4040	Therm./ Clock/ Humidity Monitor	4/15/2024	Biennial	4/15/2026	240310280
Control Company	4040	Therm./ Clock/ Humidity Monitor	10/15/2024	Biennial	10/15/2026	240763503
Testo	ALARM-HYGROMETER	ALARM-HYGROMETER	7/3/2025	Annual	7/3/2026	83316952
Testo	ALARM-HYGROMETER	ALARM-HYGROMETER	7/3/2025	Annual	7/3/2026	83316953
Testo	ALARM-HYGROMETER	ALARM-HYGROMETER	7/3/2025	Annual	7/3/2026	83316970
Keysight Technologies	N9020A	MXA Signal Analyzer	9/15/2025	Annual	9/15/2026	MY48010233
MCL	BW-N6W5+	6dB Attenuator	CBT	N/A	CBT	1139
MCL	BW-N3W5+	3dB Attenuator	CBT	N/A	CBT	2028
Mini-Circuits	VLF-6000+	Low Pass Filter DC to 6000 MHz	CBT	N/A	CBT	N/A
Mini-Circuits	VLF-6000+	Low Pass Filter DC to 6000 MHz	CBT	N/A	CBT	31634
Mini-Circuits	BW-N20W5+	DC to 18 GHz Precision Fixed 20 dB Attenuator	CBT	N/A	CBT	N/A
Mini-Circuits	NLP-1200+	Low Pass Filter DC to 1000 MHz	CBT	N/A	CBT	N/A
Mini-Circuits	NLP-2950+	Low Pass Filter DC to 2700 MHz	CBT	N/A	CBT	N/A
Mini-Circuits	BW-N20W5	Power Attenuator	CBT	N/A	CBT	1226
Mini-Circuits	ZUDC10-83-S+	Directional Coupler	CBT	N/A	CBT	2050
Narda	4772-3	Attenuator (3dB)	CBT	N/A	CBT	9406
Narda	BW-S3W2	Attenuator (3dB)	CBT	N/A	CBT	120
Seekonk	NC-100	Torque Wrench	4/2/2024	Biennial	4/2/2026	1262
SPEAG	DAK-3.5	Dielectric Assessment Kit	11/10/2025	Annual	11/10/2026	1277
SPEAG	DAK-3.5	Dielectric Assessment Kit	8/5/2025	Annual	8/6/2026	1041
SPEAG	DAK-3.5	Dielectric Assessment Kit	7/14/2025	Annual	7/14/2026	1039
SPEAG	MAIA	Modulation and Audio Interference Analyzer	N/A	N/A	N/A	1237
SPEAG	MAIA	Modulation and Audio Interference Analyzer	N/A	N/A	N/A	1331
SPEAG	MAIA	Modulation and Audio Interference Analyzer	N/A	N/A	N/A	1390
SPEAG	D2450V2	2450 MHz SAR Dipole	10/7/2025	Annual	10/7/2026	797
SPEAG	D5GHzV2	5 GHz SAR Dipole	2/21/2024	Biennial	2/21/2027	1057
SPEAG	D6.5GHzV2	6.5 GHz SAR Dipole	12/5/2025	Annual	12/5/2026	1018
SPEAG	5G Verification Source 10GHz	10GHz System Verification Antenna	3/4/2025	Annual	3/4/2026	1002
SPEAG	DAE4	Dasy Data Acquisition Electronics	3/11/2025	Annual	3/11/2026	1415
SPEAG	DAE4	Dasy Data Acquisition Electronics	12/3/2025	Annual	12/3/2026	1213
SPEAG	DAE4	Dasy Data Acquisition Electronics	6/5/2025	Annual	6/5/2026	1558
SPEAG	DAE4ip	Dasy Data Acquisition Electronics	2/7/2025	Annual	2/7/2026	1638
SPEAG	EUmmWV3	EUmmWV3 Probe	3/12/2025	Annual	3/12/2026	9421
SPEAG	EX3DV4	SAR Probe	3/7/2025	Annual	3/7/2026	7488
SPEAG	EX3DV4	SAR Probe	6/11/2025	Annual	6/11/2026	7661
SPEAG	EX3DV4	SAR Probe	2/10/2025	Annual	2/10/2026	7570

Note: 1) All equipment was used solely within its respective calibration period. 2) CBT (Calibrated Before Testing). Prior to testing, the measurement paths containing a cable, amplifier, attenuator, coupler or filter were connected to a calibrated source (i.e. a signal generator) to determine the losses of the measurement path. The power meter offset was then adjusted to compensate for the measurement system losses. This level offset is stored within the power meter before measurements are made. This calibration verification procedure applies to the system verification and output power measurements. The calibrated reading is then taken directly from the power meter after compensation of the losses for all final power measurements.

FCC ID: C3K2085	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
Document S/N: 1M2511200095-01.C3K	DUT Type: Portable Computing Device	Page 48 of 53

REV 22.0
03/30/2022

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element. If you have any questions or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact CT.INFO@ELEMENT.COM.

14 MEASUREMENT UNCERTAINTIES

Applicable for SAR measurements:

SAR Uncertainty Budget based on IEEE 1528-2013 (0.3 GHz to 10 GHz)

a	b	c	d	e f(d,k)	f	g	h cx/f/e	i cxg/e	k
Uncertainty component	Reference	Tol. (± %)	Prob. dist.	Dvi.	ci (1g)	ci (10g)	lg ui (± %)	10g ui (± %)	vi
Measurement system									
Probe calibration	E.2.1	9.30	N	1	1	1	9.30	9.30	∞
Axial isotropy	E.2.2	0.25	N	1	0.707	0.707	0.18	0.18	∞
Hemispherical isotropy	E.2.2	1.30	N	1	0.707	0.707	0.92	0.92	∞
Boundary effect	E.2.3	2.00	R	1.73	1	1	1.15	1.15	∞
Linearity	E.2.4	0.30	R	1.73	1	1	0.17	0.17	∞
System detection limits	E.2.4	0.25	R	1.73	1	1	0.14	0.14	∞
Modulation response	E.2.5	4.80	R	1.73	1	1	2.77	2.77	∞
Readout electronics	E.2.6	0.30	N	1	1	1	0.30	0.30	∞
Response time	E.2.7	1.01	R	1.73	1	1	0.58	0.58	∞
Integration time	E.2.8	2.60	R	1.73	1	1	1.50	1.50	∞
RF ambient conditions - noise	E.6.1	3.00	R	1.73	1	1	1.73	1.73	∞
RF ambient conditions - reflections	E.6.1	3.00	R	1.73	1	1	1.73	1.73	∞
Probe positioner mechanical tolerance	E.6.2	0.04	R	1.73	1	1	0.02	0.02	∞
Probe positioning with respect to phantom shell	E.6.3	0.80	R	1.73	1	1	0.46	0.46	∞
Extrapolation, interpolation, and integration algorithms for max. SAR evaluation	E.5	4.00	R	1.73	1	1	2.31	2.31	∞
Test sample related									
Test sample positioning	E.4.2	3.12	N	1	1	1	3.12	3.12	35
Device holder uncertainty	E.4.1	1.67	N	1	1	1	1.67	1.67	5
Output power variation - SAR drift	E.2.9	5.00	R	1.73	1	1	2.89	2.89	∞
SAR scaling	E.6.5	0.00	R	1.73	1	1	0.00	0.00	∞
Phantom and tissue parameters									
Phantom shell uncertainty - shape, thickness and permittivity	E.3.1	7.60	R	1.73	1	1	4.39	4.39	∞
Uncertainty in SAR correction for deviations in permittivity and conductivity	E.3.2	0.00	N	1	1	1	0.00	0.00	∞
Liquid conductivity measurement	E.3.3	4.27	N	1	0.78	0.71	3.33	3.03	55
Liquid permittivity measurement	E.3.3	4.18	N	1	0.23	0.26	0.96	1.09	55
Liquid conductivity - temperature uncertainty	E.3.4	3.40	R	1.73	0.78	0.71	1.53	1.39	∞
Liquid permittivity - temperature uncertainty	E.3.4	0.60	R	1.73	0.23	0.26	0.08	0.09	∞
Liquid Conductivity - deviation from target values	E.3.2	5.00	R	1.73	0.64	0.43	1.85	1.24	∞
Liquid Permittivity - deviation from target values	E.3.2	5.00	R	1.73	0.60	0.49	1.73	1.41	∞
Combined standard uncertainty							13.1	12.9	150
Expanded uncertainty (95% confidence interval)							26.2	25.8	

FCC ID: C3K2085	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
Document S/N: 1M2511200095-01.C3K	DUT Type: Portable Computing Device	Page 49 of 53

REV 22.0
03/30/2022

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element. If you have any questions or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact CT.INFO@ELEMENT.COM.

Applicable for Power Density Measurements:

a	b	c	d	e	f = c x f/e	g
Uncertainty Component	Unc. (± dB)	Prob. Dist.	Div.	c _i	u _i (± dB)	v _i
Measurement System						
Calibration	0.49	N	1	1	0.49	∞
Probe Correction	0.00	R	1.73	1	0.00	∞
Frequency Response	0.20	R	1.73	1	0.12	∞
Sensor Cross Coupling	0.00	R	1.73	1	0.00	∞
Isotropy	0.50	R	1.73	1	0.29	∞
Linearity	0.20	R	1.73	1	0.12	∞
Probe Scattering	0.00	R	1.73	1	0.00	∞
Probe Positioning offset	0.30	R	1.73	1	0.17	∞
Probe Positioning Repeatability	0.04	R	1.73	1	0.02	∞
Sensor Mechanical Offset	0.00	R	1.73	1	0.00	∞
Probe Spatial Resolution	0.00	R	1.73	1	0.00	∞
Field Impedance Dependence	0.00	R	1.73	1	0.00	∞
Amplitude and Phase Drift	0.00	R	1.73	1	0.00	∞
Amplitude and Phase Noise	0.04	R	1.73	1	0.02	∞
Measurement Area Truncation	0.00	R	1.73	1	0.00	∞
Data Acquisition	0.03	N	1	1	0.03	∞
Sampling	0.00	R	1.73	1	0.00	∞
Field Reconstruction	2.00	R	1.73	1	1.15	∞
Forward Transformation	0.00	R	1.73	1	0.00	∞
Power Density Scaling	0.00	R	1.73	1	0.00	∞
Spatial Averaging	0.10	R	1.73	1	0.06	∞
System Detection Limit	0.04	R	1.73	1	0.02	∞
Test Sample Related						
Probe Coupling with DUT	0.00	R	1.73	1	0.00	∞
Modulation Response	0.40	R	1.73	1	0.23	∞
Integration Time	0.00	R	1.73	1	0.00	∞
Response Time	0.00	R	1.73	1	0.00	∞
Device Holder Influence	0.10	R	1.73	1	0.06	∞
DUT alignment	0.00	R	1.73	1	0.00	∞
RF Ambient Conditions	0.04	R	1.73	1	0.02	∞
Ambient Reflections	0.04	R	1.73	1	0.02	∞
Immunity/Secondary Reception	0.00	R	1.73	1	0.00	∞
Drift of DUT	0.21	R	1.73	1	0.12	∞
Combined Standard Uncertainty (k=1)					RSS	1.34
Expanded Uncertainty (95% CONFIDENCE LEVEL)					k=2	2.68

FCC ID: C3K2085	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
Document S/N: 1M2511200095-01.C3K	DUT Type: Portable Computing Device	Page 50 of 53

REV 22.0
03/30/2022

15 CONCLUSION

15.1 Measurement Conclusion

The SAR evaluation indicates that the EUT complies with the RF radiation exposure limits of the FCC and Innovation, Science, and Economic Development Canada, with respect to all parameters subject to this test. These measurements were taken to simulate the RF effects of RF exposure under worst-case conditions. Precise laboratory measures were taken to assure repeatability of the tests. The results and statements relate only to the item(s) tested.

Please note that the absorption and distribution of electromagnetic energy in the body are very complex phenomena that depend on the mass, shape, and size of the body, the orientation of the body with respect to the field vectors, and the electrical properties of both the body and the environment. Other variables that may play a substantial role in possible biological effects are those that characterize the environment (e.g. ambient temperature, air velocity, relative humidity, and body insulation) and those that characterize the individual (e.g. age, gender, activity level, debilitation, or disease). Because various factors may interact with one another to vary the specific biological outcome of an exposure to electromagnetic fields, any protection guide should consider maximal amplification of biological effects as a result of field-body interactions, environmental conditions, and physiological variables. [3]

FCC ID: C3K2085	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
Document S/N: 1M2511200095-01.C3K	DUT Type: Portable Computing Device	Page 51 of 53

REV 22.0
03/30/2022

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element. If you have any questions or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact CT.INFO@ELEMENT.COM.

16 REFERENCES

- [1] Federal Communications Commission, ET Docket 93-62, Guidelines for Evaluating the Environmental Effects of Radiofrequency Radiation, Aug. 1996.
- [2] ANSI/IEEE C95.1-2005, American National Standard safety levels with respect to human exposure to radio frequency electromagnetic fields, 3kHz to 300GHz, New York: IEEE, 2006.
- [3] ANSI/IEEE C95.1-1992, American National Standard safety levels with respect to human exposure to radio frequency electromagnetic fields, 3kHz to 300GHz, New York: IEEE, Sept. 1992.
- [4] ANSI/IEEE C95.3-2002, IEEE Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields - RF and Microwave, New York: IEEE, December 2002.
- [5] IEEE Standards Coordinating Committee 39 –Standards Coordinating Committee 34 – IEEE Std. 1528-2013, IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques.
- [6] NCRP, National Council on Radiation Protection and Measurements, Biological Effects and Exposure Criteria for RadioFrequency Electromagnetic Fields, NCRP Report No. 86, 1986. Reprinted Feb. 1995.
- [7] T. Schmid, O. Egger, N. Kuster, Automated E-field scanning system for dosimetric assessments, IEEE Transaction on Microwave Theory and Techniques, vol. 44, Jan. 1996, pp. 105-113.
- [8] K. Pokovic, T. Schmid, N. Kuster, Robust setup for precise calibration of E-field probes in tissue simulating liquids at mobile communications frequencies, ICECOM97, Oct. 1997, pp. 1 -124.
- [9] K. Pokovic, T. Schmid, and N. Kuster, E-field Probe with improved isotropy in brain simulating liquids, Proceedings of the ELMAR, Zadar, Croatia, June 23-25, 1996, pp. 172-175.
- [10] Schmid & Partner Engineering AG, Application Note: Data Storage and Evaluation, June 1998, p2.
- [11] V. Hombach, K. Meier, M. Burkhardt, E. Kuhn, N. Kuster, The Dependence of EM Energy Absorption upon Human Modeling at 900 MHz, IEEE Transaction on Microwave Theory and Techniques, vol. 44 no. 10, Oct. 1996, pp. 1865-1873.
- [12] N. Kuster and Q. Balzano, Energy absorption mechanism by biological bodies in the near field of dipole antennas above 300MHz, IEEE Transaction on Vehicular Technology, vol. 41, no. 1, Feb. 1992, pp. 17-23.
- [13] G. Hartsgrrove, A. Kraszewski, A. Surowiec, Simulated Biological Materials for Electromagnetic Radiation Absorption Studies, University of Ottawa, Bioelectromagnetics, Canada: 1987, pp. 29-36.
- [14] Q. Balzano, O. Garay, T. Manning Jr., Electromagnetic Energy Exposure of Simulated Users of Portable Cellular Telephones, IEEE Transactions on Vehicular Technology, vol. 44, no.3, Aug. 1995.
- [15] W. Gander, Computermathematic, Birkhaeuser, Basel, 1992.
- [16] W.H. Press, S.A. Teukolsky, W.T. Vetterling, and B.P. Flannery, Numerical Recipes in C, The Art of Scientific Computing, Second edition, Cambridge University Press, 1992.
- [17] N. Kuster, R. Kastle, T. Schmid, Dosimetric evaluation of mobile communications equipment with known precision, IEEE Transaction on Communications, vol. E80-B, no. 5, May 1997, pp. 645-652.
- [18] CENELEC CLC/SC111B, European Prestandard (prENV 50166-2), Human Exposure to Electromagnetic Fields High-frequency: 10kHz-300GHz, Jan. 1995.
- [19] Prof. Dr. Niels Kuster, ETH, Eidgenössische Technische Hochschule Zürich, Dosimetric Evaluation of the Cellular Phone.

FCC ID: C3K2085	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
Document S/N: 1M2511200095-01.C3K	DUT Type: Portable Computing Device	Page 52 of 53

REV 22.0
03/30/2022

- [20] IEC 62209-1, Measurement procedure for the assessment of specific absorption rate of human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices - Part 1: Devices used next to the ear (Frequency range of 300 MHz to 6 GHz), July 2016.
- [21] Innovation, Science, Economic Development Canada RSS-102 Radio Frequency Exposure Compliance of Radiocommunication Apparatus (All Frequency Bands) Issue 5, March 2015.
- [22] Health Canada Safety Code 6 Limits of Human Exposure to Radio Frequency Electromagnetic Fields in the Frequency Range from 3 kHz – 300 GHz, 2015
- [23] FCC SAR Test Procedures for 2G-3G Devices, Mobile Hotspot and UMPC Devices KDB Publications 941225, D01-D07
- [24] SAR Measurement Guidance for IEEE 802.11 Transmitters, KDB Publication 248227 D01
- [25] FCC SAR Considerations for Handsets with Multiple Transmitters and Antennas, KDB Publications 648474 D03-D04
- [26] FCC SAR Evaluation Considerations for Laptop, Notebook, Netbook and Tablet Computers, FCC KDB Publication 616217 D04
- [27] FCC SAR Measurement and Reporting Requirements for 100MHz – 6 GHz, KDB Publications 865664 D01-D02
- [28] FCC General RF Exposure Guidance and SAR Procedures for Dongles, KDB Publication 447498, D01-D02
- [29] Anexo à Resolução No. 533, de 10 de Setembro de 2009.
- [30] IEC 62209-2, Human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices - Human models, instrumentation, and procedures - Part 2: Procedure to determine the specific absorption rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz), Mar. 2010.

FCC ID: C3K2085	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
Document S/N: 1M2511200095-01.C3K	DUT Type: Portable Computing Device	Page 53 of 53

REV 22.0
03/30/2022