

APPENDIX B: TEST SEQUENCES



This report is Blockchain Verified. To verify the report authenticity, please visit [HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM](https://www.blockchain-verified.com) or by clicking on the Blockchain logo.

FCC ID: C3K2114	PART 2 RF EXPOSURE REPORT	Approved by: Technical Manager
DUT Type: Wireless Module		APPENDIX B: Page 1 of 4

1. Test sequence is generated based on below parameters of the DUT:
 - a. Measured maximum power (P_{max})
 - b. Measured Tx_power_at_SAR_design_target (P_{limit})
 - c. Reserve_power_margin (dB)
 - $P_{reserve} \text{ (dBm)} = \text{measured } P_{limit} \text{ (dBm)} - \text{Reserve_power_margin (dB)}$
 - d. SAR_time_window (100s for FCC)

2. Test Sequence 1 Waveform:

Based on the parameters above, the Test Sequence 1 is generated with one transition between high and low Tx powers. Here, high power = P_{max} ; low power = $P_{max}/2$, and the transition occurs after 80 seconds at high power P_{max} . As long as the power enforcement is taking into effective during one 100s/60s time window, the validation test with this defined test sequence 1 is valid, otherwise, select other radio configuration (band/DSI within the same technology group) having lower P_{limit} for this test. The Test sequence 1 waveform is shown below:




Figure B-1
Test sequence 1 waveform

FCC ID: C3K2114	PART 2 RF EXPOSURE REPORT	Approved by: Technical Manager
DUT Type: Wireless Module		APPENDIX B: Page 2 of 4

3. Test Sequence 2 Waveform:

Based on the parameters described above, the Test Sequence 2 is generated as described in Table B-1, which contains two 170 second-long sequences (yellow and green highlighted rows) that are mirrored around the center row of 20s, resulting in a total duration of 360 seconds:

Table B-1
Test Sequence 2

Time duration (seconds)	dB relative to P_{limit} or $P_{reserve}$
15	$P_{reserve} - 2$
20	P_{limit}
20	$(P_{limit} + P_{max})/2$ averaged in mW and rounded to nearest 0.1 dB step
10	$P_{reserve} - 6$
20	P_{max}
15	P_{limit}
15	$P_{reserve} - 5$
20	P_{max}
10	$P_{reserve} - 3$
15	P_{limit}
10	$P_{reserve} - 4$
20	$(P_{limit} + P_{max})/2$ averaged in mW and rounded to nearest 0.1 dB step
10	$P_{reserve} - 4$
15	P_{limit}
10	$P_{reserve} - 3$
20	P_{max}
15	$P_{reserve} - 5$
15	P_{limit}
20	P_{max}
10	$P_{reserve} - 6$
20	$(P_{limit} + P_{max})/2$ averaged in mW and rounded to nearest 0.1 dB step
20	P_{limit}
15	$P_{reserve} - 2$

FCC ID: C3K2114	PART 2 RF EXPOSURE REPORT	Approved by: Technical Manager
DUT Type: Wireless Module		APPENDIX B: Page 3 of 4

The Test Sequence 2 waveform is shown in Figure B-2.




Figure B-2
Test sequence 2 waveform

FCC ID: C3K2114	PART 2 RF EXPOSURE REPORT	Approved by: Technical Manager
DUT Type: Wireless Module		APPENDIX B: Page 4 of 4