LTA
Laboratory for Test & Approval Co.,Ltd.

243 Jubug-Ri,Yangji-Myeon, Yongin-Si, Gyeonggi-Do, Korea 449-822
Tel: +82-31-323-6008 Fax: +82-31-323-6010
http://www.ltalab.com

EMERSYS

Dates of Tests: March 28~April 06, 2012
Test Report S/N: LR500111204B
Test Site : LTA CO., LTD.

CERTIFICATION OF COMPLIANCE

FCC ID **C4OEMSD-W1**

APPLICANT **Emersys Corp**

Equipment Class	:	**Part 15 Spread Spectrum Transmitter (DSS)**
Manufacturing Description	:	**Bluetooth Speaker**
Manufacturer	:	**Emersys Corp**
Model name	:	**EMSD-W1**
Test Device Serial No.:	:	**Identical prototype**
Rule Part(s)	:	**FCC Part 15.247 Subpart C; ANSI C-63.4-2003**
Frequency Range	:	**2402 ~ 2480MHz**
RF power	:	**Max 2.54 dBm - Conducted**
Data of issue	:	**April 06 , 2012**

This test report is issued under the authority of:

Kyu-Hyun Lee, Manager

The test was supervised by:

Ki-Hun Cho, Test Engineer

This test result only responds to the tested sample. It is not allowed to copy this report even partly without the allowance of the test laboratory. The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.

NVLAP®

NVLAP LAB Code.: 200723-0

Copyright © 2012, LTA Co., Ltd.

TABLE OF CONTENTS

1. GENERAL INFORMATION'S ---------- 3

2. INFORMATION'S ABOUT TEST ITEM ---------- 4

3. TEST REPORT ---------- 5
3.1 SUMMARY OF TESTS ---------- 5
3.2 TECHNICAL CHARACTERISTICS TEST ---------- 6
3.2.1 CARRIER FREQUENCY SEPARATION ---------- 6
3.2.2 NUMBER OF HOPPING FREQUENCIES ---------- 8
3.2.3 20 dB BANDWIDTH ---------- 10
3.2.4 TIME OF OCCUPANCY (Dwell Time) ---------- 17
3.2.5 TRANSMITTER OUTPUT POWER ---------- 22
3.2.6 BAND – EDGE & SPURIOUS ---------- 26
3.2.7 FIELD STRENGTH OF HARMONICS-Transmitter ---------- 32
3.2.8 AC CONDUCTED EMISSIONS ---------- 36

APPENDIX
APPENDIX TEST EQUIPMENT USED FOR TESTS ---------- 39

Copyright © 2012, LTA Co., Ltd.

1. General information's

1-1 Test Performed

Company name : LTA Co., Ltd.
Address : 243, Jubug-ri,Yangji-Myeon,Youngin-Si, Kyunggi-Do, Korea. 449-822
Web site : http://www.ltalab.com
E-mail : chahn@ltalab.com
Telephone : +82-31-323-6008
Facsimile +82-31-323-6010

Quality control in the testing laboratory is implemented as per ISO/IEC 17025 which is the "General requirements for the competents of calibration and testing laboratory".

1-2 Accredited agencies

LTA Co., Ltd. is approved to perform EMC testing by the following agencies:

Agency	Country	Accreditation No.	Validity	Reference
NVLAP	U.S.A	200723-0	2012-09-30	ECT accredited Lab.
RRL	KOREA	KR0049	2013-04-24	EMC accredited Lab.
FCC	U.S.A	610755	2014-04-27	FCC filing
FCC	U.S.A	649054	2013-04-13	FCC CAB
VCCI	JAPAN	R2133(10m), C2307	2014-06-21	VCCI registration
VCCI	JAPAN	T-2009	2013-12-23	VCCI registration
IC	CANADA	IC5799	2012-05-14	IC filing

Copyright © 2012, LTA Co., Ltd.

2. Information's about test item

2-1 Client & Manufacturer

Company name	:	Emersys Corp
Address	:	#304 ACTS, 3-1, Doryong-Dong, Yuseong-Gu, Daejeon, KOREA
Telephone / Facsimile	:	+82-42-862-5034/ +82-42-862-5033

2-2 Equipment Under Test (EUT)

Trade name	:	Bluetooth Speaker
Model name	:	EMSD-W1
Serial number	:	Identical prototype
Date of receipt	:	March 26, 2012
EUT condition	:	Pre-production, not damaged
Antenna type	:	PCB Pattern antenna, Max Gain 0.6 dBi
Frequency Range	:	2402 ~ 2480MHz
RF output power	:	Max. 2.54 dBm - Conducted
Number of channels	:	79
Duty cycle	:	80.55 %
Channel spacing	:	1MHz
Channel Access Protocol	:	Frequency Hopping Spread Spectrum (FHSS)
Type of Modulation	:	Basic Mode(GFSK), EDR Mode(Pi/4 DQPSK, 8DPSK)
Power Source	:	3.7 Vdc from Internal Battery (Li-Ion Polymer Battery)
Firmware Version	:	V1.0

2-4 Tested frequency

	LOW	MID	HIGH
Frequency (MHz)	2402	2441	2480

2-5 Ancillary Equipment

Equipment	Model No.	Serial No.	Manufacturer
-	-	-	-

Copyright ⓒ 2012, LTA Co., Ltd.

3. Test Report

3.1 Summary of tests

FCC Part Section(s)	Parameter	Limit	Test Condition	Status (note 1)
15.247(a)	Carrier Frequency Separation	> 25 kHz	Conducted	C
15.247(a)	Number of Hopping Frequencies	> 15 hops		C
15.247(a)	20 dB Bandwidth 99% Bandwidth	> 1.5 MHz		C
15.247	Dwell Time	< 0.4 seconds		C
15.247(b)	Transmitter Output Power	< 250 mWatt		C
15.247(d)	Conducted Spurious emission	> 20 dBc		C
15.247(d)	Band Edge	> 20 dBc		C
15.249 / 15.209	Field Strength of Harmonics	< 54 dBuV (at 3m)	Radiated	C
15.109	Field Strength	-		C
15.207 /15.107	AC Conducted Emissions	EN 55022	Line Conducted	C
15.203	Antenna requirement	-	-	C

Note 1: C=Complies NC=Not Complies NT=Not Tested NA=Not Applicable

Note 2: The data in this test report are traceable to the national or international standards.

Note 1: Antenna Requirement

→ The **Emersys Corp** , FCC ID:**C4OEMSD-W1** unit complies with the requirement of §15.203.

The antenna type is PCB Pattern antenna

Note 2: The sample was tested according to the following specification:
FCC Parts 15.247; ANSI C-63.4-2003

Copyright © 2012, LTA Co., Ltd.

3.2 Transmitter requirements

3.2.1 Carrier Frequency Separation

Procedure:

The carrier frequency separation was measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function enabled.

After the trace being stable, the reading value between the peaks of the adjacent channels using the marker-delta function was recorded as the measurement results.

The spectrum analyzer is set to:

Span = 2~ 3 MHz (wide enough to capture the peaks of two adjacent channels)

RBW = 10 kHz (1% of the span or more) Sweep = auto

VBW = 10 kHz Detector function = peak

Trace = max hold

Measurement Data:

Test Results	
Carrier Frequency Separation (MHz)	**Result**
1.0014	Complies

- See next pages for actual measured spectrum plots.

Minimum Standard:

The EUT shall have hopping channel carrier frequencies separated by a minimum of 25kHz or two-thirds of 20dB bandwidth of the hopping channel, whichever is greater.

Measurement Setup



Figure 1: Measurement setup for the carrier frequency separation

Copyright © 2012, LTA Co., Ltd.

Carrier Frequency Separation

Basic Mode



EDR Mode



Copyright © 2012, LTA Co., Ltd.

3.2.2 Number of Hopping Frequencies

Procedure:

The number of hopping frequencies was measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function enabled.

To get higher resolution, four frequency ranges within the 2400 ~ 2483.5 MHz FH band were examined.

The spectrum analyzer is set to:

Frequency range Start = 2400.0MHz, Stop = 2483.5 MHz

RBW = 100 kHz (1% of the span or more) Sweep = auto

VBW = 100 kHz (VBW ≥ RBW) Detector function = peak

Trace = max hold Span > 40MHz

Measurement Data: Complies

Total number of Hopping Channels	79

- See next pages for actual measured spectrum plots.

Minimum Standard:

At least 15 hopes

Measurement Setup

Same as the Chapter 3.2.1 (Figure 1)

Copyright © 2012, LTA Co., Ltd.

Number of Hopping Frequencies



3.2.3 20 dB Bandwidth

Procedure:

The bandwidth at 20 dB below the highest inband spectral density was measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function disabled at the highest, middle and the lowest available channels..

After the trace being stable, Use the marker-to-peak function to set the marker to the peak of the emission. Use the marker-delta function to measure 20dB down one side of the emission. Reset the marker-delta function, and move the marker to the other side of the emission, until it is (as close as possible to) even with the reference marker level. The marker-delta reading at this point is the 20 dB bandwidth of the emission.

The spectrum analyzer is set to:

Center frequency = the highest, middle and the lowest channels

Span = 3 MHz (approximately 2 or 3 times of the 20 dB bandwidth)

RBW = 30 kHz

VBW = 30 kHz (VBW ≥ RBW)

Trace = max hold

Sweep = auto

Detector function = peak

Measurement Data: Basic Mode

Frequency (MHz)	Channel No.	Test Results(MHz)	
		20dB Bandwidth	99% Bandwidth
2402	0	0.821	0.860
2441	39	0.816	0.860
2480	78	0.816	0.860

Measurement Data: EDR Mode

Frequency (MHz)	Channel No.	Test Results(MHz)	
		20dB Bandwidth	99% Bandwidth
2402	0	1.216	1.207
2441	39	1.211	1.172
2480	78	1.211	1.164

- See next pages for actual measured spectrum plots.

Minimum Standard:

N/A

Measurement Setup

Same as the Chapter 3.2.1 (Figure 1)

Channel 1 of basic mode

20 dB Bandwidth



99% Bandwidth



Copyright © 2012, LTA Co., Ltd.

Channel 2 of basic mode

20 dB Bandwidth

99% Bandwidth



Copyright © 2012, LTA Co., Ltd.

Channel 3 of basic mode

20 dB Bandwidth



99% Bandwidth



Copyright © 2012, LTA Co., Ltd.

Channel 1 at EDR mode

20 dB Bandwidth



99% Bandwidth



Copyright © 2012, LTA Co., Ltd.

Channel 2 at EDR mode

20 dB Bandwidth



99% Bandwidth

Copyright © 2012, LTA Co., Ltd.

Channel 3 at EDR mode

20 dB Bandwidth



99% Bandwidth

Copyright © 2012, LTA Co., Ltd.

3.2.4 Time of Occupancy (Dwell Time)

Procedure:

The dwell time was measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function enabled.

The spectrum analyzer is set to:

Center frequency = 2441 MHz Span = zero

RBW = 1 MHz VBW = 1 MHz (VBW ≥ RBW)

Trace = max hold Detector function = peak

Measurement Data:

Mode	Number of transmission ina 31.6s (79Hopping*0.4)	Length of Transmission Time (msec)	Result (msec)	Limit (msec)
DH1	**30(Times / 3sec) *10.533 = 315.99**	**0.542**	**171.27**	**400**
DH3	**15(Times / 3sec) *10.533 = 158.00**	**1.791**	**282.98**	**400**
DH5	**10(Times / 3sec) *10.533 = 105.33**	**3.065**	**322.84**	**400**
EDR 3Mbps DH5	**10(Times / 3sec) *10.533 = 105.33**	**3.058**	**322.10**	**400**

- See next pages for actual measured spectrum plots.
- dwell time = {(number of hopping per second / number of slot) x duration time per channel} x 0.4 ms

Minimum Standard:

0.4 seconds within a 30 second period per any frequency

Measurement Setup

Same as the Chapter 3.2.1 (Figure 1)

Copyright © 2012, LTA Co., Ltd.

DH1 at basic mode





DH3 at basic mode





DH5 at basic mode





DH5 at EDR mode with 3Mbps





3.2.5 Transmitter Output Power

Procedure:

The peak output power was measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function disabled at the highest, middle and the lowest available channels..

After the trace being stable, Use the marker-to-peak function to set the marker to the peak of the emission. The indicated level is the peak output power.

The spectrum analyzer is set to:

Center frequency = the highest, middle and the lowest channels

Span = 10 MHz (approximately 5 times of the 20 dB bandwidth)

RBW = 3 MHz (greater than the 20dB bandwidth of the emission being measured)

VBW = 3 MHz (VBW ≥ RBW) Detector function = peak

Trace = max hold Sweep = auto

Measurement Data: Basic Mode

Frequency (MHz)	Ch.	Test Results		
		dBm	mW	Result
2402	0	**2.54**	**1.79**	Complies
2441	39	**2.46**	**1.76**	Complies
2480	78	**1.50**	**1.41**	Complies

Measurement Data: EDR Mode

Frequency (MHz)	Ch.	Test Results		
		dBm	mW	Result
2402	0	**1.89**	**1.55**	Complies
2441	39	**1.64**	**1.46**	Complies
2480	78	**0.33**	**1.08**	Complies

- See next pages for actual measured spectrum plots.

Minimum Standard:	< 250 mW

Measurement Setup

Same as the Chapter 3.2.1 (Figure 1)

Copyright © 2012, LTA Co., Ltd.

Channel 1
Basic mode

EDR mode



Copyright © 2012, LTA Co., Ltd.

Channel 2
Basic mode



EDR mode



Copyright © 2012, LTA Co., Ltd.

Channel 3
Basic mode

EDR mode



Copyright © 2012, LTA Co., Ltd.

3.2.6 Band Edge

Procedure:

The bandwidth at 20dB down from the highest inband spectral density is measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function disabled at the highest, middle and the lowest available channels.

After the trace being stable, Use the marker-to-peak function to measure 20 dB down both sides of the intentional emission.

The spectrum analyzer is set to:

Center frequency = the highest, middle and the lowest channels

RBW = 100 kHz	VBW = 100 kHz
Span = 10~30 MHz	Detector function = peak
Trace = max hold	Sweep = auto

Measurement Data: Complies

- All conducted emission in any 100kHz bandwidth outside of the spread spectrum band was at least 20dB lower than the highest inband spectral density. Therefore the applying equipment meets the requirement.
- See next pages for actual measured spectrum plots.

Minimum Standard:	> 20 dBc

Measurement Setup

Same as the Chapter 3.2.1 (Figure 1)

Band – edge

Lower edge



Upper edge



Band-edges in the restricted band 2310-2390 MHz measurement

Frequency [MHz]	Reading [dBuV/m] AV	Reading [dBuV/m] Peak	Pol.	Correction Factor Antenna	Correction Factor Amp. Gain	Correction Factor Cable	Limits [dBuV/m] AV	Limits [dBuV/m] Peak	Result [dBuV/m] AV	Result [dBuV/m] Peak	Margin [dB] AV	Margin [dB] Peak
2376.0	38.1	55.4	V	25.4	37.1	4.0	54.0	74.0	30.4	47.7	23.7	26.4

Band-edges in the restricted band 2483.5-2500 MHz measurement

Frequency [MHz]	Reading [dBuV/m] AV	Reading [dBuV/m] Peak	Pol.	Correction Factor Antenna	Correction Factor Amp. Gain	Correction Factor Cable	Limits [dBuV/m] AV	Limits [dBuV/m] Peak	Result [dBuV/m] AV	Result [dBuV/m] Peak	Margin [dB] AV	Margin [dB] Peak
2483.5	45.5	59.2	V	25.4	37.1	4.0	54.0	74.0	37.8	51.5	16.3	22.6

Note : This EUT was tested in 3 orthogonal positions and the worst-case data was presented.

Copyright © 2012, LTA Co., Ltd.

Unwanted Emission – Low channel

Frequency Range = 30 MHz ~ 26.5 GHz



Unwanted Emission – Middle channel

Frequency Range = 30 MHz ~ 26.5 GHz



Unwanted Emission – High channel

Frequency Range = 30 MHz ~ 26.5 GHz



3.2.7 Field Strength of Harmonics - Transmitter

Procedure:

The EUT was placed on a 0.8m high wooden table inside a shielded enclosure. An antenna was placed near the EUT and measurements of frequencies and amplitudes of field strengths were recorded for reference during final measurements. For final radiated testing, measurements were performed in OATS. Measurements were performed with the EUT oriented in 3 orthogonal axis and rotated 360 degrees to determine worst-case orientation for maximum emissions.

(a) In the frequency range of 9kHz to 30 MHz, magnetic field is measured with Loop Test Antenna. The Test Antenna is positioned with its plane vertical at 1m distance from the EUT. The center of the Loop Test Antenna is 1m above the ground. During the measurement the Loop Test Antenna rotates about its vertical axis for maximum response at each azimuth about the EUT.

(b) In the frequency range above 30MHz, Bi-Log Test Antenna (30MHz to 1GHz) and Horn Test Antenna (above 1GHz) are used. Test Antenna is 3m away from the EUT. Test Antenna height is carried from 1m to 4m above the ground to determine the maximum value of the field strength. The emission levels at both horizontal and vertical polarizations should be tested.

<u>The spectrum analyzer is set to:</u>

Center frequency = the worst channel

Frequency Range = 10 MHz ~ 10th harmonic.

RBW = 100 kHz (10MHz ~ 1 GHz) VBW $\geq$ RBW

= 1 MHz (1 GHz ~ 10th harmonic)

Span = 100 MHz Detector function = peak

Trace = max hold Sweep = auto

below 30MHz



below 1GHz (30MHz to 1GHz)



above 1GHz



Measurement Data: Complies

- See next pages for actual measured data.
- No other emissions were detected at a level greater than 20dB below limit include from 9KHz to 30MHz.

Minimum Standard: FCC Part 15.209(a)

Frequency (MHz)	Limit (uV/m) @ 3m
0.009 ~ 0.490	2400/F(kHz) **(@ 300m)**
0.490 ~ 1.705	24000/F(kHz) **(@ 30m)**
1.705 ~ 30	30**(@ 30m)**
30 ~ 88	100 **
88 ~ 216	150 **
216 ~ 960	200 **
Above 960	500

** Except as provided in 15.209(g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88MHz, 174-216MHz or 470-806MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g. 15.231 and 15.241.

Copyright © 2012, LTA Co., Ltd.

Measurement Data:

Frequency [MHz]	Reading [dBuV/m] AV	Reading [dBuV/m] Peak	Pol.	Correction Factor Antenna	Correction Factor Amp.Gain	Correction Factor Cable	D.C.F	Limits [dBuV/m] AV	Limits [dBuV/m] Peak	Result [dBuV/m] AV	Result [dBuV/m] Peak	Margin [dB] AV	Margin [dB] Peak
4803.0	64.4	73.9	V	31.4	36.5	5.7	-30.27	54.0	74.0	34.8	44.3	19.2	29.8
Frequency [MHz]	**Reading [dBuV/m] AV**	**Reading [dBuV/m] Peak**	**Pol.**	**Correction Factor Antenna**	**Correction Factor Amp.Gain**	**Correction Factor Cable**	**D.C.F**	**Limits [dBuV/m] AV**	**Limits [dBuV/m] Peak**	**Result [dBuV/m] AV**	**Result [dBuV/m] Peak**	**Margin [dB] AV**	**Margin [dB] Peak**
4881.0	63.6	70.1	V	31.4	36.5	5.7	-30.27	54.0	74.0	34.0	40.5	20.0	33.5
Frequency [MHz]	**Reading [dBuV/m] AV**	**Reading [dBuV/m] Peak**	**Pol.**	**Correction Factor Antenna**	**Correction Factor Amp.Gain**	**Correction Factor Cable**	**D.C.F**	**Limits [dBuV/m] AV**	**Limits [dBuV/m] Peak**	**Result [dBuV/m] AV**	**Result [dBuV/m] Peak**	**Margin [dB] AV**	**Margin [dB] Peak**
4960.0	54.5	63.1	V	31.4	36.5	5.7	-30.27	54.0	74.0	24.9	33.5	29.2	40.5

- No other emissions were detected at a level greater than 20dB below limit.
- D.C.F (Duty Cycle Correction Factor) = 20log(The worst Case DWELL Time/100ms)

  = 20log(3.065ms/100ms) = -30.27

Copyright © 2012, LTA Co., Ltd.

Radiated Emissions – BT + Charging mode

LTA
Laboratory for Test & Approval Co.,Ltd.

243 Jubug-ri, yangji-Myeon, Youngin-si,
Gyeonggi-do 449-822 Korea
Tel :+82-31-3236008,9
Fax:+82-31-3236010

EUT/Model No.: EMSD-W1 TEST MODE: BT + Charging mode

Temp Humi : 8 / 35 Tested by: PARK.H.W



	Freq MHz	Reading dBuV/m	C.F dB/m	Result dBuV/m	Limit QP dBuV/m	Margin dB	Height cm	Angle deg	Polarity
1	32.50	50.06	-24.54	25.52	29.50	3.98	100	235	VERTICAL
2	125.33	53.95	-24.46	29.49	33.00	3.51	100	83	VERTICAL
3	201.56	54.20	-24.28	29.92	33.00	3.08	400	112	HORIZONTAL
4	267.36	56.61	-24.30	32.31	35.60	3.29	375	201	HORIZONTAL
5	401.11	55.65	-25.25	30.40	35.60	5.20	100	69	VERTICAL
6	520.59	56.00	-25.99	30.01	35.60	5.59	150	213	HORIZONTAL

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain

- 1 -

Copyright © 2012, LTA Co., Ltd.

3.2.8 AC Conducted Emissions

Procedure:

The conducted emissions are measured in the shielded room with a spectrum analyzer in peak hold. While the measurement, EUT had its hopping function disabled at the middle channels in line with Section 15.31(m). Emissions closest to the limit are measured in the quasi-peak mode (QP) with the tuned receiver using a bandwidth of 9 kHz. The emissions are maximized further by cable manipulation and Exerciser operation. The highest emissions relative to the limit are listed.

Measurement Data: Complies

- Refer to the next page.
- No other emissions were detected at a level greater than 20dB below limit
- It gave the worse case emissions

Minimum Standard: FCC Part 15.207(a)/EN 55022

Frequency Range (MHz)	Conducted Limit (dBuV)	
	Quasi-Peak	Average
0.15 ~ 0.5	66 to 56 *	56 to 46 *
0.5 ~ 5	56	46
5 ~ 30	60	50

* Note: The limits will decrease with the frequency logarithmically within 0.15MHz to 0.5MHz

Copyright © 2012, LTA Co., Ltd.

Radiated Emissions – BT + Charging LINE

LTA
Laboratory for Test & Approval Co.,Ltd.

243 Jubug-ri, yangji-Myeon, Youngin-si,
Gyeonggi-do 449-822 Korea
Tel :+82-31-3236008,9
Fax:+82-31-3236010

EUT / Model No.	: EMSD-W1	Phase	: LINE
Test Mode	: BT+Charging mode	Test Power	: 120 / 60
Temp./Humi.	: 13 / 27	Test Engineer	: PARK H W



Freq MHz	RD QP dBuV	RD AV dBuV	C.F dB	Result QP dBuV	Result AV dBuV	Limit QP dBuV	Limit AV dBuV	Margin QP dB	Margin AV dB
0.278	30.33	10.43	9.58	39.91	20.01	60.88	50.88	20.97	30.87
0.552	25.72	6.82	9.63	35.35	16.45	56.00	46.00	20.65	29.55
0.849	22.83	6.73	9.69	32.51	16.41	56.00	46.00	23.49	29.59
1.132	17.23	3.23	9.72	26.95	12.95	56.00	46.00	29.05	33.05
1.452	29.94	20.09	9.74	39.68	29.83	56.00	46.00	16.32	16.17
2.030	28.35	19.55	9.72	38.07	29.27	56.00	46.00	17.93	16.73

Remarks: C.F (Correction Factor) = Insertion loss + Cable loss

- 1 -

Copyright © 2012, LTA Co., Ltd.

Radiated Emissions – BT + Charging NEUTRAL

LTA
Laboratory for Test & Approval Co.,Ltd.

243 Jubug-ri, yangji-Myeon, Youngin-si,
Gyeonggi-do 449-822 Korea
Tel :+82-31-3236008,9
Fax:+82-31-3236010

EUT / Model No.	: EMSD-W1	Phase	: NEUTRAL
Test Mode	: BT+Charging mode	Test Power	: 120 / 60
Temp./Humi.	: 12 / 27	Test Engineer	: PARK H W



Freq MHz	RD QP dBuV	RD AV dBuV	C.F dB	Result QP dBuV	Result AV dBuV	Limit QP dBuV	Limit AV dBuV	Margin QP dB	Margin AV dB
0.286	38.63	28.03	9.58	48.21	37.61	60.64	50.64	12.43	13.03
0.563	29.92	15.12	9.66	39.58	24.78	56.00	46.00	16.42	21.22
0.862	35.33	27.83	9.62	44.94	37.44	56.00	46.00	11.06	8.56
1.439	34.24	26.64	9.66	43.90	36.30	56.00	46.00	12.10	9.70
2.014	34.15	26.65	9.69	43.84	36.34	56.00	46.00	12.16	9.66
3.127	24.79	14.39	9.69	34.49	24.09	56.00	46.00	21.51	21.91

Remarks: C.F (Correction Factor) = Insertion loss + Cable loss

- 1 -

Copyright © 2012, LTA Co., Ltd.

APPENDIX

TEST EQUIPMENT USED FOR TESTS

Copyright © 2012, LTA Co., Ltd.

	Description	Model No.	Serial No.	Manufacturer	Interval	Last Cal. Date
1	Spectrum Analyzer (~30GHz)	FSV-30	100757	R&S	1 year	2012-01-10
2	Signal Generator (~3.2GHz)	8648C	3623A02597	HP	1 year	2012-03-28
3	Signal Generator (1~20GHz)	83711B	US34490456	HP	1 year	2012-03-28
4	Attenuator (3dB)	8491A	37822	HP	2 year	2010-10-08
5	Attenuator (10dB)	8491A	63196	HP	2 year	2010-10-08
6	Attenuator (30dB)	8498A	3318A10929	HP	2 year	2011-01-05
7	Test Receiver (~30MHz)	ESHS10	828404/009	R&S	1 year	2012-03-28
8	EMI Test Receiver (~1GHz)	ESCI7	100722	R&S	1 year	2011-10-07
9	RF Amplifier (~1.3GHz)	8447D	2439A09058	HP	2 year	2010-10-08
10	RF Amplifier (1~18GHz)	8449B	3008A02126	HP	2 year	2012-03-28
11	Horn Antenna (1~18GHz)	BBHA 9120D	9120D122	SCHWARZBECK	2 year	2010-12-24
12	Horn Antenna (18 ~ 40GHz)	SAS-574	154	Schwarzbeck	2 year	2010-11-25
13	Horn Antenna (18 ~ 40GHz)	SAS-574	155	Schwarzbeck	2 year	2010-11-25
14	TRILOG Antenna	VULB 9160	9160-3172	SCHWARZBECK	2 year	2010-10-07
15	Dipole Antenna	VHA9103	2116	SCHWARZBECK	2 year	2010-11-25
16	Dipole Antenna	VHA9103	2117	SCHWARZBECK	2 year	2010-11-25
17	Dipole Antenna	VHA9105	2261	SCHWARZBECK	2 year	2010-11-25
18	Dipole Antenna	VHA9105	2262	SCHWARZBECK	2 year	2010-11-25
19	Hygro-Thermograph	THB-36	0041557-01	ISUZU	2 year	2010-04-12
20	Splitter (SMA)	ZFSC-2-2500	SF617800326	Mini-Circuits	-	-
21	Power Divider	11636A	6243	HP	2 year	2010-10-08
22	DC Power Supply	6622A	3448A03079	HP	-	-
23	Frequency Counter	5342A	2826A12411	HP	1 year	2012-03-28
24	Power Meter	EPM-441A	GB32481702	HP	1 year	2012-03-28
25	Power Sensor	8481A	US41030291	HP	1 year	2011-10-07
26	Audio Analyzer	8903B	3729A18901	HP	1 year	2011-10-07
27	Modulation Analyzer	8901B	3749A05878	HP	1 year	2011-10-07
28	TEMP & HUMIDITY Chamber	YJ-500	LTAS06041	JinYoung Tech	1 year	2011-10-07
29	Stop Watch	HS-3	601Q09R	CASIO	2 year	2012-03-28
30	LISN	ENV216	100408	R&S	1 year	2011-10-07
31	UNIVERSAL RADIO COMMUNICATION TESTER	CMU200	106243	R&S	2 year	2010-05-13
32	Highpass Filter	WHKX1.5/15G-10SS	74	Wainwright Instruments	-	-
33	Highpass Filter	WHKX3.0/18G-10SS	118	Wainwright Instruments	-	-
34	Loop Antenna	FMZB 1516	151602/94	SCHWARZBECK	2 year	2011-04-05

Copyright © 2012, LTA Co., Ltd.