



深圳市锦鸿无线科技有限公司

产品规格书Product Specification

产品描述 Part Description	客户：科立讯 Vendor: 产品名称：V段136-150M Product Name: 物料代码： Part NO:	规格型号：JHKLX2505-127-A Description: 所承认项目：TP35 Project: 版本：A1 Version:		
附件 Attachments	☒ 规格书 Spec ☒ CPK 报告 Cpk Report ☐ 制造流程图 QC Flow Chart ☒ 包装方式 Packing Content	☒ 工程图面 Drawing ☒ 关键尺寸报告 FAI Report ☐ 成型条件 Molding conditions C3C 证书 3C Certificate	☒ 样品 Sample ☒ 可靠性测试报告 Reliability Report ☒ 材质证明书 Material Verification Sheet ☒ 物料检验标准 Material inspection standard	☒ ROHS 报告 ROHS Repot ☐ 安规报告 Safety Report
供应商签核 Vendor	拟制：胥万芳 Design:	审核：郑翠兰 Check:	批准：彭发辉 Approval:	
技术确认 Technology check	结构意见/签名： Mechanical 工业/包材设计意见/签名： ID 品质意见/签名： DQE/SQE	硬件意见/签名： Hardware 项目意见/签名： Market		
最终确认 Final check	质量策划： Quality planning	ROHS: ☐ Rohs 物料 ☐ 非 Rohs 物料		
承认条件 Approval condition	☐ 承认 Approved ☐ 条件承认 Condition approved ☐ 临时承认 Temporary approved	☐ 拒绝承认 Reject 需满足条件: _____ 限量 _____ PCS 采购		
审批 Approval by	研发总工（技术总监）： RD Leader(Technology Director)	质量总监： Quality Director		
分发部门 Distribute	☐ IQC	☐ 采购（供应商）	☐ 样品管理/文控	☐ 外协厂 ☐ 其它

Content

1	Content.....	2
2	Instructions.....	3
3	Product specifications.....	3
4	Mechanical properties test.....	4
5	Reliability test.....	5
6	VSWR test.....	6
7	Engineering drawings.....	7
8	Packing method.....	8

2 说明instructions

这份报告包含天线电性能测试的若干设备、测试环境和测试结果，以及天线的结构图纸和检验报告. 以下为天线图片。

This report includes several equipment, test environment and test results for the electrical performance of the antenna, as well as structural drawings and inspection reports of the antenna.Below is a picture of the antenna。



3 产品技术指标 Product specifications

电性能指标 Electrical Specifications	
频率范围 Frequency Range（MHz）	136-150M+GPS1575M
增益 Gain（dBi）	1.2
电压驻波比 VSWR	≤3.5
输入阻抗 Input Impedance（Ω）	50
极化方式 Polarization	垂直
最大功率 Maximum input power（W）	10
天线类型	棒状螺旋天线
接头型号 Input connector type	SMA-J
机械指标 Mechanical Specifications	
尺寸 Dimensions（mm）	171.5*16.4
重量 Antenna weight（kg）	25g
颜色 Antenna color	黑色

4 机械性能测试 Mechanical properties test

1	摇摆测试 BENDING TEST	放离接头 30CM 的线端上荷重 120g, 固定接头后进行遥摆测试, 遥摆角度左右各 60 度, 遥摆 1000 次后测试特性. The load on the wire end 30cm away from the connector is 120g. After fixing the connector, carry out the remote swing test, and the remote swing angle is on the left and right 60 degrees, Test the characteristics after 1000 remote swings	遥摆 1000 次后测试特性无任何现象显示电器性能之损坏. After 1000 times of remote swing, the test characteristics show no damage to the electrical performance
2	强度测试 STRENG TEST	一个 15 磅之静负荷施加放线端底部持续一分钟. A static load of 15 pounds is applied to the bottom of the paying off end for one minute	无任何现象显示机械及电器性能之损坏. There is no sign of damage to mechanical and electrical properties
3	拉力测试 PULLING FORCE	用拉力计接头及线材间进行拉力测试. Conduct tension test between joint and wire rod with tension meter	可承受拉力为5Kg 无任何现象显示电器性能之损坏. It can bear the tensile force of 5kg without any damage to the electrical performance
4	振动测试 VIBRATION TEST	以 1.10mm 和振幅和33.30Hz/sec 振动频率以 X 轴方向振动 120 分钟, Y轴方向振动 120 分钟, Z 轴方向振动 240 分钟. Vibrate in the x-axis direction for 120 minutes with an amplitude of 1.10mm and a vibration frequency of 33.30hz/sec, and vibrate in the y-axis direction 120 minutes, vibration in z-axis direction for 240 minutes	无任何现象显示电器性能之损坏. There is no sign of damage to the electrical performance

5 耐久性测试


1	盐雾试验 SAIT SPRAY TEST	盐水喷雾试验：依 GB1266-86 标准蒸馏水： 一次蒸馏PH6.5~7 喷雾量：1.4me80cm²/h 压缩空气压力： 1Kgf/ cm² 试验相对度：98° 温度：45° ~47° 压力温度：35° 测试时间：24hr Brine spray test: distilled water according to GB1266-86 standard: single distillationPH6.5~7 Spray volume: 1.4me80cm²/ H compressed air pressure: 1kgf / cm² Test Relativity: 98 ° Temperature: 45 ° ~ 47 ° Pressure temperature: 35 ° Test time: 24hr	所有规格变华 范围初始值 30% All characteristic range is 30% of the initial value
2	高温试验 HEAT TEST	在 85+2℃环境中放 96 小时，再放在正常环境中 30 分钟后进行测试 85+2℃ for 96 hours, after keep in normal condition for 30min the to test.	
3	中温试验 HUMIDITY TEST	在 40+2℃ 90-95%RH 环境中放 96 小时，再放在正常环境中 30 分钟后进行测试 40+2℃ 90-95%RH for 96hours, after keep in normal condition for 30min the to test.	
4	底温试验 COLD TEST	在-40+2℃ 环境中放 96 小时，再置放正常环境中 30 分钟后进行测试 -40+2℃ for 96hours, after keep in normal condition for 30min the to test.	

6 驻波测试 VSWR Test



7工程图纸 Engineering drawings

说明：天线内部导线为GPS辐射振子



8 包装方式 **Packing method**

Inside:


PE bag packaging, 100pcs / bag



PE bag size: 30*180

External :

carton packaging, 50 bags / box



carton packaging size 330*270*220



深圳市锦鸿无线科技有限公司

产品规格书Product Specification

产品描述 Part Description	客户：科立讯 Vendor: 产品名称：TP35-V全段天线 Product Name: 物料代码： Part NO:	规格型号：JHKLX2606-213-A Description: 所承认项目： Project: 版本：A1 Version:		
附件 Attachments	☒ 规格书 Spec ☒ CPK 报告 Cpk Report ☐ 制造流程图 QC Flow Chart ☒ 包装方式 Packing Content	☒ 工程图面 Drawing ☒ 关键尺寸报告 FAI Report ☐ 成型条件 Molding conditions C3C 证书 3C Certificate	☒ 样品 Sample ☒ 可靠性测试报告 Reliability Report ☒ 材质证明书 Material Verification Sheet ☒ 物料检验标准 Material inspection standard	☒ ROHS 报告 ROHS Repot ☐ 安规报告 Safety Report
供应商签核 Vendor	拟制：胥万芳 Design:	审核：郑翠兰 Check:	批准：彭发辉 Approval:	
技术确认 Technology check	结构意见/签名： Mechanical 工业/包材设计意见/签名： ID 品质意见/签名： DQE/SQE	硬件意见/签名： Hardware 项目意见/签名： Market		
最终确认 Final check	质量策划： Quality planning	ROHS: ☐ Rohs 物料 ☐ 非 Rohs 物料		
承认条件 Approval condition	☐ 承认 Approved ☐ 条件承认 Condition approved ☐ 临时承认 Temporary approved	☐ 拒绝承认 Reject 需满足条件:_____ 限量_____PCS 采购		
审批 Approval by	研发总工（技术总监）： RD Leader(Technology Director)	质量总监： Quality Director		
分发部门 Distribute	☐ IQC	☐ 采购（供应商）	☐ 样品管理/文控	☐ 外协厂 ☐ 其它

Content

1	Content.....	2
2	Instructions.....	3
3	Product specifications.....	3
4	Mechanical properties test.....	4
5	Reliability test.....	5
6	VSWR test.....	6
7	Engineering drawings.....	7
8	Packing method.....	8

2 说明instructions

这份报告包含天线电性能测试的若干设备、测试环境和测试结果，以及天线的结构图纸和检验报告. 以下为天线图片。

This report includes several equipment, test environment and test results for the electrical performance of the antenna, as well as structural drawings and inspection reports of the antenna.Below is a picture of the antenna。



3 产品技术指标 Product specifications

电性能指标 Electrical Specifications	
频率范围 Frequency Range (MHz)	136-174+GPS1575
增益 Gain (dBi)	1.5
电压驻波比 VSWR	V段3.5 GPS 3.0
输入阻抗 Input Impedance (Ω)	50
极化方式 Polarization	垂直
最大功率 Maximum input power (W)	10
接头型号 Input connector type	SMA-J
天线类型 ANT TYPE	螺旋天线
机械指标 Mechanical Specifications	
尺寸 Dimensions (mm)	209.5*16.4
重量 Antenna weight (kg)	25g
颜色 Antenna color	黑色

4 机械性能测试 Mechanical properties test

1	摇摆测试 BENDING TEST	放离接头 30CM 的线端上荷重 120g, 固定接头后进行遥摆测试, 遥摆角度左右各 60 度, 遥摆 1000 次后测试特性. The load on the wire end 30cm away from the connector is 120g. After fixing the connector, carry out the remote swing test, and the remote swing angle is on the left and right 60 degrees, Test the characteristics after 1000 remote swings	遥摆 1000 次后测试特性无任何现象显示电器性能之损坏. After 1000 times of remote swing, the test characteristics show no damage to the electrical performance
2	强度测试 STRENG TEST	一个 15 磅之静负荷施加放线端底部持续一分钟. A static load of 15 pounds is applied to the bottom of the paying off end for one minute	无任何现象显示机械及电器性能之损坏. There is no sign of damage to mechanical and electrical properties
3	拉力测试 PULLING FORCE	用拉力计接头及线材间进行拉力测试. Conduct tension test between joint and wire rod with tension meter	可承受拉力为5Kg 无任何现象显示电器性能之损坏. It can bear the tensile force of 5kg without any damage to the electrical performance
4	振动测试 VIBRATION TEST	以 1.10mm 和振幅和33.30Hz/sec 振动频率以 X 轴方向振动 120 分钟, Y轴方向振动 120 分钟, Z 轴方向振动 240 分钟. Vibrate in the x-axis direction for 120 minutes with an amplitude of 1.10mm and a vibration frequency of 33.30hz/sec, and vibrate in the y-axis direction 120 minutes, vibration in z-axis direction for 240 minutes	无任何现象显示电器性能之损坏. There is no sign of damage to the electrical performance


5 耐久性测试

1	盐雾试验 SAIT SPRAY TEST	盐水喷雾试验：依 GB1266-86 标准蒸馏水： 一次蒸馏PH6.5~7 喷雾量：1.4me80cm²/h 压缩空气压力： 1Kgf/ cm² 试验相对度：98° 温度：45° ~47° 压力温度：35° 测试时间：24hr Brine spray test: distilled water according to GB1266-86 standard: single distillationPH6.5~7 Spray volume: 1.4me80cm²/ H compressed air pressure: 1kgf / cm² Test Relativity: 98 ° Temperature: 45 ° ~ 47 ° Pressure temperature: 35 ° Test time: 24hr	所有规格变华 范围初始值 30% All characteristic range is 30% of the initial value
2	高温试验 HEAT TEST	在 85+2℃环境中放 96 小时，再放在正常环境中 30 分钟后进行测试 85+2℃ for 96 hours, after keep in normal condition for 30min the to test.	
3	中温试验 HUMIDITY TEST	在 40+2℃ 90-95%RH 环境中放 96 小时，再放在正常环境中 30 分钟后进行测试 40+2℃ 90-95%RH for 96hours, after keep in normal condition for 30min the to test.	
4	底温试验 COLD TEST	在-40+2℃ 环境中放 96 小时，再置放正常环境中 30 分钟后进行测试 -40+2℃ for 96hours, after keep in normal condition for 30min the to test.	

6 驻波测试 VSWR Test



7工程图纸 Engineering drawings



8 包装方式 **Packing method**

Inside:


PE bag packaging, 100pcs / bag



PE bag size: 50*240

External :

carton packaging, 30 bags / box



carton packaging size 330*270*220



深圳市锦鸿无线科技有限公司

产品规格书Product Specification

产品描述 Part Description	客户：科立讯 Vendor: 产品名称：V段150-174M Product Name: 物料代码： Part NO:	规格型号：JHKLX2505-127-B Description: 所承认项目：TP35 Project: 版本：A1 Version:		
附件 Attachments	☒ 规格书 Spec ☒ CPK 报告 Cpk Report ☐ 制造流程图 QC Flow Chart ☒ 包装方式 Packing Content	☒ 工程图面 Drawing ☒ 关键尺寸报告 FAI Report ☐ 成型条件 Molding conditions C3C 证书 3C Certificate	☒ 样品 Sample ☒ 可靠性测试报告 Reliability Report ☒ 材质证明书 Material Verification Sheet ☒ 物料检验标准 Material inspection standard	☒ ROHS 报告 ROHS Repot ☐ 安规报告 Safety Report
供应商签核 Vendor	拟制：胥万芳 Design:	审核：郑翠兰 Check:	批准：彭发辉 Approval:	
技术确认 Technology check	结构意见/签名： Mechanical 工业/包材设计意见/签名： ID 品质意见/签名： DQE/SQE	硬件意见/签名： Hardware 项目意见/签名： Market		
最终确认 Final check	质量策划： Quality planning	ROHS: ☐ Rohs 物料 ☐ 非 Rohs 物料		
承认条件 Approval condition	☐ 承认 Approved ☐ 条件承认 Condition approved ☐ 临时承认 Temporary approved	☐ 拒绝承认 Reject 需满足条件: _____ 限量 _____ PCS 采购		
审批 Approval by	研发总工（技术总监）： RD Leader(Technology Director)	质量总监： Quality Director		
分发部门 Distribute	☐ IQC	☐ 采购（供应商）	☐ 样品管理/文控	☐ 外协厂 ☐ 其它

Content

1	Content.....	2
2	Instructions.....	3
3	Product specifications.....	3
4	Mechanical properties test.....	4
5	Reliability test.....	5
6	VSWR test.....	6
7	Engineering drawings.....	7
8	Packing method.....	8

2 说明instructions

这份报告包含天线电性能测试的若干设备、测试环境和测试结果，以及天线的结构图纸和检验报告. 以下为天线图片。

This report includes several equipment, test environment and test results for the electrical performance of the antenna, as well as structural drawings and inspection reports of the antenna.Below is a picture of the antenna。



3 产品技术指标 Product specifications

电性能指标 Electrical Specifications	
频率范围 Frequency Range（MHz）	150-174M+GPS1575M
增益 Gain（dBi）	1.2
电压驻波比 VSWR	≤3.5
输入阻抗 Input Impedance（Ω）	50
极化方式 Polarization	垂直
最大功率 Maximum input power（W）	10
天线形式	棒状螺旋天线
接头型号 Input connector type	SMA-J
机械指标 Mechanical Specifications	
尺寸 Dimensions（mm）	171.5*16.4
重量 Antenna weight（kg）	25g
颜色 Antenna color	黑色

4 机械性能测试 Mechanical properties test

1	摇摆测试 BENDING TEST	放离接头 30CM 的线端上荷重 120g, 固定接头后进行遥摆测试, 遥摆角度左右各 60 度, 遥摆 1000 次后测试特性. The load on the wire end 30cm away from the connector is 120g. After fixing the connector, carry out the remote swing test, and the remote swing angle is on the left and right 60 degrees, Test the characteristics after 1000 remote swings	遥摆 1000 次后测试特性无任何现象显示电器性能之损坏. After 1000 times of remote swing, the test characteristics show no damage to the electrical performance
2	强度测试 STRENG TEST	一个 15 磅之静负荷施加放线端底部持续一分钟. A static load of 15 pounds is applied to the bottom of the paying off end for one minute	无任何现象显示机械及电器性能之损坏. There is no sign of damage to mechanical and electrical properties
3	拉力测试 PULLING FORCE	用拉力计接头及线材间进行拉力测试. Conduct tension test between joint and wire rod with tension meter	可承受拉力为5Kg 无任何现象显示电器性能之损坏. It can bear the tensile force of 5kg without any damage to the electrical performance
4	振动测试 VIBRATION TEST	以 1.10mm 和振幅和33.30Hz/sec 振动频率以 X 轴方向振动 120 分钟, Y轴方向振动 120 分钟, Z 轴方向振动 240 分钟. Vibrate in the x-axis direction for 120 minutes with an amplitude of 1.10mm and a vibration frequency of 33.30hz/sec, and vibrate in the y-axis direction 120 minutes, vibration in z-axis direction for 240 minutes	无任何现象显示电器性能之损坏. There is no sign of damage to the electrical performance

5 耐久性测试


1	盐雾试验 SAIT SPRAY TEST	盐水喷雾试验：依 GB1266-86 标准蒸馏水： 一次蒸馏PH6.5~7 喷雾量：1.4me80cm²/h 压缩空气压力： 1Kgf/ cm² 试验相对度：98° 温度：45° ~47° 压力温度：35° 测试时间：24hr Brine spray test: distilled water according to GB1266-86 standard: single distillationPH6.5~7 Spray volume: 1.4me80cm²/ H compressed air pressure: 1kgf / cm² Test Relativity: 98 ° Temperature: 45 ° ~ 47 ° Pressure temperature: 35 ° Test time: 24hr	所有规格变华 范围初始值 30% All characteristic range is 30% of the initial value
2	高温试验 HEAT TEST	在 85+2℃环境中放 96 小时，再放在正常环境中 30 分钟后进行测试 85+2℃ for 96 hours, after keep in normal condition for 30min the to test.	
3	中温试验 HUMIDITY TEST	在 40+2℃ 90-95%RH 环境中放 96 小时，再放在正常环境中 30 分钟后进行测试 40+2℃ 90-95%RH for 96hours, after keep in normal condition for 30min the to test.	
4	底温试验 COLD TEST	在-40+2℃ 环境中放 96 小时，再置放正常环境中 30 分钟后进行测试 -40+2℃ for 96hours, after keep in normal condition for 30min the to test.	

6 驻波测试 VSWR Test



7工程图纸 Engineering drawings

说明：天线内部导线为GPS天线辐射振子



8 包装方式 **Packing method**

Inside:


PE bag packaging, 100pcs / bag



PE bag size: 30*180

External :

carton packaging, 50 bags / box



carton packaging size 330*270*220