



243 Jubug-Ri, Yangji-Myeon, Yongin-Si, Gyeonggi-Do, Korea 449-822
 Tel: +82-31-323-6008 Fax: +82-31-323-6010
<http://www.ltalab.com>

Dates of Tests: October 18, 2016 ~ February 1, 2017
 Test Report S/N: LR500111702J
 Test Site : LTA CO., LTD.

CERTIFICATION OF COMPLIANCE

FCC ID.
 IC Application
 APPLICANT

CCECDL-3PBR
22254-CDL3PBR
COMMAX Co., Ltd.

Equipment Class	:	Digital Transmission System (DTS)
Manufacturing Description	:	DIGITAL DOOR LOCK
Manufacturer	:	COMMAX Co., Ltd.
Model name	:	CDL-3PBR
Test Device Serial No.:	:	Identical prototype
Rule Part(s)	:	FCC Part 15.247 Subpart C ; ANSI C-63.4-2014 RSS-247 and Issue No.2 DATE : 2017
Frequency Range	:	2405 ~ 2480 MHz (Zigbee) 2402 ~ 2480 MHz (Bluetooth)
Max. Output Power	:	Max 21.32 dBm – Conducted (Zigbee) Max 4.74 dBm – Conducted (Bluetooth)
Data of issue	:	February 1, 2017

This test report is issued under the authority of:

The test was supervised by:

Yong-Cheol, Wang / Manager

Hee-Cheon, Kwon / Test Engineer

This test result only responds to the tested sample. It is not allowed to copy this report even partly without the allowance of the test laboratory. The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.



NVLAP LAB Code.: 200723-0

TABLE OF CONTENTS

1. GENERAL INFORMATION	3
2. INFORMATION ABOUT TEST ITEM	4
3. TEST REPORT	5
3.1 SUMMARY OF TESTS	5
3.2 TECHNICAL CHARACTERISTICS TEST	6
3.2.1 6 dB BANDWIDTH&99% Bandwidth	6
3.2.2 PEAK OUTPUT POWER	13
3.2.3 POWER SPECTRAL DENSITY	17
3.2.4 BAND EDGE	21
3.2.5 CONDUCTED SPURIOUS EMISSIONS	25
3.2.6 RADIATED SPURIOUS EMISSIONS	29
 APPENDIX	
APPENDIX TEST EQUIPMENT USED FOR TESTS	51

1. General information

1-1 Test Performed

Company name : LTA Co., Ltd.
 Address : 243, Jubug-ri, Yangji-Myeon, Youngin-Si, Kyunggi-Do, Korea. 449-822
 Web site : <http://www.ltalab.com>
 E-mail : chahn@ltalab.com
 Telephone : +82-31-323-6008
 Facsimile : +82-31-323-6010

Quality control in the testing laboratory is implemented as per ISO/IEC 17025 which is the “General requirements for the competents of calibration and testing laboratory”.

1-2 Accredited agencies

LTA Co., Ltd. is approved to perform EMC testing by the following agencies:

Agency	Country	Accreditation No.	Validity	Reference
NVLAP	U.S.A	200723-0	2017-09-30	ECT accredited Lab.
RRA	KOREA	KR0049	-	EMC accredited Lab.
FCC	U.S.A	610755	2017-04-21	FCC filing
FCC	U.S.A	649054	2017-04-13	FCC CAB
VCCI	JAPAN	R2133(10 m), C2307	2017-06-21	VCCI registration
VCCI	JAPAN	T-2009	2017-12-23	VCCI registration
VCCI	JAPAN	G-563	2018-12-13	VCCI registration
IC	CANADA	5799A-1	2019-11-07	IC filing
KOLAS	KOREA	NO.551	2017-01-08	KOLAS accredited Lab.

2-1 Client & Manufacturer

3. Test Report

3.1 Summary of tests

FCC Part Section(s)	Parameter	Limit	Test Condition	Status (note 1)
15.247(a)	6 dB Bandwidth & 99 % Bandwidth	> 500 kHz	Conducted	C
15.247(b)	Transmitter Peak Output Power	< 1 Watt		C
15.247(d)	Transmitter Power Spectral Density	< 8 dBm @ 3 kHz		C
15.247(d)	Band Edge	> 20 dBc		C
15.209	Field Strength of Harmonics	Emission	Radiated	C
15.207	AC Conducted Emissions	Emissions	Conducted	NA
15.203	Antenna requirement	-	-	C

Note 1: C=Complies NC=Not Complies NT=Not Tested NA=Not Applicable

Note 2: The data in this test report are traceable to the national or international standards.

→ Antenna Requirement

The COMMAX Co., Ltd. FCC ID: CCECDL-3PBR unit complies with the requirement of §15.203.

The antenna type is Pattern Antenna.

The sample was tested according to the following specification:

- *FCC Parts 15.247; ANSI C-63.4-2014
- *FCC KDB Publication No. 558074 D01 v03r05
- *FCC TCB Workshop 2012, April
- *RSS-247 and Issue No.2 Date:2017

3.2 Technical Characteristics Test

3.2.1 6 dB Bandwidth & 99 % Bandwidth

Procedure:

The bandwidth at 6 dB below the highest in-band spectral density was measured with a spectrum analyzer connected to the antenna terminal, while EUT is operating in transmission mode at the appropriate frequencies.

After the trace being stable, Use the marker-to-peak function to set the marker to the peak of the emission. Use the marker-delta function to measure 6 dB down one side of the emission. Reset the marker-delta function, and move the marker to the other side of the emission, until it is (as close as possible to) even with the reference marker level. The marker-delta reading at this point is the 6 dB bandwidth of the emission.

The spectrum analyzer is set to:

Center frequency = the highest, middle and the lowest channels

RBW = 100 kHz

Span = 5 MHz

VBW = 100 kHz (VBW $\geq$ RBW)

Sweep = auto

Trace = max hold

Detector function = peak

Measurement Data : **Complies**

Frequency (MHz)	Test Results	
	Measured Bandwidth (MHz)	99 % Bandwidth (MHz)
Zigbee		
2405	1.58	2.07
2440	1.59	2.10
2480	1.61	2.10
Bluetooth		
2402	0.774	1.15
2442	0.767	1.16
2480	0.767	1.17

- See next pages for actual measured spectrum plots.

Minimum Standard:

6 dB Bandwidth > 500 kHz

Measurement Setup






Figure 1: Measurement setup for the carrier frequency separation


Low Channel (Zigbee)




99% Bandwidth




Middle Channel (Zigbee)




99% Bandwidth




High Channel (Zigbee)




99% Bandwidth




Low Channel (Bluetooth)




99% Bandwidth




Middle Channel (Bluetooth)




99% Bandwidth



High Channel (Bluetooth)



99% Bandwidth



3.2.2 Peak Output Power Measurement

Procedure:

The maximum peak output power was measured with the spectrum analyzer connected to the antenna output of the EUT. The spectrum analyzer's internal channel power integration function is used to integrate the power over a bandwidth greater than or equal to the 99 % bandwidth. The EUT was operating in transmit mode at the appropriate center frequency.

The spectrum analyzer is set to:

Center frequency = the highest, middle and the lowest channels

RBW = 1 MHz

Span = auto

VBW = 1 MHz (VBW $\geq$ RBW)

Sweep = auto

Detector function = peak

Measurement Data : **Complies**

Frequency (MHz)	Test Results		
	dBm	mW	Result
Zigbee			
2405	20.46	111.17	Complies
2440	21.03	126.77	Complies
2480	21.32	135.52	Complies
Bluetooth			
2402	4.68	2.94	Complies
2442	4.60	2.88	Complies
2480	4.74	2.98	Complies

- See next pages for actual measured spectrum plots.


Minimum Standard:

Peak output power	< 1 W
-------------------	-------


Measurement Setup

Same as the Chapter 3.2.1 (Figure 1)


Low Channel (Zigbee)




Middle Channel (Zigbee)




High Channel (Zigbee)




Low Channel (Bluetooth)



Middle Channel (Bluetooth)



High Channel (Bluetooth)



3.2.3 Power Spectral Density

Procedure:

The peak power density is measured with a spectrum analyzer connected to the antenna terminal while the EUT is operating in transmission mode at the appropriate frequencies.

The spectrum analyzer is set to:

RBW = 3 kHz

Span = 300 kHz

VBW = 3 kHz

Sweep = auto

Detector function = peak

Trace = max hold

Measurement Data : **Complies**

Frequency (MHz)	Test Results	
	dBm / 3 kHz	Result
Zigbee		
2405	3.25	Complies
2440	4.01	Complies
2480	4.19	Complies
Bluetooth		
2402	-8.06	Complies
2442	-8.27	Complies
2480	-8.50	Complies

- See next pages for actual measured spectrum plots.


Minimum Standard:

Power Spectral Density	< 8 dBm @ 3 kHz BW
------------------------	--------------------


Measurement Setup

Same as the Chapter 3.2.1 (Figure 1)


Power Density Measurement Low Channel (Zigbee)




Middle Channel (Zigbee)




High Channel (Zigbee)




Low Channel (Bluetooth)



Middle Channel (Bluetooth)



High Channel (Bluetooth)



3.2.4 Band Edge

Procedure:

The bandwidth at 20 dB down from the highest inband spectral density is measured with a spectrum analyzer connected to the antenna terminal, while EUT is operating in transmission mode at the appropriate frequencies.

After the trace being stable, Use the marker-to-peak function to measure 20 dB down both sides of the intentional emission.

The spectrum analyzer is set to:

Center frequency = the highest, middle and the lowest channels

RBW = 100 kHz

VBW = 100 kHz

Span = 40 MHz

Detector function = peak

Trace = max hold

Sweep = auto

Radiated emissions which fall in the restricted bands, as defined in 15.205(a), must also comply with the radiated emission limits specified in 15.209(a)

The spectrum analyzer is set to:

Center frequency = the highest, the lowest channels

PEAK:

RBW = VBW = 1 MHz, Sweep=Auto

Average:

RBW = 1 MHz, VBW=10 Hz, Sweep=Auto

Measurement Distance:

3 m

Polarization:


Horizontal / Vertical

Measurement Data: Complies


- All conducted emission in any 100 kHz bandwidth outside of the spread spectrum band was at least 20 dB lower than the highest inband spectral density. Therefore the applying equipment meets the requirement.
- See next pages for actual measured spectrum plots.

Minimum Standard:	> 20 dBc
--------------------------	----------


Band edge Lower edge (Zigbee)




Upper edge (Zigbee)



Lower edge (Bluetooth)



Upper edge (Bluetooth)



Radiated Band-edges in the restricted band 2310-2390 MHz measurement_Zigbee

Frequency [MHz]	Reading [dBuV/ m]		Pol.	Correction Factor		Limits [dBuV/ m]		Result [dBuV/ m]		Margin [dB]	
	AV / Peak			Antenna	Amp. Gain + Cable Loss	AV / Peak	AV / Peak	AV / Peak	AV / Peak		
2390.0	35.2	58.2	H	27.9	22.9	54.0	74.0	40.2	63.2	13.8	10.8

Radiated Band-edges in the restricted band 2483.5-2500 MHz measurement_Zigbee

Frequency [MHz]	Reading [dBuV/ m]		Pol.	Correction Factor		Limits [dBuV/ m]		Result [dBuV/ m]		Margin [dB]	
	AV / Peak			Antenna	Amp. Gain + Cable Loss	AV / Peak		AV / Peak		AV / Peak	
2483.5	34.9	57.4	H	27.9	22.9	54.0	74.0	39.9	62.4	13.1	11.6

Note : This EUT was tested in 3 orthogonal positions and the worst-case data was presented

Radiated Band-edges in the restricted band 2310-2390 MHz measurement_Bluetooth

Frequency [MHz]	Reading [dBuV/ m]		Pol.	Correction Factor		Limits [dBuV/ m]		Result [dBuV/ m]		Margin [dB]	
	AV / Peak			Antenna	Amp. Gain + Cable Loss	AV / Peak	AV / Peak	AV / Peak	AV / Peak		
2390.0	29.8	38.2	H	27.9	22.9	54.0	74.0	34.8	43.2	19.2	33.8

Radiated Band-edges in the restricted band 2483.5-2500 MHz measurement_ Bluetooth

Frequency [MHz]	Reading [dBuV/ m]		Pol.	Correction Factor		Limits [dBuV/ m]		Result [dBuV/ m]		Margin [dB]	
	AV / Peak			Antenna	Amp. Gain + Cable Loss	AV / Peak	AV / Peak	AV / Peak			
2483.5	33.7	39.8	H	27.9	22.9	54.0	74.0	38.7	44.8	15.3	29.2

Note : This EUT was tested in 3 orthogonal positions and the worst-case data was presented

3.2.5 Conducted Spurious Emissions

Procedure:

The test follows KDB558074. The conducted spurious emissions were measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function disabled at the highest, middle and the lowest available channels..

After the trace being stable, set the marker on the peak of any spurious emission recorded.

The spectrum analyzer is set to:

Span = wide enough to capture the peak level of the in-band emission and all spurious emissions

RBW = 100 kHz

Sweep = auto

VBW = 100 kHz

Detector function = peak

Trace = max hold



Measurement Data: **Complies**



- All conducted emission in any 100 kHz bandwidth outside of the spread spectrum band was at least 20 dB lower than the highest inband spectral density. Therefore the applying equipment meets the requirement.
- See next pages for actual measured spectrum plots.



Minimum Standard:	> 20 dBc
--------------------------	----------

Measurement Setup

Same as the Chapter 3.2.1 (Figure 1)

Unwanted Emission – Low Channel (Zigbee)**Frequency Range = 30 MHz ~ 26.5 GHz****Unwanted Emission – Middle Channel (Zigbee)****Frequency Range = 30 MHz ~ 26.5 GHz**

Unwanted Emission – High Channel (Zigbee)**Frequency Range = 30 MHz ~ 26.5 GHz****Unwanted Emission – Low Channel (Bluetooth)****Frequency Range = 30 MHz ~ 26.5 GHz**

Unwanted Emission – Middle Channel (Bluetooth)**Frequency Range = 30 MHz ~ 26.5 GHz****Unwanted Emission – High Channel (Bluetooth)****Frequency Range = 30 MHz ~ 26.5 GHz**

3.2.6 Radiated Spurious Emissions

Procedure:

The EUT was placed on a 0.8m high wooden table inside a shielded enclosure. An antenna was placed near the EUT and measurements of frequencies and amplitudes of field strengths were recorded for reference during final measurements. For final radiated testing, measurements were performed in OATS. Measurements were performed with the EUT oriented in 3 orthogonal axis and rotated 360 degrees to determine worst-case orientation for maximum emissions.

The spectrum analyzer is set to:

Center frequency = the worst channel

Frequency Range = 9 kHz ~ 10th harmonic.

RBW = 100 kHz (30 MHz ~ 1 GHz)

= 1 MHz (1 GHz ~ 10th harmonic)

Span = 100 MHz


Trace = max hold

VBW $\geq$ RBW


Detector function = peak

Sweep = auto


below 30 MHz



below 1 GHz (30 MHz to 1 GHz)



above 1 GHz



Measurement Data: Complies

- See next pages for actual measured data.
- No other emissions were detected at a level greater than 20 dB below limit include from 9 kHz to 30 MHz.

Minimum Standard: FCC Part 15.209(a)

Frequency (MHz)	Limit (uV/m) @ 3 m
0.009 ~ 0.490	2400/F(kHz) (@ 300 m)
0.490 ~ 1.705	24000/F(kHz) (@ 30 m)
1.705 ~ 30	30(@ 30 m)
30 ~ 88	100 **
88 ~ 216	150 **
216 ~ 960	200 **
Above 960	500

** Except as provided in 15.209(g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g. 15.231 and 15.241.

Measurement Data : (Above 1 GHz) - Zigbee

Frequency [MHz]	Reading [dBuV/ m]		Pol.	Correction Factor		Limits [dBuV/ m]		Result [dBuV/ m]		Margin [dB]	
	AV / Peak			Antenna	Amp.Gain+ Cable	AV/ Peak		AV/ Peak		AV / Peak	
7599.7	15.96	25.96	H	37.08	4.42	54.0	74.0	48.62	58.62	5.38	15.38
7614.8	17.68	27.68	H	37.04	4.68	54.0	74.0	50.04	60.04	3.96	13.96
7311.6	18.13	28.13	H	36.87	6.25	54.0	74.0	48.75	58.75	5.25	15.25

- No other emissions were detected at a level greater than 20 dB below limit.

Measurement Data : (9 kHz – 30 MHz)

Frequency [MHz]	Reading [dBuV/ m]		Pol.	Correction Factor		Limits [dBuV/ m]		Result [dBuV/ m]		Margin [dB]	
	AV / Peak			Antenna	Amp.Gain+ Cable	AV / Peak		AV / Peak		AV / Peak	
-	-	-	-	-	-	-	-	-	-	-	-
No emissions were detected at a level greater than 20 dB below limit.											
-	-	-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-	-

*No emissions were detected at a level greater than 20 dB below limit.

Measurement Data : (Above 1 GHz) – Bluetooth

Frequency [MHz]	Reading [dBuV/ m]		Pol.	Correction Factor		Limits [dBuV/ m]		Result [dBuV/ m]		Margin [dB]	
	AV / Peak			Antenna	Amp.Gain+ Cable	AV/ Peak		AV/ Peak		AV / Peak	
7514.7	17.29	27.29	H	37.18	3.64	54.0	74.0	50.83	60.83	3.17	13.17
7541.1	15.37	27.77	H	37.13	3.90	54.0	74.0	48.60	61.00	5.40	13.00
7845.2	20.18	30.18	H	36.75	7.01	54.0	74.0	49.92	59.92	4.08	14.08

- No other emissions were detected at a level greater than 20 dB below limit.

Measurement Data : (9 kHz – 30 MHz)

Frequency [MHz]	Reading [dBuV/ m]		Pol.	Correction Factor		Limits [dBuV/ m]		Result [dBuV/ m]		Margin [dB]	
	AV / Peak			Antenna	Amp.Gain+ Cable	AV / Peak		AV / Peak		AV / Peak	
-	-	-	-	-	-	-	-	-	-	-	-
No emissions were detected at a level greater than 20 dB below limit.											
-	-	-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-	-

*No emissions were detected at a level greater than 20 dB below limit.

Radiated Emissions (Below 1 GHz) – 2.4GHz Zigbee mode (LOW)

4, Songjuro236Beon-gil, Yangji-myeon,
Cheoin-gu, Youngin-si, Gyeonggi-do,
449-822 Korea
Tel :+82-31-3236008,9
Fax:+82-31-3236010

EUT/Model No.: CDL-3PBR

TEST MODE: Zig low mode


Temp Humi : 0 / 50

Tested by: BANG Y H

Data: 271

Level (dBuV/m)

Date: 2016-12-28



	Freq	Reading	C.F	Result	Limit	Margin	Height	Angle	Polarity
	MHz	dBuV	dB	dBuV/m	QP dBuV/m	dB	cm	deg	
1	37.45	43.30	-18.40	24.90	40.00	15.10	100	51	VERTICAL
2	168.40	40.50	-15.58	24.92	43.50	18.58	100	33	VERTICAL
3	191.40	41.80	-17.19	24.61	43.50	18.89	100	62	VERTICAL
4	217.40	40.50	-16.83	23.67	46.00	22.33	100	88	VERTICAL
5	241.80	40.50	-15.67	24.83	46.00	21.17	100	321	VERTICAL
6	265.40	38.90	-14.69	24.21	46.00	21.79	100	15	VERTICAL

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain

Radiated Emissions (Below 1 GHz) – 2.4GHz Zigbee mode (MID)

4, Songjuro236Beon-gil, Yangji-myeon,
Cheoin-gu, Youngin-si, Gyeonggi-do,
449-822 Korea
Tel :+82-31-3236008,9
Fax:+82-31-3236010

EUT/Model No.: CDL-3PBR

TEST MODE: Zig middle mode


Temp Humi : 0 / 50

Tested by: BANG Y H

Data: 272

Level (dBuV/m)

Date: 2016-12-28



	Freq	Reading	C.F	Result	Limit	Margin	Height	Angle	Polarity
	MHz	dBuV	dB	dBuV/m	QP dBuV/m	dB	cm	deg	
1	37.40	41.50	-18.40	23.10	40.00	16.90	100	84	VERTICAL
2	61.40	41.40	-17.09	24.31	40.00	15.69	100	46	VERTICAL
3	86.10	44.80	-21.48	23.32	40.00	16.68	100	331	VERTICAL
4	168.40	35.80	-15.58	20.22	43.50	23.28	100	154	VERTICAL
5	187.40	40.60	-16.92	23.68	43.50	19.82	218	48	HORIZONTAL
6	277.40	38.90	-14.24	24.66	46.00	21.34	311	87	HORIZONTAL

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain

Radiated Emissions (Below 1 GHz) – 2.4GHz Zigbee mode (HIGH)

4, Songjuro236Beon-gil, Yangji-myeon,
Cheoin-gu, Youngin-si, Gyeonggi-do,
449-822 Korea
Tel :+82-31-3236008,9
Fax:+82-31-3236010

EUT/Model No.: CDL-3PBR

TEST MODE: Zig high mode


Temp Humi : 0 / 50

Tested by: BANG Y H

Data: 273

Level (dBuV/m)

Date: 2016-12-28



	Freq	Reading	C.F	Result	Limit	Margin	Height	Angle	Polarity
	MHz	dBuV	dB	dBuV/m	QP	dB	cm	deg	
1	38.40	41.80	-18.29	23.51	40.00	16.49	100	84	VERTICAL
2	167.50	38.60	-15.51	23.09	43.50	20.41	100	155	VERTICAL
3	191.56	39.60	-17.20	22.40	43.50	21.10	100	12	VERTICAL
4	221.50	39.80	-16.63	23.17	46.00	22.83	100	55	VERTICAL
5	253.10	38.30	-15.17	23.13	46.00	22.87	100	214	VERTICAL
6	290.40	37.10	-13.78	23.32	46.00	22.68	100	121	VERTICAL

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain

Radiated Emissions (Above 1 GHz) – 2.4GHz Zigbee mode (LOW)

EMI Chamber of LTA CO.,LTD.
4, Songjuro236Beon-gil, Yangji-myeon,
Yongin-si, Gyeonggi-do, Korea Autho.by NVLAP
Tel :+82-31-3236008,9 www.ltalab.com
Fax:+82-31-3236010


EUT/Model No. : CDL-3PBR

Test Mode: Zig Low mode

Tested by : BANG Y H

Temp/Humi: 19 / 43

Data: 113 File: D:\LTA_e3\3_backup\1GHz 이상\2016\CH1_ABOVE 1GHz_1612-1.EMI (161)
Level (dBuV/m) Date: 2016-12-27 Time: 15:30:14



	Freq	Reading	C.F	Result	Limit	Margin	Polarity
	MHz	dBuV	dB	PK dBuV/m	dBuV/m	dB	
1	7164.54	33.80	23.04	56.84	74.00	17.16	HORIZONTAL
2	7164.54	23.80	23.04	46.84	54.00	7.16	HORIZONTAL
3	7314.15	32.90	24.67	57.57	74.00	16.43	HORIZONTAL
4	7314.15	22.90	24.67	47.57	54.00	6.43	HORIZONTAL
5	7516.45	31.80	26.62	58.42	74.00	15.58	HORIZONTAL
6	7516.45	21.80	26.62	48.42	54.00	5.58	HORIZONTAL
7	7599.65	32.40	26.22	58.62	74.00	15.38	HORIZONTAL
8	7599.65	22.40	26.22	48.62	54.00	5.38	HORIZONTAL
9	7629.65	31.90	26.07	57.97	74.00	16.03	HORIZONTAL
10	7629.65	21.90	26.07	47.97	54.00	6.03	HORIZONTAL

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain
Blue : Vertical Black : Horizontal



EMI Chamber of LTA CO.,LTD.
 4, Songjuro236Beon-gil, Yangji-myeon,
 Yongin-si, Gyeonggi-do, Korea Autho.by NVLAP
 Tel :+82-31-3236008,9 www.ltalab.com
 Fax:+82-31-3236010


EUT/Model No.: CDL-3PBR

Test Mode: Zig Low mode

Tested by : BANG Y H

Temp/Humi: 19 / 43

Data: 114 File: D:\LTA_e3\3_backup\1GHz 이상\2016\CH1_ABOVE 1GHz_1612-1.EMI (144)
 Level (dBuV/m) Date: 2016-12-27 Time: 15:33:06



Freq	Reading	C.F	Result	Limit	Margin	Polarity
MHz	dBuV	dB	PK dBuV/m	dBuV/m	dB	
118142.50	45.10	13.13	58.23	74.00	15.77	HORIZONTAL
218142.50	35.10	13.13	48.23	54.00	5.77	HORIZONTAL

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain
 Blue : Vertical Black : Horizontal

Radiated Emissions (Above 1 GHz) – 2.4GHz Zigbee mode (MID)

EMI Chamber of LTA CO.,LTD.
4, Songjuro236Beon-gil, Yangji-myeon,
Yongin-si, Gyeonggi-do, Korea Autho.by NVLAP
Tel :+82-31-3236008,9 www.ltalab.com
Fax:+82-31-3236010


EUT/Model No. : CDL-3PBR

Test Mode: Zig Middle mode

Tested by : BANG Y H

Temp/Humi: 19 / 43

Data: 115 File: D:\LTA_e3\3_backup\1GHz 이상\2016\CH1_ABOVE 1GHz_1612-1.EMI (144)
Level (dBuV/m) Date: 2016-12-27 Time: 15:43:31



	Freq	Reading	C.F	Result	Limit	Margin	Polarity
	MHz	dBuV	dB	PK dBuV/m	dBuV/m	dB	
1	7045.00	35.80	21.73	57.53	74.00	16.47	HORIZONTAL
2	7045.00	25.80	21.73	47.53	54.00	6.47	HORIZONTAL
3	7219.45	22.80	23.64	46.44	54.00	7.56	HORIZONTAL
4	7219.45	32.80	23.64	56.44	74.00	17.56	HORIZONTAL
5	7364.84	32.60	25.23	57.83	74.00	16.17	HORIZONTAL
6	7364.84	22.60	25.23	47.83	54.00	6.17	HORIZONTAL
7	7614.84	23.90	26.14	50.04	54.00	3.96	HORIZONTAL
8	7614.84	33.90	26.14	60.04	74.00	13.96	HORIZONTAL
9	7841.77	32.80	25.03	57.83	74.00	16.17	HORIZONTAL
10	7841.77	22.80	25.03	47.83	54.00	6.17	HORIZONTAL

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain
Blue : Vertical Black : Horizontal



EMI I Chamber of LTA CO.,LTD.
 4, Songjuro236Beon-gil, Yangji-myeon,
 Yongin-si, Gyeonggi-do, Korea Autho.by NVLAP
 Tel :+82-31-3236008,9 www.ltalab.com
 Fax:+82-31-3236010

EUT/Model No. : CDL-3PBR

Test Mode: Zig Middle mode

Tested by : BANG Y H

Temp/Humi: 19 / 43

Data: 116 File: D:\LTA_e3\3_backup\1GHz 이상\2016\CH1_ABOVE 1GHz_1612-1.EMI (116)
 Level (dBuV/m) Date: 2016-12-27 Time: 15:45:12



Freq	Reading	C.F	Result	Limit	Margin	Polarity
MHz	dBuV	dB	PK dBuV/m	dBuV/m	dB	
118166.40	41.50	13.15	54.65	74.00	19.35	HORIZONTAL
218166.40	31.50	13.15	44.65	54.00	9.35	HORIZONTAL

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain
 Blue : Vertical Black : Horizontal

Radiated Emissions (Above 1 GHz) – 2.4GHz Zigbee mode (HIGH)

EMI Chamber of LTA CO.,LTD.
4, Songjuro236Beon-gil, Yangji-myeon,
Yongin-si, Gyeonggi-do, Korea Autho.by NVLAP
Tel :+82-31-3236008,9 www.ltalab.com
Fax:+82-31-3236010


EUT/Model No. : CDL-3PBR

Test Mode: Zig High mode

Tested by : BANG Y H

Temp/Humi: 19 / 43

Data: 117 File: D:\LTA_e3\3_backup\1GHz 이상\2016\CH1_ABOVE 1GHz_1612-1.EMI (144)
Level (dBuV/m) Date: 2016-12-27 Time: 16:19:02



	Freq	Reading	C.F	Result	Limit	Margin	Polarity
	MHz	dBuV	dB	PK dBuV/m	dBuV/m	dB	
1	7065.40	33.80	21.96	55.76	74.00	18.24	HORIZONTAL
2	7065.40	23.80	21.96	45.76	54.00	8.24	HORIZONTAL
3	7114.45	33.10	22.49	55.59	74.00	18.41	HORIZONTAL
4	7114.45	23.10	22.49	45.59	54.00	8.41	HORIZONTAL
5	7261.15	33.90	24.09	57.99	74.00	16.01	HORIZONTAL
6	7261.15	22.90	24.09	46.99	54.00	7.01	HORIZONTAL
7	7311.56	34.10	24.65	58.75	74.00	15.25	HORIZONTAL
8	7311.56	24.10	24.65	48.75	54.00	5.25	HORIZONTAL
9	7416.54	32.80	25.79	58.59	74.00	15.41	HORIZONTAL
10	7416.54	22.80	25.79	48.59	54.00	5.41	HORIZONTAL

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain
Blue : Vertical Black : Horizontal



EMI Chamber of LTA CO.,LTD.
 4, Songjuro236Beon-gil, Yangji-myeon,
 Yongin-si, Gyeonggi-do, Korea Autho.by NVLAP
 Tel :+82-31-3236008,9 www.ltalab.com
 Fax:+82-31-3236010


EUT/Model No. : CDL-3PBR

Test Mode: Zig High mode

Tested by : BANG Y H

Temp/Humi: 19 / 43

Data: 118 File: D:\LTA_e3\3_backup\1GHz 이상\2016\CH1_ABOVE 1GHz_1612-1.EMI (118)
 Level (dBuV/m) Date: 2016-12-27 Time: 16:22:42



Freq	Reading	C.F	Result	Limit	Margin	Polarity
MHz	dBuV	dB	PK dBuV/m	dBuV/m	dB	
118147.40	38.60	13.14	51.74	74.00	22.26	HORIZONTAL
218147.40	28.60	13.14	41.74	54.00	12.26	HORIZONTAL

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain
 Blue : Vertical Black : Horizontal

Radiated Emissions (Below 1 GHz) – 2.4GHz Bluetooth mode (LOW)

4, Songjuro236Beon-gil, Yangji-myeon,
Cheoin-gu, Youngin-si, Gyeonggi-do,
449-822 Korea
Tel :+82-31-3236008,9
Fax:+82-31-3236010

EUT/Model No.: CDL-3PBR

TEST MODE: BLE LOW mode


Temp Humi : 0 / 50

Tested by: BANG Y H

Data: 268

Level (dBuV/m)

Date: 2016-12-28



	Freq	Reading	C.F	Result	Limit	Margin	Height	Angle	Polarity
	MHz	dBuV	dB	dBuV/m	QP dBuV/m	dB	cm	deg	
1	34.65	40.80	-18.72	22.08	40.00	17.92	100	54	VERTICAL
2	840.10	35.60	-0.13	35.47	46.00	10.53	317	98	HORIZONTAL
3	880.60	38.40	0.68	39.08	46.00	6.92	211	78	HORIZONTAL
4	900.10	37.40	1.07	38.47	46.00	7.53	315	147	HORIZONTAL
5	922.60	31.40	1.52	32.92	46.00	13.08	157	41	HORIZONTAL
6	933.60	34.10	1.73	35.83	46.00	10.17	148	11	HORIZONTAL

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain

Radiated Emissions (Below 1 GHz) – 2.4GHz Bluetooth mode (MID)

4, Songjuro236Beon-gil, Yangji-myeon,
Cheoin-gu, Youngin-si, Gyeonggi-do,
449-822 Korea
Tel :+82-31-3236008,9
Fax:+82-31-3236010

EUT/Model No.: CDL-3PER

TEST MODE: BLE Middle mode


Temp Humi : 0 / 50

Tested by: BANG Y H

Data: 269

Level (dBuV/m)

Date: 2016-12-28



	Freq	Reading	C.F	Result	Limit	Margin	Height	Angle	Polarity
	MHz	dBuV	dB	dBuV/m	QP dBuV/m	dB	cm	deg	
1	35.80	42.10	-18.59	23.51	40.00	16.49	100	85	VERTICAL
2	755.10	34.80	-1.65	33.15	46.00	12.85	218	48	HORIZONTAL
3	767.80	36.10	-1.43	34.67	46.00	11.33	318	55	HORIZONTAL
4	801.40	35.80	-0.86	34.94	46.00	11.06	248	21	HORIZONTAL
5	816.40	34.20	-0.57	33.63	46.00	12.37	358	48	HORIZONTAL
6	919.60	31.50	1.46	32.96	46.00	13.04	252	11	HORIZONTAL

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain

Radiated Emissions (Below 1 GHz) – 2.4GHz Bluetooth mode (HIGH)

4, Songjuro236Beon-gil, Yangji-myeon,
Cheoin-gu, Youngin-si, Gyeonggi-do,
449-822 Korea
Tel :+82-31-3236008,9
Fax:+82-31-3236010

EUT/Model No.: CDL-3PBR

TEST MODE: BLE high mode


Temp Humi : 0 / 50

Tested by: BANG Y H

Data: 270

Level (dBuV/m)

Date: 2016-12-28



	Freq	Reading	C.F	Result	Limit	Margin	Height	Angle	Polarity
	MHz	dBuV	dB	dBuV/m	QP dBuV/m	dB	cm	deg	
1	37.50	45.40	-18.39	27.01	40.00	12.99	100	152	VERTICAL
2	81.40	42.90	-21.36	21.54	40.00	18.46	100	111	VERTICAL
3	788.40	34.60	-1.08	33.52	46.00	12.48	100	12	VERTICAL
4	852.10	33.80	0.10	33.90	46.00	12.10	218	48	HORIZONTAL
5	881.60	33.60	0.70	34.30	46.00	11.70	315	174	HORIZONTAL
6	905.40	32.20	1.18	33.38	46.00	12.62	400	84	HORIZONTAL

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain

Radiated Emissions (Above 1 GHz) – 2.4GHz Bluetooth mode (LOW)

EMI Chamber of LTA CO.,LTD.
 4, Songjuro236Beon-gil, Yangji-myeon,
 Yongin-si, Gyeonggi-do, Korea Autho.by NVLAP
 Tel :+82-31-3236008,9 www.ltalab.com
 Fax:+82-31-3236010


EUT/Model No.: CDL-3PBR

Test Mode: BLE LOW mode

Tested by : BANG Y H

Temp/Humi: 19 / 43

Data: 119 File: D:\LTA_e3\3_backup\1GHz 이상\2016\CH1_ABOVE 1GHz_1612-1.EMI (144)
 Level (dBuV/m) Date: 2016-12-27 Time: 16:24:09



	Freq	Reading	C.F	Result	Limit	Margin	Polarity
	MHz	dBuV	dB	PK dBuV/m	dBuV/m	dB	
1	7100.50	21.90	22.34	44.24	54.00	9.76	HORIZONTAL
2	7100.50	31.90	22.34	54.24	74.00	19.76	HORIZONTAL
3	7154.12	35.10	22.93	58.03	74.00	15.97	HORIZONTAL
4	7154.12	25.10	22.93	48.03	54.00	5.97	HORIZONTAL
5	7345.15	31.50	25.01	56.51	74.00	17.49	HORIZONTAL
6	7345.15	21.50	25.01	46.51	54.00	7.49	HORIZONTAL
7	7411.62	22.10	25.74	47.84	54.00	6.16	HORIZONTAL
8	7411.62	32.10	25.74	57.84	74.00	16.16	HORIZONTAL
9	7514.65	24.20	26.63	50.83	54.00	3.17	HORIZONTAL
10	7514.65	34.20	26.63	60.83	74.00	13.17	HORIZONTAL

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain
 Blue : Vertical Black : Horizontal



EMI Chamber of LTA CO.,LTD.
4, Songjuro236Beon-gil, Yangji-myeon,
Yongin-si, Gyeonggi-do, Korea Autho.by NVLAP
Tel :+82-31-3236008,9 www.ltalab.com
Fax:+82-31-3236010


EUT/Model No. : CDL-3PBR

Test Mode: BLE LOW mode

Tested by : BANG Y H

Temp/Humi: 19 / 43

Data: 120 File: D:\LTA_e3\Backup\1GHz 이상\2016\CH1_ABOVE 1GHz_1612-1.EMI (120)
Level (dBuV/m) Date: 2016-12-27 Time: 16:27:06



Freq	Reading	C.F	Result	Limit	Margin	Polarity
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
118133.60	40.20	13.13	53.33	74.00	20.67	HORIZONTAL
218133.60	30.20	13.13	43.33	54.00	10.67	HORIZONTAL

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain
Blue : Vertical Black : Horizontal

Radiated Emissions (Above 1 GHz) – 2.4GHz Bluetooth mode (MID)

EMI Chamber of LTA CO.,LTD.
4, Songjuro236Beon-gil, Yangji-myeon,
Yongin-si, Gyeonggi-do, Korea Autho.by NVLAP
Tel :+82-31-3236008,9 www.ltalab.com
Fax:+82-31-3236010


EUT/Model No. : CDL-3PBR

Test Mode: BLE MIDDLE mode

Tested by : BANG Y H

Temp/Humi: 19 / 43

Data: 121 File: D:\LTA_e3\3_backup\1GHz 이상\2016\CH1_ABOVE 1GHz_1612-1.EMI (144)
Level (dBuV/m) Date: 2016-12-27 Time: 16:28:17



	Freq	Reading	C.F	Result	Limit	Margin	Polarity
	MHz	dBuV	dB	PK dBuV/m	dBuV/m	dB	
1	7165.32	22.90	23.05	45.95	54.00	8.05	HORIZONTAL
2	7165.32	32.90	23.05	55.95	74.00	18.05	HORIZONTAL
3	7541.10	22.10	26.50	48.60	54.00	5.40	HORIZONTAL
4	7541.10	34.50	26.50	61.00	74.00	13.00	HORIZONTAL
5	7659.45	21.90	25.92	47.82	54.00	6.18	HORIZONTAL
6	7659.45	31.90	25.92	57.82	74.00	16.18	HORIZONTAL
7	7741.45	22.10	25.52	47.62	54.00	6.38	HORIZONTAL
8	7741.45	32.10	25.52	57.62	74.00	16.38	HORIZONTAL
9	7841.45	21.80	25.03	46.83	54.00	7.17	HORIZONTAL
10	7841.45	31.80	25.03	56.83	74.00	17.17	HORIZONTAL

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain
Blue : Vertical Black : Horizontal



EMI I Chamber of LTA CO.,LTD.
 4, Songjuro236Beon-gil, Yangji-myeon,
 Yongin-si, Gyeonggi-do, Korea Autho.by NVLAP
 Tel :+82-31-3236008,9 www.ltalab.com
 Fax:+82-31-3236010


EUT/Model No. : CDL-3PBR

Test Mode: BLE MIDDLE mode

Tested by : BANG Y H

Temp/Humi: 19 / 43

Data: 122 File: D:\LTA_e3\3_backup\1GHz 이상\2016\CH1_ABOVE 1GHz_1612-1.EMI (144)
 Level (dBuV/m) Date: 2016-12-27 Time: 16:31:23



Freq	Reading	C.F	Result	Limit	Margin	Polarity
MHz	dBuV	dB	PK dBuV/m	dBuV/m	dB	
118111.40	41.50	13.11	54.61	74.00	19.39	HORIZONTAL
218111.40	31.50	13.11	44.61	54.00	9.39	HORIZONTAL

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain
 Blue : Vertical Black : Horizontal

Radiated Emissions (Above 1 GHz) – 2.4GHz Bluetooth mode (HIGH)

EMI Chamber of LTA CO.,LTD.
4, Songjuro236Beon-gil, Yangji-myeon,
Yongin-si, Gyeonggi-do, Korea Autho.by NVLAP
Tel :+82-31-3236008,9 www.ltalab.com
Fax:+82-31-3236010


EUT/Model No. : CDL-3PBR

Test Mode: BLE HIGH mode

Tested by : BANG Y H

Temp/Humi: 19 / 43

Data: 123 File: D:\LTA_e3\3_backup\1GHz 이상\2016\CH1_ABOVE 1GHz_1612-1.EMI (144)
Level (dBuV/m) Date: 2016-12-27 Time: 16:33:21



	Freq	Reading	C.F	Result	Limit	Margin	Polarity
	MHz	dBuV	dB	PK dBuV/m	dBuV/m	dB	
1	7142.41	34.30	22.80	57.10	74.00	16.90	HORIZONTAL
2	7142.41	24.30	22.80	47.10	54.00	6.90	HORIZONTAL
3	7261.48	34.50	24.10	58.60	74.00	15.40	HORIZONTAL
4	7261.48	24.50	24.10	48.60	54.00	5.40	HORIZONTAL
5	7415.12	33.50	25.78	59.28	74.00	14.72	HORIZONTAL
6	7415.12	23.50	25.78	49.28	54.00	4.72	HORIZONTAL
7	7516.84	31.90	26.62	58.52	74.00	15.48	HORIZONTAL
8	7516.84	21.90	26.62	48.52	54.00	5.48	HORIZONTAL
9	7845.21	34.90	25.02	59.92	74.00	14.08	HORIZONTAL
10	7845.21	24.90	25.02	49.92	54.00	4.08	HORIZONTAL

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain
Blue : Vertical Black : Horizontal



EMI Chamber of LTA CO.,LTD.
 4, Songjuro236Beon-gil, Yangji-myeon,
 Yongin-si, Gyeonggi-do, Korea Autho.by NVLAP
 Tel :+82-31-3236008,9 www.ltalab.com
 Fax:+82-31-3236010


EUT/Model No. : CDL-3PBR

Test Mode: BLE HIGH mode

Tested by : BANG Y H

Temp/Humi: 19 / 43

Data: 124 File: D:\LTA_e3\3_backup\1GHz 이상\2016\CH1_ABOVE 1GHz_1612-1.EMI (144)
 Level (dBuV/m) Date: 2016-12-27 Time: 16:36:05



Freq	Reading	C.F	Result	Limit	Margin	Polarity
MHz	dBuV	dB	PK dBuV/m	dBuV/m	dB	
118136.45	41.60	13.13	54.73	74.00	19.27	HORIZONTAL
218136.45	31.60	13.13	44.73	54.00	9.27	HORIZONTAL

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain
 Blue : Vertical Black : Horizontal

APPENDIX

TEST EQUIPMENT USED FOR TESTS

	Description	Model No.	Serial No.	Manufacturer	Interval	Last Cal. Date
1	Signal Analyzer (9 kHz ~ 30 GHz)	FSV-30	100757	R&S	1 year	2016-03-22
2	Signal Generator (~3.2 GHz)	8648C	3623A02597	HP	1 year	2016-03-21
3	SYNTHESIZED CW GENERATOR	83711B	US34490456	HP	1 year	2016-03-21
4	Attenuator (3 dB)	8491A	37822	HP	1 year	2016-09-12
5	Attenuator (10 dB)	8491A	63196	HP	1 year	2016-09-12
6	Test Receiver (~30 MHz)	ESHS10	828404/009	R&S	1 year	2016-03-21
7	EMI Test Receiver (~7 GHz)	ESCI7	100722	R&S	1 year	2016-09-12
8	RF Amplifier (~1.3 GHz)	8447D OPT 010	2944A07684	HP	1 year	2016-09-12
9	RF Amplifier (1~26.5 GHz)	8449B	3008A02126	HP	1 year	2016-03-21
10	Horn Antenna (1~18 GHz)	3115	00114105	ETS	1 year	2016-04-21
11	DRG Horn (Small)	3116B	81109	ETS-Lindgren	1 year	2016-05-03
12	DRG Horn (Small)	3116B	133350	ETS-Lindgren	1 year	2016-05-03
13	TRILOG Antenna	VULB 9160	9160-3237	SCHWARZBECK	2 year	2015-04-21
14	Temp.Humidity Data Logger	SK-L200TH II A	00801	SATO	1 year	2016-03-22
15	Splitter (SMA)	ZFSC-2-2500	SF617800326	Mini-Circuits	-	-
16	Power Divider	11636A	06243	HP	1 year	2016-09-12
17	DC Power Supply	6674A	3637A01657	Agilent	-	-
18	Frequency Counter	5342A	2826A12411	HP	1 year	2016-03-21
19	Power Meter	EPM-441A	GB32481702	HP	1 year	2016-03-22
20	Power Sensor	8481A	3318A94972	HP	1 year	2016-12-31
21	Audio Analyzer	8903B	3729A18901	HP	1 year	2016-09-12
22	Modulation Analyzer	8901B	3749A05878	HP	1 year	2016-09-12
23	TEMP & HUMIDITY Chamber	YJ-500	LTAS06041	JinYoung Tech	1 year	2016-09-12
24	Stop Watch	HS-3	812Q08R	CASIO	2 year	2016-03-22
25	LISN	KNW-407	8-1430-1	Kyoritsu	1 year	2016-09-12
26	Two-Lime V-Network	ESH3-Z5	893045/017	R&S	1 year	2016-03-21
27	UNIVERSAL RADIO COMMUNICATION TESTER	CMU200	106243	R&S	1 year	2016-03-21
28	Highpass Filter	WHKX1.5/15G-10SS	74	Wainwright Instruments	1 year	2016-03-21
29	Highpass Filter	WHKX3.0/18G-10SS	118	Wainwright Instruments	1 year	2016-03-21
30	Active Loop Antenna	FMZB1519	1519-031	SCHWARZBECK	2 year	2016-01-12
31	OSP120 BASE UNIT	OSP120	101230	R&S	1 year	2016-03-22
32	Signal Generator(100 kHz ~ 40 GHz)	SMB100A03	177621	R&S	1 year	2016-03-22
33	Signal Analyzer (10 Hz ~ 40 GHz)	FSV40	101367	R&S	1 year	2016-03-22