



Compliance Testing, LLC

Previously Flom Test Lab

EMI, EMC, RF Testing Experts Since 1963

toll-free: (866) 311-3268

fax: (480) 926-3598

<http://www.ComplianceTesting.com>

info@ComplianceTesting.com

Test Report

Prepared for: Digital Monitoring Products Inc.

Model: 1115

Description: Water and Temperature Sensor

Serial Number: N/A

FCC ID: CCKPC0192

To

FCC Part 1.1310

Date of Issue: December 8, 2016

On the behalf of the applicant:

**Digital Monitoring Products Inc.
2500 North Partnership Blvd
Springfield, MO 65802**

Attention of:

**James Wilson
Ph: (417)831-9362
Email: jwilson@dmp.com**

**Prepared By
Compliance Testing, LLC
1724 S. Nevada Way
Mesa, AZ 85204
(480) 926-3100 phone / (480) 926-3598 fax
www.compliancetesting.com
Project No: p16a0004**

**Poona Saber
Project Test Engineer**

This report may not be reproduced, except in full, without written permission from Compliance Testing
All results contained herein relate only to the sample tested



Test Report Revision History

Revision	Date	Revised By	Reason for Revision
1.0	October 21, 2016	Poona Saber	Original Document
2.0	December 6, 2016	Poona Saber	Changed the units of power from dBm to mW
3.0	December 8, 2016	Poona Saber	Fixed the power density value



ILAC / A2LA

Compliance Testing, LLC, has been accredited in accordance with the recognized International Standard ISO/IEC 17025:2005. This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer joint ISO-ILAC-IAF Communiqué dated January 2009)

The tests results contained within this test report all fall within our scope of accreditation, unless below

Please refer to <http://www.compliancetesting.com/labscope.html> for current scope of accreditation.

Testing Certificate Number: **2152.01**



FCC Site Reg. #349717

IC Site Reg. #2044A-2

Non-accredited tests contained in this report:

N/A

EUT Description

Model: 1115

Description: Water and temperature sensor



Source Based Time Averaged Power Calculation

Average Power calculations

Average Power = Peak Power * duty-cycle%

Tuned Frequency (MHz)	Conducted Peak Output Power (mW)	Duty Cycle (%)	Average Power (mW)
905.6	12.1	100	12.1
915.02	13.7	100	13.7
924.39	15.52	100	15.52



MPE Evaluation

This is a portable device used in Uncontrolled Exposure environment.

Limits Uncontrolled Exposure 47 CFR 1.1310 Table 1, (B)

0.3-1.234 MHz:	Limit [mW/cm ²] = 100
1.34-30 MHz:	Limit [mW/cm ²] = (180/f ²)
30-300 MHz:	Limit [mW/cm ²] = 0.2
300-1500 MHz:	Limit [mW/cm ²] = f/1500
1500-100,000 MHz	Limit [mW/cm ²] = 1.0

Test Data

Test Frequency, MHz	924.39
Power, Conducted, mW (P)	15.52
Antenna Gain Isotropic	1 dBi
Antenna Gain Numeric (G)	1.25
Antenna Type	Internal
Distance (R)	20 cm

$S = \frac{P * G}{4\pi r^2}$
Power Density (S) mw/cm ²

Power Density (S) =0.00385
Limit =(from above table) = 0.61