

Test Method:	FCC Part 15 Subpart C Radiated Emissions Paragraph 15.249						
Customer:	Fisher Price			Job No.	R-8198-3A		
Test Sample:	906.6 Mhz Transmitter			FCC ID:	CCT1580T		
Model No.:	1580T			Serial No.	N/A		
Operating Mode:	Continuously Transmitter 906.6 Mhz Signal (Channel B)						
Technician:	Dennis Cortes			Date:	September 8, 1999		
Notes:	Test Distance: 3 Meters		Temp:23C	Humidity: 92%			
	Detector: Peak						
Test Freq.	Antenna Pol./Height	EUT Orientation	Meter Reading	Correction Factor	Corrected Reading	Converted Reading	Limit
Mhz	(V/H) / Meters	X / Y / Z	dBuv	dB	dBuV/m	uV/m	uV/m
906.6	H / 1.3	X	78.8	7.2	86.0	19952.6	50000
906.6	H / 1.1	Y	77.6	7.2	84.8	17378.0	50000
906.6	H / 1.0	Z	84.1	7.2	91.3	36728.2	50000
906.6	V / 1.0	X	85.5	7.2	92.7	43151.9	50000
906.6	V / 1.0	Y	85.2	7.2	92.4	41686.9	50000
906.6	V / 1.0	Z	81.4	7.2	88.6	26915.3	50000
1813.3	H / 1.0	X	51.1	-2.7	48.4	263.0	500
1813.3	H / 1.7	Y	51.7	-2.7	49.0	281.8	500
1813.3	H / 1.2	Z	53.7	-2.7	51.0	354.8	500
1813.3	V / 1.5	X	54.7	-2.7	52.0	398.1	500
1813.3	V / 1.4	Y	54.0	-2.7	51.3	367.3	500
1813.3	V / 1.0	Z	51.8	-2.7	49.1	285.1	500
2719.9	H / 1.0	X	41.9	-0.6	41.3	*116.1	500
2719.9	H / 1.0	Y	41.9	-0.6	41.3	*116.1	500
2719.9	H / 1.0	Z	41.9	-0.6	41.3	*116.1	500
2719.9	V / 1.0	X	41.9	-0.6	41.3	*116.1	500
2719.9	V / 1.0	Y	41.9	-0.6	41.3	*116.1	500
2719.9	V / 1.0	Z	41.9	-0.6	41.3	*116.1	500
3626.6	H / 1.0	X	41.0	7.2	48.2	*257.0	500
3626.6	H / 1.0	Y	41.0	7.2	48.2	*257.0	500
3626.6	H / 1.0	Z	41.0	7.2	48.2	*257.0	500
3626.6	V / 1.0	X	41.0	7.2	48.2	*257.0	500
3626.6	V / 1.0	Y	41.0	7.2	48.2	*257.0	500
3626.6	V / 1.0	Z	41.0	7.2	48.2	*257.0	500
4533.2	H / 1.0	X	42.3	2.7	45.0	*177.8	500
4533.2	H / 1.0	Y	42.3	2.7	45.0	*177.8	500
4533.2	H / 1.0	Z	42.3	2.7	45.0	*177.8	500
4533.2	V / 1.0	X	42.3	2.7	45.0	*177.8	500
4533.2	V / 1.0	Y	42.3	2.7	45.0	*177.8	500
4533.2	V / 1.0	Z	42.3	2.7	45.0	*177.8	500
	The frequency range was scanned from 30 Mhz to 9.2Ghz. All emissions not recorded were more						
	Than 10 dB below the specified limit. Emissions from the EUT do not exceed the specified limits.						
	*=Noise Floor Measurements (Minimum system sensitivity)						

Test Method:	FCC Part 15 Subpart C Radiated Emissions 15.249						
Customer:	Fisher Price			Job No.	R-8198-3A		
Test Sample:	906.6 Mhz Transmitter			FCC ID:	CCT1580T		
Model No.:	1580T			Serial No.	N/A		
Operating Mode:	Continuously Transmitter 906.6 Mhz Signal (Channel B)						
Technician:	Dennis Cortes			Date:	September 8, 1999		
Notes:	Test Distance: 3 Meters		Temp:23C	Humidity: 92%			
	Detector: Quasi-Peak						
Test Freq.	Antenna Pol./Height	EUT Orientation	Meter Reading	Correction Factor	Corrected Reading	Converted Reading	Limit
Mhz	(V/H) / Degrees	X / Y / Z	dBuv	dB	dBuV/m	UV/m	uV/m
5439.9	H / 1.0	X	43.3	3.6	46.9	*221.3	500
5439.9	H / 1.0	Y	43.3	3.6	46.9	*221.3	500
5439.9	H / 1.0	Z	43.3	3.6	46.9	*221.3	500
5439.9	V / 1.0	X	43.3	3.6	46.9	*221.3	500
5439.9	V / 1.0	Y	43.3	3.6	46.9	*221.3	500
5439.9	V / 1.0	Z	43.3	3.6	46.9	*221.3	500
6346.5	H / 1.0	X	42.8	3.0	45.8	*195.0	500
6346.5	H / 1.0	Y	42.8	3.0	45.8	*195.0	500
6346.5	H / 1.0	Z	42.8	3.0	45.8	*195.0	500
6346.5	V / 1.0	X	42.8	3.0	45.8	*195.0	500
6346.5	V / 1.0	Y	42.8	3.0	45.8	*195.0	500
6346.5	V / 1.0	Z	42.8	3.0	45.8	*195.0	500
7253.2	H / 1.0	X	42.8	1.5	44.3	*164.1	500
7253.2	H / 1.0	Y	42.8	1.5	44.3	*164.1	500
7253.2	H / 1.0	Z	42.8	1.5	44.3	*164.1	500
7253.2	V / 1.0	X	42.8	1.5	44.3	*164.1	500
7253.2	V / 1.0	Y	42.8	1.5	44.3	*164.1	500
7253.2	V / 1.0	Z	42.8	1.5	44.3	*164.1	500
8159.8	H / 1.0	X	43.1	2.2	45.3	*184.1	500
8159.8	H / 1.0	Y	43.1	2.2	45.3	*184.1	500
8159.8	H / 1.0	Z	43.1	2.2	45.3	*184.1	500
8159.8	V / 1.0	X	43.1	2.2	45.3	*184.1	500
8159.8	V / 1.0	Y	43.1	2.2	45.3	*184.1	500
8159.8	V / 1.0	Z	43.1	2.2	45.3	*184.1	500
9066.5	H / 1.0	X	44.1	0.3	44.4	*166.0	500
9066.5	H / 1.0	Y	44.1	0.3	44.4	*166.0	500
9066.5	H / 1.0	Z	44.1	0.3	44.4	*166.0	500
9066.5	V / 1.0	X	44.1	0.3	44.4	*166.0	500
9066.5	V / 1.0	Y	44.1	0.3	44.4	*166.0	500
9066.5	V / 1.0	Z	44.1	0.3	44.4	*166.0	500
	The frequency range was scanned from 30 Mhz to 9.2 Ghz. All emissions not recorded were more						
	Than 10 dB below the specified limit. Emissions from the EUT do not exceed the specified limits.						
	*=Noise Floor Measurements (Minimum system sensitivity)						