FCC Test Report

Report No.: AGC19I120201-02F2B

FCC ID	:	CFOMOON
PRODUCT DESIGNATION	:	GSM cell phone
BRAND NAME	:	TECH
TEST MODEL	:	MOON
CLIENT	:	TECH MIAMI LLC
DATE OF ISSUE	:	Mar.14, 2012
STANDARD(S)	:	FCC Part 15 Rules

Attestation of ***G***lobal ***C***ompliance Co., Ltd.

CAUTION: This report shall not be reproduced except in full without the written permission of the test laboratory and shall not be quoted out of context.

VERIFICATION OF COMPLIANCE

Applicant	TECH MIAMI LLC
	3164 nw 72nd AV Miami, FI 33122, USA
Manufacturer	Capeak Digitech Co.,Ltd.
	Bld 206, Terra Industry Park, Che Gong Miao, Futian, Shenzhen, China
Product Designation:	GSM cell phone
Brand name:	TECH
Model Name:	MOON, Dance, Music, C3, Q1, Q2, Q3, Q4, Q5, Q6
Model Difference and Test Model:	All models above are the same except for model name. The test model is MOON.
FCC ID	CFOMOON
Report Number	AGC19I120201-02F2B
Date of Test	Mar.07, 2012 to Mar.13, 2012

WE HEREBY CERTIFY THAT:

The above equipment was tested by Attestation of Global Compliance Co., Ltd. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.4 (2003) and the energy emitted by the sample EUT tested as described in this report is in compliance with radiated emission limits of FCC Rules Part 15.247.

Tested By: Curoky Chen

Curoky Chen Mar.14, 2012

Reviewed By: Forrest Lei

Forrest Lei Mar.14, 2012

Approved By: Solger Zhang

Solger Zhang Mar.14, 2012

TABLE OF CONTENTS

1. GENERAL INFORMATION 4

1.1 PRODUCT DESCRIPTION 4
1.2 TABLE OF CARRIER FREQUENCYS 4
1.3 RECEIVER INPUT BANDWIDTH 4
1.4 EXAMPLE OF A HOPPING SEQUENCY IN DATA MODE 5
1.5 EQUALLY AVERAGE USE OF FREQUENCIES AND BEHAVIOUR 5
1.6 RELATED SUBMITTAL(S) / GRANT (S) 5
1.7 TEST METHODOLOGY 5
1.8 TEST FACILITY 6
1.9 SPECIAL ACCESSORIES 6
1.10 EQUIPMENT MODIFICATIONS 6

2. SYSTEM TEST CONFIGURATION 7

2.1 CONFIGURATION OF EUT SYSTEM 7
2.2 EQUIPMENT USED IN EUT SYSTEM 7

3. SUMMARY OF TEST RESULTS 8

4. DESCRIPTION OF TEST MODES 8

5. PEAK OUTPUT POWER 9

5.1 MEASUREMENT PROCEDURE 9
5.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) 9
5.3 MEASUREMENT EQUIPMENT USED 10
5.4 LIMITS AND MEASUREMENT RESULT 10

6. 20 DB BANDWIDTH 11

6.1 MEASUREMENT PROCEDURE 11
6.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) 11
6.3 MEASUREMENT EQUIPMENT USED 11
6.4 LIMITS AND MEASUREMENT RESULTS 11

7. CONDUCTED SPURIOUS EMISSION 13

7.1 MEASUREMENT PROCEDURE 13
7.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) 13
7.3 MEASUREMENT EQUIPMENT USED 13
7.4 LIMITS AND MEASUREMENT RESULT 13

8. RADIATED EMISSION 15

8.1 MEASUREMENT PROCEDURE 15
8.2 TEST SETUP 16
8.3 TEST EQUIMENT LIST 17
8.4 TEST RESULT 18

9. BAND EDGE EMISSION 22

9.1 MEASUREMENT PROCEDURE 22
9.2 TEST SET-UP 22
9.3 TEST RESULT 22

10. NUMBER OF HOPPING FREQUENCY 26

10.1 MEASUREMENT PROCEDURE 26
10.2 TEST SETUP (BLOCK DIAGRAM OF CONFIGURATION) 26

10.3 MEASUREMENT EQUIPMENT USED 26
10.4 LIMITS AND MEASUREMENT RESULT 26

11. TIME OF OCCUPANCY (DWELL TIME) 27

11.1 MEASUREMENT PROCEDURE 27
11.2 TEST SETUP (BLOCK DIAGRAM OF CONFIGURATION) 27
11.3 MEASUREMENT EQUIPMENT USED 27
11.4 LIMITS AND MEASUREMENT RESULT 27

12. FREQUENCY SEPARATION 30

12.1 MEASUREMENT PROCEDURE 30
12.2 TEST SETUP (BLOCK DIAGRAM OF CONFIGURATION) 30
12.3 MEASUREMENT EQUIPMENT USED 30
12.4 LIMITS AND MEASUREMENT RESULT 30

13. FCC LINE CONDUCTED EMISSION TEST 31

13.1 LIMITS OF LINE CONDUCTED EMISSION TEST 31
13.2 BLOCK DIAGRAM OF LINE CONDUCTED EMISSION TEST 31
13.3 PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST 32
13.4 FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST 32
13.5 TEST RESULT OF LINE CONDUCTED EMISSION TEST 33

APPENDIX Ⅰ 35

PHOTOGRAPHS OF THE EUT 35

APPENDIX Ⅱ 42

PHOTOGRAPHS OF THE TEST SETUP 42

1. GENERAL INFORMATION

1.1 PRODUCT DESCRIPTION

The EUT is a **GSM cell phone** designed as an “Communication Device”. It is designed by way of utilizing the FHSS technology to achieve the system operation.

A major technical description of EUT is described as following

Operation Frequency	2.402 GHz to 2.480GHz
Rated Output Power	3.36dBm
Bluetooth Version:	V2.1 with EDR
Modulation	GFSK, Π/4-DQPSK, 8-DPSK
Number of channels	79
Antenna Designation	Integrated Antenna
Antenna Gain	0.8dBi
Power Supply	DC3.7V by Built-in Li-ion Battery
***note: the EUT can charged by PC while transfer information.*	

1.2 TABLE OF CARRIER FREQUENCYS

Frequency Band	Channel Number	Frequency
2400~2483.5MHZ	0	2402MHZ
	1	2403MHZ
	:	:
	38	2440 MHZ
	39	2441 MHZ
	40	2442 MHZ
	:	:
	77	2479 MHZ
	78	2480 MHZ

1.3 RECEIVER INPUT BANDWIDTH

The input bandwidth of the receiver is 1.2MHZ,In every connection one Bluetooth device is the master and the other one is slave. The master determines the hopping sequence. The slave follows this sequence. Both devices shift between RX and TX time slot according to the clock of the master. Additionally the type of connection(e.g. single of multislot packet) is set up at the beginning of the connection. The master adapts its hopping frequency and its TX/RX timing according to the packet type of the connection. Also the slave of the connection will use these settings.
Repeating of a packet has no influence on the hopping sequence. The hopping sequence generated by the master of the connection will be followed in any case. That means, a repeated packet will not be send on the same frequency, it is send on the next frequency of the hopping sequence.

1.4 EXAMPLE OF A HOPPING SEQUENCY IN DATA MODE

Example of a 79 hopping sequence in data mode:
40,21,44,23,42,53,46,55,48,33,52,35,50,65,54,67
56,37,60,39,58,69,62,71,64,25,68,27,66,57,70,59
72,29,76,31,74,61,78,63,01,41,05,43,03,73,07,75
09,45,13,47,11,77,15,00,64,49,66,53,68,02,70,06
01,51,03,55,05,04

1.5 EQUALLY AVERAGE USE OF FREQUENCIES AND BEHAVIOUR

The generation of the hopping sequence in connection mode depends essentially on two input values:
1 LAP/UAP of the master of the connection
2. Internal master clock
The LAP(lower address part) are the 24 LSB's of the 48 BD_ADDRESS. The BD_ADDRESS is an unambiguous number of every Bluetooth unit. The UAP(upper address part) are the 24MSB's of the 48BD_ADDRESS
The internal clock of a Bluetooth unit is derived from a free running clock which is never adjusted and Is never turned off. For ehavior zation with other units only offset are used. It has no relation to the time Of the day. Its resolution is at least half the RX/TX slot length of 312.5us.The clock has a cycle of about One day(23h30).In most case it is implemented as 28 bit counter. For the deriving of the hopping sequence the entire.
LAP(24 bits),4LSB's(4bits)(Input 1) and the 27MSB's of the clock(Input 2) are used. With this input values different mathematical procedures(permutations, additions, XOR-operations)are performed to generate te Sequence. This will be done at the beginning of every new transmission.
Regarding short transmissions the Bluetooth system has the following ehavior:
The first connection between the two devices is established, a hopping sequence was generated. For Transmitting the wanted data the complete hopping sequence was not used. The connection ended.
The second connection will be established. A new hopping sequence is generated. Due to the fact the Bluetooth clock has a different value, because the period between the two transmission is longer(and it Cannot be shorter)than the minimum resolution of the clock(312.5us).The hopping sequence will always Differ from the first one.

1.6 RELATED SUBMITTAL(S) / GRANT (S)

This submittal(s) (test report) is intended for **FCC ID: CFOMOON** filing to comply with Section 15.247 of the FCC Part 15, Subpart C Rules.

1.7 TEST METHODOLOGY

Both conducted and radiated testing were performed according to the procedures in ANSI C63.4 (2003). Radiated testing was performed at an antenna to EUT distance 3 meters.

1.8 TEST FACILITY

All measurement facilities used to collect the measurement data are located at
Attestation of Global Compliance Co., Ltd.

1&2F., No.2 Building, Huafeng No.1 Technical Industrial Park, Sanwei, XiXiang, Baoan District, Shenzhen
The test site is constructed and calibrated to meet the FCC requirements in documents ANSI C63.4: 2003.
FCC register No.: 259865

1.9 SPECIAL ACCESSORIES

Refer to section 2.2.

1.10 EQUIPMENT MODIFICATIONS

Not available for this EUT intended for grant.

2. SYSTEM TEST CONFIGURATION

2.1 CONFIGURATION OF EUT SYSTEM

Configure :



***Note:** *No software used to control the EUT for staying in continuous transmitting mode for testing.*

2.2 EQUIPMENT USED IN EUT SYSTEM

Item	Equipment	Mfr/Brand	Model/Type No.	Remark
1	GSM cell phone	TECH	MOON	EUT
2	Adapter	TECH	BC-M9	accessory
3	battery	TECH	BL-4S	accessory
4	USB Cable	N/A	N/A	accessory
5	Earphone	N/A	N/A	accessory

Note: All the accessories have been used during the test except for earphone. the USB cable and earphone could not Work simultaneous, all the following "EUT" in setup diagram means EUT system.

3. SUMMARY OF TEST RESULTS

FCC RULES	DESCRIPTION OF TEST	RESULT
§15.247	Peak Output Power	Compliant
§15.247	20 dB Bandwidth	Compliant
§15.247	Spurious Emission	Compliant
§15.209	Radiated Emission	Compliant
§15.247	Band Edges	Compliant
§15.207	Conduction Emission	Compliant
§15.247	Number of Hopping Frequency	Compliant
§15.247	Time of Occupancy	Compliant
§15.247	Frequency Separation	Compliant

4. DESCRIPTION OF TEST MODES

The following operating modes were applied for the related test items. For Radiated Emission, 3 axis were chosen for testing for each applicable modes.

No.	TEST MODES
1	Low Channel(TX)
2	Middle Channel(TX)
3	High Channel(TX)
4	Normal Hopping

Note: All the test modes can be supply by Built-in Li-ion battery and adapter, only the result of the worst case was recorded in the report.

5. PEAK OUTPUT POWER

5.1 MEASUREMENT PROCEDURE

1. The EUT was placed on a turn table which is 0.8m above ground plane.
2. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
3. Set the EUT Work on the top, middle and the bottom operation frequency individually.
4. Set Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel
   RBW > the 20 dB bandwidth of the emission being measured
   VBW ≥ RBW; Sweep = auto; Detector function = peak
5. Set SPA Trace 1 Max hold, then View.

5.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)



5.3 MEASUREMENT EQUIPMENT USED

Description	Manufacturer	Model	SERIAL NUMBER	Cal. Date	Cal. Due
Spectrum Analyzer	Agilent	E4440A	N/A	06/27/2011	06/26/2012
RF attenuator	N/A	RFA20db	N/A	N/A	N/A

5.4 LIMITS AND MEASUREMENT RESULT

PEAK OUTPUT POWER MEASUREMENT RESULT FOR GFSK MOUDULATION			
Frequency (GHz)	Result (dBm)	Applicable Limits (dBm)	Pass or Fail
2.402	3.36	30	Pass
2.441	3.31	30	Pass
2.480	3.28	30	Pass

PEAK OUTPUT POWER MEASUREMENT RESULT FOR Π /4-DQPSK, 8-DPSK MODULATION				
Frequency (GHz)	Test Result 2 Mbps (dBm)	Test Result 3 Mbps (dBm)	Applicable Limits (dBm)	Pass or Fail
2.402	3.25	3.24	30	Pass
2.441	3.21	3.22	30	Pass
2.480	3.18	3.16	30	Pass

6. 20 DB BANDWIDTH

6.1 MEASUREMENT PROCEDURE

1. The EUT was placed on a turn table which is 0.8m above ground plane.
2. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
3, Set the EUT Work on the top, the middle and the bottom operation frequency individually.
4. Set Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hoping channel RBW ≥ 1% of the 20 dB bandwidth, VBW ≥ RBW; Sweep = auto; Detector function = peak
5. Set SPA Trace 1 Max hold, then View.

6.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)

The Same as described in Section 5.2

6.3 MEASUREMENT EQUIPMENT USED

The same as described in Section 5.3

6.4 LIMITS AND MEASUREMENT RESULTS

LIMITS AND MEASUREMENT RESULT			
Applicable Limits	Measurement Result(3Mbps)		
	Test Data (MHz)		Criteria
N/A	Low Channel	1.178	PASS
	Middle Channel	1.243	PASS
	High Channel	1.246	PASS

TEST PLOT OF BANDWIDTH FOR LOW CHANNEL



TEST PLOT OF BANDWIDTH FOR MIDDLE CHANNEL



TEST PLOT OF BANDWIDTH FOR HIGH CHANNEL



7. CONDUCTED SPURIOUS EMISSION

7.1 MEASUREMENT PROCEDURE

1. The EUT was placed on a turn table which is 0.8m above ground plane.
2. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
3, Set the EUT Work on the top, the Middle and the bottom operation frequency individually.
4. Set the Span = wide enough to capture the peak level of the in-band emission and all spurious emissions from the lowest frequency generated in the EUT up through the 10th harmonic.
   RBW = 100 kHz; VBW ≥ RBW; Sweep = auto; Detector function = peak.
5. Set SPA Trace 1 Max hold, then View.

7.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)

The Same as described in section 5.2

7.3 MEASUREMENT EQUIPMENT USED

The Same as described in section 5.3

7.4 LIMITS AND MEASUREMENT RESULT

LIMITS AND MEASUREMENT RESULT		
Applicable Limits	Measurement Result	
	Test Data	Criteria
In any 100 KHz Bandwidth Outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produce by the intentional radiator shall be at least 20 dB below that in 100KHz bandwidth within the band that contains the highest level of the desired power. In addition, radiation emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in§15.209(a))	At least -20dBc than the limit Specified on the BOTTOM Channel	PASS
	At least -20dBc than the limit Specified on the TOP Channel	PASS

TEST PLOT OF OUT OF BAND EMISSIONS WITH THE WORST CASE OF 1 MBPS FOR GFSK MODULATION IN HIGH CHANNEL





8. RADIATED EMISSION

8.1 MEASUREMENT PROCEDURE

1. Configure the EUT according to ANSI C63.4. The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
6. For emissions above 1GHz, use 1MHz VBW and RBW for peak reading. Then 1MHz RBW and 10Hz VBW for average reading in spectrum analyzer.
7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.
8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High – Low scan is not required in this case.

The following table is the setting of spectrum analyzer and receiver.'

Spectrum Parameter	Setting
Start ~Stop Frequency	9KHz~150KHz/RB 200Hz for QP
Start ~Stop Frequency	150KHz~30MHz/RB 9KHz for QP
Start ~Stop Frequency	30MHz~1000MHz/RB 120KHz for QP
Start ~Stop Frequency	1GHz~26.5GHz 1MHz/1MHz for Peark, 1MHz/10Hz for Average

Receiver Parameter	Setting
Start ~Stop Frequency	9KHz~150KHz/RB 200Hz for QP
Start ~Stop Frequency	150KHz~30MHz/RB 9KHz for QP
Start ~Stop Frequency	30MHz~1000MHz/RB 120KHz for QP

8.2 TEST SETUP

RADIATED EMISSION TEST SETUP BELOW 30MHz



RADIATED EMISSION TEST SETUP 30MHz-1000MHz



RADIATED EMISSION TEST SETUP ABOVE 1000MHz



8.3 TEST EQUIMENT LIST

Description	Manufacturer	Model	SERIAL NUMBER	Cal. Date	Cal. Due
Spectrum Analyzer	Agilent	E4440A	N/A	06/27/2011	06/26/2012
Amplifier	EM	EM30180	0607030	06/27/2011	06/26/2012
Horn Antenna	EM	EM-AH-10180	N/A	06/27/2011	06/26/2012
Horn Antenna	A.H. Systems Inc.	SAS-574	--	06/27/2011	06/26/2012
EMI Test Receiver	Rohde & Schwarz	ESCI	N/A	06/27/2011	06/26/2012
Amplifier	EM	EM30180	N/A	06/27/2011	06/26/2012
Bilogical Antenna	A.H. Systems Inc.	SAS-521-4	N/A	06/27/2011	06/26/2012
Loop Antenna	Daze	ZN30900N	SEL0097	06/27/2011	06/26/2012
Isolation Transformer	LETEAC	LTBK	--	06/27/2011	06/26/2012

8.4 TEST RESULT

RADIATED EMISSION BELOW 30MHZ

No emission found between lowest internal used/generated Frequency to 30MHz.

RADIATED EMISSION BELOW 1GHZ



Site: site #1
Limit: FCC Class B 3M Radiation
EUT: GSM cell phone
M/N: MOON
Mode: Normal Hopping
Note:

Polarization: *Horizontal*
Power: AC120V/60Hz
Distance: 3m

Temperature: 26
Humidity: 60 %

No.	Mk.	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		51.0167	21.77	5.44	27.21	40.00	-12.79	peak			
2		57.4833	26.64	2.41	29.05	40.00	-10.95	peak			
3		78.5000	16.57	9.53	26.10	40.00	-13.90	peak			
4		89.8167	15.55	17.11	32.66	43.50	-10.84	peak			
5	*	178.7332	15.25	17.91	33.16	43.50	-10.34	peak			
6		574.8167	4.50	24.49	28.99	46.00	-17.01	peak			



Site: site #1
Limit: FCC Class B 3M Radiation
EUT: GSM cell phone
M/N: MOON
Mode: Normal Hopping
Note:

Polarization: *Vertical*
Power: AC120V/60Hz
Distance: 3m

Temperature: 26
Humidity: 60 %

No.	Mk.	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1	*	57.4833	31.98	2.40	34.38	40.00	-5.62	peak			
2		89.8167	26.40	8.37	34.77	43.50	-8.73	peak			
3		149.6333	14.58	19.01	33.59	43.50	-9.91	peak			
4		201.3667	21.76	15.12	36.88	43.50	-6.62	peak			
5		240.1667	14.52	17.23	31.75	46.00	-14.25	peak			
6		537.6332	13.11	23.42	36.53	46.00	-9.47	peak			

RADIATED EMISSION ABOVE 1GHZ(1-10th Harmonics)



Site: site #1
Limit: FCC Class B 3M Radiation above 1GHZ(PK)
EUT: GSM cell phone
M/N: MOON
Mode: Normal Hopping
Note:

Polarization: *Horizontal*
Power: AC 120V/60Hz
Distance: 3m

Temperature: 26
Humidity: 60 %

No.	Mk.	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2133.333	34.91	0.03	34.94	74.00	-39.06	peak			
2		2402.167	72.14	0.33	72.47	74.00	-1.53	peak			
3	*	2480.000	72.26	0.41	72.67	74.00	-1.33	peak			
4		4160.000	36.04	2.53	38.57	74.00	-35.43	peak			



Site: site #1 | Polarization: *Vertical* | Temperature: 26
Limit: FCC Class B 3M Radiation above 1GHZ(PK) | Power: | Humidity: 60 %
EUT: GSM cell phone | Distance: 3m
M/N: MOON
Mode: Normal Hopping
Note:

No.	Mk.	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2402.000	62.54	10.32	72.86	74.00	-1.14	peak			
2	*	2480.000	62.49	10.41	72.90	74.00	-1.10	peak			
3		3360.000	27.48	11.98	39.46	74.00	-34.54	peak			
4		3966.667	26.18	14.98	41.16	74.00	-32.84	peak			

Note:5~25GHz at least have 20dB margin. no recording in the test report.
Factor=Antenna Factor+ Cable loss-Amplifier gain, Margin=Measurement-Limit.

9. BAND EDGE EMISSION

9.1 MEASUREMENT PROCEDURE

1, Set the EUT Work on the top, the bottom operation frequency individually.
2. Set SPA Start or Stop Frequency = Operation Frequency, RBW>=1%span, VBW>=RBW
3. The band edges was measured and recorded.

9.2 TEST SET-UP

Radiated same as 8.2

9.3 TEST RESULT

TEST PLOT OF BAND EDGE FOR LOW CHANNEL (1Mbps)



Site: site #1
Limit: FCC Class B 3M Radiation above 1GHZ(PK)
EUT: GSM cell phone
M/N: MOON
Mode: Low Channel-TX
Note:

Polarization: *Horizontal*
Power:
Distance: 3m

Temperature: 26
Humidity: 60 %

No.	Mk.	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2393.375	27.31	10.29	37.60	74.00	-36.40	peak			
2		2401.000	32.38	10.31	42.69	74.00	-31.31	peak			
3	*	2402.000	61.89	10.32	72.21	74.00	-1.79	peak			



Site: site #1 | Polarization: *Vertical* | Temperature: 26
Limit: FCC Class B 3M Radiation above 1GHZ(PK) | Power: | Humidity: 60 %
EUT: GSM cell phone | Distance: 3m
M/N: MOON
Mode: Low Channel-TX
Note:

No.	Mk.	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2395.792	29.43	10.28	39.71	74.00	-34.29	peak			
2		2401.000	34.29	10.31	44.60	74.00	-29.40	peak			
3	*	2402.083	62.88	10.32	73.20	74.00	-0.80	peak			

TEST PLOT OF BAND EDGE FOR HIGH CHANNEL (1Mbps)



Site: site #1
Limit: FCC Class B 3M Radiation above 1GHZ(PK)
EUT: GSM cell phone
M/N: MOON
Mode: High Channel-TX
Note:

Polarization: ***Horizontal***
Power:
Distance: 3m

Temperature: 26
Humidity: 60 %

No.	Mk.	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1	*	2480.000	62.70	10.41	73.11	74.00	-0.89	peak			
2		2480.970	35.22	10.42	45.64	74.00	-28.36	peak			
3		2485.480	27.65	10.44	38.09	74.00	-35.91	peak			



Site: site #1
Limit: FCC Class B 3M Radiation above 1GHZ(PK)
EUT: GSM cell phone
M/N: MOON
Mode: High-Channel-TX
Note:

Polarization: *Vertical*
Power:
Distance: 3m

Temperature: 26
Humidity: 60 %

No.	Mk.	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1	*	2480.000	62.90	10.41	73.31	74.00	-0.69	peak			
2		2482.143	29.84	10.41	40.25	74.00	-33.75	peak			
3		2483.903	31.13	10.42	41.55	74.00	-32.45	peak			
4		2487.533	29.46	10.44	39.90	74.00	-34.10	peak			

10. NUMBER OF HOPPING FREQUENCY

10.1 MEASUREMENT PROCEDURE

1. Place the EUT on the table and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum analyzer.
3. Set the spectrum analyzer Start = 2.4GHz Stop = 2.4835GHz
4. Set the Spectrum Analyzer as RBW>=1%span, VBW>=RBW.

10.2 TEST SETUP (BLOCK DIAGRAM OF CONFIGURATION)

Same as described in section 5.2

10.3 MEASUREMENT EQUIPMENT USED

The Same as described in section 5.3

10.4 LIMITS AND MEASUREMENT RESULT

TOTAL NO. OF HOPPING CHANNEL	LIMIT (NO. OF CH)	MEASUREMENT (NO. OF CH)	RESULT
	>=15	79	PASS

TEST PLOT FOR NO. OF TOTAL CHANNELS



11. TIME OF OCCUPANCY (DWELL TIME)

11.1 MEASUREMENT PROCEDURE

1. Place the EUT on the table and set it in transmitting mode
2. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum analyzer
3. Set Span = zero span, centered on a hoping channel
4. Set the spectrum analyzer as RBW=1MHz, VBW>=RBW, Span = 0 Hz

11.2 TEST SETUP (BLOCK DIAGRAM OF CONFIGURATION)

Same as described in section 5.2

11.3 MEASUREMENT EQUIPMENT USED

The same as described in section 5.3

11.4 LIMITS AND MEASUREMENT RESULT

The Worst Case (3Mbps)

Channel	Time of Pulse for DH5 (ms)	Period Time (s)	Sweep Time (ms)	Limit (ms)
Low	2.892	31.6	308.48	400
Middle	2.867	31.6	305.81	400
High	2.9	31.6	309.33	400

Low Channel Time
2.892*(1600/6)/79*31.6=308.48ms
Middle Channel Time
2.867*(1600/6)/79*31.6=305.81ms
High Channel Time
2.9*(1600/6)/79*31.6=309.33ms

TEST PLOT OF LOW CHANNEL



TEST PLOT OF MIDDLE CHANNEL



TEST PLOT OF HIGH CHANNEL



12. FREQUENCY SEPARATION

12.1 MEASUREMENT PROCEDURE

1. Place the EUT on the table and set it in transmitting mode
2. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum analyzer
3. Set Span = wide enough to capture the peaks of two adjacent channels Resolution (or IF) Bandwidth (RBW) ≥ 1% of the span Video (or Average) Bandwidth (VBW) ≥ RBW; Sweep = auto; Detector function = peak; Trace = max hold

12.2 TEST SETUP (BLOCK DIAGRAM OF CONFIGURATION)

Same as described in section 5.2

12.3 MEASUREMENT EQUIPMENT USED

The same as described in section 5.3

12.4 LIMITS AND MEASUREMENT RESULT

CHANNEL	CHANNEL SEPARATION	LIMIT	RESULT
	KHz	KHz	
CH00-CH01	1000	>=25 KHz or 2/3 20 dB BW	Pass

TEST PLOT FOR FREQUENCY SEPARATION



13. FCC LINE CONDUCTED EMISSION TEST

13.1 LIMITS OF LINE CONDUCTED EMISSION TEST

Frequency	Maximum RF Line Voltage	
	Q.P.(dBuV)	Average(dBuV)
150kHz~500kHz	66-56	56-46
500kHz~5MHz	56	46
5MHz~30MHz	60	50

**Note: 1. The lower limit shall apply at the transition frequency.
2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz

13.2 BLOCK DIAGRAM OF LINE CONDUCTED EMISSION TEST



13.3 PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST

1) The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.4 (see Test Facility for the dimensions of the ground plane used). When the EUT is a floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.
2) Support equipment, if needed, was placed as per ANSI C63.4.
3) All I/O cables were positioned to simulate typical actual usage as per ANSI C63.4.
4) All support equipments received AC120V/60Hz power from a LISN, if any.
5) The EUT received power by adapter which received 120V/60Hzpower by a LISN..
6) The test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
7) Analyzer / Receiver scanned from 150 kHz to 30MHz for emissions in each of the test modes.
8) During the above scans, the emissions were maximized by cable manipulation.
9) The test mode(s) were scanned during the preliminary test.

   Then, the EUT configuration and cable configuration of the above highest emission level were recorded for reference of final testing.

13.4 FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST

1) EUT and support equipment was set up on the test bench as per step 2 of the preliminary test.
2) A scan was taken on both power lines, Line 1 and Line 2, recording at least the six highest emissions. Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit. If EUT emission level was less –2dB to the A.V. limit in Peak mode, then the emission signal was re-checked using Q.P and Average detector.
3) The test data of the worst case condition(s) was reported on the Summary Data page.

13.5 TEST RESULT OF LINE CONDUCTED EMISSION TEST

Line Conducted Emission Test Line 1-L



Site: Conduction | Phase: *L1* | Temperature: 26
Limit: FCC Class B Conduction(QP) | Power: AC 120V/60Hz | Humidity: 60 %
EUT: GSM cell phone
M/N: MOON
Mode: Normal Hopping
Note:

No.	Freq. (MHz)	Reading_Level (dBuV)			Correct Factor	Measurement (dBuV)			Limit (dBuV)		Margin (dB)		P/F	Comment
		Peak	QP	AVG	dB	Peak	QP	AVG	QP	AVG	QP	AVG		
1	0.1940	43.78		36.24	10.21	53.99		46.45	63.86	53.86	-9.87	-7.41	P	
2	0.2580	39.84		29.87	10.27	50.11		40.14	61.49	51.49	-11.38	-11.35	P	
3	0.3260	34.57		25.02	10.30	44.87		35.32	59.55	49.55	-14.68	-14.23	P	
4	3.1180	33.02		28.03	10.54	43.56		38.57	56.00	46.00	-12.44	-7.43	P	
5	5.2579	34.66		30.44	10.25	44.91		40.69	60.00	50.00	-15.09	-9.31	P	
6	6.9459	37.92		32.78	10.35	48.27		43.13	60.00	50.00	-11.73	-6.87	P	

Line Conducted Emission Test Line 2-N



Site: Conduction
Phase: *N*
Temperature: 26
Limit: FCC Class B Conduction(QP)
Power: AC 120V/60Hz
Humidity: 60 %
EUT: GSM cell phone
M/N: MOON
Mode: Normal Hopping
Note:

No.	Freq. (MHz)	Reading_Level (dBuV)			Correct Factor	Measurement (dBuV)			Limit (dBuV)		Margin (dB)		P/F	Comment
		Peak	QP	AVG	dB	Peak	QP	AVG	QP	AVG	QP	AVG		
1	0.1940	43.62		39.56	10.21	53.83		49.77	63.86	53.86	-10.03	-4.09	P	
2	0.2620	41.11		33.34	10.27	51.38		43.61	61.36	51.36	-9.98	-7.75	P	
3	0.3260	35.42		27.90	10.30	45.72		38.20	59.55	49.55	-13.83	-11.35	P	
4	0.5860	30.30		29.48	10.32	40.62		39.80	56.00	46.00	-15.38	-6.20	P	
5	3.0579	29.73		27.48	10.55	40.28		38.03	56.00	46.00	-15.72	-7.97	P	
6	8.9139	37.56		33.20	10.23	47.79		43.43	60.00	50.00	-12.21	-6.57	P	

APPENDIX Ⅰ
PHOTOGRAPHS OF THE EUT

TOP VIEW

BOTTOM VIEW

LEFT VIEW

RIGHT VIEW

FRONT VIEW

BACK VEIW

ALL VIEW

OPEN VIEW-1



OPEN VIEW-2



OPEN VIEW-3



OPEN VIEW-4



OPEN VIEW-5



OPEN VIEW-6



APPENDIX Ⅱ
PHOTOGRAPHS OF THE TEST SETUP

CONDUCTED EMISSION

RADIATED SPURIOUS EMISSION



----END OF REPORT----