

DATE: 6/30/00 TESTED BY: Greg Barbato APPROVED BY: Ken Addy
 TEST SAMPLE (model): ADEMCO 5800RL (TRANSMITTER)

ALARM DEVICE MANUFACTURING COMPANY
165 EILEEN WAY
SYOSSET, NY 11791

FCC : CFS8DL5800RL

TEST METHOD: ANSI C63.4-1992

TEST SPECIFICATION: FCC PART 15, SUBPART C.

- NOTES: 1) Fo= 345 MHZ
 2) DETECTOR = PEAK.
 3) FREQUENCY RANGE SCANNED TO 4 GHz.

(METER READING +CABLE /AMP FACTOR +ANTENNA FACTOR)

20

4) CONVERTED READING = 10

5) CORRECTED READING = CONVERTED READING X DUTY CYCLE

6) SIX HIGHEST EMISSIONS RECORDED.

Frequency (MHz)	Antenna Polarity (V-H)	Meter Reading (dB uV)	Cable/Amp Factor (dB)	Antenna Factor (dB/M)	Converted Reading (uV/M)	Duty Cycle (%)	Corrected Reading (uV/M)	Limit @ 3 Meter (uV/M)
30								729
345	H	65.0	1.5	15.1	12,022.6	15.26	1834.6	7,292
690	H	50.0	2.1	20.6	4,315.2	15.26	658.5	729
1035	V	37.2	2.6	24.0	1548.8	15.26	236.3	500
1380	V	39.0	3.0	27.9	3,126.0	15.26	477.0	500
1725	H	39.6	3.4	30.0	4,466.8	15.26	681.6	729
2070	V	27.0	3.7	28.0	861.0	15.26	131.4	729
2415	V	33.0	4.0	28.8	1,949.8	15.26	297.5	729
2760	V	27.8	4.3	30.0	1,380.4	15.26	210.6	729
3105	V	22.5	4.5	30.7	767.4	15.26	117.1	729
3450	V	23.0	4.8	31.1	881.0	15.26	134.4	729
4000								729

NOTES: