

HONEYWELL SECURITY & CUSTOM ELECTRONICS

REV 2011C

**2 Corporate Center Drive
Melville, NY 11747**

EXHIBIT 5-3

FCC ID: CFS8DL 5828V1

Date : 31-May 2011

Tested by: G. BARBATO

Approved by: K. Eskildsen

Test Sample (model): 5828V1

Test method: ANSI C63.4 - 2004

Test specification: FCC Part 15, Sub-part C and RSS 210 , Issue 8

Notes: (1) Fo: 344.94 (2) Detector = Peak (3) Frequency range scanned to 4 GHz.

Emissions not reported were more than 20dB below the specified unit.

[(Meter reading + Cable/Amp factor + Antenna factor) / 20]

(4) Conv. Reading = 10

(5) Corr. Reading = Conv. Reading X Duty Cycle

(6) Six Highest Emissions Recorded

Freq. (MHz):	Sense Antenna Polarity (V/H):	THE ORENTATION OF THE UUT (V,H,O,):	Meter Reading (dB uV):	Cable/Amp Factor (dB):	Antenna Factor (dB/m):	Conv. Reading (uV/M):	Duty Cycle (%):	Corr. Reading (uV/M):	Limit @ 3M (uV/M):
344.94	H	H	77.60	2.3	13.81	48473.0	10.0%	4847.3	7292
689.88	H	H	26.56	3.2	19.44	288.4	10.0%	28.8	729
1034.82	V	H	26.69	4.4	23.84	557.8	10.0%	55.8	500
1379.76	V	V	20.74	4.9	26.08	385.5	10.0%	38.5	500
1724.70	H	H	20.57	5.5	28.07	509.3	10.0%	50.9	729
2069.64	V	V	21.98	6.4	30.28	857.0	10.0%	85.7	729
2414.58	H	O	21.63	6.9	32.01	1064.1	10.0%	106.4	729
2759.52	V	V	23.67	7.4	31.56	1353.6	10.0%	135.4	500
3104.46	H	V	23.38	7.9	32.34	1517.1	10.0%	151.7	729
3449.40	H	V	23.44	9.2	33.01	1916.5	10.0%	191.6	729
4000				LAST CAL 05 FEB 11 CABLE C	LAST CAL 09-SEP-10 BICONILOG S/N:0004568 2				