

**HONEYWELL SECURITY & CUSTOM ELECTRONICS****165 EILEEN WAY****SYOSSET, NY 11791****EXHIBIT 5-3****FCC ID # CFS8DL6150RFT**

Date :12/6/2005

Tested by :Y. Mohammed

Approved by :K.Addy

Test Sample (model) : 6150RFAS-T3

Test method: ANSI C63.4 - 1992

Test specification: FCC Part 15, Sub-part C

Notes: (1) Fo = 345MHz. (2) Detector = Peak (3) Frequency range scanned to 4 GHz.

Emissions not reported were more than 20dB below the specified unit.

[(Meter reading + Cable/Amp factor + Antenna factor) / 20 ]

(4) Conv. Reading = 10

(5) Corr. Reading = Conv. Reading X Duty Cycle

(6) Six Highest Emissions Recorded

| Freq.<br>(MHz) | Antenna<br>Polarity<br>(V/H) | Meter<br>Reading<br>(dB uV) | Cable/Amp<br>Factor<br>(dB) | Antenna<br>Factor<br>(dB/M) | Conv.<br>Reading<br>(uV/M) | Duty<br>Cycle<br>(%) | Corr.<br>Reading<br>(uV/M) | Limit<br>@ 3M<br>(uV/M) |
|----------------|------------------------------|-----------------------------|-----------------------------|-----------------------------|----------------------------|----------------------|----------------------------|-------------------------|
| 30             |                              |                             | CABLE "A"                   | BICONILOG                   |                            |                      |                            | 729                     |
| 345            | H                            | 77.60                       | 1.2                         | 14.78                       | 47752.9                    | 15.0%                | 7162.9                     | 7292                    |
| 690            | H                            | 45.00                       | 1.8                         | 19.10                       | 1972.4                     | 15.0%                | 295.9                      | 729                     |
| 1035           | H                            | 38.00                       | 2.2                         | 22.70                       | 1396.4                     | 15.0%                | 209.5                      | 500                     |
| 1380           | H                            | 28.00                       | 2.5                         | 24.96                       | 592.9                      | 15.0%                | 88.9                       | 500                     |
| 1725           | H                            | 28.00                       | 2.8                         | 27.55                       | 827.0                      | 15.0%                | 124.0                      | 729                     |
| 2070           | H                            | 28.00                       | 3.0                         | 29.52                       | 1061.7                     | 15.0%                | 159.3                      | 729                     |
| 2415           | H                            | 28.00                       | 3.3                         | 31.13                       | 1322.8                     | 15.0%                | 198.4                      | 729                     |
| 2760           | H                            | 28.00                       | 3.7                         | 31.50                       | 1445.4                     | 15.0%                | 216.8                      | 729                     |
| 3105           | H                            | 28.00                       | 4.1                         | 31.61                       | 1532.9                     | 15.0%                | 229.9                      | 729                     |
| 3450           | H                            | 28.00                       | 4.4                         | 32.22                       | 1702.2                     | 15.0%                | 255.3                      | 729                     |
| 4000           |                              |                             | CABLE "A"                   | BICONILOG                   |                            |                      |                            |                         |