ALARM DEVICE MANUFACTURING COMPANY
165 EILEEN WAY
SYOSSET, NY 11791 **FCC ID: CFS8DL6160RF**

DATE: 9/20/02 TESTED BY: JOHN FITZGERALD APPROVED BY: KEN ADDY

6160RF (TRANSMITTER)

TEST SAMPLE (model) _____

TEST METHOD: ANSI C63.4-1992
TEST SPECIFICATION: FCC PART 15, SUBPART C.

NOTES: 1) Fo= 345 MHZ
2) DETECTOR = PEAK.
3) FREQUENCY RANGE SCANNED TO 4 GHz.

4) CONVERTED READING = $10^{\left[\frac{(\text{METER READING} + \text{CABLE /AMP FACTOR} + \text{ANTENNA FACTOR})}{20}\right]}$

5) CORRECTED READING = CONVERTED READING X DUTY CYCLE

6) FIVE HIGHEST EMISSIONS RECORDED.

Frequency (MHz)	Antenna Polarity (V-H)	Meter Reading (dB uV)	Cable/Amp Factor (dB)	Antenna Factor (dB/M)	Converted Reading (uV/M)	Duty Cycle (%)	Corrected Reading (uV/M)	Limit @ 3 Meter (uV/M)
30								729
345	H	74.5	1.5	16.66	39810	17.4	6926.9	7,291
690	H	24.5	2.0	21.1	239	17.4	41.586	729
1035	H	22.5	3.0	25.2	342.7	17.4	59.62	500
1380	H	26.1	3.17	28.8	800	17.4	139.2	500
1725	H	19.5	3.83	31.2	532.7	17.4	92.69	729
4000								729