

ALARM DEVICE MANUFACTURING COMPANY**165 EILEEN WAY
SYOSSET, NY 11791****FCC ID#** _____

June 10, 2000

DATE: _____ TESTED BY: *John O'Keefe* APPROVED BY: _____

ADEMCO LYNXRU4 (RECEIVER)

TEST SAMPLE (model): _____

TEST METHOD: ANSI C63.4-1992

TEST SPECIFICATION: FCC PART 15, SUBPART B

NOTES: 1) F₀= 355.7 MHZ

2) DETECTOR = PEAK.

3) FREQUENCY RANGE SCANNED TO 4 GHz.

$$\left[\frac{(\text{METER READING} + \text{CABLE / AMP FACTOR} + \text{ANTENNA FACTOR})}{20} \right]$$

4) CONVERTED READING = 10

5) SIX HIGHEST EMISSIONS RECORDED.

Frequency (MHz)	Antenna Polarity (V-H)	Meter Reading (dB uV)	Cable/Amp Factor (dB)	Antenna Factor (dB/M)	Converted Reading (uV/M)	Duty Cycle (%)	Corrected Reading (uV/M)	Limit @ 3 Meter (uV/M)
118.6	H	18.3	.8	11.1	32.4	N/A		150
237.1	H	14.8	1.1	15.6	37.6	N/A		200
415	H	14.3	1.3	16.5	40.3	N/A		200
533.6	H	13.0	1.6	18.1	43.2	N/A		200
592.8	H	11.9	1.6	19.6	45.2	N/A		200
830.0	V	13.1	1.9	21.9	70.0	N/A		200

NOTES: