

FCC PART 15 SUBPART C TEST REPORT

for

2.4G Digital Two-Way Tour Guide System

Model No.: DCR-511

FCC ID: CINDCR-511

of

Applicant: Chiayo Electronics Co Ltd
Address: No.88, Chung Hsiao Street 2, Chiayi Taiwan

Tested and Prepared

by

Worldwide Testing Services (Taiwan) Co., Ltd.

FCC Registration No.: 930600

Industry Canada filed test laboratory Reg. No. IC 5679A-1

A2LA Accredited No.: 2732.01



Report No.: W6M21406-14253-C-1

6F, NO. 58, LANE 188, RUEY-KUANG RD., NEIHU TAIPEI 114, TAIWAN, R.O.C.
TEL: 886-2-66068877 FAX: 886-2-66068879 E-mail: wts@wts-lab.com



TABLE OF CONTENTS

1	GENERAL INFORMATION	2
1.1	NOTES.....	2
1.2	TESTING LABORATORY	3
1.2.1	Location	3
1.2.2	Details of accreditation status	3
1.3	DETAILS OF APPROVAL HOLDER.....	3
1.4	APPLICATION DETAILS	4
1.5	GENERAL INFORMATION OF TEST ITEM	4
1.6	TEST STANDARDS.....	5
2	TECHNICAL TEST	6
2.1	SUMMARY OF TEST RESULTS	6
2.2	TEST ENVIRONMENT	6
2.3	TEST EQUIPMENT LIST	7
2.4	GENERAL TEST PROCEDURE	9
3	TEST RESULTS (ENCLOSURE)	11
3.1	PEAK OUTPUT POWER (TRANSMITTER)	12
3.2	EQUIVALENT ISOTROPIC RADIATED POWER.....	15
3.3	RF EXPOSURE COMPLIANCE REQUIREMENTS	15
3.4	TRANSMITTER RADIATED EMISSIONS IN RESTRICTED BANDS.....	16
3.5	SPURIOUS EMISSIONS (TX)	17
3.6	RADIATED EMISSION ON THE BAND EDGE	22
3.7	MINIMUM 6 dB BANDWIDTH	24
3.8	PEAK POWER SPECTRAL DENSITY	27
3.9	RADIATED EMISSION FROM RECEIVER PART.....	30
3.10	POWER LINE CONDUCTED EMISSION	33
	APPENDIX.....	25



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21406-14253-C-1

FCC ID: CINDCR-511

1 General Information

1.1 Notes

The purpose of conformity testing is to increase the probability of adherence to the essential requirements or conformity specifications, as appropriate.

The complexity of the technical specifications, however, means that full and thorough testing is impractical for both technical and economic reasons.

Furthermore, there is no guarantee that a test sample which has passed all the relevant tests conforms to a specification.

Neither is there any guarantee that such a test sample will interwork with other genuinely open systems.

The existence of the tests nevertheless provides the confidence that the test sample possesses the qualities as maintained and that its performance generally conforms to representative cases of communications equipment.

The test results of this test report relate exclusively to the item tested as specified in 1.5.

The test report may only be reproduced or published in full.

Reproduction or publication of extracts from the report requires the prior written approval of the Worldwide Testing Services(Taiwan) Co., Ltd.

Specific Conditions:

Usage of the hereunder tested device in combination with other integrated or external antennas requires at least additional output power measurements, spurious emission measurements, conducted emission measurements (AC supply lines) and radio frequency exposure evaluations for each individual configuration performed, for certification by FCC.

Tester:

July 11, 2014

Robert Ren

Date

WTS-Lab.

Name

Signature

Technical responsibility for area of testing:

July 11, 2014


Kevin Wang

Date

WTS

Name

Signature



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21406-14253-C-1

FCC ID: CINDCR-511

1.2 Testing laboratory

1.2.1 Location

OATS

No.5-1, Lishui, Shuang Sing Village,

Wanli Dist., New Taipei City 207,

Taiwan (R.O.C.)

3 meter semi-anechoic chamber

No.35, Aly. 21, Ln. 228, Ankang Rd., Neihu Dist., Taipei City 114, Taiwan (R.O.C.)

TEL:886-2-6613-0228

FAX:886-2-2791-5046

Company

Worldwide Testing Services(Taiwan) Co., Ltd.

6F, NO. 58, LANE 188, RUEY-KUANG RD.

NEIHU, TAIPEI 114, TAIWAN R.O.C.

Tel : 886-2-66068877

Fax : 886-2-66068879

1.2.2 Details of accreditation status

Accredited testing laboratory

A2LA accredited number: 2732.01

FCC filed test laboratory Reg. No. 930600

Industry Canada filed test laboratory Reg. No. IC 5679A-1



Test location, where different from Worldwide Testing Services (Taiwan) Co., Ltd. :

Name: ./.

Accredited number: ./.

Street: ./.

Town: ./.


Country: ./.

Telephone: ./.

Fax: ./.

1.3 Details of approval holder

Name: Chiayo Electronics Co Ltd
Street: No.88, Chung Hsiao Street 2,
Town: Chiayi
Country: Taiwan
Telephone: +886-5-271-1000
Fax: +886-5-276-7611



Registration number: W6M21406-14253-C-1
FCC ID: CINDCR-511

1.4 Application details

Date of receipt of test item: June 10, 2014
Date of test: from June 11, 2014 to July 11, 2014

1.5 General information of Test item


Type of test item: 2.4G Digital Two-Way Tour Guide System
Model Number: DCR-511
Brand Name: CHIAYO
Multi-listing model number: ./.
Photos: see Appendix

Technical data

Frequency band: 2403 MHz–2478 MHz
Frequency (ch 1 or A): 2403 MHz
Frequency (ch 13 or B): 2439 MHz
Frequency (ch 26 or C): 2478 MHz
Number of Channels: 26
Operation modes: Semi-duplex
Modulation Type: GFSK

Fixed point-to-point operation: ☐ Yes / ☒ No
Type of Antenna: Spiral antenna
Antenna gain: 2.7 dBi
Power supply: Adaptor (I/P:100-240V~50/60Hz, 0.2A ; O/P:5V, 1A)
Battery 3.7V, 1200mAh, 4.44Wh

Emission designator: 3M13F7D
Host device: none



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21406-14253-C-1

FCC ID: CINDCR-511

Classification :

Fixed Device	☐
Mobile Device (Human Body distance > 20cm)	☒
Portable Device (Human Body distance < 20cm)	☐

Transmitter

Unom

Power (ch 1 or A):

Conducted: 15.30 dBm

Power (ch 13 or B):

Conducted: 16.09 dBm

Power (ch 26 or C):

Conducted: 16.15 dBm

Manufacturer: (if applicable)

Name: ./.

Street: ./.


Town: ./.

Country: ./.

Additional information: ./.

1.6 Test standards

Technical standard : FCC RULES PART 15 SUBPART C § 15.247 (2013-10)



Registration number: W6M21406-14253-C-1
FCC ID: CINDCR-511

2 Technical test

2.1 Summary of test results

No deviations from the technical specification(s) were ascertained in the course of the tests performed.



or

The deviations as specified in 2.5 were ascertained in the course of the tests performed.



2.2 Test environment


Temperature: 23 °C

Relative humidity content: 20 ... 75 %

Air pressure: 86 ... 103 kPa

Power supply: Adaptor (I/P:100-240V~50/60Hz, 0.2A ; O/P:5V, 1A)
Battery 3.7V, 1200mAh, 4.44Wh

Extreme conditions parameters: ./.




Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21406-14253-C-1

FCC ID: CINDCR-511

2.3 Test Equipment List

No.	Test equipment	Type	Serial No.	Manufacturer	Cal. Date	Next Cal. Date
ETSTW-CE 001	EMI TEST RECEIVER	ESHS10	842121/013	R&S	2013/9/2	2014/9/1
ETSTW-CE 003	AC POWER SOURCE	APS-9102	D161137	GW	Function Test	
ETSTW-CE 008	HF-EICHLITUNG RF STEP ATTENUATOR 139dB DPSP	334.6010.02	844581/024	R&S	Function Test	
ETSTW-CE 009	TEMP.&HUMIDITY CHAMBER	GTH-225-40-1P-U	MAA0305-009	GIANT FORCE	2014/7/9	2015/7/8
ETSTW-CE 016	TWO-LINE V-NETWORK	ENV216	100050	R&S	2013/10/28	2014/10/27
ETSTW-RE 004	EMI TEST RECEIVER	ESI 40	832427/004	R&S	2013/9/2	2014/9/1
ETSTW-RE 005	EMI TEST RECEIVER	ESVS10	843207/020	R&S	2013/9/2	2014/9/1
ETSTW-RE 012	TUNABLE BANDREJECT FILTER	D.C 0309	146	K&L	Function Test	
ETSTW-RE 013	TUNABLE BANDREJECT FILTER	D.C 0336	397	K&L	Function Test	
ETSTW-RE 018	MICROWAVE HORN ANTENNA	AT4560	27212	AR	2013/10/15	2014/10/14
ETSTW-RE 027	Passive Loop Antenna	6512	00034563	ETS-Lindgren	2014/7/01	2015/6/30
ETSTW-RE 030	Double-Ridged Guide Horn Antenna	3117	00035224	EMCO	2014/2/25	2015/2/24
ETSTW-RE 045	ESA-E SERIES SPECTRUM ANALYZER	E4404B	MY45111242	Agilent	Pre-test Use	
ETSTW-RE 049	TRILOG Super Broadband test Antenna	VULB 9160	9160-3185	Schwarzbeck	2014/2/18	2015/2/17
ETSTW-RE 050	Attenuator 10dB	50HF-010-1	None	JFW	2014/3/3	2015/3/2
ETSTW-RE 051	Attenuator 6dB	50HF-006-1	None	JFW	2014/3/3	2015/3/2
ETSTW-RE 053	Attenuator 3dB	50HF-003-1	None	JFW	2014/3/3	2015/3/2
ETSTW-RE 055	SPECTRUM ANALYZER	FSU 26	200074	R&S	2014/6/05	2015/6/04
ETSTW-RE 060	Attenuator 30dB	5015-30	F651012z-01	ATM	2014/3/3	2015/3/2
ETSTW-RE 062	Amplifier Module	CHC 2	None	KMIC	2013/11/27	2014/11/26
ETSTW-RE 064	Bluetooth Test Set	MT8852B-042	6K00005709	Anritsu	Function Test	
ETSTW-RE 069	Double-Ridged Guide Horn Antenna	3117	00069377	EMCO	Function Test	
ETSTW-RE 072	CELL SITE TEST SET	8921A	3339A00375	HP	2013/10/7	2014/10/6
ETSTW-RE 088	SOLID STATE AMPLIFIER	KMA180265A01	99057	KMIC	2013/10/11	2014/10/10
ETSTW-RE 099	DC Block	50DB-007-1	None	JFW	2014/3/3	2015/3/2
ETSTW-RE 106	Humidity Temperature Meter	TES-1366	091011113	TES	2013/12/04	2014/12/03
ETSTW-RE 111	TRILOG Super Broadband test Antenna	VULB 9160	9160-3309	Schwarz beck	2013/12/27	2014/12/26
ETSTW-RE 112	AC POWER SOURCE	TFC-1005	None	T-Power	Function test	
ETSTW-RE 115	2.4GHz Notch Filter	N0124411	473874	MICROWAVE CIRCUITS	2014/1/10	2015/1/09
ETSTW-RE 120	RF Player	MP9200	MP9210-111022	ADIVIC	Function test	
ETSTW-RE 122	SIGNAL GENERATOR	SMF100A	102149	R&S	2014/6/11	2015/6/10
ETSTW-RE 125	5GHz Notch filter	5NSL11-5200/E221.3-O/O	1	K&L Microwave	2013/8/16	2014/8/15




Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21406-14253-C-1

FCC ID: CINDCR-511

ETSTW-RE 126	5GHz Notch filter	5NSL11-5800/E221.3-O/O	1	K&L Microwave	2013/8/16	2014/8/15
ETSTW-RE 127	RF Switch Box	RFS-01	None	WTS	2014/3/3	2015/3/2
ETSTW-RE 128	5.3GHz Notch filter	N0153001	SN487233	Microwave Circits	2013/8/13	2014/8/12
ETSTW-RE 129	5.5GHz Notch filter	N0555984	SN487234	Microwave Circits	2013/8/13	2014/8/12
ETSTW-RE 130	Handheld RF Spectrum Analyzer	N9340A	CN0147000204	Agilent	Pre-test Use	
ETSTW-GSM 002	Universal Radio Communication Tester	CMU 200	109439	R&S	2013/10/7	2014/10/6
ETSTW-GSM 019	Band Reject Filter	WRCTF824/849-822/851-40 /12+9SS	3	WI	2014/1/10	2015/1/09
ETSTW-GSM 020	Band Reject Filter	WRCD1747/1748-1743/1752-32/5SS	1	WI	2014/1/10	2015/1/09
ETSTW-GSM 021	Band Reject Filter	WRCD1879.5/1880.5-1875.5/1884.5-32/5SS	3	WI	2014/1/10	2015/1/09
ETSTW-GSM 022	Band Reject Filter	WRCT901.9/903.1-904.25-50/8SS	1	WI	2014/1/10	2015/1/09
ETSTW-GSM 023	Power Divider	4901.19.A	None	SUHNER	2013/9/18	2014/9/17
ETSTW-Cable 010	BNC Cable	5 M BNC Cable	None	JYE BAO CO.,LTD.	2014/2/27	2015/2/26
ETSTW-Cable 011	BNC Cable	BNC Cable 1	None	JYE BAO CO.,LTD.	Pre-test Use NCR	
ETSTW-Cable 012	N TYPE To SMA Cable	Cable 012	None	JYE BAO CO.,LTD.	2014/2/27	2015/2/26
ETSTW-Cable 016	BNC Cable	Switch Box	B Cable 1	Schwarz beck	2014/2/27	2015/2/26
ETSTW-Cable 017	BNC Cable	X Cable	B Cable 2	Schwarz beck	2014/2/27	2015/2/26
ETSTW-Cable 018	BNC Cable	Y Cable	B Cable 3	Schwarz beck	2014/2/27	2015/2/26
ETSTW-Cable 019	BNC Cable	Z Cable	B Cable 4	Schwarz beck	2014/2/27	2015/2/26
ETSTW-Cable 022	N TYPE Cable	5006	0002	JYE BAO CO.,LTD.	2014/2/19	2015/2/18
ETSTW-Cable 026	Microwave Cable	SUCOFLEX 104	279075	HUBER+SUHNER	2014/3/3	2015/3/2
ETSTW-Cable 027	Microwave Cable	SUCOFLEX 104	279083	HUBER+SUHNER	2014/3/3	2015/3/2
ETSTW-Cable 028	Microwave Cable	FA147A0015M2020	30064-2	UTIFLEX	2013/10/11	2014/10/10
ETSTW-Cable 029	Microwave Cable	FA147A0015M2020	30064-3	UTIFLEX	2013/10/11	2014/10/10
ETSTW-Cable 030	Microwave Cable	SUCOFLEX 104 (S_Cable 9)	279067	HUBER+SUHNER	2014/3/3	2015/3/2
ETSTW-Cable 031	Microwave Cable	SUCOFLEX 104 (S_Cable 10)	238092	HUBER+SUHNER	2013/11/27	2014/11/26
ETSTW-Cable 043	Microwave Cable	SUCOFLEX 104	317576	HUBER+SUHNER	2013/11/27	2014/11/26
ETSTW-Cable 047	Microwave Cable	SUCOFLEX 104	325518	HUBER+SUHNER	2013/11/27	2014/11/26
ETSTW-Cable 053	N TYPE To SMA Cable	RG142	None	JYE BAO CO.,LTD.	2014/2/19	2015/2/18
ETSTW-Cable 058	Microwave Cable	SUCOFLEX 104	none	HUBER+SUHNER	2014/2/19	2015/2/18
WTSTW-SW 002	EMI TEST SOFTWARE	EZ EMC	None	Farad	Version ETS-03A1	



Registration number: W6M21406-14253-C-1
FCC ID: CINDCR-511

2.4 General Test Procedure

POWER LINE CONDUCTED INTERFERENCE: The procedure used was ANSI STANDARD C63.4-2009 5.2 using a 50 μ H LISN (if necessary). Both lines were observed. The bandwidth of the spectrum analyzer was 10 kHz with an appropriate sweep speed.

RADIATION INTERFERENCE: The test procedure used was according to ANSI STANDARD C63.4-2009 6.4 employing a spectrum analyzer. For investigated frequency is equal to or below 1GHz, the RBW and VBW of the spectrum analyzer was 100 kHz and 100kHz respectively with an appropriate sweep speed. For investigated frequency is above 1GHz, both of RBW and VBW of the spectrum analyzer were 1 MHz with an appropriate sweep speed. The analyzer was calibrated in dB above a microvolt at the output of the antenna.

FORMULA OF CONVERSION FACTORS: The Field Strength at 3m was established by adding the meter reading of the spectrum analyzer (which is set to read in units of dB μ V) to the antenna correction factor supplied by the antenna manufacturer. The antenna correction factors are stated in terms of dB.

Example:

Freq (MHz)	METER READING + ACF + CABLE LOSS (to the receiver) = FS
33	20 dB μ V + 10.36 dB + 6 dB = 36.36 dB μ V/m @3m


The EUT was placed on a table 80 cm high and with dimensions of 1m by 1.5m (non metallic table) and arranged according to ANSI C63.4-2009 6.3.1. The table used for radiated measurements is capable of continuous rotation. The spectrum was scanned from 30 MHz to the frequency specified as follows:

- (1) If the intentional radiator operates below 10 GHz: to the tenth harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower.
- (2) If the intentional radiator operates at or above 10 GHz and below 30 GHz: to the fifth harmonic of the highest fundamental frequency or to 100 GHz, whichever is lower.
- (3) If the intentional radiator operates at or above 30 GHz: to the fifth harmonic of the highest fundamental frequency or to 200 GHz, whichever is lower, unless specified otherwise elsewhere in the rules.
- (4) If the intentional radiator contains a digital device, regardless of whether this digital device controls the functions of the intentional radiator or the digital device is used for additional control or function purposes other than to enable the operation of the intentional radiator, the frequency range shall be investigated up to the range specified in paragraphs (a)(1)-(a)(3) of this section or the range applicable to the digital device, as shown in paragraph (b)(1) of this Section, whichever is the higher frequency range of investigation.

For hand-held devices, a exploratory test was performed with three (3) orthogonal planes to determine the highest emissions.

Measurements were made by Worldwide Testing Services(Taiwan) Co., Ltd. at the registered open field test site located at No.5-1, Lishui, Shuang Sing Village, Wanli Dist., New Taipei City 207, Taiwan (R.O.C.). The Registration Number: 930600.

When an emission was found, the table was rotated to produce the maximum signal strength. At this point, the antenna was raised and lowered from 1m to 4m. The antenna was placed in both the horizontal and vertical planes.



Registration number: W6M21406-14253-C-1
FCC ID: CINDCR-511

When the radiated emission limits are expressed in terms of the average value of the emission, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.

The formula is as follows:


Average = Peak + Duty Factor

Duty Factor = $20 \log (\text{dwell time}/T)$

$T = 100\text{ms}$ when the pulse train period is over 100 ms or the period of the pulse train.

Modified Limits for peak according to 15.35 (b) = Max Permitted average Limits + 20dB

ANSI STANDARD C63.4-2009 10.2.7: Any measurements that utilize special test software shall be indicated and referenced in the test report. During testing, test software 'EZ EMC' was used for setting up different operation modes.



Registration number: W6M21406-14253-C-1

FCC ID: CINDCR-511

3 Test results (enclosure)

TEST CASE	Para. Number	Required	Test passed	Test failed
Peak Output Power	15.247(b)	☒	☒	☐
Equivalent isotropically radiated Power	15.247(b)	☒	☒	☐
Spurious Emissions radiated – Transmitter operating	15.247(c): 15.209	☒	☒	☐
Band Edge Measurement	15.247(d)	☒	☒	☐
Minimum 6 dB Bandwidth	15.247(a)(2)	☒	☒	☐
Peak Power Spectral Density	15.247(e)	☒	☒	☐
Radiated Emission from Receiver Part	15.109	☒	☒	☐
Power Line Conducted Emission	15.207	☒	☒	☐

The following is intentionally left blank.




Registration number: W6M21406-14253-C-1
FCC ID: CINDCR-511

3.1 Peak Output Power (transmitter)


FCC Rule: 15.247(b)(3)

This measurement applies to equipment with an integral antenna and to equipment with an antenna connector and equipped with an antenna as declared by the applicant.




MAX OUTPUT POWER 2403MHZ

Date: 11.JUN.2014 15:13:31




Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21406-14253-C-1
FCC ID: CINDCR-511



MAX OUTPUT POWER 2439MHZ
Date: 11.JUN.2014 15:12:26



MAX OUTPUT POWER 2478MHZ
Date: 11.JUN.2014 15:10:58




Registration number: W6M21406-14253-C-1
FCC ID: CINDCR-511

Limits:

Frequency MHz	Power dBm
902 - 928	30
2400 – 2483.5	30
5725 – 5850	30

In case of employing transmitter antennas having antenna gain > 6 dBi and using fixed point-to point operation consider §15.247 (b)(4)

Test equipment used: ETSTW-RE 055, ETSTW-RE 050



Registration number: W6M21406-14253-C-1

FCC ID: CINDCR-511

3.2 Equivalent isotropic radiated power

FCC Rule: 15.247(b)(3)

EIRP = max. conducted output power + antenna gain (Directional gain)

EIRP = 16.15 dBm + (2.7 dBi)

= 18.85 dBm

Limit: EIRP = +36 dBm for Antenna gain <6dBi

Test equipment used: ETSTW-RE 055

3.3 RF Exposure Compliance Requirements

FCC OET Bulletin 65 Edition 97.01 determines the equations for predicting RF fields and applicable limits.

The prediction for power density in the far-field but will over-predict power density in the near field, where it could be used for walking a “worst case” or conservative prediction.

$$S = \frac{PG}{4\pi R^2}$$

S – Power Density

P – Output power ERP

R – Distance

D – Cable Loss

AG – Antenna Gain

Item	Unit	Value	Remarks
P	mW	41.2097	Peak value
D	dB		
AG	dBi	2.7	
G		1.8620	Calculated Value
R	cm	20	Assumed value
S	mW/cm ²	0.0152	Calculated value

Limits:

Limit for General Population / Uncontrolled Exposure	
Frequency (MHz)	Power Density (mW/cm ²)
1500 – 100.000	1.0



Registration number: W6M21406-14253-C-1

FCC ID: CINDCR-511

3.4 Transmitter Radiated Emissions in Restricted Bands

FCC Rules: 15.247 (c), 15.205, 15.209, 15.35

Radiated emission measurements were performed from 30 MHz to 26500 MHz.

For radiated emission tests, the analyzer setting was as followings:

Frequency $\leq$ 1 GHz, RBW:100 kHz, VBW: 100 kHz (Peak measurements)

Frequency $>$ 1 GHz, RBW: 1 MHz, VBW: 1 MHz (Peak measurements)

Frequency $>$ 1 GHz , RBW:1 MHz , VBW: 10 Hz (Average measurements)

Limits.

For frequencies below 1GHz:

Frequency of Emission (MHz)	Field strength (microvolts/meter)	Field Strength (dB microvolts/meter)
30 - 88	100	40.0
88 - 216	150	43.5
216 - 960	200	46.0
Above	500	54.0

For frequencies above 1GHz (Average measurements).


Guidance on Measurement of Digit Transmission Systems:

“If the emission is pulsed, modify the unit for continuous operation, use the setting shown above, then correct the reading by subtracting the peak-average correction factor, derived from the appropriate duty cycle calculation.”

The correction factor, based on the total channel dwell time in a 100 ms period, may be mathematically applied to a measurement made with an average detector, to further reduce the value.

Duty cycle correction = $20 \log (\text{dwell time} / 100\text{ms})$

Note: No duty cycle correction was added to the reading of this EUT.



Registration number: W6M21406-14253-C-1

FCC ID: CINDCR-511

3.5 Spurious Emissions (tx)

Spurious emission was measured with modulation (declared by manufacturer).

In any 100 kHz bandwidth outside the frequency band in which the intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in § 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c))

FCC Rule: 15.247(c), 15.35

For out of band emissions that are close to or that exceed the 20 dB attenuation requirement described in the specification, radiated measurements were performed at a 3 m separation distance to determine whether these emissions complied with the general radiated emission requirement.

Limits:

For frequencies above 1GHz (Peak measurements).

Modified Limit for peak according to 15.35 (b) = Max Permitted average Limits + 20dB

For frequencies above 1GHz (Average measurements).

Max. reading – 20dB

Max. reading – 20 dB

Guidance on Measurement of Digit Transmission Systems:

“If the emission is pulsed, modify the unit for continuous operation, use the settings shown above, then correct the reading by subtracting the peak-average correction factor, derived from the appropriate duty cycle calculation.”

The correction factor, based on the total channel dwell time in a 100 ms period, may be mathematically applied to a measurement made with an average detector, to further reduce the value.

Duty Cycle correction = $20 \log (\text{dwell time}/100\text{ms})$

Note: No duty cycle correction was added to the reading of EUT.



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21406-14253-C-1

FCC ID: CINDCR-511

SAMPLE CALCULATION OF LIMIT. All results will be updated by an automatic measuring system in accordance with point 2.3.

Calculation of test results:

Such factors like antenna correction, cable loss, external attenuation etc. are already included in the provided measurement results. This is done by using validated test software and calibrated test system according the accreditation requirements.

The peak and average spurious emission plots was measured with the average limits.

In the Table being listed the critical peak and average value and exhibit the compliance with the above calculated Limits.


If in the column's correction factor states a value then the max. Field strength in the same row is corrected by a value gained from the "Correction Factor".

Summary table with radiated data of the test plots

Model: DCR-511 Date: 2014/7/8
 Mode: TX_2403MHz Temperature: 24 °C Engineer: Roy
 Polarization: Horizontal Humidity: 60 %

Frequency (MHz)	Reading (dBuV)	Detector	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
119.4188	24.23	peak	13.15	37.38	43.50	-6.12	190	100
239.9398	21.38	peak	14.16	35.54	46.00	-10.46	85	100

Frequency (MHz)	Reading (dBuV)		Factor (dB)	Result (dBuV/m)		Limit (dBuV/m)		Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
	Peak	Ave.	Corr.	Peak	Ave.	Peak	Ave.			
2186.5630	60.71	46.37	-5.72	54.99	40.65	74.00	54.00	-13.35	135	100
2306.5310	66.97	49.14	-5.20	61.77	43.94	74.00	54.00	-10.06	145	100
2330.5670	72.02	52.63	-5.07	66.95	47.56	74.00	54.00	-6.44	130	100
2354.5670	66.15	51.63	-4.93	61.22	46.70	74.00	54.00	-7.30	120	100
2378.6230	61.54	47.30	-4.79	56.75	42.51	74.00	54.00	-11.49	155	100
2521.0420	56.36	44.84	-4.30	52.06	40.54	74.00	54.00	-13.46	70	100
2593.1860	56.56	44.97	-4.15	52.41	40.82	74.00	54.00	-13.18	240	100
4801.6030	49.80	---	0.27	50.07	---	74.00	54.00	-23.93	300	100
7209.0000	41.23	---	3.84	45.07	---	74.00	54.00	-28.93	190	100
9612.0000	33.45	---	7.93	41.38	---	74.00	54.00	-32.62	55	100
12015.0000	32.91	---	12.69	45.60	---	74.00	54.00	-28.40	120	100



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21406-14253-C-1

FCC ID: CINDCR-511

Polarization: Vertical

Frequency (MHz)	Reading (dBuV)	Detector	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
216.6132	21.18	peak	12.66	33.84	46.00	-12.16	255	100
239.9400	16.90	peak	14.16	31.06	46.00	-14.94	95	100


Frequency (MHz)	Reading (dBuV)		Factor (dB) Corr.	Result (dBuV/m)		Limit (dBuV/m)		Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
	Peak	Ave.		Peak	Ave.	Peak	Ave.			
2306.5670	58.72	45.93	-5.20	53.52	40.73	74.00	54.00	-13.27	280	100
2330.5750	68.84	49.78	-5.07	63.77	44.71	74.00	54.00	-9.29	320	100
2354.5990	68.56	49.55	-4.93	63.63	44.62	74.00	54.00	-9.38	305	100
4805.0880	52.64	44.79	0.28	52.92	45.07	74.00	54.00	-8.93	140	100
7209.0000	40.39	---	3.84	44.23	---	74.00	54.00	-29.77	165	100
9612.0000	34.44	---	7.93	42.37	---	74.00	54.00	-31.63	105	100
12015.0000	33.32	---	12.69	46.01	---	74.00	54.00	-27.99	30	100

Mode: TX_2439MHz

Polarization: Horizontal

Frequency (MHz)	Reading (dBuV)	Detector	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
119.4188	24.19	peak	13.15	37.34	43.50	-6.16	170	100
360.4607	19.06	peak	17.45	36.51	46.00	-9.49	285	100

Frequency (MHz)	Reading (dBuV)		Factor (dB) Corr.	Result (dBuV/m)		Limit (dBuV/m)		Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
	Peak	Ave.		Peak	Ave.	Peak	Ave.			
2246.5830	61.74	45.91	-5.49	56.25	40.42	74.00	54.00	-13.58	185	100
2318.6230	62.85	46.93	-5.13	57.72	41.80	74.00	54.00	-12.20	100	100
2342.6030	62.57	49.09	-5.00	57.57	44.09	74.00	54.00	-9.91	90	100
2366.5670	72.74	51.21	-4.86	67.88	46.35	74.00	54.00	-7.65	105	100
2510.5390	64.77	47.19	-4.32	60.45	42.87	74.00	54.00	-11.13	130	100
2534.5750	57.95	45.97	-4.27	53.68	41.70	74.00	54.00	-12.30	170	100
2654.5920	57.63	45.21	-4.12	53.51	41.09	74.00	54.00	-12.91	160	100
4873.7480	51.16	---	0.45	51.61	---	74.00	54.00	-22.39	155	100
7317.0000	38.34	---	3.64	41.98	---	74.00	54.00	-32.02	265	100
9756.0000	33.77	---	8.26	42.03	---	74.00	54.00	-31.97	90	100
12195.0000	32.98	---	13.71	46.69	---	74.00	54.00	-27.31	200	100



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21406-14253-C-1

FCC ID: CINDCR-511

Polarization: Vertical

Frequency (MHz)	Reading (dBuV)	Detector	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
216.6132	21.94	peak	12.66	34.60	46.00	-11.40	165	100
455.7114	12.81	peak	20.12	32.93	46.00	-13.07	110	100


Frequency (MHz)	Reading (dBuV)		Factor (dB) Corr.	Result (dBuV/m)		Limit (dBuV/m)		Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
	Peak	Ave.		Peak	Ave.	Peak	Ave.			
2222.6150	58.15	46.12	-5.60	52.55	40.52	74.00	54.00	-13.48	275	100
2318.5190	59.72	46.06	-5.13	54.59	40.93	74.00	54.00	-13.07	125	100
2342.5670	61.73	47.74	-5.00	56.73	42.74	74.00	54.00	-11.26	285	100
2366.6110	67.07	49.91	-4.86	62.21	45.05	74.00	54.00	-8.95	140	100
2534.5590	56.74	44.28	-4.27	52.47	40.01	74.00	54.00	-13.99	170	100
4877.0790	56.56	43.75	0.46	57.02	44.21	74.00	54.00	-9.79	320	100
7317.0000	39.91	---	3.64	43.55	---	74.00	54.00	-30.45	75	100
9751.5030	42.36	---	8.23	50.59	---	74.00	54.00	-23.41	45	100
12195.0000	32.01	---	13.71	45.72	---	74.00	54.00	-28.28	170	100

Mode: TX_2478MHz

Polarization: Horizontal

Frequency (MHz)	Reading (dBuV)	Detector	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
119.4188	24.13	peak	13.15	37.28	43.50	-6.22	185	100
239.9398	21.68	peak	14.16	35.84	46.00	-10.16	130	100

Frequency (MHz)	Reading (dBuV)		Factor (dB) Corr.	Result (dBuV/m)		Limit (dBuV/m)		Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
	Peak	Ave.		Peak	Ave.	Peak	Ave.			
2238.4770	60.92	47.04	-5.53	55.39	41.51	74.00	54.00	-12.49	140	100
2286.5730	58.90	46.36	-5.30	53.60	41.06	74.00	54.00	-12.94	220	100
2358.7170	62.58	47.41	-4.91	57.67	42.50	74.00	54.00	-11.50	135	100
2527.0540	63.76	47.79	-4.29	59.47	43.50	74.00	54.00	-10.50	230	100
2551.1020	63.74	47.72	-4.24	59.50	43.48	74.00	54.00	-10.52	215	100
2575.1500	57.59	46.01	-4.19	53.40	41.82	74.00	54.00	-12.18	175	100
4953.9080	50.89	43.28	0.84	51.73	44.12	74.00	54.00	-9.88	290	100
7434.0000	40.31	---	3.93	44.24	---	74.00	54.00	-29.76	230	100
9912.0000	33.30	---	8.51	41.81	---	74.00	54.00	-32.19	275	100
12390.0000	31.36	---	14.46	45.82	---	74.00	54.00	-28.18	210	100



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21406-14253-C-1

FCC ID: CINDCR-511

Polarization: Vertical

Frequency (MHz)	Reading (dBuV)	Detector	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
216.6132	21.09	peak	12.66	33.75	46.00	-12.25	225	100
239.9400	16.64	peak	14.16	30.80	46.00	-15.20	305	100

Frequency (MHz)	Reading (dBuV)		Factor (dB) Corr.	Result (dBuV/m)		Limit (dBuV/m)		Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
	Peak	Ave.		Peak	Ave.	Peak	Ave.			
2358.7170	59.21	46.50	-4.91	54.30	41.59	74.00	54.00	-12.41	270	100
2527.0540	60.88	47.07	-4.29	56.59	42.78	74.00	54.00	-11.22	285	100
2551.1020	58.77	45.68	-4.24	54.53	41.44	74.00	54.00	-12.56	125	100
2575.1500	56.12	44.97	-4.19	51.93	40.78	74.00	54.00	-13.22	145	100
4953.9080	53.64	41.68	0.84	54.48	42.52	74.00	54.00	-11.48	335	100
7438.8780	44.06	---	3.93	47.99	---	74.00	54.00	-26.01	300	100
9913.3270	42.16	---	8.51	50.67	---	74.00	54.00	-23.33	30	100
12390.0000	31.70	---	14.46	46.16	---	74.00	54.00	-27.84	105	100

Note

1. Correction Factor = Antenna factor + Cable loss - Preamplifier
2. The formula of measured value as: Test Result = Reading + Correction Factor
3. Detector function in the form : PK = Peak, QP = Quasi Peak, AV = Average
4. All not in the table noted test results are more than 20 dB below the relevant limits.
5. Measurement uncertainty for 3m measurement: 30-1000 MHz = ± 3.68 dB, 1-18 GHz = ± 5.37 dB, 18-40 GHz = ± 3.43 dB ; Reported uncertainties represent expanded uncertainties expressed at approximately the 95% confidence level using a coverage factor of k = 2.
6. See attached diagrams in appendix.

TEST RESULT (Transmitter): The unit DOES meet the FCC requirements.

Test equipment used: ETSTW-RE 004, ETSTW-RE 030, ETSTW-RE 111,
ETSTW-RE 088, ETSTW-RE 018




Registration number: W6M21406-14253-C-1
FCC ID: CINDCR-511

3.6 Radiated Emission on the band edge


According to FCC rules part 15 subpart C §15.247(d) in any 100 kHz bandwidth outside the frequency band in which the intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in § 15.209(a) is not required.

In addition radiated emission which fall in the restricted bands, as defined in section 15.205(a), must also with the radiated emission limits.




BANDEGE 2403MHZ

Date: 11.JUN.2014 15:25:11



Registration number: W6M21406-14253-C-1

FCC ID: CINDCR-511




BANDEDGE 2478MHZ

Date: 11.JUN.2014 15:23:55

Limit:

Frequency Range / MHz	Limit
902 – 928	- 20 dB
2400 – 2483.5	
5725 - 5850	


Test equipment used: ETSTW-RE 055, ETSTW-RE 050



Registration number: W6M21406-14253-C-1
FCC ID: CINDCR-511


3.7 Minimum 6 dB Bandwidth

The analyzer ResBW was set to 100 kHz. For each RF output channel investigated, the spectrum analyzer center frequency was set to the channel carrier. A PEAK reading was taken, two markers were set 6 dB below the maximum level on the right and the left side of the emission.
The 6 dB bandwidth is the frequency difference between the two markers.




6DB BANDWIDTH 2403MHZ

Date: 11.JUN.2014 15:07:33




Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21406-14253-C-1
FCC ID: CINDCR-511



6DB BANDWIDTH 2439MHZ
Date: 11.JUN.2014 15:06:27



6DB BANDWIDTH 2478MHZ
Date: 11.JUN.2014 15:08:58




Registration number: W6M21406-14253-C-1
FCC ID: CINDCR-511

Limits:

Frequency Range MHz	Limits
902-928	min 500 kHz
2400-2483.5	min 500 kHz
5725-5850	min 500 kHz


Test equipment used: ETSTW-RE 055, ETSTW-RE 050



Registration number: W6M21406-14253-C-1
FCC ID: CINDCR-511


3.8 Peak Power Spectral Density

Peak Power Spectral density is a measured at low, middle and high channel.
The peak output power is measured with a measurement bandwidth of 10 MHz and displayed on diagram together with Peak Power Spectral Density result which was measured with a bandwidth of 3 kHz, appreciate frequency span and sweep time.




POWER DENSITY 2403MHZ


Date: 11.JUN.2014 15:16:51




Registration number: W6M21406-14253-C-1
FCC ID: CINDCR-511



POWER DENSITY 2439MHZ
Date: 11.JUN.2014 15:18:00



POWER DENSITY 2478MHZ
Date: 11.JUN.2014 15:18:58




Registration number: W6M21406-14253-C-1

FCC ID: CINDCR-511

Limits:

Frequency Range MHz	dBm
902-928	8
2400-2483.5	8
5725-5850	8

Test equipment used: ETSTW-RE 055, ETSTW-RE 050



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21406-14253-C-1

FCC ID: CINDCR-511

3.9 Radiated Emission from Receiver Part

FCC Rule: 15.109

Model: DCR-511

Date: 2014/7/8

Mode: RX_2403MHz

Temperature: 24 °C

Engineer: Roy

Polarization: Horizontal

Humidity: 60 %

Frequency (MHz)	Reading (dBuV)	Detector	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
119.4188	24.03	peak	13.15	37.18	43.50	-6.32	125	100
216.6132	19.99	peak	12.66	32.65	46.00	-13.35	300	100
239.9398	21.92	peak	14.16	36.08	46.00	-9.92	185	100
360.4607	19.82	peak	17.45	37.27	46.00	-8.73	235	100

Frequency (MHz)	Reading (dBuV)		Factor (dB)	Result (dBuV/m)		Limit (dBuV/m)		Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
	Peak	Ave.	Corr.	Peak	Ave.	Peak	Ave.			
4226.4530	41.51	---	-0.49	41.02	---	74.00	54.00	-32.98	45	100
5993.9880	40.12	---	2.70	42.82	---	74.00	54.00	-31.18	125	100

Polarization: Vertical


Frequency (MHz)	Reading (dBuV)	Detector	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
119.4188	16.50	peak	13.15	29.65	43.50	-13.85	240	100
216.6132	20.93	peak	12.66	33.59	46.00	-12.41	155	100
239.9400	16.52	peak	14.16	30.68	46.00	-15.32	295	100
335.1904	13.88	peak	16.91	30.79	46.00	-15.21	60	100

Frequency (MHz)	Reading (dBuV)		Factor (dB)	Result (dBuV/m)		Limit (dBuV/m)		Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
	Peak	Ave.	Corr.	Peak	Ave.	Peak	Ave.			
4044.0880	41.53	---	-0.95	40.58	---	74.00	54.00	-33.42	165	100
5320.6410	40.83	---	2.21	43.04	---	74.00	54.00	-30.96	270	100

Mode: RX_2439MHz

Polarization: Horizontal

Frequency (MHz)	Reading (dBuV)	Detector	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
119.4188	24.07	peak	13.15	37.22	43.50	-6.28	190	100
239.9398	21.87	peak	14.16	36.03	46.00	-9.97	100	100
360.4607	19.58	peak	17.45	37.03	46.00	-8.97	40	100
383.7875	18.00	peak	18.26	36.26	46.00	-9.74	250	100



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21406-14253-C-1

FCC ID: CINDCR-511

Frequency (MHz)	Reading (dBuV)		Factor (dB) Corr.	Result (dBuV/m)		Limit (dBuV/m)		Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
	Peak	Ave.		Peak	Ave.	Peak	Ave.			
4044.0880	41.41	---	-0.95	40.46	---	74.00	54.00	-33.54	70	100
5250.5010	40.61	---	1.93	42.54	---	74.00	54.00	-31.46	195	100

Polarization: Vertical

Frequency (MHz)	Reading (dBuV)	Detector	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
216.6132	20.91	peak	12.66	33.57	46.00	-12.43	265	100
239.9400	16.39	peak	14.16	30.55	46.00	-15.45	175	100
455.7114	12.15	peak	20.12	32.27	46.00	-13.73	220	100
624.8297	10.13	peak	23.39	33.52	46.00	-12.48	130	100


Frequency (MHz)	Reading (dBuV)		Factor (dB) Corr.	Result (dBuV/m)		Limit (dBuV/m)		Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
	Peak	Ave.		Peak	Ave.	Peak	Ave.			
4030.0600	41.53	---	-0.86	40.67	---	74.00	54.00	-33.33	155	100
6569.1380	38.88	---	3.98	42.86	---	74.00	54.00	-31.14	225	100

Mode: RX_2478MHz

Polarization: Horizontal

Frequency (MHz)	Reading (dBuV)	Detector	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
119.4188	24.35	peak	13.15	37.50	43.50	-6.00	90	100
239.9398	21.57	peak	14.16	35.73	46.00	-10.27	245	100
360.4607	19.56	peak	17.45	37.01	46.00	-8.99	165	100
383.7875	18.03	peak	18.26	36.29	46.00	-9.71	315	100

Frequency (MHz)	Reading (dBuV)		Factor (dB) Corr.	Result (dBuV/m)		Limit (dBuV/m)		Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
	Peak	Ave.		Peak	Ave.	Peak	Ave.			
4478.9580	42.04	---	-0.18	41.86	---	74.00	54.00	-32.14	80	100
6456.9140	39.81	---	3.64	43.45	---	74.00	54.00	-30.55	260	100



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21406-14253-C-1

FCC ID: CINDCR-511

Polarization: Vertical

Frequency (MHz)	Reading (dBuV)	Detector	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
119.4188	15.89	peak	13.15	29.04	43.50	-14.46	220	100
216.6132	21.33	peak	12.66	33.99	46.00	-12.01	115	100
239.9400	17.05	peak	14.16	31.21	46.00	-14.79	210	100
455.7114	12.52	peak	20.12	32.64	46.00	-13.36	35	100


Frequency (MHz)	Reading (dBuV)		Factor (dB)	Result (dBuV/m)		Limit (dBuV/m)		Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
	Peak	Ave.	Corr.	Peak	Ave.	Peak	Ave.			
4142.2840	42.55	---	-0.95	41.60	---	74.00	54.00	-32.40	100	100
5657.3150	40.51	---	1.83	42.34	---	74.00	54.00	-31.66	185	100

- Note**
1. Correction Factor = Antenna factor + Cable loss - Preamplifier
 2. The formula of measured value as: Test Result = Reading + Correction Factor
 3. Detector function in the form : PK = Peak, QP = Quasi Peak, AV = Average
 4. All not in the table noted test results are more than 20 dB below the relevant limits.
 5. Measurement uncertainty for 3m measurement: 30-1000 MHz = ± 3.68 dB, 1-18 GHz = ± 5.37 dB, 18-40 GHz = ± 3.43 dB ; Reported uncertainties represent expanded uncertainties expressed at approximately the 95% confidence level using a coverage factor of k = 2.
 6. See attached diagrams in appendix.

Except for Class A digital devices, the field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values:

Frequency of Emission (MHz)	Field Strength (microvolts/meter)	Field Strength (dBmicrovolts/meter)
30 – 88	100	40.0
88 – 216	150	43.5
216 – 960	200	46.0
Above 960	500	54.0

Test equipment used: ETSTW-RE 055, ETSTW-RE 064, ETSTW-RE 003, ETSTW-RE 004, ETSTW-RE 030, ETSTW-RE 111




Registration number: W6M21406-14253-C-1

FCC ID: CINDCR-511


3.10 Power Line Conducted Emission

For an intentional radiator which is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the table bellows with this provision shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminals.

This measurement was transact first with instrumentation using an average and peak detector and a 10 kHz bandwidth. If the peak detector achieves a calculated level, the measurement is repeated by an instrumentation using a quasi-peak detector.




Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corrected factor(dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Comment
	0.2921	29.14	QP	9.67	38.81	60.46	-21.65	
	0.2921	15.29	AVG	9.67	24.96	50.46	-25.50	
*	0.3651	28.99	QP	9.68	38.67	58.61	-19.94	
	0.3651	10.98	AVG	9.68	20.66	48.61	-27.95	
	0.5517	22.32	QP	9.68	32.00	56.00	-24.00	
	0.5517	6.71	AVG	9.68	16.39	46.00	-29.61	
	1.0040	24.67	QP	9.70	34.37	56.00	-21.63	
	1.0040	12.14	AVG	9.70	21.84	46.00	-24.16	
	1.4113	24.95	QP	9.72	34.67	56.00	-21.33	
	1.4113	14.78	AVG	9.72	24.50	46.00	-21.50	
	4.9348	21.90	QP	9.86	31.76	56.00	-24.24	
	4.9348	14.74	AVG	9.86	24.60	46.00	-21.40	



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21406-14253-C-1

FCC ID: CINDCR-511



Site : Chamber_03

Condition : FCC Part 15 Class B Conduction (QP)

EUT : W6M21406-14253

M/N: DCR-511

Test Mode :

Note :

Phase: L1

Power : 120 V.a.c.

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corrected factor(dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Comment
*	0.3503	30.90	QP	9.67	40.57	58.96	-18.39	
	0.3503	18.30	AVG	9.67	27.97	48.96	-20.99	
	0.3791	23.56	QP	9.67	33.23	58.30	-25.07	
	0.3791	10.29	AVG	9.67	19.96	48.30	-28.34	
	1.0444	23.38	QP	9.70	33.08	56.00	-22.92	
	1.0444	12.24	AVG	9.70	21.94	46.00	-24.06	
	1.3933	24.77	QP	9.72	34.49	56.00	-21.51	
	1.3933	14.64	AVG	9.72	24.36	46.00	-21.64	
	1.9625	19.89	QP	9.75	29.64	56.00	-26.36	
	1.9625	10.52	AVG	9.75	20.27	46.00	-25.73	
	4.9078	23.02	QP	9.84	32.86	56.00	-23.14	
	4.9078	14.25	AVG	9.84	24.09	46.00	-21.91	

Note: 1. The formula of measured value as: Test Result = Reading + Correction Factor


2. The Correction Factor = Cable Loss + LISN Insertion Loss + Pulse Limit Loss

3. Detector function in the form : PK = Peak, QP = Quasi Peak, AV = Average

4. All not in the table noted test results are more than 20 dB below the relevant limits.

5. Measurement uncertainty = ± 1.41 dB; Reported uncertainties represent expanded uncertainties expressed at approximately the 95% confidence level using a coverage factor of $k = 2$.

6. Up Line: QP Limit Line, Down Line: Ave Limit Line.



Worldwide Testing Services(Taiwan) Co., Ltd.


Registration number: W6M21406-14253-C-1

FCC ID: CINDCR-511

Limits:

Frequency of Emission (MHz)	Conducted Limit (dBuV)	
	Quasi Peak	Average
0.15-0.5	66 to 56	56 to 46
0.5-5	56	46
5-30	60	50

Test equipment used: ETSTW-CE 001, ETSTW-CE 016, ETSTW-CE 006, ETSTW-RE 045




Appendix

A Measurement diagrams

Spurious Emissions radiated

B Photos

1. External Photos
2. Internal Photos
3. Set Up Photo of Radiated Emission
4. Set Up Photo of Conducted Emission




Registration number: W6M21406-14253-C-1

FCC ID: CINDCR-511

Spurious Emissions radiated_TX

TX_2403 MHz


Antenna Polarization H



Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:



1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21406-14253-C-1


FCC ID: CINDCR-511



Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:


1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21406-14253-C-1


FCC ID: CINDCR-511



Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:

1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.




Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21406-14253-C-1

FCC ID: CINDCR-511


Antenna Polarization V



Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:



1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21406-14253-C-1


FCC ID: CINDCR-511



Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:



1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21406-14253-C-1


FCC ID: CINDCR-511



Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:

1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.




Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21406-14253-C-1

FCC ID: CINDCR-511

TX_2439 MHz


Antenna Polarization H



Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:



1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21406-14253-C-1


FCC ID: CINDCR-511



Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:



1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21406-14253-C-1


FCC ID: CINDCR-511



Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:


1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.



Registration number: W6M21406-14253-C-1

FCC ID: CINDCR-511


Antenna Polarization V



Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:



1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21406-14253-C-1


FCC ID: CINDCR-511



Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:



1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21406-14253-C-1


FCC ID: CINDCR-511



Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:

1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.




Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21406-14253-C-1

FCC ID: CINDCR-511

TX_2478 MHz


Antenna Polarization H



Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:



1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21406-14253-C-1


FCC ID: CINDCR-511



Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:



1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21406-14253-C-1


FCC ID: CINDCR-511



Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:


1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21406-14253-C-1
FCC ID: CINDCR-511


Antenna Polarization V



Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:


1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21406-14253-C-1


FCC ID: CINDCR-511



Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:



1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21406-14253-C-1


FCC ID: CINDCR-511



Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:

1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.




Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21406-14253-C-1
FCC ID: CINDCR-511

Spurious Emissions radiated_RX

RX_2403 MHz


Antenna Polarization H



Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:



1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21406-14253-C-1


FCC ID: CINDCR-511



Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:


1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.




Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21406-14253-C-1

FCC ID: CINDCR-511




Antenna Polarization V



Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:



1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21406-14253-C-1


FCC ID: CINDCR-511



Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:



1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21406-14253-C-1


FCC ID: CINDCR-511



Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:

1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.




Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21406-14253-C-1

FCC ID: CINDCR-511

RX_2439 MHz


Antenna Polarization H



Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:



1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21406-14253-C-1


FCC ID: CINDCR-511



Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:


1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.




Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21406-14253-C-1

FCC ID: CINDCR-511




Antenna Polarization V



Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:



1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21406-14253-C-1


FCC ID: CINDCR-511



Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:



1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21406-14253-C-1


FCC ID: CINDCR-511



Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:

1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.




Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21406-14253-C-1

FCC ID: CINDCR-511

RX_2478 MHz


Antenna Polarization H



Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:



1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21406-14253-C-1


FCC ID: CINDCR-511



Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:


1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.




Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21406-14253-C-1

FCC ID: CINDCR-511




Antenna Polarization V



Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:



1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21406-14253-C-1


FCC ID: CINDCR-511



Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:



1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21406-14253-C-1

FCC ID: CINDCR-511



Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:

1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.