



FCC PART 15, SUBPART C
ISED RSS-247, ISSUE 1, MAY 2015

TEST AND MEASUREMENT REPORT

For

GoPro, Inc.

3000 Clearview Way,

San Mateo, CA 94402, USA

FCC ID: CNFHWMR1
IC: 10193A-HWMR1

Report Type: Original Report	Product Type: Wireless Video Camera
Jose Martinez Prepared By: Test Engineer	
<i>Jose de Jesus R. Martinez</i>	
Report Number: R1606032-247 DSS	
Report Date: 2016-08-18	
Bo Li Reviewed By: RF Lead	
<i>Bo Li</i>	
Bay Area Compliance Laboratories Corp. 1274 Anvilwood Avenue, Sunnyvale, CA 94089, USA Tel: (408) 732-9162 Fax: (408) 732-9164	

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. This report **must not** be used by the customer to claim product certification, approval, or endorsement by A2LA*, NIST, or any agency of the Federal Government.

* This report may contain data that are not covered by the A2LA accreditation and are marked with an asterisk “*” (Rev. 0)

TABLE OF CONTENTS

1 General Description.....	5
1.1 Product Description for Equipment Under Test (EUT)	5
1.2 Objective.....	5
1.3 Related Submittal(s)/Grant(s)	5
1.4 Test Methodology	5
1.5 Measurement Uncertainty	5
1.6 Test Facility Registrations	6
1.7 Test Facility Accreditations	6
2 System Test Configuration.....	10
2.1 Justification	10
2.2 EUT Exercise Software.....	10
2.3 Duty Cycle Correction Factor	10
2.4 Equipment Modifications.....	11
2.5 Local Support Equipment	11
2.6 Support Equipment	12
2.7 Interface Ports and Cabling.....	12
3 Summary of Test Results	13
4 FCC §15.203 & ISED RSS-Gen §8.3 - Antenna Requirements	14
4.1 Applicable Standards	14
4.2 Antenna Description	14
5 FCC §2.1093, §15.247(i) & ISED RSS-102 - RF Exposure	15
5.1 Applicable Standards	15
5.2 Test Results.....	15
6 FCC §15.207 & ISED RSS-Gen §8.8 - AC Line Conducted Emissions.....	16
6.1 Applicable Standards	16
6.2 Test Setup	16
6.3 Test Procedure	16
6.4 Corrected Amplitude & Margin Calculation.....	17
6.5 Test Setup Block Diagram	17
6.6 Test Equipment List and Details.....	18
6.7 Test Environmental Conditions	18
6.8 Summary of Test Results	18
6.9 Conducted Emissions Test Plots and Data.....	19
7 FCC §15.209, §15.247(d) & ISED RSS-247 §5.5, RSS-Gen §8.9, §8.10 - Spurious Radiated Emissions.....	21
7.1 Applicable Standards	21
7.2 Test Setup	23
7.3 Test Procedure	23
7.4 Corrected Amplitude & Margin Calculation.....	23
7.5 Test Equipment List and Details.....	24
7.6 Test Environmental Conditions	24
7.7 Summary of Test Results	25
7.8 Radiated Emissions Test Results	25
8 FCC §15.247(a) (1) & ISED RSS-247 §5.1, RSS-Gen §6.6 - Emission Bandwidth.....	31
8.1 Applicable Standards	31
8.2 Measurement Procedure.....	31
8.3 Test Equipment List and Details.....	31
8.4 Test Environmental Conditions	31
8.5 Test Results.....	32
9 FCC §15.247(b) (1) & ISED RSS-247 §5.4 -Output Power	36
9.1 Applicable Standards	36
9.2 Measurement Procedure.....	36
9.3 Test Equipment List and Details.....	36

9.4	Test Environmental Conditions	36
9.5	Test Results	37
10	FCC §15.247(d) & ISED RSS-247 §5.5 - 100 kHz Bandwidth of Band Edges	41
10.1	Applicable Standards	41
10.2	Measurement Procedure	41
10.3	Test Equipment List and Details	41
10.4	Test Environmental Conditions	42
10.5	Test Results	42
11	FCC §15.247(a) (1) (iii) & ISED RSS-247 §5.1 (4) - Dwell Time	44
11.1	Applicable Standards	44
11.2	Measurement Procedure	44
11.3	Test Equipment List and Details	45
11.4	Test Environmental Conditions	45
11.5	Test Results	46
12	FCC §15.247(a)(1)(iii) & ISED RSS-247 §5.1(4) - Number of Hopping Channels.....	65
12.1	Applicable Standards	65
12.2	Test Procedure	65
12.3	Test Equipment List and Details	65
12.4	Test Environmental Conditions	65
12.5	Test Results	65
13	FCC §15.247(a) (1) & ISED RSS-247 §5.1(2) - Hopping Channel Separation	67
13.1	Applicable Standards	67
13.2	Test Procedure	67
13.3	Test Equipment List and Details	67
13.4	Test Environmental Conditions	67
13.5	Test Results	68
14	FCC §15.247(d) & ISED RSS-247 §5.5 - Spurious Emissions at Antenna Terminals	72
14.1	Applicable Standards	72
14.2	Test Procedure	72
14.3	Test Equipment List and Details	72
14.4	Test Environmental Conditions	73
14.5	Test Results	73
15	Exhibit A - FCC & ISED Equipment Labeling Requirements.....	78
15.1	FCC ID Label Requirements	78
15.2	ISED Label Requirements	78
15.3	FCC ID & ISED Label Contents and Location	79
16	Exhibit B - Test Setup Photographs.....	80
16.1	Radiated Emission below 1 GHz Front View	80
16.2	Radiated Emission below 1 GHz Rear View	80
16.3	Radiated Emission above 1 GHz Front View	81
16.4	Radiated Emission above 1 GHz Rear View	81
16.5	AC Conducted Emissions Front View	82
16.6	AC Conducted Emissions Side View.....	82
17	Exhibit C - EUT Photographs	83
17.1	EUT – Front View	83
17.2	EUT – Back View	83
17.3	EUT – Left View	84
17.4	EUT – Right View	84
17.5	EUT – Top View.....	85
17.6	EUT – Bottom View	85
17.7	EUT – Open Case View.....	86
17.8	EUT – Main PCB Board – Top view	86
17.9	EUT – Main PCB board – Bottom View	87
17.10	EUT – Attachment 1 view	87
17.11	EUT – Attachment 2 view	88
17.12	EUT – Battery View	88

DOCUMENT REVISION HISTORY

Revision Number	Report Number	Description of Revision	Date of Revision
0	R1606032-247 DSS	Original Report	2016-08-18

1 General Description

1.1 Product Description for Equipment Under Test (EUT)

This test and measurement report was prepared on behalf of *GoPro, Inc.*, and their product model: *HWMR1*, FCC ID: CNFHWMR1; IC: 10193A-HWMR1 or the “EUT” as referred to in this report. It is a Wireless video camera.

1.2 Objective

This report is prepared on behalf of *GoPro, Inc.*, in accordance with Part 2, Subpart J, and Part 15, Subparts B and C of the Federal Communication Commission’s rules and IC RSS-247 Issue 1, MAY 2015.

The objective is to determine compliance with FCC Part 15.247 and IC RSS-247 rules for Output Power, Antenna Requirements, 20 dB Bandwidth, 100 kHz Bandwidth of Band Edges Measurement, Conducted and Radiated Spurious Emissions, Number of Hopping Channels, Dwell Time, and Hopping Channel Separation.

1.3 Related Submittal(s)/Grant(s)

FCC Part 15, Subpart C, Equipment DTS with FCC ID: CNFHWMR1;
FCC Part 15, Subpart E, Equipment NII with FCC ID: CNFHWMR1

1.4 Test Methodology

All measurements contained in this report were conducted in accordance with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

1.5 Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in the field of EMC. The factors contributing to uncertainties are spectrum analyzer, cable loss, antenna factor calibration, antenna directivity, antenna factor variation with height, antenna phase center variation, antenna factor frequency interpolation, measurement distance variation, site imperfections, mismatch (average), and system repeatability.

Parameter	Measurement uncertainty
Occupied Channel Bandwidth	±5 %
RF output power, conducted	±0.57 dB
Power Spectral Density, conducted	±1.48dB
Unwanted Emissions, conducted	±1.57dB
All emissions, radiated	±4.0 dB
AC power line Conducted Emission	±2.0 dB
Temperature	±2 ° C
Humidity	±5 %
DC and low frequency voltages	±1.0 %
Time	±2 %
Duty Cycle	±3 %

1.6 Test Facility Registrations

BACLs test facilities that are used to perform Radiated and Conducted Emissions tests are currently recognized by the Federal Communications Commission as Accredited with NIST Designation Number US1129.

BACL's test facilities that are used to perform Radiated and Conducted Emissions tests are currently registered with Industry Canada under Registration Numbers: 3062A-1, 3062A-2, and 3062A-3.

BACL is a Chinese Taipei Bureau of Standards Metrology and Inspection (BSMI) validated Conformity Assessment Body (CAB), under Appendix B, Phase I Procedures of the APEC Mutual Recognition Arrangement (MRA). BACL's BSMI Lab Code Number is: SL2-IN-E-1002R

BACL's test facilities that are used to perform AC Line Conducted Emissions, Telecommunications Line Conducted Emissions, Radiated Emissions from 30 MHz to 1 GHz, and Radiated Emissions from 1 GHz to 6 GHz are currently recognized as Accredited in accordance with the Voluntary Control Council for Interference [VCCI] Article 15 procedures under Registration Number A-0027.

1.7 Test Facility Accreditations

Bay Area Compliance Laboratories Corp. (BACL) is:

A- An independent, 3rd-Party, Commercial Test Laboratory accredited to ISO/IEC 17025:2005 by A2LA (Test Laboratory Accreditation Certificate Number 3279.02), in the fields of: Electromagnetic Compatibility and Telecommunications. Unless noted by an Asterisk (*) in the Compliance Matrix (See Section 3 of this Test Report), BACL's ISO/IEC 17025:2005 Scope of Accreditation includes all of the Test Method Standards and/or the Product Family Standards detailed in this Test Report..

BACL's ISO/IEC 17025:2005 Scope of Accreditation includes a comprehensive suite of EMC Emissions, EMC Immunity, Radio, RF Exposure, Safety and wireline Telecommunications test methods applicable to a wide range of product categories. These product categories include Central Office Telecommunications Equipment [including NEBS - Network Equipment Building Systems], Unlicensed and Licensed Wireless and RF devices, Information Technology Equipment (ITE); Telecommunications Terminal Equipment (TTE); Medical Electrical Equipment; Industrial, Scientific and Medical Test Equipment; Professional Audio and Video Equipment; Industrial and Scientific Instruments and Laboratory Apparatus; Cable Distribution Systems, and Energy Efficient Lighting.

B- A Product Certification Body accredited to ISO/IEC 17065:2012 by A2LA (Product Certification Body Accreditation Certificate Number 3279.03) to certify

- For the USA (Federal Communications Commission):
 - 1- All Unlicensed radio frequency devices within FCC Scopes A1, A2, A3, and A4;
 - 2- All Licensed radio frequency devices within FCC Scopes B1, B2, B3, and B4;
 - 3- All Telephone Terminal Equipment within FCC Scope C.
- For the Canada (Industry Canada):
 - 1 All Scope 1-Licence-Exempt Radio Frequency Devices;
 - 2 All Scope 2-Licensed Personal Mobile Radio Services;
 - 3 All Scope 3-Licensed General Mobile & Fixed Radio Services;
 - 4 All Scope 4-Licensed Maritime & Aviation Radio Services;
 - 5 All Scope 5-Licensed Fixed Microwave Radio Services
 - 6 All Broadcasting Technical Standards (BETS) in the Category I Equipment Standards List.
- For Singapore (Info-Communications Development Authority (IDA)):
 - 1 All Line Terminal Equipment: All Technical Specifications for Line Terminal Equipment – Table 1 of IDA MRA Recognition Scheme: 2011, Annex 2
 - 2. All Radio-Communication Equipment: All Technical Specifications for Radio-Communication Equipment – Table 2 of IDA MRA Recognition Scheme: 2011, Annex 2
- For the Hong Kong Special Administrative Region:
 - 1 All Radio Equipment, per KHCA 10XX-series Specifications;
 - 2 All GMDSS Marine Radio Equipment, per HKCA 12XX-series Specifications;
 - 3 All Fixed Network Equipment, per HKCA 20XX-series Specifications.
- For Japan:
 - 1 MIC Telecommunication Business Law (Terminal Equipment):
 - All Scope A1 - Terminal Equipment for the Purpose of Calls;
 - All Scope A2 - Other Terminal Equipment
 - 2 Radio Law (Radio Equipment):
 - All Scope B1 - Specified Radio Equipment specified in Article 38-2-2, paragraph 1, item 1 of the Radio Law
 - All Scope B2 - Specified Radio Equipment specified in Article 38-2-2, paragraph 1, item 2 of the Radio Law
 - All Scope B3 - Specified Radio Equipment specified in Article 38-2-2, paragraph 1, item 3 of the Radio Law

C- A Product Certification Body accredited to ISO/IEC 17065:2012 by A2LA (Product Certification Body Accreditation Certificate Number 3279.01) to certify Products to USA's Environmental Protection Agency (EPA) ENERGY STAR Product Specifications for:

- 1 Electronics and Office Equipment:
 - for Telephony (ver. 3.0)
 - for Audio/Video (ver. 3.0)
 - for Battery Charging Systems (ver. 1.1)
 - for Set-top Boxes & Cable Boxes (ver. 4.1)
 - for Televisions (ver. 6.1)
 - for Computers (ver. 6.0)
 - for Displays (ver. 6.0)
 - for Imaging Equipment (ver. 2.0)
 - for Computer Servers (ver. 2.0)
- 2 Commercial Food Service Equipment
 - for Commercial Dishwashers (ver. 2.0)
 - for Commercial Ice Machines (ver. 2.0)
 - for Commercial Ovens (ver. 2.1)
 - for Commercial Refrigerators and Freezers

- 3 Lighting Products
 - For Decorative Light Strings (ver. 1.5)
 - For Luminaires (including sub-components) and Lamps (ver. 1.2)
 - For Compact Fluorescent Lamps (CFLs) (ver. 4.3)
 - For Integral LED Lamps (ver. 1.4)
- 4 Heating, Ventilation, and AC Products
 - for Residential Ceiling Fans (ver. 3.0)
 - for Residential Ventilating Fans (ver. 3.2)
- 5 Other
 - For Water Coolers (ver. 3.0)

D- A NIST Designated Phase-I and Phase-II Conformity Assessment Body (CAB) for the following economies and regulatory authorities under the terms of the stated MRAs/Treaties:

- Australia: ACMA (Australian Communication and Media Authority) – APEC Tel MRA -Phase I;
- Canada: (Industry Canada - IC) Foreign Certification Body – FCB – APEC Tel MRA -Phase I & Phase II;
- Chinese Taipei (Republic of China – Taiwan):
 - o BSMI (Bureau of Standards, Metrology and Inspection) APEC Tel MRA -Phase I;
 - o NCC (National Communications Commission) APEC Tel MRA -Phase I;
- European Union:
 - o EMC Directive 2004/108/EC US-EU EMC & Telecom MRA CAB
 - o Radio & Teleterminal Equipment (R&TTE) Directive 1995/5/EC
US -EU EMC & Telecom MRA CAB
- Hong Kong Special Administrative Region: (Office of the Telecommunications Authority – OFTA)
APEC Tel MRA -Phase I & Phase II
- Israel – US-Israel MRA Phase I
- Republic of Korea (Ministry of Communications - Radio Research Laboratory) APEC Tel MRA -Phase I
- Singapore: (Infocomm Development Authority - IDA) APEC Tel MRA -Phase I & Phase II;
- Japan: VCCI - Voluntary Control Council for Interference US-Japan Telecom Treaty VCCI Side Letter-
USA:
 - o ENERGY STAR Recognized Test Laboratory – US EPA
 - o Telecommunications Certification Body (TCB) – US FCC;
- Vietnam: APEC Tel MRA -Phase I;



American Association for Laboratory Accreditation

Accredited Product Certification Body

A2LA has accredited

BAY AREA COMPLIANCE LABORATORIES CORP.

Sunnyvale, CA

for technical competence as a

Product Certification Body

This product certification body is accredited in accordance with the recognized International Standard ISO/IEC 17065:2012 General requirements for bodies operating product certification systems. This accreditation demonstrates technical competence for a defined scope and the operation of a quality management system.

Presented this 8th day of September 2014.

President & CEO
For the Accreditation Council
Certificate Number 3297.03
Valid to September 30, 2016



For the product certification schemes to which this accreditation applies, please refer to the organization's Product Certification Scope of Accreditation

2 System Test Configuration

2.1 Justification

The EUT was configured for testing in accordance to ANSI C63.10-2013

The worst-case data rates are determined by measuring the peak power across all data rates.

2.2 EUT Exercise Software

The test firmware used was V00:04:02 provided by *GoPro, Inc.*, the software is comply with the standard requirements being tested against.

2.3 Duty Cycle Correction Factor

According to ANSI C63.10-2013 section 7.5:

Unless otherwise specified, when the radiated emission limits are expressed in terms of the average value of the emission, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 s (100 ms). In cases where the pulse train exceeds 0.1 s, the measured field strength shall be determined during a 0.1 s interval. The following procedure is an example of how the average value may be determined. The average field strength may be found by measuring the peak pulse amplitude (in log equivalent units) and determining the duty cycle correction factor (in dB) associated with the pulse modulation as shown in following equation:

$$\delta(\text{dB}) = 20\log(\Delta)$$

where

δ is the duty cycle correction factor (dB)


Δ is the duty cycle (dimensionless)

Radio Mode	On Time (μs)	Period (μs)	Duty Cycle (%)	Duty Cycle Correction Factor (dB)
GFSK	380	1252	30.35	-10.36
$\pi/4$ -DQPSK	384.5	1251	30.73	-10.25
8DPSK	389.3	1251	31.12	-10.14


$$\text{Duty Cycle} = \text{On Time (ms)} / \text{Period (ms)}$$

Please refer to the following plots.


GFSK Mode



$\pi/4$ -DQPSK Mode



8DPSK Mode



2.4 Equipment Modifications

A hole was cut in the back of the EUT to access the antenna ports.

2.5 Local Support Equipment

Manufacturer	Description	Model
Dell	Laptop	Latitude D630

2.6 Support Equipment

There was no support equipment included, or intended for use with EUT during these tests.

2.7 Interface Ports and Cabling

Cable Description	Length (m)	To	From
USB Cable	< 1 m	Laptop	EUT
RF Cable	< 1 m	EUT	PSA

3 Summary of Test Results

Results reported relate only to the product tested.

FCC & ISED Rules	Description of Test	Results
FCC §15.203 ISED RSS-Gen §8.3	Antenna Requirement	Compliant
FCC §15.207 ISED RSS-Gen §8.8	AC Line Conducted Emissions	Compliant
FCC §2.1093, §15.247(i) ISED RSS-102	RF Exposure	Compliant ¹
FCC §2.1051, §15.247 (d) ISED RSS-247 §5.5	Spurious Emissions at Antenna Port	Compliant
FCC §2.1053, §15.205, §15.209, §15.247(d) ISED RSS-247 §5.5 RSS-Gen §8.9, §8.10	Radiated Spurious Emissions	Compliant
FCC §15.247(a)(1) ISED RSS-247 §5.1 (1)	20 dB & 99% Emission Bandwidth	Compliant
FCC §15.247(b)(1) ISED RSS-247 §5.1(2)	Maximum Peak Output Power	Compliant
FCC §15.247(d) ISED RSS-247 §5.5	100 kHz Bandwidth of Frequency Band Edge	Compliant
FCC §15.247(a)(1)(iii) ISED RSS-247 §5.1(4)	Number of Hopping Channels	Compliant
FCC §15.247(a)(1) ISED RSS-247 §5.1 (2)	Hopping Channel Separation	Compliant
FCC §15.247(a)(1)(iii) ISED RSS-247 §5.1 (4)	Dwell Time	Compliant

Note¹: RF exposure analysis is covered in a separate report. Please refers to R1606032-SAR

4 FCC §15.203 & ISED RSS-Gen §8.3 - Antenna Requirements

4.1 Applicable Standards

According to FCC §15.203:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

And according to FCC §15.247 (b) (4), if transmitting antennas of directional gain greater than 6 dBi are used the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

According to IC RSS-Gen §8.3: Transmitter Antenna

The applicant for equipment certification, as per RSP-100, must provide a list of all antenna types that may be used with the license-exempt transmitter, indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna.

License-exempt transmitters that have received equipment certification may operate with different types of antennas. However, it is not permissible to exceed the maximum equivalent isotropically radiated power (e.i.r.p.) limits specified in the applicable standard (RSS) for the license-exempt apparatus.

Testing shall be performed using the highest gain antenna of each combination of license-exempt transmitter and antenna type, with the transmitter output power set at the maximum level. When a measurement at the antenna connector is used to determine RF output power, the effective gain of the device's antenna shall be stated, based on a measurement or on data from the antenna manufacturer.

User manuals for transmitters equipped with detachable antennas shall also contain the following notice in a conspicuous location:

This radio transmitter (identify the device by certification number) has been approved by Industry Canada to operate with the antenna types listed below with the maximum permissible gain indicated. Antenna types not included in this list, having a gain greater than the maximum gain indicated for that type, are strictly prohibited for use with this device.

Immediately following the above notice, the manufacturer shall provide a list of all antenna types approved for use with the transmitter, indicating the maximum permissible antenna gain (in dBi).

4.2 Antenna Description

The antennas used by the EUT are permanent attached antennas.

Antenna usage	Frequency Range (MHz)	Maximum Antenna Gain (dBi)
Wi-Fi/Bluetooth	2400-2500	-0.98
Wi-Fi	5100-5600	1.41

5 FCC §2.1093, §15.247(i) & ISED RSS-102 - RF Exposure

5.1 Applicable Standards

FCC §2.1093, §15.247(i) & IC RSS-102

5.2 Test Results

Please refer to the SAR Report: R1606032- SAR.

6 FCC §15.207 & ISED RSS-Gen §8.8 - AC Line Conducted Emissions

6.1 Applicable Standards

As per FCC §15.207 and IC RSS-Gen §8.8 Conducted limits:

For an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequencies ranges.

Frequency of Emission (MHz)	Conducted Limit (dBuV)	
	Quasi-Peak	Average
0.15-0.5	66 to 56 ^{Note 1}	56 to 46 ^{Note 2}
0.5-5	56	46
5-30	60	50

Note 1: Decreases with the logarithm of the frequency.

Note 2: A linear average detector is required

6.2 Test Setup

The measurement was performed at shield room, using the setup per ANSI C63.10-2013 measurement procedure. The specification used was FCC §15.207 and IC RSS-Gen §8.8 limits.

External I/O cables were draped along the edge of the test table and bundle when necessary.

The AC/DC power adapter of the EUT was connected with LISN-1 which provided 120 V / 60 Hz AC power.

6.3 Test Procedure

During the conducted emissions test, the power cord of the EUT host system was connected to the mains outlet of the LISN-1 and the power cords of support equipment were connected to LISN-2.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data were recorded in the peak detection mode, quasi-peak, and average detection mode. Quasi-Peak readings are distinguished with a “QP.” Average readings are distinguished with an “Ave”.

6.4 Corrected Amplitude & Margin Calculation

The Corrected Amplitude (CA) is calculated by adding the Cable Loss (CL), the Attenuator Factor (Atten) to indicated Amplitude (Ai) reading. The basic equation is as follows:


$$CA = Ai + CL + Atten$$

For example, a corrected amplitude of 46.2 dBuV = Indicated Reading (32.5 dBuV) + Cable Loss (3.7 dB) + Attenuator (10 dB)

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. For example, a margin of -7 dB means the emission is 7 dB below the maximum limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Corrected Amplitude} - \text{Limit}$$

6.5 Test Setup Block Diagram



6.6 Test Equipment List and Details

Manufacturer	Description	Model No.	Serial No.	Calibration Date	Calibration Interval
Rohde & Schwarz	Receiver, EMI Test	ESCI 1166.5950K03	100338	2016-02-04	2 year
Rohde & Schwarz	Impulse Limiter	ESH3-Z2	101964	2016-07-22	1 year
Keysight Technologies	RF Limiter	11867A	MY42242932	2015-12-15	1 year
Solar Electronics Company	High Pass Filter	Type 7930-100	7930150204	2016-03-09	1 Year
Suirong	30 ft conductive emission cable	LMR 400	-	2016-03-05	1 year
Vasona	Test software	V6.0 build 11	10400213	N/R	N/R

Statement of Traceability: *BACL Corp. attests that all calibrations have been performed per the A2LA requirements, traceable to the NIST.*

6.7 Test Environmental Conditions

Temperature:	22 °C
Relative Humidity:	43 %
ATM Pressure:	101.8 kPa

The testing was performed by Jose Martinez on 2016-07-22 in the outside emission test site.


6.8 Summary of Test Results

According to the recorded data in following table, the EUT complied with the FCC 15C and IC RSS-Gen standard's conducted emissions limits, with the margin reading of:

Connection: AC/DC adapter connected to 120 V/60 Hz, AC			
Margin (dB)	Frequency (MHz)	Conductor Mode (Live/Neutral)	Range (MHz)
-12.94	0.411776	Neutral	0.15-30


6.9 Conducted Emissions Test Plots and Data

120 V, 60 Hz – Line



Frequency (MHz)	Corrected Amplitude (dBuV)	Conductor (Line/Neutral)	Limit (dBuV)	Margin (dB)	Detector (QP/Ave.)
0.412394	43.27	Line	57.6	-14.33	QP
28.13056	38.04	Line	60	-21.96	QP
0.902918	37.16	Line	56	-18.84	QP
28.33187	39.55	Line	60	-20.45	QP
28.61882	38.9	Line	60	-21.1	QP
0.658989	37.8	Line	56	-18.2	QP

Frequency (MHz)	Corrected Amplitude (dBuV)	Conductor (Line/Neutral)	Limit (dBuV)	Margin (dB)	Detector (QP/Ave.)
0.412394	32.29	Line	47.6	-15.31	Ave.
28.13056	27.52	Line	50	-22.48	Ave.
0.902918	26.27	Line	46	-19.73	Ave.
28.33187	29.1	Line	50	-20.9	Ave.
28.61882	28.87	Line	50	-21.13	Ave.
0.658989	26.68	Line	46	-19.32	Ave.

120 V, 60 Hz – Neutral

Frequency (MHz)	Corrected Amplitude (dBuV)	Conductor (Line/Neutral)	Limit (dBuV)	Margin (dB)	Detector (QP/Ave.)
28.58529	40.21	Neutral	60	-19.79	QP
0.449595	39.06	Neutral	56.88	-17.82	QP
0.411776	40.09	Neutral	57.61	-17.52	QP
27.69517	37.29	Neutral	60	-22.71	QP
27.16609	35.8	Neutral	60	-24.2	QP
28.09098	38.32	Neutral	60	-21.68	QP

Frequency (MHz)	Corrected Amplitude (dBuV)	Conductor (Line/Neutral)	Limit (dBuV)	Margin (dB)	Detector (QP/Ave.)
28.58529	32.54	Neutral	50	-17.46	Ave.
0.449595	30.48	Neutral	46.88	-16.4	Ave.
0.411776	34.67	Neutral	47.61	-12.94	Ave.
27.69517	28.68	Neutral	50	-21.32	Ave.
27.16609	26.95	Neutral	50	-23.05	Ave.
28.09098	30.47	Neutral	50	-19.53	Ave.

7 FCC §15.209, §15.247(d) & ISED RSS-247 §5.5, RSS-Gen §8.9, §8.10 - Spurious Radiated Emissions

7.1 Applicable Standards

As per FCC §15.35(d): Unless otherwise specified, on any frequency or frequencies above 1000 MHz, the radiated emission limits are based on the use of measurement instrumentation employing an average detector function. Unless otherwise specified, measurements above 1000 MHz shall be performed using a minimum resolution bandwidth of 1 MHz.

As Per FCC §15.205(a) and RSS-Gen except as show in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090 – 0.110	16.42 – 16.423	960 – 1240	4.5 – 5.15
0.495 – 0.505	16.69475 – 16.69525	1300 – 1427	5.35 – 5.46
2.1735 – 2.1905	25.5 – 25.67	1435 – 1626.5	7.25 – 7.75
4.125 – 4.128	37.5 – 38.25	1645.5 – 1646.5	8.025 – 8.5
4.17725 – 4.17775	73 – 74.6	1660 – 1710	9.0 – 9.2
4.20725 – 4.20775	74.8 – 75.2	1718.8 – 1722.2	9.3 – 9.5
6.215 – 6.218	108 – 121.94	2200 – 2300	10.6 – 12.7
6.26775 – 6.26825	123 – 138	2310 – 2390	13.25 – 13.4
6.31175 – 6.31225	149.9 – 150.05	2483.5 – 2500	14.47 – 14.5
8.291 – 8.294	156.52475 – 156.52525	2690 – 2900	15.35 – 16.2
8.362 – 8.366	156.7 – 156.9	3260 – 3267	17.7 – 21.4
8.37625 – 8.38675	162.0125 – 167.17	3.332 – 3.339	22.01 – 23.12
8.41425 – 8.41475	167.72 – 173.2	3.3458 – 3.358	23.6 – 24.0
12.29 – 12.293	240 – 285	3.600 – 4.400	31.2 – 31.8
12.51975 – 12.52025	322 – 335.4		36.43 – 36.5
12.57675 – 12.57725	399.9 – 410		Above 38.6
13.36 – 13.41	608 – 614		

As per FCC §15.209(a): Except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength (micro volts/meter)	Measurement Distance (meters)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 - 30.0	30	30
30 - 88	100**	3
88 - 216	150**	3
216 - 960	200**	3
Above 960	500	3

** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.

As per FCC §15.247 (d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

As per IC RSS-Gen 8.9,

Except when the requirements applicable to a given device state otherwise, emissions from licence-exempt transmitters shall comply with the field strength limits shown in Table 4 or Table 5 below. Additionally, the level of any transmitter emission shall not exceed the level of the transmitter's fundamental emission.

Table 4 – General Field Strength Limits for Licence-Exempt Transmitters at Frequencies Above 30 MHz

Frequency (MHz)	Field Strength (µV/m at 3 metres)
30-88	100
88-216	150
216-960	200
Above 960*	500

* Unless otherwise specified, for all frequencies greater than 1 GHz, the radiated emission limits for licence-exempt radio apparatus stated in applicable RSSs (including RSS-Gen) are based on measurements using a linear average detector function having a minimum resolution bandwidth of 1 MHz. If an average limit is specified for the EUT, then the peak emission shall also be measured with instrumentation properly adjusted for such factors as pulse desensitization to ensure the peak emission is less than 20 dB above the average limit.

Note: Transmitting devices are not permitted in restricted frequency bands unless stated otherwise in the specific RSS.

As per IC RSS-247 §5.5, in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of root-mean-square averaging over a time interval, as permitted under Section 5.4(4), the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general field strength limits specified in RSS-Gen is not required.

7.2 Test Setup

The radiated emissions tests were performed in the 5-meter Chamber, using the setup in accordance with ANSI C63.10-2013. The specification used was the FCC 15 Subpart C and IC RSS-247 limits.

The spacing between the peripherals was 10 centimeters.

External I/O cables were draped along the edge of the test table and bundle when necessary.

7.3 Test Procedure

For the radiated emissions test, the EUT host, and all support equipment power cords was connected to the AC floor outlet.

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

The EUT was set 3 meter away from the testing antenna, which was varied from 1-4 meter, and the EUT was placed on a turntable, which was 0.8 meter and 1.5 meter above the ground plane for below and above 1000 MHz measurements, the table shall be rotated for 360 degrees to find out the highest emission. The receiving antenna should be changed the polarization both of horizontal and vertical.

The spectrum analyzer or receiver is set as:

Below 1000 MHz:

$$\text{RBW} = 100 \text{ kHz} / \text{VBW} = 300 \text{ kHz} / \text{Sweep} = \text{Auto}$$

Above 1000 MHz:

- (1) Peak: RBW = 1MHz / VBW = 1MHz / Sweep = Auto
- (2) Average: RBW = 1MHz / VBW = 10Hz / Sweep = Auto

7.4 Corrected Amplitude & Margin Calculation

The Corrected Amplitude (CA) is calculated by adding the Antenna Factor (AF), the Cable Loss (CL), the Attenuator Factor (Atten) and subtracting the Amplifier Gain (Ga) to indicated Amplitude (Ai) reading. The basic equation is as follows:

$$\text{CA} = \text{Ai} + \text{AF} + \text{CL} + \text{Atten} - \text{Ga}$$

For example, a corrected amplitude of 40.3 dBuV/m = Indicated Reading (32.5 dBuV) + Antenna Factor (+23.5dB) + Cable Loss (3.7 dB) + Attenuator (10 dB) - Amplifier Gain (29.4 dB)

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. For example, a margin of -7 dB means the emission is 7 dB below the maximum limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Corrected Amplitude} - \text{Limit}$$

7.5 Test Equipment List and Details

Manufacturer	Description	Model No.	Serial No.	Calibration Date	Calibration Interval
Rohde & Schwarz	Receiver, EMI Test	ESCI 1166.5950K03	100338	2016-02-04	2 year
Agilent	Analyzer, Spectrum	E4446A	US44300386	2015-10-22	1 year
Sunol Science Corp	System Controller	SC99V	011003-1	N/R	N/R
Sunol Sciences	Antenna, Biconi-Log	JB3	A020106-2	2015-07-11	2 Years
EMCO	Antenna, Horn	3115	9511-4627	2016-01-28	2 years
Agilent	Amplifier, Pre	8447D	2944A10187	2016-03-23	1 year
IW	AOBOR Hi frequency Co AX CabelCable	DC 1531	KPS- 1501A3960K PS	2015-08-10	1 Year
-	SMA cable	-	C0002	Each time ¹	N/A
-	N-Type Cable	-	C00013	2016-04-28	1 year
-	N-Type Cable	-	C00014	2016-05-28	1 year
Agilent	Pre-Amplifier	8449B	3008A01978	2015-09-02	1year
Wisewave	Antenna, Horn	ARH-4223-02	10555-02	2013-09-20	3 year
Wisewave	Antenna, Horn	ARH-2823-02	10555-02	2013-09-20	3 year
Wisewave	Amplifier, Low Noise	ALN-33144030-01	11424-01	2016-04-28	1 year
Wisewave	Amplifier, Low Noise	ALN-22093530-01	12263-01	2016-05-16	1 year
Vasona	Test software	V6.0 build 11	10400213	N/R	N/R

Note¹: cable and attenuator included in the test set-up will be checked each time before testing.

Statement of Traceability: *BACL attests that all calibrations have been performed per the A2LA requirements, traceable to NIST.*

7.6 Test Environmental Conditions

Temperature:	23 °C
Relative Humidity:	42 %
ATM Pressure:	102.7 kPa

The testing was performed by Jose Martinez on 2016-08-08 in 5m chamber 3.

7.7 Summary of Test Results


According to the data hereinafter, the EUT complied with FCC Title 47, Part 15C and IC RSS-247 standard's radiated emissions limits, and had the worst margin of:

Mode: Transmitting			
Margin (dB)	Frequency (MHz)	Polarization (Horizontal/Vertical)	Mode, Channel
-12.63	4960	Horizontal	$\pi/4$ -DQPSK, High Channel

Please refer to the following table and plots for specific test result details.

7.8 Radiated Emissions Test Results

1) 30 MHz – 1 GHz Worst Case, Measured at 3 meters



Frequency (MHz)	Corrected Amplitude (dBμV/m)	Antenna Height (cm)	Antenna Polarity (H/V)	Turntable Azimuth (degrees)	Limit (dBμV/m)	Margin (dB)	Comment
30	14.72	269	H	19	40	-25.28	QP
-	-	-	-	-	-	-	QP

Note: “-” noise floor

2) 1–25 GHz Measured at 3 meters

GFSK mode

Frequency (MHz)	S.A. Reading (dBμV)	Turntable Azimuth (degrees)	Test Antenna			Cable Loss (dB)	Pre- Amp. (dB)	Cord. Reading (dBμV/m)	FCC/IC		Comments
			Height (cm)	Polarity (H/V)	Factor (dB/m)				Limit (dBμV/m)	Margin (dB)	
Low Channel 2402 MHz (power setting: 9)											
2402	65.09	160	283	V	29.04	5.21	0	99.34	-	-	Peak
2402	69.34	200	158	H	29.04	5.21	0	103.59	-	-	Peak
2402	50.23	23	300	V	29.04	5.21	0	84.48	-	-	Ave
2402	52.97	220	141	H	29.04	5.21	0	87.22	-	-	Ave
2390	36.82	340	100	V	29.04	5.21	37.77	33.30	74	-40.70	Peak
2390	37.23	251	150	H	29.04	5.21	37.77	33.71	74	-40.29	Peak
2390	28.22	160	300	V	29.04	5.81	37.77	25.30	54	-28.70	Ave
2390	27.74	71	300	H	29.04	5.81	37.77	24.82	54	-29.18	Ave
4804	51.6	220	300	H	32.47	8.85	38.2	54.72	74	-19.28	Peak
4804	25.91	220	300	H	32.47	8.85	38.2	29.03	54	-24.97	Ave
7206	46.86	220	300	H	36.69	11.261	37.68	57.13	74	-16.87	Peak
7206	22.14	360	100	H	36.69	11.261	37.68	32.41	54	-21.59	Ave
9608	48.16	360	100	H	37.77	12.408	38.16	60.18	74	-13.82	Peak
9608	27.92	360	100	H	37.77	12.408	38.16	39.94	54	-14.06	Ave
Middle Channel 2441 MHz (power setting: 9)											
2441	66.19	175	300	V	29.35	5.21	0.00	100.75	-	-	Peak
2441	69.22	219	219	H	29.35	5.21	0.00	103.78	-	-	Peak
2441	47.53	5	189	V	29.35	5.21	0.00	82.08	-	-	Ave
2441	54.68	218	194	H	29.35	5.21	0.00	89.23	-	-	Ave
4882	54.73	131	250	H	32.64	9.002	38.16	58.21	74	-15.79	Peak
4882	30.62	124	251	H	32.64	9.002	38.16	34.10	54	-19.90	Ave
7323	47.18	0	100	H	37.15	11.345	37.63	58.04	74	-15.96	Peak
7323	25.52	0	100	H	37.15	11.345	37.63	36.38	54	-17.62	Ave
9764	48.69	0	100	H	37.87	11.629	38.31	59.87	74	-14.13	Peak
9764	26.16	0	100	H	37.87	11.629	38.31	37.34	54	-16.66	Ave

Frequency (MHz)	S.A. Reading (dBμV)	Turntable Azimuth (degrees)	Test Antenna			Cable Loss (dB)	Pre- Amp. (dB)	Cord. Reading (dBμV/m)	FCC/IC		Comments
			Height (cm)	Polarity (H/V)	Factor (dB/m)				Limit (dBμV/m)	Margin (dB)	
High Channel 2480 MHz (power setting: 9)											
2480	67.14	170	300	V	29.41	5.21	0.00	101.76	-	-	Peak
2480	66.72	156	300	H	29.41	5.21	0.00	101.34	-	-	Peak
2480	50.96	159	300	V	29.41	5.21	0.00	85.58	-	-	Ave
2480	55.26	202	171	H	29.41	5.21	0.00	89.88	-	-	Ave
2483.5	28.48	0	130	V	29.41	5.21	37.72	25.38	74	-48.62	Peak
2483.5	28.17	12	200	H	29.41	5.21	37.72	25.07	74	-48.93	Peak
2483.5	27.19	190	290	V	29.41	5.81	37.72	24.69	54	-29.31	Ave
2483.5	28.71	190	100	H	29.41	5.81	37.72	26.21	54	-27.79	Ave
4960	53.55	156	142	V	32.74	8.89	38.14	57.04	74	-16.96	Peak
4960	52.78	120	100	H	32.74	8.89	38.14	56.27	74	-17.73	Peak
4960	34.79	150	142	V	32.74	8.89	38.14	38.28	54	-15.72	Ave
4960	33.34	123	130	H	32.74	8.89	38.14	36.83	54	-17.17	Ave
7440	47.17	0	100	V	37.03	11.11	37.73	57.58	74	-16.42	Peak
7440	47.09	0	100	H	37.03	11.11	37.73	57.50	74	-16.50	Peak
7440	25.95	0	100	V	37.03	11.11	37.73	36.36	54	-17.64	Ave
7440	26.5	0	100	H	37.03	11.11	37.73	36.91	54	-17.09	Ave
9920	47.73	0	100	V	37.99	11.83	38.36	59.18	74	-14.82	Peak
9920	47.63	0	100	H	37.99	11.83	38.36	59.08	74	-14.92	Peak
9920	24.74	0	100	V	37.99	11.83	38.36	36.19	54	-17.81	Ave
9920	24.89	0	100	H	37.99	11.83	38.36	36.34	54	-17.66	Ave

$\pi/4$ -DQPSK mode

Frequency (MHz)	S.A. Reading (dBμV)	Turntable Azimuth (degrees)	Test Antenna			Cable Loss (dB)	Pre- Amp. (dB)	Cord. Reading (dBμV/m)	FCC/IC		Comments
			Height (cm)	Polarity (H/V)	Factor (dB/m)				Limit (dBμV/m)	Margin (dB)	
Low Channel 2402 MHz (power setting: 9)											
2402	64.23	164	282	V	29.04	5.21	0	98.48	-	-	Peak
2402	66.38	325	300	H	29.04	5.21	0	100.63	-	-	Peak
2402	45.57	215	280	V	29.04	5.21	0	79.82	-	-	Ave
2402	55.8	240	184	H	29.04	5.21	0	90.05	-	-	Ave
2390	27.67	86	300	V	29.04	5.21	37.77	24.15	74	-49.85	Peak
2390	27.3	100	79	H	29.04	5.21	37.77	23.78	74	-50.22	Peak
2390	28.98	165	100	V	29.04	5.81	37.77	26.06	54	-27.94	Ave
2390	27.68	223	171	H	29.04	5.81	37.77	24.76	54	-29.24	Ave
4804	51.94	126	260	H	32.47	8.85	38.2	55.06	74	-18.94	Peak
4804	29.82	116	300	H	32.47	8.85	38.2	32.94	54	-21.06	Ave
7206	47.16	0	100	H	36.69	11.26	37.68	57.43	74	-16.57	Peak
7206	24.73	0	100	H	36.69	11.26	37.68	35.00	54	-19.00	Ave
9608	47.57	0	100	H	38.16	12.41	38.16	59.98	74	-14.02	Peak
9608	25.15	0	100	H	38.16	12.41	38.16	37.56	54	-16.44	Ave
Middle Channel 2441 MHz (power setting: 9)											
2441	65.24	165	269	V	29.41	5.21	0	99.86	-	-	Peak
2441	68.85	235	175	H	29.41	5.21	0	103.47	-	-	Peak
2441	45.55	10	261	V	29.41	5.21	0	80.17	-	-	Ave
2441	51.80	208	175	H	29.41	5.21	0	86.42	-	-	Ave
4882	48.98	304	100	H	32.64	9.00	38.16	52.46	74	-21.54	Peak
4882	28.02	347	120	H	32.64	9.00	38.16	31.50	54	-22.50	Ave
7323	47.97	100	0	H	37.15	11.35	37.63	58.83	74	-15.17	Peak
7323	25.28	100	0	H	37.15	11.35	37.63	36.14	54	-17.86	Ave
9764	48.64	100	0	H	37.87	11.63	38.31	59.82	74	-14.18	Peak
9764	26.5	100	0	H	37.87	11.63	38.31	37.69	54	-16.31	Ave

Frequency (MHz)	S.A. Reading (dBμV)	Turntable Azimuth (degrees)	Test Antenna			Cable Loss (dB)	Pre- Amp. (dB)	Cord. Reading (dBμV/m)	FCC/IC		Comments
			Height (cm)	Polarity (H/V)	Factor (dB/m)				Limit (dBμV/m)	Margin (dB)	
High Channel 2480 MHz (power setting: 9)											
2480	66.86	175	300	V	29.41	5.21	0	101.48	-	-	Peak
2480	69.57	202	219	H	29.41	5.21	0	104.19	-	-	Peak
2480	49.41	176	300	V	29.41	5.21	0	84.03	-	-	Ave
2480	51.64	230	300	H	29.41	5.21	0	86.26	-	-	Ave
2483.5	27.67	230	100	V	29.41	5.21	37.72	24.57	74	-49.43	Peak
2483.5	27.79	222	100	H	29.41	5.21	37.72	24.69	74	-49.31	Peak
2483.5	28.03	190	300	V	29.41	5.81	37.72	25.53	54	-28.47	Ave
2483.5	29.35	225	280	H	29.41	5.81	37.72	26.85	54	-27.15	Ave
4960	49.61	0	100	H	32.74	8.89	38.14	53.10	74	-20.90	Peak
4960	37.88	0	100	H	32.74	8.89	38.14	41.37	54	-12.63	Ave
7440	47.29	0	100	H	37.03	11.11	37.73	57.70	74	-16.30	Peak
7440	25.67	0	100	H	37.03	11.11	37.73	36.08	54	-17.92	Ave
9920	48.62	0	100	H	37.99	11.83	38.36	60.07	74	-13.93	Peak
9920	24.8	0	100	H	37.99	11.83	38.36	36.25	54	-17.75	Ave

8DPSK mode

Frequency (MHz)	S.A. Reading (dBμV)	Turntable Azimuth (degrees)	Test Antenna			Cable Loss (dB)	Pre- Amp. (dB)	Cord. Reading (dBμV/m)	FCC/IC		Comments
			Height (cm)	Polarity (H/V)	Factor (dB/m)				Limit (dBμV/m)	Margin (dB)	
Low Channel 2402 MHz (power setting: 9)											
2402	64.55	170	284	V	29.04	5.21	0	98.80	-	-	Peak
2402	68.31	226	230	H	29.04	5.21	0	102.56	-	-	Peak
2402	46.85	168	287	V	29.04	5.21	0	81.11	-	-	Ave
2402	50.33	207	208	H	29.04	5.21	0	84.59	-	-	Ave
2390	26.60	200	100	V	29.04	5.21	37.77	23.08	74	-50.92	Peak
2390	26.92	123	100	H	29.04	5.21	37.77	23.40	74	-50.60	Peak
2390	28.42	320	300	V	29.04	5.81	37.77	25.51	54	-28.49	Ave
2390	27.52	305	300	H	29.04	5.81	37.77	24.61	54	-29.39	Ave
4804	50.84	96	300	H	32.47	8.85	38.2	53.96	74	-20.04	Peak
4804	30.08	96	300	H	32.47	8.85	38.2	33.21	54	-20.79	Ave
7206	47.72	0	100	H	36.69	6.92	33.93215	57.40	74	-16.60	Peak
7206	25.09	0	100	H	36.69	6.92	33.93215	34.77	54	-19.23	Ave
9608	47.92	0	100	H	37.84	9.84	34.31475	61.28	74	-12.72	Peak
9608	25.7	0	100	H	37.84	9.84	34.31475	39.06	54	-14.94	Ave
Middle Channel 2441 MHz (power setting: 9)											
2441	65.51	164	269	V	29.41	5.21	0	100.13	-	-	Peak
2441	66.94	220	199	H	29.41	5.21	0	101.56	-	-	Peak
2441	47.32	167	300	V	29.41	5.21	0	81.95	-	-	Ave
2441	51.79	230	199	H	29.41	5.21	0	86.42	-	-	Ave
4882	50.52	106	300	H	32.64	9.00	38.16	54.00	74	-20.00	Peak
4882	29.02	106	300	H	32.64	9.00	38.16	32.50	54	-21.50	Ave
7323	47.19	0	100	H	37.15	11.35	37.63	58.05	74	-15.95	Peak
7323	25.03	0	100	H	37.15	11.35	37.63	35.90	54	-18.10	Ave
9764	48.84	0	100	H	37.87	11.63	38.31	60.02	74	-13.98	Peak
9764	26.1	0	100	H	37.87	11.63	38.31	37.29	54	-16.71	Ave
High Channel 2441 MHz (power setting: 9)											
2480	66.13	160	300	V	29.41	5.21	0	100.75	-	-	Peak
2480	69.69	230	260	H	29.41	5.21	0	104.31	-	-	Peak
2480	47.94	162	276	V	29.41	5.21	0	82.57	-	-	Ave
2480	52.25	225	218	H	29.41	5.21	0	86.88	-	-	Ave
2483.5	27.76	240	300	V	29.41	5.21	37.72	24.66	74	-49.34	Peak
2483.5	28.74	240	100	H	29.41	5.21	37.72	25.64	74	-48.36	Peak
2483.5	27.69	200	270	V	29.41	5.81	37.72	25.20	54	-28.80	Ave
2483.5	29.11	224	150	H	29.41	5.81	37.72	26.62	54	-27.38	Ave
4960	47.35	0	100	H	32.74	8.89	38.14	3.49	74	-70.51	Peak
4960	27.42	270	130	H	32.74	8.89	38.14	30.91	54	-23.09	Ave
7440	47.57	0	100	H	37.03	11.11	37.73	57.98	74	-16.02	Peak
7440	25.61	0	100	H	37.03	11.11	37.73	36.02	54	-17.98	Ave
9920	48.52	0	100	H	37.99	11.83	38.36	59.97	74	-14.03	Peak
9608	25.15	0	100	H	38.16	12.41	38.16	37.56	54	-16.44	Ave

Note: duty cycle factor was taken into account.

8 FCC §15.247(a) (1) & ISSED RSS-247 §5.1, RSS-Gen §6.6 - Emission Bandwidth

8.1 Applicable Standards

According to FCC §15.247(a) (1) and IC RSS-247 §5.1: the maximum 20 dB bandwidth of the hopping channel shall be presented.

8.2 Measurement Procedure

Span = approximately 2 to 5 times the 99% occupied bandwidth, centered on a hopping channel

RBW = 1% to 5 % of the 99% occupied bandwidth

VBW = 3RBW

Sweep = auto

Detector function = peak

Trace = max hold

8.3 Test Equipment List and Details

Manufacturer	Description	Model No.	Serial No.	Calibration Date	Calibration Interval
Agilent	Analyzer, Spectrum	E4446A	MY48250238	2015-11-12	1 year
-	RF cable	-	-	Each time ¹	N/A
-	10 dB attenuator	-	-	Each time ¹	N/A

Note¹: cable and attenuator included in the test set-up will be checked each time before testing.

Statement of Traceability: *BACL Corp. attests that all calibrations have been performed per the A2LA requirements, traceable to the NIST.*

8.4 Test Environmental Conditions

Temperature:	22°C
Relative Humidity:	42 %
ATM Pressure:	102.6 KPa

The testing was performed by Jose Martinez on 2016-08-02 in RF site.


8.5 Test Results

Channel	Frequency (MHz)	99% OBW (kHz)	20 dB OBW (kHz)
GFSK			
Low	2402	873.18	836.01
Middle	2441	872.98	836.16
High	2480	871.84	835.23
$\pi/4$ -DQPSK			
Low	2402	1156.8	1212
Middle	2441	1161.0	1217
High	2480	1159.9	1259
8DPSK			
Low	2402	1154.7	1205
Middle	2441	1146.0	1193
High	2480	1147.0	1191


Please refer to the following plots for detailed test results.

GFSK


Low Channel 2402 MHz



Middle Channel 2441 MHz




High Channel 2480 MHz




$\pi/4$ -DQPSK


Low Channel 2402 MHz



Middle Channel 2441 MHz




High Channel 2480 MHz




8DPSK


Low Channel 2402 MHz



Middle Channel 2441 MHz



High Channel 2480 MHz



9 FCC §15.247(b) (1) & ISED RSS-247 §5.4 -Output Power

9.1 Applicable Standards

According to FCC §15.247(b) (1): For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts.

According to RSS-247 §5.4: For frequency hopping systems operating in the band 2400-2483.5 MHz, the maximum peak conducted output power shall not exceed 1.0 W and the e.i.r.p. shall not exceed 4 W if the hopset uses 75 or more hopping channels; the maximum peak conducted output power shall not exceed 0.125 W and the e.i.r.p. shall not exceed 0.5 W if the hopset uses less than 75 hopping channels.

9.2 Measurement Procedure

Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel

RBW > the 20 dB bandwidth of the emission being measured

VBW ≥ RBW

Sweep = auto

Detector function = peak

Trace = max hold

9.3 Test Equipment List and Details

Manufacturer	Description	Model No.	Serial No.	Calibration Date	Calibration Interval
Agilent	Analyzer, Spectrum	E4446A	MY48250238	2015-11-12	1 year
-	RF cable	-	-	Each time ¹	N/A
-	10dB attenuator	-	-	Each time ¹	N/A

Note¹: cable and attenuator included in the test set-up will be checked each time before testing.

Statement of Traceability: *BACL Corp. attests that all calibrations have been performed per the A2LA requirements, traceable to the NIST.*

9.4 Test Environmental Conditions

Temperature:	23 °C
Relative Humidity:	42 %
ATM Pressure:	102.9 KPa

The testing was performed by Jose Martinez on 2016-08-15 in RF site.


9.5 Test Results

Channel	Frequency (MHz)	Conducted Output Power (dBm)		Limit (dBm)
		Peak	Average	
GFSK				
Low	2402	12.36	7.18	30
Middle	2441	12.65	7.47	30
High	2480	12.54	7.36	30
$\pi/4$ -DQPSK				
Low	2402	11.63	6.51	30
Middle	2441	11.78	6.66	30
High	2480	11.63	6.51	30
8DPSK				
Low	2402	11.89	6.82	30
Middle	2441	12.03	6.96	30
High	2480	11.90	6.83	30


Please refer to the following plots for detailed test results.

GFSK


Low Channel 2402 MHz



Middle Channel 2441 MHz




High Channel 2480 MHz




$\pi/4$ -DQPSK


Low Channel 2402 MHz



Middle Channel 2441 MHz




High Channel 2480 MHz




8DPSK


Low Channel 2402 MHz



Middle Channel 2441 MHz



High Channel 2480 MHz



10 FCC §15.247(d) & ISED RSS-247 §5.5 - 100 kHz Bandwidth of Band Edges

10.1 Applicable Standards

According to FCC §15.247(d), in any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emissions limits specified in §15.209(a) see §15.205(c).

According to IC RSS-247 §5.5. In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of root-mean-square averaging over a time interval, as permitted under Section 5.4(4), the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general field strength limits specified in RSS-Gen is not required.

10.2 Measurement Procedure

Span = wide enough to capture the peak level of the emission operating on the channel closest to the band edge, as well as any modulation products which fall outside of the authorized band of operation

RBW = 100 kHz

VBW = 300 kHz

Sweep = coupled

Detector function = peak

Trace = max hold

10.3 Test Equipment List and Details

Manufacturer	Description	Model No.	Serial No.	Calibration Date	Calibration Interval
Agilent	Analyzer, Spectrum	E4446A	MY48250238	2015-11-12	1 year
-	U. FL to SMA pigtail	-	-	Each time ¹	N/A
-	10 dB attenuator	-	-	Each time ¹	N/A

Note¹: cable and attenuator included in the test set-up will be checked each time before testing.

Statement of Traceability: *BACL Corp. attests that all calibrations have been performed per the A2LA requirements, traceable to the NIST.*

10.4 Test Environmental Conditions


Temperature:	22 °C
Relative Humidity:	42 %
ATM Pressure:	102.6 KPa

The testing was performed by Jose Martinez on 2016-08-02 in RF site.


10.5 Test Results

GFSK

Low Channel 2402 MHz




High Channel 2480 MHz




$\pi/4$ -DQPSK

Low Channel 2402 MHz




High Channel 2480 MHz




8DPSK

Low Channel 2402 MHz



High Channel 2480 MHz



11 FCC §15.247(a) (1) (iii) & ISSED RSS-247 §5.1 (4) - Dwell Time

11.1 Applicable Standards

According to FCC §15.247(a) (1) (iii) and RSS-247 §5.1(4), Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

11.2 Measurement Procedure

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

Span = zero span, centered on a hopping channel

RBW $\leq$ channel spacing and where possible RBW should be set $\gg 1/T$, where T is the expected dwell time per channel

Sweep = as necessary to capture the entire dwell time per hopping channel

Detector function = peak

Trace = max hold

Use the marker-delta function to determine the transmit time per hop. If this value varies with different modes of operation (data rate, modulation format, number of hopping channels, etc.), then repeat this test for each variation in transmit time.

Repeat the measurement using a longer sweep time to determine the number of hops over the period specified in the requirements. The sweep time shall be equal to, or less than, the period specified in the requirements. Determine the number of hops over the sweep time and calculate the total number of hops in the period specified in the requirements, using the following equation:

$$\begin{aligned} &(\text{Number of hops in the period specified in the requirements}) = \\ &(\text{number of hops on spectrum analyzer}) \times (\text{period specified in the requirements} / \text{analyzer sweep time}) \end{aligned}$$

The average time of occupancy is calculated from the transmit time per hop multiplied by the number of hops in the period specified. If the number of hops in a specific time varies with different modes of operation (data rate, modulation format, number of hopping channels, etc.), then repeat this test for each variation.

11.3 Test Equipment List and Details

Manufacturer	Description	Model No.	Serial No.	Calibration Date	Calibration Interval
Agilent	Analyzer, Spectrum	E4446A	MY48250238	2015-11-12	1 year
-	RF cable	-	-	Each time ¹	N/A
-	10 dB attenuator	-	-	Each time ¹	N/A

Note¹: cable and attenuator included in the test set-up will be checked each time before testing.

Statement of Traceability: *BACL Corp. attests that all calibrations have been performed per the A2LA requirements, traceable to the NIST.*

11.4 Test Environmental Conditions

Temperature:	22 °C
Relative Humidity:	42 %
ATM Pressure:	102.5 KPa

The testing was performed by Xiao Lin on 2016-07-30 in RF site.


11.5 Test Results

Channel	Pulse Width (ms)	Number of Hops in the Period Specified in the Requirements	Average Time of Occupancy (s)	Limit (sec)	Results
GFSK,DH1					
Low	0.3833	310	0.118823	0.4	compliant
Middle	0.3726	310	0.115506	0.4	compliant
High	0.3867	320	0.123744	0.4	compliant
GFSK,DH3					
Low	1.65	140	0.231	0.4	compliant
Middle	1.65	130	0.2145	0.4	compliant
High	1.617	170	0.27489	0.4	compliant
GFSK,DH5					
Low	2.9	90	0.261	0.4	compliant
Middle	2.875	70	0.20125	0.4	compliant
High	2.794	90	0.25146	0.4	compliant
Π/4-DQPSK,DH1					
Low	0.3917	300	0.11751	0.4	compliant
Middle	0.3917	300	0.11751	0.4	compliant
High	0.3917	300	0.11751	0.4	compliant
Π/4-DQPSK,DH3					
Low	1.633	170	0.27761	0.4	compliant
Middle	1.633	120	0.19596	0.4	compliant
High	1.65	150	0.2475	0.4	compliant
Π/4-DQPSK,DH5					
Low	2.89	70	0.2023	0.4	compliant
Middle	2.89	80	0.2312	0.4	compliant
High	2.794	90	0.25146	0.4	compliant
8DPSK,DH1					
Low	0.3952	310	0.122512	0.4	compliant
Middle	0.3901	290	0.113129	0.4	compliant
High	0.3901	320	0.124832	0.4	compliant
8DPSK,DH3					
Low	1.673	160	0.26768	0.4	compliant
Middle	1.642	180	0.29556	0.4	compliant
High	1.641	150	0.24615	0.4	compliant
8DPSK,DH5					
Low	2.893	80	0.23144	0.4	compliant
Middle	2.863	100	0.2863	0.4	compliant
High	2.893	70	0.20251	0.4	compliant


Please refer to the following plots for detailed test results.

GFSK, DH1 Pulse Width


Low Channel 2402 MHz



Middle Channel 2441 MHz




High Channel 2480 MHz




GFSK, DH1 Number of Pulses within a Specified Time

Low Channel 2402 MHz

Middle Channel 2441 MHz




High Channel 2480 MHz




GFSK, DH3 Pulse Width


Low Channel 2402 MHz




Middle Channel 2441 MHz




High Channel 2480 MHz




Low Channel 2402 MHz



Middle Channel 2441 MHz




High Channel 2480 MHz




GFSK, DH5 Pulse Width


Low Channel 2402 MHz



Middle Channel 2441 MHz




High Channel 2480 MHz




GFSK, DH5 Number of Pulses within a Specified Time


Low Channel 2402 MHz



Middle Channel 2441 MHz




High Channel 2480 MHz




Π/4-DQPSK, DH1 Pulse Width


Low Channel 2402 MHz



Middle Channel 2441 MHz




High Channel 2480 MHz




Π/4-DQPSK, DH1 Number of Pulses within a Specified Time


Low Channel 2402 MHz



Middle Channel 2441 MHz




High Channel 2480 MHz




Π/4-DQPSK, DH3 Pulse Width


Low Channel 2402 MHz



Middle Channel 2441 MHz




High Channel 2480 MHz




Π/4-DQPSK, DH3 Number of Pulses within a Specified Time


Low Channel 2402 MHz



Middle Channel 2441 MHz




High Channel 2480 MHz




Π/4-DQPSK, DH5 Pulse Width


Low Channel 2402 MHz



Middle Channel 2441 MHz




High Channel 2480 MHz




Π/4-DQPSK, DH5 Number of Pulses within a Specified Time


Low Channel 2402 MHz



Middle Channel 2441 MHz




High Channel 2480 MHz




8DPSK, DH1 Pulse Width


Low Channel 2402 MHz




Middle Channel 2441 MHz



High Channel 2480 MHz



Middle Channel 2441 MHz



Agilent

Ref 19.5 dBm Atten 20 dB

Norm
Log
10
dB/
Offset
10.5
dB

LgAv

W1 S2
S3 FS
AA

E(f):
f>50k

Center 2.480 000 GHz Span 0 Hz
Res BW 100 kHz VBW 300 kHz Sweep 3.16 s (1000 pts)

Freq/Channel

Center Freq
2.48000000 GHz

Start Freq
2.48000000 GHz

Stop Freq
2.48000000 GHz


CF Step
100.000000 kHz
Auto Mar

Freq Offset
0.00000000 Hz


Signal Tracking
On Off

8DPSK, DH3 Pulse Width


Low Channel 2402 MHz



Middle Channel 2441 MHz




High Channel 2480 MHz




8DPSK, DH3 Number of Pulses within a Specified Time


Low Channel 2402 MHz



Middle Channel 2441 MHz




High Channel 2480 MHz




8DPSK, DH5 Pulse Width


Low Channel 2402 MHz



Middle Channel 2441 MHz




High Channel 2480 MHz




8DPSK, DH5 Number of Pulses within a Specified Time


Low Channel 2402 MHz



Middle Channel 2441 MHz



High Channel 2480 MHz



12 FCC §15.247(a)(1)(iii) & ISED RSS-247 §5.1(4) - Number of Hopping Channels

12.1 Applicable Standards

According to FCC §15.247(a) (1) (iii) and RSS-247 §5.1(4): Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

12.2 Test Procedure

Span = the frequency band of operation

RBW < 30% of the channel spacing or the 20 dB bandwidth, whichever is smaller

VBW ≥ RBW

Sweep = auto

Detector function = peak

Trace = max hold

12.3 Test Equipment List and Details

Manufacturer	Description	Model No.	Serial No.	Calibration Date	Calibration Interval
Agilent	Analyzer, Spectrum	E4446A	MY48250238	2015-11-12	1 year
-	RF cable	-	-	Each time ¹	N/A
-	10dB attenuator	-	-	Each time ¹	N/A

Note¹: cable and attenuator included in the test set-up will be checked each time before testing.

Statement of Traceability: *BACL Corp. attests that all calibrations have been performed per the A2LA requirements, traceable to the NIST.*

12.4 Test Environmental Conditions


Temperature:	23 °C
Relative Humidity:	42 %
ATM Pressure:	102.5 KPa

The testing was performed by Jose Martinez on 2016-08-17 in RF site.


12.5 Test Results

Total 79 channels; please refer to the plots hereinafter.

39 Channels between 2400 to 2441 MHz



40 Channels between 2441 to 2483.5 MHz



13 FCC §15.247(a) (1) & ISSED RSS-247 §5.1(2) - Hopping Channel Separation

13.1 Applicable Standards

According to FCC §15.247(a) (1) and RSS-247 §5.1(2): Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

13.2 Test Procedure

Span = wide enough to capture the peaks of two adjacent channels

Resolution (or IF) Bandwidth (RBW) $\approx$ 30% of the channel spacing, adjust as necessary to best identify the center of each individual channel

Video (or Average) Bandwidth (VBW) $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

13.3 Test Equipment List and Details

Manufacturer	Description	Model No.	Serial No.	Calibration Date	Calibration Interval
Agilent	Analyzer, Spectrum	E4446A	MY48250238	2015-11-12	1 year
-	RF cable	-	-	Each time ¹	N/A
-	10dB attenuator	-	-	Each time ¹	N/A

Note¹: cable and attenuator included in the test set-up will be checked each time before testing.

Statement of Traceability: *BACL Corp.* attests that all calibrations have been performed per the A2LA requirements, traceable to the NIST.

13.4 Test Environmental Conditions

Temperature:	23 °C
Relative Humidity:	42 %
ATM Pressure:	102.5 KPa

The testing was performed by Jose Martinez on 2016-08-10 in RF site.


13.5 Test Results

Channel	Frequency (MHz)	Channel Separation (kHz)	Limit > 2/3 20 dB OBW (kHz)
GFSK			
Low	2402	942	557.28
Middle	2441	858	556.88
High	2480	975	556.26
$\pi/4$ -DQPSK			
Low	2402	858	807.92
Middle	2441	1008	810.522
High	2480	1058	838.494
8DPSK			
Low	2402	892	802.53
Middle	2441	858	794.54
High	2480	975	793.21


Please refer to following plots.

GFSK


Low Channel 2402 MHz



Middle Channel 2441 MHz




High Channel 2480 MHz




$\pi/4$ -DQPSK


Low Channel 2402 MHz



Middle Channel 2441 MHz




High Channel 2480 MHz




8DPSK


Low Channel 2402 MHz



Middle Channel 2441 MHz



High Channel 2480 MHz



14 FCC §15.247(d) & ISED RSS-247 §5.5 - Spurious Emissions at Antenna Terminals

14.1 Applicable Standards

For FCC §15.247(d) in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

As per IC RSS-247 §5.5, in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of root-mean-square averaging over a time interval, as permitted under Section 5.4(4), the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general field strength limits specified in RSS-Gen is not required.

14.2 Test Procedure

The RF output of the EUT was connected to a spectrum analyzer through appropriate attenuation. The resolution bandwidth of the spectrum analyzer was set at 100 kHz. Sufficient scans were taken to show any out of band emissions up to 10th harmonic.

14.3 Test Equipment List and Details

Manufacturer	Description	Model No.	Serial No.	Calibration Date	Calibration Interval
Agilent	Analyzer, Spectrum	E4446A	MY48250238	2015-11-12	1 year
-	RF cable	-	-	Each time ¹	N/A
-	10dB attenuator	-	-	Each time ¹	N/A

Note¹: cable and attenuator included in the test set-up will be checked each time before testing.

Statement of Traceability: *BACL Corp.* attests that all calibrations have been performed per the A2LA requirements, traceable to the NIST.

14.4 Test Environmental Conditions

Temperature:	23° C
Relative Humidity:	42 %
ATM Pressure:	102.5 KPa


The testing was performed by Jose Martinez on 2016-08-10 in RF site.

14.5 Test Results


Please refer to following plots.

GFSK


Low Channel 30 MHz – 1 GHz




Low Channels 1GHz – 25 GHz




Middle Channel 30 MHz – 1 GHz




Middle Channels 1 GHz – 25 GHz



High Channel 30 MHz – 1 GHz




High Channels 1 GHz – 25 GHz




$\pi/4$ -DQPSK


Low Channel 30 MHz – 1 GHz




Low Channels 1 GHz – 25 GHz




Middle Channel 30 MHz – 1 GHz




Middle Channels 1 GHz – 25 GHz



High Channel 30 MHz – 1 GHz




High Channels 1 GHz – 25 GHz




8DPSK


Low Channel 30 MHz – 1 GHz




Low Channels 1 GHz – 25 GHz




Middle Channel 30 MHz – 1 GHz



Middle Channels 1 GHz – 25 GHz



High Channel 30 MHz – 1 GHz



High Channels 1 GHz – 25 GHz

