FCC RADIO TEST REPORT

FCC ID	:	COF-WMCW51MS
Equipment	:	802.11a/b/g/n/ac/ax 1x1 + BT 5.3 Combo Module
Brand Name	:	USI
Model Name	:	WM-CW-51MS
Marketing Name	:	WM-CW-51MS
Applicant	:	Universal Global Scientific Industrial Co., Ltd. No. 141, Lane 351, Sec. 1, Taiping Road, Tsaotuen, Nantou County 542007, Taiwan
Manufacturer	:	Universal Global Scientific Industrial Co., Ltd. No. 141, Lane 351, Sec. 1, Taiping Road, Tsaotuen, Nantou County 542007, Taiwan
Standard	:	FCC Part 15 Subpart E §15.407

The product was received on Sep. 16, 2025 and testing was performed from Sep. 26, 2025 to Nov. 17, 2025. We, Sporton International Inc. Wensan Laboratory, would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this variant report apply exclusively to the tested model / sample. Without written approval from Sporton International Inc. Wensan Laboratory, the test report shall not be reproduced except in full.

Louis Wu

Approved by: Louis Wu

Sporton International Inc. Wensan Laboratory

No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City 333010, Taiwan (R.O.C.)

Table of Contents

History of this test report **3**
Summary of Test Result **4**
1 General Description **5**
1.1 Product Feature of Equipment Under Test 5
1.2 Modification of EUT 5
1.3 Testing Location 6
1.4 Applicable Standards 6
2 Test Configuration of Equipment Under Test **7**
2.1 Carrier Frequency and Channel 7
2.2 Test Mode 8
2.3 Connection Diagram of Test System 9
2.4 Support Unit used in test configuration and system 9
2.5 EUT Operation Test Setup 10
2.6 Measurement Results Explanation Example 10
3 Test Result **11**
3.1 6dB and 26dB and 99% Occupied Bandwidth Measurement 11
3.2 Maximum Conducted Output Power Measurement 12
3.3 Power Spectral Density Measurement 13
3.4 Unwanted Emissions Measurement 15
3.5 AC Conducted Emission Measurement 20
3.6 Antenna Requirements 22
4 List of Measuring Equipment **23**
5 Measurement Uncertainty **25**
Appendix A. Conducted Test Results
Appendix B. AC Conducted Emission Test Result
Appendix C. Radiated Spurious Emission Test Result
Appendix D. Duty Cycle Plots
Appendix E. Setup Photographs

History of this test report

Report No.	Version	Description	Issue Date
FR591512-01E	01	Initial issue of report	Jun. 10, 2026
FR591512-01E	02	Revise Ant.1 / Ant. 2 to Original antenna / Second antenna This report is an updated version, replacing the report issued on Jun. 10, 2026.	Jun. 25, 2026

Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
3.1	15.403	6dB & 26dB Bandwidth	Pass	-
3.1	2.1049	99% Occupied Bandwidth	Pass	-
3.2	15.407(a)	Maximum Conducted Output Power	Pass	-
3.3	15.407(a)	Power Spectral Density	Pass	-
3.4	15.407(b)	Unwanted Emissions	Pass	-
3.5	15.207	AC Conducted Emission	Pass	-
3.6	15.203	Antenna Requirement	Pass	-

Note: This is a variant report by adding the second antenna. Since the test result is not affected by the changes, all the test cases were performed on original report which can be referred to Sporton Report Number FR591512E.

Conformity Assessment Condition:

1. The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacturer who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
2. The measurement uncertainty please refer to each test result in the section “Measurement Uncertainty”.

Disclaimer:

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.

Reviewed by: Wei Chen

Report Producer: Shannon Huang

1 General Description

1.1 Product Feature of Equipment Under Test

Product Feature
General Specs Bluetooth, Wi-Fi 2.4GHz 802.11b/g/n/ac/ax, Wi-Fi 5GHz 802.11a/n/ac/ax, Wi-Fi 6GHz 802.11a/ax **Antenna Type** WLAN: <Original antenna>：Dipole Antenna <Second antenna>：Dipole Antenna

Antenna information		
5725 MHz ~ 5850 MHz	Peak Gain (dBi)	<Original antenna>：4.81 <Second antenna>：4.21

Remark: The EUT's information above is declared by manufacturer. Please refer to Disclaimer in report summary.

1.2 Modification of EUT

No modifications made to the EUT during the testing.

1.3 Testing Location

The test location is accredited based on TAF code 3786 designated by NCC (National Communication Commission).

Test Site	Sporton International Inc. Wensan Laboratory
Test Site Location	No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City 333010, Taiwan (R.O.C.)

FCC designation No.: TW3786

Note: The test site complies with ANSI C63.4 2014 requirement.

1.4 Applicable Standards

According to the specifications declared by the manufacturer, the EUT must comply with the requirements of the following standards:

- FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.
- FCC KDB 414788 D01 Radiated Test Site v01r01.
- FCC Part 15 Subpart E
- ANSI C63.10-2020 + Cor.1-2023

Remark:

1. All the test items were validated and recorded in accordance with the standards without any modification during the testing.
2. The TAF code is not including all the FCC KDB listed without accreditation.

2 Test Configuration of Equipment Under Test

a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, the measured emission level of the EUT was maximized by rotating the EUT on a turntable, adjusting the orientation of the EUT and EUT antenna in three orthogonal axis (X: flat, Y: portrait, Z: landscape), and adjusting the measurement antenna orientation, following C63.10 exploratory test procedures and only the worst case emissions were reported in this report.

b. AC power line Conducted Emission was tested under maximum output power.

2.1 Carrier Frequency and Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
5725-5850 MHz Band 4 (U-NII-3)	149	5745	157	5785
	151*	5755	159*	5795
	153	5765	161	5805
	155#	5775	165	5825

Note:

1. The above Frequency and Channel with "*" are 802.11n HT40 and 802.11ac VHT40 and 802.11ax HE40.
2. The above Frequency and Channel with "#" are 802.11ac VHT80 and 802.11ax HE80.

2.2 Test Mode

This device support 26/52/106/242/484/996-tone RU.

The PSD of partial RU is reduced to be smaller than full RU according to TCB workshop interim guidance Oct. 2018.

The 802.11ax mode is investigated among different tones, full resource units (RU), partial resource units. The partial RU has no higher power than full RU's, thus the full RU is chosen as main test configuration.

The 242-tone RU is covered by 20MHz channel, 484-tone RU is covered by 40MHz channel and 996-tone RU is covered by 80MHz channel.

The power for 802.11n and 802.11ac mode is smaller than 802.11ax mode, so all other conducted and radiated test is covered by 802.11ax mode.

The final test modes include the worst data rates for each modulation shown in the table below.

Modulation	Data Rate
802.11a	6 Mbps
802.11n HT20 (Covered by VHT20)	MCS0
802.11n HT40 (Covered by VHT40)	MCS0
802.11ac VHT20	MCS0
802.11ac VHT40	MCS0
802.11ac VHT80	MCS0
802.11ax HE20	MCS0
802.11ax HE40	MCS0
802.11ax HE80	MCS0

Test Cases	
AC Conducted Emission	Mode 1:: WLAN 5G link + BT link Mode 2:: WLAN 6G link + BT link

Remark:
1. The worst case of Conducted Emission is mode 2; only the test data of it was reported.
2. The detailed Radiated test modes are shown in Appendix C.
3. For radiation spurious emission, the modulation and the data rate picked for testing are determined by the Max. RF conducted power.

2.3 Connection Diagram of Test System



2.4 Support Unit used in test configuration and system

Item	Equipment	Brand Name	Model Name	FCC ID	Data Cable	Power Cord
1.	DC Power Supply	GW Instek	GPE2323	NA	N/A	N/A
2.	WLAN AP	Netgear	RAXE500	PY320300508	N/A	Unshielded,1.8m
3.	Bluetooth Earphone	SonyErricsson	MW600	PY700A2029	N/A	N/A
4.	DC Power Supply	GW Instek	GPE-2323	FCC DoC	N/A	Unshielded,1.8m

2.5 EUT Operation Test Setup

The RF test items, utility “Terminal” was installed in Notebook which was programmed in order to make the EUT get into the engineering modes to provide channel selection, power level, data rate and the application type and for continuous transmitting signals.

2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 4.2 dB and 10 dB attenuator.

Offset(dB) = RF cable loss(dB) + attenuator factor(dB).

= 4.2 + 10 = 14.2 (dB)

3 Test Result

3.1 6dB and 26dB and 99% Occupied Bandwidth Measurement

3.1.1 Description of 6dB and 26dB and 99% Occupied Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.

26dB and 99% Occupied bandwidth are reporting only.

3.1.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.1.3 Test Procedures

1. The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01. Section C) Emission bandwidth for the band 5.725-5.85 GHz
2. Set RBW = 100 kHz.
3. Set the VBW ≥ 3 x RBW.
4. Detector = Peak.
5. Trace mode = max hold
6. Measure the maximum width of the emission that is 6 dB down from the peak of the emission.
7. Measure and record the results in the test report.

3.1.4 Test Setup



3.1.5 Test Result of 6dB and 26dB and 99% Occupied Bandwidth

Please refer to Appendix A.

3.2 Maximum Conducted Output Power Measurement

3.2.1 Limit of Maximum Conducted Output Power

For the band 5.725–5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W.

If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

3.2.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.2.3 Test Procedures

The testing follows Method PM-G of FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.

Method PM-G (Measurement using a gated RF average power meter):

1. Measurement is performed using a wideband RF power meter.
2. The EUT is configured to transmit at its maximum power control level.
3. Measure the average power of the transmitter.
4. Since the measurement is made only during the ON time of the transmitter, no duty cycle correction factor is required.

3.2.4 Test Setup



3.2.5 Test Result of Maximum Conducted Output Power

Please refer to Appendix A.

3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

For the band 5.725–5.85 GHz, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band.

If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

3.3.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.3.3 Test Procedures

The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.
Section F) Maximum power spectral density.

 # Method SA-2 #

(trace averaging across on and off times of the EUT transmissions, followed by duty cycle correction).

- Measure the duty cycle.
- Set span to encompass the entire emission bandwidth (EBW) of the signal.
- Set RBW = 500kHz.
- Set VBW ≥ 1 MHz.
- Number of points in sweep ≥ 2 Span / RBW.
- Sweep time = auto.
- Detector = RMS
- Trace average at least 100 traces in power averaging mode.
- Add 10 log(1/x), where x is the duty cycle, to the measured power in order to compute the average power during the actual transmission times. For example, add 10 log(1/0.25) = 6 dB if the duty cycle is 25 percent.

1. The RF output of EUT is connected to the spectrum analyzer by a low loss cable.
2. Each plot has already offset with cable loss, and attenuator loss. Measure the PPSD and record it.

3.3.4 Test Setup



3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.

3.4 Unwanted Emissions Measurement

This section is to measure unwanted emissions through radiated measurement for band edge spurious emissions and out of band emissions measurement.

3.4.1 Limit of Unwanted Emissions

(1) For transmitters operating in the 5.725-5.85 GHz band:

15.407(b)(4)(i) All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

(2) Unwanted spurious emissions falls in restricted bands shall comply with the general field strength limits as below table,

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

Note: The following formula is used to convert the EIRP to field strength.

$$E=\frac{1000000\sqrt{30P}}{3}$$ μV/m, where P is the eirp (Watts)

EIRP (dBm)	Field Strength at 3m (dBμV/m)
- 27	68.3

(3) KDB789033 D02 v02r01 G)2)c)

(i) Sections 15.407(b)(1-3) specifies the unwanted emissions limit for the U-NII-1 and U-NII-2 bands. As specified, emissions above 1000 MHz that are outside of the restricted bands are subject to a peak emission limit of −27 dBm/MHz.

(ii) Section 15.407(b)(4) specifies the unwanted emissions limit for the U-NII-3 band. A band emissions mask is specified in Section 15.407(b)(4)(i). The emission limits are based on the use of a peak detector.

3.4.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.4.3 Test Procedures

1. The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01. Section G) Unwanted emissions measurement.

   (1) Procedure for Unwanted Emissions Measurements Below 1000 MHz

   - RBW = 120 kHz
   - VBW = 300 kHz
   - Detector = Peak
   - Trace mode = max hold

   (2) Procedure for Peak Unwanted Emissions Measurements Above 1000 MHz

   - RBW = 1 MHz
   - VBW ≥ 3 MHz
   - Detector = Peak
   - Sweep time = auto
   - Trace mode = max hold

   (3) Procedures for Average Unwanted Emissions Measurements Above 1000 MHz

   - RBW = 1 MHz
   - VBW = 10 Hz, when duty cycle is no less than 98 percent.
   - VBW ≥ 1/T, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.
2. The EUT is placed on a turntable with 0.8 meter for frequency below 1 GHz and 1.5 meter for frequency above 1 GHz respectively above ground.
3. The EUT is set 3 meters away from the receiving antenna which is mounted on the top of a variable height antenna tower.
4. The antenna is a broadband antenna and its height is adjusted between one meter and four meters above ground to find the maximum value of the field strength for both horizontal polarization and vertical polarization of the antenna.
5. For each suspected emission, the EUT is arranged to its worst case and then adjust the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading.

6. Radiated testing below 1 GHz is performed by adjusting the antenna tower from 1 m to 4 m and by rotating the turn table from 0 degree to 360 degrees to find the peak maximum hold reading. When there is no suspected emission found and the emission level is with at least 6 dB margin against QP limit line, the position is marked as "-".
7. Radiated testing above 1 GHz is performed by adjusting the antenna tower from 1 m to 4 m and by rotating the turn table from 0 degree to 360 degrees to find the peak maximum hold reading for scanning all frequencies.
   When there is no suspected emission found and the harmonic emission level is with at least 6 dB margin against average limit line, the position is marked as "-".

3.4.4 Test Setup

For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated test from 1GHz to 18GHz



For radiated test above 18GHz



3.4.5 Test Results of Radiated Emissions (9 kHz ~ 30 MHz)

The low frequency, which starts from 9 kHz to 30 MHz, is pre-scanned and the result which is 20 dB lower than the limit line is not reported.

There is adequate comparison measurement of both open-field test site and alternative test site - semi-Anechoic chamber according to 414788 D01 Radiated Test Site **v01r01**, and the result came out very similar.

3.4.6 Test Result of Radiated Band Edges

Please refer to Appendix C.

3.4.7 Duty Cycle

Please refer to Appendix D.

3.4.8 Test Result of Unwanted Radiated Emission (30MHz ~ 10th Harmonic)

Please refer to Appendix C.

3.5 AC Conducted Emission Measurement

3.5.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dBμV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

3.5.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.5.3 Test Procedures

1. The EUT is placed 0.4 meter away from the conducting wall of the shielding room, and is kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN shall be used.
6. Both Line and Neutral shall be tested in order to find out the maximum conducted emission.
7. The frequency range from 150 kHz to 30 MHz is scanned.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode.

3.5.4 Test Setup



AMN = Artificial mains network (LISN)
AE = Associated equipment
EUT = Equipment under test
ISN = Impedance stabilization network

3.5.5 Test Result of AC Conducted Emission

Please refer to Appendix B.

3.6 Antenna Requirements

3.6.1 Standard Applicable

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of § 15.211, 15.213, 15.217, 15.219, 15.221, or § 15.236. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with § 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

3.6.2 Antenna Anti-Replacement Construction

Professional installation.

4 List of Measuring Equipment

Instrument	Brand Name	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Loop Antenna	Rohde & Schwarz	HFH2-Z2E	101108	9 kHz~30 MHz	Dec 18, 2024	Oct. 18, 2025~ Oct. 30, 2025	Dec 17, 2025	Radiation (03CH23-HY)
Bilog Antenna	TESEQ & WOKEN	CBL 6111D & 00802N1D-06	62028 & 003	30MHz~1GHz	Nov. 27, 2024	Oct. 18, 2025~ Oct. 30, 2025	Nov. 26, 2025	Radiation (03CH23-HY)
Amplifier	SONOMA	310N	421582	9kHz~1GHz	Jul. 13, 2025	Oct. 18, 2025~ Oct. 30, 2025	Jul. 12 2026	Radiation (03CH23-HY)
Amplifier	EMEC	EM01G18GA	060878	1GHz~18GHz	Sep. 26, 2025	Oct. 18, 2025~ Oct. 30, 2025	Sep. 25, 2026	Radiation (03CH23-HY)
Double Ridged Guide Horn Antenna	RFSPIN	DRH18-E	LE2C05A18EN	1GHz~18GHz	Jul.02 ,2025	Oct. 18, 2025~ Oct. 30, 2025	Jul. 01,2026	Radiation (03CH23-HY)
SHF-EHF Horn Antenna	SCHWARZBECK	BBHA 9170	1225	18GHz-40GHz	Jul.02 ,2025	Oct. 18, 2025~ Oct. 30, 2025	Jul. 01,2026	Radiation (03CH23-HY)
Preamplifier	EMEC	EM18G40G	060873	18GHz-40GHz	Aug. 26, 2025	Oct. 18, 2025~ Oct. 30, 2025	Aug. 25, 2026	Radiation (03CH23-HY)
Signal Analyzer	Keysight	N9010B	MY62170337	10Hz~44GHz	Aug. 26, 2025	Oct. 18, 2025~ Oct. 30, 2025	Aug. 25, 2026	Radiation (03CH23-HY)
Hygrometer	TECPEL	DTM-303A	TP211469	N/A	Dec. 24, 2024	Oct. 18, 2025~ Oct. 30, 2025	Dec. 23, 2025	Radiation (03CH23-HY)
Controller	EMEC	EM1000	N/A	Control Turn table & Ant Mast	N/A	Oct. 18, 2025~ Oct. 30, 2025	N/A	Radiation (03CH23-HY)
Antenna Mast	ChainTek	MBS-520-1	N/A	1m~4m	N/A	Oct. 18, 2025~ Oct. 30, 2025	N/A	Radiation (03CH23-HY)
Turn Table	ChainTek	T-200-S-1	N/A	0~360 Degree	N/A	Oct. 18, 2025~ Oct. 30, 2025	N/A	Radiation (03CH23-HY)
Software	Audix	E3 6.09824_2019122	RK-002348	N/A	N/A	Oct. 18, 2025~ Oct. 30, 2025	N/A	Radiation (03CH23-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	804395/2	30MHz~40GHz	Nov. 26, 2024	Oct. 18, 2025~ Oct. 30, 2025	Nov. 25, 2025	Radiation (03CH23-HY)
RF Cable	EMC	EMC101Y	231115/231119/231122	30MHz~40GHz	Nov. 26, 2024	Oct. 18, 2025~ Oct. 30, 2025	Nov. 25, 2025	Radiation (03CH23-HY)

Instrument	Brand Name	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
AC Power Source	ACPOWER	AFC-11003G	F317040033	N/A	N/A	Nov. 17, 2025	N/A	Conduction (CO07-HY)
Software	Rohde & Schwarz	EMC32 V10.30	N/A	N/A	N/A	Nov. 17, 2025	N/A	Conduction (CO07-HY)
Pulse Limiter	SCHWARZBECK	VTSD 9561-F N	9561-F N00373	9kHz-200MHz	Oct. 20, 2025	Nov. 17, 2025	Oct. 19, 2026	Conduction (CO07-HY)
RF Cable	HUBER + SUHNER	RG 214/U	1358175	9kHz~30MHz	Mar. 03, 2025	Nov. 17, 2025	Mar. 02, 2026	Conduction (CO07-HY)
Two-Line V-Network	TESEQ	NNB 51	45051	N/A	Mar. 24, 2025	Nov. 17, 2025	Mar. 23, 2026	Conduction (CO07-HY)
Four-Line V-Network	TESEQ	NNB 52	36122	N/A	Mar. 26, 2025	Nov. 17, 2025	Mar. 25, 2026	Conduction (CO07-HY)
EMI Test Receiver	Rohde & Schwarz	ESCI7	100724	9kHz~7GHz	Feb. 13, 2025	Nov. 17, 2025	Feb. 12, 2026	Conduction (CO07-HY)
Hygrometer	TECPEL	DTM-303A	TP224371	N/A	Jun. 16, 2025	Sep. 26, 2025~ Nov. 03, 2025	Jun. 15, 2026	Conducted (TH05-HY)
Power Sensor	DARE	RPR3006W	13I00030SNO31 (NO:182)	9kHz~6GHz	Jan. 09, 2025	Sep. 26, 2025~ Nov. 03, 2025	Jan. 08, 2026	Conducted (TH05-HY)
Signal Analyzer	Rohde & Schwarz	FSV40	101566	10Hz~40GHz	Aug. 29, 2025	Sep. 26, 2025~ Nov. 03, 2025	Aug. 28, 2026	Conducted (TH05-HY)
Switch Control Mainframe	E-Instument	ETF-1405-0	EC1900157 (BOX6)	N/A	Feb. 10, 2025	Sep. 26, 2025~ Nov. 03, 2025	Feb. 09, 2026	Conducted (TH05-HY)
Software	Sporton	BTWIFI_Final_version_240513	N/A	Conducted Other Test Item	N/A	Sep. 26, 2025~ Nov. 03, 2025	N/A	Conducted (TH05-HY)

5 Measurement Uncertainty

Uncertainty of Conducted Emission Measurement (150kHz ~ 30MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	3.7 dB

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	6.6 dB

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 6000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	5.4 dB

Uncertainty of Radiated Emission Measurement (6000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	4.8 dB

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	5.7 dB

Appendix A. Test Result of Conducted Test Items

Test Engineer:	Willy Chang	Temperature:	21~25	°C
Test Date:	2025/9/26~2025/11/3	Relative Humidity:	51~54	%

TEST RESULTS DATA
6dB and 26dB EBW and 99% OBW

U-NII-3 single antenna												
Mod.	Data Rate	N_{TX}	CH.	Freq. (MHz)	99% Bandwidth (MHz)		26dB Bandwidth (MHz)		6 dB Bandwidth (MHz)		6 dB Bandwidth Min. Limit (MHz)	Pass/Fail
					Second antenna	-	Second antenna	-	Second antenna	-		
11a	6Mbps	1	149	5745	17.95	-	21.98	-	16.29	-	0.5	Pass
11a	6Mbps	1	157	5785	18.06	-	22.81	-	16.29	-	0.5	Pass
11a	6Mbps	1	165	5825	18.03	-	22.16	-	16.00	-	0.5	Pass
VHT20	MCS0	1	149	5745	18.79	-	25.02	-	17.50	-	0.5	Pass
VHT20	MCS0	1	157	5785	18.72	-	25.34	-	17.27	-	0.5	Pass
VHT20	MCS0	1	165	5825	18.78	-	25.99	-	16.91	-	0.5	Pass
VHT40	MCS0	1	151	5755	36.73	-	41.50	-	35.73	-	0.5	Pass
VHT40	MCS0	1	159	5795	36.53	-	40.86	-	35.49	-	0.5	Pass
VHT80	MCS0	1	155	5775	76.18	-	83.30	-	75.20	-	0.5	Pass

TEST RESULTS DATA
Average Power Table

U-NII-3 single antenna												
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Average Conducted Power (dBm)			FCC Conducted Power Limit (dBm)		DG (dBi)		Pass/Fail
					Second antenna	-	SUM	Second antenna	-	Second antenna	-	
11a	6Mbps	1	149	5745	18.11	-		30.00	-	4.82	-	Pass
11a	6Mbps	1	157	5785	18.15	-		30.00	-	4.82	-	Pass
11a	6Mbps	1	165	5825	18.71	-		30.00	-	4.82	-	Pass
HT20	MCS0	1	149	5745	18.82	-		30.00	-	4.82	-	Pass
HT20	MCS0	1	157	5785	17.98	-		30.00	-	4.82	-	Pass
HT20	MCS0	1	165	5825	18.68	-		30.00	-	4.82	-	Pass
HT40	MCS0	1	151	5755	17.86	-		30.00	-	4.82	-	Pass
HT40	MCS0	1	159	5795	17.41	-		30.00	-	4.82	-	Pass
VHT20	MCS0	1	149	5745	18.86	-		30.00	-	4.82	-	Pass
VHT20	MCS0	1	157	5785	18.04	-		30.00	-	4.82	-	Pass
VHT20	MCS0	1	165	5825	18.73	-		30.00	-	4.82	-	Pass
VHT40	MCS0	1	151	5755	17.98	-		30.00	-	4.82	-	Pass
VHT40	MCS0	1	159	5795	17.46	-		30.00	-	4.82	-	Pass
VHT80	MCS0	1	155	5775	17.55	-		30.00	-	4.82	-	Pass

TEST RESULTS DATA
Power Spectral Density

U-NII-3 single antenna														
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Duty Factor (dB)		Average Power Density with Duty Factor (dBm/500kHz)			Average PSD Limit (dBm/500kHz)		DG (dBi)		Pass /Fail
					Second antenna	-	Second antenna	-	SUM	Second antenna	-	Second antenna	-	
11a	6Mbps	1	149	5745	0.43		4.37	-		30.00	-	4.82	-	Pass
11a	6Mbps	1	157	5785	0.43		4.99	-		30.00	-	4.82	-	Pass
11a	6Mbps	1	165	5825	0.43		5.45	-		30.00	-	4.82	-	Pass
VHT20	MCS0	1	149	5745	0.46		5.02	-		30.00	-	4.82	-	Pass
VHT20	MCS0	1	157	5785	0.46		4.66	-		30.00	-	4.82	-	Pass
VHT20	MCS0	1	165	5825	0.46		5.08	-		30.00	-	4.82	-	Pass
VHT40	MCS0	1	151	5755	0.88		1.58	-		30.00	-	4.82	-	Pass
VHT40	MCS0	1	159	5795	0.88		1.60	-		30.00	-	4.82	-	Pass
VHT80	MCS0	1	155	5775	1.62		-1.58	-		30.00	-	4.82	-	Pass

Note: PSD Sum = Max PSD(Ant. 1, Ant. 2) + 10 log (n)

TEST RESULTS DATA
6dB and 26dB EBW and 99% OBW

U-NII-3 single antenna													
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	RU Config.	99% Bandwidth (MHz)		26dB Bandwidth (MHz)		6 dB Bandwidth (MHz)		6 dB Bandwidth Min. Limit (MHz)	Pass/Fail
						Second antenna	-	Second antenna	-	Second antenna	-		
HE20	MCS0	1	149	5745	Full	19.28	-	21.98	-	18.84	-	0.5	Pass
HE20	MCS0	1	157	5785	Full	19.28	-	21.91	-	18.86	-	0.5	Pass
HE20	MCS0	1	165	5825	Full	19.29	-	21.94	-	18.84	-	0.5	Pass
HE40	MCS0	1	151	5755	Full	37.84	-	40.66	-	37.19	-	0.5	Pass
HE40	MCS0	1	159	5795	Full	37.75	-	40.91	-	36.57	-	0.5	Pass
HE80	MCS0	1	155	5775	Full	77.61	-	83.55	-	75.86	-	0.5	Pass

Report Number : FR591512-01E

TEST RESULTS DATA
Average Power Table

U-NII-3 single antenna													
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	RU Config.	Average Conducted Power (dBm)			FCC Conducted Power Limit (dBm)		DG (dBi)		Pass/Fail
						Second antenna	-	SUM	Second antenna	-	Second antenna	-	
HE20	MCS0	1	149	5745	Full	17.04	-		30.00	-	4.82	-	Pass
HE20	MCS0	1	149	5745	26/0	8.97	-		30.00	-	4.82	-	Pass
HE20	MCS0	1	149	5745	52/37	11.76	-		30.00	-	4.82	-	Pass
HE20	MCS0	1	149	5745	106/53	15.11	-		30.00	-	4.82	-	Pass
HE20	MCS0	1	157	5785	Full	17.17	-		30.00	-	4.82	-	Pass
HE20	MCS0	1	157	5785	26/4	10.21	-		30.00	-	4.82	-	Pass
HE20	MCS0	1	157	5785	52/38	12.63	-		30.00	-	4.82	-	Pass
HE20	MCS0	1	157	5785	106/53	15.82	-		30.00	-	4.82	-	Pass
HE20	MCS0	1	165	5825	Full	17.79	-		30.00	-	4.82	-	Pass
HE20	MCS0	1	165	5825	26/8	10.06	-		30.00	-	4.82	-	Pass
HE20	MCS0	1	165	5825	52/40	12.98	-		30.00	-	4.82	-	Pass
HE20	MCS0	1	165	5825	106/54	16.44	-		30.00	-	4.82	-	Pass
HE40	MCS0	1	151	5755	Full	17.99	-		30.00	-	4.82	-	Pass
HE40	MCS0	1	151	5755	242/61	16.25	-		30.00	-	4.82	-	Pass
HE40	MCS0	1	159	5795	Full	17.43	-		30.00	-	4.82	-	Pass
HE40	MCS0	1	159	5795	242/62	16.33	-		30.00	-	4.82	-	Pass
HE80	MCS0	1	155	5775	Full	17.51	-		30.00	-	4.82	-	Pass
HE80	MCS0	1	155	5775	484/65	14.13	-		30.00	-	4.82	-	Pass
HE80	MCS0	1	155	5775	484/66	14.57	-		30.00	-	4.82	-	Pass

Report Number : FR591512-01E

TEST RESULTS DATA
Power Spectral Density

U-NII-3 single antenna															
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	RU Config.	Duty Factor (dB)		Average Power Density with Duty Factor (dBm/500kHz)			Average PSD Limit (dBm/500kHz)		DG (dBi)		Pass /Fail
						Second antenna	-	Second antenna	-	SUM	Second antenna	-	Second antenna	-	
HE20	MCS0	1	149	5745	Full	0.58	-	2.90	-		30.00	-	4.82	-	Pass
HE20	MCS0	1	149	5745	26/0	1.78	-	2.48	-		30.00	-	4.82	-	Pass
HE20	MCS0	1	149	5745	52/37	2.97	-	2.42	-		30.00	-	4.82	-	Pass
HE20	MCS0	1	149	5745	106/53	4.69	-	2.64	-		30.00	-	4.82	-	Pass
HE20	MCS0	1	157	5785	Full	0.58	-	3.69	-		30.00	-	4.82	-	Pass
HE20	MCS0	1	157	5785	26/4	1.78	-	3.67	-		30.00	-	4.82	-	Pass
HE20	MCS0	1	157	5785	52/38	2.97	-	3.22	-		30.00	-	4.82	-	Pass
HE20	MCS0	1	157	5785	106/53	4.69	-	3.42	-		30.00	-	4.82	-	Pass
HE20	MCS0	1	165	5825	Full	0.58	-	4.19	-		30.00	-	4.82	-	Pass
HE20	MCS0	1	165	5825	26/8	1.78	-	3.70	-		30.00	-	4.82	-	Pass
HE20	MCS0	1	165	5825	52/40	2.97	-	3.69	-		30.00	-	4.82	-	Pass
HE20	MCS0	1	165	5825	106/54	4.69	-	3.93	-		30.00	-	4.82	-	Pass
HE40	MCS0	1	151	5755	Full	1.05	-	1.62	-		30.00	-	4.82	-	Pass
HE40	MCS0	1	151	5755	242/61	6.80	-	1.12	-		30.00	-	4.82	-	Pass
HE40	MCS0	1	159	5795	Full	1.05	-	1.68	-		30.00	-	4.82	-	Pass
HE40	MCS0	1	159	5795	242/62	6.80	-	1.47	-		30.00	-	4.82	-	Pass
HE80	MCS0	1	155	5775	Full	1.78	-	-1.38	-		30.00	-	4.82	-	Pass
HE80	MCS0	1	155	5775	484/65	8.45	-	-1.99	-		30.00	-	4.82	-	Pass
HE80	MCS0	1	155	5775	484/66	8.45	-	-1.79	-		30.00	-	4.82	-	Pass

Note: PSD Sum = Max PSD(Ant. 1, Ant. 2) + 10 log (n)

Test Result of 6dB and 26dB and 99% Occupied Bandwidth

SISO

<802.11a>

6dB Bandwidth	26dB Bandwidth
	
99% Occupied Bandwidth	**N/A**
	

<802.11ac VHT20>

6dB Bandwidth	26dB Bandwidth
	
99% Occupied Bandwidth	**N/A**
	

<802.11ac VHT40>

6dB Bandwidth	26dB Bandwidth
	
99% Occupied Bandwidth	**N/A**
	

<802.11ac VHT80>

6dB Bandwidth	26dB Bandwidth
	
99% Occupied Bandwidth	**N/A**
	

<802.11ax HE20>

6dB Bandwidth	26dB Bandwidth
	
99% Occupied Bandwidth	**N/A**
	

<802.11ax HE40>

6dB Bandwidth	26dB Bandwidth
	
99% Occupied Bandwidth	**N/A**
	

<802.11ax HE80>

6dB Bandwidth	26dB Bandwidth
	
99% Occupied Bandwidth	**N/A**
	

Test Result of Power Spectral Density

<802.11a>

Maximum Power Density Plot (dBm/500kHz)	
Second antenna	**-**
	

<802.11ac VHT20>

Maximum Power Density Plot (dBm/500kHz)	
Second antenna	**-**
	

<802.11ac VHT40>

Maximum Power Density Plot (dBm/500kHz)	
Second antenna	**-**
	

<802.11ac VHT80>

Maximum Power Density Plot (dBm/500kHz)	
Second antenna	**-**
	

<802.11ax HE20>

Maximum Power Density Plot (dBm/500kHz)	
Second antenna	**-**
	

<802.11ax HE40>

Maximum Power Density Plot (dBm/500kHz)	
Second antenna	**-**
	

<802.11ax HE80>

Maximum Power Density Plot (dBm/500kHz)	
Second antenna	**-**
	

Appendix B. AC Conducted Emission Test Results

Test Engineer :	Louis Chung	**Temperature :**	22.6~25.3℃
		Relative Humidity :	45.8~51.1%

EUT Information

Report NO :	591512-01
Test Mode :	Mode 2
Test Voltage :	120Vac/60Hz
Phase :	Line



Final_Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.154000	---	26.82	55.78	28.96	L1	OFF	20.0
0.154000	29.77	---	65.78	36.01	L1	OFF	20.0
0.250000	---	7.06	51.76	44.70	L1	OFF	20.0
0.250000	10.84	---	61.76	50.92	L1	OFF	20.0
19.206000	---	22.94	50.00	27.06	L1	OFF	20.2
19.206000	28.40	---	60.00	31.60	L1	OFF	20.2
21.546000	---	36.68	50.00	13.32	L1	OFF	20.2
21.546000	42.80	---	60.00	17.20	L1	OFF	20.2
22.942000	---	35.74	50.00	14.26	L1	OFF	20.2
22.942000	42.10	---	60.00	17.90	L1	OFF	20.2
24.142000	---	36.90	50.00	13.10	L1	OFF	20.2
24.142000	43.45	---	60.00	16.55	L1	OFF	20.2

EUT Information

Report NO :	591512-01
Test Mode :	Mode 2
Test Voltage :	120Vac/60Hz
Phase :	Neutral



Final_Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.154000	---	26.89	55.78	28.89	N	OFF	20.0
0.154000	29.70	---	65.78	36.08	N	OFF	20.0
0.650000	---	5.87	46.00	40.13	N	OFF	20.0
0.650000	8.80	---	56.00	47.20	N	OFF	20.0
18.826000	---	21.92	50.00	28.08	N	OFF	20.2
18.826000	27.94	---	60.00	32.06	N	OFF	20.2
21.534000	---	38.04	50.00	11.96	N	OFF	20.2
21.534000	44.15	---	60.00	15.85	N	OFF	20.2
22.934000	---	36.64	50.00	13.36	N	OFF	20.2
22.934000	42.94	---	60.00	17.06	N	OFF	20.2
24.330000	---	38.01	50.00	11.99	N	OFF	20.2
24.330000	43.93	---	60.00	16.07	N	OFF	20.2

Appendix C. Radiated Spurious Emission Test Data

Test Engineer :	Leo Li, Karl Hou, and Lucifer Jiang	**Temperature :**	19.0 ~ 23.0°C
		Relative Humidity :	60.0 ~ 64.5%

Note symbol

-L	**Low channel location**
-R	**High channel location**

C1. Radiated Spurious Emission Test Modes

Mode	Band	Band (GHz)	Antenna	Modulation	Channel	Frequency	Data Rate	RU	Remark
Mode 46	U-NII-3	5.725-5.85	Second antenna	802.11a	149	5745	6Mbps	-	-
Mode 47	U-NII-3	5.725-5.85	Second antenna	802.11a	157	5785	6Mbps	-	-
Mode 48	U-NII-3	5.725-5.85	Second antenna	802.11a	165	5825	6Mbps	-	-
Mode 49	U-NII-3	5.725-5.85	Second antenna	802.11ax HE20	149	5745	MCS0	Full RU	-
Mode 50	U-NII-3	5.725-5.85	Second antenna	802.11ax HE20	149	5745	MCS0	Partial RU 106/53	-
Mode 51	U-NII-3	5.725-5.85	Second antenna	802.11ax HE20	157	5785	MCS0	Full RU	-
Mode 52	U-NII-3	5.725-5.85	Second antenna	802.11ax HE20	165	5825	MCS0	Full RU	-
Mode 53	U-NII-3	5.725-5.85	Second antenna	802.11ax HE20	165	5825	MCS0	Partial RU 106/54	-
Mode 54	U-NII-3	5.725-5.85	Second antenna	802.11ax HE40	151	5755	MCS0	Full RU	-
Mode 55	U-NII-3	5.725-5.85	Second antenna	802.11ax HE40	151	5755	MCS0	Partial RU 242/61	-
Mode 56	U-NII-3	5.725-5.85	Second antenna	802.11ax HE40	159	5795	MCS0	Full RU	-

Mode	Band	Band (GHz)	Antenna	Modulation	Channel	Frequency	Data Rate	RU	Remark
Mode 57	U-NII-3	5.725-5.85	**Second antenna**	802.11ax HE40	159	5795	MCS0	Partial RU 242/62	-
Mode 58	U-NII-3	5.725-5.85	**Second antenna**	802.11ax HE80	155	5775	MCS0	Full RU	-
Mode 59	U-NII-3	5.725-5.85	**Second antenna**	802.11ax HE80	155	5775	MCS0	Partial RU 484/65	-
Mode 60	U-NII-3	5.725-5.85	**Second antenna**	802.11ax HE80	155	5775	MCS0	Partial RU 484/66	-
Mode 118	U-NII-3	5.725-5.85	**Second antenna**	802.11ax HE80	155	5775	MCS0	Full RU	LF
Mode 120	U-NII-3	5.725-5.85	**Second antenna**	802.11ax HE80	155	5775	MCS0	Full RU	SHF

C2. Summary of each worse mode

Mode	Modulation	Ch.	Freq. (MHz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pol.	Peak Avg.	Result	RU	Remark
46	802.11a	149	5646.98	53.39	68.20	-14.81	H	Peak	Pass	-	Band Edge
	802.11a	149	11490.00	42.18	54.00	-11.82	H	Avg.	Pass	-	Harmonic
47	802.11a	157	5946.87	52.29	68.20	-15.91	V	Peak	Pass	-	Band Edge
	802.11a	157	11570.00	43.25	54.00	-10.75	V	Avg.	Pass	-	Harmonic
48	802.11a	165	5933.38	52.71	68.20	-15.49	H	Peak	Pass	-	Band Edge
	802.11a	165	11650.00	42.97	54.00	-11.03	V	Avg.	Pass	-	Harmonic
49	802.11ax HE20	149	5642.92	53.13	68.20	-15.07	H	Peak	Pass	Full RU	Band Edge
	802.11ax HE20	149	11490.00	41.71	54.00	-12.29	H	Avg.	Pass	Full RU	Harmonic
50	802.11ax HE20	149	5647.71	53.35	68.20	-14.85	H	Peak	Pass	Partial RU 106/53	Band Edge
	802.11ax HE20	149	-	-	-	-	-	-	-	Partial RU 106/53	Harmonic
51	802.11ax HE20	157	5647.92	53.30	68.20	-14.90	H	Peak	Pass	Full RU	Band Edge

Mode	Modulation	Ch.	Freq. (MHz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pol.	Peak Avg.	Result	RU	Remark
51	802.11ax HE20	157	11570.00	41.84	54.00	-12.16	V	Avg.	Pass	Full RU	Harmonic
52	802.11ax HE20	165	5934.63	53.34	68.20	-14.86	H	Peak	Pass	Full RU	Band Edge
	802.11ax HE20	165	11650.00	41.93	54.00	-12.07	V	Avg.	Pass	Full RU	Harmonic
53	802.11ax HE20	165	5924.75	56.60	68.38	-11.78	H	Peak	Pass	Partial RU 106/54	Band Edge
	802.11ax HE20	165	-	-	-	-	-	-	-	Partial RU 106/54	Harmonic
54	802.11ax HE40	151	5636.89	53.50	68.20	-14.70	H	Peak	Pass	Full RU	Band Edge
	802.11ax HE40	151	11510.00	42.13	54.00	-11.87	V	Avg.	Pass	Full RU	Harmonic
55	802.11ax HE40	151	5634.57	53.18	68.20	-15.02	V	Peak	Pass	Partial RU 242/61	Band Edge
	802.11ax HE40	151	-	-	-	-	-	-	-	Partial RU 242/61	Harmonic
56	802.11ax HE40	159	5649.92	52.81	68.20	-15.39	H	Peak	Pass	Full RU	Band Edge
	802.11ax HE40	159	11590.00	41.98	54.00	-12.02	V	Avg.	Pass	Full RU	Harmonic

Mode	Modulation	Ch.	Freq. (MHz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pol.	Peak Avg.	Result	RU	Remark
57	802.11ax HE40	159	5947.83	53.02	68.20	-15.18	H	Peak	Pass	Partial RU 242/62	Band Edge
	802.11ax HE40	159	-	-	-	-	-	-	-	Partial RU 242/62	Harmonic
58	802.11ax HE80	155	5642.18	61.24	68.20	-6.96	H	Peak	Pass	Full RU	Band Edge
	802.11ax HE80	155	11550.00	42.15	54.00	-11.85	H	Avg.	Pass	Full RU	Harmonic
59	802.11ax HE80	155	5927.08	52.57	68.20	-15.63	H	Peak	Pass	Partial RU 484/65	Band Edge
	802.11ax HE80	155	-	-	-	-	-	-	-	Partial RU 484/65	Harmonic
60	802.11ax HE80	155	5925.15	52.57	68.20	-15.63	H	Peak	Pass	Partial RU 484/66	Band Edge
	802.11ax HE80	155	-	-	-	-	-	-	-	Partial RU 484/66	Harmonic
118	LF	155	35.82	32.16	40.00	-7.84	V	Peak	Pass	-	LF
120	SHF	155	39550.79	47.93	74.00	-26.07	H	Peak	Pass	-	SHF

Mode	46	
	Band Edge	
	U-NII-3_5.725-5.85_802.11a_CH149_5745MHz	
ANT	Second antenna	
Pol.	Horizontal	Fundamental
Peak	 Site : 03CH23-HY Condition: PEAK_BE(B4)_16-24 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5646.98 53.39 68.20 -14.81 39.01 33.48 11.18 33.84 3.56 100 287 Peak 2 5650.32 51.56 68.43 -16.87 37.16 33.50 11.18 33.85 3.57 100 287 Peak 3 5713.54 67.22 108.99 -41.77 52.52 33.85 11.20 33.93 3.58 100 287 Peak 4 5721.22 73.59 113.58 -39.99 58.86 33.88 11.20 33.94 3.59 100 287 Peak	 Site : 03CH23-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5745.00 112.40 ------ ------ 97.57 34.00 11.21 33.98 3.60 100 287 Peak
Avg	Blank	 Site : 03CH23-HY Condition: AVG_54 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL : RBW:1000.000kHz VBW:0.750kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5745.00 103.15 ------ ------ 88.34 33.98 11.21 33.97 3.59 100 287 Average

Mode	46	
	Band Edge	
	U-NII-3_5.725-5.85_802.11a_CH149_5745MHz	
ANT	Second antenna	
Pol.	Vertical	Fundamental
Peak	 Site : 03CH23-HY Condition: PEAK_BE(B4)_16-24 3m DRH18-E_LE2C05A18EN_250702 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5636.69 52.48 68.20 -15.72 38.16 33.42 11.17 33.83 3.56 254 67 Peak 2 5650.17 52.13 68.33 -16.20 37.73 33.50 11.18 33.85 3.57 254 67 Peak 3 5717.89 67.80 110.21 -42.41 53.07 33.87 11.20 33.93 3.59 254 67 Peak 4 5721.95 70.36 115.24 -44.88 55.62 33.89 11.20 33.94 3.59 254 67 Peak	 Site : 03CH23-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C05A18EN_250702 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5745.00 108.55 ------ ------ 93.75 33.96 11.21 33.96 3.59 254 67 Peak
Avg	Blank	 Site : 03CH23-HY Condition: AVG_54 3m DRH18-E_LE2C05A18EN_250702 VERTICAL : RBW:1000.000kHz VBW:0.750kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5745.00 100.55 ------ ------ 85.74 33.98 11.21 33.97 3.59 254 67 Average	

Mode	46	
	Harmonic	
	U-NII-3_5.725-5.85_802.11a_CH149_5745MHz	
ANT	Second antenna	
Pol.	Horizontal	Vertical
Peak Avg	 Site : 03CH23-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 11490.00 52.40 74.00 -21.60 35.79 38.60 15.70 39.97 2.28 -- -- Peak 2 11490.00 42.18 54.00 -11.82 25.57 38.60 15.70 39.97 2.28 -- -- Average 3 17235.00 54.66 68.20 -13.54 38.74 40.10 19.25 46.48 3.05 -- -- Peak	 Site : 03CH23-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C05A18EN_250702 VERTICAL Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 11490.00 53.02 74.00 -20.98 36.41 38.60 15.70 39.97 2.28 -- -- Peak 2 11490.00 41.80 54.00 -12.20 25.19 38.60 15.70 39.97 2.28 -- -- Average 3 17235.00 55.04 68.20 -13.16 39.12 40.10 19.25 46.48 3.05 -- -- Peak

Mode	46	
	Harmonic	
	U-NII-3_5.725-5.85_802.11a_CH149_5745MHz	
ANT	Second antenna	
Pol.	Horizontal	Vertical
10.6G ~18G Avg	 Site : 03CH23-HY Condition: AVG_54 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL	 Site : 03CH23-HY Condition: AVG_54 3m DRH18-E_LE2C05A18EN_250702 VERTICAL

Mode	47	
	Band Edge - L	
	U-NII-3_5.725-5.85_802.11a_CH157_5785MHz	
ANT	Second antenna	
Pol.	Horizontal	Fundamental
Peak	 Site : 03CH23-HY Condition: PEAK_BE(B4)_16-24 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5616.84 52.28 68.20 -15.92 38.05 33.30 11.17 33.80 3.56 101 285 Peak 2 5650.32 50.99 68.44 -17.45 36.59 33.50 11.18 33.85 3.57 101 285 Peak 3 5708.97 62.14 107.71 -45.57 47.44 33.84 11.20 33.92 3.58 101 285 Peak 4 5720.44 61.51 111.79 -50.28 46.78 33.88 11.20 33.94 3.59 101 285 Peak	 Site : 03CH23-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5785.00 113.37 ------ ------ 98.47 34.08 11.23 34.02 3.61 101 285 Peak
Avg	Blank	 Site : 03CH23-HY Condition: AVG_54 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL : RBW:1000.000kHz VBW:0.750kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5785.00 103.88 ------ ------ 89.02 34.06 11.22 34.02 3.60 101 285 Average

Mode	47	
	Band Edge - R	
	U-NII-3_5.725-5.85_802.11a_CH157_5785MHz	
ANT	Second antenna	
Pol.	Horizontal	Fundamental
Peak	 Site : 03CH23-HY Condition: PEAK_BE(B4)_16-24 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Limit Read Ant Cable Preamp Aux APos TPos Freq Level Line Margin Level Factor Loss Factor Factor Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5854.30 60.15 112.40 -52.25 45.30 34.09 11.28 34.11 3.59 101 285 Peak 2 5861.07 62.47 109.10 -46.63 47.63 34.08 11.29 34.12 3.59 101 285 Peak 3 5924.59 51.75 68.50 -16.75 37.03 34.00 11.35 34.20 3.57 101 285 Peak 4 5938.78 52.16 68.20 -16.04 37.46 34.00 11.36 34.22 3.56 101 285 Peak	Blank

Mode	47	
	Band Edge - L	
	U-NII-3_5.725-5.85_802.11a_CH157_5785MHz	
ANT	Second antenna	
Pol.	Vertical	Fundamental
Peak	 Site : 03CH23-HY Condition: PEAK_BE(B4)_16-24 3m DRH18-E_LE2C05A18EN_250702 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5636.82 52.01 68.20 -16.19 37.69 33.42 11.17 33.83 3.56 265 70 Peak 2 5650.14 49.94 68.30 -18.36 35.54 33.50 11.18 33.85 3.57 265 70 Peak 3 5712.11 58.58 108.59 -50.01 43.88 33.85 11.20 33.93 3.58 265 70 Peak 4 5720.07 58.24 110.95 -52.71 43.51 33.88 11.20 33.94 3.59 265 70 Peak	 Site : 03CH23-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C05A18EN_250702 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5785.00 109.91 ------ ------ 95.05 34.06 11.22 34.02 3.60 265 70 Peak
Avg	Blank	 Site : 03CH23-HY Condition: AVG_54 3m DRH18-E_LE2C05A18EN_250702 VERTICAL : RBW:1000.000kHz VBW:0.750kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5785.00 100.78 ------ ------ 85.88 34.08 11.23 34.02 3.61 265 70 Average

Mode	47	
	Band Edge - R	
	U-NII-3_5.725-5.85_802.11a_CH157_5785MHz	
ANT	Second antenna	
Pol.	Vertical	Fundamental
Peak	 Site : 03CH23-HY Condition: PEAK_BE(B4)_16-24 3m DRH18-E_LE2C05A18EN_250702 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Limit Read Ant Cable Preamp Aux APos TPos Freq Level Line Margin Level Factor Loss Factor Factor Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5854.63 54.90 111.64 -56.74 40.05 34.09 11.28 34.11 3.59 265 70 Peak 2 5855.62 58.67 110.63 -51.96 43.82 34.09 11.28 34.11 3.59 265 70 Peak 3 5924.26 50.87 68.75 -17.88 36.15 34.00 11.35 34.20 3.57 265 70 Peak 4 5946.87 52.29 68.20 -15.91 37.59 34.00 11.37 34.23 3.56 265 70 Peak	Blank

Mode	47	
	Harmonic	
	U-NII-3_5.725-5.85_802.11a_CH157_5785MHz	
ANT	Second antenna	
Pol.	Horizontal	Vertical
Peak Avg	 Site : 03CH23-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 11570.00 53.05 74.00 -20.95 36.45 38.60 15.75 40.04 2.29 -- -- Peak 2 11570.00 42.83 54.00 -11.17 26.23 38.60 15.75 40.04 2.29 -- -- Average 3 17355.00 55.69 68.20 -12.51 39.63 40.20 19.34 46.59 3.11 -- -- Peak	 Site : 03CH23-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C05A18EN_250702 VERTICAL Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 11570.00 53.47 74.00 -20.53 36.87 38.60 15.75 40.04 2.29 -- -- Peak 2 11570.00 43.25 54.00 -10.75 26.65 38.60 15.75 40.04 2.29 -- -- Average 3 17355.00 54.51 68.20 -13.69 38.45 40.20 19.34 46.59 3.11 -- -- Peak

Mode	47	
	Harmonic	
	U-NII-3_5.725-5.85_802.11a_CH157_5785MHz	
ANT	Second antenna	
Pol.	Horizontal	Vertical
10.6G ~18G Avg	 Site : 03CH23-HY Condition: AVG_54 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL	 Site : 03CH23-HY Condition: AVG_54 3m DRH18-E_LE2C05A18EN_250702 VERTICAL

Mode	48	
	Band Edge	
	U-NII-3_5.725-5.85_802.11a_CH165_5825MHz	
ANT	Second antenna	
Pol.	Horizontal	Fundamental
Peak	 Site : 03CH23-HY Condition: PEAK_BE(B4)_16-24 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5854.88 52.32 111.08 -58.76 37.47 34.09 11.28 34.11 3.59 100 285 Peak 2 5874.63 51.09 105.30 -54.21 36.30 34.05 11.30 34.14 3.58 100 285 Peak 3 5924.88 50.21 68.29 -18.08 35.49 34.00 11.35 34.20 3.57 100 285 Peak 4 5933.38 52.71 68.20 -15.49 38.00 34.00 11.36 34.21 3.56 100 285 Peak	 Site : 03CH23-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5825.00 99.63 ------ ------ 84.74 34.10 11.25 34.06 3.60 100 285 Peak
Avg	Blank	 Site : 03CH23-HY Condition: AVG_54 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL : RBW:1000.000kHz VBW:0.750kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5825.00 89.84 ------ ------ 74.96 34.10 11.25 34.07 3.60 100 285 Average

Mode	48	
	Band Edge	
	U-NII-3_5.725-5.85_802.11a_CH165_5825MHz	
ANT	Second antenna	
Pol.	Vertical	Fundamental
Peak	 Site : 03CH23-HY Condition: PEAK_BE(B4)_16-24 3m DRH18-E_LE2C05A18EN_250702 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5855.00 51.86 110.80 -58.94 37.01 34.09 11.28 34.11 3.59 237 71 Peak 2 5874.50 51.50 105.34 -53.84 36.71 34.05 11.30 34.14 3.58 237 71 Peak 3 5924.63 51.95 68.48 -16.53 37.23 34.00 11.35 34.20 3.57 237 71 Peak 4 5931.63 51.87 68.20 -16.33 37.16 34.00 11.36 34.21 3.56 237 71 Peak	 Site : 03CH23-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C05A18EN_250702 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5825.00 94.34 ------ ------ 79.45 34.10 11.25 34.06 3.60 237 71 Peak
Avg	Blank	 Site : 03CH23-HY Condition: AVG_54 3m DRH18-E_LE2C05A18EN_250702 VERTICAL : RBW:1000.000kHz VBW:0.750kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5825.00 85.67 ------ ------ 70.78 34.10 11.25 34.06 3.60 237 71 Average

Mode	48	
	Harmonic	
	U-NII-3_5.725-5.85_802.11a_CH165_5825MHz	
ANT	Second antenna	
Pol.	Horizontal	Vertical
Peak Avg	 Site : 03CH23-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark 1 11650.00 51.95 74.00 -22.05 35.35 38.60 15.81 40.11 2.30 -- -- Peak 2 11650.00 41.73 54.00 -12.27 25.13 38.60 15.81 40.11 2.30 -- -- Average 3 17475.00 55.79 68.20 -12.41 39.66 40.25 19.42 46.70 3.16 -- -- Peak	 Site : 03CH23-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C05A18EN_250702 VERTICAL Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark 1 11650.00 53.19 74.00 -20.81 36.59 38.60 15.81 40.11 2.30 -- -- Peak 2 11650.00 42.97 54.00 -11.03 26.37 38.60 15.81 40.11 2.30 -- -- Average 3 17475.00 54.80 68.20 -13.40 38.67 40.25 19.42 46.70 3.16 -- -- Peak

Mode	48	
	Harmonic	
	U-NII-3_5.725-5.85_802.11a_CH165_5825MHz	
ANT	Second antenna	
Pol.	Horizontal	Vertical
10.6G ~18G Avg		

Mode	49	
	Band Edge	
	U-NII-3_5.725-5.85_802.11ax HE20_CH149_Full RU_5745MHz	
ANT	Second antenna	
Pol.	Horizontal	Fundamental
Peak	 Site : 03CH23-HY Condition: PEAK_BE(B4)_16-24 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5642.92 53.13 68.20 -15.07 38.77 33.46 11.18 33.84 3.56 100 284 Peak 2 5651.04 53.65 68.97 -15.32 39.24 33.51 11.18 33.85 3.57 100 284 Peak 3 5719.92 67.23 110.78 -43.55 52.50 33.88 11.20 33.94 3.59 100 284 Peak 4 5722.38 71.72 116.23 -44.51 56.98 33.89 11.20 33.94 3.59 100 284 Peak	 Site : 03CH23-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5745.00 111.60 ------ ------ 96.79 33.98 11.21 33.97 3.59 100 284 Peak
Avg	Blank	 Site : 03CH23-HY Condition: AVG_54 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL : RBW:1000.000kHz VBW:1.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5745.00 104.44 ------ ------ 89.63 33.98 11.21 33.97 3.59 100 284 Average	

Mode	49	
	Band Edge	
	U-NII-3_5.725-5.85_802.11ax HE20_CH149_Full RU_5745MHz	
ANT	Second antenna	
Pol.	Vertical	Fundamental
Peak	 Site : 03CH23-HY Condition: PEAK_BE(B4)_16-24 3m DRH18-E_LE2C05A18EN_250702 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5619.87 53.12 68.20 -15.08 38.88 33.32 11.17 33.81 3.56 258 67 Peak 2 5650.03 50.69 68.22 -17.53 36.29 33.50 11.18 33.85 3.57 258 67 Peak 3 5701.65 56.21 105.66 -49.45 41.53 33.81 11.20 33.91 3.58 258 67 Peak 4 5721.22 64.22 113.58 -49.36 49.49 33.88 11.20 33.94 3.59 258 67 Peak	 Site : 03CH23-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C05A18EN_250702 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5745.00 107.45 ------ ------ 92.64 33.98 11.21 33.97 3.59 258 67 Peak
Avg	Blank	 Site : 03CH23-HY Condition: AVG_54 3m DRH18-E_LE2C05A18EN_250702 VERTICAL : RBW:1000.000kHz VBW:1.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5745.00 100.50 ------ ------ 85.69 33.98 11.21 33.97 3.59 258 67 Average

Mode	49	
	Harmonic	
	U-NII-3_5.725-5.85_802.11ax HE20_CH149_Full RU_5745MHz	
ANT	Second antenna	
Pol.	Horizontal	Vertical
Peak Avg	 Site : 03CH23-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 11490.00 51.52 74.00 -22.48 34.91 38.60 15.70 39.97 2.28 -- -- Peak 2 11490.00 41.71 54.00 -12.29 25.10 38.60 15.70 39.97 2.28 -- -- Average 3 17235.00 55.30 68.20 -12.90 39.38 40.10 19.25 46.48 3.05 -- -- Peak	 Site : 03CH23-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C05A18EN_250702 VERTICAL Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 11490.00 51.66 74.00 -22.34 35.05 38.60 15.70 39.97 2.28 -- -- Peak 2 11490.00 41.65 54.00 -12.35 25.04 38.60 15.70 39.97 2.28 -- -- Average 3 17235.00 54.78 68.20 -13.42 38.86 40.10 19.25 46.48 3.05 -- -- Peak

Mode	49	
	Harmonic	
	U-NII-3_5.725-5.85_802.11ax HE20_CH149_Full RU_5745MHz	
ANT	Second antenna	
Pol.	Horizontal	Vertical
10.6G ~18G Avg	 Site : 03CH23-HY Condition: AVG_54 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL	 Site : 03CH23-HY Condition: AVG_54 3m DRH18-E_LE2C05A18EN_250702 VERTICAL

Mode	50	
	Band Edge	
	U-NII-3_5.725-5.85_802.11ax HE20_CH149_Partial RU 106/53_5745MHz	
ANT	Second antenna	
Pol.	Horizontal	Fundamental
Peak	 Site : 03CH23-HY Condition: PEAK_BE(B4)_16-24 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5647.71 53.35 68.20 -14.85 38.96 33.49 11.18 33.84 3.56 100 284 Peak 2 5652.64 53.24 70.16 -16.92 38.82 33.52 11.18 33.85 3.57 100 284 Peak 3 5717.45 63.09 110.09 -47.00 48.36 33.87 11.20 33.93 3.59 100 284 Peak 4 5720.50 65.44 111.93 -46.49 50.71 33.88 11.20 33.94 3.59 100 284 Peak	 Site : 03CH23-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5745.00 112.90 ------ ------ 98.10 33.96 11.21 33.96 3.59 100 284 Peak
Avg	Blank	 Site : 03CH23-HY Condition: AVG_54 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL : RBW:1000.000kHz VBW:2.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5745.00 105.95 ------ ------ 91.15 33.96 11.21 33.96 3.59 100 284 Average	

Mode	50	
	Band Edge	
	U-NII-3_5.725-5.85_802.11ax HE20_CH149_Partial RU 106/53_5745MHz	
ANT	Second antenna	
Pol.	Vertical	Fundamental
Peak	 Site : 03CH23-HY Condition: PEAK_BE(B4)_16-24 3m DRH18-E_LE2C05A18EN_250702 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5632.48 52.06 68.20 -16.14 37.76 33.39 11.17 33.82 3.56 249 71 Peak 2 5650.32 50.94 68.43 -17.49 36.54 33.50 11.18 33.85 3.57 249 71 Peak 3 5706.00 54.02 106.88 -52.86 39.34 33.82 11.20 33.92 3.58 249 71 Peak 4 5721.08 59.81 113.25 -53.44 45.08 33.88 11.20 33.94 3.59 249 71 Peak	 Site : 03CH23-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C05A18EN_250702 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5745.00 108.48 ------ ------ 93.68 33.96 11.21 33.96 3.59 249 71 Peak
Avg	Blank	 Site : 03CH23-HY Condition: AVG_54 3m DRH18-E_LE2C05A18EN_250702 VERTICAL : RBW:1000.000kHz VBW:2.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5745.00 101.79 ------ ------ 86.99 33.96 11.21 33.96 3.59 249 71 Average

Mode	51	
	Band Edge - L	
	U-NII-3_5.725-5.85_802.11ax HE20_CH157_Full RU_5785MHz	
ANT	Second antenna	
Pol.	Horizontal	Fundamental
Peak	 Site : 03CH23-HY Condition: PEAK_BE(B4)_16-24 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5647.92 53.30 68.20 -14.90 38.91 33.49 11.18 33.84 3.56 100 285 Peak 2 5652.17 52.30 69.81 -17.51 37.89 33.51 11.18 33.85 3.57 100 285 Peak 3 5701.38 53.43 105.59 -52.16 38.75 33.81 11.20 33.91 3.58 100 285 Peak 4 5720.07 55.14 110.95 -55.81 40.41 33.88 11.20 33.94 3.59 100 285 Peak	 Site : 03CH23-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5785.00 110.27 ------ ------ 95.41 34.06 11.22 34.02 3.60 100 285 Peak
Avg	Blank	 Site : 03CH23-HY Condition: AVG_54 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL : RBW:1000.000kHz VBW:1.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5785.00 104.05 ------ ------ 89.15 34.08 11.23 34.02 3.61 100 285 Average

Mode	51	
	Band Edge - R	
	U-NII-3_5.725-5.85_802.11ax HE20_CH157_Full RU_5785MHz	
ANT	Second antenna	
Pol.	Horizontal	Fundamental
Peak	 Site : 03CH23-HY Condition: PEAK_BE(B4)_16-24 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5854.80 54.18 111.27 -57.09 39.33 34.09 11.28 34.11 3.59 100 285 Peak 2 5872.12 54.44 106.01 -51.57 39.63 34.06 11.30 34.13 3.58 100 285 Peak 3 5924.43 51.46 68.62 -17.16 36.74 34.00 11.35 34.20 3.57 100 285 Peak 4 5942.74 52.77 68.20 -15.43 38.07 34.00 11.37 34.23 3.56 100 285 Peak	Blank

Mode	51	
	Band Edge - L	
	U-NII-3_5.725-5.85_802.11ax HE20_CH157_Full RU_5785MHz	
ANT	Second antenna	
Pol.	Vertical	Fundamental
Peak	 Site : 03CH23-HY Condition: PEAK_BE(B4)_16-24 3m DRH18-E_LE2C05A18EN_250702 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5642.55 52.81 68.20 -15.39 38.46 33.46 11.17 33.84 3.56 245 63 Peak 2 5651.80 51.02 69.54 -18.52 36.61 33.51 11.18 33.85 3.57 245 63 Peak 3 5703.60 51.60 106.21 -54.61 36.92 33.81 11.20 33.91 3.58 245 63 Peak 4 5720.07 51.94 110.95 -59.01 37.21 33.88 11.20 33.94 3.59 245 63 Peak	 Site : 03CH23-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C05A18EN_250702 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5785.00 107.26 ------ ------ 92.40 34.06 11.22 34.02 3.60 245 63 Peak
Avg	Blank	 Site : 03CH23-HY Condition: AVG_54 3m DRH18-E_LE2C05A18EN_250702 VERTICAL : RBW:1000.000kHz VBW:1.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5785.00 98.60 ------ ------ 83.70 34.08 11.23 34.02 3.61 245 63 Average

Mode	51	
	Band Edge - R	
	U-NII-3_5.725-5.85_802.11ax HE20_CH157_Full RU_5785MHz	
ANT	Second antenna	
Pol.	Vertical	Fundamental
Peak	 Site : 03CH23-HY Condition: PEAK_BE(B4)_16-24 3m DRH18-E_LE2C05A18EN_250702 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Limit Read Ant Cable Preamp Aux APos TPos Freq Level Line Margin Level Factor Loss Factor Factor Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5854.96 51.00 110.89 -59.89 36.15 34.09 11.28 34.11 3.59 245 63 Peak 2 5870.14 52.46 106.56 -54.10 37.64 34.06 11.30 34.13 3.59 245 63 Peak 3 5924.92 50.65 68.26 -17.61 35.93 34.00 11.35 34.20 3.57 245 63 Peak 4 5945.22 51.69 68.20 -16.51 36.99 34.00 11.37 34.23 3.56 245 63 Peak	Blank

Mode	51	
	Harmonic	
	U-NII-3_5.725-5.85_802.11ax HE20_CH157_Full RU_5785MHz	
ANT	Second antenna	
Pol.	Horizontal	Vertical
Peak Avg	 Site : 03CH23-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 11570.00 51.38 74.00 -22.62 34.78 38.60 15.75 40.04 2.29 -- -- Peak 2 11570.00 41.55 54.00 -12.45 24.95 38.60 15.75 40.04 2.29 -- -- Average 3 17355.00 54.12 68.20 -14.08 38.06 40.20 19.34 46.59 3.11 -- -- Peak	 Site : 03CH23-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C05A18EN_250702 VERTICAL Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 11570.00 52.13 74.00 -21.87 35.53 38.60 15.75 40.04 2.29 -- -- Peak 2 11570.00 41.84 54.00 -12.16 25.24 38.60 15.75 40.04 2.29 -- -- Average 3 17355.00 54.76 68.20 -13.44 38.70 40.20 19.34 46.59 3.11 -- -- Peak

Mode	51	
	Harmonic	
	U-NII-3_5.725-5.85_802.11ax HE20_CH157_Full RU_5785MHz	
ANT	Second antenna	
Pol.	Horizontal	Vertical
10.6G ~18G Avg	 Site : 03CH23-HY Condition: AVG_54 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL	 Site : 03CH23-HY Condition: AVG_54 3m DRH18-E_LE2C05A18EN_250702 VERTICAL

Mode	52	
	Band Edge	
	U-NII-3_5.725-5.85_802.11ax HE20_CH165_Full RU_5825MHz	
ANT	Second antenna	
Pol.	Horizontal	Fundamental
Peak	 Site : 03CH23-HY Condition: PEAK_BE(B4)_16-24 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5854.63 67.46 111.65 -44.19 52.61 34.09 11.28 34.11 3.59 102 288 Peak 2 5856.25 68.18 110.45 -42.27 53.33 34.09 11.28 34.11 3.59 102 288 Peak 3 5924.63 51.78 68.48 -16.70 37.06 34.00 11.35 34.20 3.57 102 288 Peak 4 5934.63 53.34 68.20 -14.86 38.64 34.00 11.36 34.22 3.56 102 288 Peak	 Site : 03CH23-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5825.00 110.73 ------ ------ 95.84 34.10 11.25 34.06 3.60 102 288 Peak
Avg	Blank	 Site : 03CH23-HY Condition: AVG_54 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL : RBW:1000.000kHz VBW:1.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5825.00 103.62 ------ ------ 88.74 34.10 11.25 34.07 3.60 102 288 Average

Mode	52	
	Band Edge	
	U-NII-3_5.725-5.85_802.11ax HE20_CH165_Full RU_5825MHz	
ANT	Second antenna	
Pol.	Vertical	Fundamental
Peak	 Site : 03CH23-HY Condition: PEAK_BE(B4)_16-24 3m DRH18-E_LE2C05A18EN_250702 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark 1 5855.00 59.35 110.80 -51.45 44.50 34.09 11.28 34.11 3.59 268 69 Peak 2 5855.75 63.02 110.59 -47.57 48.17 34.09 11.28 34.11 3.59 268 69 Peak 3 5924.13 51.07 68.84 -17.77 36.35 34.00 11.35 34.20 3.57 268 69 Peak 4 5926.00 51.65 68.20 -16.55 36.93 34.00 11.35 34.20 3.57 268 69 Peak	 Site : 03CH23-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C05A18EN_250702 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark 1 5825.00 104.62 ------ ------ 89.74 34.10 11.25 34.07 3.60 268 69 Peak
Avg	Blank	 Site : 03CH23-HY Condition: AVG_54 3m DRH18-E_LE2C05A18EN_250702 VERTICAL : RBW:1000.000kHz VBW:1.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark 1 5825.00 97.29 ------ ------ 82.41 34.10 11.25 34.07 3.60 268 69 Average

Mode	52	
	Harmonic	
	U-NII-3_5.725-5.85_802.11ax HE20_CH165_Full RU_5825MHz	
ANT	Second antenna	
Pol.	Horizontal	Vertical
Peak Avg	 Site : 03CH23-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 11650.00 51.16 74.00 -22.84 34.56 38.60 15.81 40.11 2.30 -- -- Peak 2 11650.00 41.71 54.00 -12.29 25.11 38.60 15.81 40.11 2.30 -- -- Average 3 17475.00 54.88 68.20 -13.32 38.75 40.25 19.42 46.70 3.16 -- -- Peak	 Site : 03CH23-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C05A18EN_250702 VERTICAL Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 11650.00 51.68 74.00 -22.32 35.08 38.60 15.81 40.11 2.30 -- -- Peak 2 11650.00 41.93 54.00 -12.07 25.33 38.60 15.81 40.11 2.30 -- -- Average 3 17475.00 54.99 68.20 -13.21 38.86 40.25 19.42 46.70 3.16 -- -- Peak

Mode	52	
	Harmonic	
	U-NII-3_5.725-5.85_802.11ax HE20_CH165_Full RU_5825MHz	
ANT	Second antenna	
Pol.	Horizontal	Vertical
10.6G ~18G Avg		

Mode	53	
	Band Edge	
	U-NII-3_5.725-5.85_802.11ax HE20_CH165_Partial RU 106/54_5825MHz	
ANT	Second antenna	
Pol.	Horizontal	Fundamental
Peak	 Site : 03CH23-HY Condition: PEAK_BE(B4)_16-24 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark 1 5853.63 71.38 113.93 -42.55 56.53 34.09 11.28 34.11 3.59 100 282 Peak 2 5857.50 70.45 110.10 -39.65 55.61 34.08 11.28 34.11 3.59 100 282 Peak 3 5924.75 56.60 68.38 -11.78 41.88 34.00 11.35 34.20 3.57 100 282 Peak 4 5936.88 53.91 68.20 -14.29 39.21 34.00 11.36 34.22 3.56 100 282 Peak	 Site : 03CH23-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark 1 5825.00 111.38 ------ ------ 96.51 34.10 11.26 34.09 3.60 100 282 Peak
Avg	Blank	 Site : 03CH23-HY Condition: AVG_54 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL : RBW:1000.000kHz VBW:2.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark 1 5825.00 105.82 ------ ------ 90.94 34.10 11.26 34.08 3.60 100 282 Average

Mode	53	
	Band Edge	
	U-NII-3_5.725-5.85_802.11ax HE20_CH165_Partial RU 106/54_5825MHz	
ANT	Second antenna	
Pol.	Vertical	Fundamental
Peak	 Site : 03CH23-HY Condition: PEAK_BE(B4)_16-24 3m DRH18-E_LE2C05A18EN_250702 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5854.50 61.70 111.94 -50.24 46.85 34.09 11.28 34.11 3.59 251 64 Peak 2 5862.50 58.61 108.70 -50.09 43.78 34.07 11.29 34.12 3.59 251 64 Peak 3 5924.88 49.85 68.29 -18.44 35.13 34.00 11.35 34.20 3.57 251 64 Peak 4 5927.63 52.01 68.20 -16.19 37.30 34.00 11.35 34.21 3.57 251 64 Peak	 Site : 03CH23-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C05A18EN_250702 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5825.00 106.25 ------ ------ 91.37 34.10 11.26 34.08 3.60 251 64 Peak
Avg	Blank	 Site : 03CH23-HY Condition: AVG_54 3m DRH18-E_LE2C05A18EN_250702 VERTICAL : RBW:1000.000kHz VBW:2.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5825.00 99.53 ------ ------ 84.65 34.10 11.26 34.08 3.60 251 64 Average

Mode	54	
	Band Edge - L	
	U-NII-3_5.725-5.85_802.11ax HE40_CH151_Full RU_5755MHz	
ANT	Second antenna	
Pol.	Horizontal	Fundamental
Peak	 Site : 03CH23-HY Condition: PEAK_BE(B4)_16-24 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5636.89 53.50 68.20 -14.70 39.18 33.42 11.17 33.83 3.56 100 285 Peak 2 5650.07 52.51 68.25 -15.74 38.11 33.50 11.18 33.85 3.57 100 285 Peak 3 5719.66 70.64 110.70 -40.06 55.91 33.88 11.20 33.94 3.59 100 285 Peak 4 5720.75 69.50 112.50 -43.00 54.77 33.88 11.20 33.94 3.59 100 285 Peak	 Site : 03CH23-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5755.00 109.75 ------ ------ 94.92 34.00 11.21 33.98 3.60 100 285 Peak
Avg	Blank	 Site : 03CH23-HY Condition: AVG_54 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL : RBW:1000.000kHz VBW:2.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5755.00 102.68 ------ ------ 87.83 34.02 11.22 33.99 3.60 100 285 Average

Mode	54	
	Band Edge - R	
	U-NII-3_5.725-5.85_802.11ax HE40_CH151_Full RU_5755MHz	
ANT	Second antenna	
Pol.	Horizontal	Fundamental
Peak	 Site : 03CH23-HY Condition: PEAK_BE(B4)_16-24 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Limit Read Ant Cable Preamp Aux APos TPos Freq Level Line Margin Level Factor Loss Factor Factor Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5854.84 52.58 111.16 -58.58 37.73 34.09 11.28 34.11 3.59 100 285 Peak 2 5872.39 54.43 105.93 -51.50 39.62 34.06 11.30 34.13 3.58 100 285 Peak 3 5924.65 50.97 68.46 -17.49 36.25 34.00 11.35 34.20 3.57 100 285 Peak 4 5925.43 51.92 68.20 -16.28 37.20 34.00 11.35 34.20 3.57 100 285 Peak	Blank

Mode	54	
	Band Edge - L	
	U-NII-3_5.725-5.85_802.11ax HE40_CH151_Full RU_5755MHz	
ANT	Second antenna	
Pol.	Vertical	Fundamental
Peak	 Site : 03CH23-HY Condition: PEAK_BE(B4)_16-24 3m DRH18-E_LE2C05A18EN_250702 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5618.29 52.65 68.20 -15.55 38.41 33.31 11.17 33.80 3.56 237 68 Peak 2 5650.07 52.79 68.25 -15.46 38.39 33.50 11.18 33.85 3.57 237 68 Peak 3 5712.53 64.78 108.71 -43.93 50.08 33.85 11.20 33.93 3.58 237 68 Peak 4 5720.13 65.65 111.09 -45.44 50.92 33.88 11.20 33.94 3.59 237 68 Peak	 Site : 03CH23-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C05A18EN_250702 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5755.00 107.08 ------ ------ 92.23 34.02 11.22 33.99 3.60 237 68 Peak
Avg	Blank	 Site : 03CH23-HY Condition: AVG_54 3m DRH18-E_LE2C05A18EN_250702 VERTICAL : RBW:1000.000kHz VBW:2.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5755.00 98.49 ------ ------ 83.64 34.02 11.22 33.99 3.60 237 68 Average

Mode	54	
	Band Edge - R	
	U-NII-3_5.725-5.85_802.11ax HE40_CH151_Full RU_5755MHz	
ANT	Second antenna	
Pol.	Vertical	Fundamental
Peak	 Site : 03CH23-HY Condition: PEAK_BE(B4)_16-24 3m DRH18-E_LE2C05A18EN_250702 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Limit Read Ant Cable Preamp Aux APos TPos Freq Level Line Margin Level Factor Loss Factor Factor Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5854.84 51.12 111.16 -60.04 36.27 34.09 11.28 34.11 3.59 237 68 Peak 2 5874.34 52.07 105.38 -53.31 37.28 34.05 11.30 34.14 3.58 237 68 Peak 3 5924.07 51.26 68.89 -17.63 36.54 34.00 11.35 34.20 3.57 237 68 Peak 4 5927.58 51.66 68.20 -16.54 36.95 34.00 11.35 34.21 3.57 237 68 Peak	Blank

Mode	54	
	Harmonic	
	U-NII-3_5.725-5.85_802.11ax HE40_CH151_Full RU_5755MHz	
ANT	Second antenna	
Pol.	Horizontal	Vertical
Peak Avg	 Site : 03CH23-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 11510.00 51.27 74.00 -22.73 34.67 38.60 15.71 39.99 2.28 -- -- Peak 2 11510.00 41.92 54.00 -12.08 25.32 38.60 15.71 39.99 2.28 -- -- Average 3 17265.00 54.81 68.20 -13.39 38.85 40.13 19.27 46.51 3.07 -- -- Peak	 Site : 03CH23-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C05A18EN_250702 VERTICAL Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 11510.00 51.56 74.00 -22.44 34.96 38.60 15.71 39.99 2.28 -- -- Peak 2 11510.00 42.13 54.00 -11.87 25.53 38.60 15.71 39.99 2.28 -- -- Average 3 17265.00 54.29 68.20 -13.91 38.33 40.13 19.27 46.51 3.07 -- -- Peak

Mode	54	
	Harmonic	
	U-NII-3_5.725-5.85_802.11ax HE40_CH151_Full RU_5755MHz	
ANT	Second antenna	
Pol.	Horizontal	Vertical
10.6G ~18G Avg	 Site : 03CH23-HY Condition: AVG_54 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL	 Site : 03CH23-HY Condition: AVG_54 3m DRH18-E_LE2C05A18EN_250702 VERTICAL

Mode	55	
	Band Edge - L	
	U-NII-3_5.725-5.85_802.11ax HE40_CH151_Partial RU 242/61_5755MHz	
ANT	Second antenna	
Pol.	Horizontal	Fundamental
Peak	 Site : 03CH23-HY Condition: PEAK_BE(B4)_16-24 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5640.30 52.89 68.20 -15.31 38.55 33.44 11.17 33.83 3.56 100 286 Peak 2 5650.38 50.19 68.48 -18.29 35.79 33.50 11.18 33.85 3.57 100 286 Peak 3 5719.04 66.28 110.53 -44.25 51.54 33.88 11.20 33.93 3.59 100 286 Peak 4 5720.28 66.49 111.44 -44.95 51.76 33.88 11.20 33.94 3.59 100 286 Peak	 Site : 03CH23-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5755.00 110.50 ------ ------ 95.67 34.00 11.21 33.98 3.60 100 286 Peak
Avg	Blank	 Site : 03CH23-HY Condition: AVG_54 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL : RBW:1000.000kHz VBW:4.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5755.00 103.45 ------ ------ 88.62 34.00 11.21 33.98 3.60 100 286 Average	

Mode	55	
	Band Edge - R	
	U-NII-3_5.725-5.85_802.11ax HE40_CH151_Partial RU 242/61_5755MHz	
ANT	Second antenna	
Pol.	Horizontal	Fundamental
Peak	 Site : 03CH23-HY Condition: PEAK_BE(B4)_16-24 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Limit Read Ant Cable Preamp Aux APos TPos Freq Level Line Margin Level Factor Loss Factor Factor Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5854.84 50.15 111.16 -61.01 35.30 34.09 11.28 34.11 3.59 100 286 Peak 2 5867.91 52.00 107.18 -55.18 37.19 34.06 11.29 34.13 3.59 100 286 Peak 3 5924.85 50.84 68.31 -17.47 36.12 34.00 11.35 34.20 3.57 100 286 Peak 4 5938.11 52.16 68.20 -16.04 37.46 34.00 11.36 34.22 3.56 100 286 Peak	Blank

Mode	55	
	Band Edge - L	
	U-NII-3_5.725-5.85_802.11ax HE40_CH151_Partial RU 242/61_5755MHz	
ANT	Second antenna	
Pol.	Vertical	Fundamental
Peak	 Site : 03CH23-HY Condition: PEAK_BE(B4)_16-24 3m DRH18-E_LE2C05A18EN_250702 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5634.57 53.18 68.20 -15.02 38.86 33.41 11.17 33.82 3.56 256 67 Peak 2 5651.46 52.08 69.29 -17.21 37.67 33.51 11.18 33.85 3.57 256 67 Peak 3 5718.42 61.58 110.36 -48.78 46.85 33.87 11.20 33.93 3.59 256 67 Peak 4 5722.30 68.28 116.03 -47.75 53.54 33.89 11.20 33.94 3.59 256 67 Peak	 Site : 03CH23-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C05A18EN_250702 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5755.00 105.33 ------ ------ 90.52 33.98 11.21 33.97 3.59 256 67 Peak
Avg	Blank	 Site : 03CH23-HY Condition: AVG_54 3m DRH18-E_LE2C05A18EN_250702 VERTICAL : RBW:1000.000kHz VBW:4.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5755.00 99.33 ------ ------ 84.50 34.00 11.21 33.98 3.60 256 67 Average

Mode	55	
	Band Edge - R	
	U-NII-3_5.725-5.85_802.11ax HE40_CH151_Partial RU 242/61_5755MHz	
ANT	Second antenna	
Pol.	Vertical	Fundamental
Peak	 Site : 03CH23-HY Condition: PEAK_BE(B4)_16-24 3m DRH18-E_LE2C05A18EN_250702 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Limit Read Ant Cable Preamp Aux APos TPos Freq Level Line Margin Level Factor Loss Factor Factor Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5854.65 50.17 111.61 -61.44 35.32 34.09 11.28 34.11 3.59 256 67 Peak 2 5872.59 51.35 105.88 -54.53 36.55 34.05 11.30 34.13 3.58 256 67 Peak 3 5923.48 51.08 69.32 -18.24 36.36 34.00 11.35 34.20 3.57 256 67 Peak 4 5926.60 52.07 68.20 -16.13 37.35 34.00 11.35 34.20 3.57 256 67 Peak	Blank

Mode	56	
	Band Edge - L	
	U-NII-3_5.725-5.85_802.11ax HE40_CH159_Full RU_5795MHz	
ANT	Second antenna	
Pol.	Horizontal	Fundamental
Peak	 Site : 03CH23-HY Condition: PEAK_BE(B4)_16-24 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5649.92 52.81 68.20 -15.39 38.41 33.50 11.18 33.84 3.56 100 284 Peak 2 5650.12 52.50 68.29 -15.79 38.10 33.50 11.18 33.85 3.57 100 284 Peak 3 5716.81 60.90 109.91 -49.01 46.17 33.87 11.20 33.93 3.59 100 284 Peak 4 5720.90 60.87 112.85 -51.98 46.14 33.88 11.20 33.94 3.59 100 284 Peak	 Site : 03CH23-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5795.00 108.94 ------ ------ 94.04 34.09 11.23 34.03 3.61 100 284 Peak
Avg	Blank	 Site : 03CH23-HY Condition: AVG_54 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL : RBW:1000.000kHz VBW:2.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5795.00 101.80 ------ ------ 86.90 34.09 11.23 34.03 3.61 100 284 Average	

Mode	56	
	Band Edge - R	
	U-NII-3_5.725-5.85_802.11ax HE40_CH159_Full RU_5795MHz	
ANT	Second antenna	
Pol.	Horizontal	Fundamental
Peak	 Site : 03CH23-HY Condition: PEAK_BE(B4)_16-24 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Limit Read Ant Cable Preamp Aux APos TPos Freq Level Line Margin Level Factor Loss Factor Factor Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5854.52 65.01 111.89 -46.88 50.16 34.09 11.28 34.11 3.59 100 284 Peak 2 5863.05 65.64 108.55 -42.91 50.81 34.07 11.29 34.12 3.59 100 284 Peak 3 5924.58 52.12 68.51 -16.39 37.40 34.00 11.35 34.20 3.57 100 284 Peak 4 5927.99 52.76 68.20 -15.44 38.05 34.00 11.35 34.21 3.57 100 284 Peak	Blank

Mode	56	
	Band Edge - L	
	U-NII-3_5.725-5.85_802.11ax HE40_CH159_Full RU_5795MHz	
ANT	Second antenna	
Pol.	Vertical	Fundamental
Peak	 Site : 03CH23-HY Condition: PEAK_BE(B4)_16-24 3m DRH18-E_LE2C05A18EN_250702 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5638.61 52.33 68.20 -15.87 38.00 33.43 11.17 33.83 3.56 302 72 Peak 2 5650.12 50.43 68.29 -17.86 36.03 33.50 11.18 33.85 3.57 302 72 Peak 3 5701.01 52.53 105.48 -52.95 37.86 33.80 11.20 33.91 3.58 302 72 Peak 4 5720.12 54.71 111.07 -56.36 39.98 33.88 11.20 33.94 3.59 302 72 Peak	 Site : 03CH23-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C05A18EN_250702 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5795.00 103.21 ------ ------ 88.31 34.09 11.23 34.03 3.61 302 72 Peak
Avg	Blank	 Site : 03CH23-HY Condition: AVG_54 3m DRH18-E_LE2C05A18EN_250702 VERTICAL : RBW:1000.000kHz VBW:2.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5795.00 96.49 ------ ------ 81.59 34.09 11.23 34.03 3.61 302 72 Average

Mode	56	
	Band Edge - R	
	U-NII-3_5.725-5.85_802.11ax HE40_CH159_Full RU_5795MHz	
ANT	Second antenna	
Pol.	Vertical	Fundamental
Peak	 Site : 03CH23-HY Condition: PEAK_BE(B4)_16-24 3m DRH18-E_LE2C05A18EN_250702 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Limit Read Ant Cable Preamp Aux APos TPos Freq Level Line Margin Level Factor Loss Factor Factor Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5854.21 57.23 112.60 -55.37 42.38 34.09 11.28 34.11 3.59 302 72 Peak 2 5864.44 56.09 108.15 -52.06 41.26 34.07 11.29 34.12 3.59 302 72 Peak 3 5923.65 52.24 69.19 -16.95 37.52 34.00 11.35 34.20 3.57 302 72 Peak 4 5948.30 51.92 68.20 -16.28 37.22 34.00 11.37 34.23 3.56 302 72 Peak	Blank

Mode	56	
	Harmonic	
	U-NII-3_5.725-5.85_802.11ax HE40_CH159_Full RU_5795MHz	
ANT	Second antenna	
Pol.	Horizontal	Vertical
Peak Avg	 Site : 03CH23-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 11590.00 51.55 74.00 -22.45 34.95 38.60 15.77 40.06 2.29 -- -- Peak 2 11590.00 41.76 54.00 -12.24 25.16 38.60 15.77 40.06 2.29 -- -- Average 3 17385.00 55.93 68.20 -12.27 39.87 40.20 19.36 46.62 3.12 -- -- Peak	 Site : 03CH23-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C05A18EN_250702 VERTICAL Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 11590.00 52.24 74.00 -21.76 35.64 38.60 15.77 40.06 2.29 -- -- Peak 2 11590.00 41.98 54.00 -12.02 25.38 38.60 15.77 40.06 2.29 -- -- Average 3 17385.00 55.52 68.20 -12.68 39.46 40.20 19.36 46.62 3.12 -- -- Peak

Mode	56	
	Harmonic	
	U-NII-3_5.725-5.85_802.11ax HE40_CH159_Full RU_5795MHz	
ANT	Second antenna	
Pol.	Horizontal	Vertical
10.6G ~18G Avg	 Site : 03CH23-HY Condition: AVG_54 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL	 Site : 03CH23-HY Condition: AVG_54 3m DRH18-E_LE2C05A18EN_250702 VERTICAL

Mode	57	
	Band Edge - L	
	U-NII-3_5.725-5.85_802.11ax HE40_CH159_Partial RU 242/62_5795MHz	
ANT	Second antenna	
Pol.	Horizontal	Fundamental
Peak	 Site : 03CH23-HY Condition: PEAK_BE(B4)_16-24 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5648.95 52.51 68.20 -15.69 38.12 33.49 11.18 33.84 3.56 100 286 Peak 2 5650.12 49.94 68.29 -18.35 35.54 33.50 11.18 33.85 3.57 100 286 Peak 3 5701.79 50.99 105.70 -54.71 36.31 33.81 11.20 33.91 3.58 100 286 Peak 4 5720.71 52.23 112.41 -60.18 37.50 33.88 11.20 33.94 3.59 100 286 Peak	 Site : 03CH23-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5795.00 108.92 ------ ------ 94.02 34.10 11.24 34.05 3.61 100 286 Peak
Avg	Blank	 Site : 03CH23-HY Condition: AVG_54 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL : RBW:1000.000kHz VBW:4.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5795.00 103.16 ------ ------ 88.26 34.10 11.23 34.04 3.61 100 286 Average	

Mode	57	
	Band Edge - R	
	U-NII-3_5.725-5.85_802.11ax HE40_CH159_Partial RU 242/62_5795MHz	
ANT	Second antenna	
Pol.	Horizontal	Fundamental
Peak	 Site : 03CH23-HY Condition: PEAK_BE(B4)_16-24 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Limit Read Ant Cable Preamp Aux APos TPos Freq Level Line Margin Level Factor Loss Factor Factor Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5854.68 65.83 111.54 -45.71 50.98 34.09 11.28 34.11 3.59 100 286 Peak 2 5859.17 62.99 109.63 -46.64 48.15 34.08 11.29 34.12 3.59 100 286 Peak 3 5924.12 51.37 68.85 -17.48 36.65 34.00 11.35 34.20 3.57 100 286 Peak 4 5947.83 53.02 68.20 -15.18 38.32 34.00 11.37 34.23 3.56 100 286 Peak	Blank

Mode	57	
	Band Edge - L	
	U-NII-3_5.725-5.85_802.11ax HE40_CH159_Partial RU 242/62_5795MHz	
ANT	Second antenna	
Pol.	Vertical	Fundamental
Peak	 Site : 03CH23-HY Condition: PEAK_BE(B4)_16-24 3m DRH18-E_LE2C05A18EN_250702 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5647.39 51.83 68.20 -16.37 37.45 33.48 11.18 33.84 3.56 302 72 Peak 2 5650.51 51.07 68.58 -17.51 36.67 33.50 11.18 33.85 3.57 302 72 Peak 3 5701.79 51.36 105.70 -54.34 36.68 33.81 11.20 33.91 3.58 302 72 Peak 4 5720.90 52.01 112.85 -60.84 37.28 33.88 11.20 33.94 3.59 302 72 Peak	 Site : 03CH23-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C05A18EN_250702 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5795.00 105.43 ------ ------ 90.53 34.10 11.23 34.04 3.61 302 72 Peak
Avg	Blank	 Site : 03CH23-HY Condition: AVG_54 3m DRH18-E_LE2C05A18EN_250702 VERTICAL : RBW:1000.000kHz VBW:4.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5795.00 97.71 ------ ------ 82.81 34.10 11.23 34.04 3.61 302 72 Average

Mode	57	
	Band Edge - R	
	U-NII-3_5.725-5.85_802.11ax HE40_CH159_Partial RU 242/62_5795MHz	
ANT	Second antenna	
Pol.	Vertical	Fundamental
Peak	 Site : 03CH23-HY Condition: PEAK_BE(B4)_16-24 3m DRH18-E_LE2C05A18EN_250702 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Limit Read Ant Cable Preamp Aux APos TPos Freq Level Line Margin Level Factor Loss Factor Factor Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5854.68 53.90 111.54 -57.64 39.05 34.09 11.28 34.11 3.59 302 72 Peak 2 5872.66 51.89 105.86 -53.97 37.09 34.05 11.30 34.13 3.58 302 72 Peak 3 5923.34 52.94 69.42 -16.48 38.22 34.00 11.35 34.20 3.57 302 72 Peak 4 5929.54 52.65 68.20 -15.55 37.95 34.00 11.35 34.21 3.56 302 72 Peak	Blank

Mode	58	
	Band Edge - L	
	U-NII-3_5.725-5.85_802.11ax HE80_CH155_Full RU_5775MHz	
ANT	Second antenna	
Pol.	Horizontal	Fundamental
Peak	 Site : 03CH23-HY Condition: PEAK_BE(B4)_16-24 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5642.18 61.24 68.20 -6.96 46.89 33.45 11.17 33.83 3.56 100 285 Peak 2 5650.05 59.80 68.24 -8.44 45.40 33.50 11.18 33.85 3.57 100 285 Peak 3 5701.33 65.99 105.57 -39.58 51.31 33.81 11.20 33.91 3.58 100 285 Peak 4 5720.58 67.72 112.11 -44.39 52.99 33.88 11.20 33.94 3.59 100 285 Peak	 Site : 03CH23-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5775.00 107.08 ------ ------ 92.22 34.06 11.22 34.02 3.60 100 285 Peak
Avg	Blank	 Site : 03CH23-HY Condition: AVG_54 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL : RBW:1000.000kHz VBW:3.600kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5775.00 99.73 ------ ------ 84.87 34.05 11.22 34.01 3.60 100 285 Average

Mode	58	
	Band Edge - R	
	U-NII-3_5.725-5.85_802.11ax HE80_CH155_Full RU_5775MHz	
ANT	Second antenna	
Pol.	Horizontal	Fundamental
Peak	 Site : 03CH23-HY Condition: PEAK_BE(B4)_16-24 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Limit Read Ant Cable Preamp Aux APos TPos Freq Level Line Margin Level Factor Loss Factor Factor Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5854.98 64.90 110.86 -45.96 50.05 34.09 11.28 34.11 3.59 100 285 Peak 2 5872.65 66.98 105.86 -38.88 52.18 34.05 11.30 34.13 3.58 100 285 Peak 3 5924.98 56.42 68.22 -11.80 41.70 34.00 11.35 34.20 3.57 100 285 Peak 4 5932.50 60.15 68.20 -8.05 45.44 34.00 11.36 34.21 3.56 100 285 Peak	Blank

Mode	58
	Band Edge - L
	U-NII-3_5.725-5.85_802.11ax HE80_CH155_Full RU_5775MHz
ANT	Second antenna

Pol.	Vertical	Fundamental
Peak	 Site : 03CH23-HY Condition: PEAK_BE(B4)_16-24 3m DRH18-E_LE2C05A18EN_250702 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5648.30 58.30 68.20 -9.90 43.91 33.49 11.18 33.84 3.56 288 71 Peak 2 5650.05 55.78 68.24 -12.46 41.38 33.50 11.18 33.85 3.57 288 71 Peak 3 5705.00 62.98 106.60 -43.62 48.30 33.82 11.20 33.92 3.58 288 71 Peak 4 5720.23 61.83 111.31 -49.48 47.10 33.88 11.20 33.94 3.59 288 71 Peak	 Site : 03CH23-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C05A18EN_250702 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5775.00 100.53 ------ ------ 85.73 33.96 11.21 33.96 3.59 288 71 Peak
Avg	Blank	 Site : 03CH23-HY Condition: AVG_54 3m DRH18-E_LE2C05A18EN_250702 VERTICAL : RBW:1000.000kHz VBW:3.600kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5775.00 94.29 ------ ------ 79.43 34.05 11.22 34.01 3.60 288 71 Average

Mode	58	
	Band Edge - R	
	U-NII-3_5.725-5.85_802.11ax HE80_CH155_Full RU_5775MHz	
ANT	Second antenna	
Pol.	Vertical	Fundamental
Peak	 Site : 03CH23-HY Condition: PEAK_BE(B4)_16-24 3m DRH18-E_LE2C05A18EN_250702 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Limit Read Ant Cable Preamp Aux APos TPos Freq Level Line Margin Level Factor Loss Factor Factor Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5854.98 56.94 110.86 -53.92 42.09 34.09 11.28 34.11 3.59 288 71 Peak 2 5870.03 59.43 106.59 -47.16 44.61 34.06 11.30 34.13 3.59 288 71 Peak 3 5923.23 53.02 69.51 -16.49 38.30 34.00 11.35 34.20 3.57 288 71 Peak 4 5931.45 53.40 68.20 -14.80 38.70 34.00 11.35 34.21 3.56 288 71 Peak	Blank

Mode	58	
	Harmonic	
	U-NII-3_5.725-5.85_802.11ax HE80_CH155_Full RU_5775MHz	
ANT	Second antenna	
Pol.	Horizontal	Vertical
Peak Avg	 Site : 03CH23-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 11550.00 51.95 74.00 -22.05 35.35 38.60 15.74 40.02 2.28 -- -- Peak 2 11550.00 42.15 54.00 -11.85 25.55 38.60 15.74 40.02 2.28 -- -- Average 3 17325.00 55.24 68.20 -12.96 39.20 40.20 19.31 46.56 3.09 -- -- Peak	 Site : 03CH23-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C05A18EN_250702 VERTICAL Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 11550.00 51.89 74.00 -22.11 35.29 38.60 15.74 40.02 2.28 -- -- Peak 2 11550.00 42.01 54.00 -11.99 25.41 38.60 15.74 40.02 2.28 -- -- Average 3 17325.00 54.74 68.20 -13.46 38.70 40.20 19.31 46.56 3.09 -- -- Peak

Mode	58	
	Harmonic	
	U-NII-3_5.725-5.85_802.11ax HE80_CH155_Full RU_5775MHz	
ANT	Second antenna	
Pol.	Horizontal	Vertical
10.6G ~18G Avg		

Mode	59	
	Band Edge - L	
	U-NII-3_5.725-5.85_802.11ax HE80_CH155_Partial RU 484/65_5775MHz	
ANT	Second antenna	
Pol.	Horizontal	Fundamental
Peak	 Site : 03CH23-HY Condition: PEAK_BE(B4)_16-24 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5616.80 52.02 68.20 -16.18 37.79 33.30 11.17 33.80 3.56 100 287 Peak 2 5650.05 50.86 68.24 -17.38 36.46 33.50 11.18 33.85 3.57 100 287 Peak 3 5709.38 57.88 107.83 -49.95 43.18 33.84 11.20 33.92 3.58 100 287 Peak 4 5720.23 55.53 111.31 -55.78 40.80 33.88 11.20 33.94 3.59 100 287 Peak	 Site : 03CH23-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5775.00 103.45 ------ ------ 88.59 34.03 11.22 33.99 3.60 100 287 Peak
Avg	Blank	 Site : 03CH23-HY Condition: AVG_54 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL : RBW:1000.000kHz VBW:6.200kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5775.00 97.19 ------ ------ 82.33 34.04 11.22 34.00 3.60 100 287 Average	

Mode	59	
	Band Edge - R	
	U-NII-3_5.725-5.85_802.11ax HE80_CH155_Partial RU 484/65_5775MHz	
ANT	Second antenna	
Pol.	Horizontal	Fundamental
Peak	 Site : 03CH23-HY Condition: PEAK_BE(B4)_16-24 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Limit Read Ant Cable Preamp Aux APos TPos Freq Level Line Margin Level Factor Loss Factor Factor Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5854.63 52.27 111.65 -59.38 37.42 34.09 11.28 34.11 3.59 100 287 Peak 2 5872.48 52.82 105.91 -53.09 38.01 34.06 11.30 34.13 3.58 100 287 Peak 3 5924.63 50.88 68.48 -17.60 36.16 34.00 11.35 34.20 3.57 100 287 Peak 4 5927.08 52.57 68.20 -15.63 37.86 34.00 11.35 34.21 3.57 100 287 Peak	Blank

Mode	59	
	Band Edge - L	
	U-NII-3_5.725-5.85_802.11ax HE80_CH155_Partial RU 484/65_5775MHz	
ANT	Second antenna	
Pol.	Vertical	Fundamental
Peak	 Site : 03CH23-HY Condition: PEAK_BE(B4)_16-24 3m DRH18-E_LE2C05A18EN_250702 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5619.08 52.34 68.20 -15.86 38.10 33.31 11.17 33.80 3.56 245 64 Peak 2 5650.05 50.23 68.24 -18.01 35.83 33.50 11.18 33.85 3.57 245 64 Peak 3 5701.15 53.98 105.52 -51.54 39.31 33.80 11.20 33.91 3.58 245 64 Peak 4 5720.58 54.13 112.11 -57.98 39.40 33.88 11.20 33.94 3.59 245 64 Peak	 Site : 03CH23-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C05A18EN_250702 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5775.00 99.00 ------ ------ 84.14 34.04 11.22 34.00 3.60 245 64 Peak
Avg	Blank	 Site : 03CH23-HY Condition: AVG_54 3m DRH18-E_LE2C05A18EN_250702 VERTICAL : RBW:1000.000kHz VBW:6.200kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5775.00 93.18 ------ ------ 78.32 34.03 11.22 33.99 3.60 245 64 Average

Mode	59	
	Band Edge - R	
	U-NII-3_5.725-5.85_802.11ax HE80_CH155_Partial RU 484/65_5775MHz	
ANT	Second antenna	
Pol.	Vertical	Fundamental
Peak	 Site : 03CH23-HY Condition: PEAK_BE(B4)_16-24 3m DRH18-E_LE2C05A18EN_250702 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Limit Read Ant Cable Preamp Aux APos TPos Freq Level Line Margin Level Factor Loss Factor Factor Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5854.98 49.99 110.86 -60.87 35.14 34.09 11.28 34.11 3.59 245 64 Peak 2 5871.43 52.19 106.20 -54.01 37.37 34.06 11.30 34.13 3.59 245 64 Peak 3 5924.98 50.47 68.22 -17.75 35.75 34.00 11.35 34.20 3.57 245 64 Peak 4 5935.48 51.50 68.20 -16.70 36.80 34.00 11.36 34.22 3.56 245 64 Peak	Blank

Mode	60	
	Band Edge - L	
	U-NII-3_5.725-5.85_802.11ax HE80_CH155_Partial RU 484/66_5775MHz	
ANT	Second antenna	
Pol.	Horizontal	Fundamental
Peak	 Site : 03CH23-HY Condition: PEAK_BE(B4)_16-24 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5606.83 52.29 68.20 -15.91 38.13 33.24 11.16 33.79 3.55 101 289 Peak 2 5650.40 51.21 68.50 -17.29 36.81 33.50 11.18 33.85 3.57 101 289 Peak 3 5701.33 52.86 105.57 -52.71 38.18 33.81 11.20 33.91 3.58 101 289 Peak 4 5721.45 54.60 114.11 -59.51 39.86 33.89 11.20 33.94 3.59 101 289 Peak	 Site : 03CH23-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5775.00 104.46 ------ ------ 89.57 34.10 11.24 34.06 3.61 101 289 Peak
Avg	Blank	 Site : 03CH23-HY Condition: AVG_54 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL : RBW:1000.000kHz VBW:6.200kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5775.00 98.13 ------ ------ 83.23 34.08 11.23 34.02 3.61 101 289 Average

Mode	60	
	Band Edge - R	
	U-NII-3_5.725-5.85_802.11ax HE80_CH155_Partial RU 484/66_5775MHz	
ANT	Second antenna	
Pol.	Horizontal	Fundamental
Peak	 Site : 03CH23-HY Condition: PEAK_BE(B4)_16-24 3m DRH18-E_LE2C05A18EN_250702 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Limit Read Ant Cable Preamp Aux APos TPos Freq Level Line Margin Level Factor Loss Factor Factor Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5854.63 54.29 111.65 -57.36 39.44 34.09 11.28 34.11 3.59 101 289 Peak 2 5873.53 52.59 105.61 -53.02 37.80 34.05 11.30 34.14 3.58 101 289 Peak 3 5923.75 50.98 69.12 -18.14 36.26 34.00 11.35 34.20 3.57 101 289 Peak 4 5925.15 52.57 68.20 -15.63 37.85 34.00 11.35 34.20 3.57 101 289 Peak	Blank