



FCC RADIO TEST REPORT

FCC ID : COF-WMCW51MS
Equipment : 802.11a/b/g/n/ac/ax 1x1 + BT 5.3 Combo Module
Brand Name : USI
Model Name : WM-CW-51MS
Marketing Name : WM-CW-51MS
Applicant : Universal Global Scientific Industrial Co., Ltd.
No. 141, Lane 351, Sec. 1, Taiping Road, Tsao-tuen,
Nantou County 542007, Taiwan
Manufacturer : Universal Global Scientific Industrial Co., Ltd.
No. 141, Lane 351, Sec. 1, Taiping Road, Tsao-tuen,
Nantou County 542007, Taiwan
Standard : FCC Part 15 Subpart C §15.247

The product was received on Sep. 16, 2025 and testing was performed from Sep. 24, 2025 to Nov. 25, 2025. We, Sporton International Inc. EMC & Wireless Communications Laboratory, would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval from Sporton International Inc. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.

Louis Wu

Approved by: Louis Wu

Sporton International Inc. EMC & Wireless Communications Laboratory

No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333, Taiwan (R.O.C.)



Table of Contents

History of this test report.....	3
Summary of Test Result.....	4
1 General Description	5
1.1 Product Feature of Equipment Under Test.....	5
1.2 Modification of EUT	5
1.3 Testing Location	5
1.4 Applicable Standards.....	6
2 Test Configuration of Equipment Under Test	7
2.1 Carrier Frequency and Channel	7
2.2 Test Mode.....	8
2.3 Connection Diagram of Test System.....	9
2.4 Support Unit used in test configuration and system	9
2.5 EUT Operation Test Setup	10
2.6 Measurement Results Explanation Example.....	10
3 Test Result	11
3.1 6dB and 99% Bandwidth Measurement	11
3.2 Output Power Measurement.....	12
3.3 Power Spectral Density Measurement	13
3.4 Conducted Band Edges and Spurious Emission Measurement	14
3.5 Radiated Band Edges and Spurious Emission Measurement	15
3.6 AC Conducted Emission Measurement.....	19
3.7 Antenna Requirements.....	21
4 List of Measuring Equipment.....	22
5 Measurement Uncertainty	24
Appendix A. Conducted Test Results	
Appendix B. AC Conducted Emission Test Result	
Appendix C. Radiated Spurious Emission Test Result	
Appendix D. Duty Cycle Plots	
Appendix E. Setup Photographs	



History of this test report

Report No.	Version	Description	Issue Date
FR591512C	01	Initial issue of report	Dec. 26, 2025
FR591512C	02	Revise Test Mode and Appendix A2 This report is an updated version, replacing the report issued on Dec. 26, 2025.	Jan. 07, 2026
FR591512C	03	Revise Test Mode This report is an updated version, replacing the report issued on Jan. 07, 2026.	Jan. 08, 2026

Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
3.1	15.247(a)(2)	6dB Bandwidth	Pass	-
3.1	2.1049	99% Occupied Bandwidth	Pass	-
3.2	15.247(b)	Power Output Measurement	Pass	-
3.3	15.247(e)	Power Spectral Density	Pass	-
3.4	15.247(d)	Conducted Band Edges	Pass	-
		Conducted Spurious Emission	Pass	-
3.5	15.247(d)	Radiated Band Edges and Radiated Spurious Emission	Pass	-
3.6	15.207	AC Conducted Emission	Pass	-
3.7	15.203	Antenna Requirement	Pass	-

Conformity Assessment Condition:

- The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacture who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
- The measurement uncertainty please refer to each test result in the section "Measurement Uncertainty".

Disclaimer:

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.

Reviewed by: Wei Chen

Report Producer: Freda Wu

1 General Description

1.1 Product Feature of Equipment Under Test

Product Feature	
General Specs Bluetooth, Wi-Fi 2.4GHz 802.11b/g/n/ac/ax, Wi-Fi 5GHz 802.11a/n/ac/ax, Wi-Fi 6GHz 802.11a/ax	
Antenna Type WLAN: Dipole Antenna	

Antenna information		
2400 MHz ~ 2483.5 MHz	Peak Gain (dBi)	2.96

Remark: The EUT's information above is declared by manufacturer. Please refer to Disclaimer in report summary.

1.2 Modification of EUT

No modifications made to the EUT during the testing.

1.3 Testing Location

The test location is accredited based on TAF code 1190 and 3786 designated by NCC (National Communication Commission).

Test Site	Sporton International Inc. EMC & Wireless Communications Laboratory
Test Site Location	No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333, Taiwan (R.O.C.)

Test Site	Sporton International Inc. Wensan Laboratory
Test Site Location	No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City 333010, Taiwan (R.O.C.)

FCC designation No.: TW1190 and TW3786

Note:

1. The test site complies with ANSI C63.4 2014 requirement.
2. The Conducted test item subcontracted to Sporton International Inc. Wensan Laboratory.



1.4 Applicable Standards

According to the specifications declared by the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC KDB Publication No. 558074 D01 15.247 Meas Guidance v05r02.
- ♦ FCC KDB 414788 D01 Radiated Test Site v01r01.
- ♦ FCC Part 15 Subpart C §15.247
- ♦ ANSI C63.10-2020

Remark:

1. All the test items were validated and recorded in accordance with the standards without any modification during the testing.
2. The TAF code is not including all the FCC KDB listed without accreditation.
3. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, the measured emission level of the EUT was maximized by rotating the EUT on a turntable, adjusting the orientation of the EUT and EUT antenna in three orthogonal axis (X: flat, Y: portrait, Z: landscape) and accessory (Adapter or Earphone), and adjusting the measurement antenna orientation, following C63.10 exploratory test procedures and only the worst case emissions were reported in this report.
- b. AC power line Conducted Emission was tested under maximum output power.

2.1 Carrier Frequency and Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	1	2412	7	2442
	2	2417	8	2447
	3	2422	9	2452
	4	2427	10	2457
	5	2432	11	2462
	6	2437		

2.2 Test Mode

This device support 26/52/106/242-tone RU.

The PSD of partial RU is reduced to be smaller than full RU according to TCB workshop interim guidance Oct. 2022.

The 802.11ax mode is investigated among different tones, full resource units (RU), partial resource units. The partial RU has no higher power than full RU's, thus the full RU is chosen as main test configuration.

The 242-tone RU is covered by 20MHz channel.

This device support SISO mode only.


The power for 802.11n mode is smaller than 802.11ac mode, so all other conducted test is covered by 802.11ac mode.

The final test modes include the worst data rates for each modulation shown in the table below.

Modulation	Data Rate
802.11b	1 Mbps
802.11g	6 Mbps
802.11n HT20 (Covered by VHT20)	MCS0
802.11ac VHT20	MCS0
802.11ax HE20	MCS0

Test Cases	
AC Conducted Emission	Mode 1 :WLAN 2.4G Link + BT Link + DC 3.3V with Power supply
Remark: 1. The detailed Radiated test modes are shown in Appendix C. 2. For radiation spurious emission, the modulation and the data rate picked for testing are determined by the Max. RF conducted power.	

2.3 Connection Diagram of Test System



2.4 Support Unit used in test configuration and system

Item	Equipment	Brand Name	Model Name	FCC ID	Data Cable	Power Cord
1.	WLAN AP	ASUS	RT-AC66U	MSQ-RTAC66U	N/A	Unshielded, 1.8 m
2.	WLAN AP	ASUS	GT-AXE11000	MSQ-RTAJF00	N/A	Unshielded, 1.8 m
3.	Notebook	DELL	Latitude 3420	FCC DoC	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
4.	Mobile Phone	Apple	A1586	BCG-E2816A	N/A	N/A
5.	DC Power Supply	GW Instek	GEU810960	FCC DoC	N/A	Unshielded, 1.8 m
6.	DC Power Supply	GW Instek	GPE2323	FCC DoC	N/A	Unshielded, 1.8 m



2.5 EUT Operation Test Setup

The RF test items, utility “Terminal” was installed in Notebook which was programmed in order to make the EUT get into the engineering modes to provide channel selection, power level, data rate and the application type and for continuous transmitting signals.

2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example:

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 4.2 dB and 10 dB attenuator.

$$\begin{aligned} \text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)}. \\ &= 4.2 + 10 = 14.2 \text{ (dB)} \end{aligned}$$

3 Test Result

3.1 6dB and 99% Bandwidth Measurement

3.1.1 Limit of 6dB and 99% Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.


3.1.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.1.3 Test Procedures

1. The testing follows the ANSI C63.10 Section 6.9.3 (OBW) and 11.8.1 (6dB BW).
2. The RF output of EUT is connected to the spectrum analyzer by RF cable and attenuator. The path loss is compensated to the results for each measurement.
3. Set the maximum power setting and enable the EUT to transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 1% to 5% of the OBW but not less than 100 kHz. Set the Video bandwidth VBW $\geq 3 * RBW$. In order to make an accurate measurement. The 6dB bandwidth must be greater than 500 kHz.
5. For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) is set 1-5% of the emission bandwidth, and set the Video bandwidth (VBW) $\geq 3 * RBW$.
6. Measure and record the results in the test report.

3.1.4 Test Setup



3.1.5 Test Result of 6dB and 99% Occupied Bandwidth

Please refer to Appendix A.

3.2 Output Power Measurement

3.2.1 Limit of Output Power

For systems using digital modulation in the 2400-2483.5 MHz, the limit for output power is 30 dBm. If transmitting antenna with directional gain greater than 6 dBi is used, the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.


3.2.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.2.3 Test Procedures

1. For Average Power, the testing follows ANSI C63.10 Section 11.9.2.3.2 Method AVGPM-G
2. The RF output of EUT is connected to the power meter by RF cable and attenuator. The path loss is compensated to the results for each measurement.
3. Set the maximum power setting and enable the EUT to transmit continuously.
4. Measure the conducted output power and record the results in the test report.

3.2.4 Test Setup



3.2.5 Test Result of Average Output Power

Please refer to Appendix A.

3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8 dBm in any 3 kHz band at any time interval of continuous transmission.

3.3.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.3.3 Test Procedures

1. The testing follows the ANSI C63.10 Section 11.10.2 Method PKPSD.
2. The RF output of EUT is connected to the spectrum analyzer by RF cable and attenuator. The path loss is compensated to the results for each measurement.
3. Set the maximum power setting and enable the EUT to transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth VBW = 10 kHz In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)
5. Detector = peak, Sweep time = No faster than coupled (auto) time, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
6. Measure and record the results in the test report.

3.3.4 Test Setup



3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.

3.4 Conducted Band Edges and Spurious Emission Measurement

3.4.1 Limit of Conducted Band Edges and Spurious Emission Measurement

In any 100 kHz bandwidth outside of the authorized frequency band, the emissions which fall in the non-restricted bands shall be attenuated at least 20 dB / 30dB relative to the maximum PSD level in 100 kHz by RF conducted measurement.


3.4.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.4.3 Test Procedures

1. The testing follows the ANSI C63.10 Section 11.11.3 Emission level measurement.
2. The RF output of EUT is connected to the spectrum analyzer by RF cable and attenuator. The path loss is compensated to the results for each measurement.
3. Set the maximum power setting and enable the EUT to transmit continuously.
4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB per 15.247(d).
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

3.4.4 Test Setup



3.4.5 Test Result of Conducted Band Edges and Spurious Emission

Please refer to Appendix A.

3.5 Radiated Band Edges and Spurious Emission Measurement

3.5.1 Limit of Radiated band edge and Spurious Emission Measurement

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device is measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.5.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.5.3 Test Procedures

1. The testing follows the ANSI C63.10 Section 11.12.1 Radiated emission measurements.
2. The EUT is arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT is placed on a turntable with 0.8 meter for frequency below 1 GHz and 1.5 meter for frequency above 1 GHz respectively above ground.
4. The EUT is set 3 meters away from the receiving antenna, which is mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. Radiated testing below 1 GHz is performed by adjusting the antenna tower from 1 m to 4 m and by rotating the turn table from 0 degree to 360 degrees to find the peak maximum hold reading. When there is no suspected emission found and the emission level is with at least 6 dB margin against QP limit line, the position is marked as “-”.


7. Radiated testing above 1 GHz is performed by adjusting the antenna tower from 1 m to 4 m and by rotating the turn table from 0 degree to 360 degrees to find the peak maximum hold reading for scanning all frequencies. When there is no suspected emission found and the harmonic emission level is with at least 6 dB margin against average limit line, the position is marked as “-”.
8. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW = 100 kHz for $f < 1$ GHz; VBW $\geq$ RBW; Sweep = auto; Detector function = peak; Trace = max hold;
 - (3) Set RBW = 1 MHz, VBW = 3 MHz for $f \geq 1$ GHz for peak measurement.

For average measurement:


 - VBW = 10 Hz, when duty cycle is no less than 98 percent.
 - VBW $\geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

3.5.4 Test Setup


For radiated emissions below 30MHz




For radiated emissions from 30MHz to 1GHz



For radiated test from 1GHz to 18GHz



For radiated test above 18GHz



3.5.5 Test Results of Radiated Spurious Emissions (9kHz ~ 30MHz)

The low frequency, which starts from 9 kHz to 30 MHz, is pre-scanned and the result which is 20 dB lower than the limit line is not reported.

There is adequate comparison measurement of both open-field test site and alternative test site - semi-Anechoic chamber according to 414788 D01 Radiated Test Site v01r01, and the result comes out very similar.

3.5.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix C.

3.5.7 Duty Cycle

Please refer to Appendix D.

3.5.8 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic)

Please refer to Appendix C.

3.6 AC Conducted Emission Measurement

3.6.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of Emission (MHz)	Conducted Limit (dB μ V)	
	Quasi-Peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.6.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.6.3 Test Procedures

1. The EUT is placed 0.4 meter away from the conducting wall of the shielding room, and is kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN shall be used.
6. Both Line and Neutral shall be tested in order to find out the maximum conducted emission.
7. The frequency range from 150 kHz to 30 MHz is scanned.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF bandwidth = 9kHz) with Maximum Hold Mode.

3.6.4 Test Setup



3.6.5 Test Result of AC Conducted Emission

Please refer to Appendix B.



3.7 Antenna Requirements

3.7.1 Standard Applicable

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of § 15.211, 15.213, 15.217, 15.219, 15.221, or § 15.236. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with § 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

3.7.2 Antenna Anti-Replacement Construction

Professional installation.



4 List of Measuring Equipment

Instrument	Brand Name	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Bilog Antenna	TESEQ	CBL 6111D & 00800N1D01N-06	35419 & 03	30MHz~1GHz	Apr. 21, 2025	Oct. 13, 2025~ Oct. 21, 2025	Apr. 20, 2026	Radiation (03CH07-HY)
Double Ridge Horn Antenna	ETS-Lindgren	3117	00075962	1GHz ~ 18GHz	Nov. 28, 2024	Oct. 13, 2025~ Oct. 21, 2025	Nov. 27, 2025	Radiation (03CH07-HY)
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100315	9 kHz~30 MHz	Mar. 06, 2025	Oct. 13, 2025~ Oct. 21, 2025	Mar. 05, 2026	Radiation (03CH07-HY)
Preamplifier	MITEQ	AMF-7D-0010 1800-30-10P	1590075	1GHz~18GHz	Apr. 18, 2025	Oct. 13, 2025~ Oct. 21, 2025	Apr. 17, 2026	Radiation (03CH07-HY)
Preamplifier	COM-POWER	PA-103A	161241	10MHz~1GHz	Sep. 30, 2025	Oct. 13, 2025~ Oct. 21, 2025	Sep. 29, 2026	Radiation (03CH07-HY)
Preamplifier	Agilent	8449B	3008A02362	1GHz~26.5GHz	Mar. 22, 2025	Oct. 13, 2025~ Oct. 21, 2025	Mar. 21, 2026	Radiation (03CH07-HY)
Preamplifier	EMEC	EM18G40G	060873	18-40GHz	Aug. 08, 2025	Oct. 13, 2025~ Oct. 21, 2025	Aug. 07, 2026	Radiation (03CH07-HY)
Spectrum Analyzer	Agilent	N9030A	MY52350276	3Hz~44GHz	Mar. 28, 2025	Oct. 13, 2025~ Oct. 21, 2025	Mar. 27, 2026	Radiation (03CH07-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY28655/4 MY24971/4 MY15682/4	30MHz to 18GHz	Feb. 20, 2025	Oct. 13, 2025~ Oct. 21, 2025	Feb. 19, 2026	Radiation (03CH07-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY28655/4 MY24971/4	9kHz to 30MHz	Feb. 20, 2025	Oct. 13, 2025~ Oct. 21, 2025	Feb. 19, 2026	Radiation (03CH07-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 126	532078/126E	30MHz~18GHz	Sep. 13, 2025	Oct. 13, 2025~ Oct. 21, 2025	Sep. 12, 2026	Radiation (03CH07-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	MY2858/2	18GHz~40GHz	Feb. 20, 2025	Oct. 13, 2025~ Oct. 21, 2025	Feb. 19, 2026	Radiation (03CH07-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	801606/2	9KHz ~ 40GHz	Apr. 23, 2025	Oct. 13, 2025~ Oct. 21, 2025	Apr. 22, 2026	Radiation (03CH07-HY)
Controller	EMEC	EM1000	N/A	Control Ant Mast	N/A	Oct. 13, 2025~ Oct. 21, 2025	N/A	Radiation (03CH07-HY)
Controller	MF	MF-7802	N/A	Control Turn table	N/A	Oct. 13, 2025~ Oct. 21, 2025	N/A	Radiation (03CH07-HY)
Antenna Mast	EMEC	AM-BS-4500E	N/A	Boresight mast 1M~4M	N/A	Oct. 13, 2025~ Oct. 21, 2025	N/A	Radiation (03CH07-HY)
Turn Table	ChainTek	Chaintek 3000	N/A	0~360 Degree	N/A	Oct. 13, 2025~ Oct. 21, 2025	N/A	Radiation (03CH07-HY)
Software	Audix	E3	N/A	N/A	N/A	Oct. 13, 2025~ Oct. 21, 2025	N/A	Radiation (03CH07-HY)
USB Data Logger	TECPEL	TR-32	HE17XB2495	N/A	Feb. 24, 2025	Oct. 13, 2025~ Oct. 21, 2025	Feb. 23, 2026	Radiation (03CH07-HY)
SHF-EHF Horn Antenna	SCHWARZBECK	BBHA 9170	00991	18GHz~40GHz	May. 29, 2025	Oct. 13, 2025~ Oct. 21, 2025	May. 28, 2026	Radiation (03CH07-HY)
AC Power Source	ChainTek	APC-1000W	N/A	N/A	N/A	Oct. 08, 2025	N/A	Conduction (CO05-HY)
EMI Test Receiver	Rohde & Schwarz	ESR3	102388	N/A	Dec. 10, 2024	Oct. 08, 2025	Dec. 09, 2025	Conduction (CO05-HY)
Hygrometer	TECPEL	DTM-303A	TP210031	N/A	Jun. 26, 2025	Oct. 08, 2025	Jun. 25, 2026	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100081	N/A	Jul. 25, 2025	Oct. 08, 2025	Jul. 24, 2026	Conduction (CO05-HY)
Software	Rohde & Schwarz	EMC32	N/A	N/A	N/A	Oct. 08, 2025	N/A	Conduction (CO05-HY)
Pulse Limiter	SCHWARZBECK	VTSD 9561-F N	00691	N/A	Jul. 29, 2025	Oct. 08, 2025	Jul. 28, 2026	Conduction (CO05-HY)
LISN Cable	MVE	RG-400	MQT24082501	N/A	Oct. 15, 2024	Oct. 08, 2025	Oct. 14, 2025	Conduction (CO05-HY)

**FCC RADIO TEST REPORT**

Report No. : FR591512C

Instrument	Brand Name	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Hygrometer	TECPEL	DTM-303A	TP201996	N/A	Nov. 01, 2024	Sep. 24, 2025~ Oct. 22, 2025	Oct. 31, 2025	Conducted (TH05-HY)
Hygrometer	TECPEL	DTM-303A	TP201996	N/A	Nov. 04, 2025	Nov. 25, 2025	Nov. 03, 2026	Conducted (TH05-HY)
Power Sensor	DARE	RPR3006W	13I00030SNO 31 (NO:182)	9kHz~6GHz	Jan. 09, 2025	Sep. 24, 2025~ Nov. 25, 2025	Jan. 08, 2026	Conducted (TH05-HY)
Signal Analyzer	Rohde & Schwarz	FSV40	101566	10Hz~40GHz	Aug. 29, 2025	Sep. 24, 2025~ Nov. 25, 2025	Aug. 28, 2026	Conducted (TH05-HY)
Switch Control Mainframe	E-Instument	ETF-1405-0	EC1900157 (BOX6)	N/A	Feb. 10, 2025	Sep. 24, 2025~ Nov. 25, 2025	Feb. 09, 2026	Conducted (TH05-HY)
Software	Sporton	BTWIFI_Final_ version_24051 3	N/A	Conducted Other Test Item	N/A	Sep. 24, 2025~ Nov. 25, 2025	N/A	Conducted (TH05-HY)

5 Measurement Uncertainty

Uncertainty of Conducted Emission Measurement (150kHz ~ 30MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	3.7 dB
---	--------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	6.3 dB
---	--------

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 6000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.7 dB
---	--------

Uncertainty of Radiated Emission Measurement (6000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.5 dB
---	--------

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.9 dB
---	--------

Appendix A. Test Result of Conducted Test Items

Test Engineer:	Willy Chang	Temperature:	21~25	°C
Test Date:	2025/9/24~2025/11/25	Relative Humidity:	51~54	%

TEST RESULTS DATA
6dB and 99% Occupied Bandwidth

2.4GHz Band Single Antenna										
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	99% Occupied BW (MHz)		6dB BW (MHz)		6dB BW Limit (MHz)	Pass/Fail
					Ant1	Ant2	Ant1	Ant2		
11b	1Mbps	1	1	2412	11.92	-	8.02	-	0.50	Pass
11b	1Mbps	1	6	2437	12.00	-	7.57	-	0.50	Pass
11b	1Mbps	1	11	2462	12.13	-	7.55	-	0.50	Pass
11g	6Mbps	1	1	2412	17.67	-	15.87	-	0.50	Pass
11g	6Mbps	1	6	2437	17.78	-	15.88	-	0.50	Pass
11g	6Mbps	1	11	2462	17.66	-	15.84	-	0.50	Pass
VHT20	MCS0	1	1	2412	18.53	-	16.97	-	0.50	Pass
VHT20	MCS0	1	6	2437	18.57	-	16.08	-	0.50	Pass
VHT20	MCS0	1	11	2462	18.48	-	16.95	-	0.50	Pass

TEST RESULTS DATA
Average Output Power

2.4GHz Band Single Antenna																
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Average Conducted Power (dBm)			Conducted Power Limit (dBm)		DG (dBi)		EIRP Power (dBm)		EIRP Power Limit (dBm)		Pass /Fail
					Ant1	Ant2	SUM	Ant1	Ant2	Ant1	Ant2	Ant1	Ant2	Ant1	Ant2	
11b	1Mbps	1	1	2412	18.98	-		30.00	-	2.96	-	21.94	-	36.00	-	Pass
11b	1Mbps	1	6	2437	18.85	-		30.00	-	2.96	-	21.81	-	36.00	-	Pass
11b	1Mbps	1	11	2462	19.18	-		30.00	-	2.96	-	22.14	-	36.00	-	Pass
11g	6Mbps	1	1	2412	18.64	-		30.00	-	2.96	-	21.60	-	36.00	-	Pass
11g	6Mbps	1	6	2437	19.63	-		30.00	-	2.96	-	22.59	-	36.00	-	Pass
11g	6Mbps	1	11	2462	16.88	-		30.00	-	2.96	-	19.84	-	36.00	-	Pass
HT20	MCS0	1	1	2412	18.67	-		30.00	-	2.96	-	21.63	-	36.00	-	Pass
HT20	MCS0	1	6	2437	19.27	-		30.00	-	2.96	-	22.23	-	36.00	-	Pass
HT20	MCS0	1	11	2462	14.75	-		30.00	-	2.96	-	17.71	-	36.00	-	Pass
VHT20	MCS0	1	1	2412	18.71	-		30.00	-	2.96	-	21.67	-	36.00	-	Pass
VHT20	MCS0	1	6	2437	19.46	-		30.00	-	2.96	-	22.42	-	36.00	-	Pass
VHT20	MCS0	1	11	2462	14.82	-		30.00	-	2.96	-	17.78	-	36.00	-	Pass

Note: Measured power (dBm) has offset with cable loss.

TEST RESULTS DATA
Peak Power Spectral Density

2.4GHz Band Single Antenna												
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Peak PSD (dBm/3kHz)			DG (dBi)		Peak PSD Limit (dBm/3kHz)		Pass/Fail
					Ant1	Ant2	Worse + 3.01	Ant1	Ant2	Ant1	Ant2	
11b	1Mbps	1	1	2412	-1.23	-		2.96	-	8.00	-	Pass
11b	1Mbps	1	6	2437	-2.71	-		2.96	-	8.00	-	Pass
11b	1Mbps	1	11	2462	-3.04	-		2.96	-	8.00	-	Pass
11g	6Mbps	1	1	2412	-5.68	-		2.96	-	8.00	-	Pass
11g	6Mbps	1	6	2437	-3.48	-		2.96	-	8.00	-	Pass
11g	6Mbps	1	11	2462	-7.64	-		2.96	-	8.00	-	Pass
VHT20	MCS0	1	1	2412	-4.53	-		2.96	-	8.00	-	Pass
VHT20	MCS0	1	6	2437	-3.66	-		2.96	-	8.00	-	Pass
VHT20	MCS0	1	11	2462	-7.55	-		2.96	-	8.00	-	Pass

Measured power density (dBm) has offset with cable loss.

TEST RESULTS DATA
6dB and 99% Occupied Bandwidth

2.4GHz Band Single Antenna											
Mod.	Data Rate	NTx	CH.	Freq. (MHz)	RU Config	99% Occupied BW (MHz)		6dB BW (MHz)		6dB BW Limit (MHz)	Pass/Fail
						Ant1	Ant2	Ant1	Ant2		
HE20	MCS0	1	1	2412	Full	19.28	-	18.87	-	0.50	Pass
HE20	MCS0	1	6	2437	Full	19.33	-	19.01	-	0.50	Pass
HE20	MCS0	1	11	2462	Full	19.28	-	18.87	-	0.50	Pass

TEST RESULTS DATA
Average Output Power

2.4GHz Band Single Antenna																	
Mod.	Data Rate	NTx	CH.	Freq. (MHz)	RU Config	Average Conducted Power (dBm)			Conducted Power Limit (dBm)		DG (dBi)		EIRP Power (dBm)		EIRP Power Limit (dBm)		Pass /Fail
						Ant1	Ant2	SUM	Ant1	Ant2	Ant1	Ant2	Ant1	Ant2	Ant1	Ant2	
HE20	MCS0	1	1	2412	Full	18.81	-		30.00	-	2.96	-	21.77	-	36.00	-	Pass
HE20	MCS0	1	1	2412	26/0	11.72	-		30.00	-	2.96	-	14.68	-	36.00	-	Pass
HE20	MCS0	1	1	2412	52/37	14.08	-		30.00	-	2.96	-	17.04	-	36.00	-	Pass
HE20	MCS0	1	1	2412	106/53	18.07	-		30.00	-	2.96	-	21.03	-	36.00	-	Pass
HE20	MCS0	1	6	2437	Full	19.56	-		30.00	-	2.96	-	22.52	-	36.00	-	Pass
HE20	MCS0	1	6	2437	26/4	12.51	-		30.00	-	2.96	-	15.47	-	36.00	-	Pass
HE20	MCS0	1	6	2437	52/38	14.71	-		30.00	-	2.96	-	17.67	-	36.00	-	Pass
HE20	MCS0	1	6	2437	106/53	18.45	-		30.00	-	2.96	-	21.41	-	36.00	-	Pass
HE20	MCS0	1	11	2462	Full	15.08	-		30.00	-	2.96	-	18.04	-	36.00	-	Pass
HE20	MCS0	1	11	2462	26/8	7.43	-		30.00	-	2.96	-	10.39	-	36.00	-	Pass
HE20	MCS0	1	11	2462	52/40	9.71	-		30.00	-	2.96	-	12.67	-	36.00	-	Pass
HE20	MCS0	1	11	2462	106/54	13.31	-		30.00	-	2.96	-	16.27	-	36.00	-	Pass

Note: Measured power (dBm) has offset with cable loss.


TEST RESULTS DATA
Peak Power Spectral Density

2.4GHz Band Single Antenna													
Mod.	Data Rate	NTx	CH.	Freq. (MHz)	RU Config	Peak PSD (dBm/3kHz)			DG (dBi)		Peak PSD Limit (dBm/3kHz)		Pass/Fail
						Ant1	Ant2	Worse + 3.01	Ant1	Ant2	Ant1	Ant2	
HE20	MCS0	1	1	2412	Full	-7.12	-		2.96	-	8.00	-	Pass
HE20	MCS0	1	1	2412	26/0	-7.45	-		2.96	-	8.00	-	Pass
HE20	MCS0	1	1	2412	52/37	-7.46	-		2.96	-	8.00	-	Pass
HE20	MCS0	1	1	2412	106/53	-7.17	-		2.96	-	8.00	-	Pass
HE20	MCS0	1	6	2437	Full	-6.07	-		2.96	-	8.00	-	Pass
HE20	MCS0	1	6	2437	26/4	-6.63	-		2.96	-	8.00	-	Pass
HE20	MCS0	1	6	2437	52/38	-6.28	-		2.96	-	8.00	-	Pass
HE20	MCS0	1	6	2437	106/53	-6.32	-		2.96	-	8.00	-	Pass
HE20	MCS0	1	11	2462	Full	-12.03	-		2.96	-	8.00	-	Pass
HE20	MCS0	1	11	2462	26/8	-12.56	-		2.96	-	8.00	-	Pass
HE20	MCS0	1	11	2462	52/40	-12.13	-		2.96	-	8.00	-	Pass
HE20	MCS0	1	11	2462	106/54	-12.37	-		2.96	-	8.00	-	Pass

Measured power density (dBm) has offset with cable loss.

**6dB and 99% Occupied Bandwidth**


<802.11b>



Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.




<802.11g>



Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.




<802.11ac20>



Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.



<802.11ax20>




Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.




Power Spectral Density(dBm/3kHz)

<802.11b>






<802.11g>






<802.11ac20>





<802.11ax20>







**Band Edges and Spurious Emission**

Number of TX = 1, Ant. 1 (Measured)

Test Mode : 802.11b

Test Channel : 01


100kHz PSD reference Level**Channel 01 Plot****Spurious Emission 30MHz~1GHz****Spurious Emission 1GHz~26.5GHz**



Test Mode : 802.11b


Test Channel : 06

100kHz PSD reference Level




Channel 06 Plot

Spurious Emission 30MHz~1GHz



Spurious Emission 1GHz~26.5GHz







Test Mode : 802.11b

Test Channel : 11


100kHz PSD reference Level




Channel 11 Plot



Spurious Emission 30MHz~1GHz



Spurious Emission 1GHz~26.5GHz







Test Mode : 802.11g

Test Channel : 01


100kHz PSD reference Level




Channel 01 Plot



Spurious Emission 30MHz~1GHz



Spurious Emission 1GHz~26.5GHz






Test Mode : 802.11g


Test Channel : 06

100kHz PSD reference Level




Channel 06 Plot

Spurious Emission 30MHz~1GHz



Spurious Emission 1GHz~26.5GHz







Test Mode : 802.11g

Test Channel : 11


100kHz PSD reference Level




Channel 11 Plot



Spurious Emission 30MHz~1GHz



Spurious Emission 1GHz~26.5GHz







Test Mode : 802.11ac20

Test Channel : 01


100kHz PSD reference Level




Channel 01 Plot



Spurious Emission 30MHz~1GHz



Spurious Emission 1GHz~26.5GHz






Test Mode : 802.11ac20


Test Channel : 06

100kHz PSD reference Level




Channel 06 Plot

Spurious Emission 30MHz~1GHz



Spurious Emission 1GHz~26.5GHz







Test Mode : 802.11ac20

Test Channel : 11


100kHz PSD reference Level




Channel 11 Plot



Spurious Emission 30MHz~1GHz



Spurious Emission 1GHz~26.5GHz







Test Mode : 802.11ax20_FullIRU

Test Channel : 01


100kHz PSD reference Level




Channel 01 Plot



Spurious Emission 30MHz~1GHz



Spurious Emission 1GHz~26.5GHz






Test Mode : 802.11ax20_FullRU


Test Channel : 06

100kHz PSD reference Level




Channel 06 Plot

Spurious Emission 30MHz~1GHz



Spurious Emission 1GHz~26.5GHz







Test Mode : 802.11ax20_FullRU

Test Channel : 11


100kHz PSD reference Level




Channel 11 Plot



Spurious Emission 30MHz~1GHz



Spurious Emission 1GHz~26.5GHz






Appendix B. AC Conducted Emission Test Results

Test Engineer :	Calvin Wang	Temperature :	23~26℃
		Relative Humidity :	45~55%

EUT Information

Report NO : 591512
Test Mode : Mode 1
Test Voltage : 120Vac/60Hz
Phase : Line

Full Spectrum




Final Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.152250	---	18.33	55.88	37.55	L1	OFF	19.8
0.152250	20.67	---	65.88	45.21	L1	OFF	19.8
0.231000	---	14.39	52.41	38.02	L1	OFF	19.8
0.231000	16.10	---	62.41	46.31	L1	OFF	19.8
0.588750	---	13.01	46.00	32.99	L1	OFF	19.8
0.588750	14.34	---	56.00	41.66	L1	OFF	19.8
2.384250	---	13.89	46.00	32.11	L1	OFF	19.8
2.384250	15.11	---	56.00	40.89	L1	OFF	19.8
13.769250	---	15.36	50.00	34.64	L1	OFF	20.2
13.769250	17.03	---	60.00	42.97	L1	OFF	20.2
23.068500	---	18.70	50.00	31.30	L1	OFF	19.9
23.068500	22.19	---	60.00	37.81	L1	OFF	19.9

EUT Information

Report NO : 591512
Test Mode : Mode 1
Test Voltage : 120Vac/60Hz
Phase : Neutral

Full Spectrum



Final Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.152250	---	18.22	55.88	37.66	N	OFF	19.8
0.152250	20.45	---	65.88	45.43	N	OFF	19.8
0.287250	---	13.77	50.60	36.83	N	OFF	19.8
0.287250	15.39	---	60.60	45.21	N	OFF	19.8
0.692250	---	12.97	46.00	33.03	N	OFF	19.8
0.692250	14.08	---	56.00	41.92	N	OFF	19.8
4.326000	---	15.01	46.00	30.99	N	OFF	19.9
4.326000	16.30	---	56.00	39.70	N	OFF	19.9
13.353000	---	16.06	50.00	33.94	N	OFF	20.2
13.353000	18.31	---	60.00	41.69	N	OFF	20.2
23.219250	---	18.75	50.00	31.25	N	OFF	20.0
23.219250	22.48	---	60.00	37.52	N	OFF	20.0



Appendix C. Radiated Spurious Emission Test Data

Test Engineer :	Jesse Wang, Stan Hsieh and Ken Wu	Temperature :	20.8~28.1°C
		Relative Humidity :	54.6~66.8%

Note symbol

-L	Low channel location
-R	High channel location

C1. Radiated Spurious Emission Test Modes

Mode	Band (MHz)	Antenna	Modulation	Channel	Frequency	Data Rate	RU	Remark
Mode 10	2400-2483.5	1	802.11b	01	2412	1Mbps	-	-
Mode 11	2400-2483.5	1	802.11b	06	2437	1Mbps	-	-
Mode 12	2400-2483.5	1	802.11b	11	2462	1Mbps	-	-
Mode 13	2400-2483.5	1	802.11g	01	2412	6Mbps	-	-
Mode 14	2400-2483.5	1	802.11g	06	2437	6Mbps	-	-
Mode 15	2400-2483.5	1	802.11g	11	2462	6Mbps	-	-
Mode 16	2400-2483.5	1	802.11ax HE20	01	2412	MCS0	Full RU	-
Mode 17	2400-2483.5	1	802.11ax HE20	01	2412	MCS0	Partial RU_106/53	-
Mode 18	2400-2483.5	1	802.11ax HE20	06	2437	MCS0	Full RU	-
Mode 19	2400-2483.5	1	802.11ax HE20	11	2462	MCS0	Full RU	-
Mode 20	2400-2483.5	1	802.11ax HE20	11	2462	MCS0	Partial RU_106/54	-

**FCC RADIO TEST REPORT**

Report No. : FR591512C

Mode	Band (MHz)	Antenna	Modulation	Channel	Frequency	Data Rate	RU	Remark
Mode 22	2400-2483.5	1	802.11ac VHT20	01	2412	MCS0	-	-
Mode 27	2400-2483.5	1	802.11ax HE20	01	2412	MCS0	Full RU	SHF
Mode 28	2400-2483.5	1	802.11ax HE20	01	2412	MCS0	Full RU	LF

C2. Summary of each worse mode

Mode	Modulation	Ch.	Freq. (MHz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pol.	Peak Avg.	Result	RU	Remark
10	802.11b	01	2385.40	48.24	54.00	-5.76	V	Avg.	Pass	-	Band Edge
	802.11b	01	4824.00	47.38	54.00	-6.62	V	Avg.	Pass	-	Harmonic
11	802.11b	06	2484.94	45.04	54.00	-8.96	V	Avg.	Pass	-	Band Edge
	802.11b	06	4874.00	48.20	54.00	-5.80	V	Avg.	Pass	-	Harmonic
12	802.11b	11	2488.68	51.18	54.00	-2.82	V	Avg.	Pass	-	Band Edge
	802.11b	11	4924.00	46.83	54.00	-7.17	V	Avg.	Pass	-	Harmonic
13	802.11g	01	2389.69	50.65	54.00	-3.35	V	Avg.	Pass	-	Band Edge
	802.11g	01	4824.00	40.38	54.00	-13.62	V	Avg.	Pass	-	Harmonic
14	802.11g	06	2487.40	47.48	54.00	-6.52	V	Avg.	Pass	-	Band Edge
	802.11g	06	7311.00	41.16	54.00	-12.84	V	Avg.	Pass	-	Harmonic
15	802.11g	11	2483.55	52.10	54.00	-1.90	V	Avg.	Pass	-	Band Edge

**FCC RADIO TEST REPORT**

Report No. : FR591512C

Mode	Modulation	Ch.	Freq. (MHz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pol.	Peak Avg.	Result	RU	Remark
15	802.11g	11	4924.00	40.06	54.00	-13.94	V	Avg.	Pass	-	Harmonic
16	802.11ax HE20	01	2389.04	52.18	54.00	-1.82	V	Avg.	Pass	Full RU	Band Edge
	802.11ax HE20	01	4824.00	40.08	54.00	-13.92	V	Avg.	Pass	Full RU	Harmonic
17	802.11ax HE20	01	2389.95	50.23	54.00	-3.77	H	Avg.	Pass	Partial RU_106/53	Band Edge
	802.11ax HE20	01	-	-	-	-	-	-	-	Partial RU_106/53	Harmonic
18	802.11ax HE20	06	2483.56	48.63	54.00	-5.37	V	Avg.	Pass	Full RU	Band Edge
	802.11ax HE20	06	7311.00	44.52	74.00	-29.48	V	Peak	Pass	Full RU	Harmonic
19	802.11ax HE20	11	2483.85	51.83	54.00	-2.17	V	Avg.	Pass	Full RU	Band Edge
	802.11ax HE20	11	7380.00	42.96	74.00	-31.04	V	Peak	Pass	Full RU	Harmonic
20	802.11ax HE20	11	2483.96	51.02	54.00	-2.98	H	Avg.	Pass	Partial RU_106/54	Band Edge
	802.11ax HE20	11	-	-	-	-	-	-	-	Partial RU_106/54	Harmonic

**FCC RADIO TEST REPORT**

Report No. : FR591512C

Mode	Modulation	Ch.	Freq. (MHz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pol.	Peak Avg.	Result	RU	Remark
22	802.11ac VHT20	01	2389.95	52.09	54.00	-1.91	H	Avg.	Pass	-	Band Edge
	802.11ac VHT20	01	4824.00	37.69	54.00	-16.31	V	Avg.	Pass	-	Harmonic
27	LF	01	24986.00	39.62	74.00	-34.38	H	Peak	Pass	-	SHF
28	SHF	01	30.97	32.50	40.00	-7.50	V	Peak	Pass	-	LF



Mode	10																																																																																									
	Band Edge																																																																																									
	2400-2483.5_802.11b_CH01_2412MHz																																																																																									
ANT	1																																																																																									
Pol.	Horizontal						Fundamental																																																																																			
Peak	Level (dBuV/m) Date: 2025-10-13 Site : 03CH07-HY Condition: PEAK_BE_74 3m HF_ANT_00075962 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>2388.00</td><td>56.10</td><td>74.00</td><td>-17.90</td><td>40.41</td><td>32.10</td><td>8.36</td><td>34.67</td><td>9.90</td><td>336</td><td>323</td><td>Peak</td></tr></table>							Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	2388.00	56.10	74.00	-17.90	40.41	32.10	8.36	34.67	9.90	336	323	Peak	Level (dBuV/m) Date: 2025-10-13 Site : 03CH07-HY Condition: PEAK_74 3m HF_ANT_00075962 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>2412.00</td><td>107.22</td><td>-----</td><td>-----</td><td>91.45</td><td>32.14</td><td>8.40</td><td>34.67</td><td>9.90</td><td>336</td><td>323</td><td>Peak</td></tr></table>							Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	2412.00	107.22	-----	-----	91.45	32.14	8.40	34.67	9.90	336	323	Peak
		Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																													
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																															
1	2388.00	56.10	74.00	-17.90	40.41	32.10	8.36	34.67	9.90	336	323	Peak																																																																														
	Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																														
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																															
1	2412.00	107.22	-----	-----	91.45	32.14	8.40	34.67	9.90	336	323	Peak																																																																														
Avg	Level (dBuV/m) Date: 2025-10-13 Site : 03CH07-HY Condition: AVG_BE_54 3m HF_ANT_00075962 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>2385.27</td><td>46.15</td><td>54.00</td><td>-7.85</td><td>30.47</td><td>32.10</td><td>8.35</td><td>34.67</td><td>9.90</td><td>336</td><td>323</td><td>Average</td></tr></table>							Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	2385.27	46.15	54.00	-7.85	30.47	32.10	8.35	34.67	9.90	336	323	Average	Level (dBuV/m) Date: 2025-10-13 Site : 03CH07-HY Condition: AVG_54 3m HF_ANT_00075962 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>2412.00</td><td>104.12</td><td>-----</td><td>-----</td><td>88.35</td><td>32.14</td><td>8.40</td><td>34.67</td><td>9.90</td><td>336</td><td>323</td><td>Average</td></tr></table>							Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	2412.00	104.12	-----	-----	88.35	32.14	8.40	34.67	9.90	336	323	Average
		Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																													
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																															
1	2385.27	46.15	54.00	-7.85	30.47	32.10	8.35	34.67	9.90	336	323	Average																																																																														
	Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																														
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																															
1	2412.00	104.12	-----	-----	88.35	32.14	8.40	34.67	9.90	336	323	Average																																																																														



Mode	10																																																																																																	
	Band Edge																																																																																																	
	2400-2483.5_802.11b_CH01_2412MHz																																																																																																	
ANT	1																																																																																																	
Pol.	Vertical						Fundamental																																																																																											
Peak	Level (dBuV/m) Date: 2025-10-13 Site : 03CH07-HY Condition: PEAK_BE_74 3m HF_ANT_00075962 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2383.45</td><td>56.97</td><td>74.00</td><td>-17.03</td><td>41.29</td><td>32.10</td><td>8.35</td><td>34.67</td><td>9.90</td><td>269</td><td>93</td><td>Peak</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dB/m	dB	dB	cm	deg	1	2383.45	56.97	74.00	-17.03	41.29	32.10	8.35	34.67	9.90	269	93	Peak	Level (dBuV/m) Date: 2025-10-13 Site : 03CH07-HY Condition: PEAK_74 3m HF_ANT_00075962 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2412.00</td><td>110.26</td><td>-----</td><td>-----</td><td>94.49</td><td>32.14</td><td>8.40</td><td>34.67</td><td>9.90</td><td>269</td><td>93</td><td>Peak</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dB/m	dB	dB	cm	deg	1	2412.00	110.26	-----	-----	94.49	32.14	8.40	34.67	9.90	269	93	Peak
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																								
Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor																																																																																											
	MHz	dBuV/m	dBuV/m	dB	dB/m	dB	dB	cm	deg																																																																																									
1	2383.45	56.97	74.00	-17.03	41.29	32.10	8.35	34.67	9.90	269	93	Peak																																																																																						
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																									
Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor																																																																																											
	MHz	dBuV/m	dBuV/m	dB	dB/m	dB	dB	cm	deg																																																																																									
1	2412.00	110.26	-----	-----	94.49	32.14	8.40	34.67	9.90	269	93	Peak																																																																																						
Avg	Level (dBuV/m) Date: 2025-10-13 Site : 03CH07-HY Condition: AVG_BE_54 3m HF_ANT_00075962 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2385.40</td><td>48.24</td><td>54.00</td><td>-5.76</td><td>32.56</td><td>32.10</td><td>8.35</td><td>34.67</td><td>9.90</td><td>269</td><td>93</td><td>Average</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dB/m	dB	dB	cm	deg	1	2385.40	48.24	54.00	-5.76	32.56	32.10	8.35	34.67	9.90	269	93	Average	Level (dBuV/m) Date: 2025-10-13 Site : 03CH07-HY Condition: AVG_54 3m HF_ANT_00075962 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2412.00</td><td>107.29</td><td>-----</td><td>-----</td><td>91.47</td><td>32.18</td><td>8.40</td><td>34.67</td><td>9.91</td><td>269</td><td>93</td><td>Average</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dB/m	dB	dB	cm	deg	1	2412.00	107.29	-----	-----	91.47	32.18	8.40	34.67	9.91	269	93	Average
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																								
Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor																																																																																											
	MHz	dBuV/m	dBuV/m	dB	dB/m	dB	dB	cm	deg																																																																																									
1	2385.40	48.24	54.00	-5.76	32.56	32.10	8.35	34.67	9.90	269	93	Average																																																																																						
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																									
Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor																																																																																											
	MHz	dBuV/m	dBuV/m	dB	dB/m	dB	dB	cm	deg																																																																																									
1	2412.00	107.29	-----	-----	91.47	32.18	8.40	34.67	9.91	269	93	Average																																																																																						







Mode	10																																																																																																																																																							
	Harmonic																																																																																																																																																							
	2400-2483.5_802.11b_CH01_2412MHz																																																																																																																																																							
ANT	1																																																																																																																																																							
Pol.	Horizontal						Vertical																																																																																																																																																	
Peak Avg	Level (dBuV/m) Date: 2025-10-14 Site : 03CH07-HY Condition: PEAK_74 3m HF_ANT_00075962 HORIZONTAL <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>4824.00</td><td>43.05</td><td>74.00</td><td>-30.95</td><td>54.18</td><td>34.25</td><td>11.95</td><td>58.37</td><td>1.04</td><td>100</td><td>193</td><td>Peak</td></tr><tr><td>2</td><td>4824.00</td><td>39.13</td><td>54.00</td><td>-14.87</td><td>50.26</td><td>34.25</td><td>11.95</td><td>58.37</td><td>1.04</td><td>100</td><td>193</td><td>Average</td></tr><tr><td>3</td><td>9975.00</td><td>50.55</td><td>-----</td><td>-----</td><td>53.89</td><td>36.90</td><td>17.88</td><td>59.28</td><td>1.16</td><td>--</td><td>--</td><td>Peak</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	4824.00	43.05	74.00	-30.95	54.18	34.25	11.95	58.37	1.04	100	193	Peak	2	4824.00	39.13	54.00	-14.87	50.26	34.25	11.95	58.37	1.04	100	193	Average	3	9975.00	50.55	-----	-----	53.89	36.90	17.88	59.28	1.16	--	--	Peak	Level (dBuV/m) Date: 2025-10-14 Site : 03CH07-HY Condition: PEAK_74 3m HF_ANT_00075962 VERTICAL <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>4824.00</td><td>50.18</td><td>74.00</td><td>-23.82</td><td>61.31</td><td>34.25</td><td>11.95</td><td>58.37</td><td>1.04</td><td>300</td><td>72</td><td>Peak</td></tr><tr><td>2</td><td>4824.00</td><td>47.38</td><td>54.00</td><td>-6.62</td><td>58.51</td><td>34.25</td><td>11.95</td><td>58.37</td><td>1.04</td><td>300</td><td>72</td><td>Average</td></tr><tr><td>3</td><td>9975.00</td><td>57.20</td><td>-----</td><td>-----</td><td>60.54</td><td>36.90</td><td>17.88</td><td>59.28</td><td>1.16</td><td>--</td><td>--</td><td>Peak</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	4824.00	50.18	74.00	-23.82	61.31	34.25	11.95	58.37	1.04	300	72	Peak	2	4824.00	47.38	54.00	-6.62	58.51	34.25	11.95	58.37	1.04	300	72	Average	3	9975.00	57.20	-----	-----	60.54	36.90	17.88	59.28	1.16	--	--	Peak
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																														
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																																
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																														
1	4824.00	43.05	74.00	-30.95	54.18	34.25	11.95	58.37	1.04	100	193	Peak																																																																																																																																												
2	4824.00	39.13	54.00	-14.87	50.26	34.25	11.95	58.37	1.04	100	193	Average																																																																																																																																												
3	9975.00	50.55	-----	-----	53.89	36.90	17.88	59.28	1.16	--	--	Peak																																																																																																																																												
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																															
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																																
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																														
1	4824.00	50.18	74.00	-23.82	61.31	34.25	11.95	58.37	1.04	300	72	Peak																																																																																																																																												
2	4824.00	47.38	54.00	-6.62	58.51	34.25	11.95	58.37	1.04	300	72	Average																																																																																																																																												
3	9975.00	57.20	-----	-----	60.54	36.90	17.88	59.28	1.16	--	--	Peak																																																																																																																																												

Remark: The unwanted signal 9975.000MHz ~ 9975.000MHz can be ignored since it falls within the non-restricted band and meet the requirements of 15.247 (d).



Mode	10	
	Harmonic	
	2400-2483.5_802.11b_CH01_2412MHz	
ANT	1	
Pol.	Horizontal	Vertical
14.47G ~14.5G Avg	Level (dBuV/m) Date: 2025-10-14 Site : 03CH07-HY Condition: AVG_54 3m HF_ANT_00075962 HORIZONTAL	Level (dBuV/m) Date: 2025-10-14 Site : 03CH07-HY Condition: AVG_54 3m HF_ANT_00075962 VERTICAL
	Level (dBuV/m) Date: 2025-10-14 Site : 03CH07-HY Condition: AVG_54 3m HF_ANT_00075962 HORIZONTAL	Level (dBuV/m) Date: 2025-10-14 Site : 03CH07-HY Condition: AVG_54 3m HF_ANT_00075962 VERTICAL



Mode	11																																																																																																
	Band Edge - L																																																																																																
	2400-2483.5_802.11b_CH06_2437MHz																																																																																																
ANT	1																																																																																																
Pol.	Horizontal						Fundamental																																																																																										
Peak	Level (dBuV/m) Date: 2025-10-13 						Level (dBuV/m) Date: 2025-10-13 																																																																																										
	Site : 03CH07-HY Condition: PEAK_BE_74 3m HF_ANT_00075962 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto						Site : 03CH07-HY Condition: PEAK_74 3m HF_ANT_00075962 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto																																																																																										
	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2374.64</td><td>55.88</td><td>74.00</td><td>-18.12</td><td>40.26</td><td>32.05</td><td>8.33</td><td>34.66</td><td>9.90</td><td>100</td><td>34 Peak</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor		Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2374.64	55.88	74.00	-18.12	40.26	32.05	8.33	34.66	9.90	100	34 Peak	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2437.00</td><td>106.32</td><td>-----</td><td>-----</td><td>90.44</td><td>32.20</td><td>8.44</td><td>34.67</td><td>9.91</td><td>100</td><td>34 Peak</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor		Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2437.00	106.32	-----	-----	90.44	32.20	8.44	34.67	9.91	100
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																									
Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor		Remark																																																																																								
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																							
1	2374.64	55.88	74.00	-18.12	40.26	32.05	8.33	34.66	9.90	100	34 Peak																																																																																						
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																									
Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor		Remark																																																																																								
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																							
1	2437.00	106.32	-----	-----	90.44	32.20	8.44	34.67	9.91	100	34 Peak																																																																																						
Avg	Level (dBuV/m) Date: 2025-10-13 						Level (dBuV/m) Date: 2025-10-13 																																																																																										
	Site : 03CH07-HY Condition: AVG_BE_54 3m HF_ANT_00075962 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto						Site : 03CH07-HY Condition: AVG_54 3m HF_ANT_00075962 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto																																																																																										
	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2388.99</td><td>44.11</td><td>54.00</td><td>-9.89</td><td>28.42</td><td>32.10</td><td>8.36</td><td>34.67</td><td>9.90</td><td>100</td><td>34 Average</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor		Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2388.99	44.11	54.00	-9.89	28.42	32.10	8.36	34.67	9.90	100	34 Average	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2437.00</td><td>103.21</td><td>-----</td><td>-----</td><td>87.33</td><td>32.20</td><td>8.44</td><td>34.67</td><td>9.91</td><td>100</td><td>34 Average</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor		Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2437.00	103.21	-----	-----	87.33	32.20	8.44	34.67	9.91	100
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																									
Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor		Remark																																																																																								
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																							
1	2388.99	44.11	54.00	-9.89	28.42	32.10	8.36	34.67	9.90	100	34 Average																																																																																						
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																									
Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor		Remark																																																																																								
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																							
1	2437.00	103.21	-----	-----	87.33	32.20	8.44	34.67	9.91	100	34 Average																																																																																						



Mode	11										
	Band Edge - R										
	2400-2483.5_802.11b_CH06_2437MHz										
ANT	1										
Pol.	Horizontal						Fundamental				
Peak	<										



Mode	11																																																																																											
	Band Edge - L																																																																																											
	2400-2483.5_802.11b_CH06_2437MHz																																																																																											
ANT	1																																																																																											
Pol.	Vertical												Fundamental																																																																															
Peak	Level (dBuV/m) Frequency (MHz) Site : 03CH07-HY Condition: PEAK_BE_74 3m HF_ANT_00075962 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>2367.02</td><td>55.40</td><td>74.00</td><td>-18.60</td><td>39.84</td><td>32.00</td><td>8.32</td><td>34.66</td><td>9.90</td><td>268</td><td>94</td><td>Peak</td></tr></table>														Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	2367.02	55.40	74.00	-18.60	39.84	32.00	8.32	34.66	9.90	268	94	Peak	Level (dBuV/m) Frequency (MHz) Site : 03CH07-HY Condition: PEAK_74 3m HF_ANT_00075962 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>2437.00</td><td>111.01</td><td>-----</td><td>-----</td><td>95.13</td><td>32.20</td><td>8.44</td><td>34.67</td><td>9.91</td><td>268</td><td>94</td><td>Peak</td></tr></table>		Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	2437.00	111.01	-----	-----	95.13	32.20	8.44	34.67	9.91	268	94	Peak
		Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																															
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																	
1	2367.02	55.40	74.00	-18.60	39.84	32.00	8.32	34.66	9.90	268	94	Peak																																																																																
	Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																																
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																	
1	2437.00	111.01	-----	-----	95.13	32.20	8.44	34.67	9.91	268	94	Peak																																																																																
Avg	Level (dBuV/m) Frequency (MHz) Site : 03CH07-HY Condition: AVG_BE_54 3m HF_ANT_00075962 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>2369.63</td><td>44.44</td><td>54.00</td><td>-9.56</td><td>28.75</td><td>32.10</td><td>8.36</td><td>34.67</td><td>9.90</td><td>268</td><td>94</td><td>Average</td></tr></table>														Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	2369.63	44.44	54.00	-9.56	28.75	32.10	8.36	34.67	9.90	268	94	Average	Level (dBuV/m) Frequency (MHz) Site : 03CH07-HY Condition: AVG_54 3m HF_ANT_00075962 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>2437.00</td><td>107.89</td><td>-----</td><td>-----</td><td>92.01</td><td>32.20</td><td>8.44</td><td>34.67</td><td>9.91</td><td>268</td><td>94</td><td>Average</td></tr></table>		Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	2437.00	107.89	-----	-----	92.01	32.20	8.44	34.67	9.91	268	94	Average
		Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																															
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																	
1	2369.63	44.44	54.00	-9.56	28.75	32.10	8.36	34.67	9.90	268	94	Average																																																																																
	Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																																
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																	
1	2437.00	107.89	-----	-----	92.01	32.20	8.44	34.67	9.91	268	94	Average																																																																																



Mode	11																																														
	Band Edge - R																																														
	2400-2483.5_802.11b_CH06_2437MHz																																														
ANT	1																																														
Pol.	Vertical						Fundamental																																								
Peak	Level (dBuV/m) Date: 2025-10-13 PEAK_BE_74 Site : 03CH07-HY Condition: PEAK_BE_74 3m HF_ANT_00075962 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>2500.00</td><td>56.49</td><td>74.00</td><td>-17.51</td><td>40.08</td><td>32.60</td><td>8.55</td><td>34.68</td><td>9.94</td><td>268</td><td>94 Peak</td></tr></table>						Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	2500.00	56.49	74.00	-17.51	40.08	32.60	8.55	34.68	9.94	268	94 Peak	Blank				
Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																				
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																					
1	2500.00	56.49	74.00	-17.51	40.08	32.60	8.55	34.68	9.94	268	94 Peak																																				
Avg	Level (dBuV/m) Date: 2025-10-13 AVG_BE_54 Site : 03CH07-HY Condition: AVG_BE_54 3m HF_ANT_00075962 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><tr><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>2484.94</td><td>45.04</td><td>54.00</td><td>-8.96</td><td>28.82</td><td>32.45</td><td>8.52</td><td>34.68</td><td>9.93</td><td>268</td><td>94 Average</td></tr></table>						Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	2484.94	45.04	54.00	-8.96	28.82	32.45	8.52	34.68	9.93	268	94 Average	Blank				
Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																				
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																					
1	2484.94	45.04	54.00	-8.96	28.82	32.45	8.52	34.68	9.93	268	94 Average																																				



	11																																																																																																																																																																								
Mode	Harmonic																																																																																																																																																																								
	2400-2483.5_802.11b_CH06_2437MHz																																																																																																																																																																								
ANT	1																																																																																																																																																																								
Pol.	Horizontal						Vertical																																																																																																																																																																		
Peak Avg	Level (dBuV/m) Date: 2025-10-14 Site : 03CH07-HY Condition: PEAK_74 3m HF_ANT_00075962 HORIZONTAL <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>4874.00</td><td>47.24</td><td>74.00</td><td>-26.76</td><td>58.28</td><td>34.20</td><td>12.02</td><td>58.26</td><td>1.00</td><td>300</td><td>16 Peak</td></tr><tr><td>2</td><td>4874.00</td><td>40.42</td><td>54.00</td><td>-13.58</td><td>51.46</td><td>34.20</td><td>12.02</td><td>58.26</td><td>1.00</td><td>300</td><td>16 Average</td></tr><tr><td>3</td><td>7311.00</td><td>43.02</td><td>74.00</td><td>-30.98</td><td>49.16</td><td>35.70</td><td>14.68</td><td>57.68</td><td>1.16</td><td>--</td><td>-- Peak</td></tr><tr><td>4</td><td>9990.00</td><td>50.96</td><td>-----</td><td>-----</td><td>54.21</td><td>36.96</td><td>17.89</td><td>59.26</td><td>1.16</td><td>--</td><td>-- Peak</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	4874.00	47.24	74.00	-26.76	58.28	34.20	12.02	58.26	1.00	300	16 Peak	2	4874.00	40.42	54.00	-13.58	51.46	34.20	12.02	58.26	1.00	300	16 Average	3	7311.00	43.02	74.00	-30.98	49.16	35.70	14.68	57.68	1.16	--	-- Peak	4	9990.00	50.96	-----	-----	54.21	36.96	17.89	59.26	1.16	--	-- Peak	Level (dBuV/m) Date: 2025-10-14 Site : 03CH07-HY Condition: PEAK_74 3m HF_ANT_00075962 VERTICAL <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>4874.00</td><td>50.65</td><td>74.00</td><td>-23.35</td><td>61.69</td><td>34.20</td><td>12.02</td><td>58.26</td><td>1.00</td><td>326</td><td>72 Peak</td></tr><tr><td>2</td><td>4874.00</td><td>48.20</td><td>54.00</td><td>-5.80</td><td>59.24</td><td>34.20</td><td>12.02</td><td>58.26</td><td>1.00</td><td>326</td><td>72 Average</td></tr><tr><td>3</td><td>7311.00</td><td>43.81</td><td>74.00</td><td>-30.19</td><td>49.95</td><td>35.70</td><td>14.68</td><td>57.68</td><td>1.16</td><td>--</td><td>-- Peak</td></tr><tr><td>4</td><td>9960.00</td><td>57.05</td><td>-----</td><td>-----</td><td>60.48</td><td>36.84</td><td>17.86</td><td>59.30</td><td>1.17</td><td>--</td><td>-- Peak</td></tr></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	4874.00	50.65	74.00	-23.35	61.69	34.20	12.02	58.26	1.00	326	72 Peak	2	4874.00	48.20	54.00	-5.80	59.24	34.20	12.02	58.26	1.00	326	72 Average	3	7311.00	43.81	74.00	-30.19	49.95	35.70	14.68	57.68	1.16	--	-- Peak	4	9960.00	57.05	-----	-----	60.48	36.84	17.86	59.30	1.17	--	-- Peak
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																																															
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																																																	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																																															
1	4874.00	47.24	74.00	-26.76	58.28	34.20	12.02	58.26	1.00	300	16 Peak																																																																																																																																																														
2	4874.00	40.42	54.00	-13.58	51.46	34.20	12.02	58.26	1.00	300	16 Average																																																																																																																																																														
3	7311.00	43.02	74.00	-30.98	49.16	35.70	14.68	57.68	1.16	--	-- Peak																																																																																																																																																														
4	9990.00	50.96	-----	-----	54.21	36.96	17.89	59.26	1.16	--	-- Peak																																																																																																																																																														
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																																																
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																																																	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																																															
1	4874.00	50.65	74.00	-23.35	61.69	34.20	12.02	58.26	1.00	326	72 Peak																																																																																																																																																														
2	4874.00	48.20	54.00	-5.80	59.24	34.20	12.02	58.26	1.00	326	72 Average																																																																																																																																																														
3	7311.00	43.81	74.00	-30.19	49.95	35.70	14.68	57.68	1.16	--	-- Peak																																																																																																																																																														
4	9960.00	57.05	-----	-----	60.48	36.84	17.86	59.30	1.17	--	-- Peak																																																																																																																																																														

Remark: The unwanted signal 9990.000MHz、9960.000MHz can be ignored since it falls within the non-restricted band and meet the requirements of 15.247 (d).







Mode	11	
	Harmonic	
	2400-2483.5_802.11b_CH06_2437MHz	
ANT	1	
Pol.	Horizontal	Vertical
14.47G ~14.5G Avg	Level (dBuV/m) Date: 2025-10-14 Site : 03CH07-HY Condition: AVG_54 3m HF_ANT_00075962 HORIZONTAL	Level (dBuV/m) Date: 2025-10-14 Site : 03CH07-HY Condition: AVG_54 3m HF_ANT_00075962 VERTICAL
	Level (dBuV/m) Date: 2025-10-14 Site : 03CH07-HY Condition: AVG_54 3m HF_ANT_00075962 HORIZONTAL	Level (dBuV/m) Date: 2025-10-14 Site : 03CH07-HY Condition: AVG_54 3m HF_ANT_00075962 VERTICAL



Mode	12																																																																																			
	Band Edge																																																																																			
	2400-2483.5_802.11b_CH11_2462MHz																																																																																			
ANT	1																																																																																			
Pol.	Horizontal						Fundamental																																																																													
Peak	Level (dBuV/m) Date: 2025-10-13 Site : 03CH07-HY Condition: PEAK_BE_74 3m HF_ANT_00075962 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1 2484.84</td><td>56.84</td><td>74.00</td><td>-17.16</td><td>40.62</td><td>32.45</td><td>8.52</td><td>34.68</td><td>9.93</td><td>100</td><td>310</td><td>Peak</td></tr></table>						Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1 2484.84	56.84	74.00	-17.16	40.62	32.45	8.52	34.68	9.93	100	310	Peak	Level (dBuV/m) Date: 2025-10-13 Site : 03CH07-HY Condition: PEAK_74 3m HF_ANT_00075962 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1 2462.00</td><td>104.85</td><td>-----</td><td>-----</td><td>88.83</td><td>32.30</td><td>8.48</td><td>34.68</td><td>9.92</td><td>100</td><td>310</td><td>Peak</td></tr></table>						Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1 2462.00	104.85	-----	-----	88.83	32.30	8.48	34.68	9.92	100	310	Peak
	Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																								
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																										
1 2484.84	56.84	74.00	-17.16	40.62	32.45	8.52	34.68	9.93	100	310	Peak																																																																									
Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																									
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																										
1 2462.00	104.85	-----	-----	88.83	32.30	8.48	34.68	9.92	100	310	Peak																																																																									
Avg	Level (dBuV/m) Date: 2025-10-13 Site : 03CH07-HY Condition: AVG_BE_54 3m HF_ANT_00075962 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><tr><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1 2488.71</td><td>47.33</td><td>54.00</td><td>-6.67</td><td>31.05</td><td>32.49</td><td>8.53</td><td>34.68</td><td>9.94</td><td>100</td><td>310</td><td>Average</td></tr></table>						Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1 2488.71	47.33	54.00	-6.67	31.05	32.49	8.53	34.68	9.94	100	310	Average	Level (dBuV/m) Date: 2025-10-13 Site : 03CH07-HY Condition: AVG_54 3m HF_ANT_00075962 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><tr><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1 2462.00</td><td>101.83</td><td>-----</td><td>-----</td><td>85.79</td><td>32.32</td><td>8.48</td><td>34.68</td><td>9.92</td><td>100</td><td>310</td><td>Average</td></tr></table>						Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1 2462.00	101.83	-----	-----	85.79	32.32	8.48	34.68	9.92	100	310	Average
	Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																								
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																										
1 2488.71	47.33	54.00	-6.67	31.05	32.49	8.53	34.68	9.94	100	310	Average																																																																									
Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																									
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																										
1 2462.00	101.83	-----	-----	85.79	32.32	8.48	34.68	9.92	100	310	Average																																																																									



Mode	12																																																																																									
	Band Edge																																																																																									
	2400-2483.5_802.11b_CH11_2462MHz																																																																																									
ANT	1																																																																																									
Pol.	Vertical						Fundamental																																																																																			
Peak	Level (dBuV/m) Date: 2025-10-13  Site : 03CH07-HY Condition: PEAK_BE_74 3m HF_ANT_00075962 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>2485.79</td><td>59.25</td><td>74.00</td><td>-14.75</td><td>43.02</td><td>32.46</td><td>8.52</td><td>34.68</td><td>9.93</td><td>301</td><td>85</td><td>Peak</td></tr></table>							Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	2485.79	59.25	74.00	-14.75	43.02	32.46	8.52	34.68	9.93	301	85	Peak	Level (dBuV/m) Date: 2025-10-13  Site : 03CH07-HY Condition: PEAK_74 3m HF_ANT_00075962 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>2462.00</td><td>111.06</td><td>-----</td><td>-----</td><td>95.02</td><td>32.32</td><td>8.48</td><td>34.68</td><td>9.92</td><td>301</td><td>85</td><td>Peak</td></tr></table>							Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	2462.00	111.06	-----	-----	95.02	32.32	8.48	34.68	9.92	301	85	Peak
		Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																													
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																															
1	2485.79	59.25	74.00	-14.75	43.02	32.46	8.52	34.68	9.93	301	85	Peak																																																																														
	Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																														
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																															
1	2462.00	111.06	-----	-----	95.02	32.32	8.48	34.68	9.92	301	85	Peak																																																																														
Avg	Level (dBuV/m) Date: 2025-10-13  Site : 03CH07-HY Condition: AVG_BE_54 3m HF_ANT_00075962 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>2488.68</td><td>51.18</td><td>54.00</td><td>-2.82</td><td>34.90</td><td>32.49</td><td>8.53</td><td>34.68</td><td>9.94</td><td>301</td><td>85</td><td>Average</td></tr></table>							Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	2488.68	51.18	54.00	-2.82	34.90	32.49	8.53	34.68	9.94	301	85	Average	Level (dBuV/m) Date: 2025-10-13  Site : 03CH07-HY Condition: AVG_54 3m HF_ANT_00075962 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>2462.00</td><td>108.00</td><td>-----</td><td>-----</td><td>91.92</td><td>32.34</td><td>8.49</td><td>34.68</td><td>9.93</td><td>301</td><td>85</td><td>Average</td></tr></table>							Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	2462.00	108.00	-----	-----	91.92	32.34	8.49	34.68	9.93	301	85	Average
	Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																														
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																															
1	2488.68	51.18	54.00	-2.82	34.90	32.49	8.53	34.68	9.94	301	85	Average																																																																														
	Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																														
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																															
1	2462.00	108.00	-----	-----	91.92	32.34	8.49	34.68	9.93	301	85	Average																																																																														







Mode	12																																																																																																																																																																								
	Harmonic																																																																																																																																																																								
	2400-2483.5_802.11b_CH11_2462MHz																																																																																																																																																																								
ANT	1																																																																																																																																																																								
Pol.	Horizontal						Vertical																																																																																																																																																																		
Peak Avg	Level (dBuV/m) Date: 2025-10-14 Site : 03CH07-HY Condition: PEAK_74 3m HF_ANT_00075962 HORIZONTAL <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>4924.00</td><td>44.07</td><td>74.00</td><td>-29.93</td><td>54.94</td><td>34.25</td><td>12.09</td><td>58.16</td><td>0.95</td><td>400</td><td>85 Peak</td></tr><tr><td>2</td><td>4924.00</td><td>41.39</td><td>54.00</td><td>-12.61</td><td>52.26</td><td>34.25</td><td>12.09</td><td>58.16</td><td>0.95</td><td>400</td><td>85 Average</td></tr><tr><td>3</td><td>7386.00</td><td>43.00</td><td>74.00</td><td>-31.00</td><td>49.15</td><td>35.70</td><td>14.82</td><td>57.81</td><td>1.14</td><td>--</td><td>-- Peak</td></tr><tr><td>4</td><td>10005.00</td><td>50.71</td><td>-----</td><td>-----</td><td>53.88</td><td>37.00</td><td>17.90</td><td>59.23</td><td>1.16</td><td>--</td><td>-- Peak</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	4924.00	44.07	74.00	-29.93	54.94	34.25	12.09	58.16	0.95	400	85 Peak	2	4924.00	41.39	54.00	-12.61	52.26	34.25	12.09	58.16	0.95	400	85 Average	3	7386.00	43.00	74.00	-31.00	49.15	35.70	14.82	57.81	1.14	--	-- Peak	4	10005.00	50.71	-----	-----	53.88	37.00	17.90	59.23	1.16	--	-- Peak	Level (dBuV/m) Date: 2025-10-14 Site : 03CH07-HY Condition: PEAK_74 3m HF_ANT_00075962 VERTICAL <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>4924.00</td><td>47.83</td><td>74.00</td><td>-26.17</td><td>58.70</td><td>34.25</td><td>12.09</td><td>58.16</td><td>0.95</td><td>311</td><td>61 Peak</td></tr><tr><td>2</td><td>4924.00</td><td>46.83</td><td>54.00</td><td>-7.17</td><td>57.70</td><td>34.25</td><td>12.09</td><td>58.16</td><td>0.95</td><td>311</td><td>61 Average</td></tr><tr><td>3</td><td>7386.00</td><td>44.88</td><td>74.00</td><td>-29.12</td><td>51.03</td><td>35.70</td><td>14.82</td><td>57.81</td><td>1.14</td><td>--</td><td>-- Peak</td></tr><tr><td>4</td><td>9990.00</td><td>56.57</td><td>-----</td><td>-----</td><td>59.82</td><td>36.96</td><td>17.89</td><td>59.26</td><td>1.16</td><td>--</td><td>-- Peak</td></tr></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	4924.00	47.83	74.00	-26.17	58.70	34.25	12.09	58.16	0.95	311	61 Peak	2	4924.00	46.83	54.00	-7.17	57.70	34.25	12.09	58.16	0.95	311	61 Average	3	7386.00	44.88	74.00	-29.12	51.03	35.70	14.82	57.81	1.14	--	-- Peak	4	9990.00	56.57	-----	-----	59.82	36.96	17.89	59.26	1.16	--	-- Peak
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																																															
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																																																	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																																															
1	4924.00	44.07	74.00	-29.93	54.94	34.25	12.09	58.16	0.95	400	85 Peak																																																																																																																																																														
2	4924.00	41.39	54.00	-12.61	52.26	34.25	12.09	58.16	0.95	400	85 Average																																																																																																																																																														
3	7386.00	43.00	74.00	-31.00	49.15	35.70	14.82	57.81	1.14	--	-- Peak																																																																																																																																																														
4	10005.00	50.71	-----	-----	53.88	37.00	17.90	59.23	1.16	--	-- Peak																																																																																																																																																														
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																																																
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																																																	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																																															
1	4924.00	47.83	74.00	-26.17	58.70	34.25	12.09	58.16	0.95	311	61 Peak																																																																																																																																																														
2	4924.00	46.83	54.00	-7.17	57.70	34.25	12.09	58.16	0.95	311	61 Average																																																																																																																																																														
3	7386.00	44.88	74.00	-29.12	51.03	35.70	14.82	57.81	1.14	--	-- Peak																																																																																																																																																														
4	9990.00	56.57	-----	-----	59.82	36.96	17.89	59.26	1.16	--	-- Peak																																																																																																																																																														

Remark: The unwanted signal 10005.000MHz 、 9990.000MHz can be ignored since it falls within the non-restricted band and meet the requirements of 15.247 (d).







Mode	12	
	Harmonic	
	2400-2483.5_802.11b_CH11_2462MHz	
ANT	1	
Pol.	Horizontal	Vertical
14.47G ~14.5G Avg	Level (dBuV/m) Date: 2025-10-14 Site : 03CH07-HY Condition: AVG_54 3m HF_ANT_00075962 HORIZONTAL	Level (dBuV/m) Date: 2025-10-14 Site : 03CH07-HY Condition: AVG_54 3m HF_ANT_00075962 VERTICAL
	Level (dBuV/m) Date: 2025-10-14 Site : 03CH07-HY Condition: AVG_54 3m HF_ANT_00075962 HORIZONTAL	Level (dBuV/m) Date: 2025-10-14 Site : 03CH07-HY Condition: AVG_54 3m HF_ANT_00075962 VERTICAL



Mode	13																																																																																										
	Band Edge																																																																																										
	2400-2483.5_802.11g_CH01_2412MHz																																																																																										
ANT	1																																																																																										
Pol.	Horizontal												Fundamental																																																																														
Peak	Level (dBuV/m) Date: 2025-10-13  Site : 03CH07-HY Condition: PEAK_BE_74 3m HF_ANT_00075962 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><thead><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr></thead><tbody><tr><td>1</td><td>2388.65</td><td>61.32</td><td>74.00</td><td>-12.68</td><td>45.63</td><td>32.10</td><td>8.36</td><td>34.67</td><td>9.90</td><td>400</td><td>69</td><td>Peak</td></tr></tbody></table> Level (dBuV/m) Date: 2025-10-13  Site : 03CH07-HY Condition: PEAK_74 3m HF_ANT_00075962 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><thead><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr></thead><tbody><tr><td>1</td><td>2412.00</td><td>107.00</td><td>-----</td><td>-----</td><td>91.31</td><td>32.14</td><td>8.40</td><td>34.67</td><td>9.90</td><td>400</td><td>69</td><td>Peak</td></tr></tbody></table>														Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	2388.65	61.32	74.00	-12.68	45.63	32.10	8.36	34.67	9.90	400	69	Peak		Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	2412.00	107.00	-----	-----	91.31	32.14	8.40	34.67	9.90	400	69	Peak
		Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																														
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																
1	2388.65	61.32	74.00	-12.68	45.63	32.10	8.36	34.67	9.90	400	69	Peak																																																																															
	Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																															
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																
1	2412.00	107.00	-----	-----	91.31	32.14	8.40	34.67	9.90	400	69	Peak																																																																															
Avg	Level (dBuV/m) Date: 2025-10-13  Site : 03CH07-HY Condition: AVG_BE_54 3m HF_ANT_00075962 HORIZONTAL : RBW:1000.000kHz VBW:0.750kHz SMT:Auto <table><thead><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr></thead><tbody><tr><td>1</td><td>2389.69</td><td>48.97</td><td>54.00</td><td>-5.03</td><td>33.28</td><td>32.10</td><td>8.36</td><td>34.67</td><td>9.90</td><td>400</td><td>69</td><td>Average</td></tr></tbody></table> Level (dBuV/m) Date: 2025-10-13  Site : 03CH07-HY Condition: AVG_54 3m HF_ANT_00075962 HORIZONTAL : RBW:1000.000kHz VBW:0.750kHz SMT:Auto <table><thead><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr></thead><tbody><tr><td>1</td><td>2412.00</td><td>100.40</td><td>-----</td><td>-----</td><td>84.63</td><td>32.14</td><td>8.40</td><td>34.67</td><td>9.90</td><td>400</td><td>69</td><td>Average</td></tr></tbody></table>														Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	2389.69	48.97	54.00	-5.03	33.28	32.10	8.36	34.67	9.90	400	69	Average		Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	2412.00	100.40	-----	-----	84.63	32.14	8.40	34.67	9.90	400	69	Average
		Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																														
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																
1	2389.69	48.97	54.00	-5.03	33.28	32.10	8.36	34.67	9.90	400	69	Average																																																																															
	Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																															
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																
1	2412.00	100.40	-----	-----	84.63	32.14	8.40	34.67	9.90	400	69	Average																																																																															



		13																																																																																																					
Mode		Band Edge																																																																																																					
		2400-2483.5_802.11g_CH01_2412MHz																																																																																																					
ANT		1																																																																																																					
Pol.		Vertical						Fundamental																																																																																															
Peak		Level (dBuV/m) Date: 2025-10-13  Site : 03CH07-HY Condition: PEAK_BE_74 3m HF_ANT_00075962 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>2389.04</td><td>61.47</td><td>74.00</td><td>-12.53</td><td>45.78</td><td>32.10</td><td>8.36</td><td>34.67</td><td>9.90</td><td>235</td><td>98</td><td>Peak</td></tr></table>													Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	2389.04	61.47	74.00	-12.53	45.78	32.10	8.36	34.67	9.90	235	98	Peak	Level (dBuV/m) Date: 2025-10-13  Site : 03CH07-HY Condition: PEAK_74 3m HF_ANT_00075962 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>2412.00</td><td>111.24</td><td>-----</td><td>-----</td><td>95.51</td><td>32.10</td><td>8.40</td><td>34.67</td><td>9.90</td><td>235</td><td>98</td><td>Peak</td></tr></table>													Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	2412.00	111.24	-----	-----	95.51	32.10	8.40	34.67	9.90	235	98	Peak
		Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																																										
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																												
1	2389.04	61.47	74.00	-12.53	45.78	32.10	8.36	34.67	9.90	235	98	Peak																																																																																											
	Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																																											
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																												
1	2412.00	111.24	-----	-----	95.51	32.10	8.40	34.67	9.90	235	98	Peak																																																																																											
		Level (dBuV/m) Date: 2025-10-13  Site : 03CH07-HY Condition: AVG_BE_54 3m HF_ANT_00075962 VERTICAL : RBW:1000.000kHz VBW:0.750kHz SMT:Auto <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>2389.69</td><td>50.65</td><td>54.00</td><td>-3.35</td><td>34.96</td><td>32.10</td><td>8.36</td><td>34.67</td><td>9.90</td><td>235</td><td>98</td><td>Average</td></tr></table>													Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	2389.69	50.65	54.00	-3.35	34.96	32.10	8.36	34.67	9.90	235	98	Average	Level (dBuV/m) Date: 2025-10-13  Site : 03CH07-HY Condition: AVG_54 3m HF_ANT_00075962 VERTICAL : RBW:1000.000kHz VBW:0.750kHz SMT:Auto <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>2412.00</td><td>103.90</td><td>-----</td><td>-----</td><td>88.13</td><td>32.14</td><td>8.40</td><td>34.67</td><td>9.90</td><td>235</td><td>98</td><td>Average</td></tr></table>													Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	2412.00	103.90	-----	-----	88.13	32.14	8.40	34.67	9.90	235	98	Average
	Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																																											
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																												
1	2389.69	50.65	54.00	-3.35	34.96	32.10	8.36	34.67	9.90	235	98	Average																																																																																											
	Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																																											
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																												
1	2412.00	103.90	-----	-----	88.13	32.14	8.40	34.67	9.90	235	98	Average																																																																																											
Avg																																																																																																							



Mode	13																																																																																																																																													
	Harmonic																																																																																																																																													
	2400-2483.5_802.11g_CH01_2412MHz																																																																																																																																													
ANT	1																																																																																																																																													
Pol.	Horizontal	Vertical																																																																																																																																												
Peak Avg	Level (dBuV/m) Date: 2025-10-14 Site : 03CH07-HY Condition: PEAK_74 3m HF_ANT_00075962 HORIZONTAL <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>4824.00</td><td>43.84</td><td>74.00</td><td>-30.16</td><td>54.97</td><td>34.25</td><td>11.95</td><td>58.37</td><td>1.04</td><td>100</td><td>193</td><td>Peak</td></tr><tr><td>2</td><td>4824.00</td><td>34.33</td><td>54.00</td><td>-19.67</td><td>45.46</td><td>34.25</td><td>11.95</td><td>58.37</td><td>1.04</td><td>100</td><td>193</td><td>Average</td></tr><tr><td>3</td><td>9990.00</td><td>50.94</td><td>-----</td><td>-----</td><td>54.19</td><td>36.96</td><td>17.89</td><td>59.26</td><td>1.16</td><td>--</td><td>--</td><td>Peak</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	4824.00	43.84	74.00	-30.16	54.97	34.25	11.95	58.37	1.04	100	193	Peak	2	4824.00	34.33	54.00	-19.67	45.46	34.25	11.95	58.37	1.04	100	193	Average	3	9990.00	50.94	-----	-----	54.19	36.96	17.89	59.26	1.16	--	--	Peak	Level (dBuV/m) Date: 2025-10-14 Site : 03CH07-HY Condition: PEAK_74 3m HF_ANT_00075962 VERTICAL <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>4824.00</td><td>48.11</td><td>74.00</td><td>-25.89</td><td>59.24</td><td>34.25</td><td>11.95</td><td>58.37</td><td>1.04</td><td>300</td><td>69</td><td>Peak</td></tr><tr><td>2</td><td>4824.00</td><td>40.38</td><td>54.00</td><td>-13.62</td><td>51.51</td><td>34.25</td><td>11.95</td><td>58.37</td><td>1.04</td><td>300</td><td>69</td><td>Average</td></tr><tr><td>3</td><td>9975.00</td><td>57.31</td><td>-----</td><td>-----</td><td>60.65</td><td>36.90</td><td>17.88</td><td>59.28</td><td>1.16</td><td>--</td><td>--</td><td>Peak</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	4824.00	48.11	74.00	-25.89	59.24	34.25	11.95	58.37	1.04	300	69	Peak	2	4824.00	40.38	54.00	-13.62	51.51	34.25	11.95	58.37	1.04	300	69	Average	3	9975.00	57.31	-----	-----	60.65	36.90	17.88	59.28	1.16	--	--	Peak
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																				
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																						
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																				
1	4824.00	43.84	74.00	-30.16	54.97	34.25	11.95	58.37	1.04	100	193	Peak																																																																																																																																		
2	4824.00	34.33	54.00	-19.67	45.46	34.25	11.95	58.37	1.04	100	193	Average																																																																																																																																		
3	9990.00	50.94	-----	-----	54.19	36.96	17.89	59.26	1.16	--	--	Peak																																																																																																																																		
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																					
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																						
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																				
1	4824.00	48.11	74.00	-25.89	59.24	34.25	11.95	58.37	1.04	300	69	Peak																																																																																																																																		
2	4824.00	40.38	54.00	-13.62	51.51	34.25	11.95	58.37	1.04	300	69	Average																																																																																																																																		
3	9975.00	57.31	-----	-----	60.65	36.90	17.88	59.28	1.16	--	--	Peak																																																																																																																																		

Remark: The unwanted signal 9990.000MHz、9975.000MHz can be ignored since it falls within the non-restricted band and meet the requirements of 15.247 (d).



Mode	13	
	Harmonic	
	2400-2483.5_802.11g_CH01_2412MHz	
ANT	1	
Pol.	Horizontal	Vertical
14.47G ~14.5G Avg	Level (dBuV/m) Date: 2025-10-14 Site : 03CH07-HY Condition: AVG_54 3m HF_ANT_00075962 HORIZONTAL	Level (dBuV/m) Date: 2025-10-14 Site : 03CH07-HY Condition: AVG_54 3m HF_ANT_00075962 VERTICAL
	Level (dBuV/m) Date: 2025-10-14 Site : 03CH07-HY Condition: AVG_54 3m HF_ANT_00075962 HORIZONTAL	Level (dBuV/m) Date: 2025-10-14 Site : 03CH07-HY Condition: AVG_54 3m HF_ANT_00075962 VERTICAL



	14																																																																																																	
Mode	Band Edge - L																																																																																																	
	2400-2483.5_802.11g_CH06_2437MHz																																																																																																	
ANT	1																																																																																																	
Pol.	Horizontal						Fundamental																																																																																											
Peak	Level (dBuV/m) Date: 2025-10-13 Site : 03CH07-HY Condition: PEAK_BE_74 3m HF_ANT_00075962 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2387.98</td><td>55.46</td><td>74.00</td><td>-18.54</td><td>39.77</td><td>32.10</td><td>8.36</td><td>34.67</td><td>9.90</td><td>100</td><td>34 Peak</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2387.98	55.46	74.00	-18.54	39.77	32.10	8.36	34.67	9.90	100	34 Peak	Level (dBuV/m) Date: 2025-10-13 Site : 03CH07-HY Condition: PEAK_74 3m HF_ANT_00075962 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2437.00</td><td>110.06</td><td>-----</td><td>-----</td><td>94.18</td><td>32.20</td><td>8.44</td><td>34.67</td><td>9.91</td><td>100</td><td>34 Peak</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2437.00	110.06	-----	-----	94.18	32.20	8.44	34.67	9.91	100	34 Peak
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																								
Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor																																																																																											
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																								
1	2387.98	55.46	74.00	-18.54	39.77	32.10	8.36	34.67	9.90	100	34 Peak																																																																																							
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																									
Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor																																																																																											
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																								
1	2437.00	110.06	-----	-----	94.18	32.20	8.44	34.67	9.91	100	34 Peak																																																																																							
Avg	Level (dBuV/m) Date: 2025-10-13 Site : 03CH07-HY Condition: AVG_BE_54 3m HF_ANT_00075962 HORIZONTAL : RBW:1000.000kHz VBW:0.750kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2382.64</td><td>45.32</td><td>54.00</td><td>-8.68</td><td>29.64</td><td>32.10</td><td>8.35</td><td>34.67</td><td>9.90</td><td>100</td><td>34 Average</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2382.64	45.32	54.00	-8.68	29.64	32.10	8.35	34.67	9.90	100	34 Average	Level (dBuV/m) Date: 2025-10-13 Site : 03CH07-HY Condition: AVG_54 3m HF_ANT_00075962 HORIZONTAL : RBW:1000.000kHz VBW:0.750kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2437.00</td><td>102.23</td><td>-----</td><td>-----</td><td>86.35</td><td>32.20</td><td>8.44</td><td>34.67</td><td>9.91</td><td>100</td><td>34 Average</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2437.00	102.23	-----	-----	86.35	32.20	8.44	34.67	9.91	100	34 Average
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																								
Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor																																																																																											
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																								
1	2382.64	45.32	54.00	-8.68	29.64	32.10	8.35	34.67	9.90	100	34 Average																																																																																							
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																									
Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor																																																																																											
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																								
1	2437.00	102.23	-----	-----	86.35	32.20	8.44	34.67	9.91	100	34 Average																																																																																							



Mode	14										
	Band Edge - R										
	2400-2483.5_802.11g_CH06_2437MHz										
ANT	1										
Pol.	Horizontal						Fundamental				
Peak											



	14																																																																																														
Mode	Band Edge - L																																																																																														
	2400-2483.5_802.11g_CH06_2437MHz																																																																																														
ANT	1																																																																																														
Pol.	Vertical						Fundamental																																																																																								
Peak	Level (dBuV/m) Date: 2025-10-13 Site : 03CH07-HY Condition: PEAK_BE_74 3m HF_ANT_00075962 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2389.38</td><td>57.80</td><td>74.00</td><td>-16.20</td><td>42.11</td><td>32.10</td><td>8.36</td><td>34.67</td><td>9.90</td><td>269</td><td>92 Peak</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2389.38	57.80	74.00	-16.20	42.11	32.10	8.36	34.67	9.90	269	92 Peak	Level (dBuV/m) Date: 2025-10-13 Site : 03CH07-HY Condition: PEAK_74 3m HF_ANT_00075962 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2437.00</td><td>113.80</td><td>-----</td><td>-----</td><td>97.92</td><td>32.20</td><td>8.44</td><td>34.67</td><td>9.91</td><td>269</td><td>92 Peak</td></tr></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2437.00	113.80	-----	-----	97.92	32.20	8.44	34.67	9.91	269	92 Peak
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																					
Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor																																																																																								
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																						
1	2389.38	57.80	74.00	-16.20	42.11	32.10	8.36	34.67	9.90	269	92 Peak																																																																																				
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																						
Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor																																																																																								
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																						
1	2437.00	113.80	-----	-----	97.92	32.20	8.44	34.67	9.91	269	92 Peak																																																																																				
Avg	Level (dBuV/m) Date: 2025-10-13 Site : 03CH07-HY Condition: AVG_BE_54 3m HF_ANT_00075962 VERTICAL : RBW:1000.000kHz VBW:0.750kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2389.38</td><td>46.78</td><td>54.00</td><td>-7.22</td><td>31.09</td><td>32.10</td><td>8.36</td><td>34.67</td><td>9.90</td><td>269</td><td>92 Average</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2389.38	46.78	54.00	-7.22	31.09	32.10	8.36	34.67	9.90	269	92 Average	Level (dBuV/m) Date: 2025-10-13 Site : 03CH07-HY Condition: AVG_54 3m HF_ANT_00075962 VERTICAL : RBW:1000.000kHz VBW:0.750kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2437.00</td><td>106.79</td><td>-----</td><td>-----</td><td>90.91</td><td>32.20</td><td>8.44</td><td>34.67</td><td>9.91</td><td>269</td><td>92 Average</td></tr></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2437.00	106.79	-----	-----	90.91	32.20	8.44	34.67	9.91	269	92 Average
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																					
Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor																																																																																								
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																						
1	2389.38	46.78	54.00	-7.22	31.09	32.10	8.36	34.67	9.90	269	92 Average																																																																																				
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																						
Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor																																																																																								
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																						
1	2437.00	106.79	-----	-----	90.91	32.20	8.44	34.67	9.91	269	92 Average																																																																																				



Mode	14										
	Band Edge - R										
	2400-2483.5_802.11g_CH06_2437MHz										
ANT	1										
Pol.	Vertical						Fundamental				
Peak	<										



Mode	14																																																																																																																																																																									
	Harmonic																																																																																																																																																																									
	2400-2483.5_802.11g_CH06_2437MHz																																																																																																																																																																									
ANT	1																																																																																																																																																																									
Pol.	Horizontal						Vertical																																																																																																																																																																			
Peak Avg	Level (dBuV/m) Date: 2025-10-14 Site : 03CH07-HY Condition: PEAK_74 3m HF_ANT_00075962 HORIZONTAL <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>4874.00</td><td>42.47</td><td>74.00</td><td>-31.53</td><td>53.51</td><td>34.20</td><td>12.02</td><td>58.26</td><td>1.00</td><td>--</td><td>Peak</td></tr><tr><td>2</td><td>7311.00</td><td>43.38</td><td>74.00</td><td>-30.62</td><td>49.52</td><td>35.70</td><td>14.68</td><td>57.68</td><td>1.16</td><td>--</td><td>Peak</td></tr><tr><td>3</td><td>9975.00</td><td>51.05</td><td>-----</td><td>-----</td><td>54.39</td><td>36.90</td><td>17.88</td><td>59.28</td><td>1.16</td><td>--</td><td>Peak</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line Margin	Level	Factor	Loss Factor	Factor			Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	1	4874.00	42.47	74.00	-31.53	53.51	34.20	12.02	58.26	1.00	--	Peak	2	7311.00	43.38	74.00	-30.62	49.52	35.70	14.68	57.68	1.16	--	Peak	3	9975.00	51.05	-----	-----	54.39	36.90	17.88	59.28	1.16	--	Peak	Level (dBuV/m) Date: 2025-10-14 Site : 03CH07-HY Condition: PEAK_74 3m HF_ANT_00075962 VERTICAL <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>4874.00</td><td>46.55</td><td>74.00</td><td>-27.45</td><td>57.59</td><td>34.20</td><td>12.02</td><td>58.26</td><td>1.00</td><td>300</td><td>73 Peak</td></tr><tr><td>2</td><td>4874.00</td><td>40.79</td><td>54.00</td><td>-13.21</td><td>51.83</td><td>34.20</td><td>12.02</td><td>58.26</td><td>1.00</td><td>300</td><td>73 Average</td></tr><tr><td>3</td><td>7311.00</td><td>48.96</td><td>74.00</td><td>-25.04</td><td>55.10</td><td>35.70</td><td>14.68</td><td>57.68</td><td>1.16</td><td>317</td><td>54 Peak</td></tr><tr><td>4</td><td>7311.00</td><td>41.16</td><td>54.00</td><td>-12.84</td><td>47.30</td><td>35.70</td><td>14.68</td><td>57.68</td><td>1.16</td><td>317</td><td>54 Average</td></tr><tr><td>5</td><td>9960.00</td><td>55.97</td><td>-----</td><td>-----</td><td>59.40</td><td>36.84</td><td>17.86</td><td>59.30</td><td>1.17</td><td>--</td><td>Peak</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line Margin	Level	Factor	Loss Factor	Factor			Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	1	4874.00	46.55	74.00	-27.45	57.59	34.20	12.02	58.26	1.00	300	73 Peak	2	4874.00	40.79	54.00	-13.21	51.83	34.20	12.02	58.26	1.00	300	73 Average	3	7311.00	48.96	74.00	-25.04	55.10	35.70	14.68	57.68	1.16	317	54 Peak	4	7311.00	41.16	54.00	-12.84	47.30	35.70	14.68	57.68	1.16	317	54 Average	5	9960.00	55.97	-----	-----	59.40	36.84	17.86	59.30	1.17	--	Peak
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																																																																	
Freq	Level	Line Margin	Level	Factor	Loss Factor	Factor			Remark																																																																																																																																																																	
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																																																																
1	4874.00	42.47	74.00	-31.53	53.51	34.20	12.02	58.26	1.00	--	Peak																																																																																																																																																															
2	7311.00	43.38	74.00	-30.62	49.52	35.70	14.68	57.68	1.16	--	Peak																																																																																																																																																															
3	9975.00	51.05	-----	-----	54.39	36.90	17.88	59.28	1.16	--	Peak																																																																																																																																																															
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																																																																		
Freq	Level	Line Margin	Level	Factor	Loss Factor	Factor			Remark																																																																																																																																																																	
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																																																																
1	4874.00	46.55	74.00	-27.45	57.59	34.20	12.02	58.26	1.00	300	73 Peak																																																																																																																																																															
2	4874.00	40.79	54.00	-13.21	51.83	34.20	12.02	58.26	1.00	300	73 Average																																																																																																																																																															
3	7311.00	48.96	74.00	-25.04	55.10	35.70	14.68	57.68	1.16	317	54 Peak																																																																																																																																																															
4	7311.00	41.16	54.00	-12.84	47.30	35.70	14.68	57.68	1.16	317	54 Average																																																																																																																																																															
5	9960.00	55.97	-----	-----	59.40	36.84	17.86	59.30	1.17	--	Peak																																																																																																																																																															

Remark: The unwanted signal 9975.000MHz、9960.000MHz can be ignored since it falls within the non-restricted band and meet the requirements of 15.247 (d).



Mode	14	
	Harmonic	
	2400-2483.5_802.11g_CH06_2437MHz	
ANT	1	
Pol.	Horizontal	Vertical
14.47G ~14.5G Avg	Level (dBuV/m) Date: 2025-10-14 Site : 03CH07-HY Condition: AVG_54 3m HF_ANT_00075962 HORIZONTAL	Level (dBuV/m) Date: 2025-10-14 Site : 03CH07-HY Condition: AVG_54 3m HF_ANT_00075962 VERTICAL
	Level (dBuV/m) Date: 2025-10-14 Site : 03CH07-HY Condition: AVG_54 3m HF_ANT_00075962 HORIZONTAL	Level (dBuV/m) Date: 2025-10-14 Site : 03CH07-HY Condition: AVG_54 3m HF_ANT_00075962 VERTICAL



Mode	15																																																																																			
	Band Edge																																																																																			
	2400-2483.5_802.11g_CH11_2462MHz																																																																																			
ANT	1																																																																																			
Pol.	Horizontal						Fundamental																																																																													
Peak	Level (dBuV/m) Date: 2025-10-13 Site : 03CH07-HY Condition: PEAK_BE_74 3m HF_ANT_00075962 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1 2487.23</td><td>58.90</td><td>74.00</td><td>-15.10</td><td>42.66</td><td>32.47</td><td>8.52</td><td>34.68</td><td>9.93</td><td>100</td><td>317</td><td>Peak</td></tr></table>						Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1 2487.23	58.90	74.00	-15.10	42.66	32.47	8.52	34.68	9.93	100	317	Peak	Level (dBuV/m) Date: 2025-10-13 Site : 03CH07-HY Condition: PEAK_74 3m HF_ANT_00075962 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1 2462.00</td><td>105.51</td><td>-----</td><td>-----</td><td>89.49</td><td>32.30</td><td>8.48</td><td>34.68</td><td>9.92</td><td>100</td><td>317</td><td>Peak</td></tr></table>						Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1 2462.00	105.51	-----	-----	89.49	32.30	8.48	34.68	9.92	100	317	Peak
	Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																								
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																										
1 2487.23	58.90	74.00	-15.10	42.66	32.47	8.52	34.68	9.93	100	317	Peak																																																																									
Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																									
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																										
1 2462.00	105.51	-----	-----	89.49	32.30	8.48	34.68	9.92	100	317	Peak																																																																									
Avg	Level (dBuV/m) Date: 2025-10-13 Site : 03CH07-HY Condition: AVG_BE_54 3m HF_ANT_00075962 HORIZONTAL : RBW:1000.000kHz VBW:0.750kHz SMT:Auto <table><tr><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1 2483.51</td><td>48.92</td><td>54.00</td><td>-5.08</td><td>32.71</td><td>32.44</td><td>8.52</td><td>34.68</td><td>9.93</td><td>100</td><td>317</td><td>Average</td></tr></table>						Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1 2483.51	48.92	54.00	-5.08	32.71	32.44	8.52	34.68	9.93	100	317	Average	Level (dBuV/m) Date: 2025-10-13 Site : 03CH07-HY Condition: AVG_54 3m HF_ANT_00075962 HORIZONTAL : RBW:1000.000kHz VBW:0.750kHz SMT:Auto <table><tr><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1 2462.00</td><td>97.93</td><td>-----</td><td>-----</td><td>81.89</td><td>32.32</td><td>8.48</td><td>34.68</td><td>9.92</td><td>100</td><td>317</td><td>Average</td></tr></table>						Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1 2462.00	97.93	-----	-----	81.89	32.32	8.48	34.68	9.92	100	317	Average
	Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																								
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																										
1 2483.51	48.92	54.00	-5.08	32.71	32.44	8.52	34.68	9.93	100	317	Average																																																																									
Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																									
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																										
1 2462.00	97.93	-----	-----	81.89	32.32	8.48	34.68	9.92	100	317	Average																																																																									